FCC RF Test Report

APPLICANT : mixi, Inc.

EQUIPMENT: Mobile Phone

BRAND NAME : RATEL MODEL NAME : CELL MODEL NUMBER : R1020

FCC ID : 2AN7THST-101-1

STANDARD : FCC Part 15 Subpart C §15.225

CLASSIFICATION: (DXX) Low Power Communication Device Transmitter

The product was received on Dec. 08, 2017 and testing was completed on Feb. 13, 2018. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager

SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AN7THST-101-1 Page Number : 1 of 20
Report Issued Date : Mar. 20, 2018
Report Version : Rev. 01

1190

Report No.: FR7D0829D

TABLE OF CONTENTS

REVISION	ON HISTORY	3
SUMMA	ARY OF THE TEST RESULT	2
	ERAL DESCRIPTION	
1.1	Applicant	
1.2	Manufacturer	
1.3	Product Feature of Equipment Under Test	
1.4	Modification of EUT	
1.5	Testing Location	6
1.6	Applicable Standards	
2. TES1	CONFIGURATION OF EQUIPMENT UNDER TEST	7
2.1	Descriptions of Test Mode	
2.2	Connection Diagram of Test System	7
2.3	Table for Supporting Units	8
2.4	EUT Operation Test Setup	8
3. TES1	「RESULTS	9
3.1	AC Power Line Conducted Emissions Measurement	9
3.2	20dB and 99% OBW Spectrum Bandwidth Measurement	1
3.3	Frequency Stability Measurement	12
3.4	Field Strength of Fundamental Emissions and Mask Measurement	
3.5	Radiated Emissions Measurement	15
3.6	Antenna Requirements	18
4. LIST	OF MEASURING EQUIPMENT	19
5. UNC	ERTAINTY OF EVALUATION	20
	DIX A. TEST RESULTS OF CONDUCTED EMISSION TEST	
APPEN	DIX B. TEST RESULTS OF CONDUCTED TEST ITEMS	
B1. T	est Result of 20dB Spectrum Bandwidth	
	est Result of Frequency Stability	
	DIX C. TEST RESULTS OF RADIATED TEST ITEMS	
C1. T	est Result of Field Strength of Fundamental Emissions	
C2. F	Results of Radiated Emissions (9 kHz~30MHz)	

C3. Results of Radiated Emissions (30MHz~1GHz)

APPEDNIX D. SETUP PHOTOGRAPHS

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AN7THST-101-1 Page Number : 2 of 20
Report Issued Date : Mar. 20, 2018
Report Version : Rev. 01

Report No.: FR7D0829D

REVISION HISTORY

Report No.: FR7D0829D

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR7D0829D	Rev. 01	Initial issue of report	Mar. 20, 2018

 SPORTON INTERNATIONAL INC.
 Page Number
 : 3 of 20

 TEL: 886-3-327-3456
 Report Issued Date
 : Mar. 20, 2018

 FAX: 886-3-328-4978
 Report Version
 : Rev. 01

SUMMARY OF THE TEST RESULT

Report No. : FR7D0829D

	Applied Standard: 47 CFR FCC Part 15 Subpart C §15.225					
Part	FCC Rule	Description of Test Result		Remark		
3.1	15.207	AC Power Line Conducted Emissions Complies 23		Under limit 22.72 dB at 0.66975MHz		
3.2	15.215(c)	20dB Spectrum Bandwidth	Complies	-		
3.2	-	99% OBW Spectrum Bandwidth	Complies	-		
3.3	15.225(e)	Frequency Stability Complies -		-		
3.4	15.225(a)(b)(c)	Field Strength of Fundamental Emissions Complies 53.27		Max level 53.27 dBµV/m at 13.560 MHz		
3.5	15.225(d) & 15.209	Radiated Spurious Emissions Complies		Under limit 6.40 dB at 339.900MHz		
3.6	15.203	Antenna Requirements Complies -		-		

 SPORTON INTERNATIONAL INC.
 Page Number
 : 4 of 20

 TEL: 886-3-327-3456
 Report Issued Date
 : Mar. 20, 2018

 FAX: 886-3-328-4978
 Report Version
 : Rev. 01

1. General Description

1.1 Applicant

mixi, Inc.

Sumitomo Fudosan Shibuya First Tower 7F, 1-2-20 Higashi, Shibuya-ku, Tokyo, 150-0011, Japan

Report No.: FR7D0829D

1.2 Manufacturer

Wistron Corporation

21F, No. 88, Sec. 1, Hsin Tai Wu Rd., Hsichih Dist, New Taipei City 221, Taiwan R.O.C.

1.3 Product Feature of Equipment Under Test

GSM/WCDMA/LTE, Bluetooth, Wi-Fi 2.4GHz 802.11b/g/n, Wi-Fi 5GHz 802.11a/n/ac, NFC, and GNSS.

Product Specification subjective to this standard			
	WWAN: PIFA Antenna		
	WLAN: PIFA Antenna		
Antenna Type	Bluetooth: PIFA Antenna		
	GPS / Glonass: PIFA Antenna		
	NFC: Coil Antenna		

1.4 Modification of EUT

No modifications are made to the EUT during all test items.

 SPORTON INTERNATIONAL INC.
 Page Number
 : 5 of 20

 TEL: 886-3-327-3456
 Report Issued Date
 : Mar. 20, 2018

 FAX: 886-3-328-4978
 Report Version
 : Rev. 01

1.5 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 1190) and the FCC designation No. TW1190 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Report No.: FR7D0829D

Test Site	SPORTON INTERNATIONAL INC.					
	No. 52, Hwa Ya 1 st Rd., H	lwa Ya Technology Park,				
Test Site Location	Kwei-Shan District, Tao Y	Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.				
	TEL: +886-3-3273456 / F	AX: +886-3-3284978				
Test Site No.	Sporton Site No.					
rest site No.	TH03-HY	CO05-HY	03CH07-HY			
Test Engineer	JH Liao Shareef Yu Jesse Wan					
Temperature	ature 22~24 24~25 13		13~14			
Relative Humidity	53~55 53~56 53~56					

Note: The test site complies with ANSI C63.4 2014 requirement.

1.6 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.225
- ANSI C63.10-2013

 SPORTON INTERNATIONAL INC.
 Page Number
 : 6 of 20

 TEL: 886-3-327-3456
 Report Issued Date
 : Mar. 20, 2018

 FAX: 886-3-328-4978
 Report Version
 : Rev. 01

2. Test Configuration of Equipment Under Test

2.1 Descriptions of Test Mode

Investigation has been done on all the possible configurations.


The following table is a list of the test modes shown in this test report.

Test Items		
AC Power Line Conducted Emissions	Field Strength of Fundamental Emissions	
20dB Spectrum Bandwidth	Frequency Stability	
Radiated Emissions 9kHz~30MHz	Radiated Emissions 30MHz~1GHz	

The EUT pre-scanned in four NFC type, A, B, F, V. The worst type (type F) was recorded in this report. Pre-scanned tests, X, Y, Z in three orthogonal panels to determine the final configuration (Z plane as worst plane) from all possible combinations.

	Test Cases			
AC	Mode 1: LTE Band 7 Idle + WLAN Link + USB cable Type C to Type C (EUT			
Conducted	Charging from Adapter) + Bluetooth Link + NFC Tx			
Emission				

2.2 Connection Diagram of Test System



SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AN7THST-101-1 Page Number : 7 of 20
Report Issued Date : Mar. 20, 2018
Report Version : Rev. 01

Report No.: FR7D0829D

2.3 Table for Supporting Units

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded,1.8m
3.	Notebook	DELL	Latitude E6320	FCC DoC/ Contains FCC ID: QDS-BRCM1054	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
4.	SD Card	SanDisk	MicroSD HC	FCC DoC	N/A	N/A

Report No.: FR7D0829D

2.4 EUT Operation Test Setup

The EUT was programmed to be in continuously transmitting mode.

The ancillary equipment, NFC card, is used to make the EUT (NFC) continuously transmit at 13.56MHz and is placed around 0.5cm gap to the EUT.

3. Test Results

3.1 AC Power Line Conducted Emissions Measurement

3.1.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission	Conducted I	Limit (dΒμV)
(MHz)	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

^{*}Decreases with the logarithm of the frequency.

3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

3.1.3 Test Procedures


- 1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
- 2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
- 3. All the support units are connecting to the other LISN.
- 4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
- 5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
- 6. Both sides of AC line were checked for maximum conducted interference.
- 7. The frequency range from 150 kHz to 30 MHz was searched.
- 8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

FAX: 886-3-328-4978 FCC ID: 2AN7THST-101-1 Page Number : 9 of 20
Report Issued Date : Mar. 20, 2018
Report Version : Rev. 01

Report No.: FR7D0829D



3.1.4 Test setup



3.1.5 Test Result of AC Conducted Emission

Please refer to Appendix A.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AN7THST-101-1 Page Number : 10 of 20
Report Issued Date : Mar. 20, 2018
Report Version : Rev. 01

Report No.: FR7D0829D

3.2 20dB and 99% OBW Spectrum Bandwidth Measurement

3.2.1 Limit

Intentional radiators must be designed to ensure that the 20dB and 99% emission bandwidth in the specific band 13.553~13.567MHz.


3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

3.2.3 Test Procedures

- The spectrum analyzer connected via a receive antenna placed near the EUT in peak Max hold mode.
- 2. The resolution bandwidth of 1 kHz and the video bandwidth of 3 kHz were used.
- 3. Measured the spectrum width with power higher than 20dB below carrier.
- 4. Measured the 99% OBW.

3.2.4 Test Setup



3.2.5 Test Result of Conducted Test Items

Please refer to Appendix B.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AN7THST-101-1 Page Number : 11 of 20
Report Issued Date : Mar. 20, 2018
Report Version : Rev. 01

Report No.: FR7D0829D

3.3 Frequency Stability Measurement

3.3.1 Limit

The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% (100ppm) of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.


3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

3.3.3 Test Procedures

- 1. The spectrum analyzer connected via a receive antenna placed near the EUT.
- 2. EUT have transmitted signal and fixed channelize.
- 3. Set the spectrum analyzer span to view the entire emissions bandwidth.
- 4. Set RBW = 1 kHz, VBW = 3 kHz with peak detector and maxhold settings.
- 5. The fc is declaring of channel frequency. Then the frequency error formula is $(fc-f)/fc \times 10^6$ ppm and the limit is less than ± 100 ppm.
- 6. Extreme temperature rule is -20°C~50°C.

3.3.4 Test Setup



3.3.5 Test Result of Conducted Test Items

Please refer to Appendix B.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AN7THST-101-1 Page Number : 12 of 20
Report Issued Date : Mar. 20, 2018
Report Version : Rev. 01

Report No.: FR7D0829D

3.4 Field Strength of Fundamental Emissions and Mask Measurement

3.4.1 Limit

Rules and specifications	FCC CFR 47 Part 15 section 15.225			
Description	Compliance with the	ne spectrum mask is	tested with RBW se	et to 9kHz.
From of Francisco (MIII-)	Field Strength	Field Strength	Field Strength	Field Strength
Freq. of Emission (MHz)	(µV/m) at 30m	(dBµV/m) at 30m	(dBµV/m) at 10m	(dBµV/m) at 3m
1.705~13.110	30	29.5	48.58	69.5
13.110~13.410	106	40.5	59.58	80.5
13.410~13.553	334	50.5	69.58	90.5
13.553~13.567	15848	84.0	103.08	124.0
13.567~13.710	334	50.5	69.58	90.5
13.710~14.010	106	40.5	59.58	80.5
14.010~30.000	30	29.5	48.58	69.5

3.4.2 Measuring Instruments

See list of measuring instruments of this test report.

SPORTON INTERNATIONAL INC.

FAX: 886-3-328-4978 FCC ID: 2AN7THST-101-1

TEL: 886-3-327-3456


Page Number : 13 of 20
Report Issued Date : Mar. 20, 2018
Report Version : Rev. 01

Report No.: FR7D0829D

3.4.3 Test Procedures

- Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the loop receiving antenna mounted antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the receiving antenna was fixed at one meter above ground to find the maximum emissions field strength.
- 4. For Fundamental emissions, use the receiver to measure QP reading.
- 5. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
- Compliance with the spectrum mask is tested with RBW set to 9kHz.
 Note: Emission level (dBμV/m) = 20 log Emission level (μV/m).

3.4.4 Test Setup



3.4.5 Test Result of Field Strength of Fundamental Emissions and Mask

Please refer to Appendix C.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AN7THST-101-1 Page Number : 14 of 20
Report Issued Date : Mar. 20, 2018
Report Version : Rev. 01

Report No.: FR7D0829D

3.5 Radiated Emissions Measurement

3.5.1 Limit

The field strength of any emissions which appear outside of 13.110 ~14.010MHz band shall not exceed the general radiated emissions limits.

Frequencies	Field Strength	Measurement Distance
(MHz)	(μV/m)	(meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

3.5.3 Measuring Instrument Setting

The following table is the setting of receiver.

Receiver Parameter	Setting
Attenuation	Auto
Frequency Range: 9kHz~150kHz	RBW 200Hz for QP
Frequency Range: 150kHz~30MHz	RBW 9kHz for QP
Frequency Range: 30MHz~1000MHz	RBW 120kHz for Peak

Note: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.

FCC ID: 2AN7THST-101-1

Report Template No.: BU5-FR15CNFC Version 2.0

Report No.: FR7D0829D

3.5.4 Test Procedures


- Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable
 8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
- In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. Antenna Requirements

FAX: 886-3-328-4978 FCC ID: 2AN7THST-101-1 Page Number : 16 of 20
Report Issued Date : Mar. 20, 2018
Report Version : Rev. 01


Report No.: FR7D0829D

3.5.5 Test Setup

For radiated emissions below 30MHz



For radiated emissions above 30MHz



3.5.6 Test Result of Radiated Emissions Measurement

Please refer to Appendix C.

Remark: There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AN7THST-101-1 Page Number : 17 of 20
Report Issued Date : Mar. 20, 2018
Report Version : Rev. 01

Report No.: FR7D0829D

3.6 Antenna Requirements

3.6.1 Standard Applicable

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited.

The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.6.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

Page Number : 18 of 20
Report Issued Date : Mar. 20, 2018
Report Version : Rev. 01

Report No.: FR7D0829D

4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	AC POWER	AFC-500W	F1040700 11	50Hz~60Hz	Dec. 01, 2016	Jan. 03, 2018 ~ Jan. 05, 2018	Nov. 30, 2018	Conducted (TH03-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP30	101329	9kHz~30GHz	Jun. 26, 2017	Jan. 03, 2018 ~ Jan. 05, 2018	Jun. 25, 2018	Conducted (TH03-HY)
Temperature Chamber	ESPEC	SU-641	92013721	-30℃ ~70℃	Nov. 16, 2016	Jan. 03, 2018 ~ Jan. 05, 2018	Nov. 15, 2018	Conducted (TH03-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Feb. 13, 2018	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	3.6GHz	Dec. 08, 2017	Feb. 13, 2018	Dec. 07, 2018	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 30, 2017	Feb. 13, 2018	Nov. 29, 2018	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Dec. 08, 2017	Feb. 13, 2018	Dec. 07, 2018	Conduction (CO05-HY)
Bilog Antenna	TESEQ	CBL 6111D&00800 N1D01N-06	35419&03	30MHz to 1GHz	Dec. 18, 2017	Feb. 06, 2018 ~ Feb. 07, 2018	Dec. 17, 2018	Radiation (03CH07-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Nov. 10, 2017	Feb. 06, 2018 ~ Feb. 07, 2018	Nov. 09, 2019	Radiation (03CH07-HY)
Preamplifier	COM-POWER	PA-103A	161241	10MHz-1GHz	Mar. 14, 2017	Feb. 06, 2018 ~ Feb. 07, 2018	Mar. 13, 2018	Radiation (03CH07-HY)
Spectrum Analyzer	Agilent	N9010A	MY534701 18	10Hz~44GHz	Apr. 17, 2017	Feb. 06, 2018 ~ Feb. 07, 2018	Apr. 16, 2018	Radiation (03CH07-HY)
Antenna Mast	Max-Full	MFA520BS	N/A	1m~4m	N/A	Feb. 06, 2018 ~ Feb. 07, 2018	N/A	Radiation (03CH07-HY)
Turn Table	ChainTek	Chaintek 3000	N/A	0~360 Degree	N/A	Feb. 06, 2018 ~ Feb. 07, 2018	N/A	Radiation (03CH07-HY)
EMI Test Receiver	Agilent	N9038A (MXE)	MY532900 53	20Hz to 26.5GHz	Jan. 16, 2018	Feb. 06, 2018 ~ Feb. 07, 2018	Jan. 15, 2019	Radiation (03CH07-HY)

Report No.: FR7D0829D

 SPORTON INTERNATIONAL INC.
 Page Number
 : 19 of 20

 TEL: 886-3-327-3456
 Report Issued Date
 : Mar. 20, 2018

 FAX: 886-3-328-4978
 Report Version
 : Rev. 01

5. Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence	2.7
of 95% (U = 2Uc(y))	2.1

Report No.: FR7D0829D

Uncertainty of Radiated Emission Measurement (9 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence	
of 95% (U = 2Uc(y))	3.4

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence	F 7
of 95% (U = 2Uc(y))	5.7

 SPORTON INTERNATIONAL INC.
 Page Number
 : 20 of 20

 TEL: 886-3-327-3456
 Report Issued Date
 : Mar. 20, 2018

 FAX: 886-3-328-4978
 Report Version
 : Rev. 01

Appendix A. Test Results of Conducted Emission Test

Report No.: FR7D0829D

SPORTON INTERNATIONAL INC. Page Number : A1 of A1

EUT Information


 Report NO :
 7D0829

 Test Mode :
 Mode 1

 Test Voltage :
 120Vac/60Hz

Phase: Line

Full Spectrum




Final_Result

Frequency (MHz)	QuasiPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Filter	Corr. (dB)
(1411-12)	(αΒμν)	(ασμν)	(ασμν)	(ub)			(ub)
0.150000		21.74	56.00	34.26	L1	OFF	19.5
0.150000	41.39		66.00	24.61	L1	OFF	19.5
0.285000		20.76	50.67	29.91	L1	OFF	19.5
0.285000	25.01		60.67	35.66	L1	OFF	19.5
0.397500		16.96	47.91	30.95	L1	OFF	19.5
0.397500	25.93		57.91	31.98	L1	OFF	19.5
0.667500		18.22	46.00	27.78	L1	OFF	19.5
0.667500	27.89		56.00	28.11	L1	OFF	19.5
0.937500		17.98	46.00	28.02	L1	OFF	19.5
0.937500	26.53		56.00	29.47	L1	OFF	19.5
2.008500		17.91	46.00	28.09	L1	OFF	19.6
2.008500	25.29		56.00	30.71	L1	OFF	19.6
13.560000		23.99	50.00	26.01	L1	OFF	19.7
13.560000	32.21		60.00	27.79	L1	OFF	19.7

EUT Information

Report NO: 7D0829
Test Mode: Mode 1
Test Voltage: 120Vac/60Hz
Phase: Neutral

Full Spectrum




Final_Result

Frequency	QuasiPeak	Average	Limit	Margin	Line	Filter	Corr.
(MHz)	(dBµV)	(dBµV)	(dBµV)	(dB)			(dB)
0.15225		23.64	55.88	32.24	N	OFF	19.5
0.15225	39.92	I	65.88	25.96	N	OFF	19.5
0.294		21.37	50.41	29.04	N	OFF	19.5
0.294	26.04		60.41	34.37	N	OFF	19.5
0.39525		20.35	47.95	27.6	N	OFF	19.5
0.39525	27.8		57.95	30.15	N	OFF	19.5
0.474		17.36	46.44	29.08	N	OFF	19.5
0.474	25.28		56.44	31.16	N	OFF	19.5
0.59325		19.22	46	26.78	N	OFF	19.5
0.59325	28.36	I	56	27.64	N	OFF	19.5
0.66975		23.28	46	22.72	N	OFF	19.5
0.66975	32.82		56	23.18	N	OFF	19.5
13.56		23.56	50	26.44	N	OFF	19.8
13.56	33.98	-	60	26.02	N	OFF	19.8

Appendix B. Test Results of Conducted Test Items

B1.Test Result of 20dB Spectrum Bandwidth



Remark: Because the measured signal is CW adjusting the RBW per C63.10 would not be practical since measured bandwidth will always follow the RBW and the result will be approximately twice the RBW.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 Report No.: FR7D0829D



B2.Test Result of Frequency Stability

B3. Voltage vs. Fr	equency Stability	Temperature vs. Frequency Stability					
Voltage (Vac)	Measurement Frequency (MHz)	Temperature (°C)	Time	Measurement Frequency (MHz)			
120	13.559710	-20	0	13.559740			
102	13.559710		2	13.559740			
138	13.559710		5	13.559740			
			10	13.559760			
		-10	0	13.559760			
			2	13.559760			
			5	13.559760			
			10	13.559760			
		0	0	13.559720			
			2	13.559730			
			5	13.559740			
			10	13.559740			
		10	0	13.559720			
			2	13.559740			
			5	13.559740			
			10	13.559740			
		20	0	13.559700			
			2	13.559700			
			5	13.559700			
			10	13.559700			
		30	0	13.559700			
			2	13.559690			
			5	13.559690			
			10	13.559680			
		40	0	13.559680			
			2	13.559680			
			5	13.559680			
			10	13.559660			

Report No. : FR7D0829D

SPORTON INTERNATIONAL INC. Page Number : B2 of B3


Voltage vs. Freque	ency Stability	Temperature vs. Frequency Stability				
Voltage (Vac)	Measurement Frequency (MHz)	Temperature (°C)	Time	Measurement Frequency (MHz)		
		50	0	13.559660		
			2	13.559660		
			5	13.559660		
			10	13.559660		
Max.Deviation (MHz)	-0.000290	Max.Deviation (MHz)		-0.000340		
Max.Deviation (ppm)	-21.3864	Max.Deviation (ppm)		-25.0737		
Limit	FS < ±100 ppm	Limit		FS < ±100 ppm		
Test Result PASS		Test Result		PASS		

Report No.: FR7D0829D

SPORTON INTERNATIONAL INC. Page Number : B3 of B3

Appendix C. Test Results of Radiated Test Items

C1. Test Result of Field Strength of Fundamental Emissions




Report No.: FR7D0829D

SPORTON INTERNATIONAL INC. Page Number : C1 of C5



C2. Results of Radiated Spurious Emissions (9 kHz~30MHz)



Report No.: FR7D0829D

25.54

19.8

16.04

20.06

19.99

19.94

0.72

0.72

0.72

Average QΡ

QΡ

TEL: 886-3-327-3456 FAX: 886-3-328-4978

0.15068

0.49751

10.68

46.32

40.51

36.7

-57.72

-33.16


-32.8

104.04

73.67

69.5





Note:

- 1. 13.56 MHz is fundamental signal which can be ignored.
- 2. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
- 3. Distance extrapolation factor = 40 log (specific distance / test distance) (dB);
- Limit line = specific limits (dBμV) + distance extrapolation factor.


Page Number

: C3 of C5

Report No.: FR7D0829D




C3. Results of Radiated Spurious Emissions (30MHz~1GHz)



Report No.: FR7D0829D

Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Remark
		Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	
(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV)	(dB)	(dB)	(dB)	(cm)	(deg)	
67.8	30.35	-9.65	40	47.59	12.14	2.11	31.59	-	-	Peak
187.68	31.22	-12.28	43.5	45.07	14.77	2.72	31.46	-	-	Peak
294.87	28.93	-17.07	46	37.76	19.06	3.28	31.31	-	-	Peak
339.9	39.6	-6.4	46	47.24	20.02	3.43	31.23	100	0	Peak
573.7	39.22	-6.78	46	39.9	25.54	4.2	30.87	-	-	Peak
852.3	39.31	-6.69	46	34.73	28.83	5.2	30.55	-	-	Peak





Report No.: FR7D0829D

Note:

- 1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
- 2. Emission level (dB μ V/m) = 20 log Emission level (μ V/m).
- 3. Corrected Reading: Antenna Factor + Cable Loss + Read Level Preamp Factor= Level.