

RF Mode	TX 802.11ax (HE40)	Channel	CH 102 : 5510 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5453.70	50.6 PK	74.0	-23.4	1.35 H	168	48.5	2.1
2	5453.70	38.2 AV	54.0	-15.8	1.35 H	168	36.1	2.1
3	#5465.75	51.6 PK	68.2	-16.6	1.35 H	168	49.5	2.1
4	*5510.00	95.5 PK			1.35 H	168	93.4	2.1
5	*5510.00	83.8 AV			1.35 H	168	81.7	2.1
6	11020.00	46.5 PK	74.0	-27.5	1.58 H	228	34.2	12.3
7	11020.00	36.0 AV	54.0	-18.0	1.58 H	228	23.7	12.3
8	#16530.00	54.9 PK	68.2	-13.3	1.29 H	319	41.0	13.9

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	60.0 PK	74.0	-14.0	1.59 V	271	57.9	2.1
2	5460.00	45.2 AV	54.0	-8.8	1.59 V	271	43.1	2.1
3	#5467.68	66.4 PK	68.2	-1.8	1.59 V	271	64.2	2.2
4	*5510.00	108.5 PK			1.59 V	271	106.4	2.1
5	*5510.00	97.0 AV			1.59 V	271	94.9	2.1
6	11020.00	48.7 PK	74.0	-25.3	2.10 V	340	36.4	12.3
7	11020.00	38.1 AV	54.0	-15.9	2.10 V	340	25.8	12.3
8	#16530.00	55.4 PK	68.2	-12.8	2.04 V	252	41.5	13.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 110 : 5550 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	57.8 PK	74.0	-16.2	1.40 H	163	55.7	2.1
2	5460.00	41.1 AV	54.0	-12.9	1.40 H	163	39.0	2.1
3	#5470.00	60.8 PK	68.2	-7.4	1.40 H	163	58.6	2.2
4	*5550.00	101.6 PK			1.40 H	163	99.5	2.1
5	*5550.00	89.5 AV			1.40 H	163	87.4	2.1
6	11100.00	45.7 PK	74.0	-28.3	1.61 H	243	33.8	11.9
7	11100.00	35.3 AV	54.0	-18.7	1.61 H	243	23.4	11.9
8	#16650.00	54.5 PK	68.2	-13.7	1.24 H	308	39.7	14.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	59.4 PK	74.0	-14.6	1.38 V	277	57.3	2.1
2	5460.00	42.7 AV	54.0	-11.3	1.38 V	277	40.6	2.1
3	#5470.00	63.1 PK	68.2	-5.1	1.38 V	277	60.9	2.2
4	*5550.00	111.3 PK			1.38 V	277	109.2	2.1
5	*5550.00	100.6 AV			1.38 V	277	98.5	2.1
6	11100.00	48.6 PK	74.0	-25.4	2.10 V	343	36.7	11.9
7	11100.00	37.6 AV	54.0	-16.4	2.10 V	343	25.7	11.9
8	#16650.00	55.7 PK	68.2	-12.5	2.04 V	246	40.9	14.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 134 : 5670 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5670.00	100.2 PK			1.43 H	171	97.9	2.3
2	*5670.00	88.6 AV			1.43 H	171	86.3	2.3
3	#5725.00	59.6 PK	68.2	-8.6	1.43 H	171	57.2	2.4
4	11340.00	46.5 PK	74.0	-27.5	1.69 H	223	34.3	12.2
5	11340.00	36.0 AV	54.0	-18.0	1.69 H	223	23.8	12.2
6	#17010.00	54.9 PK	68.2	-13.3	1.25 H	325	38.3	16.6
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5670.00	112.2 PK			1.58 V	278	109.9	2.3
2	*5670.00	100.2 AV			1.58 V	278	97.9	2.3
3	#5732.68	66.4 PK	68.2	-1.8	1.58 V	278	63.9	2.5
4	11340.00	49.4 PK	74.0	-24.6	2.06 V	339	37.2	12.2
5	11340.00	38.3 AV	54.0	-15.7	2.06 V	339	26.1	12.2
6	#17010.00	55.7 PK	68.2	-12.5	2.00 V	230	39.1	16.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 142 : 5710 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	51.1 PK	74.0	-22.9	1.41 H	168	49.0	2.1
2	5460.00	37.9 AV	54.0	-16.1	1.41 H	168	35.8	2.1
3	#5470.00	52.1 PK	68.2	-16.1	1.41 H	168	49.9	2.2
4	*5710.00	100.8 PK			1.41 H	168	98.4	2.4
5	*5710.00	89.0 AV			1.41 H	168	86.6	2.4
6	#5850.00	53.8 PK	68.2	-14.4	1.41 H	168	51.1	2.7
7	11420.00	46.4 PK	74.0	-27.6	1.65 H	230	33.9	12.5
8	11420.00	36.1 AV	54.0	-17.9	1.65 H	230	23.6	12.5
9	#17130.00	54.5 PK	68.2	-13.7	1.32 H	328	37.7	16.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	51.8 PK	74.0	-22.2	1.58 V	271	49.7	2.1
2	5460.00	38.1 AV	54.0	-15.9	1.58 V	271	36.0	2.1
3	#5470.00	53.1 PK	68.2	-15.1	1.58 V	271	50.9	2.2
4	*5710.00	112.5 PK			1.58 V	271	110.1	2.4
5	*5710.00	100.8 AV			1.58 V	271	98.4	2.4
6	#5850.00	55.5 PK	68.2	-12.7	1.58 V	271	52.8	2.7
7	11420.00	48.7 PK	74.0	-25.3	2.14 V	336	36.2	12.5
8	11420.00	37.5 AV	54.0	-16.5	2.14 V	336	25.0	12.5
9	#17130.00	55.6 PK	68.2	-12.6	2.03 V	251	38.8	16.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 151 : 5755 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5632.16	49.8 PK	68.2	-18.4	2.61 H	139	47.5	2.3
2	*5755.00	100.4 PK			2.61 H	139	97.9	2.5
3	*5755.00	88.2 AV			2.61 H	139	85.7	2.5
4	#5971.19	51.3 PK	68.2	-16.9	2.61 H	139	48.4	2.9
5	11510.00	45.4 PK	74.0	-28.6	1.66 H	250	32.8	12.6
6	11510.00	35.4 AV	54.0	-18.6	1.66 H	250	22.8	12.6
7	#17265.00	54.6 PK	68.2	-13.6	1.34 H	318	37.7	16.9
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5649.67	53.9 PK	68.2	-14.3	1.48 V	288	51.6	2.3
2	*5755.00	112.8 PK			1.48 V	288	110.3	2.5
3	*5755.00	101.7 AV			1.48 V	288	99.2	2.5
4	#5930.75	52.6 PK	68.2	-15.6	1.48 V	288	49.7	2.9
5	11510.00	48.6 PK	74.0	-25.4	2.10 V	344	36.0	12.6
6	11510.00	37.7 AV	54.0	-16.3	2.10 V	344	25.1	12.6
7	#17265.00	56.3 PK	68.2	-11.9	1.97 V	255	39.4	16.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 159 : 5795 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5629.61	50.4 PK	68.2	-17.8	2.57 H	135	48.1	2.3
2	*5795.00	100.2 PK			2.57 H	135	97.6	2.6
3	*5795.00	87.9 AV			2.57 H	135	85.3	2.6
4	#6022.65	51.3 PK	68.2	-16.9	2.57 H	135	48.3	3.0
5	11590.00	46.1 PK	74.0	-27.9	1.64 H	242	33.5	12.6
6	11590.00	35.7 AV	54.0	-18.3	1.64 H	242	23.1	12.6
7	#17385.00	54.9 PK	68.2	-13.3	1.23 H	309	37.0	17.9
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5648.31	52.8 PK	68.2	-15.4	1.47 V	284	50.5	2.3
2	*5795.00	113.0 PK			1.47 V	284	110.4	2.6
3	*5795.00	101.6 AV			1.47 V	284	99.0	2.6
4	#5931.76	57.4 PK	68.2	-10.8	1.47 V	284	54.5	2.9
5	11590.00	49.0 PK	74.0	-25.0	2.12 V	356	36.4	12.6
6	11590.00	38.3 AV	54.0	-15.7	2.12 V	356	25.7	12.6
7	#17385.00	55.7 PK	68.2	-12.5	1.99 V	231	37.8	17.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE80)	Channel	CH 42 : 5210 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5125.34	54.1 PK	74.0	-19.9	1.50 H	108	51.8	2.3
2	5125.34	41.4 AV	54.0	-12.6	1.50 H	108	39.1	2.3
3	*5210.00	92.9 PK			1.50 H	108	90.8	2.1
4	*5210.00	81.4 AV			1.50 H	108	79.3	2.1
5	5350.00	49.9 PK	74.0	-24.1	1.50 H	108	48.0	1.9
6	5350.00	37.3 AV	54.0	-16.7	1.50 H	108	35.4	1.9
7	#10420.00	46.1 PK	68.2	-22.1	1.58 H	239	34.0	12.1
8	15630.00	54.8 PK	74.0	-19.2	1.30 H	307	43.1	11.7
9	15630.00	42.0 AV	54.0	-12.0	1.30 H	307	30.3	11.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5141.35	63.9 PK	74.0	-10.1	1.55 V	273	61.6	2.3
2	5141.35	52.4 AV	54.0	-1.6	1.55 V	273	50.1	2.3
3	5147.00	68.1 PK	74.0	-5.9	1.55 V	273	65.8	2.3
4	5147.00	51.7 AV	54.0	-2.3	1.55 V	273	49.4	2.3
5	*5210.00	105.5 PK			1.55 V	273	103.4	2.1
6	*5210.00	93.8 AV			1.55 V	273	91.7	2.1
7	5350.00	50.9 PK	74.0	-23.1	1.55 V	273	49.0	1.9
8	5350.00	39.4 AV	54.0	-14.6	1.55 V	273	37.5	1.9
9	#10420.00	49.4 PK	68.2	-18.8	2.15 V	356	37.3	12.1
10	15630.00	55.0 PK	74.0	-19.0	1.98 V	220	43.3	11.7
11	15630.00	42.4 AV	54.0	-11.6	1.98 V	220	30.7	11.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE80)	Channel	CH 58 : 5290 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	51.4 PK	74.0	-22.6	1.35 H	168	49.1	2.3
2	5150.00	38.5 AV	54.0	-15.5	1.35 H	168	36.2	2.3
3	*5290.00	91.7 PK			1.35 H	168	89.9	1.8
4	*5290.00	80.2 AV			1.35 H	168	78.4	1.8
5	5373.70	57.9 PK	74.0	-16.1	1.35 H	168	55.9	2.0
6	5373.70	42.1 AV	54.0	-11.9	1.35 H	168	40.1	2.0
7	#10580.00	46.2 PK	68.2	-22.0	1.59 H	251	34.4	11.8
8	15870.00	54.4 PK	74.0	-19.6	1.30 H	323	43.1	11.3
9	15870.00	41.6 AV	54.0	-12.4	1.30 H	323	30.3	11.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	53.2 PK	74.0	-20.8	1.27 V	273	50.9	2.3
2	5150.00	40.7 AV	54.0	-13.3	1.27 V	273	38.4	2.3
3	*5290.00	105.3 PK			1.27 V	273	103.5	1.8
4	*5290.00	93.9 AV			1.27 V	273	92.1	1.8
5	5358.00	68.1 PK	74.0	-5.9	1.27 V	273	66.1	2.0
6	5358.00	52.2 AV	54.0	-1.8	1.27 V	273	50.2	2.0
7	#10580.00	48.9 PK	68.2	-19.3	2.09 V	359	37.1	11.8
8	15870.00	55.4 PK	74.0	-18.6	1.96 V	220	44.1	11.3
9	15870.00	42.8 AV	54.0	-11.2	1.96 V	220	31.5	11.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE80)	Channel	CH 106 : 5530 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5442.50	49.7 PK	74.0	-24.3	1.43 H	163	47.6	2.1
2	5442.50	38.2 AV	54.0	-15.8	1.43 H	163	36.1	2.1
3	#5465.60	50.4 PK	68.2	-17.8	1.43 H	163	48.3	2.1
4	*5530.00	89.4 PK			1.43 H	163	87.4	2.0
5	*5530.00	78.8 AV			1.43 H	163	76.8	2.0
6	#5794.60	50.0 PK	68.2	-18.2	1.43 H	163	47.4	2.6
7	11060.00	45.9 PK	74.0	-28.1	1.58 H	241	33.8	12.1
8	11060.00	35.6 AV	54.0	-18.4	1.58 H	241	23.5	12.1
9	#16590.00	54.3 PK	68.2	-13.9	1.34 H	310	40.0	14.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5458.50	64.3 PK	74.0	-9.7	1.50 V	281	62.2	2.1
2	5458.50	47.8 AV	54.0	-6.2	1.50 V	281	45.7	2.1
3	#5467.11	66.6 PK	68.2	-1.6	1.50 V	281	64.4	2.2
4	*5530.00	104.0 PK			1.50 V	281	102.0	2.0
5	*5530.00	92.2 AV			1.50 V	281	90.2	2.0
6	#5770.48	51.6 PK	68.2	-16.6	1.50 V	281	49.1	2.5
7	11060.00	49.7 PK	74.0	-24.3	2.12 V	355	37.6	12.1
8	11060.00	38.8 AV	54.0	-15.2	2.12 V	355	26.7	12.1
9	#16590.00	55.9 PK	68.2	-12.3	2.02 V	217	41.6	14.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE80)	Channel	CH 122 : 5610 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5610.00	92.9 PK			1.43 H	150	90.8	2.1
2	*5610.00	91.8 AV			1.43 H	150	89.7	2.1
3	#5725.00	53.8 PK	68.2	-14.4	1.43 H	150	51.4	2.4
4	11220.00	45.8 PK	74.0	-28.2	1.67 H	242	33.7	12.1
5	11220.00	35.4 AV	54.0	-18.6	1.67 H	242	23.3	12.1
6	#16830.00	55.2 PK	68.2	-13.0	1.25 H	306	39.4	15.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5610.00	108.3 PK			1.52 V	282	106.2	2.1
2	*5610.00	96.7 AV			1.52 V	282	94.6	2.1
3	#5725.00	64.6 PK	68.2	-3.6	1.52 V	282	62.2	2.4
4	11220.00	48.5 PK	74.0	-25.5	2.09 V	345	36.4	12.1
5	11220.00	37.9 AV	54.0	-16.1	2.09 V	345	25.8	12.1
6	#16830.00	56.3 PK	68.2	-11.9	1.96 V	219	40.5	15.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE80)	Channel	CH 138 : 5690 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	53.6 PK	74.0	-20.4	1.45 H	148	51.5	2.1
2	5460.00	38.4 AV	54.0	-15.6	1.45 H	148	36.3	2.1
3	#5470.00	53.8 PK	68.2	-14.4	1.45 H	148	51.6	2.2
4	*5690.00	92.7 PK			1.45 H	148	90.4	2.3
5	*5690.00	91.5 AV			1.45 H	148	89.2	2.3
6	#5850.00	55.5 PK	68.2	-12.7	1.45 H	148	52.8	2.7
7	11380.00	46.1 PK	74.0	-27.9	1.60 H	222	33.7	12.4
8	11380.00	35.9 AV	54.0	-18.1	1.60 H	222	23.5	12.4
9	#17070.00	54.8 PK	68.2	-13.4	1.28 H	302	38.0	16.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	54.2 PK	74.0	-19.8	1.55 V	289	52.1	2.1
2	5460.00	39.9 AV	54.0	-14.1	1.55 V	289	37.8	2.1
3	#5470.00	55.6 PK	68.2	-12.6	1.55 V	289	53.4	2.2
4	*5690.00	108.1 PK			1.55 V	289	105.8	2.3
5	*5690.00	96.3 AV			1.55 V	289	94.0	2.3
6	#5850.00	62.7 PK	68.2	-5.5	1.55 V	289	60.0	2.7
7	11380.00	49.3 PK	74.0	-24.7	2.07 V	346	36.9	12.4
8	11380.00	38.5 AV	54.0	-15.5	2.07 V	346	26.1	12.4
9	#17070.00	55.4 PK	68.2	-12.8	2.00 V	220	38.6	16.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE80)	Channel	CH 155 : 5775 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5649.09	52.1 PK	68.2	-16.1	1.26 H	139	49.8	2.3
2	*5775.00	95.6 PK			1.26 H	139	93.1	2.5
3	*5775.00	84.3 AV			1.26 H	139	81.8	2.5
4	#5929.45	54.7 PK	68.2	-13.5	1.26 H	139	51.8	2.9
5	11550.00	46.0 PK	74.0	-28.0	1.68 H	229	33.5	12.5
6	11550.00	35.7 AV	54.0	-18.3	1.68 H	229	23.2	12.5
7	#17325.00	55.0 PK	68.2	-13.2	1.32 H	321	37.7	17.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5647.53	59.5 PK	68.2	-8.7	1.32 V	273	57.2	2.3
2	*5775.00	107.5 PK			1.32 V	273	105.0	2.5
3	*5775.00	96.1 AV			1.32 V	273	93.6	2.5
4	#5929.15	62.0 PK	68.2	-6.2	1.32 V	273	59.1	2.9
5	11550.00	48.5 PK	74.0	-25.5	2.08 V	356	36.0	12.5
6	11550.00	38.1 AV	54.0	-15.9	2.08 V	356	25.6	12.5
7	#17325.00	55.5 PK	68.2	-12.7	2.00 V	218	38.2	17.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU26)	Channel	CH 36 : 5180 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5004.86	51.0 PK	74.0	-23.0	1.61 H	171	48.9	2.1
2	5004.86	37.4 AV	54.0	-16.6	1.61 H	171	35.3	2.1
3	5131.82	49.8 PK	74.0	-24.2	1.61 H	171	47.5	2.3
4	5131.82	38.1 AV	54.0	-15.9	1.61 H	171	35.8	2.3
5	*5180.00	106.9 PK			1.61 H	171	104.7	2.2
6	*5180.00	95.8 AV			1.61 H	171	93.6	2.2
7	#10360.00	50.8 PK	68.2	-17.4	1.03 H	286	39.0	11.8
8	15540.00	59.1 PK	74.0	-14.9	3.10 H	308	47.3	11.8
9	15540.00	48.7 AV	54.0	-5.3	3.10 H	308	36.9	11.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5146.60	66.6 PK	74.0	-7.4	1.59 V	277	64.3	2.3
2	5146.60	42.1 AV	54.0	-11.9	1.59 V	277	39.8	2.3
3	5150.00	64.8 PK	74.0	-9.2	1.59 V	277	62.5	2.3
4	5150.00	42.7 AV	54.0	-11.3	1.59 V	277	40.4	2.3
5	*5180.00	122.2 PK			1.59 V	277	120.0	2.2
6	*5180.00	110.8 AV			1.59 V	277	108.6	2.2
7	#10360.00	54.5 PK	68.2	-13.7	2.08 V	228	42.7	11.8
8	15540.00	60.4 PK	74.0	-13.6	1.96 V	265	48.6	11.8
9	15540.00	49.8 AV	54.0	-4.2	1.96 V	265	38.0	11.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU26)	Channel	CH 40 : 5200 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	50.9 PK	74.0	-23.1	1.56 H	165	48.6	2.3
2	5150.00	37.6 AV	54.0	-16.4	1.56 H	165	35.3	2.3
3	*5200.00	106.7 PK			1.56 H	165	104.6	2.1
4	*5200.00	95.7 AV			1.56 H	165	93.6	2.1
5	#10400.00	50.5 PK	68.2	-17.7	1.06 H	285	38.5	12.0
6	15600.00	59.4 PK	74.0	-14.6	3.15 H	312	47.9	11.5
7	15600.00	48.8 AV	54.0	-5.2	3.15 H	312	37.3	11.5
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	53.4 PK	74.0	-20.6	1.58 V	283	51.1	2.3
2	5150.00	39.4 AV	54.0	-14.6	1.58 V	283	37.1	2.3
3	*5200.00	122.6 PK			1.58 V	283	120.5	2.1
4	*5200.00	110.9 AV			1.58 V	283	108.8	2.1
5	#10400.00	53.9 PK	68.2	-14.3	2.03 V	223	41.9	12.0
6	15600.00	60.5 PK	74.0	-13.5	2.01 V	269	49.0	11.5
7	15600.00	50.0 AV	54.0	-4.0	2.01 V	269	38.5	11.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU26)	Channel	CH 48 : 5240 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	51.6 PK	74.0	-22.4	1.65 H	183	49.3	2.3
2	5150.00	37.8 AV	54.0	-16.2	1.65 H	183	35.5	2.3
3	*5240.00	107.4 PK			1.65 H	183	105.4	2.0
4	*5240.00	96.1 AV			1.65 H	183	94.1	2.0
5	5350.00	49.8 PK	74.0	-24.2	1.65 H	183	47.9	1.9
6	5350.00	38.2 AV	54.0	-15.8	1.65 H	183	36.3	1.9
7	#10480.00	50.6 PK	68.2	-17.6	1.05 H	286	38.7	11.9
8	15720.00	59.4 PK	74.0	-14.6	3.05 H	313	47.6	11.8
9	15720.00	48.8 AV	54.0	-5.2	3.05 H	313	37.0	11.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	53.5 PK	74.0	-20.5	1.55 V	264	51.2	2.3
2	5150.00	39.3 AV	54.0	-14.7	1.55 V	264	37.0	2.3
3	*5240.00	122.4 PK			1.55 V	264	120.4	2.0
4	*5240.00	111.1 AV			1.55 V	264	109.1	2.0
5	5350.00	52.9 PK	74.0	-21.1	1.55 V	264	51.0	1.9
6	5350.00	39.0 AV	54.0	-15.0	1.55 V	264	37.1	1.9
7	#10480.00	54.2 PK	68.2	-14.0	2.08 V	235	42.3	11.9
8	15720.00	60.1 PK	74.0	-13.9	1.99 V	253	48.3	11.8
9	15720.00	49.4 AV	54.0	-4.6	1.99 V	253	37.6	11.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU26)	Channel	CH 52 : 5260 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	50.4 PK	74.0	-23.6	1.55 H	161	48.1	2.3
2	5150.00	37.1 AV	54.0	-16.9	1.55 H	161	34.8	2.3
3	*5260.00	106.6 PK			1.55 H	161	104.6	2.0
4	*5260.00	95.4 AV			1.55 H	161	93.4	2.0
5	5350.00	49.6 PK	74.0	-24.4	1.55 H	161	47.7	1.9
6	5350.00	37.7 AV	54.0	-16.3	1.55 H	161	35.8	1.9
7	#10520.00	50.6 PK	68.2	-17.6	1.00 H	294	38.6	12.0
8	15780.00	59.3 PK	74.0	-14.7	3.15 H	317	47.8	11.5
9	15780.00	48.8 AV	54.0	-5.2	3.15 H	317	37.3	11.5
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	53.8 PK	74.0	-20.2	1.59 V	282	51.5	2.3
2	5150.00	39.7 AV	54.0	-14.3	1.59 V	282	37.4	2.3
3	*5260.00	121.7 PK			1.59 V	282	119.7	2.0
4	*5260.00	110.5 AV			1.59 V	282	108.5	2.0
5	5350.00	52.9 PK	74.0	-21.1	1.59 V	282	51.0	1.9
6	5350.00	39.3 AV	54.0	-14.7	1.59 V	282	37.4	1.9
7	#10520.00	54.4 PK	68.2	-13.8	2.12 V	240	42.4	12.0
8	15780.00	59.8 PK	74.0	-14.2	1.94 V	265	48.3	11.5
9	15780.00	49.5 AV	54.0	-4.5	1.94 V	265	38.0	11.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU26)	Channel	CH 60 : 5300 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5300.00	107.3 PK			1.61 H	185	105.6	1.7
2	*5300.00	96.1 AV			1.61 H	185	94.4	1.7
3	5350.00	51.2 PK	74.0	-22.8	1.61 H	185	49.3	1.9
4	5350.00	37.8 AV	54.0	-16.2	1.61 H	185	35.9	1.9
5	10600.00	51.2 PK	74.0	-22.8	1.02 H	270	39.3	11.9
6	10600.00	40.6 AV	54.0	-13.4	1.02 H	270	28.7	11.9
7	15900.00	60.0 PK	74.0	-14.0	3.12 H	312	48.7	11.3
8	15900.00	49.2 AV	54.0	-4.8	3.12 H	312	37.9	11.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5300.00	121.6 PK			1.61 V	268	119.9	1.7
2	*5300.00	110.4 AV			1.61 V	268	108.7	1.7
3	5350.00	52.8 PK	74.0	-21.2	1.61 V	268	50.9	1.9
4	5350.00	38.9 AV	54.0	-15.1	1.61 V	268	37.0	1.9
5	10600.00	54.1 PK	74.0	-19.9	2.10 V	244	42.2	11.9
6	10600.00	43.6 AV	54.0	-10.4	2.10 V	244	31.7	11.9
7	15900.00	59.9 PK	74.0	-14.1	1.93 V	266	48.6	11.3
8	15900.00	49.4 AV	54.0	-4.6	1.93 V	266	38.1	11.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 20MHz Preamble 802.11ax (RU26)	Channel	CH 64 : 5320 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5320.00	106.5 PK			1.58 H	165	104.7	1.8
2	*5320.00	95.5 AV			1.58 H	165	93.7	1.8
3	5362.50	50.2 PK	74.0	-23.8	1.58 H	165	48.2	2.0
4	5362.50	37.4 AV	54.0	-16.6	1.58 H	165	35.4	2.0
5	10640.00	50.6 PK	74.0	-23.4	1.08 H	278	38.8	11.8
6	10640.00	40.6 AV	54.0	-13.4	1.08 H	278	28.8	11.8
7	15960.00	59.9 PK	74.0	-14.1	3.18 H	328	48.3	11.6
8	15960.00	49.2 AV	54.0	-4.8	3.18 H	328	37.6	11.6
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5320.00	121.1 PK			1.36 V	283	119.3	1.8
2	*5320.00	110.5 AV			1.36 V	283	108.7	1.8
3	5355.60	69.1 PK	74.0	-4.9	1.36 V	283	67.1	2.0
4	5355.60	42.0 AV	54.0	-12.0	1.36 V	283	40.0	2.0
5	5368.00	53.0 PK	74.0	-21.0	1.36 V	283	51.0	2.0
6	5368.00	42.9 AV	54.0	-11.1	1.36 V	283	40.9	2.0
7	10640.00	54.7 PK	74.0	-19.3	2.11 V	239	42.9	11.8
8	10640.00	44.2 AV	54.0	-9.8	2.11 V	239	32.4	11.8
9	15960.00	61.0 PK	74.0	-13.0	1.93 V	279	49.4	11.6
10	15960.00	50.2 AV	54.0	-3.8	1.93 V	279	38.6	11.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 20MHz Preamble 802.11ax (RU26)	Channel	CH 100 : 5500 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	50.3 PK	74.0	-23.7	1.63 H	169	48.2	2.1
2	5460.00	37.6 AV	54.0	-16.4	1.63 H	169	35.5	2.1
3	#5470.00	49.1 PK	68.2	-19.1	1.63 H	169	46.9	2.2
4	*5500.00	107.4 PK			1.63 H	169	105.3	2.1
5	*5500.00	96.4 AV			1.63 H	169	94.3	2.1
6	11000.00	50.9 PK	74.0	-23.1	1.09 H	292	38.5	12.4
7	11000.00	40.3 AV	54.0	-13.7	1.09 H	292	27.9	12.4
8	#16500.00	59.6 PK	68.2	-8.6	3.12 H	298	45.9	13.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5457.20	61.9 PK	74.0	-12.1	1.60 V	273	59.8	2.1
2	5457.20	43.4 AV	54.0	-10.6	1.60 V	273	41.3	2.1
3	#5467.80	65.9 PK	68.2	-2.3	1.60 V	273	63.7	2.2
4	*5500.00	121.9 PK			1.60 V	273	119.8	2.1
5	*5500.00	111.3 AV			1.60 V	273	109.2	2.1
6	11000.00	54.3 PK	74.0	-19.7	2.08 V	242	41.9	12.4
7	11000.00	44.0 AV	54.0	-10.0	2.08 V	242	31.6	12.4
8	#16500.00	60.7 PK	68.2	-7.5	2.00 V	251	47.0	13.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU26)	Channel	CH 116 : 5580 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5580.00	107.3 PK			1.62 H	178	105.2	2.1
2	*5580.00	96.2 AV			1.62 H	178	94.1	2.1
3	11160.00	50.2 PK	74.0	-23.8	1.09 H	295	38.2	12.0
4	11160.00	39.9 AV	54.0	-14.1	1.09 H	295	27.9	12.0
5	#16740.00	59.3 PK	68.2	-8.9	3.20 H	308	44.0	15.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5580.00	122.9 PK			1.64 V	270	120.8	2.1
2	*5580.00	111.3 AV			1.64 V	270	109.2	2.1
3	11160.00	54.5 PK	74.0	-19.5	2.03 V	237	42.5	12.0
4	11160.00	44.1 AV	54.0	-9.9	2.03 V	237	32.1	12.0
5	#16740.00	60.6 PK	68.2	-7.6	2.00 V	260	45.3	15.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU26)	Channel	CH 140 : 5700 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5700.00	106.9 PK			1.61 H	179	104.6	2.3
2	*5700.00	95.9 AV			1.61 H	179	93.6	2.3
3	#5725.00	57.8 PK	68.2	-10.4	1.61 H	179	55.4	2.4
4	11400.00	50.3 PK	74.0	-23.7	1.09 H	292	37.8	12.5
5	11400.00	40.2 AV	54.0	-13.8	1.09 H	292	27.7	12.5
6	#17100.00	59.7 PK	68.2	-8.5	3.19 H	327	42.9	16.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5700.00	120.8 PK			1.28 V	286	118.5	2.3
2	*5700.00	110.9 AV			1.28 V	286	108.6	2.3
3	#5725.00	66.5 PK	68.2	-1.7	1.28 V	286	64.1	2.4
4	11400.00	54.0 PK	74.0	-20.0	2.08 V	220	41.5	12.5
5	11400.00	43.5 AV	54.0	-10.5	2.08 V	220	31.0	12.5
6	#17100.00	60.1 PK	68.2	-8.1	1.93 V	252	43.3	16.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU26)	Channel	CH 144 : 5720 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	51.3 PK	74.0	-22.7	1.58 H	181	49.2	2.1
2	5460.00	37.9 AV	54.0	-16.1	1.58 H	181	35.8	2.1
3	#5470.00	50.2 PK	68.2	-18.0	1.58 H	181	48.0	2.2
4	*5720.00	106.9 PK			1.58 H	181	104.5	2.4
5	*5720.00	95.7 AV			1.58 H	181	93.3	2.4
6	#5850.00	51.8 PK	68.2	-16.4	1.58 H	181	49.1	2.7
7	11440.00	49.9 PK	74.0	-24.1	1.02 H	272	37.5	12.4
8	11440.00	39.8 AV	54.0	-14.2	1.02 H	272	27.4	12.4
9	#17160.00	59.9 PK	68.2	-8.3	3.13 H	308	43.3	16.6
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	52.9 PK	74.0	-21.1	1.57 V	280	50.8	2.1
2	5460.00	39.0 AV	54.0	-15.0	1.57 V	280	36.9	2.1
3	#5470.00	53.3 PK	68.2	-14.9	1.57 V	280	51.1	2.2
4	*5720.00	122.5 PK			1.57 V	280	120.1	2.4
5	*5720.00	110.8 AV			1.57 V	280	108.4	2.4
6	#5850.00	52.1 PK	68.2	-16.1	1.57 V	280	49.4	2.7
7	11440.00	54.5 PK	74.0	-19.5	2.10 V	206	42.1	12.4
8	11440.00	43.9 AV	54.0	-10.1	2.10 V	206	31.5	12.4
9	#17160.00	60.1 PK	68.2	-8.1	1.87 V	247	43.5	16.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU26)	Channel	CH 149 : 5745 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5609.71	50.2 PK	68.2	-18.0	1.06 H	178	48.1	2.1
2	*5745.00	109.2 PK			1.06 H	178	106.8	2.4
3	*5745.00	99.8 AV			1.06 H	178	97.4	2.4
4	#6005.32	50.7 PK	68.2	-17.5	1.06 H	178	47.8	2.9
5	11490.00	50.9 PK	74.0	-23.1	1.10 H	270	38.3	12.6
6	11490.00	40.5 AV	54.0	-13.5	1.10 H	270	27.9	12.6
7	#17235.00	58.9 PK	68.2	-9.3	3.14 H	314	42.1	16.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5627.64	52.2 PK	68.2	-16.0	1.35 V	278	49.9	2.3
2	*5745.00	124.5 PK			1.35 V	278	122.1	2.4
3	*5745.00	113.4 AV			1.35 V	278	111.0	2.4
4	#5992.32	50.6 PK	68.2	-17.6	1.35 V	278	47.7	2.9
5	11490.00	54.2 PK	74.0	-19.8	2.08 V	229	41.6	12.6
6	11490.00	43.8 AV	54.0	-10.2	2.08 V	229	31.2	12.6
7	#17235.00	60.2 PK	68.2	-8.0	1.94 V	250	43.4	16.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU26)	Channel	CH 157 : 5785 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5623.77	50.8 PK	68.2	-17.4	1.10 H	176	48.7	2.1
2	*5785.00	108.9 PK			1.10 H	176	106.3	2.6
3	*5785.00	99.7 AV			1.10 H	176	97.1	2.6
4	#5925.87	50.5 PK	68.2	-17.7	1.10 H	176	47.6	2.9
5	11570.00	50.3 PK	74.0	-23.7	1.06 H	285	37.7	12.6
6	11570.00	40.1 AV	54.0	-13.9	1.06 H	285	27.5	12.6
7	#17355.00	62.7 PK	68.2	-5.5	3.13 H	301	45.0	17.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5572.53	51.9 PK	68.2	-16.3	1.49 V	276	49.8	2.1
2	*5785.00	124.6 PK			1.49 V	276	122.0	2.6
3	*5785.00	113.5 AV			1.49 V	276	110.9	2.6
4	#5962.91	51.3 PK	68.2	-16.9	1.49 V	276	48.4	2.9
5	11570.00	53.8 PK	74.0	-20.2	2.06 V	217	41.2	12.6
6	11570.00	43.4 AV	54.0	-10.6	2.06 V	217	30.8	12.6
7	#17355.00	62.9 PK	68.2	-5.3	1.98 V	267	45.2	17.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU26)	Channel	CH 165 : 5825 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5590.29	50.3 PK	68.2	-17.9	1.25 H	179	48.2	2.1
2	*5825.00	108.1 PK			1.25 H	179	105.5	2.6
3	*5825.00	98.7 AV			1.25 H	179	96.1	2.6
4	#6023.92	50.6 PK	68.2	-17.6	1.25 H	179	47.6	3.0
5	11650.00	50.2 PK	74.0	-23.8	1.09 H	279	38.0	12.2
6	11650.00	40.0 AV	54.0	-14.0	1.09 H	279	27.8	12.2
7	#17475.00	59.0 PK	68.2	-9.2	3.12 H	314	40.3	18.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5565.07	51.4 PK	68.2	-16.8	1.51 V	272	49.3	2.1
2	*5825.00	124.3 PK			1.51 V	272	121.7	2.6
3	*5825.00	113.2 AV			1.51 V	272	110.6	2.6
4	#5929.81	50.6 PK	68.2	-17.6	1.51 V	272	47.7	2.9
5	11650.00	54.0 PK	74.0	-20.0	2.06 V	243	41.8	12.2
6	11650.00	43.5 AV	54.0	-10.5	2.06 V	243	31.3	12.2
7	#17475.00	60.9 PK	68.2	-7.3	2.02 V	274	42.2	18.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU52)	Channel	CH 36 : 5180 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5144.90	53.4 PK	74.0	-20.6	1.69 H	163	51.1	2.3
2	5144.90	39.5 AV	54.0	-14.5	1.69 H	163	37.2	2.3
3	*5180.00	106.6 PK			1.69 H	163	104.4	2.2
4	*5180.00	94.8 AV			1.69 H	163	92.6	2.2
5	#10360.00	47.2 PK	68.2	-21.0	1.02 H	279	35.4	11.8
6	15540.00	58.8 PK	74.0	-15.2	1.30 H	331	47.0	11.8
7	15540.00	45.4 AV	54.0	-8.6	1.30 H	331	33.6	11.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5146.60	69.5 PK	74.0	-4.5	1.70 V	280	67.2	2.3
2	5146.60	43.6 AV	54.0	-10.4	1.70 V	280	41.3	2.3
3	5150.00	61.3 PK	74.0	-12.7	1.70 V	280	59.0	2.3
4	5150.00	45.1 AV	54.0	-8.9	1.70 V	280	42.8	2.3
5	*5180.00	120.8 PK			1.70 V	280	118.6	2.2
6	*5180.00	108.7 AV			1.70 V	280	106.5	2.2
7	#10360.00	48.8 PK	68.2	-19.4	2.00 V	197	37.0	11.8
8	15540.00	56.8 PK	74.0	-17.2	1.44 V	289	45.0	11.8
9	15540.00	43.2 AV	54.0	-10.8	1.44 V	289	31.4	11.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU52)	Channel	CH 40 : 5200 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	51.4 PK	74.0	-22.6	1.65 H	171	49.1	2.3
2	5150.00	37.7 AV	54.0	-16.3	1.65 H	171	35.4	2.3
3	*5200.00	106.6 PK			1.65 H	171	104.5	2.1
4	*5200.00	95.0 AV			1.65 H	171	92.9	2.1
5	#10400.00	46.6 PK	68.2	-21.6	1.00 H	266	34.6	12.0
6	15600.00	58.5 PK	74.0	-15.5	1.34 H	337	47.0	11.5
7	15600.00	45.1 AV	54.0	-8.9	1.34 H	337	33.6	11.5
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	53.5 PK	74.0	-20.5	1.69 V	287	51.2	2.3
2	5150.00	39.2 AV	54.0	-14.8	1.69 V	287	36.9	2.3
3	*5200.00	120.7 PK			1.69 V	287	118.6	2.1
4	*5200.00	108.4 AV			1.69 V	287	106.3	2.1
5	#10400.00	49.5 PK	68.2	-18.7	2.04 V	187	37.5	12.0
6	15600.00	57.1 PK	74.0	-16.9	1.41 V	304	45.6	11.5
7	15600.00	43.3 AV	54.0	-10.7	1.41 V	304	31.8	11.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU52)	Channel	CH 48 : 5240 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	51.1 PK	74.0	-22.9	1.74 H	164	48.8	2.3
2	5150.00	37.6 AV	54.0	-16.4	1.74 H	164	35.3	2.3
3	*5240.00	105.9 PK			1.74 H	164	103.9	2.0
4	*5240.00	94.3 AV			1.74 H	164	92.3	2.0
5	5350.00	49.4 PK	74.0	-24.6	1.74 H	164	47.5	1.9
6	5350.00	38.0 AV	54.0	-16.0	1.74 H	164	36.1	1.9
7	#10480.00	47.5 PK	68.2	-20.7	1.00 H	267	35.6	11.9
8	15720.00	58.8 PK	74.0	-15.2	1.27 H	318	47.0	11.8
9	15720.00	45.7 AV	54.0	-8.3	1.27 H	318	33.9	11.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	53.9 PK	74.0	-20.1	1.73 V	284	51.6	2.3
2	5150.00	39.5 AV	54.0	-14.5	1.73 V	284	37.2	2.3
3	*5240.00	121.0 PK			1.73 V	284	119.0	2.0
4	*5240.00	108.7 AV			1.73 V	284	106.7	2.0
5	5350.00	52.6 PK	74.0	-21.4	1.73 V	284	50.7	1.9
6	5350.00	38.8 AV	54.0	-15.2	1.73 V	284	36.9	1.9
7	#10480.00	48.8 PK	68.2	-19.4	2.00 V	203	36.9	11.9
8	15720.00	57.4 PK	74.0	-16.6	1.43 V	291	45.6	11.8
9	15720.00	43.7 AV	54.0	-10.3	1.43 V	291	31.9	11.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU52)	Channel	CH 52 : 5260 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	50.7 PK	74.0	-23.3	1.71 H	154	48.4	2.3
2	5150.00	36.9 AV	54.0	-17.1	1.71 H	154	34.6	2.3
3	*5260.00	107.1 PK			1.71 H	154	105.1	2.0
4	*5260.00	95.0 AV			1.71 H	154	93.0	2.0
5	5350.00	49.7 PK	74.0	-24.3	1.71 H	154	47.8	1.9
6	5350.00	37.9 AV	54.0	-16.1	1.71 H	154	36.0	1.9
7	#10520.00	46.9 PK	68.2	-21.3	1.08 H	270	34.9	12.0
8	15780.00	58.5 PK	74.0	-15.5	1.25 H	333	47.0	11.5
9	15780.00	45.2 AV	54.0	-8.8	1.25 H	333	33.7	11.5
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	53.7 PK	74.0	-20.3	1.67 V	277	51.4	2.3
2	5150.00	39.1 AV	54.0	-14.9	1.67 V	277	36.8	2.3
3	*5260.00	120.9 PK			1.67 V	277	118.9	2.0
4	*5260.00	108.9 AV			1.67 V	277	106.9	2.0
5	5350.00	52.1 PK	74.0	-21.9	1.67 V	277	50.2	1.9
6	5350.00	38.5 AV	54.0	-15.5	1.67 V	277	36.6	1.9
7	#10520.00	49.0 PK	68.2	-19.2	2.02 V	207	37.0	12.0
8	15780.00	56.6 PK	74.0	-17.4	1.50 V	303	45.1	11.5
9	15780.00	42.8 AV	54.0	-11.2	1.50 V	303	31.3	11.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU52)	Channel	CH 60 : 5300 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5300.00	106.2 PK			1.74 H	163	104.5	1.7
2	*5300.00	94.3 AV			1.74 H	163	92.6	1.7
3	5350.00	50.6 PK	74.0	-23.4	1.74 H	163	48.7	1.9
4	5350.00	37.0 AV	54.0	-17.0	1.74 H	163	35.1	1.9
5	10600.00	47.0 PK	74.0	-27.0	1.01 H	272	35.1	11.9
6	10600.00	36.7 AV	54.0	-17.3	1.01 H	272	24.8	11.9
7	15900.00	59.3 PK	74.0	-14.7	1.29 H	322	48.0	11.3
8	15900.00	45.8 AV	54.0	-8.2	1.29 H	322	34.5	11.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5300.00	121.1 PK			1.69 V	283	119.4	1.7
2	*5300.00	108.7 AV			1.69 V	283	107.0	1.7
3	5350.00	54.2 PK	74.0	-19.8	1.69 V	283	52.3	1.9
4	5350.00	39.8 AV	54.0	-14.2	1.69 V	283	37.9	1.9
5	10600.00	49.0 PK	74.0	-25.0	2.04 V	209	37.1	11.9
6	10600.00	39.5 AV	54.0	-14.5	2.04 V	209	27.6	11.9
7	15900.00	56.2 PK	74.0	-17.8	1.46 V	294	44.9	11.3
8	15900.00	42.7 AV	54.0	-11.3	1.46 V	294	31.4	11.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 20MHz Preamble 802.11ax (RU52)	Channel	CH 64 : 5320 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5320.00	107.4 PK			1.74 H	166	105.6	1.8
2	*5320.00	95.0 AV			1.74 H	166	93.2	1.8
3	5355.10	54.3 PK	74.0	-19.7	1.74 H	166	52.3	2.0
4	5355.10	38.8 AV	54.0	-15.2	1.74 H	166	36.8	2.0
5	10640.00	47.5 PK	74.0	-26.5	1.05 H	277	35.7	11.8
6	10640.00	36.8 AV	54.0	-17.2	1.05 H	277	25.0	11.8
7	15960.00	58.7 PK	74.0	-15.3	1.25 H	338	47.1	11.6
8	15960.00	45.5 AV	54.0	-8.5	1.25 H	338	33.9	11.6
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5320.00	120.9 PK			1.50 V	282	119.1	1.8
2	*5320.00	108.7 AV			1.50 V	282	106.9	1.8
3	5353.20	58.8 PK	74.0	-15.2	1.50 V	282	56.9	1.9
4	5353.20	44.9 AV	54.0	-9.1	1.50 V	282	43.0	1.9
5	5356.60	68.3 PK	74.0	-5.7	1.50 V	282	66.3	2.0
6	5356.60	44.3 AV	54.0	-9.7	1.50 V	282	42.3	2.0
7	10640.00	49.2 PK	74.0	-24.8	1.98 V	183	37.4	11.8
8	10640.00	39.2 AV	54.0	-14.8	1.98 V	183	27.4	11.8
9	15960.00	57.1 PK	74.0	-16.9	1.45 V	275	45.5	11.6
10	15960.00	43.3 AV	54.0	-10.7	1.45 V	275	31.7	11.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 20MHz Preamble 802.11ax (RU52)	Channel	CH 100 : 5500 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5411.30	49.7 PK	74.0	-24.3	1.57 H	165	47.7	2.0
2	5411.30	37.6 AV	54.0	-16.4	1.57 H	165	35.6	2.0
3	5460.00	48.5 PK	74.0	-25.5	1.57 H	165	46.4	2.1
4	5460.00	38.2 AV	54.0	-15.8	1.57 H	165	36.1	2.1
5	#5469.90	52.8 PK	68.2	-15.4	1.57 H	165	50.6	2.2
6	*5500.00	105.8 PK			1.57 H	165	103.7	2.1
7	*5500.00	94.7 AV			1.57 H	165	92.6	2.1
8	11000.00	47.5 PK	74.0	-26.5	1.02 H	289	35.1	12.4
9	11000.00	37.2 AV	54.0	-16.8	1.02 H	289	24.8	12.4
10	#16500.00	59.3 PK	68.2	-8.9	1.35 H	336	45.6	13.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	59.5 PK	74.0	-14.5	1.52 V	279	57.4	2.1
2	5460.00	43.3 AV	54.0	-10.7	1.52 V	279	41.2	2.1
3	#5467.90	65.0 PK	68.2	-3.2	1.52 V	279	62.8	2.2
4	*5500.00	120.5 PK			1.52 V	279	118.4	2.1
5	*5500.00	108.9 AV			1.52 V	279	106.8	2.1
6	11000.00	48.8 PK	74.0	-25.2	2.03 V	210	36.4	12.4
7	11000.00	38.9 AV	54.0	-15.1	2.03 V	210	26.5	12.4
8	#16500.00	57.1 PK	68.2	-11.1	1.41 V	284	43.4	13.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU52)	Channel	CH 116 : 5580 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5580.00	106.2 PK			1.67 H	149	104.1	2.1
2	*5580.00	94.5 AV			1.67 H	149	92.4	2.1
3	11160.00	47.5 PK	74.0	-26.5	1.07 H	284	35.5	12.0
4	11160.00	37.1 AV	54.0	-16.9	1.07 H	284	25.1	12.0
5	#16740.00	59.1 PK	68.2	-9.1	1.30 H	320	43.8	15.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5580.00	120.4 PK			1.74 V	276	118.3	2.1
2	*5580.00	108.4 AV			1.74 V	276	106.3	2.1
3	11160.00	48.6 PK	74.0	-25.4	2.01 V	184	36.6	12.0
4	11160.00	38.8 AV	54.0	-15.2	2.01 V	184	26.8	12.0
5	#16740.00	56.7 PK	68.2	-11.5	1.42 V	303	41.4	15.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU52)	Channel	CH 140 : 5700 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5700.00	104.9 PK			1.73 H	173	102.6	2.3
2	*5700.00	92.8 AV			1.73 H	173	90.5	2.3
3	#5725.00	57.6 PK	68.2	-10.6	1.73 H	173	55.2	2.4
4	11400.00	47.0 PK	74.0	-27.0	1.03 H	280	34.5	12.5
5	11400.00	36.5 AV	54.0	-17.5	1.03 H	280	24.0	12.5
6	#17100.00	58.2 PK	68.2	-10.0	1.32 H	335	41.4	16.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5700.00	118.2 PK			1.49 V	276	115.9	2.3
2	*5700.00	107.1 AV			1.49 V	276	104.8	2.3
3	#5725.00	66.5 PK	68.2	-1.7	1.49 V	276	64.1	2.4
4	11400.00	49.1 PK	74.0	-24.9	2.03 V	189	36.6	12.5
5	11400.00	39.3 AV	54.0	-14.7	2.03 V	189	26.8	12.5
6	#17100.00	56.6 PK	68.2	-11.6	1.49 V	300	39.8	16.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU52)	Channel	CH 144 : 5720 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	51.4 PK	74.0	-22.6	1.74 H	156	49.3	2.1
2	5460.00	37.8 AV	54.0	-16.2	1.74 H	156	35.7	2.1
3	#5470.00	50.3 PK	68.2	-17.9	1.74 H	156	48.1	2.2
4	*5720.00	107.1 PK			1.74 H	156	104.7	2.4
5	*5720.00	95.1 AV			1.74 H	156	92.7	2.4
6	#5850.00	52.0 PK	68.2	-16.2	1.74 H	156	49.3	2.7
7	11440.00	47.3 PK	74.0	-26.7	1.04 H	273	34.9	12.4
8	11440.00	36.8 AV	54.0	-17.2	1.04 H	273	24.4	12.4
9	#17160.00	58.2 PK	68.2	-10.0	1.32 H	317	41.6	16.6
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	52.8 PK	74.0	-21.2	1.70 V	293	50.7	2.1
2	5460.00	38.8 AV	54.0	-15.2	1.70 V	293	36.7	2.1
3	#5470.00	54.0 PK	68.2	-14.2	1.70 V	293	51.8	2.2
4	*5720.00	120.4 PK			1.70 V	293	118.0	2.4
5	*5720.00	108.4 AV			1.70 V	293	106.0	2.4
6	#5850.00	52.5 PK	68.2	-15.7	1.70 V	293	49.8	2.7
7	11440.00	48.6 PK	74.0	-25.4	1.97 V	210	36.2	12.4
8	11440.00	38.7 AV	54.0	-15.3	1.97 V	210	26.3	12.4
9	#17160.00	57.0 PK	68.2	-11.2	1.40 V	278	40.4	16.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU52)	Channel	CH 149 : 5745 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5628.32	50.2 PK	68.2	-18.0	1.24 H	166	47.9	2.3
2	*5745.00	108.9 PK			1.24 H	166	106.5	2.4
3	*5745.00	97.9 AV			1.24 H	166	95.5	2.4
4	#6003.86	51.2 PK	68.2	-17.0	1.24 H	166	48.3	2.9
5	11490.00	47.1 PK	74.0	-26.9	1.01 H	261	34.5	12.6
6	11490.00	36.7 AV	54.0	-17.3	1.01 H	261	24.1	12.6
7	#17235.00	58.5 PK	68.2	-9.7	1.27 H	327	41.7	16.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5645.83	51.7 PK	68.2	-16.5	1.48 V	275	49.4	2.3
2	*5745.00	121.8 PK			1.48 V	275	119.4	2.4
3	*5745.00	111.6 AV			1.48 V	275	109.2	2.4
4	#6008.02	51.4 PK	68.2	-16.8	1.48 V	275	48.5	2.9
5	11490.00	49.2 PK	74.0	-24.8	2.06 V	190	36.6	12.6
6	11490.00	39.3 AV	54.0	-14.7	2.06 V	190	26.7	12.6
7	#17235.00	56.9 PK	68.2	-11.3	1.42 V	277	40.1	16.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU52)	Channel	CH 157 : 5785 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5592.62	51.2 PK	68.2	-17.0	1.28 H	169	49.1	2.1
2	*5785.00	106.6 PK			1.28 H	169	104.0	2.6
3	*5785.00	96.3 AV			1.28 H	169	93.7	2.6
4	#5985.36	50.7 PK	68.2	-17.5	1.28 H	169	47.8	2.9
5	11570.00	47.8 PK	74.0	-26.2	1.06 H	267	35.2	12.6
6	11570.00	37.3 AV	54.0	-16.7	1.06 H	267	24.7	12.6
7	#17355.00	60.7 PK	68.2	-7.5	1.36 H	321	43.0	17.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5568.39	51.9 PK	68.2	-16.3	1.54 V	275	49.8	2.1
2	*5785.00	121.2 PK			1.54 V	275	118.6	2.6
3	*5785.00	110.8 AV			1.54 V	275	108.2	2.6
4	#5983.44	51.1 PK	68.2	-17.1	1.54 V	275	48.2	2.9
5	11570.00	49.0 PK	74.0	-25.0	2.00 V	206	36.4	12.6
6	11570.00	39.1 AV	54.0	-14.9	2.00 V	206	26.5	12.6
7	#17355.00	58.2 PK	68.2	-10.0	1.47 V	274	40.5	17.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.