



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen,
Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053

Fax: +86 (0) 755 2671 0594

Email: ee.shenzhen@sgs.com

Report No.: SZEM170400351906

Page : 1 of 74

FCC SAR TEST REPORT

Application No: SZEM1704003519RG
Applicant: Saygus
Manufacturer: Saygus
Factory: Smart Gadgets (Shenzhen) , LTD
Product Name: Saygus smartphone V-Squared
Model No.(EUT): SG02
Trade Mark: Saygus
FCC ID: 2ANBZ-F10104215
Standards: FCC 47CFR §2.1093
Date of Receipt: 2017-07-14
Date of Test: 2017-07-15 to 2017-07-22
Date of Issue: 2017-11-01
Test conclusion: **PASS ***

* In the configuration tested, the EUT detailed in this report complied with the standards specified above.

Authorized Signature:

Derek Yang

Wireless Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only



REVISION HISTORY

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2017-11-01		Original



TEST SUMMARY

Frequency Band	Test position	Test mode	Max Report SAR (W/kg)	SAR limit (W/kg)	Verdict
GSM850	Head	GSM	<0.10	1.6	PASS
	Body-worn	GSM	<0.10	1.6	PASS
	Hotspot	GPRS 4TS	0.10	1.6	PASS
GSM1900	Head	GSM	<0.10	1.6	PASS
	Body-worn	GSM	0.16	1.6	PASS
	Hotspot	GPRS 2TS	1.45	1.6	PASS
WCDMA Band II	Head	RMC	<0.10	1.6	PASS
	Body-worn	RMC	0.12	1.6	PASS
	Hotspot	RMC	0.29	1.6	PASS
WCDMA Band IV	Head	RMC	<0.10	1.6	PASS
	Body-worn	RMC	0.14	1.6	PASS
	Hotspot	RMC	0.50	1.6	PASS
CDMA BC0	Head	QPSK	<0.10	1.6	PASS
	Body-worn	QPSK	<0.10	1.6	PASS
	Hotspot	QPSK	<0.10	1.6	PASS
CDMA BC1	Head	QPSK	<0.10	1.6	PASS
	Body-worn	QPSK	0.12	1.6	PASS
	Hotspot	QPSK	0.49	1.6	PASS
LTE Band 2	Head	QPSK	<0.10	1.6	PASS
	Body-worn	QPSK	0.20	1.6	PASS
	Hotspot	QPSK	0.74	1.6	PASS
LTE Band 4	Head	QPSK	0.11	1.6	PASS
	Body-worn	QPSK	0.22	1.6	PASS
	Hotspot	QPSK	0.79	1.6	PASS
LTE Band 12	Head	QPSK	<0.10	1.6	PASS
	Body-worn	QPSK	<0.10	1.6	PASS
	Hotspot	QPSK	0.10	1.6	PASS
WI-FI (5GHz)	Head	802.11a	0.52	1.6	PASS
	Body-worn	802.11a	<0.10	1.6	PASS
	Hotspot	802.11a	0.11	1.6	PASS
Maximum Simultaneous SAR for Head			0.63		
Maximum Simultaneous SAR for Body-worn			0.29		
Maximum Simultaneous SAR for Hotspot			1.54		



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM170400351906

Page: 4 of 74

Approved & Released by

Simon Ling

SAR Manager

Tested by

Evan Mi

SAR Engineer



CONTENTS

1	GENERAL INFORMATION.....	8
1.1	DETAILS OF CLIENT	8
1.2	TEST LOCATION	8
1.3	TEST FACILITY	9
1.4	GENERAL DESCRIPTION OF EUT	10
1.5	TEST SPECIFICATION	11
1.6	RF EXPOSURE LIMITS	11
2	SAR MEASUREMENTS SYSTEM CONFIGURATION	12
2.1	THE SAR MEASUREMENT SYSTEM	12
2.2	ISOTROPIC E-FIELD PROBE EX3DV4.....	13
2.3	DATA ACQUISITION ELECTRONICS (DAE).....	14
2.4	SAM TWIN PHANTOM	14
2.5	ELI PHANTOM.....	15
2.6	DEVICE HOLDER FOR TRANSMITTERS	16
2.7	MEASUREMENT PROCEDURE.....	17
2.7.1	Scanning procedure.....	17
2.7.2	Data Storage.....	19
2.7.3	Data Evaluation by SEMCAD.....	19
3	DESCRIPTION OF TEST POSITION	21
3.1	THE HEAD TEST POSITION	21
3.1.1	SAM Phantom Shape	21
3.1.2	EUT constructions	22
3.1.3	Definition of the “cheek” position.....	22
3.1.4	Definition of the “tilted” position.....	23
3.2	THE BODY TEST POSITION	24
3.2.1	Body-worn accessory exposure conditions.....	24
3.2.2	Wireless Router exposure conditions.....	25
4	SAR SYSTEM VERIFICATION PROCEDURE	26
4.1	TISSUE SIMULATE LIQUID.....	26
4.1.1	Recipes for Tissue Simulate Liquid	26
4.1.2	Measurement for Tissue Simulate Liquid	27
4.2	SAR SYSTEM VALIDATION.....	28
4.2.1	Justification for Extended SAR Dipole Calibrations	29
4.2.2	Summary System Validation Result(s).....	30



4.2.3	Detailed System Validation Results.....	30
5	TEST RESULTS AND MEASUREMENT DATA.....	31
5.1	3G SAR TEST REDUCTION PROCEDURE	31
5.2	OPERATION CONFIGURATIONS	31
5.2.1	GSM Test Configuration.....	31
5.2.2	WCDMA Test Configuration.....	32
5.2.3	CDMA Test Configuration	36
5.2.4	WiFi Test Configuration.....	37
5.2.5	LTE Test Configuration.....	40
5.2.6	DUT Antenna Locations	41
5.2.7	EUT side for SAR Testing.....	42
5.2.8	Stand-alone SAR test evaluation.....	43
5.3	MEASUREMENT OF RF CONDUCTED POWER.....	44
5.3.1	Conducted Power Of GSM.....	44
5.3.2	Conducted Power Of WCDMA.....	45
5.3.3	Conducted Power Of CDMA.....	46
5.3.4	Conducted Power Of LTE	47
5.3.5	Conducted Power Of WIFI and BT	53
5.4	MEASUREMENT OF SAR DATA	55
5.4.1	SAR Result Of GSM850.....	55
5.4.2	SAR Result Of GSM1900.....	56
5.4.3	SAR Result Of WCDMA Band 2	57
5.4.4	SAR Result Of WCDMA Band 4	58
5.4.5	SAR Result Of CDMA BC0.....	59
5.4.6	SAR Result Of CDMA BC1.....	60
5.4.7	SAR Result Of LTE Band 2.....	61
5.4.1	SAR Result Of LTE Band 4.....	62
5.4.2	SAR Result Of LTE Band 12	63
5.4.3	SAR Result Of 5GHz WIFI.....	64
5.5	MULTIPLE TRANSMITTER EVALUATION.....	65
5.5.1	Simultaneous SAR SAR test evaluation	65
5.5.2	Estimated SAR.....	65
6	EQUIPMENT LIST	71
7	MEASUREMENT UNCERTAINTY	72
8	CALIBRATION CERTIFICATE	73



9	PHOTOGRAPHS	73
	APPENDIX A: DETAILED SYSTEM VALIDATION RESULTS	74
	APPENDIX B: DETAILED TEST RESULTS.....	74
	APPENDIX C: CALIBRATION CERTIFICATE	74
	APPENDIX D: PHOTOGRAPHS.....	74



1 General Information

1.1 Details of Client

Applicant:	Saygus
Address:	10421 South Jordan Gateway, Suite 500, South Jordan, UT 84095
Manufacturer:	Saygus
Address:	10421 South Jordan Gateway, Suite 500, South Jordan, UT 84095
Factory:	Smart Gadgets (Shenzhen) , LTD
Address:	912 Building 1 A, Hezheng-Huiyi Cheng, Xinhua Road, Xixiang Baoan District, Shenzhen, China

1.2 Test Location

Company: SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch
Address: No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China
Post code: 518057
Telephone: +86 (0) 755 2601 2053
Fax: +86 (0) 755 2671 0594
E-mail: ee.shenzhen@sgs.com



1.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations: ↵

• **CNAS (No. CNAS L2929)** ↵

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC ↵
Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration
Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration
Laboratories) for the competence in the field of testing. ↵

• **A2LA (Certificate No. 3816.01)** ↵

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the
American Association for Laboratory Accreditation (A2LA). Certificate No. 3816.01. ↵

• **VCCI** ↵

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services
Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures
with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively. ↵

• **FCC –Designation Number: CN1178** ↵

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been
recognized as an accredited testing laboratory. ↵

Designation Number: CN1178. Test Firm Registration Number: 406779. ↵

• **Industry Canada (IC)** ↵

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards
Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and
Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1,
4620C-2, 4620C-3. ↵



1.4 General Description of EUT

Product Name:	Saygus smartphone V-Squared		
Model No.(EUT):	SG02		
Trade Mark:	V Squared		
Product Phase:	production unit		
Device Type :	portable device		
Exposure Category:	uncontrolled environment / general population		
FCC ID:	2ANBZ-F10104215		
SN:	aaaae4052		
Hardware Version:	SG02_V5.0		
Software Version:	Msm8974-userdebug 6.0.1 MMB29M herman.20170914.193102 test-keys		
Antenna Type:	Inner Antenna		
Device Operating Configurations :			
Modulation Mode:	GSM:GMSK, 8PSK;WCDMA: CDMA:1xRTT/1xEv-Do(Rev.0)/1xEv Do(Rev.A);LTE:QPSK,16QAM;WIFI: DSSS,OFDM;BT: GFSK, π/4DQPSK,8DPSK		
Device Class:	B		
GPRS Multi-slots Class:	12	EGPRS Multi-slots Class:	12
HSDPA UE Category:	14	HSUPA UE Category	6
Frequency Bands:	Band	Tx (MHz)	Rx (MHz)
	GSM850	824-849	869-894
	GSM1900	1850-1910	1930-1990
	CDMA BC0	824-849	869-894
	CDMA BC1	1850-1910	1930-1990
	WCDMA1700	1710-1755	2110- 2155
	WCDMA1900	1850-1910	1930-1990
	LTE Band 2	1850-1910	1930-1990
	LTE Band 4	1710-1755	2110- 2155
	LTE Band 12	699-716	729- 746
	WIFI(5GHz)	5150-5250	5150-5250
		5250-5350	5250-5350
5470-5725		5470-5725	
BT	2402-2480	2402-2480	
Battery Information:	Model: HPP553692AB		
	Rated capacity:3200mAh		
	Battery Type: Rechargeable Li-ion Battery		
	Manufacturer: Huizhou High power Technolgy Co., LTD		
Headset Information:	Model: ERS308		
	Manufacturer: Speaker Electronic Technolgy(HK) Co., LTD		



1.5 Test Specification

Identity	Document Title
FCC 47CFR §2.1093	Radiofrequency Radiation Exposure Evaluation: Portable Devices
IEEE Std C95.1 – 1991	IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz – 300 GHz.
IEEE 1528-2013	Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
KDB 941225 D01 3G SAR Procedures v03r01	3G SAR Measurement Procedures
KDB 941225 D05 SAR for LTE Devices v02r05	SAR EVALUATION CONSIDERATIONS FOR LTE DEVICES
KDB 248227 D01 802.11 Wi-Fi SAR v02r02	SAR GUIDANCE FOR IEEE 802.11 (Wi-Fi) TRANSMITTERS
KDB 941225 D06 Hotspot Mode SAR v02r01	SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities
KDB 648474 D04 Handset SAR v01r03	SAR Evaluation Considerations for Wireless Handsets
KDB447498 D01 General RF Exposure Guidance v06	Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies
KDB447498 D03 Supplement C Cross-Reference v01	OET Bulletin 65, Supplement C Cross-Reference
KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04	SAR Measurement Requirements for 100 MHz to 6 GHz
KDB 865664 D02 RF Exposure Reporting v01r02	RF Exposure Compliance Reporting and Documentation Considerations

1.6 RF exposure limits

Human Exposure	Uncontrolled Environment General Population	Controlled Environment Occupational
Spatial Peak SAR* (Brain*Trunk)	1.60 mW/g	8.00 mW/g
Spatial Average SAR** (Whole Body)	0.08 mW/g	0.40 mW/g
Spatial Peak SAR*** (Hands/Feet/Ankle/Wrist)	4.00 mW/g	20.00 mW/g

Notes:

* The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time

** The Spatial Average value of the SAR averaged over the whole body.

*** The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation.)

2 SAR Measurements System Configuration

2.1 The SAR Measurement System

This SAR Measurement System uses a Computer-controlled 3-D stepper motor system (SPEAG DASY5 professional system). A E-field probe is used to determine the internal electric fields. The SAR can be obtained from the equation $SAR = \sigma (|E|^2) / \rho$ where σ and ρ are the conductivity and mass density of the tissue-Simulate.


The DASY5 system for performing compliance tests consists of the following items:

A standard high precision 6-axis robot (Stabile RX family) with controller, teach pendant and software .An arm extension for accommodation the data acquisition electronics (DAE).

A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.

A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.


The Electro-optical converter (EOC) performs the conversion between optical and electrical of the signals for the digital communication to DAE and for the analog signal from the optical surface detection. The EOC is connected to the measurement server.




F-1. SAR Measurement System Configuration

- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- A probe alignment unit which improves the (absolute) accuracy of the probe positioning.
- A computer operating Windows 7.
- DASY5 software.
- Remote control with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
- The SAM twin phantom enabling testing left-hand, right-hand and Body Worn usage.
- The device holder for handheld mobile phones.
- Tissue simulating liquid mixed according to the given recipes.
- Validation dipole kits allowing to validating the proper functioning of the system.


2.2 Isotropic E-field Probe EX3DV4

	<p>Symmetrical design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)</p>
Calibration	ISO/IEC 17025 calibration service available.
Frequency	10 MHz to > 6 GHz Linearity: ± 0.2 dB (30 MHz to 6 GHz)
Directivity	± 0.3 dB in TSL (rotation around probe axis) ± 0.5 dB in TSL (rotation normal to probe axis)
Dynamic Range	10 μ W/g to > 100 mW/g Linearity: ± 0.2 dB (noise: typically < 1 μ W/g)
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm
Application	High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields); the only probe that enables compliance testing for frequencies up to 6 GHz with precision of better 30%.
Compatibility	DASY3, DASY4, DASY52 SAR and higher, EASY4/MRI

2.3 Data Acquisition Electronics (DAE)

Model	DAE3, DAE4	
Construction	Signal amplifier, multiplexer, A/D converter and control logic. Serial optical link for communication with DASY4/5 embedded system (fully remote controlled). Two step probe touch detector for mechanical surface detection and emergency robot stop.	
Measurement Range	-100 to +300 mV (16 bit resolution and two range settings: 4mV, 400mV)	
Input Offset Voltage	< 5µV (with auto zero)	
Input Bias Current	< 50 f A	
Dimensions	60 x 60 x 68 mm	


2.4 SAM Twin Phantom

Material	Vynlester, glass fiber reinforced (VE-GF)	
Liquid Compatibility	Compatible with all SPEAG tissue simulating liquids (incl. DGBE type)	
Shell Thickness	2 ± 0.2 mm (6 ± 0.2 mm at ear point)	
Dimensions (incl. Wooden Support)	Length: 1000 mm Width: 500 mm Height: adjustable feet	
Filling Volume	approx. 25 liters	
Wooden Support	SPEAG standard phantom table	

The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528 and IEC 62209-1. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by teaching three points with the robot.

Twin SAM V5.0 has the same shell geometry and is manufactured from the same material as Twin SAM V4.0, but has reinforced top structure.

2.5 ELI Phantom

Material	Vinylester, glass fiber reinforced (VE-GF)	
Liquid Compatibility	Compatible with all SPEAG tissue simulating liquids (incl. DGBE type)	
Shell Thickness	2.0 ± 0.2 mm (bottom plate)	
Dimensions	Major axis: 600 mm Minor axis: 400 mm	
Filling Volume	approx. 30 liters	
Wooden Support	SPEAG standard phantom table	

Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI is fully compatible with the IEC 62209-2 standard and all known tissue simulating liquids. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all SPEAG dosimetric probes and dipoles.

ELI V5.0 has the same shell geometry and is manufactured from the same material as ELI4, but has reinforced top structure.

2.6 Device Holder for Transmitters



F-2. Device Holder for Transmitters

- The DASY device holder is designed to cope with different positions given in the standard. It has two scales for the device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear reference points). The rotation centres for both scales are the ear reference point (ERP). Thus the device needs no repositioning when changing the angles.
- The DASY device holder has been made out of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon=3$ and loss tangent $\delta=0.02$. The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.



2.7 Measurement procedure

2.7.1 Scanning procedure

Step 1: Power reference measurement

The “reference” and “drift” measurements are located at the beginning and end of the batch process. They measure the field drift at one single point in the liquid over the complete procedure.

Step 2: Area scan

The SAR distribution at the exposed side of the head was measured at a distance of 4mm from the inner surface of the shell. The area covered the entire dimension of the head and the horizontal grid spacing was 15mm*15mm or 12mm*12mm or 10mm*10mm. Based on the area scan data, the area of the maximum absorption was determined by spline interpolation.

Step 3: Zoom scan

Around this point, a volume of 32mm*32mm*30mm ($f \leq 2\text{GHz}$), 30mm*30mm*30mm (f for 2-3GHz) and 24mm*24mm*22mm (f for 5-6GHz) was assessed by measuring 5x5x7 points ($f \leq 2\text{GHz}$), 7x7x7 points (f for 2-3GHz) and 7x7x12 points (f for 5-6GHz). On this basis of this data set, the spatial peak SAR value was evaluated with the following procedure:

The data at the surface was extrapolated, since the centre of the dipoles is 2.0mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.2mm. (This can be variable. Refer to the probe specification). The extrapolation was based on a least square algorithm. A polynomial of the fourth order was calculated through the points in z-axes. This polynomial was then used to evaluate the points between the surface and the probe tip. The maximum interpolated value was searched with a straight-forward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1g or 10g) were computed using the 3D-Spline interpolation algorithm. The volume was integrated with the trapezoidal algorithm. One thousand points were interpolated to calculate the average. All neighbouring volumes were evaluated until no neighboring volume with a higher average value was found.

The area and zoom scan resolutions specified in the table below must be applied to the SAR measurements. Probe boundary effect error compensation is required for measurements with the probe tip closer than half a probe tip diameter to the phantom surface. Both the probe tip diameter and sensor offset distance must satisfy measurement protocols; to ensure probe boundary effect errors are minimized and the higher fields closest to the phantom surface can be correctly measured and extrapolated to the phantom surface for computing 1-g SAR. Tolerances of the post-processing algorithms must be verified by the test laboratory for the scan resolutions used in the SAR measurements, according to the reference distribution functions specified in IEEE Std. 1528-2013.



			≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface			5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location			$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: Δx_{Area} , Δy_{Area}			≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
			When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be \leq the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: Δx_{Zoom} , Δy_{Zoom}			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{Zoom}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{Zoom}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{Zoom}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{Zoom}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.				
* When zoom scan is required and the <i>reported</i> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

Step 4: Power reference measurement (drift)

The Power Drift Measurement job measures the field at the same location as the most recent power reference measurement job within the same procedure, and with the same settings. The indicated drift is mainly the variation of the DUT's output power and should vary max. $\pm 5\%$



2.7.2 Data Storage

The DASY software stores the acquired data from the data acquisition electronics as raw data (in microvolt readings from the probe sensors), together with all necessary software parameters for the data evaluation (probe calibration data, liquid parameters and device frequency and modulation data) in measurement files with the extension ".DAE3". The software evaluates the desired unit and format for output each time the data is visualized or exported. This allows verification of the complete software setup even after the measurement and allows correction of incorrect parameter settings. For example, if a measurement has been performed with a wrong crest factor parameter in the device setup, the parameter can be corrected afterwards and the data can be re-evaluated. The measured data can be visualized or exported in different units or formats, depending on the selected probe type ([V/m], [A/m], [°C], [m W/g], [m W/cm²], [dBrel], etc.). Some of these units are not available in certain situations or show meaningless results, e.g., a SAR output in a lossless media will always be zero. Raw data can also be exported to perform the evaluation with other software packages.

2.7.3 Data Evaluation by SEMCAD

The SEMCAD software automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

Probe parameters:	- Sensitivity	Normi, ai0, ai1, ai2
	- Conversion factor	ConvFi
	- Diode compression point	Dcpi
Device parameters:	- Frequency	f
	- Crest factor	cf
Media parameters:	- Conductivity	ε
	- Density	ρ

These parameters must be set correctly in the software. They can be found in the component documents or they can be imported into the software from the configuration files issued for the DASY components. In the direct measuring mode of the multimeter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics.

If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power.

The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot cf / dcp_i$$

With V_i = compensated signal of channel i (i = x, y, z)

U_i = input signal of channel i (i = x, y, z)

cf = crest factor of exciting field (DASY parameter)

dcp i = diode compression point (DASY parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

E-field probes:

$$E_i = (V_i / Norm_i \cdot ConvF)^{1/2}$$



H-field probes:

$$H_i = (V_i)^{1/2} \cdot (a_{i0} + a_{i1}f + a_{i2}f^2) / f$$

With V_i = compensated signal of channel i (i = x, y, z)

Normi = sensor sensitivity of channel i (i = x, y, z)
 [mV/(V/m)²] for E-field Probes

ConvF = sensitivity enhancement in solution

a_{ij} = sensor sensitivity factors for H-field probes

f = carrier frequency [GHz]

E_i = electric field strength of channel i in V/m

H_i = magnetic field strength of channel i in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = (E_x^2 + E_y^2 + E_z^2)^{1/2}$$

The primary field data are used to calculate the derived field units.

$$SAR = (E_{tot}^2 \cdot \sigma) / (\epsilon \cdot 1000)$$

with SAR = local specific absorption rate in mW/g

E_{tot} = total field strength in V/m

σ = conductivity in [mho/m] or [Siemens/m]

ε = equivalent tissue density in g/cm³

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid. The power flow density is calculated assuming the excitation field to be a free space field.

$$P_{pwe} = E_{tot}^2 / 3770 \text{ or } P_{pwe} = H_{tot}^2 \cdot 37.7$$

with P_{pwe} = equivalent power density of a plane wave in mW/cm²

E_{tot} = total electric field strength in V/m

H_{tot} = total magnetic field strength in A/m

3 Description of Test Position

3.1 The Head Test Position

3.1.1 SAM Phantom Shape




F-3. Front, back, and side views of SAM (model for the phantom shell). Full-head model is for illustration purposes only—procedures in this recommended practice are intended primarily for the phantom setup.


Note: The centre strip including the nose region has a different thickness tolerance.



F-4. Sagittally bisected phantom with extended perimeter (shown placed on its side as used for SAR measurements)




F-5. Close-up side view of phantom, showing the ear region, N-F and B-M lines, and seven cross-sectional plane locations




F-6. Side view of the phantom showing relevant markings and seven cross-sectional plane locations

3.1.2 EUT constructions



F-7. Handset vertical and horizontal reference lines-"fixed case"




F-8. Handset vertical and horizontal reference lines-"clam-shell case"

3.1.3 Definition of the "cheek" position


- Position the device with the vertical centre line of the body of the device and the horizontal line crossing the centre of the ear piece in a plane parallel to the sagittal plane of the phantom ("initial position"). While maintaining the device in this plane, align the vertical centre line with the reference plane containing the three ear and mouth reference points (M, RE and LE) and align the centre of the ear piece with the line RE-LE.
- Translate the mobile phone box towards the phantom with the ear piece aligned with the line LE-RE until telephone touches the ear. While maintaining the device in the reference plane and maintaining the phone contact with the ear, move the bottom of the box until any point on the front side is in contact with the cheek of the phantom or until contact with the ear is lost.

3.1.4 Definition of the “tilted” position

- Position the device in the “cheek” position described above;
- While maintaining the device in the reference plane described above and pivoting against the ear, move it outward away from the mouth by an angle of 15 degrees or until contact with the ear is lost.



F-9. Definition of the reference lines and points, on the phone and on the phantom and initial position



F-10. “Cheek” and “tilt” positions of the mobile phone on the left side

3.2 The Body Test Position


3.2.1 Body-worn accessory exposure conditions

Body-worn operating configurations should be tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in normal use configurations.

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration. Per FCC KDB Publication 648474 D04, Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB Publication 447498 D01 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is $> 1.2 \text{ W/kg}$, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.

Accessories for Body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are tested with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.

Body-worn accessories may not always be supplied or available as options for some devices intended to be authorized for body-worn use. In this case, a test configuration with a separation distance between the back of the device and the flat phantom is used. Test position spacing was documented. Transmitters that are designed to operate in front of a person's face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom in head fluid. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters, SAR compliance is tested with the accessories, including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.



F-11. Test positions for body-worn devices



3.2.2 Wireless Router exposure conditions

Some battery-operated handsets have the capability to transmit and receive user data through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06 where SAR test considerations for handsets ($L \times W \geq 9 \text{ cm} \times 5 \text{ cm}$) are based on a composite test separation distance of 10 mm from the front, back and edges of the device containing transmitting antennas within 2.5 cm of their edges, determined from general mixed use conditions for this type of devices. For devices with form factors smaller than 9 cm x 5 cm, a test separation distance of 5 mm is required.



4 SAR System Verification Procedure

4.1 Tissue Simulate Liquid

4.1.1 Recipes for Tissue Simulate Liquid

The following tables give the recipes for tissue simulating liquids to be used in different frequency bands:

Ingredients (% by weight)	Frequency (MHz)							
	450		835		1800-2000		2300-2700	
Tissue Type	Head	Body	Head	Body	Head	Body	Head	Body
Water	38.56	51.16	40.30	50.75	55.24	70.17	55.00	68.53
Salt (NaCl)	3.95	1.49	1.38	0.94	0.31	0.39	0.2	0.1
Sucrose	56.32	46.78	57.90	48.21	0	0	0	0
HEC	0.98	0.52	0.24	0	0	0	0	0
Bactericide	0.19	0.05	0.18	0.10	0	0	0	0
Tween	0	0	0	0	44.45	29.44	44.80	31.37
Salt: 99% Pure Sodium Chloride Water: De-ionized, 16 MΩ ⁺ resistivity Tween: Polyoxyethylene (20) sorbitan monolaurate								
Sucrose: 98% Pure Sucrose HEC: Hydroxyethyl Cellulose								
HSL5GHz is composed of the following ingredients: Water: 50-65% Mineral oil: 10-30% Emulsifiers: 8-25% Sodium salt: 0-1.5%								
MSL5GHz is composed of the following ingredients: Water: 64-78% Mineral oil: 11-18% Emulsifiers: 9-15% Sodium salt: 2-3%								

Table 1 : Recipe of Tissue Simulate Liquid



4.1.2 Measurement for Tissue Simulate Liquid


The dielectric properties for this Tissue Simulate Liquids were measured by using the Agilent Model 85070E Dielectric Probe in conjunction with Agilent E5071C Network Analyzer (300 KHz-8500 MHz). The Conductivity (σ) and Permittivity (ρ) are listed in Table 1. For the SAR measurement given in this report. The temperature variation of the Tissue Simulate Liquids was $22 \pm 2^\circ\text{C}$.

Measurement for Tissue Simulate Liquid							
Tissue Type	Measured Frequency (MHz)	Target Tissue ($\pm 5\%$)		Measured Tissue		Liquid Temp.	Measured Date
		ϵ_r	$\sigma(\text{S/m})$	ϵ_r	$\sigma(\text{S/m})$	($^\circ\text{C}$)	
750 Head	750	41.9 (39.81~44)	0.89 (0.85~0.94)	41.649	0.895	22.1	2017/7/22
750 Body	750	55.5 (52.73~58.28)	0.96 (0.91~1.00)	56.463	0.972	22.1	2017/7/20
835 Head	835	41.5 (39.43~43.58)	0.90 (0.86~0.95)	42.04	0.909	22.1	2017/7/22
835 Body	835	55.2 (52.44~57.96)	0.97 (0.92~1.02)	53.807	0.985	22.1	2017/7/16
1750 Head	1750	40.1 (38.10~42.11)	1.37 (1.30~1.44)	40.757	1.332	22.2	2017/7/21
1750 Body	1750	53.4 (50.73~56.07)	1.49 (1.42~1.56)	53.088	1.537	22.2	2017/7/15
1900 Head	1900	40.0 (38.00~42.00)	1.40 (1.33~1.47)	40.58	1.373	22.3	2017/7/18
1900 Body	1900	53.3 (50.64~55.97)	1.52 (1.44~1.60)	53.234	1.51	22.3	2017/7/17
5250 Head	5250	35.9 (34.11~37.70)	4.71 (4.47~4.95)	35.566	4.629	22.2	2017/7/21
5250 Body	5250	48.9 (46.46~51.35)	5.36 (5.09~5.63)	49.767	5.344	22.2	2017/7/19
5600 Head	5600	35.5 (33.73~37.28)	5.07 (4.82~5.32)	34.894	5.096	22.2	2017/7/21
5600 Body	5600	48.5 (46.08~50.93)	5.77 (5.48~6.06)	48.938	5.72	22.2	2017/7/19

Table 2 : Measurement result of Tissue electric parameters

4.2 SAR System Validation

The microwave circuit arrangement for system verification is sketched in bellow figure. The daily system accuracy verification occurs within the flat section of the SAM phantom. A SAR measurement was performed to see if the measured SAR was within $\pm 10\%$ from the target SAR values. The tests were conducted on the same days as the measurement of the EUT. The obtained results from the system accuracy verification are displayed in the table 5 (A power level of 250mw was input to the dipole antenna). During the tests, the ambient temperature of the laboratory was in the range $22\pm 2^{\circ}\text{C}$, the relative humidity was in the range 60% and the liquid depth above the ear reference points was above 15 cm in all the cases. It is seen that the system is operating within its specification, as the results are within acceptable tolerance of the reference values.



F-12. the microwave circuit arrangement used for SAR system verification



4.2.1 Justification for Extended SAR Dipole Calibrations

1) Referring to KDB865664 D01 requirements for dipole calibration, instead of the typical annual calibration recommended by measurement standards, longer calibration intervals of up to three years may be considered when it is demonstrated that the SAR target, impedance and return loss of a dipole have remain stable according to the following requirements. Each measured dipole is expected to evaluate with the following criteria at least on annual interval in Appendix C.

- a) There is no physical damage on the dipole;
- b) System check with specific dipole is within 10% of calibrated value;
- c) Return-loss is within 10% of calibrated measurement;
- d) Impedance is within 5Ω from the previous measurement.

2) Network analyzer probe calibration against air, distilled water and a shorting block performed before measuring liquid parameters.



4.2.2 Summary System Validation Result(s)

Validation Kit		Measured SAR 250mW	Measured SAR (normalized to 1w)	Target SAR (normalized to 1w) (±10%)	Liquid Temp. (°C)	Measured Date
		1g (W/kg)	1g (W/kg)	1-g(W/kg)		
D750V2	Head	2.14	8.56	8.17 (7.35~8.99)	22.1	2017/7/22
	Body	2.26	9.04	8.57 (7.71~9.43)	22.1	2017/7/20
D835V2	Head	2.35	9.4	9.59 (8.63~10.55)	22.1	2017/7/22
	Body	2.27	9.08	9.65 (8.69~10.62)	22.1	2017/7/16
D1750V2	Head	8.91	35.64	36.7 (33.03~40.37)	22.2	2017/7/21
	Body	10.1	40.4	37 (33.30~40.70)	22.2	2017/7/15
D1900V2	Head	9.45	37.8	40.7 (36.63~44.77)	22.3	2017/7/18
	Body	10.9	43.6	41.6 (37.44~45.76)	22.3	2017/7/17
Validation Kit		Measured SAR 100mW	Measured SAR (normalized to 1w)	Target SAR (normalized to 1w) (±10%)	Liquid Temp. (°C)	Measured Date
		1g (W/kg)	1g (W/kg)	1-g(W/kg)		
D5GHzV2	Head(5.25GHz)	6.96	69.6	76.6 (68.94~84.26)	22.2	2017/7/21
	Body(5.25GHz)	7.97	79.7	75.6 (68.04~83.16)	22.2	2017/7/19
	Head(5.6GHz)	7.65	76.5	80.4 (72.36~88.44)	22.2	2017/7/21
	Body(5.6GHz)	8.29	82.9	81.1 (72.99~89.21)	22.2	2017/7/19

Table 3 : SAR System Validation Result

4.2.3 Detailed System Validation Results

Please see the Appendix A



5 Test results and Measurement Data

5.1 3G SAR Test Reduction Procedure

According to KDB 941225D01 v03, in the following procedures, the mode tested for SAR is referred to as the primary mode. The equivalent modes considered for SAR test reduction are denoted as secondary modes. Both primary and secondary modes must be in the same frequency band. When the maximum output power and tune-up tolerance specified for production units in a secondary mode is $\leq \frac{1}{4}$ dB higher than the primary mode or when the highest reported SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for the secondary mode. This is referred to as the 3G SAR test reduction procedure in the following SAR test guidance, where the primary mode is identified in the applicable wireless mode test procedures and the secondary mode is wireless mode being considered for SAR test reduction by that procedure. When the 3G SAR test reduction procedure is not satisfied, it is identified as “otherwise” in the applicable procedures; SAR measurement is required for the secondary mode.

5.2 Operation Configurations

5.2.1 GSM Test Configuration

SAR tests for GSM 850 and GSM 1900, a communication link is set up with a base station by air link. Using CMU200 the power lever is set to “5” and “0” in SAR of GSM 850 and GSM 1900. The tests in the band of GSM 850 and GSM 1900 are performed in the mode of GPRS/EGPRS function. Since the GPRS class is 12 for this EUT, it has at most 4 timeslots in uplink and at most 4 timeslots in downlink, the maximum total timeslot is 5. The EGPRS class is 12 for this EUT, it has at most 4 timeslots in uplink, and at most 4 timeslots in downlink, the maximum total timeslot is 5.

SAR test reduction for GPRS and EDGE modes is determined by the source-based time-averaged output power specified for production units, including tune-up tolerance. The data mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested.

When SAR tests for EGPRS mode is necessary, GMSK modulation should be used to minimize SAR measurement error due to higher peak-to-average power (PAR) ratios inherent in 8-PSK.

The 3G SAR test reduction procedure is applied to 8-PSK EDGE with GMSK GPRS/EDGE as the primary mode



5.2.2 WCDMA Test Configuration

1) . Output Power Verification

Maximum output power is verified on the high, middle and low channels according to procedures described in section 5.2 of 3GPP TS 34.121, using the appropriate RMC or AMR with TPC (transmit power control) set to all "1's" for WCDMA/HSDPA or by applying the required inner loop power control procedures to maintain maximum output power while HSUPA is active. Results for all applicable physical channel configurations (DPCCH, DPDCHn and spreading codes, HSDPA, HSPA) are required in the SAR report. All configurations that are not supported by the handset or cannot be measured due to technical or equipment limitations must be clearly identified.

2) . Head SAR

SAR for next to the ear head exposure is measured using a 12.2 kbps RMC with TPC bits configured to all "1's". The 3G SAR test reduction procedure is applied to AMR configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for 12.2 kbps AMR in 3.4 kbps SRB (signaling radio bearer) using the highest reported SAR configuration in 12.2 kbps RMC for head exposure

3) . Body SAR

SAR for body configurations is measured using a 12.2 kbps RMC with TPC bits configured to all "1's". The 3G SAR test reduction procedure is applied to other spreading codes and multiple DPDCHn configurations supported by the handset with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured using an applicable RMC configuration with the corresponding spreading code or DPDCHn, for the highest reported body-worn accessory exposure SAR configuration in 12.2 kbps RMC. When more than 2 DPDCHn are supported by the handset, it may be necessary to configure additional DPDCHn using FTM (Factory Test Mode) or other chipset based test approaches with parameters similar to those used in 384 kbps and 768 kbps RMC.

4) . HSDPA / HSUPA / DC-HSDPA

According to KDB 941225 D01v03, RMC 12.2kbps setting is used to evaluate SAR. If the maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA / DC-HSDPA is $\leq \frac{1}{4}$ dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA / DC-HSDPA to RMC12.2Kbps and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA

a) HSDPA

HSDPA is configured according to the applicable UE category of a test device. The number of HS-DSCH/HS-PDSCHs, HARQ processes, minimum inter-TTI interval, transport block sizes and RV coding sequence are defined by the H-set. To maintain a consistent test configuration and stable transmission conditions, QPSK is used in the H-set for SAR testing. HS-DPCCH should be configured with a CQI feedback cycle of 4 ms and a CQI repetition factor of 2 to maintain a constant rate of active CQI slots. DPCCH and DPDCH gain factors(β_c , β_d), and HS-DPCCH power offset parameters (Δ_{ACK} , Δ_{NACK} , Δ_{CQI}) are set according to values indicated in the following table. The CQI value is determined by the UE category, transport block size, number of HS-PDSCHs and modulation used in the H-set.



Sub-test	β_c	Bd	$\beta_d(\text{SF})$	β_c/β_d	β_{hs}	CM(dB)	MPR (dB)
1	2/15	15/15	64	2/15	4/15	0.0	0
2	12/15(3)	15/15(3)	64	12/15(3)	24/15	1.0	0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5

Note1: ΔACK , ΔNACK and $\Delta\text{CQI} = 8$ $A_{hs} = \beta_{hs}/\beta_c = 30/15$ $\beta_{hs} = 30/15 * \beta_c$

Note2: For the HS-DPCCH power mask requirement test in clause 5.2C, 5.7A, and the Error Vector Magnitude (EVM) with HS-DPCCH test in clause 5.13.1.A, and HSDPA EVM with phase discontinuity in clause 5.13.1AA, ΔACK and $\Delta\text{NACK} = 8$ ($A_{hs} = 30/15$) with $\beta_{hs} = 30/15 * \beta_c$, and $\Delta\text{CQI} =$

7 ($A_{hs} = 24/15$) with $\beta_{hs} = 24/15 * \beta_c$.

Note3: CM=1 for $\beta_c/\beta_d = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.

The measurements were performed with a Fixed Reference Channel (FRC) and H-Set 1 QPSK.

Parameter	Value
Nominal average inf. bit rate	534 kbit/s
Inter-TTI Distance	3 TTI"s
Number of HARQ Processes	2 Processes
Information Bit Payload	3202 Bits
MAC-d PDU size	336 Bits
Number Code Blocks	1 Block
Binary Channel Bits Per TTI	4800 Bits
Total Available SMLs in UE	19200 SMLs
Number of SMLs per HARQ Process	9600 SMLs
Coding Rate	0.67
Number of Physical Channel Codes	5

Table 4 : settings of required H-Set 1 QPSK acc. to 3GPP 34.121



HS-DSCH Category	Maximum HS-DSCH Codes Received	Minimum Inter-TTI Interval	MaximumH S-DSCH Transport BlockBits/HS-DSCH TTI	Total Soft Channel Bits
1	5	3	7298	19200
2	5	3	7298	28800
3	5	2	7298	28800
4	5	2	7298	38400
5	5	1	7298	57600
6	5	1	7298	67200
7	10	1	14411	115200
8	10	1	14411	134400
9	15	1	25251	172800
10	15	1	27952	172800
11	5	2	3630	14400
12	5	1	3630	28800
13	15	1	34800	259200
14	15	1	42196	259200
15	15	1	23370	345600
16	15	1	27952	345600

Table 5 : HSDPA UE category

b) HSUPA

Due to inner loop power control requirements in HSUPA, a commercial communication test set should be used for the output power and SAR tests. The 12.2 kbps RMC, FRC H-set 1 and E-DCH configurations for HSUPA should be configured according to the values indicated below as well as other applicable procedures described in the „WCDMA Handset“ and „Release 5 HSUPA Data Device“ sections of 3G device.



Sub-test ^o	β_e ^o	β_d ^o	β_d (SF) ^o	β_e/β_d ^o	$\beta_{hs}(1)$ ^o	β_{est} ^o	β_{ed} ^o	β_e (SF) ^o	β_{ed} (code) ^o	CM ⁽²⁾ (dB) ^o	MP R ^o (dB) ^o	AG ⁽⁴⁾ Inde x ^o	E- TFC I ^o
1 ^o	11/15 ⁽³⁾ ^o	15/15 ⁽³⁾ ^o	64 ^o	11/15 ⁽³⁾ ^o	22/15 ^o	209/225 ^o	1039/225 ^o	4 ^o	1 ^o	1.0 ^o	0.0 ^o	20 ^o	75 ^o
2 ^o	6/15 ^o	15/15 ^o	64 ^o	6/15 ^o	12/15 ^o	12/15 ^o	94/75 ^o	4 ^o	1 ^o	3.0 ^o	2.0 ^o	12 ^o	67 ^o
3 ^o	15/15 ^o	9/15 ^o	64 ^o	15/9 ^o	30/15 ^o	30/15 ^o	$\beta_{ad1}:47/15$ $\beta_{ed2}:47/15$	4 ^o	2 ^o	2.0 ^o	1.0 ^o	15 ^o	92 ^o
4 ^o	2/15 ^o	15/15 ^o	64 ^o	2/15 ^o	4/15 ^o	2/15 ^o	56/75 ^o	4 ^o	1 ^o	3.0 ^o	2.0 ^o	17 ^o	71 ^o
5 ^o	15/15 ⁽⁴⁾ ^o	15/15 ⁽⁴⁾ ^o	64 ^o	15/15 ⁽⁴⁾ ^o	30/15 ^o	24/15 ^o	134/15 ^o	4 ^o	1 ^o	1.0 ^o	0.0 ^o	21 ^o	81 ^o
Note 1: ΔACK , $\Delta NACK$ and $\Delta CQI=8$ $A_{hs} = \beta_{hs}/\beta_e = 30/15$ $\beta_{hs} = 30/15 * \beta_e$ Note 2: CM = 1 for $\beta_e/\beta_d = 12/15$, $\beta_{hs}/\beta_e = 24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference ^o Note 3 : For subtest 1 the β_e/β_d ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_e = 10/15$ and $\beta_d = 15/15$ ^o Note 4 : For subtest 5 the β_e/β_d ratio of 15/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_e = 14/15$ and $\beta_d = 15/15$ ^o Note 5 : Testing UE using E-DPDCH Physical Layer category 1 Sub-test 3 is not required according to TS 25.306 Table 5.1g ^o Note 6: β_{ad} can not be set directly; it is set by Absolute Grant Value. ^o													

Table 6 : Subtests for UMTS Release 6 HSUPA

UE E-DCH Category	Maximum E-DCH Codes Transmitted	Number of HARQ Processes	E-DCH TTI(ms)	Minimum Spreading Factor	Maximum E-DCH Transport Block Bits	Max Rate (Mbps)
1	1	4	10	4	7110	0.7296
2	2	8	2	4	2798	1.4592
	2	4	10	4	14484	
3	2	4	10	4	14484	1.4592
4	2	8	2	2	5772	2.9185
	2	4	10	2	20000	2.00
5	2	4	10	2	20000	2.00
6 (No DPDCH)	4	8	10	2SF2&2SF	11484	5.76
	4	4	2	4	20000	2.00
7 (No DPDCH)	4	8	2	2SF2&2SF	22996	?
	4	4	10	4	20000	?
NOTE: When 4 codes are transmitted in parallel, two codes shall be transmitted with SF2 and two with SF4. UE categories 1 to 6 support QPSK only. UE category 7 supports QPSK and 16QAM. (TS25.306-7.3.0).						

Table 7 : HSUPA UE category



5.2.3 CDMA Test Configuration

1) 1x RTT Handsets

The following procedures apply to CDMA 2000 Release 0 and Release A single carrier (1x RTT) handsets operating with Mobile Protocol Revision 6 or 7 (MOB_P_REV 6 or 7). The default test configuration is to measure SAR in RC3 with an established radio link between the handset and a communication test set. SAR in RC1 is selectively confirmed according to the 3G SAR test reduction procedure with RC3 as the primary mode. The forward and reverse links are configured with the same RC for SAR measurement. Maximum output power is verified by applying the procedures defined in 3GPP2 C.S0011 and TIA-98-E. SAR must be measured according to these maximum output conditions and requirements in KDB Publication 447498 D01.

2) Output Power Verification

Maximum output power is verified on the high, middle and low channels according to procedures in section 4.4.5.2 of 3GPP2 C.S0011/TIA-98-E. Results for at least steps 3, 4 and 10 of the power measurement procedures are required in the SAR report. Steps 3 and 4 are measured using Loopback Service Option SO55 with power control bits in "All Up" condition. TDSO/SO32 may be used instead of SO55 for step 4. Step 10 is measured using TDSO/SO32 with power control bits in the "Bits Hold" condition (i.e. alternative Up/Down Bits). All power measurements defined in C.S0011/TIA-98-E that are inapplicable to the handset or cannot be measured due to technical or equipment limitations must be clearly identified in the test report.

3) Head SAR

SAR for next to the ear head exposure is measured in RC3 with the handset configured to transmit at full rate in SO55. The 3G SAR test reduction procedure is applied to RC1 with RC3 as the primary mode; otherwise, SAR is required for the channel with maximum measured output in RC1 using the head exposure configuration that results in the highest reported SAR in RC3.

4) Body-Worn Accessory SAR

Body-worn accessory SAR is measured in RC3 with the handset configured in TDSO/SO32 to transmit at full rate on FCH only with all other code channels disabled. The body-worn accessory procedures in KDB Publication 447498 D01 are applied. The 3G SAR test reduction procedure is applied to the multiple code channel configuration (FCH+SCHn), with FCH only as the primary mode. Otherwise, SAR is required for multiple code channel configuration (FCH + SCHn), with FCH at full rate and SCH0 enabled at 9600 bps, using the highest reported SAR configuration for FCH only. When multiple code channels are enabled, the transmitter output can shift by more than 0.5 dB and may lead to higher SAR drifts and SCH dropouts.

The 3G SAR test reduction procedure is applied to body-worn accessory SAR in RC1 with RC3 as the primary mode. Otherwise, SAR is required for RC1, with SO55 and full rate, using the highest reported SAR configuration for body-worn accessory exposure in RC3.

5) Handsets with built-in Ev-Do

For handsets with Ev-Do capabilities, the 3G SAR test reduction procedure is applied to Ev-Do Rev. 0 with 1x RTT RC3 as the primary mode to determine body-worn accessory test requirements. Otherwise, body-worn accessory SAR is required for Rev. 0, at 153.6 kbps, using the highest reported SAR configuration for body-worn accessory exposure in RC3.

The 3G SAR test reduction procedure is applied separately to Rev. A and Rev. B, with Rev. 0 as the primary mode to determine body-worn accessory SAR test requirements. When SAR is not required for Rev. 0, the 3G SAR test reduction is applied with 1x RTT RC3 as the primary mode. Otherwise, SAR is required for Rev. A or Rev. B, with a Reverse Data Channel payload size of 4096 bits and a Termination Target of 16 slots defined for Subtype 2 and 3 Physical Layer configurations, using the highest reported SAR configuration for body-worn accessory exposure in Rev. 0 or RC3, as appropriate.

A Forward Traffic Channel data rate corresponding to the 2-slot version of 307.2 kbps with ACK Channel transmitting in all slots is configured in the downlink for Rev. 0, Rev. A and Rev. B.




5.2.4 WiFi Test Configuration

A Wi-Fi device must be configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools for SAR measurement.

Duty cycle for 5GHz:

$1.365/1.56=87.5\%$



Date: 20 JUL 2017 00:06:16



5.2.4.1 Initial Test Position SAR Test Reduction Procedure

DSSS and OFDM configurations are considered separately according to the required SAR procedures. SAR is measured in the initial test position using the 802.11 transmission mode configuration required by the DSSS procedure or initial test configuration and subsequent test configuration(s) according to the OFDM procedures. The initial test position procedure is described in the following:

- 1) . When the reported SAR of the initial test position is ≤ 0.4 W/kg, further SAR measurement is not required for the other (remaining) test positions in that exposure configuration and 802.11 transmission mode combinations within the frequency band or aggregated band. SAR is also not required for that exposure configuration in the subsequent test configuration(s).
- 2) . When the reported SAR of the initial test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position using subsequent highest extrapolated or estimated 1-g SAR conditions determined by area scans or next closest/smallest test separation distance and maximum RF coupling test positions based on manufacturer justification, on the highest maximum output power channel, until the reported SAR is ≤ 0.8 W/kg or all required test positions (left, right, touch, tilt or subsequent surfaces and edges) are tested.
- 3) . For all positions/configurations tested using the initial test position and subsequent test positions, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested. a) Additional power measurements may be required for this step, which should be limited to those necessary for identifying the subsequent highest output power channels.

5.2.4.2 Initial Test Configuration Procedures

An initial test configuration is determined for OFDM transmission modes according to the channel bandwidth, modulation and data rate combination(s) with the highest maximum output power specified for production units in each standalone and aggregated frequency band. SAR is measured using the highest measured maximum output power channel. For configurations with the same specified or measured maximum output power, additional transmission mode and test channel selection procedures are required. SAR test reduction for subsequent highest output test channels is determined according to *reported* SAR of the initial test configuration. For next to the ear, hotspot mode and UMC mini-tablet exposure configurations where multiple test positions are required, the initial test position procedure is applied to minimize the number of test positions required for SAR measurement using the initial test configuration transmission mode. For fixed exposure conditions that do not have multiple SAR test positions, SAR is measured in the transmission mode determined by the initial test configuration.

When the *reported* SAR of the initial test configuration is > 0.8 W/kg, SAR measurement is required for subsequent next highest measured output power channel(s) in the initial test configuration until *reported* SAR is ≤ 1.2 W/kg or all required channels are tested.

5.2.4.3 Subsequent Test Configuration Procedures

SAR measurement requirements for the remaining 802.11 transmission mode configurations that have not been tested in the initial test configuration are determined separately for each standalone and aggregated frequency band, in each exposure condition, according to the maximum output power specified for production units. The initial test position procedure is applied to next to the ear, UMPC mini-tablet and hotspot mode configurations. When the same maximum output power is specified for multiple transmission modes, additional power measurements may be required to determine if SAR measurements are required for subsequent highest output power channels in a subsequent test configuration. The subsequent test configuration and SAR measurement procedures are described in the following.

- 1) . When SAR test exclusion provisions of KDB Publication 447498 are applicable and SAR measurement is not required for the initial test configuration, SAR is also not required for the next highest maximum output power transmission mode subsequent test configuration(s) in that frequency band or aggregated band and exposure configuration.
- 2) . When the highest *reported* SAR for the initial test configuration (when applicable, include subsequent highest output channels), according to the initial test position or fixed exposure position requirements, is adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for that subsequent test configuration.
- 3) . The number of channels in the initial test configuration and subsequent test configuration can be



different due to differences in channel bandwidth. When SAR measurement is required for a subsequent test configuration and the channel bandwidth is smaller than that in the initial test configuration, all channels in the subsequent test configuration that overlap with the larger bandwidth channel tested in the initial test configuration should be used to determine the highest maximum output power channel. This step requires additional power measurement to identify the highest maximum output power channel in the subsequent test configuration to determine SAR test reduction.

- a) SAR should first be measured for the channel with highest measured output power in the subsequent test configuration.
 - b) SAR for subsequent highest measured maximum output power channels in the subsequent test configuration is required only when the *reported* SAR of the preceding higher maximum output power channel(s) in the subsequent test configuration is > 1.2 W/kg or until all required channels are tested. i) For channels with the same measured maximum output power, SAR should be measured using the channel closest to the center frequency of the larger channel bandwidth channel in the initial test configuration.
- 4) . SAR measurements for the remaining highest specified maximum output power OFDM transmission mode configurations that have not been tested in the initial test configuration (highest maximum output) or subsequent test configuration(s) (subsequent next highest maximum output power) is determined by recursively applying the subsequent test configuration procedures in this section to the remaining configurations according to the following:
- a) replace "subsequent test configuration" with "next subsequent test configuration" (i.e., subsequent next highest specified maximum output power configuration)
 - b) replace "initial test configuration" with "all tested higher output power configurations"

5.2.4.4 2.4 GHz SAR Procedures

Separate SAR procedures are applied to DSSS and OFDM configurations in the 2.4 GHz band to simplify DSSS test requirements. For 802.11b DSSS SAR measurements, DSSS SAR procedure applies to fixed exposure test position and initial test position procedure applies to multiple exposure test positions. When SAR measurement is required for an OFDM configuration, the initial test configuration, subsequent test configuration and initial test position procedures are applied. The SAR test exclusion requirements for 802.11g/n OFDM configurations are described in following.

- **802.11b DSSS SAR Test Requirements**

SAR is measured for 2.4 GHz 802.11b DSSS using either a fixed test position or, when applicable, the initial test position procedure. SAR test reduction is determined according to the following:

- 1) . When the reported SAR of the highest measured maximum output power channel for the exposure configuration is ≤ 0.8 W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.
- 2) . When the reported SAR is > 0.8 W/kg, SAR is required for that exposure configuration using the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel; i.e., all channels require testing.

- **2.4 GHz 802.11g/n OFDM SAR Test Exclusion Requirements**

When SAR measurement is required for 2.4 GHz 802.11g/n OFDM configurations, the measurement and test reduction procedures for OFDM are applied (section 5.3, including sub-sections). SAR is not required for the following 2.4 GHz OFDM conditions.

- 1) . When KDB Publication 447498 SAR test exclusion applies to the OFDM configuration.
- 2) . When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.



5.2.5 LTE Test Configuration

LTE modes were tested according to FCC KDB 941225 D05 publication. Please see notes after the tabulated SAR data for required test configurations. Establishing connections with base station simulators ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. The R&S CMW500 was used for LTE output power measurements and SAR testing. Max power control was used so the UE transmits with maximum output power during SAR testing. SAR must be measured with the maximum TTI (transmit time interval) supported by the device in each LTE configuration.

A) Spectrum Plots for RB Configurations

A properly configured base station simulator was used for SAR tests and power measurements. Therefore, spectrum plots for RB configurations were not required to be included in this report.

B) MPR

MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.

C) A-MPR

A-MPR (Additional MPR) has been disabled for all SAR tests by setting NS=01 on the base station simulator.

D) Largest channel bandwidth standalone SAR test requirements

1) QPSK with 1 RB allocation

Start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required for 1 RB allocation; otherwise, SAR is required for the remaining required test channels and only for the RB offset configuration with the highest output power for that channel. When the reported SAR of a required test channel is > 1.45 W/kg, SAR is required for all three RB offset configurations for that required test channel.

2) QPSK with 50% RB allocation

The procedures required for 1 RB allocation in 1) are applied to measure the SAR for QPSK with 50% RB allocation.

3) QPSK with 100% RB allocation

For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation in 1) and 2) are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.


4) Higher order modulations

For each modulation besides QPSK; e.g., 16-QAM, 64-QAM, apply the QPSK procedures in above sections to determine the QAM configurations that may need SAR measurement. For each configuration identified as required for testing, SAR is required only when the highest maximum output power for the configuration in the higher order modulation is $> \frac{1}{2}$ dB higher than the same configuration in QPSK or when the reported SAR for the QPSK configuration is > 1.45 W/kg.

E) Other channel bandwidth standalone SAR test requirements

For the other channel bandwidths used by the device in a frequency band, apply all the procedures required for the largest channel bandwidth in section A) to determine the channels and RB configurations that need SAR testing and only measure SAR when the highest maximum output power of a configuration requiring testing in the smaller channel bandwidth is $> \frac{1}{2}$ dB higher than the equivalent channel configurations in the largest channel bandwidth configuration or the reported SAR of a configuration for the largest channel bandwidth is > 1.45 W/kg.

5.2.6 DUT Antenna Locations



Unit: mm

Display diagonal dimension: 12.6 cm

Overall diagonal dimension: 13.4 cm



5.2.7 EUT side for SAR Testing

According to the distance between Main&WIFI antennas and the sides of the EUT we can draw the conclusion that:

EUT Sides for SAR Testing						
Mode	Front	Back	Left	Right	Top	Bottom
GSM	Yes	Yes	Yes	Yes	No	Yes
WCDMA	Yes	Yes	Yes	Yes	No	Yes
CDMA	Yes	Yes	Yes	Yes	No	Yes
LTE	Yes	Yes	Yes	Yes	No	Yes
Wi-Fi (5GHz)	Yes	Yes	No	Yes	Yes	No

Table 8: EUT Sides for SAR Testing.

Note: When the antenna-to-edge distance is greater than 2.5cm, such position does not need to be tested.



5.2.8 Stand-alone SAR test evaluation

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition is satisfied. These test exclusion conditions are based on source-based time-averaged maximum conducted output power of the RF channel requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.

Freq. Band	Frequency (GHz)	Position	Average Power		Test Separation (mm)	Calculate Value	Exclusion Threshold	Exclusion (Y/N)
			dBm	mW				
Wi-Fi	5GHz	Head	13.5	22.4	0	10.0	3	N
		Body-worn	13.5	22.4	15	0.0	5	N
		hotspot	13.5	22.4	10	5.0	6	N
Bluetooth	2.48	Head	6.5	4.5	0	1.4	3	Y
		Body-worn	6.5	4.5	15	0.5	3	Y
		hotspot	6.5	4.5	10	0.7	3	Y

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$$
for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.



5.3 Measurement of RF conducted Power

5.3.1 Conducted Power Of GSM

GSM 850										
Burst Output Power(dBm)					Tune up	Division Factors	Frame-Average Output Power(dBm)			Tune up
Channel		128	190	251			128	190	251	
GSM (GMSK)	GSM	31.28	31.35	31.23	32	-9.19	22.09	22.16	22.04	22.81
GPRS/E GPRS (GMSK)	1 TX Slot	31.2	31.28	31.22	32	-9.19	22.01	22.09	22.03	22.81
	2 TX Slots	31.04	30.95	30.82	31.5	-6.18	24.86	24.77	24.64	25.32
	3 TX Slots	29.09	29.14	29.07	29.5	-4.42	24.67	24.72	24.65	25.08
	4 TX Slots	27.86	27.89	27.75	28.5	-3.17	24.69	24.72	24.58	25.33
EGPRS(8PSK)	1 TX Slot	26.74	26.82	26.87	27.5	-9.19	17.55	17.63	17.68	18.31
	2 TX Slots	25.15	25.14	25.26	26	-6.18	18.97	18.96	19.08	19.82
	3 TX Slots	23.34	23.44	23.48	24	-4.42	18.92	19.02	19.06	19.58
	4 TX Slots	22	22.17	22.12	22.5	-3.17	18.83	19	18.95	19.33
GSM 1900										
Burst Output Power(dBm)					Tune up	Division Factors	Frame-Average Output Power(dBm)			Tune up
Channel		512	661	810			512	661	810	
GSM(G MSK)	GSM	30.76	30.72	30.67	31	-9.19	21.57	21.53	21.48	21.81
GPRS/E GPRS (GMSK)	1 TX Slot	30.86	30.84	30.61	31	-9.19	21.67	21.65	21.42	21.81
	2 TX Slots	30.44	30.73	30.35	31	-6.18	24.26	24.55	24.17	24.82
	3 TX Slots	28.82	28.72	28.71	29	-4.42	24.4	24.3	24.29	24.58
	4 TX Slots	26.98	26.93	26.77	27.5	-3.17	23.81	23.76	23.6	24.33
EGPRS(8PSK)	1 TX Slot	25.3	25.22	24.96	26	-9.19	16.11	16.03	15.77	16.81
	2 TX Slots	24.05	23.94	23.72	24.5	-6.18	17.87	17.76	17.54	18.32
	3 TX Slots	23.26	23.27	23.17	23.5	-4.42	18.84	18.85	18.75	19.08
	4 TX Slots	21.48	21.29	21.14	22	-3.17	18.31	18.12	17.97	18.83

Table 9: Conducted Power Of GSM

Note:

- 1) . CMU200 measures GSM peak and average output power for active timeslots. For SAR the time based average power is relevant. The difference in between depends on the duty cycle of the TDMA signal:

No. of timeslots	1	2	3	4
Duty Cycle	1:8.3	1:4.15	1:2.77	1:2.075
Time based avg. power compared to slotted avg. power	-9.19	-6.18	-4.42	-3.17

- 2) . The frame-averaged power is linearly proportion to the slot number configured and it is linearly scaled the maximum burst-averaged power based on time slots. The calculated method is shown as below:

Frame-averaged power = $10 \times \log (\text{Burst-averaged power mW} \times \text{Slot used} / 8)$

- 3) . When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel must be used



5.3.2 Conducted Power Of WCDMA

WCDMA Band II					
Average Conducted Power(dBm)					
Channel		9262	9400	9538	Tune up
WCDMA	12.2kbps RMC	23.16	23.04	23.12	23.5
	12.2kbps AMR	22.93	22.96	22.99	23.5
HSDPA	Subtest 1	22.15	22.05	22.11	22.5
	Subtest 2	22.03	22.02	21.98	22.5
	Subtest 3	21.47	21.52	21.42	22
	Subtest 4	21.45	21.5	21.46	22
HSUPA	Subtest 1	21.58	21.59	21.64	22
	Subtest 2	21.62	21.56	21.61	22
	Subtest 3	21.58	21.59	21.58	22
	Subtest 4	21.63	21.58	21.56	22
	Subtest 5	21.84	21.74	21.73	22

WCDMA Band IV					
Average Conducted Power(dBm)					
Channel		1312	1412	1513	Tune up
WCDMA	12.2kbps RMC	22.72	22.88	22.99	23.5
	12.2kbps AMR	22.57	22.65	22.84	23.5
HSDPA	Subtest 1	21.8	21.86	21.88	22.5
	Subtest 2	21.71	21.77	22.01	22.5
	Subtest 3	21.28	21.37	21.53	22
	Subtest 4	21.23	21.33	21.43	22
HSUPA	Subtest 1	21.16	21.24	21.48	22
	Subtest 2	21.18	21.2	21.45	22
	Subtest 3	21.11	21.22	21.41	22
	Subtest 4	21.11	21.28	21.48	22
	Subtest 5	21.3	21.41	21.65	22

Table 10: Conducted Power Of WCDMA



5.3.3 Conducted Power Of CDMA

CDMA BC0(850MHz)					
Average Conducted Power(dBm)					
Channel		1013	384	777	Tune up
1xRTT	RC1 SO55 (Loopback)	21.57	21.54	21.46	22
	RC3 SO55 (Loopback)	21.59	21.58	21.47	22
	RC3 SO32 (+FCH)	21.56	21.52	21.46	22
	RC3 SO32 (FCH+SCH)	21.54	21.5	21.44	22
CDMA BC1(1900MHz)					
Average Conducted Power(dBm)					
Channel		25	600	1175	Tune up
1xRTT	RC1 SO55 (Loopback)	21.74	21.59	21.2	22
	RC3 SO55 (Loopback)	21.77	21.62	21.26	22
	RC3 SO32 (+FCH)	21.75	21.6	21.22	22
	RC3 SO32 (FCH+SCH)	21.74	21.58	21.21	22

Table 11: Conducted Power Of CDMA



5.3.4 Conducted Power Of LTE

LTE Band 2				Conducted Power(dBm)			
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				18607	18900	19193	
1.4MHz	QPSK	1	0	22.17	22.1	22.16	22.5
		1	2	22.12	22.11	22.11	22.5
		1	5	22.14	22.08	22.16	22.5
		3	0	22.12	22.06	22.16	22.5
		3	2	22.12	22.08	22.15	22.5
		3	3	22.11	22.08	22.12	22.5
	16QAM	6	0	21.29	21.17	21.18	21.5
		1	0	21.1	21.09	21.14	21.5
		1	2	21.11	21.1	21.07	21.5
		1	5	21.17	21.08	21.08	21.5
		3	0	21.14	21.14	21.1	21.5
		3	2	21.14	21.1	21.08	21.5
		3	3	21.15	21.11	21.09	21.5
		6	0	20.11	20.07	20.15	20.5
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				18615	18900	19185	
3MHz	QPSK	1	0	22.1	22.05	22.12	22.5
		1	7	22.1	22.03	22.07	22.5
		1	14	22.1	22.08	22.09	22.5
		8	0	21.2	21.09	21.17	21.5
		8	4	21.18	21.09	21.12	21.5
		8	7	21.22	21.09	21.13	21.5
	16QAM	15	0	21.2	21.13	21.14	21.5
		1	0	21.13	21.06	21.05	21.5
		1	7	21.09	21.05	21.06	21.5
		1	14	21.04	21.06	21.06	21.5
		8	0	20.23	20.16	20.26	20.5
		8	4	20.22	20.16	20.21	20.5
		8	7	20.19	20.16	20.25	20.5
		15	0	20.22	20.15	20.21	20.5
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				18625	18900	19175	
5MHz	QPSK	1	0	22.13	22.11	22.14	22.5
		1	13	22.16	22.1	22.15	22.5
		1	24	22.04	22.15	22.14	22.5
		12	0	21.22	21.12	21.17	21.5
		12	6	21.22	21.16	21.19	21.5
		12	13	21.21	21.16	21.21	21.5
	16QAM	25	0	21.28	21.12	21.23	21.5
		1	0	21.16	21.05	21.06	21.5
		1	13	21.15	21.07	21.1	21.5
		1	24	21.03	21.11	21.07	21.5
		12	0	20.28	20.17	20.25	20.5
		12	6	20.29	20.22	20.27	20.5
		12	13	20.26	20.23	20.3	20.5
		25	0	20.27	20.18	20.25	20.5



Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				18650	18900	19150	
10MHz	QPSK	1	0	22.15	22.12	22.16	22.5
		1	25	22.04	22.09	22.15	22.5
		1	49	22.11	22.07	22.19	22.5
		25	0	21.26	21.16	21.13	21.5
		25	13	21.17	21.18	21.14	21.5
		25	25	21.16	21.24	21.14	21.5
		50	0	21.25	21.16	21.16	21.5
	16QAM	1	0	21.14	21.04	21.14	21.5
		1	25	21.07	21.11	21.06	21.5
		1	49	21.12	21.03	21.11	21.5
		25	0	20.31	20.23	20.22	20.5
		25	13	20.16	20.18	20.29	20.5
		25	25	20.18	20.2	20.31	20.5
		50	0	20.22	20.16	20.25	20.5
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				18675	18900	19125	
15MHz	QPSK	1	0	22.2	22.14	22.17	22.5
		1	38	22.18	22.11	22.1	22.5
		1	74	22.2	22.12	22.18	22.5
		36	0	21.18	21.16	21.13	21.5
		36	18	21.18	21.18	21.12	21.5
		36	39	21.28	21.06	21.14	21.5
		75	0	21.3	21.15	21.09	21.5
	16QAM	1	0	21.15	21.1	21.18	21.5
		1	38	21.16	21.09	21.05	21.5
		1	74	21.11	21.05	21.1	21.5
		36	0	20.2	20.11	20.2	20.5
		36	18	20.13	20.16	20.11	20.5
		36	39	20.22	20.12	20.22	20.5
		75	0	20.24	20.19	20.16	20.5
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				18700	18900	19100	
20MHz	QPSK	1	0	22.17	22.21	22.18	22.5
		1	50	22.13	22.1	22.12	22.5
		1	99	22.15	22.14	22.16	22.5
		50	0	21.26	21.34	21.18	21.5
		50	25	21.2	21.27	21.18	21.5
		50	50	21.14	21.29	21.12	21.5
		100	0	21.25	21.27	21.18	21.5
	16QAM	1	0	21.17	21.22	21.17	21.5
		1	50	21.18	21.1	21.11	21.5
		1	99	21.14	21.12	21.14	21.5
		50	0	20.31	20.21	20.25	20.5
		50	25	20.26	20.16	20.24	20.5
		50	50	20.22	20.14	20.24	20.5
		100	0	20.28	20.22	20.21	20.5

Table 12: Conducted Power Of LTE



LTE Band 4				Conducted Power(dBm)			
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				19957	20175	20393	
1.4MHz	QPSK	1	0	21.59	21.75	21.81	22
		1	2	21.5	21.76	21.82	22
		1	5	21.51	21.67	21.83	22
		3	0	21.62	21.76	21.83	22
		3	2	21.57	21.75	21.84	22
		3	3	21.5	21.7	21.82	22
		6	0	20.45	20.75	20.82	21
	16QAM	1	0	20.35	20.63	20.69	21
		1	2	20.41	20.64	20.66	21
		1	5	20.31	20.46	20.7	21
		3	0	20.39	20.63	20.7	21
		3	2	20.34	20.63	20.69	21
		3	3	20.41	20.48	20.7	21
		6	0	19.31	19.5	19.6	20
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				19965	20175	20385	
3MHz	QPSK	1	0	21.52	21.77	21.7	22
		1	7	21.4	21.65	21.79	22
		1	14	21.42	21.68	21.79	22
		8	0	20.38	20.64	20.63	21
		8	4	20.29	20.61	20.7	21
		8	7	20.34	20.54	20.71	21
		15	0	20.33	20.7	20.76	21
	16QAM	1	0	20.35	20.56	20.46	21
		1	7	20.23	20.43	20.56	21
		1	14	20.25	20.4	20.63	21
		8	0	19.42	19.58	19.58	20
		8	4	19.31	19.58	19.71	20
		8	7	19.28	19.5	19.67	20
		15	0	19.25	19.56	19.65	20
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				19975	20175	20375	
5MHz	QPSK	1	0	21.6	21.81	21.65	22
		1	13	21.46	21.66	21.76	22
		1	24	21.49	21.67	21.81	22
		12	0	20.46	20.73	20.6	21
		12	6	20.39	20.69	20.68	21
		12	13	20.35	20.57	20.8	21
		25	0	20.32	20.74	20.66	21
	16QAM	1	0	20.4	20.62	20.41	21
		1	13	20.17	20.48	20.5	21
		1	24	20.28	20.47	20.69	21
		12	0	19.44	19.63	19.63	20
		12	6	19.34	19.66	19.64	20
		12	13	19.36	19.54	19.7	20
		25	0	19.37	19.64	19.59	20



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM170400351906

Page: 50 of 74

Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				20000	20175	20350	
10MHz	QPSK	1	0	21.62	21.81	21.58	22
		1	25	21.49	21.67	21.61	22
		1	49	21.5	21.61	21.83	22
		25	0	20.38	20.72	20.43	21
		25	13	20.34	20.73	20.54	21
		25	25	20.34	20.6	20.66	21
		50	0	20.32	20.69	20.55	21
	16QAM	1	0	20.39	20.64	20.36	21
		1	25	20.3	20.45	20.43	21
		1	49	20.33	20.35	20.7	21
		25	0	19.35	19.65	19.43	20
		25	13	19.38	19.63	19.52	20
		25	25	19.4	19.54	19.63	20
		50	0	19.38	19.57	19.52	20
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				20025	20175	20325	
15MHz	QPSK	1	0	21.63	21.8	21.67	22
		1	38	21.52	21.71	21.54	22
		1	74	21.74	21.6	21.8	22
		36	0	20.38	20.7	20.41	21
		36	18	20.41	20.69	20.41	21
		36	39	20.51	20.44	20.53	21
		75	0	20.37	20.57	20.47	21
	16QAM	1	0	20.43	20.69	20.48	21
		1	38	20.31	20.49	20.29	21
		1	74	20.57	20.37	20.7	21
		36	0	19.32	19.66	19.35	20
		36	18	19.35	19.6	19.35	20
		36	39	19.45	19.42	19.45	20
		75	0	19.38	19.55	19.5	20
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				20050	20175	20300	
20MHz	QPSK	1	0	21.59	21.77	21.86	22
		1	50	21.52	21.71	21.52	22
		1	99	21.57	21.56	21.64	22
		50	0	20.72	20.79	20.82	21
		50	25	20.54	20.75	20.39	21
		50	50	20.68	20.48	20.54	21
		100	0	20.59	20.59	20.56	21
	16QAM	1	0	20.46	20.69	20.46	21
		1	50	20.34	20.49	20.34	21
		1	99	20.58	20.39	20.63	21
		50	0	19.39	19.65	19.51	20
		50	25	19.44	19.59	19.36	20
		50	50	19.59	19.42	19.47	20
		100	0	19.48	19.59	19.49	20



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM170400351906

Page: 51 of 74

LTE Band 12				Conducted Power(dBm)			
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				23017	23095	23173	
1.4MHz	QPSK	1	0	21.16	20.98	20.91	21.5
		1	2	21.17	20.93	20.88	21.5
		1	5	21.15	21.03	20.89	21.5
		3	0	21.16	20.96	20.9	21.5
		3	2	21.14	21.02	20.91	21.5
		3	3	21.15	21.05	20.9	21.5
		6	0	20.31	20.17	19.98	20.5
	16QAM	1	0	20.16	19.92	19.88	20.5
		1	2	20.14	19.93	19.89	20.5
		1	5	20.22	20.02	19.9	20.5
		3	0	20.19	19.95	19.9	20.5
		3	2	20.17	20.05	19.91	20.5
		3	3	20.22	20.07	19.92	20.5
		6	0	19.22	19.06	18.92	19.5
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				23025	23095	23165	
3MHz	QPSK	1	0	21.17	20.89	20.93	21.5
		1	7	21.15	20.98	20.88	21.5
		1	14	21.09	21.03	20.89	21.5
		8	0	20.26	19.96	19.98	20.5
		8	4	20.21	20.05	19.95	20.5
		8	7	20.15	20.06	19.97	20.5
		15	0	20.26	20.1	19.98	20.5
	16QAM	1	0	20.16	19.86	19.86	20.5
		1	7	20.1	19.97	19.85	20.5
		1	14	20.1	20.01	19.88	20.5
		8	0	19.27	19.01	19.06	19.5
		8	4	19.27	19.1	19.02	19.5
		8	7	19.21	19.11	18.99	19.5
		15	0	19.22	19.07	18.98	19.5
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				23035	23095	23155	
5MHz	QPSK	1	0	21.14	20.89	20.94	21.5
		1	13	21.09	21.01	20.9	21.5
		1	24	20.86	21.01	20.9	21.5
		12	0	20.22	19.94	20.01	20.5
		12	6	20.11	20.12	19.96	20.5
		12	13	20.07	20.12	19.98	20.5
		25	0	20.05	20.13	20	20.5
	16QAM	1	0	20.16	19.85	19.91	20.5
		1	13	20	19.94	19.88	20.5
		1	24	19.77	19.97	19.9	20.5
		12	0	19.23	19.02	19.03	19.5
		12	6	19.19	19.15	19.02	19.5
		12	13	19.12	19.16	19.05	19.5
		25	0	19.09	19.09	19.02	19.5



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM170400351906

Page: 52 of 74

Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				23060	23095	23130	
10MHz	QPSK	1	0	21.17	20.88	20.89	21.5
		1	25	20.92	21.02	20.98	21.5
		1	49	21.12	21.08	21.06	21.5
		25	0	20.1	19.96	20.09	20.5
		25	13	20.01	20.09	20.01	20.5
		25	25	20.19	20.11	20.1	20.5
		50	0	20.04	20.11	20.1	20.5
	16QAM	1	0	20.14	19.84	19.86	20.5
		1	25	19.9	20	19.95	20.5
		1	49	20.1	20.01	20	20.5
		25	0	19.06	18.99	19.11	19.5
		25	13	19.03	19.11	19.13	19.5
		25	25	19.18	19.14	19.1	19.5
		50	0	19.08	19.12	19.06	19.5



5.3.5 Conducted Power Of WIFI and BT

	Average Power (dBm) for Data Rates (Mbps)		
5GHz	Channel	6	Tune up
802.11a	36	13.364	13.5
	40	13.331	13.5
	44	13.308	13.5
	48	13.012	13.5
	52	13.221	13.5
	56	13.214	13.5
	60	13.028	13.5
	64	13.056	13.5
	100	12.919	13.5
	104	12.923	13.5
	108	12.892	13.5
	112	12.987	13.5
	116	13.265	13.5
	120	13.203	13.5
	124	13.152	13.5
	128	12.984	13.5
	132	12.907	13.5
	136	12.882	13.5
	140	12.921	13.5
	144	12.993	13.5
5GHz	Channel	MCS0	Tune up
802.11n-HT20	36	12.365	12.5
	40	12.347	12.5
	44	12.299	12.5
	48	12.108	12.5
	52	12.189	12.5
	56	12.123	12.5
	60	12.142	12.5
	64	12.211	12.5
	100	12.191	12.5



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM170400351906

Page: 54 of 74

104	12.259	12.5
108	12.369	12.5
112	12.389	12.5
116	12.359	12.5
120	12.401	12.5
124	12.216	12.5
128	12.333	12.5
132	12.256	12.5
136	12.135	12.5
140	12.057	12.5
144	12.388	12.5

Table 13: Conducted Power Of WIFI

BT		Average Conducted Power(dBm)			
Band	Channel	GFSK	$\pi/4$ DQPSK	8DPSK	Tune up
BT	0	5.729	4.312	4.318	6.5
	39	5.756	4.338	4.28	
	78	5.709	4.309	4.303	
BLE	0	-11.397	/	/	
	19	-2.699	/	/	
	39	-5.941	/	/	

Table 14: Conducted Power Of BT



5.4 Measurement of SAR Data

5.4.1 SAR Result Of GSM850

Test position	Test mode	Test Ch./Freq.	Duty Cycle	SAR (W/kg) 1-g	Power Drift (dB)	Conducted Power (dBm)	Tune up Limit (dBm)	Scaled factor	Scaled SAR(W/kg)	Liquid Temp
Head Test data										
Left touch cheek	GSM	190/836.6	1:8.3	0.00781	0.02	31.35	32	1.161	0.009	22.1
Left tilted 15 degree	GSM	190/836.6	1:8.3	0.00272	0.07	31.35	32	1.161	0.003	22.1
Right touch cheek	GSM	190/836.6	1:8.3	0.00572	0.06	31.35	32	1.161	0.007	22.1
Right tilted 15 degree	GSM	190/836.6	1:8.3	0.00135	-0.08	31.35	32	1.161	0.002	22.1
Body worn Test data(Separate 15mm)										
Front side	GSM	190/836.6	1:8.3	0.0169	-0.13	31.35	32	1.161	0.020	22.1
Back side	GSM	190/836.6	1:8.3	0.021	-0.06	31.35	32	1.161	0.024	22.1
Hotspot Test data(Separate 10mm)										
Front side	GPRS 4TS	190/836.6	1:2.075	0.0612	-0.09	27.89	28.5	1.151	0.070	22.1
Back side	GPRS 4TS	190/836.6	1:2.075	0.083	-0.07	27.89	28.5	1.151	0.096	22.1
Left side	GPRS 4TS	190/836.6	1:2.075	0.0287	0.08	27.89	28.5	1.151	0.033	22.1
Right side	GPRS 4TS	190/836.6	1:2.075	0.015	-0.04	27.89	28.5	1.151	0.017	22.1
Bottom side	GPRS 4TS	190/836.6	1:2.075	0.0448	0.13	27.89	28.5	1.151	0.052	22.1

Table 15: SAR of GSM850 for Head and Body.

Note:

- 1) The maximum Scaled SAR value is marked in bold. Graph results refer to Appendix B
- 2) Per FCC KDB Publication 447498 D01, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s).



5.4.2 SAR Result Of GSM1900

Test position	Test mode	Test Ch./Freq.	Duty Cycle	SAR (W/kg) 1-g	Power Drift (dB)	Conducted Power (dBm)	Tune up Limit (dBm)	Scaled factor	Scaled SAR (W/kg)	Liquid Temp
Head Test data										
Left touch cheek	GSM	661/1880	1:8.3	0.0649	0.12	30.72	31	1.067	0.069	22.3
Left tilted 15 degree	GSM	661/1880	1:8.3	0.0263	0.05	30.72	31	1.067	0.028	22.3
Right touch cheek	GSM	661/1880	1:8.3	0.075	0.17	30.72	31	1.067	0.080	22.3
Right tilted 15 degree	GSM	661/1880	1:8.3	0.0269	-0.14	30.72	31	1.067	0.029	22.3
Body worn Test data(Separate 15mm)										
Front side	GSM	661/1880	1:8.3	0.109	0	30.72	31	1.067	0.116	22.3
Back side	GSM	661/1880	1:8.3	0.151	0.11	30.72	31	1.067	0.161	22.3
Hotspot Test data(Separate 10mm)										
Front side	GPRS 2TS	661/1880	1:4.15	0.372	0.03	30.73	31	1.064	0.396	22.3
Back side	GPRS 2TS	661/1880	1:4.15	0.545	0.05	30.73	31	1.064	0.580	22.3
Left side	GPRS 2TS	661/1880	1:4.15	0.285	0.06	30.73	31	1.064	0.303	22.3
Right side	GPRS 2TS	661/1880	1:4.15	0.0593	-0.08	30.73	31	1.064	0.063	22.3
Bottom side	GPRS 2TS	661/1880	1:4.15	0.981	-0.02	30.73	31	1.064	1.044	22.3
Bottom side	GPRS 2TS	512/1850.2	1:4.15	1.27	0.09	30.44	31	1.138	1.445	22.3
Bottom side	GPRS 2TS	810/1909.8	1:4.15	0.832	-0.02	30.35	31	1.161	0.966	22.3
Bottom side-repeat	GPRS 2TS	512/1850.2	1:4.15	1.24	0.06	30.44	31	1.138	1.411	22.3

Table 16: SAR of GSM1900 for Head and Body.

Note:

- 1) The maximum Scaled SAR value is marked in bold. Graph results refer to Appendix B
- 2) Per FCC KDB Publication 447498 D01, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s).



5.4.3 SAR Result Of WCDMA Band 2

Test position	Test mode	Test Ch./Freq.	Duty Cycle	SAR (W/kg) 1-g	Power Drift(dB)	Conducted Power (dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR (W/kg)	Liquid Temp
Head Test data										
Left touch cheek	RMC	9400/1880	1:1	0.0401	0.07	23.04	23.5	1.112	0.045	22.3
Left tilted 15 degree	RMC	9400/1880	1:1	0.0151	0.18	23.04	23.5	1.112	0.017	22.3
Right touch cheek	RMC	9400/1880	1:1	0.042	-0.14	23.04	23.5	1.112	0.047	22.3
Right tilted 15 degree	RMC	9400/1880	1:1	0.0146	0.08	23.04	23.5	1.112	0.016	22.3
Body worn Test data(Separate 15mm)										
Front side	RMC	9400/1880	1:1	0.0771	-0.15	23.04	23.5	1.112	0.086	22.3
Back side	RMC	9400/1880	1:1	0.104	-0.06	23.04	23.5	1.112	0.116	22.3
Hotspot Test data(Separate 10mm)										
Front side	RMC	9400/1880	1:1	0.143	0.08	23.04	23.5	1.112	0.159	22.3
Back side	RMC	9400/1880	1:1	0.192	-0.11	23.04	23.5	1.112	0.213	22.3
Left side	RMC	9400/1880	1:1	0.109	-0.06	23.04	23.5	1.112	0.121	22.3
Right side	RMC	9400/1880	1:1	0.0236	-0.05	23.04	23.5	1.112	0.026	22.3
Bottom side	RMC	9400/1880	1:1	0.260	0.10	23.04	23.5	1.112	0.289	22.3

Table 17: SAR of WCDMA1900 for Head and Body.

Note:

- 1) The maximum Scaled SAR value is marked in bold. Graph Results refer to Appendix B
- 2) If the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s).



5.4.4 SAR Result Of WCDMA Band 4

Test position	Test mode	Test Ch./Freq.	Duty Cycle	SAR (W/kg)1-g	Power Drift(dB)	Conducted Power(dBm)	Tune up Limit (dBm)	Scaled factor	Scaled SAR (W/kg)	Liquid Temp
Head Test data										
Left touch cheek	RMC	1412/1732.4	1:1	0.067	0.09	22.88	23.5	1.153	0.077	22.2
Left tilted 15 degree	RMC	1412/1732.4	1:1	0.0175	-0.13	22.88	23.5	1.153	0.020	22.2
Right touch cheek	RMC	1412/1732.4	1:1	0.0445	0.08	22.88	23.5	1.153	0.051	22.2
Right tilted 15 degree	RMC	1412/1732.4	1:1	0.025	0.19	22.88	23.5	1.153	0.029	22.2
Body worn Test data(Separate 15mm)										
Front side	RMC	1412/1732.4	1:1	0.0795	-0.09	22.88	23.5	1.153	0.092	22.2
Back side	RMC	1412/1732.4	1:1	0.119	0.11	22.88	23.5	1.153	0.137	22.2
Hotspot Test data(Separate 10mm)										
Front side	RMC	1412/1732.4	1:1	0.164	-0.02	22.88	23.5	1.153	0.189	22.2
Back side	RMC	1412/1732.4	1:1	0.227	0.02	22.88	23.5	1.153	0.262	22.2
Left side	RMC	1412/1732.4	1:1	0.119	0.2	22.88	23.5	1.153	0.137	22.2
Right side	RMC	1412/1732.4	1:1	0.0194	0.06	22.88	23.5	1.153	0.022	22.2
Bottom side	RMC	1412/1732.4	1:1	0.437	-0.05	22.88	23.5	1.153	0.504	22.2

Table 18: SAR of WCDMA1700 for Head and Body.

Note:

- 1) The maximum Scaled SAR value is marked in bold. Graph Results refer to Appendix B
- 2) If the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s).



5.4.5 SAR Result Of CDMA BC0

Test position	Test mode	Test Ch./Freq.	Duty Cycle	SAR (W/kg) 1-g	Power Drift(dB)	Conducted Power (dBm)	Tune up Limit(d Bm)	Scaled factor	Scaled SAR (W/kg)	Liquid Temp
Head Test data										
Left touch cheek	1xRTT(RC 3 SO55)	384/836.52	1:1	0.015	0.08	21.58	22	1.102	0.017	22.1
Left tilted 15 degree	1xRTT(RC 3 SO55)	384/836.52	1:1	0.00459	0.07	21.58	22	1.102	0.005	22.1
Right touch cheek	1xRTT(RC 3 SO55)	384/836.52	1:1	0.00946	0.01	21.58	22	1.102	0.010	22.1
Right tilted 15 degree	1xRTT(RC 3 SO55)	384/836.52	1:1	0.00292	0	21.58	22	1.102	0.003	22.1
Body worn Test data(Separate 15mm)										
Front side	1xRTT(RC 3 SO32)	384/836.52	1:1	0.0322	0.14	21.52	22	1.117	0.036	22.1
Back side	1xRTT(RC 3 SO32)	384/836.52	1:1	0.037	-0.02	21.52	22	1.117	0.041	22.1
Hotspot Test data(Separate 10mm)										
Front side	1xRTT(RC 3 SO32)	384/836.52	1:1	0.0553	0.05	21.52	22	1.117	0.062	22.1
Back side	1xRTT(RC 3 SO32)	384/836.52	1:1	0.068	-0.09	21.52	22	1.117	0.076	22.1
Left side	1xRTT(RC 3 SO32)	384/836.52	1:1	0.0247	0	21.52	22	1.117	0.028	22.1
Right side	1xRTT(RC 3 SO32)	384/836.52	1:1	0.0118	-0.19	21.52	22	1.117	0.013	22.1
Bottom side	1xRTT(RC 3 SO32)	384/836.52	1:1	0.0355	-0.03	21.52	22	1.117	0.040	22.1

Table 19: SAR of CDMA BC0 for Head and Body.

Note:

- 1) The maximum Scaled SAR value is marked in bold. Graph Results refer to Appendix B
- 2) If the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s).



5.4.6 SAR Result Of CDMA BC1

Test position	Test mode	Test Ch./Freq.	Duty Cycle	SAR (W/kg) 1-g	Power Drift(dB)	Conducted Power (dBm)	Tune up Limit(d Bm)	Scaled factor	Scaled SAR (W/kg)	Liquid Temp
Head Test data										
Left touch cheek	1xRTT(RC 3 SO55)	600/1880	1:1	0.0486	0.04	21.6	22	1.096	0.053	22.3
Left tilted 15 degree	1xRTT(RC 3 SO55)	600/1880	1:1	0.0175	0.19	21.6	22	1.096	0.019	22.3
Right touch cheek	1xRTT(RC 3 SO55)	600/1880	1:1	0.0617	0.07	21.6	22	1.096	0.068	22.3
Right tilted 15 degree	1xRTT(RC 3 SO55)	600/1880	1:1	0.0179	0.05	21.6	22	1.096	0.020	22.3
Body worn Test data(Separate 15mm)										
Front side	1xRTT(RC 3 SO32)	600/1880	1:1	0.0787	-0.04	21.6	22	1.096	0.086	22.3
Back side	1xRTT(RC 3 SO32)	600/1880	1:1	0.105	-0.02	21.6	22	1.096	0.115	22.3
Hotspot Test data(Separate 10mm)										
Front side	1xRTT(RC 3 SO32)	600/1880	1:1	0.159	0.14	21.6	22	1.096	0.174	22.3
Back side	1xRTT(RC 3 SO32)	600/1880	1:1	0.19	0.06	21.6	22	1.096	0.208	22.3
Left side	1xRTT(RC 3 SO32)	600/1880	1:1	0.121	0.01	21.6	22	1.096	0.133	22.3
Right side	1xRTT(RC 3 SO32)	600/1880	1:1	0.0219	-0.06	21.6	22	1.096	0.024	22.3
Bottom side	1xRTT(RC 3 SO32)	600/1880	1:1	0.446	0.1	21.6	22	1.096	0.489	22.3

Table 20: SAR of CDMA BC1 for Head and Body.

Note:

- 1) The maximum Scaled SAR value is marked in bold. Graph Results refer to Appendix B
- 2) If the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s).



5.4.7 SAR Result Of LTE Band 2

Test position	BW.	Test mode	Test Ch./Freq.	Duty Cycle	SAR (W/kg) 1-g	Power Drift (dB)	Conducted power(dB m)	Tune up Limit(d Bm)	Scaled factor	Scaled SAR(W/kg)	Liquid Temp.
Head Test data(1RB_0 offset)											
Left touch cheek	20	QPSK	18900/1880	1:1	0.0725	0.13	22.21	22.5	1.069	0.078	22.3
Left tilted 15 degree	20	QPSK	18900/1880	1:1	0.0232	0.13	22.21	22.5	1.069	0.025	22.3
Right touch cheek	20	QPSK	18900/1880	1:1	0.080	0.07	22.21	22.5	1.069	0.086	22.3
Right tilted 15 degree	20	QPSK	18900/1880	1:1	0.0284	0.15	22.21	22.5	1.069	0.030	22.3
Head Test data(50%RB)											
Left touch cheek	20	QPSK	18900/1880	1:1	0.0541	-0.04	21.34	21.5	1.038	0.056	22.3
Left tilted 15 degree	20	QPSK	18900/1880	1:1	0.0174	-0.12	21.34	21.5	1.038	0.018	22.3
Right touch cheek	20	QPSK	18900/1880	1:1	0.0613	0.07	21.34	21.5	1.038	0.064	22.3
Right tilted 15 degree	20	QPSK	18900/1880	1:1	0.0207	0.08	21.34	21.5	1.038	0.021	22.3
Body worn Test data(Separate 15mm 1RB_0 offset)											
Front side	20	QPSK	18900/1880	1:1	0.144	-0.05	22.21	22.5	1.069	0.154	22.3
Back side	20	QPSK	18900/1880	1:1	0.186	0.05	22.21	22.5	1.069	0.199	22.3
Body worn Test data (Separate 15mm 50%RB)											
Front side	20	QPSK	18900/1880	1:1	0.112	0.07	21.34	21.5	1.038	0.116	22.3
Back side	20	QPSK	18900/1880	1:1	0.146	0.09	21.34	21.5	1.038	0.151	22.3
Hotspot Test data(Separate 10mm 1RB_0 offset)											
Front side	20	QPSK	18900/1880	1:1	0.248	-0.07	22.21	22.5	1.069	0.265	22.3
Back side	20	QPSK	18900/1880	1:1	0.322	0.03	22.21	22.5	1.069	0.344	22.3
Left side	20	QPSK	18900/1880	1:1	0.178	-0.11	22.21	22.5	1.069	0.190	22.3
Right side	20	QPSK	18900/1880	1:1	0.0416	0.11	22.21	22.5	1.069	0.044	22.3
Bottom side	20	QPSK	18900/1880	1:1	0.691	0	22.21	22.5	1.069	0.739	22.3
Hotspot Test data (Separate 10mm 50%RB)											
Front side	20	QPSK	18900/1880	1:1	0.191	0.09	21.34	21.5	1.038	0.198	22.3
Back side	20	QPSK	18900/1880	1:1	0.251	0.03	21.34	21.5	1.038	0.260	22.3
Left side	20	QPSK	18900/1880	1:1	0.141	0.08	21.34	21.5	1.038	0.146	22.3
Right side	20	QPSK	18900/1880	1:1	0.0327	0.08	21.34	21.5	1.038	0.034	22.3
Bottom side	20	QPSK	18900/1880	1:1	0.366	0.01	21.34	21.5	1.038	0.380	22.3

Table 21: SAR of LTE band 2 for Head and Body.

Note:

- 1) The maximum Scaled SAR value is marked in bold. Graph results refer to Appendix B
- 2) If the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s).



5.4.1 SAR Result Of LTE Band 4

Test position	BW.	Test mode	Test Ch./Freq.	Duty Cycle	SAR (W/kg)1-g	Power Drift(dB)	Conducted power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR(W/kg)	Liquid Temp.
Head Test data(1RB_0 offset)											
Left touch cheek	20	QPSK	20300/1745	1:1	0.107	-0.01	21.86	22	1.033	0.111	22.2
Left tilted 15 degree	20	QPSK	20300/1745	1:1	0.0378	0.03	21.86	22	1.033	0.039	22.2
Right touch cheek	20	QPSK	20300/1745	1:1	0.0843	0.06	21.86	22	1.033	0.087	22.2
Right tilted 15 degree	20	QPSK	20300/1745	1:1	0.0457	0.08	21.86	22	1.033	0.047	22.2
Head Test data(50%RB)											
Left touch cheek	20	QPSK	20300/1745	1:1	0.0839	0.08	20.82	21	1.042	0.087	22.2
Left tilted 15 degree	20	QPSK	20300/1745	1:1	0.0302	0.11	20.82	21	1.042	0.031	22.2
Right touch cheek	20	QPSK	20300/1745	1:1	0.0668	0.19	20.82	21	1.042	0.070	22.2
Right tilted 15 degree	20	QPSK	20300/1745	1:1	0.0351	0.06	20.82	21	1.042	0.037	22.2
Body worn Test data(Separate 15mm 1RB_0 offset)											
Front side	20	QPSK	20300/1745	1:1	0.159	-0.02	21.86	22	1.033	0.164	22.2
Back side	20	QPSK	20300/1745	1:1	0.216	0.06	21.86	22	1.033	0.223	22.2
Body worn Test data (Separate 15mm 50%RB)											
Front side	20	QPSK	20300/1745	1:1	0.127	-0.06	20.82	21	1.042	0.132	22.2
Back side	20	QPSK	20300/1745	1:1	0.173	0.11	20.82	21	1.042	0.180	22.2
Hotspot Test data(Separate 10mm 1RB_0 offset)											
Front side	20	QPSK	20300/1745	1:1	0.287	0.14	21.86	22	1.033	0.296	22.2
Back side	20	QPSK	20300/1745	1:1	0.412	0.18	21.86	22	1.033	0.425	22.2
Left side	20	QPSK	20300/1745	1:1	0.244	0.06	21.86	22	1.033	0.252	22.2
Right side	20	QPSK	20300/1745	1:1	0.0369	-0.11	21.86	22	1.033	0.038	22.2
Bottom side	20	QPSK	20300/1745	1:1	0.761	0.05	21.86	22	1.033	0.786	22.2
Hotspot Test data (Separate 10mm 50%RB)											
Front side	20	QPSK	20300/1745	1:1	0.23	0.14	20.82	21	1.042	0.240	22.2
Back side	20	QPSK	20300/1745	1:1	0.32	-0.01	20.82	21	1.042	0.334	22.2
Left side	20	QPSK	20300/1745	1:1	0.2	-0.05	20.82	21	1.042	0.208	22.2
Right side	20	QPSK	20300/1745	1:1	0.0277	0.02	20.82	21	1.042	0.029	22.2
Bottom side	20	QPSK	20300/1745	1:1	0.616	-0.02	20.82	21	1.042	0.642	22.2

Table 22: SAR of LTE band 4 for Head and Body.

Note:

- 1) The maximum Scaled SAR value is marked in bold. Graph results refer to Appendix B
- 2) If the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s).



5.4.2 SAR Result Of LTE Band 12

Test position	BW.	Test mode	Test Ch./Freq.	Duty Cycle	SAR (W/kg)1-g	Power Drift (dB)	Conducted power(dB m)	Tune up Limit (dBm)	Scaled factor	Scaled SAR (W/kg)	Liquid Temp.
Head Test data(1RB_49 offset)											
Left touch cheek	10	QPSK	23060/704	1:1	0.00899	0.06	21.12	21.5	1.091	0.010	22.1
Left tilted 15 degree	10	QPSK	23060/704	1:1	0.00701	0.08	21.12	21.5	1.091	0.008	22.1
Right touch cheek	10	QPSK	23060/704	1:1	0.00919	0.09	21.12	21.5	1.091	0.010	22.1
Right tilted 15 degree	10	QPSK	23060/704	1:1	0.00661	0.12	21.12	21.5	1.091	0.007	22.1
Head Test data(25RB_25 offset)											
Left touch cheek	10	QPSK	23060/704	1:1	0.014	0.05	20.19	20.5	1.074	0.015	22.1
Left tilted 15 degree	10	QPSK	23060/704	1:1	0.00524	0.17	20.19	20.5	1.074	0.006	22.1
Right touch cheek	10	QPSK	23060/704	1:1	0.00693	0.06	20.19	20.5	1.074	0.007	22.1
Right tilted 15 degree	10	QPSK	23060/704	1:1	0.00499	0.04	20.19	20.5	1.074	0.005	22.1
Body worn Test data(Separate 15mm 1RB_49 offset)											
Front side	10	QPSK	23060/704	1:1	0.0422	0.14	21.12	21.5	1.091	0.046	22.1
Back side	10	QPSK	23060/704	1:1	0.05	0.16	21.12	21.5	1.091	0.055	22.1
Body worn Test data (Separate 15mm 25RB_25 offset)											
Front side	10	QPSK	23060/704	1:1	0.0338	0.09	20.19	20.5	1.074	0.036	22.1
Back side	10	QPSK	23060/704	1:1	0.0416	-0.02	20.19	20.5	1.074	0.045	22.1
Hotspot Test data(Separate 10mm 1RB_49 offset)											
Front side	10	QPSK	23060/704	1:1	0.0667	-0.13	21.12	21.5	1.091	0.073	22.1
Back side	10	QPSK	23060/704	1:1	0.088	-0.03	21.12	21.5	1.091	0.096	22.1
Left side	10	QPSK	23060/704	1:1	0.0242	0.01	21.12	21.5	1.091	0.026	22.1
Right side	10	QPSK	23060/704	1:1	0.0144	-0.05	21.12	21.5	1.091	0.016	22.1
Bottom side	10	QPSK	23060/704	1:1	0.0579	-0.01	21.12	21.5	1.091	0.063	22.1
Hotspot Test data (Separate 10mm 25RB_25 offset)											
Front side	10	QPSK	23060/704	1:1	0.0579	0.08	20.19	20.5	1.074	0.062	22.1
Back side	10	QPSK	23060/704	1:1	0.0676	0.07	20.19	20.5	1.074	0.073	22.1
Left side	10	QPSK	23060/704	1:1	0.0184	-0.12	20.19	20.5	1.074	0.020	22.1
Right side	10	QPSK	23060/704	1:1	0.0112	-0.11	20.19	20.5	1.074	0.012	22.1
Bottom side	10	QPSK	23060/704	1:1	0.0579	-0.09	20.19	20.5	1.074	0.062	22.1

Table 23: SAR of LTE band 12 for Head and Body.

Note:

- 1) The maximum Scaled SAR value is marked in bold. Graph results refer to Appendix B
- 2) If the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s).



5.4.3 SAR Result Of 5GHz WIFI

Test position	Test mode	Test Ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg) 1-g	Power drift (dB)	Conducted power (dBm)	Tune up Limit (dBm)	Scale d factor	Scaled SAR (W/kg)	Liquid Temp.	SAR limit (W/kg)
Head Test data U-NII-2A												
Left touch cheek	802.11a	52/5260	87.50%	1.143	0.239	0.05	13.221	13.5	1.066	0.291	22.2	1.6
Left tilted 15 degree	802.11a	52/5260	87.50%	1.143	0.159	0.02	13.221	13.5	1.066	0.194	22.2	1.6
Right touch cheek	802.11a	52/5260	87.50%	1.143	0.142	0.07	13.221	13.5	1.066	0.173	22.2	1.6
Right tilted 15 degree	802.11a	52/5260	87.50%	1.143	0.0989	0.07	13.221	13.5	1.066	0.121	22.2	1.6
Head Test data U-NII-2C												
Left touch cheek	802.11a	116/5580	87.50%	1.143	0.427	0.09	13.265	13.5	1.056	0.515	22.2	1.6
Left tilted 15 degree	802.11a	116/5580	87.50%	1.143	0.279	0.01	13.265	13.5	1.056	0.337	22.2	1.6
Right touch cheek	802.11a	116/5580	87.50%	1.143	0.21	-0.06	13.265	13.5	1.056	0.253	22.2	1.6
Right tilted 15 degree	802.11a	116/5580	87.50%	1.143	0.177	0.05	13.265	13.5	1.056	0.214	22.2	1.6
Body worn Test data U-NII-2A(Separate 15mm)												
Front side	802.11a	52/5260	87.50%	1.143	0.034	-0.05	13.221	13.5	1.066	0.041	22.2	1.6
Back side	802.11a	52/5260	87.50%	1.143	0.0106	0.02	13.221	13.5	1.066	0.013	22.2	1.6
Body worn Test data U-NII-2C(Separate 15mm)												
Front side	802.11a	116/5580	87.50%	1.143	0.024	-0.08	13.265	13.5	1.056	0.029	22.2	1.6
Back side	802.11a	116/5580	87.50%	1.143	0.0167	0.06	13.265	13.5	1.056	0.020	22.2	1.6
Hotspot Test data U-NII-1(Separate 10mm)												
Front side	802.11a	36/5180	87.50%	1.143	0.086	-0.02	13.36	13.5	1.033	0.102	22.2	1.6
Back side	802.11a	36/5180	87.50%	1.143	0.061	-0.11	13.36	13.5	1.033	0.072	22.2	1.6
Right side	802.11a	36/5180	87.50%	1.143	0.0115	-0.07	13.36	13.5	1.033	0.014	22.2	1.6
Top side	802.11a	36/5180	87.50%	1.143	0.0388	-0.12	13.36	13.5	1.033	0.046	22.2	1.6

Table 24: SAR of WIFI for Head and Body

Note:

- 1) The maximum Scaled SAR value is marked in bold. Graph results refer to Appendix B
- 2) If the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s).
- 3) Each channel was tested at the lowest data rate.
- 4) When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, 802.11g/n OFDM SAR Test is not required.



5.5 Multiple Transmitter Evaluation

5.5.1 Simultaneous SAR test evaluation

1) Simultaneous Transmission

NO.	Simultaneous Transmission Configuration	Head	Body worn	Hotspot
1	GSM(Voice) + WiFi	Yes	Yes	No
2	GSM(Voice) + BT	Yes	Yes	No
3	WCDMA(Voice) + WiFi	Yes	Yes	No
4	WCDMA(Voice) + BT	Yes	Yes	No
5	GPRS / EDGE(Data) + WiFi	No	No	Yes
6	GPRS / EDGE(Data) + BT	No	No	Yes
7	WCDMA(Data) + WiFi	No	No	Yes
8	WCDMA(Data) + BT	No	No	Yes
9	LTE(Data) + WiFi	Yes	Yes	Yes
10	LTE(Data) + BT	Yes	Yes	Yes
11	BT+WIFI (They share the same antenna and cannot transmit at the same time by design.)	No	No	No

5.5.2 Estimated SAR

When the standalone SAR test exclusion is applied to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to the following to determine simultaneous transmission SAR test exclusion:

• $(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm}) \cdot [\sqrt{f(\text{GHz})} / x] \text{ W/kg}$
for test separation distances $\leq 50 \text{ mm}$;

Where $x = 7.5$ for 1-g SAR, and $x = 18.75$ for 10-g SAR.

• 0.4 W/kg for 1-g SAR and 1.0 W/kg for 10-g SAR, when the test separation distances is $> 50 \text{ mm}$.

Estimated SAR Result

Freq. Band	Frequency (GHz)	Test Position	max. power(dBm)	Test Separation (mm)	Estimated
					1g SAR (W/kg)
Bluetooth	2.48	Head	6.5	0	0.188
		Body-worn	6.5	15	0.063
		hotspot	6.5	10	0.094



2) Simultaneous Transmission SAR Summation Scenario for head

WWAN Band	Exposure position	① MAX. WWAN SAR(W/kg)	② MAX.BT SAR (W/kg)	③ MAX.W LAN 5G SAR (W/kg)	Summed SAR ①+②	Summed SAR ①+③	Case NO.
GSM850	Left Touch	0.009	0.188	0.515	0.197	0.524	No
	Left Tilt	0.003	0.188	0.337	0.191	0.340	No
	Right Touch	0.007	0.188	0.253	0.195	0.260	No
	Right Tilt	0.002	0.188	0.214	0.190	0.216	No
GSM1900	Left Touch	0.069	0.188	0.515	0.257	0.584	No
	Left Tilt	0.028	0.188	0.337	0.216	0.365	No
	Right Touch	0.080	0.188	0.253	0.268	0.333	No
	Right Tilt	0.029	0.188	0.214	0.217	0.243	No
WCDMA Band II	Left Touch	0.045	0.188	0.515	0.233	0.560	No
	Left Tilt	0.017	0.188	0.337	0.205	0.354	No
	Right Touch	0.047	0.188	0.253	0.235	0.300	No
	Right Tilt	0.016	0.188	0.214	0.204	0.230	No
WCDMA Band IV	Left Touch	0.077	0.188	0.515	0.265	0.592	No
	Left Tilt	0.020	0.188	0.337	0.208	0.357	No
	Right Touch	0.051	0.188	0.253	0.239	0.304	No
	Right Tilt	0.029	0.188	0.214	0.217	0.243	No
CDMA BC0	Left Touch	0.017	0.188	0.515	0.205	0.532	No
	Left Tilt	0.005	0.188	0.337	0.193	0.342	No
	Right Touch	0.010	0.188	0.253	0.198	0.263	No
	Right Tilt	0.003	0.188	0.214	0.191	0.217	No
CDMA BC1	Left Touch	0.053	0.188	0.515	0.241	0.568	No
	Left Tilt	0.019	0.188	0.337	0.207	0.356	No
	Right Touch	0.068	0.188	0.253	0.256	0.321	No
	Right Tilt	0.020	0.188	0.214	0.208	0.234	No
LTE Band 2	Left Touch	0.078	0.188	0.515	0.266	0.593	No
	Left Tilt	0.025	0.188	0.337	0.213	0.362	No
	Right Touch	0.086	0.188	0.253	0.274	0.339	No
	Right Tilt	0.030	0.188	0.214	0.218	0.244	No



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM170400351906

Page: 67 of 74

LTE Band 4	Left Touch	0.111	0.188	0.515	0.299	0.626	No
	Left Tilt	0.039	0.188	0.337	0.227	0.376	No
	Right Touch	0.087	0.188	0.253	0.275	0.340	No
	Right Tilt	0.047	0.188	0.214	0.235	0.261	No
LTE Band 12	Left Touch	0.015	0.188	0.515	0.203	0.530	No
	Left Tilt	0.008	0.188	0.337	0.196	0.345	No
	Right Touch	0.010	0.188	0.253	0.198	0.263	No
	Right Tilt	0.007	0.188	0.214	0.195	0.221	No



3) Simultaneous Transmission SAR Summation Scenario for body worn

WWAN Band	Exposure position	① MAX. WWAN SAR(W/kg)	② MAX.BT SAR (W/kg)	③MAX. WLAN 5G SAR (W/kg)	Summed SAR ①+②	Summed SAR ①+③	Case NO.
GSM850	Front	0.020	0.063	0.041	0.083	0.061	No
	Back	0.024	0.063	0.020	0.087	0.044	No
GSM1900	Front	0.116	0.063	0.041	0.179	0.157	No
	Back	0.161	0.063	0.020	0.224	0.181	No
WCDMA Band II	Front	0.086	0.063	0.041	0.149	0.127	No
	Back	0.116	0.063	0.020	0.179	0.136	No
WCDMA Band IV	Front	0.092	0.063	0.041	0.155	0.133	No
	Back	0.137	0.063	0.020	0.200	0.157	No
CDMA BC0	Front	0.036	0.063	0.041	0.099	0.077	No
	Back	0.041	0.063	0.020	0.104	0.061	No
CDMA BC1	Front	0.086	0.063	0.041	0.149	0.127	No
	Back	0.115	0.063	0.020	0.178	0.135	No
LTE Band 2	Front	0.154	0.063	0.041	0.217	0.195	No
	Back	0.199	0.063	0.020	0.262	0.219	No
LTE Band 4	Front	0.164	0.063	0.041	0.227	0.205	No
	Back	0.223	0.063	0.020	0.286	0.243	No
LTE Band 12	Front	0.046	0.063	0.041	0.109	0.087	No
	Back	0.055	0.063	0.020	0.118	0.075	No



4) Simultaneous Transmission SAR Summation Scenario for hotspot

WWAN Band	Exposure position	①MAX .WWAN SAR (W/kg)	② MAX.BT SAR (W/kg)	③MAX.W LAN 5G SAR (W/kg)	Summed SAR ①+②	Summed SAR ①+③	Case NO.
GSM850	Front	0.070	0.094	0.102	0.164	0.172	No
	Back	0.096	0.094	0.072	0.190	0.168	No
	Left	0.033	0.094	0.000	0.127	0.033	No
	Right	0.017	0.094	0.014	0.111	0.031	No
	Top	0.000	0.094	0.046	0.094	0.046	No
	Bottom	0.052	0.094	0.000	0.146	0.052	No
GSM1900	Front	0.396	0.094	0.102	0.490	0.498	No
	Back	0.580	0.094	0.072	0.674	0.652	No
	Left	0.303	0.094	0.000	0.397	0.303	No
	Right	0.063	0.094	0.014	0.157	0.077	No
	Top	0.000	0.094	0.046	0.094	0.046	No
	Bottom	1.445	0.094	0.000	1.539	1.445	No
WCDMA Band II	Front	0.159	0.094	0.102	0.253	0.261	No
	Back	0.213	0.094	0.072	0.307	0.285	No
	Left	0.121	0.094	0.000	0.215	0.121	No
	Right	0.026	0.094	0.014	0.120	0.040	No
	Top	0.000	0.094	0.046	0.094	0.046	No
	Bottom	0.289	0.094	0.000	0.383	0.289	No
WCDMA Band IV	Front	0.189	0.094	0.102	0.283	0.291	No
	Back	0.262	0.094	0.072	0.356	0.334	No
	Left	0.137	0.094	0.000	0.231	0.137	No
	Right	0.022	0.094	0.014	0.116	0.036	No
	Top	0.000	0.094	0.046	0.094	0.046	No
	Bottom	0.504	0.094	0.000	0.598	0.504	No
CDMA BC0	Front	0.062	0.094	0.102	0.156	0.164	No
	Back	0.076	0.094	0.072	0.170	0.148	No
	Left	0.028	0.094	0.000	0.122	0.028	No
	Right	0.013	0.094	0.014	0.107	0.027	No
	Top	0.000	0.094	0.046	0.094	0.046	No
	Bottom	0.040	0.094	0.000	0.134	0.040	No



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM170400351906

Page: 70 of 74

CDMA BC1	Front	0.174	0.094	0.102	0.268	0.276	No
	Back	0.208	0.094	0.072	0.302	0.280	No
	Left	0.133	0.094	0.000	0.227	0.133	No
	Right	0.024	0.094	0.014	0.118	0.038	No
	Top	0.000	0.094	0.046	0.094	0.046	No
	Bottom	0.489	0.094	0.000	0.583	0.489	No
LTE Band 2	Front	0.265	0.094	0.102	0.359	0.367	No
	Back	0.344	0.094	0.072	0.438	0.416	No
	Left	0.190	0.094	0.000	0.284	0.190	No
	Right	0.044	0.094	0.014	0.138	0.058	No
	Top	0.000	0.094	0.046	0.094	0.046	No
	Bottom	0.739	0.094	0.000	0.833	0.739	No
LTE Band 4	Front	0.296	0.094	0.102	0.390	0.398	No
	Back	0.425	0.094	0.072	0.519	0.497	No
	Left	0.252	0.094	0.000	0.346	0.252	No
	Right	0.038	0.094	0.014	0.132	0.052	No
	Top	0.000	0.094	0.046	0.094	0.046	No
	Bottom	0.786	0.094	0.000	0.880	0.786	No
LTE Band 12	Front	0.073	0.094	0.102	0.167	0.175	No
	Back	0.096	0.094	0.072	0.190	0.168	No
	Left	0.026	0.094	0.000	0.120	0.026	No
	Right	0.016	0.094	0.014	0.110	0.030	No
	Top	0.000	0.094	0.046	0.094	0.046	No
	Bottom	0.063	0.094	0.000	0.157	0.063	No



6 Equipment list

Test Platform		SPEAG DASY5 Professional				
Location		SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch				
Description		SAR Test System (Frequency range 300MHz-6GHz)				
Software Reference		DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)				
Hardware Reference						
Equipment		Manufacturer	Model	Serial Number	Calibration Date	Due date of calibration
<input checked="" type="checkbox"/>	Robot	Staubli	RX90L	F03/5V32A1/A01	NCR	NCR
<input checked="" type="checkbox"/>	Twin Phantom	SPEAG	SAM 1	TP-1283	NCR	NCR
<input checked="" type="checkbox"/>	Twin Phantom	SPEAG	SAM 2	1913	NCR	NCR
<input type="checkbox"/>	DAE	SPEAG	DAE3	569	2016-12-09	2017-12-08
<input checked="" type="checkbox"/>	DAE	SPEAG	DAE4	1374	2017-02-23	2018-02-22
<input checked="" type="checkbox"/>	E-Field Probe	SPEAG	EX3DV4	3789	2017-01-13	2018-01-12
<input type="checkbox"/>	E-Field Probe	SPEAG	EX3DV4	3962	2016-12-19	2017-12-18
<input checked="" type="checkbox"/>	Validation Kits	SPEAG	D750V3	1160	2016-06-22	2019-06-21
<input checked="" type="checkbox"/>	Validation Kits	SPEAG	D835V2	4d105	2016-12-08	2019-12-07
<input checked="" type="checkbox"/>	Validation Kits	SPEAG	D1750V2	1149	2016-06-23	2019-06-22
<input checked="" type="checkbox"/>	Validation Kits	SPEAG	D1900V2	5d142	2016-06-23	2019-06-22
<input checked="" type="checkbox"/>	Validation Kits	SPEAG	D2450V2	733	2016-12-07	2019-12-06
<input type="checkbox"/>	Validation Kits	SPEAG	D2600V2	1125	2016-06-22	2019-06-21
<input checked="" type="checkbox"/>	Validation Kits	SPEAG	D5GHzV2	1165	2016-12-13	2017-12-12
<input checked="" type="checkbox"/>	Universal Radio Communication Tester	R&S	CMU200	123090	2016-06-27	2017-06-26
<input checked="" type="checkbox"/>	Universal Radio Communication Tester	R&S	CMW500	152271	2017-03-06	2018-03-05
<input checked="" type="checkbox"/>	Agilent Network Analyzer	Agilent	E5071C	MY46523590	2017-03-06	2018-03-05
<input checked="" type="checkbox"/>	Dielectric Probe Kit	Agilent	85070E	US01440210	NCR	NCR
<input checked="" type="checkbox"/>	RF Bi-Directional Coupler	Agilent	86205-60001	MY31400031	NCR	NCR
<input checked="" type="checkbox"/>	Signal Generator	Agilent	N5171B	MY53050736	2017-03-06	2018-03-05
<input checked="" type="checkbox"/>	Preamplifier	Mini-Circuits	ZHL-42W	15542	NCR	NCR
<input checked="" type="checkbox"/>	Power Meter	Agilent	E4416A	GB41292095	2017-03-06	2018-03-05
<input checked="" type="checkbox"/>	Power Sensor	Agilent	8481H	MY41091234	2017-03-05	2018-03-04
<input checked="" type="checkbox"/>	Power Sensor	R&S	NRP-Z92	100025	2017-03-06	2018-03-05
<input checked="" type="checkbox"/>	Attenuator	SHX	TS2-3dB	30704	NCR	NCR
<input checked="" type="checkbox"/>	Coaxial low pass filter	Mini-Circuits	VLF-2500(+)	NA	NCR	NCR
<input checked="" type="checkbox"/>	Coaxial low pass filter	Microlab Fxr	LA-F13	NA	NCR	NCR
<input checked="" type="checkbox"/>	50 Ω coaxial load	Mini-Circuits	KARN-50+	00850	NCR	NCR
<input checked="" type="checkbox"/>	DC POWER SUPPLY	SAKO	SK1730SL5A	NA	NCR	NCR
<input checked="" type="checkbox"/>	Speed reading thermometer	MingGao	T809	NA	2017-03-08	2018-03-07
<input checked="" type="checkbox"/>	Humidity and Temperature Indicator	KIMTOKA	KIMTOKA	NA	2017-03-08	2018-03-07

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only



7 Measurement Uncertainty

Measurements and results are all in compliance with the standards listed in this report. All measurements and results are recorded and maintained at the laboratory performing the tests and measurement uncertainties are taken into account when comparing measurements to pass/ fail criteria. The Expanded uncertainty (95% CONFIDENCE INTERVAL) is **21.60%**.

A	b1	c	d	e = f(d,k)	g	i = C*g/e	k
Uncertainty Component	Section in P1528	Tol (%)	Prob . Dist.	Div.	Ci (1g)	1g ui (%)	Vi (Veff)
Probe calibration	E.2.1	6.3	N	1	1	6.30	∞
Axial isotropy	E.2.2	0.5	R	$\sqrt{3}$	$(1 - C_p)1/2$	0.20	∞
hemispherical isotropy	E.2.2	2.6	R	$\sqrt{3}$	$\sqrt{C_p}$	1.06	∞
Boundary effect	E.2.3	1.0	R	$\sqrt{3}$	1	0.58	∞
Linearity	E.2.4	0.6	R	$\sqrt{3}$	1	0.35	∞
System detection limit	E.2.5	0.25	R	$\sqrt{3}$	1	0.14	∞
Readout electronics	E.2.6	0.3	N	1	1	0.30	∞
Response time	E.2.7	0	R	$\sqrt{3}$	1	0.00	∞
Integration time	E.2.8	2.6	R	$\sqrt{3}$	1	1.50	∞
RF ambient Condition –Noise	E.6.1	3	R	$\sqrt{3}$	1	1.73	∞
RF ambient Condition - reflections	E.6.1	3	R	$\sqrt{3}$	1	1.73	∞
Probe positioning- mechanical tolerance	E.6.2	1.5	R	$\sqrt{3}$	1	0.87	∞
Probe positioning- with respect to phantom	E.6.3	2.9	R	$\sqrt{3}$	1	1.67	∞
Max. SAR evaluation	E.5.2	1	R	$\sqrt{3}$	1	0.58	∞
Test sample positioning	E.4.2	3.7	N	1	1	3.70	9
Device holder uncertainty	E.4.1	3.6	N	1	1	3.60	∞
Output power variation –SAR drift measurement	6.6.2	5	R	$\sqrt{3}$	1	2.89	∞
Phantom uncertainty (shape and thickness tolerances)	E.3.1	4	R	$\sqrt{3}$	1	2.31	∞
Liquid conductivity - deviation from target values	E.3.2	5	R	$\sqrt{3}$	0.64	1.85	∞
Liquid conductivity - measurement uncertainty	E.3.2	5.78	N	1	0.64	3.68	5
Liquid permittivity - deviation from target values	E.3.3	5	R	$\sqrt{3}$	0.6	1.73	∞



Liquid permittivity - measurement uncertainty	E.3.3	0.62	N	1	0.6	0.372	5
Combined standard uncertainty				RSS		10.80	430
Expanded uncertainty (95% CONFIDENCE INTERVAL)				K=2		21.60	

Table 25 : Measurement Uncertainty

8 Calibration certificate

Please see the Appendix C

9 Photographs

Please see the Appendix D



Appendix A: Detailed System Validation Results

Appendix B: Detailed Test Results

Appendix C: Calibration certificate

Appendix D: Photographs

---END---



Appendix A

Detailed System Validation Results

1. System Performance Check for Head
System Performance Check 750 MHz Head
System Performance Check 835 MHz Head
System Performance Check 1750 MHz Head
System Performance Check 1900 MHz Head
System Performance Check 5GHz Head
2. System Performance Check for Body
System Performance Check 750 MHz Body
System Performance Check 835 MHz Body
System Performance Check 1750 MHz Body
System Performance Check 1900 MHz Body
System Performance Check 5GHz Body

Test Laboratory: SGS-SAR Lab

System Performance Check 750 MHz Head

DUT: D750V3; Type: D750V3; Serial: 1160

Communication System: UID 0, CW (0); Frequency: 750 MHz; Duty Cycle: 1:1

Medium: HSL750; Medium parameters used: $f = 750$ MHz; $\sigma = 0.895$ S/m; $\epsilon_r = 41.649$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3789; ConvF(8.89, 8.89, 8.89); Calibrated: 2017-01-13;
- Sensor-Surface: 2mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn1374; Calibrated: 2016-08-23
- Phantom: SAM2; Type: SAM; Serial: 1913
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Body/d=15mm, Pin=250mW/Area Scan (7x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 2.34 W/kg


Body/d=15mm, Pin=250mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 52.02 V/m; Power Drift = -0.00 dB

Peak SAR (extrapolated) = 3.29 W/kg

SAR(1 g) = 2.14 W/kg; SAR(10 g) = 1.5 W/kg

Maximum value of SAR (measured) = 2.40 W/kg



0 dB = 2.40 W/kg = 3.80 dBW/kg

Test Laboratory: SGS-SAR Lab

System Performance Check 750 MHz Body

DUT: D750V3; Type: D750V3; Serial: 1160

Communication System: UID 0, CW (0); Frequency: 750 MHz; Duty Cycle: 1:1

Medium: MSL750; Medium parameters used: $f = 750$ MHz; $\sigma = 0.972$ S/m; $\epsilon_r = 56.463$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3789; ConvF(9.13, 9.13, 9.13); Calibrated: 2017-01-13;
- Sensor-Surface: 2mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn1374; Calibrated: 2016-08-23
- Phantom: SAM 1; Type: SAM V4.0; Serial: TP-1283
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Body/d=15mm, Pin=250mW/Area Scan (7x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 2.47 W/kg


Body/d=15mm, Pin=250mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 51.33 V/m; Power Drift = -0.00 dB

Peak SAR (extrapolated) = 3.46 W/kg

SAR(1 g) = 2.26 W/kg; SAR(10 g) = 1.58 W/kg

Maximum value of SAR (measured) = 2.53 W/kg



0 dB = 2.53 W/kg = 4.03 dBW/kg

Test Laboratory: SGS-SAR Lab

System Performance Check 835 MHz Head

DUT: D835V2; Type: D835V2; Serial: 4d120

Communication System: UID 0, CW (0); Frequency: 835 MHz; Duty Cycle: 1:1

Medium: HSL835; Medium parameters used: $f = 835$ MHz; $\sigma = 0.909$ S/m; $\epsilon_r = 42.04$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3789; ConvF(8.61, 8.61, 8.61); Calibrated: 2017-01-13;
- Sensor-Surface: 2mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn1374; Calibrated: 2016-08-23
- Phantom: SAM2; Type: SAM; Serial: 1913
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Body/d=15mm, Pin=250mW/Area Scan (7x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 2.53 W/kg


Body/d=15mm, Pin=250mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 54.64 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 3.42 W/kg

SAR(1 g) = 2.35 W/kg; SAR(10 g) = 1.58 W/kg

Maximum value of SAR (measured) = 2.54 W/kg



0 dB = 2.54 W/kg = 4.05 dBW/kg

Test Laboratory: SGS-SAR Lab

System Performance Check 835 MHz Body

DUT: D835V2; Type: D835V2; Serial: 4d105

Communication System: UID 0, CW (0); Frequency: 835 MHz; Duty Cycle: 1:1

Medium: MSL835; Medium parameters used: $f = 835$ MHz; $\sigma = 0.985$ S/m; $\epsilon_r = 53.807$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3789; ConvF(8.8, 8.8, 8.8); Calibrated: 2017-01-13;
- Sensor-Surface: 2mm (Mechanical Surface Detection), $z = -2.0, 31.0$
- Electronics: DAE4 Sn1374; Calibrated: 2016-08-23
- Phantom: SAM 1; Type: SAM V4.0; Serial: TP-1283
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Body/d=15mm, Pin=250mW/Area Scan (7x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 2.38 W/kg


Body/d=15mm, Pin=250mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 50.44 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 3.26 W/kg

SAR(1 g) = 2.27 W/kg; SAR(10 g) = 1.54 W/kg

Maximum value of SAR (measured) = 2.44 W/kg



0 dB = 2.44 W/kg = 3.87 dBW/kg

Test Laboratory: SGS-SAR Lab

System Performance Check 1750 MHz Head

DUT: D1750V2; Type: D1750V2; Serial: 1149

Communication System: UID 0, CW (0); Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: HSL1750; Medium parameters used: $f = 1750$ MHz; $\sigma = 1.332$ S/m; $\epsilon_r = 40.757$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3789; ConvF(7.55, 7.55, 7.55); Calibrated: 2017-01-13;
- Sensor-Surface: 2mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn1374; Calibrated: 2016-08-23
- Phantom: SAM 1; Type: SAM V4.0; Serial: TP-1283
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Body/d=10mm, Pin=250mW/Area Scan (7x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 8.83 W/kg


Body/d=10mm, Pin=250mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 86.67 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 16.0 W/kg

SAR(1 g) = 8.91 W/kg; SAR(10 g) = 4.76 W/kg

Maximum value of SAR (measured) = 9.97 W/kg



0 dB = 9.97 W/kg = 9.99 dBW/kg

Test Laboratory: SGS-SAR Lab

System Performance Check 1750 MHz Body

DUT: D1750V2; Type: D1750V2; Serial: 1149

Communication System: UID 0, CW (0); Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: MSL1750; Medium parameters used: $f = 1750$ MHz; $\sigma = 1.537$ S/m; $\epsilon_r = 53.088$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3789; ConvF(7.36, 7.36, 7.36); Calibrated: 2017-01-13;
- Sensor-Surface: 2mm (Mechanical Surface Detection), $z = -2.0, 31.0$
- Electronics: DAE4 Sn1374; Calibrated: 2016-08-23
- Phantom: SAM 1; Type: SAM V4.0; Serial: TP-1283
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Body/d=10mm, Pin=250mW/Area Scan (7x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 10.1 W/kg


Body/d=10mm, Pin=250mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 85.30 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 18.1 W/kg

SAR(1 g) = 10.1 W/kg; SAR(10 g) = 5.42 W/kg

Maximum value of SAR (measured) = 11.3 W/kg



0 dB = 11.3 W/kg = 10.53 dBW/kg

Test Laboratory: SGS-SAR Lab

System Performance Check 1900 MHz Head

DUT: D1900V2; Type: D1900V2; Serial: 5d028

Communication System: UID 0, CW (0); Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: HSL1900; Medium parameters used: $f = 1900$ MHz; $\sigma = 1.373$ S/m; $\epsilon_r = 40.58$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3789; ConvF(7.37, 7.37, 7.37); Calibrated: 2017-01-13;
- Sensor-Surface: 2mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn1374; Calibrated: 2016-08-23
- Phantom: SAM2; Type: SAM; Serial: 1913
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Body/d=10mm, Pin=250mW/Area Scan (7x11x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 10.1 W/kg


Body/d=10mm, Pin=250mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 84.45 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 17.5 W/kg

SAR(1 g) = 9.45 W/kg; SAR(10 g) = 4.9 W/kg

Maximum value of SAR (measured) = 10.7 W/kg



0 dB = 10.7 W/kg = 10.29 dBW/kg

Test Laboratory: SGS-SAR Lab

System Performance Check 1900 MHz Body

DUT: D1900V2; Type: D1900V2; Serial: 5d028

Communication System: UID 0, CW (0); Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: MSL1900; Medium parameters used: $f = 1900$ MHz; $\sigma = 1.51$ S/m; $\epsilon_r = 53.234$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3789; ConvF(7.06, 7.06, 7.06); Calibrated: 2017-01-13;
- Sensor-Surface: 2mm (Mechanical Surface Detection), $z = -2.0, 31.0$
- Electronics: DAE4 Sn1374; Calibrated: 2016-08-23
- Phantom: SAM2; Type: SAM; Serial: 1913
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Body/d=10mm, Pin=250mW/Area Scan (7x11x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 11.4 W/kg

Body/d=10mm, Pin=250mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 89.22 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 21.3 W/kg

SAR(1 g) = 10.9 W/kg; SAR(10 g) = 5.49 W/kg

Maximum value of SAR (measured) = 12.1 W/kg



0 dB = 12.1 W/kg = 10.83 dBW/kg

Test Laboratory: SGS-SAR Lab

System Performance Check D5.25GHz Head

DUT: D5GHzV2; Type: D5GHzV2; Serial: 1165

Communication System: UID 0, CW (0); Frequency: 5250 MHz; Duty Cycle: 1:1

Medium: HSL5GHz; Medium parameters used: $f = 5250$ MHz; $\sigma = 4.629$ S/m; $\epsilon_r = 35.566$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3789; ConvF(5, 5, 5); Calibrated: 2017-01-13;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = -2.0, 31.0$
- Electronics: DAE4 Sn1374; Calibrated: 2016-08-23
- Phantom: SAM2; Type: SAM; Serial: 1913
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Body/d=10mm, Pin=100mW, f=5250 MHz/Area Scan (10x10x1): Measurement grid:

$dx=10$ mm, $dy=10$ mm

Maximum value of SAR (measured) = 12.0 W/kg


Body/d=10mm, Pin=100mW, f=5250 MHz/Zoom Scan (4x4x1.4mm, graded), dist=1.4mm (8x8x7)/Cube 0: Measurement grid: $dx=4$ mm, $dy=4$ mm, $dz=1.4$ mm

Reference Value = 66.58 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 28.8 W/kg

SAR(1 g) = 6.96 W/kg; SAR(10 g) = 1.98 W/kg

Maximum value of SAR (measured) = 16.4 W/kg



Test Laboratory: SGS-SAR Lab

System Performance Check D5.25GHz Body

DUT: D5GHzV2; Type: D5GHzV2; Serial: 1165

Communication System: UID 0, CW (0); Frequency: 5250 MHz; Duty Cycle: 1:1

Medium: MSL5GHz; Medium parameters used: $f = 5250$ MHz; $\sigma = 5.344$ S/m; $\epsilon_r = 49.767$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3789; ConvF(4.64, 4.64, 4.64); Calibrated: 2017-01-13;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = -2.0, 31.0$
- Electronics: DAE4 Sn1374; Calibrated: 2016-08-23
- Phantom: ELI V5.0; Type: ELI; Serial: 1128
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Body/d=10mm, Pin=100mW, f=5250 MHz/Area Scan (10x10x1): Measurement grid:

$dx=10$ mm, $dy=10$ mm

Maximum value of SAR (measured) = 21.4 W/kg


Body/d=10mm, Pin=100mW, f=5250 MHz/Zoom Scan (4x4x1.4mm, graded), dist=1.4mm (8x8x7)/Cube 0: Measurement grid: $dx=4$ mm, $dy=4$ mm, $dz=1.4$ mm

Reference Value = 53.77 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 35.8 W/kg

SAR(1 g) = 7.97 W/kg; SAR(10 g) = 2.22 W/kg

Maximum value of SAR (measured) = 19.6 W/kg



0 dB = 19.6 W/kg = 12.92 dBW/kg

Test Laboratory: SGS-SAR Lab

System Performance Check D5.6GHz Head

DUT: D5GHzV2; Type: D5GHzV2; Serial: 1165

Communication System: UID 0, CW (0); Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: HSL5GHz; Medium parameters used: $f = 5600$ MHz; $\sigma = 5.096$ S/m; $\epsilon_r = 34.894$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3789; ConvF(4.48, 4.48, 4.48); Calibrated: 2017-01-13;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = -2.0, 31.0$
- Electronics: DAE4 Sn1374; Calibrated: 2016-08-23
- Phantom: SAM2; Type: SAM; Serial: 1913
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Body/d=10mm, Pin=100mW, f=5600 MHz/Area Scan (10x10x1): Measurement grid:

$dx=10$ mm, $dy=10$ mm

Maximum value of SAR (measured) = 16.4 W/kg


Body/d=10mm, Pin=100mW, f=5600 MHz/Zoom Scan (4x4x1.4mm, graded), dist=1.4mm (8x8x7)/Cube 0: Measurement grid: $dx=4$ mm, $dy=4$ mm, $dz=1.4$ mm

Reference Value = 63.24 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 34.7 W/kg

SAR(1 g) = 7.65 W/kg; SAR(10 g) = 2.16 W/kg

Maximum value of SAR (measured) = 19.2 W/kg



0 dB = 19.2 W/kg = 12.83 dBW/kg

Test Laboratory: SGS-SAR Lab

System Performance Check D5.6GHz Body

DUT: D5GHzV2; Type: D5GHzV2; Serial: 1165

Communication System: UID 0, CW (0); Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: MSL5GHz; Medium parameters used: $f = 5600$ MHz; $\sigma = 5.72$ S/m; $\epsilon_r = 48.938$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3789; ConvF(3.86, 3.86, 3.86); Calibrated: 2017-01-13;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = -2.0, 31.0$
- Electronics: DAE4 Sn1374; Calibrated: 2016-08-23
- Phantom: ELI V5.0; Type: ELI; Serial: 1128
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Body/d=10mm, Pin=100mW, f=5600 MHz/Area Scan (10x10x1): Measurement grid:

$dx=10$ mm, $dy=10$ mm

Maximum value of SAR (measured) = 22.7 W/kg


Body/d=10mm, Pin=100mW, f=5600 MHz/Zoom Scan (4x4x1.4mm, graded), dist=1.4mm (8x8x7)/Cube 0: Measurement grid: $dx=4$ mm, $dy=4$ mm, $dz=1.4$ mm

Reference Value = 54.37 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 38.8 W/kg

SAR(1 g) = 8.29 W/kg; SAR(10 g) = 2.29 W/kg

Maximum value of SAR (measured) = 20.8 W/kg



0 dB = 20.8 W/kg = 13.18 dBW/kg



Appendix B

Detailed Test Results

1. GSM
GSM850 for Head &Body
GSM1900 for Head &Body
2. WCDMA
WCDMA Band II for Head &Body
WCDMA Band IV for Head &Body
3. CDMA
CDMA BC0 for Head &Body
CDMA BC1 for Head &Body
4. LTE
LTE Band 2
LTE Band 4
LTE Band 12
5. WIFI
WIFI 5G for Head &Body

Test Laboratory: SGS-SAR Lab

SG02 GSM850 190CH Left touch cheek

DUT: SG02; Type: Saygus smartphone V-Squared; Serial: aace4052

Communication System: UID 0, GSM Only Communication System (0); Frequency: 836.6 MHz; Duty Cycle: 1:8.30042

Medium: HSL835; Medium parameters used: $f = 837$ MHz; $\sigma = 0.897$ S/m; $\epsilon_r = 41.911$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3789; ConvF(8.61, 8.61, 8.61); Calibrated: 2017-01-13;
- Sensor-Surface: 2mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn1374; Calibrated: 2016-08-23
- Phantom: SAM2; Type: SAM; Serial: 1913
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Head/Area Scan (8x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm
Maximum value of SAR (measured) = 0.00941 W/kg


Configuration/Head/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 1.026 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.0110 W/kg

SAR(1 g) = 0.00781 W/kg; SAR(10 g) = 0.0053 W/kg

Maximum value of SAR (measured) = 0.00959 W/kg



0 dB = 0.00959 W/kg = -20.18 dBW/kg

Test Laboratory: SGS-SAR Lab

SG02 GSM850 GSM 190CH Back side 15mm

DUT: SG02; Type: Saygus smartphone V-Squared; Serial: aaee4052

Communication System: UID 0, GSM Only Communication System (0); Frequency: 836.6 MHz; Duty Cycle: 1:8.30042

Medium: MSL835; Medium parameters used: $f = 837$ MHz; $\sigma = 0.982$ S/m; $\epsilon_r = 53.849$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3789; ConvF(8.8, 8.8, 8.8); Calibrated: 2017-01-13;
- Sensor-Surface: 2mm (Mechanical Surface Detection), $z = -2.0, 31.0$
- Electronics: DAE4 Sn1374; Calibrated: 2016-08-23
- Phantom: SAM 1; Type: SAM V4.0; Serial: TP-1283
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Body/Area Scan (8x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm
Maximum value of SAR (measured) = 0.0248 W/kg


Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 2.605 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 0.0290 W/kg

SAR(1 g) = 0.021 W/kg; SAR(10 g) = 0.014 W/kg

Maximum value of SAR (measured) = 0.0252 W/kg



0 dB = 0.0252 W/kg = -15.99 dBW/kg

Test Laboratory: SGS-SAR Lab

SG02 GSM850 GPRS 4TS 190CH Back side 10mm

DUT: SG02; Type: Saygus smartphone V-Squared; Serial: aaee4052

Communication System: UID 0, GPRS/EGPRS Mode(4up) Communication System (0); Frequency: 836.6 MHz; Duty Cycle: 1:2.0797

Medium: MSL835; Medium parameters used: $f = 837$ MHz; $\sigma = 0.982$ S/m; $\epsilon_r = 53.849$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3789; ConvF(8.8, 8.8, 8.8); Calibrated: 2017-01-13;
- Sensor-Surface: 2mm (Mechanical Surface Detection), $z = -2.0, 31.0$
- Electronics: DAE4 Sn1374; Calibrated: 2016-08-23
- Phantom: SAM 1; Type: SAM V4.0; Serial: TP-1283
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Body/Area Scan (8x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm
Maximum value of SAR (measured) = 0.100 W/kg


Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 9.491 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 0.121 W/kg

SAR(1 g) = 0.083 W/kg; SAR(10 g) = 0.055 W/kg

Maximum value of SAR (measured) = 0.101 W/kg



0 dB = 0.101 W/kg = -9.96 dBW/kg

Test Laboratory: SGS-SAR Lab

SG02 GSM1900 661CH Right touch cheek

DUT: SG02; Type: Saygus smartphone V-Squared; Serial: aaee4052

Communication System: UID 0, GSM Only Communication System (0); Frequency: 1880 MHz; Duty Cycle: 1:8.30042

Medium: HSL1900; Medium parameters used: $f = 1880$ MHz; $\sigma = 1.368$ S/m; $\epsilon_r = 40.662$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3789; ConvF(7.37, 7.37, 7.37); Calibrated: 2017-01-13;
- Sensor-Surface: 2mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn1374; Calibrated: 2016-08-23
- Phantom: SAM2; Type: SAM; Serial: 1913
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Head/Area Scan (8x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm
Maximum value of SAR (measured) = 0.0831 W/kg


Configuration/Head/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 3.270 V/m; Power Drift = 0.17 dB

Peak SAR (extrapolated) = 0.112 W/kg

SAR(1 g) = 0.075 W/kg; SAR(10 g) = 0.047 W/kg

Maximum value of SAR (measured) = 0.0947 W/kg



0 dB = 0.0947 W/kg = -10.24 dBW/kg

Test Laboratory: SGS-SAR Lab

SG02 GSM1900 661CH Back side 15mm

DUT: SG02; Type: Saygus smartphone V-Squared; Serial: aaee4052

Communication System: UID 0, GSM Only Communication System (0); Frequency: 1880 MHz; Duty Cycle: 1:8.30042

Medium: MSL1900; Medium parameters used: $f = 1880$ MHz; $\sigma = 1.502$ S/m; $\epsilon_r = 53.457$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3789; ConvF(7.06, 7.06, 7.06); Calibrated: 2017-01-13;
- Sensor-Surface: 2mm (Mechanical Surface Detection), $z = -2.0, 31.0$
- Electronics: DAE4 Sn1374; Calibrated: 2016-08-23
- Phantom: SAM2; Type: SAM; Serial: 1913
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Body/Area Scan (8x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm
Maximum value of SAR (measured) = 0.185 W/kg


Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 6.430 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 0.229 W/kg

SAR(1 g) = 0.151 W/kg; SAR(10 g) = 0.095 W/kg

Maximum value of SAR (measured) = 0.192 W/kg



0 dB = 0.192 W/kg = -7.17 dBW/kg

Test Laboratory: SGS-SAR Lab

SG02 GSM1900 GPRS 2TS 512CH Bottom side 10mm

DUT: SG02; Type: Saygus smartphone V-Squared; Serial: aaee4052

Communication System: UID 0, GPRS/EGPRS Mode(2up) Communication System (0); Frequency: 1850.2 MHz; Duty Cycle: 1:4.14954

Medium: MSL1900; Medium parameters used (interpolated): $f = 1850.2$ MHz; $\sigma = 1.479$ S/m; $\epsilon_r = 53.547$; $\rho = 1000$ kg/m³
Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3789; ConvF(7.06, 7.06, 7.06); Calibrated: 2017-01-13;
- Sensor-Surface: 2mm (Mechanical Surface Detection), $z = -2.0, 31.0$
- Electronics: DAE4 Sn1374; Calibrated: 2016-08-23
- Phantom: SAM2; Type: SAM; Serial: 1913
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Body/Area Scan (5x9x1): Measurement grid: $dx=15$ mm, $dy=15$ mm
Maximum value of SAR (measured) = 1.54 W/kg


Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 26.56 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 2.03 W/kg

SAR(1 g) = 1.27 W/kg; SAR(10 g) = 0.722 W/kg

Maximum value of SAR (measured) = 1.67 W/kg



0 dB = 1.67 W/kg = 2.23 dBW/kg

Test Laboratory: SGS-SAR Lab

SG02 WCDMA Band II RMC 9400CH Right touch cheek

DUT: SG02; Type: Saygus smartphone V-Squared; Serial: aace4052

Communication System: UID 0, WCDMA (0); Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: HSL1900; Medium parameters used: $f = 1880$ MHz; $\sigma = 1.368$ S/m; $\epsilon_r = 40.662$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3789; ConvF(7.37, 7.37, 7.37); Calibrated: 2017-01-13;
- Sensor-Surface: 2mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn1374; Calibrated: 2016-08-23
- Phantom: SAM2; Type: SAM; Serial: 1913
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Head/Area Scan (8x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm
Maximum value of SAR (measured) = 0.0460 W/kg


Configuration/Head/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 2.522 V/m; Power Drift = -0.14 dB

Peak SAR (extrapolated) = 0.0640 W/kg

SAR(1 g) = 0.042 W/kg; SAR(10 g) = 0.027 W/kg

Maximum value of SAR (measured) = 0.0536 W/kg



0 dB = 0.0536 W/kg = -12.71 dBW/kg

Test Laboratory: SGS-SAR Lab

SG02 WCDMA Band II RMC 9400CH Back side 15mm

DUT: SG02; Type: Saygus smartphone V-Squared; Serial: aaee4052

Communication System: UID 0, WCDMA (0); Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: MSL1900; Medium parameters used: $f = 1880$ MHz; $\sigma = 1.502$ S/m; $\epsilon_r = 53.457$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3789; ConvF(7.06, 7.06, 7.06); Calibrated: 2017-01-13;
- Sensor-Surface: 2mm (Mechanical Surface Detection), $z = -2.0, 31.0$
- Electronics: DAE4 Sn1374; Calibrated: 2016-08-23
- Phantom: SAM2; Type: SAM; Serial: 1913
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Body/Area Scan (8x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm
Maximum value of SAR (measured) = 0.120 W/kg


Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 3.900 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 0.156 W/kg

SAR(1 g) = 0.104 W/kg; SAR(10 g) = 0.066 W/kg

Maximum value of SAR (measured) = 0.132 W/kg



0 dB = 0.132 W/kg = -8.79 dBW/kg

Test Laboratory: SGS-SAR Lab

SG02 WCDMA Band II RMC 9400CH Bottom side 10mm

DUT: SG02; Type: Saygus smartphone V-Squared; Serial: aaee4052

Communication System: UID 0, WCDMA (0); Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: MSL1900; Medium parameters used: $f = 1880$ MHz; $\sigma = 1.502$ S/m; $\epsilon_r = 53.457$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3789; ConvF(7.06, 7.06, 7.06); Calibrated: 2017-01-13;
- Sensor-Surface: 2mm (Mechanical Surface Detection), $z = -2.0, 31.0$
- Electronics: DAE4 Sn1374; Calibrated: 2016-08-23
- Phantom: SAM2; Type: SAM; Serial: 1913
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Body/Area Scan (5x9x1): Measurement grid: $dx=15$ mm, $dy=15$ mm
Maximum value of SAR (measured) = 0.345 W/kg


Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 13.02 V/m; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 0.419 W/kg

SAR(1 g) = 0.260 W/kg; SAR(10 g) = 0.149 W/kg

Maximum value of SAR (measured) = 0.347 W/kg



0 dB = 0.347 W/kg = -4.60 dBW/kg

Test Laboratory: SGS-SAR Lab

SG02 WCDMA Band IV RMC 1412CH Left touch cheek

DUT: SG02; Type: Saygus smartphone V-Squared; Serial: aace4052

Communication System: UID 0, WCDMA (0); Frequency: 1732.4 MHz; Duty Cycle: 1:1

Medium: HSL1750; Medium parameters used (interpolated): $f = 1732.4$ MHz; $\sigma = 1.32$ S/m; $\epsilon_r = 40.669$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3789; ConvF(7.55, 7.55, 7.55); Calibrated: 2017-01-13;
- Sensor-Surface: 2mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn1374; Calibrated: 2016-08-23
- Phantom: SAM 1; Type: SAM V4.0; Serial: TP-1283
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Head/Area Scan (8x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm
Maximum value of SAR (measured) = 0.0772 W/kg


Configuration/Head/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 2.624 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 0.0990 W/kg

SAR(1 g) = 0.067 W/kg; SAR(10 g) = 0.042 W/kg

Maximum value of SAR (measured) = 0.0839 W/kg



0 dB = 0.0839 W/kg = -10.76 dBW/kg

Test Laboratory: SGS-SAR Lab

SG02 WCDMA Band IV RMC 1412CH Back side 15mm

DUT: SG02; Type: Saygus smartphone V-Squared; Serial: aace4052

Communication System: UID 0, WCDMA (0); Frequency: 1732.4 MHz; Duty Cycle: 1:1

Medium: MSL1750; Medium parameters used (interpolated): $f = 1732.4$ MHz; $\sigma = 1.523$ S/m; $\epsilon_r = 52.962$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3789; ConvF(7.36, 7.36, 7.36); Calibrated: 2017-01-13;
- Sensor-Surface: 2mm (Mechanical Surface Detection), $z = -2.0, 31.0$
- Electronics: DAE4 Sn1374; Calibrated: 2016-08-23
- Phantom: SAM 1; Type: SAM V4.0; Serial: TP-1283
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Body/Area Scan (8x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm
Maximum value of SAR (measured) = 0.147 W/kg


Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 3.541 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 0.180 W/kg

SAR(1 g) = 0.119 W/kg; SAR(10 g) = 0.074 W/kg

Maximum value of SAR (measured) = 0.152 W/kg



0 dB = 0.152 W/kg = -8.18 dBW/kg

Test Laboratory: SGS-SAR Lab

SG02 WCDMA Band IV RMC 1412CH Bottom side 10mm

DUT: SG02; Type: Saygus smartphone V-Squared; Serial: aace4052

Communication System: UID 0, WCDMA (0); Frequency: 1732.4 MHz; Duty Cycle: 1:1

Medium: MSL1750; Medium parameters used (interpolated): $f = 1732.4$ MHz; $\sigma = 1.523$ S/m; $\epsilon_r = 52.962$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3789; ConvF(7.36, 7.36, 7.36); Calibrated: 2017-01-13;
- Sensor-Surface: 2mm (Mechanical Surface Detection), $z = -2.0, 31.0$
- Electronics: DAE4 Sn1374; Calibrated: 2016-08-23
- Phantom: SAM 1; Type: SAM V4.0; Serial: TP-1283
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Body/Area Scan (5x9x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.580 W/kg


Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 17.78 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 0.720 W/kg

SAR(1 g) = 0.437 W/kg; SAR(10 g) = 0.245 W/kg

Maximum value of SAR (measured) = 0.582 W/kg



0 dB = 0.582 W/kg = -2.35 dBW/kg

Test Laboratory: SGS-SAR Lab

SG02 CDMA BC0 RC3 SO55 384CH Left touch cheek

DUT: SG02; Type: Saygus smartphone V-Squared; Serial: aaee4052

Communication System: UID 0, CDMA (0); Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium: HSL835; Medium parameters used: $f = 837$ MHz; $\sigma = 0.897$ S/m; $\epsilon_r = 41.911$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3789; ConvF(8.61, 8.61, 8.61); Calibrated: 2017-01-13;
- Sensor-Surface: 2mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn1374; Calibrated: 2016-08-23
- Phantom: SAM2; Type: SAM; Serial: 1913
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Head/Area Scan (8x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm
Maximum value of SAR (measured) = 0.0188 W/kg


Configuration/Head/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 0.6170 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 0.0200 W/kg

SAR(1 g) = 0.015 W/kg; SAR(10 g) = 0.011 W/kg

Maximum value of SAR (measured) = 0.0176 W/kg



0 dB = 0.0176 W/kg = -17.54 dBW/kg

Test Laboratory: SGS-SAR Lab

SG02 CDMA BC0 RC3 SO32 384CH Back side 15mm

DUT: SG02; Type: Saygus smartphone V-Squared; Serial: aace4052

Communication System: UID 0, CDMA (0); Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium: MSL835; Medium parameters used: $f = 837$ MHz; $\sigma = 0.982$ S/m; $\epsilon_r = 53.849$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3789; ConvF(8.8, 8.8, 8.8); Calibrated: 2017-01-13;
- Sensor-Surface: 2mm (Mechanical Surface Detection), $z = -2.0, 31.0$
- Electronics: DAE4 Sn1374; Calibrated: 2016-08-23
- Phantom: SAM 1; Type: SAM V4.0; Serial: TP-1283
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Body/Area Scan (8x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm
Maximum value of SAR (measured) = 0.0448 W/kg


Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 3.789 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.0530 W/kg

SAR(1 g) = 0.037 W/kg; SAR(10 g) = 0.026 W/kg

Maximum value of SAR (measured) = 0.0450 W/kg



0 dB = 0.0450 W/kg = -13.47 dBW/kg

Test Laboratory: SGS-SAR Lab

SG02 CDMA BC0 RC3 SO32 384CH Back side 10mm

DUT: SG02; Type: Saygus smartphone V-Squared; Serial: aaee4052

Communication System: UID 0, CDMA (0); Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium: MSL835; Medium parameters used: $f = 837$ MHz; $\sigma = 0.982$ S/m; $\epsilon_r = 53.849$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3789; ConvF(8.8, 8.8, 8.8); Calibrated: 2017-01-13;
- Sensor-Surface: 2mm (Mechanical Surface Detection), $z = -2.0, 31.0$
- Electronics: DAE4 Sn1374; Calibrated: 2016-08-23
- Phantom: SAM 1; Type: SAM V4.0; Serial: TP-1283
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Body/Area Scan (8x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm
Maximum value of SAR (measured) = 0.0822 W/kg


Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 8.304 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 0.100 W/kg

SAR(1 g) = 0.068 W/kg; SAR(10 g) = 0.045 W/kg

Maximum value of SAR (measured) = 0.0831 W/kg



0 dB = 0.0831 W/kg = -10.80 dBW/kg

Test Laboratory: SGS-SAR Lab

SG02 CDMA BC1 RC3 SO55 600CH Right touch cheek

DUT: SG02; Type: Saygus smartphone V-Squared; Serial: aaee4052

Communication System: UID 0, CDMA (0); Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: HSL1900; Medium parameters used: $f = 1880$ MHz; $\sigma = 1.368$ S/m; $\epsilon_r = 40.662$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3789; ConvF(7.37, 7.37, 7.37); Calibrated: 2017-01-13;
- Sensor-Surface: 2mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn1374; Calibrated: 2016-08-23
- Phantom: SAM2; Type: SAM; Serial: 1913
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Head/Area Scan (8x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm
Maximum value of SAR (measured) = 0.0686 W/kg


Configuration/Head/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 2.784 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.0940 W/kg

SAR(1 g) = 0.062 W/kg; SAR(10 g) = 0.038 W/kg

Maximum value of SAR (measured) = 0.0796 W/kg



0 dB = 0.0796 W/kg = -10.99 dBW/kg

Test Laboratory: SGS-SAR Lab

SG02 CDMA BC1 RC3 SO32 600CH Back side 15mm

DUT: SG02; Type: Saygus smartphone V-Squared; Serial: aaee4052

Communication System: UID 0, CDMA (0); Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: MSL1900; Medium parameters used: $f = 1880$ MHz; $\sigma = 1.502$ S/m; $\epsilon_r = 53.457$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3789; ConvF(7.06, 7.06, 7.06); Calibrated: 2017-01-13;
- Sensor-Surface: 2mm (Mechanical Surface Detection), $z = -2.0, 31.0$
- Electronics: DAE4 Sn1374; Calibrated: 2016-08-23
- Phantom: SAM2; Type: SAM; Serial: 1913
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Body/Area Scan (8x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm
Maximum value of SAR (measured) = 0.132 W/kg


Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 5.499 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.159 W/kg

SAR(1 g) = 0.105 W/kg; SAR(10 g) = 0.066 W/kg

Maximum value of SAR (measured) = 0.133 W/kg



0 dB = 0.133 W/kg = -8.76 dBW/kg

Test Laboratory: SGS-SAR Lab

SG02 CDMA BC1 RC3 SO32 600CH Bottom side 10mm

DUT: SG02; Type: Saygus smartphone V-Squared; Serial: aaee4052

Communication System: UID 0, CDMA (0); Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: MSL1900; Medium parameters used: $f = 1880$ MHz; $\sigma = 1.502$ S/m; $\epsilon_r = 53.457$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3789; ConvF(7.06, 7.06, 7.06); Calibrated: 2017-01-13;
- Sensor-Surface: 2mm (Mechanical Surface Detection), $z = -2.0, 31.0$
- Electronics: DAE4 Sn1374; Calibrated: 2016-08-23
- Phantom: SAM2; Type: SAM; Serial: 1913
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Body/Area Scan (5x8x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.528 W/kg


Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 17.74 V/m; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 0.718 W/kg

SAR(1 g) = 0.446 W/kg; SAR(10 g) = 0.253 W/kg

Maximum value of SAR (measured) = 0.599 W/kg



0 dB = 0.599 W/kg = -2.23 dBW/kg

Test Laboratory: SGS-SAR Lab

SG02 LTE Band 2 20MHz bandwidth QPSK 1RB0 Offset 18900CH Right touch cheek

DUT: SG02; Type: Saygus smartphone V-Squared; Serial: aace4052

Communication System: UID 0, LTE-FDD BW 20MHz (0); Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: HSL1900; Medium parameters used: $f = 1880$ MHz; $\sigma = 1.368$ S/m; $\epsilon_r = 40.662$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3789; ConvF(7.37, 7.37, 7.37); Calibrated: 2017-01-13;
- Sensor-Surface: 2mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn1374; Calibrated: 2016-08-23
- Phantom: SAM2; Type: SAM; Serial: 1913
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Head/Area Scan (8x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm
Maximum value of SAR (measured) = 0.0865 W/kg



Configuration/Head/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 3.101 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.118 W/kg

SAR(1 g) = 0.080 W/kg; SAR(10 g) = 0.051 W/kg

Maximum value of SAR (measured) = 0.101 W/kg



0 dB = 0.101 W/kg = -9.96 dBW/kg

Test Laboratory: SGS-SAR Lab

SG02 LTE Band 2 20MHz bandwidth QPSK 1RB0 Offset 18900CH Back side 15mm

DUT: SG02; Type: Saygus smartphone V-Squared; Serial: aace4052

Communication System: UID 0, LTE-FDD BW 20MHz (0); Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: MSL1900; Medium parameters used: $f = 1880$ MHz; $\sigma = 1.502$ S/m; $\epsilon_r = 53.457$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3789; ConvF(7.06, 7.06, 7.06); Calibrated: 2017-01-13;
- Sensor-Surface: 2mm (Mechanical Surface Detection), $z = -2.0, 31.0$
- Electronics: DAE4 Sn1374; Calibrated: 2016-08-23
- Phantom: SAM2; Type: SAM; Serial: 1913
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Body/Area Scan (8x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.210 W/kg


Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 4.982 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.280 W/kg

SAR(1 g) = 0.186 W/kg; SAR(10 g) = 0.118 W/kg

Maximum value of SAR (measured) = 0.238 W/kg



Test Laboratory: SGS-SAR Lab

SG02 LTE Band 2 20MHz bandwidth QPSK 1RB0 Offset 18900CH Bottom side 10mm

DUT: SG02; Type: Saygus smartphone V-Squared; Serial: aace4052

Communication System: UID 0, LTE-FDD BW 20MHz (0); Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: MSL1900; Medium parameters used: $f = 1880$ MHz; $\sigma = 1.502$ S/m; $\epsilon_r = 53.457$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3789; ConvF(7.06, 7.06, 7.06); Calibrated: 2017-01-13;
- Sensor-Surface: 2mm (Mechanical Surface Detection), $z = -2.0, 31.0$
- Electronics: DAE4 Sn1374; Calibrated: 2016-08-23
- Phantom: SAM2; Type: SAM; Serial: 1913
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Body/Area Scan (5x9x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.896 W/kg


Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 22.38 V/m; Power Drift = -0.00 dB

Peak SAR (extrapolated) = 1.11 W/kg

SAR(1 g) = 0.691 W/kg; SAR(10 g) = 0.393 W/kg

Maximum value of SAR (measured) = 0.921 W/kg



0 dB = 0.921 W/kg = -0.36 dBW/kg

Test Laboratory: SGS-SAR Lab

SG02 LTE Band 4 20MHz bandwidth QPSK 1RB0 Offset 20300CH Left touch cheek

DUT: SG02; Type: Saygus smartphone V-Squared; Serial: aace4052

Communication System: UID 0, LTE-FDD BW 20MHz (0); Frequency: 1745 MHz; Duty Cycle: 1:1

Medium: HSL1750; Medium parameters used: $f = 1745$ MHz; $\sigma = 1.342$ S/m; $\epsilon_r = 40.78$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3789; ConvF(7.55, 7.55, 7.55); Calibrated: 2017-01-13;
- Sensor-Surface: 2mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn1374; Calibrated: 2016-08-23
- Phantom: SAM 1; Type: SAM V4.0; Serial: TP-1283
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Head/Area Scan (8x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm
Maximum value of SAR (measured) = 0.118 W/kg


Configuration/Head/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 3.761 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.158 W/kg

SAR(1 g) = 0.107 W/kg; SAR(10 g) = 0.067 W/kg

Maximum value of SAR (measured) = 0.136 W/kg



0 dB = 0.136 W/kg = -8.66 dBW/kg

Test Laboratory: SGS-SAR Lab

SG02 LTE Band 4 20MHz bandwidth QPSK 1RB0 Offset 20300CH Back side 15mm

DUT: SG02; Type: Saygus smartphone V-Squared; Serial: aae4052

Communication System: UID 0, LTE-FDD BW 20MHz (0); Frequency: 1745 MHz; Duty Cycle: 1:1

Medium: MSL1750; Medium parameters used: $f = 1745$ MHz; $\sigma = 1.539$ S/m; $\epsilon_r = 53.057$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3789; ConvF(7.36, 7.36, 7.36); Calibrated: 2017-01-13;
- Sensor-Surface: 2mm (Mechanical Surface Detection), $z = -2.0, 31.0$
- Electronics: DAE4 Sn1374; Calibrated: 2016-08-23
- Phantom: SAM 1; Type: SAM V4.0; Serial: TP-1283
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Body/Area Scan (8x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.260 W/kg


Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 4.606 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.327 W/kg

SAR(1 g) = 0.216 W/kg; SAR(10 g) = 0.134 W/kg

Maximum value of SAR (measured) = 0.276 W/kg



Test Laboratory: SGS-SAR Lab

SG02 LTE Band 4 20MHz bandwidth QPSK 1RB0 Offset 20300CH Bottom side 10mm

DUT: SG02; Type: Saygus smartphone V-Squared; Serial: aace4052

Communication System: UID 0, LTE-FDD BW 20MHz (0); Frequency: 1745 MHz; Duty Cycle: 1:1

Medium: MSL1750; Medium parameters used: $f = 1745$ MHz; $\sigma = 1.539$ S/m; $\epsilon_r = 53.057$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3789; ConvF(7.36, 7.36, 7.36); Calibrated: 2017-01-13;
- Sensor-Surface: 2mm (Mechanical Surface Detection), $z = -2.0, 31.0$
- Electronics: DAE4 Sn1374; Calibrated: 2016-08-23
- Phantom: SAM 1; Type: SAM V4.0; Serial: TP-1283
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Body/Area Scan (5x9x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 1.02 W/kg


Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 23.31 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 1.24 W/kg

SAR(1 g) = 0.761 W/kg; SAR(10 g) = 0.429 W/kg

Maximum value of SAR (measured) = 1.01 W/kg



0 dB = 1.01 W/kg = 0.04 dBW/kg

Test Laboratory: SGS-SAR Lab

SG02 LTE Band 12 10MHz bandwidth QPSK 25RB25 Offset 23060CH Left touch cheek

DUT: SG02; Type: Saygus smartphone V-Squared; Serial: aace4052

Communication System: UID 0, LTE-FDD BW 10MHZ (0); Frequency: 704 MHz; Duty Cycle: 1:1

Medium: HSL750; Medium parameters used: $f = 704$ MHz; $\sigma = 0.863$ S/m; $\epsilon_r = 42.594$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3789; ConvF(8.89, 8.89, 8.89); Calibrated: 2017-01-13;
- Sensor-Surface: 2mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn1374; Calibrated: 2016-08-23
- Phantom: SAM2; Type: SAM; Serial: 1913
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Head/Area Scan (8x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm
Maximum value of SAR (measured) = 0.0200 W/kg



Configuration/Head/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 1.039 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.0240 W/kg

SAR(1 g) = 0.014 W/kg; SAR(10 g) = 0.00702 W/kg

Maximum value of SAR (measured) = 0.0203 W/kg



0 dB = 0.0203 W/kg = -16.93 dBW/kg

Test Laboratory: SGS-SAR Lab

SG02 LTE Band 12 10MHz bandwidth QPSK 1RB49 Offset 23060CH Back side 15mm

DUT: SG02; Type: Saygus smartphone V-Squared; Serial: aace4052

Communication System: UID 0, LTE-FDD BW 10MHZ (0); Frequency: 704 MHz; Duty Cycle: 1:1

Medium: MSL750; Medium parameters used: $f = 704 \text{ MHz}$; $\sigma = 0.932 \text{ S/m}$; $\epsilon_r = 56.855$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3789; ConvF(9.13, 9.13, 9.13); Calibrated: 2017-01-13;
- Sensor-Surface: 2mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn1374; Calibrated: 2016-08-23
- Phantom: SAM 1; Type: SAM V4.0; Serial: TP-1283
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Body/Area Scan (8x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 0.0580 W/kg


Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 4.744 V/m ; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 0.0710 W/kg

SAR(1 g) = 0.050 W/kg ; SAR(10 g) = 0.035 W/kg

Maximum value of SAR (measured) = 0.0612 W/kg



$0 \text{ dB} = 0.0612 \text{ W/kg} = -12.13 \text{ dBW/kg}$

Test Laboratory: SGS-SAR Lab

SG02 LTE Band 12 10MHz bandwidth QPSK 1RB49 Offset 23060CH Back side 10mm

DUT: SG02; Type: Saygus smartphone V-Squared; Serial: aace4052

Communication System: UID 0, LTE-FDD BW 10MHZ (0); Frequency: 704 MHz; Duty Cycle: 1:1

Medium: MSL750; Medium parameters used: $f = 704 \text{ MHz}$; $\sigma = 0.932 \text{ S/m}$; $\epsilon_r = 56.855$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3789; ConvF(9.13, 9.13, 9.13); Calibrated: 2017-01-13;
- Sensor-Surface: 2mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn1374; Calibrated: 2016-08-23
- Phantom: SAM 1; Type: SAM V4.0; Serial: TP-1283
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Body/Area Scan (8x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 0.107 W/kg



Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 5.439 V/m ; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.130 W/kg

SAR(1 g) = 0.088 W/kg ; SAR(10 g) = 0.058 W/kg

Maximum value of SAR (measured) = 0.109 W/kg



0 dB = 0.109 W/kg = -9.63 dBW/kg

Test Laboratory: SGS-SAR Lab

SG02 WIFI 802.11a 116CH Left touch cheek

DUT: SG02; Type: Saygus smartphone V-Squared; Serial: aaee4052

Communication System: UID 0, WI-FI(5GHz) (0); Frequency: 5580 MHz; Duty Cycle: 1:1

Medium: HSL5GHz; Medium parameters used: $f = 5580 \text{ MHz}$; $\sigma = 5.076 \text{ S/m}$; $\epsilon_r = 34.987$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3789; ConvF(4.48, 4.48, 4.48); Calibrated: 2017-01-13;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = -2.0, 31.0$
- Electronics: DAE4 Sn1374; Calibrated: 2016-08-23
- Phantom: SAM2; Type: SAM; Serial: 1913
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Head/Area Scan (11x18x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$
Maximum value of SAR (measured) = 1.19 W/kg


Configuration/Head/Zoom Scan (7x7x12)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=2\text{mm}$

Reference Value = 3.155 V/m ; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 2.25 W/kg

SAR(1 g) = 0.427 W/kg ; SAR(10 g) = 0.102 W/kg

Maximum value of SAR (measured) = 1.11 W/kg



0 dB = 1.11 W/kg = 0.45 dBW/kg

Test Laboratory: SGS-SAR Lab

SG02 WIFI 802.11a 52CH Front side 15mm

DUT: SG02; Type: Saygus smartphone V-Squared; Serial: aaee4052

Communication System: UID 0, WI-FI(5GHz) (0); Frequency: 5260 MHz; Duty Cycle: 1:1

Medium: MSL5GHz; Medium parameters used: $f = 5260$ MHz; $\sigma = 5.35$ S/m; $\epsilon_r = 49.725$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3789; ConvF(4.64, 4.64, 4.64); Calibrated: 2017-01-13;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = -2.0, 31.0$
- Electronics: DAE4 Sn1374; Calibrated: 2016-08-23
- Phantom: ELI V5.0; Type: ELI; Serial: 1128
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Body/Area Scan (11x19x1): Measurement grid: $dx=10$ mm, $dy=10$ mm
Maximum value of SAR (measured) = 0.0668 W/kg


Configuration/Body/Zoom Scan (7x7x12)/Cube 0: Measurement grid: $dx=4$ mm, $dy=4$ mm, $dz=2$ mm

Reference Value = 1.474 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 0.121 W/kg

SAR(1 g) = 0.034 W/kg; SAR(10 g) = 0.016 W/kg

Maximum value of SAR (measured) = 0.0616 W/kg



0 dB = 0.0616 W/kg = -12.10 dBW/kg

Test Laboratory: SGS-SAR Lab

SG02 WIFI 802.11a 52CH Front side 10mm

DUT: SG02; Type: Saygus smartphone V-Squared; Serial: aaee4052

Communication System: UID 0, WI-FI(5GHz) (0); Frequency: 5180 MHz; Duty Cycle: 1:1

Medium: MSL5GHz; Medium parameters used: $f = 5180 \text{ MHz}$; $\sigma = 5.45 \text{ S/m}$; $\epsilon_r = 49.525$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY 5 Configuration:

- Probe: EX3DV4 - SN3789; ConvF(4.64, 4.64, 4.64); Calibrated: 2017-01-13;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = -2.0, 31.0$
- Electronics: DAE4 Sn1374; Calibrated: 2016-08-23
- Phantom: ELI V5.0; Type: ELI; Serial: 1128
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Body/Area Scan (11x19x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$
Maximum value of SAR (measured) = 0.155 W/kg

Configuration/Body/Zoom Scan (7x7x12)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=2\text{mm}$

Reference Value = 1.594 V/m ; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.357 W/kg

SAR(1 g) = 0.086 W/kg ; SAR(10 g) = 0.029 W/kg

Maximum value of SAR (measured) = 0.172 W/kg

