



Certificate No.: 3745.01



## FCC/ISED - TEST REPORT

Report Number : **709502405494-00A** Date of Issue: August 16, 2024

Model : TCS905-3S

Product Type : Wi-Fi and Bluetooth Module

Applicant : Hangzhou Tuya Information Technology Co.,Ltd

Address : Room 301, Building 1, Huace Center, Xihu District,  
Hangzhou City, Zhejiang Province, China

Production Facility : Hangzhou Tuya Information Technology Co.,Ltd

Address : Room 301, Building 1, Huace Center, Xihu District,  
Hangzhou City, Zhejiang Province, China

Test Result :  **Positive**  **Negative**

Total pages including Appendices : 24



*TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch is a subcontractor to TÜV SÜD Product Service GmbH according to the principles outlined in ISO 17025.*

*TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch reports apply only to the specific samples tested under stated test conditions. Construction of the actual test samples has been documented. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. The manufacturer/importer is responsible to the Competent Authorities in Europe for any modifications made to the production units which result in non-compliance to the relevant regulations. TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch shall have no liability for any deductions, inferences or generalizations drawn by the client or others from TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch issued reports.*

*This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval.*



## 1 Table of Contents

1	Table of Contents .....	2
2	Details about the Test Laboratory.....	3
3	Description of the Equipment under Test.....	4
4	Summary of Test Standards .....	6
5	Summary of Test Results .....	7
6	General Remarks .....	8
7	Test Setups .....	9
8	Systems test configuration .....	11
9	Technical Requirement.....	12
9.1	Conducted peak output power and EIRP.....	12
9.2	Spurious radiated emissions for transmitter.....	14
10	Test Equipment List.....	21
11	System Measurement Uncertainty .....	22
12	Photographs of Test Set-ups.....	23
13	Photographs of EUT .....	24



## 2 Details about the Test Laboratory

### Details about the Test Laboratory

#### Test Site 1

Company name: TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch  
No.16 Lane, 1951 Du Hui Road,  
Shanghai 201108,  
P.R. China

Telephone: +86 21 6141 0123

Fax: +86 21 6140 8600

FCC Registration No.: 820234

FCC Designation Number: CN1183

ISED CAB identifier: CN0101

IC Registration No.: 31668



### 3 Description of the Equipment under Test

Product:	Wi-Fi and Bluetooth Module
Model no.:	TCS905-3S
Hardware Version Identification No. (HVIN)	TCS905-3S
Product Marketing Name (PMN)	TCS905-3S
FCC ID:	2ANDL-TCS905-3S
IC:	23243-TCS9053S
Options and accessories:	NA
Rating:	DC 3.0-3.6V
RF Transmission Frequency:	For 802.11b/g/n(HT20): 2412~2462 MHz (Wi-Fi) For 802.15.1: 2402~2480 MHz
No. of Operated Channel:	2.4GHz WIFI: 11 for 802.11b/g/n(HT20) 2.4GHz BLE: 40
Modulation:	For 2.4GHz WIFI: Direct Sequence Spread Spectrum (DSSS) for 802.11b Orthogonal Frequency Division Multiplexing (OFDM) for 802.11g/n(HT20) For 2.4GHz BLE: GFSK, 1Mbps



Channel list:

802.11b/g/n(HT20)			
Ch	Fre(MHz)	Ch	Fre(MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437		

Bluetooth Low Energy							
Ch	Fre(MHz)	Ch	Fre(MHz)	Ch	Fre(MHz)	Ch	Fre(MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

Antenna Type: onboard PCB antenna

Antenna Gain: 1.3 dBi

Description of the EUT: The Equipment Under Test (EUT) is a low-power embedded Wi-Fi and Bluetooth module (5.1). We tested it and listed the worst data in this report.

Test sample no.: SHA-831078-1 (Conducted sample), SHA-831078-2 (Radiated sample)

The sample's mentioned in this report is/are submitted/ supplied/ manufactured by client. The laboratory therefore assumes no responsibility for accuracy of information on the brand name, model number, origin of manufacture, consignment, antenna gain or any information supplied.



## 4 Summary of Test Standards

Test Standards	
FCC Part 15 Subpart C 10-1-2023 Edition	PART 15 - RADIO FREQUENCY DEVICES Subpart C - Intentional Radiators
RSS-Gen Issue 5 April 2018 + Amendment 1 March 2019 + Amendment 2 February 2021	General Requirements for Compliance of Radio Apparatus
RSS-247 Issue 3 August 2023	Digital Transmission Systems (DTSS), Frequency Hopping Systems (FHSS) and License-Exempt Local Area Network (LE-LAN) Devices

All the test methods were according to KDB 558074 D01 15.247 Measurement Guidance v05r02 and ANSI C63.10 (2013).



## 5 Summary of Test Results

Technical Requirements							
FCC Part 15 Subpart C & RSS-247 Issue 3/RSS-Gen Issue 5							
Test Condition			Pages	Test Site	Test Result		
					Pass	Fail	N/A
§15.247 (b) (3)	RSS-247 5.4(d)	Conducted peak output power	12-13	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
	RSS-247 5.4(d)	Equivalent Isotropic Radiated Power		Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
§15.247(d) & §15.209 & §15.205	RSS-247 5.5 & RSS-Gen 6.13	Spurious radiated emissions for transmitter	14-20	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
§15.203	RSS-Gen 6.8	Antenna requirement	See note 1		<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

Remark 1: N/A-Not Applicable.

Note 1: The EUT uses an PCB antenna, which gain is 1.3 dBi. In accordance to §15.203, It is considered sufficiently to comply with the provisions of this section.

15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.



## 6 General Remarks

### Remarks

NOTICE: This report is a supplement of project 709502204666-00A and 709502204666-01A. So the report is not valid without the report of 709502204666-00A and 709502204666-01A.

This submittal(s) (test report) is intended for FCC ID: 2ANDL-TCS905-3S, IC: 23243-TCS9053S complies with Section 15.207, 15.209, 15.247 of the FCC Part 15, Subpart C Rules and RSS-247, RSS-GEN.

According to the client's declaration, the module optimizes and upgrades the antenna matching circuit. So in this test report only test data of "Conducted peak output power" and "Spurious radiated emissions for transmitter" was new data, other tests were referred from 709502204666-00A and 709502204666-01A, and the test data are still effective.

This report is only for the 2.4GHz Wi-Fi test report, for the 2.4GHz BLE test report please refer to 709502405494-00B.

According to the client's declaration, the "ILAC – A2LA Accredited" symbol is added to the report.

### SUMMARY:

All tests according to the regulations cited on page 6 were

■ - Performed

□ - **Not** Performed

The Equipment under Test

■ - **Fulfills** the general approval requirements.

□ - **Does not** fulfill the general approval requirements.

Sample Received Date: July 11, 2024

Testing Start Date: July 12, 2024

Testing End Date: August 9, 2024

-TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch

Reviewed by:

Prepared by:

Tested by:



Hui TONG  
Review Engineer

Jiaxi XU  
Project Engineer


Huali Cheng  
Test Engineer




## 7 Test Setups

### 7.1 Radiated test setups


9kHz ~ 30MHz Test Setup:




30MHz ~ 1GHz Test Setup:



1GHz ~ 18GHz Test Setup:




18GHz ~ 25GHz Test Setup:



7.3 Conducted RF test setups

For Conducted peak output power





## 8 Systems test configuration

Auxiliary Equipment Used during Test:

DESCRIPTION	MANUFACTURER	MODEL NO.(SHIELD)	S/N(LENGTH)
Notebook	Lenove	E470	PF-OU5TS7 17/09

Test software: Wifi Test Tool v1.6.0 release.

The system was configured to channel 1(2412MHz), 6(2437MHz), and 11(2462MHz) for 802.11 b/g/n(HT20) test.

Test Mode Applicability and Tested Channel Detail:

Mode	Tested Channel	Data Rate (Mbps)	Modulation	Index Value (Power level setting)
802.11b	1	1	CCK	14
	6	1	CCK	15
	11	1	CCK	18
802.11g	1	6	OFDM	32
	6	6	OFDM	34
	11	6	OFDM	39
802.11n HT20	1	MCS0	OFDM	28
	6	MCS0	OFDM	30
	11	MCS0	OFDM	35


Non-hopping mode: The system was configured to operate at a signal channel transmitting. The test software allows the configuration and operation at the worst-case duty and the highest transmit power.

## 9 Technical Requirement

### 9.1 Conducted peak output power

#### Test Method

- 1) The EUT is configured to transmit continuously, or to transmit with a constant duty cycle.
- 2) At all times when the EUT is transmitting, it shall be transmitting at its maximum power control level.
- 3) The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.
- 4) Measure the peak power of the transmitter. This measurement is a peak over both the ON and OFF periods of the transmitter.



**Wideband Power Sensor conducted test setup**

#### Limits

According to §15.247 (b) (3) & RSS-247 5.4(d), conducted peak output power limit as below:

Frequency Range MHz	Limit W	Limit dBm
2400-2483.5	≤1	≤30

Frequency Range MHz	Limit (EIRP) W	Limit dBm
2400-2483.5	≤4	≤36



Test result as below table

#### 802.11b modulation Test Result

Frequency (MHz)	Conducted Peak Output Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	Result
Low channel 2412MHz	17.58	1.3	18.88	Pass
Middle channel 2437MHz	17.46	1.3	18.76	Pass
High channel 2462MHz	17.98	1.3	19.28	Pass

#### 802.11g modulation Test Result

Frequency (MHz)	Conducted Peak Output Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	Result
Low channel 2412MHz	21.09	1.3	22.39	Pass
Middle channel 2437MHz	20.77	1.3	22.07	Pass
High channel 2462MHz	21.17	1.3	22.47	Pass

#### 802.11n20 modulation Test Result

Frequency (MHz)	Conducted Peak Output Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	Result
Low channel 2412MHz	20.42	1.3	21.72	Pass
Middle channel 2437MHz	20.28	1.3	21.58	Pass
High channel 2462MHz	20.73	1.3	22.03	Pass

## 9.2 Spurious radiated emissions for transmitter

### Test Method

1. The EUT was placed on a turn table which is 1.5m above ground plane for above 1GHz and 0.8m above ground for below 1GHz at 3meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference – receiving antenna, which was mounted on the top of a variable – height antenna tower.
3. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. Use the following spectrum analyzer settings According to C63.10
  - 1) Procedure for Unwanted Emissions Measurements Below 1000 MHz  
Span = wide enough to capture the peak level of the in-band emission and all spurious  
RBW = 100 kHz to 120kHz, VBW ≥ RBW for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.
  - 2) For Peak unwanted emissions Above 1GHz:  
Span = wide enough to capture the peak level of the in-band emission and all spurious  
RBW = 1MHz, VBW ≥ RBW for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.  
Procedures for average unwanted emissions measurements above 1GHz
    - a) RBW = 1MHz.
    - b) VBW \ [3 × RBW].
    - c) Detector = RMS (power averaging), if [span / (# of points in sweep)] \ RBW / 2.  
Satisfying this condition can require increasing the number of points in the sweep or reducing the span. If the condition is not satisfied, then the detector mode shall be set to peak.
    - d) Averaging type = power (i.e., rms) (As an alternative, the detector and averaging type may be set for linear voltage averaging. Some instruments require linear display mode to use linear voltage averaging. Log or dB averaging shall not be used.)
    - e) Sweep time = auto.
    - f) Perform a trace average of at least 100 traces if the transmission is continuous. If the transmission is not continuous, then the number of traces shall be increased by a factor of 1 / D, where D is the duty cycle. For example, with 50% duty cycle, at least 200 traces shall be averaged. (If a specific emission is demonstrated to be continuous—i.e., 100% duty cycle—then rather than turning ON and OFF with the transmit cycle, at least 100 traces shall be averaged.)
    - g) If tests are performed with the EUT transmitting at a duty cycle less than 98%, then a correction factor shall be added to the measurement results prior to comparing with the emission limit, to compute the emission level that would have been measured had the test been performed at 100% duty cycle. The correction factor is computed as follows:
      - 1) If power averaging (rms) mode was used in the preceding step e), then the correction factor is [10 log (1 / D)], where D is the duty cycle. For example, if the transmit duty cycle was 50%, then 3 dB shall be added to the measured emission levels.
      - 2) If linear voltage averaging mode was used in the preceding step e), then the correction



factor is  $[20 \log (1 / D)]$ , where D is the duty cycle. For example, if the transmit duty cycle was 50%, then 6 dB shall be added to the measured emission levels.

3) If a specific emission is demonstrated to be continuous (100% duty cycle) rather than turning ON and OFF with the transmit cycle, then no duty cycle correction is required for that emission (AV) at frequency above 1GHz.

## Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under § 15.247(b)(3) and RSS 247 section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in § 15.209(a) and RSS-Gen is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a) and RSS-Gen section 8.9, must also comply with the radiated emission limits specified in § 15.209(a) and RSS-Gen section 8.10.

Frequency MHz	Field Strength $\mu\text{V/m}$	Field Strength $\text{dB}\mu\text{V/m}$	Detector	Measurement distance meters
0.009-0.490	2400/F(kHz)	48.5-13.8	AV	300
0.490-1.705	24000/F(kHz)	33.8-23.0	QP	30
1.705-30	30	29.5	QP	30
30-88	100	40	QP	3
88-216	150	43.5	QP	3
216-960	200	46	QP	3
960-1000	500	54	QP	3
Above 1000	500	54	AV	3
Above 1000	5000	74	PK	3

Note 1: Limit  $3\text{m}(\text{dB}\mu\text{V/m}) = \text{Limit } 300\text{m}(\text{dB}\mu\text{V/m}) + 40\text{Log}(300\text{m}/3\text{m})$  (Below 30MHz)

Note 2: Limit  $3\text{m}(\text{dB}\mu\text{V/m}) = \text{Limit } 30\text{m}(\text{dB}\mu\text{V/m}) + 40\text{Log}(30\text{m}/3\text{m})$  (Below 30MHz)

## Spurious Radiated Emissions for Transmitter

According to C63.10, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement, so AV emission value did not show in below table if the peak value complies with average limit.

Data of measurement within frequency range 9kHz-30MHz is the noise floor or attenuated more than 20dB below the permissible limits or the field strength is too small to be measured, so test data does not present in this report.



**Above 1GHz Transmitting spurious emission test result as below:**

<b>Test mode:2.4G_802.11b_2412MHz</b>					
<b>Frequency MHz</b>	<b>Measure Level (dBuV/m)</b>	<b>Limit (dBuV/M)</b>	<b>Margin (dB)</b>	<b>Detector</b>	<b>Polarization</b>
4823.94	49.30	74.00	24.70	PK	Hor
9647.69	49.12	74.00	24.89	PK	Hor
4823.94	45.25	74.00	28.75	PK	Ver
2386.64	50.00	74.00	24.00	PK	Hor
2386.51	47.45	74.00	26.55	PK	Ver

<b>Test mode:2.4G_802.11b_2437MHz</b>					
<b>Frequency MHz</b>	<b>Measure Level (dBuV/m)</b>	<b>Limit (dBuV/M)</b>	<b>Margin (dB)</b>	<b>Detector</b>	<b>Polarization</b>
4873.88	48.31	74.00	25.69	PK	Hor
9748.09	49.01	74.00	24.99	PK	Hor
4873.88	44.46	74.00	29.54	PK	Ver

<b>Test mode:2.4G_802.11b_2462MHz</b>					
<b>Frequency MHz</b>	<b>Measure Level (dBuV/m)</b>	<b>Limit (dBuV/M)</b>	<b>Margin (dB)</b>	<b>Detector</b>	<b>Polarization</b>
4923.81	53.57	74.00	20.44	PK	Hor
9847.44	48.88	74.00	25.12	PK	Hor
4934.81	46.86	74.00	27.15	PK	Ver
2483.52	53.34	74.00	20.67	PK	Hor
2483.52	47.60	54.00	6.40	AV	Hor
2487.47	52.90	74.00	21.10	PK	Hor
2487.47	47.40	54.00	6.60	AV	Hor
2483.60	49.63	74.00	24.37	PK	Ver





Test mode:2.4G_802.11g_2412MHz					
Frequency MHz	Measure Level (dBuV/m)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
4823.94	43.61	74.00	30.39	PK	Hor
9648.22	48.42	74.00	25.58	PK	Hor
4822.88	41.87	74.00	32.13	PK	Ver
2389.90	55.47	74.00	18.53	PK	Hor
2389.90	43.40	54.00	10.60	AV	Hor
2389.89	51.31	74.00	22.69	PK	Ver

Test mode:2.4G_802.11g_2437MHz					
Frequency MHz	Measure Level (dBuV/m)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
4874.94	42.02	74.00	31.98	PK	Hor
9748.09	49.28	74.00	24.72	PK	Hor
4872.28	41.34	74.00	32.66	PK	Ver

Test mode:2.4G_802.11g_2462MHz					
Frequency MHz	Measure Level (dBuV/m)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
4922.75	43.16	74.00	30.84	PK	Hor
9847.97	48.81	74.00	25.19	PK	Hor
4924.34	41.55	74.00	32.45	PK	Ver
2483.56	55.28	74.00	18.72	PK	Hor
2483.56	45.50	54.00	8.50	AV	Hor
2483.51	51.65	74.00	22.35	PK	Ver

Test mode:2.4GHz 802.11n20 2412MHz					
Frequency MHz	Measure Level (dBuV/m)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
4822.34	42.88	74.00	31.12	PK	Hor
9647.69	48.71	74.00	25.29	PK	Hor
4824.47	41.27	74.00	32.73	PK	Ver
2389.94	52.65	74.00	21.36	PK	Ver
2389.94	39.20	54.00	14.80	AV	Ver
2389.83	56.93	74.00	17.07	PK	Hor
2389.83	43.20	54.00	10.80	AV	Hor

Test mode:2.4GHz 802.11n20 2437MHz					
Frequency MHz	Measure Level (dBuV/m)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
4874.94	42.89	74.00	31.11	PK	Hor
9748.09	50.11	74.00	23.89	PK	Hor
4873.34	41.60	74.00	32.40	PK	Ver

Test mode:2.4GHz 802.11n20 2462MHz					
Frequency MHz	Measure Level (dBuV/m)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
4923.81	45.27	74.00	28.73	PK	Hor
4922.22	41.51	74.00	32.49	PK	Ver
9848.50	49.39	74.00	24.61	PK	Hor
2483.53	59.18	74.00	14.83	PK	Hor
2483.53	44.80	54.00	9.20	AV	Hor
2483.56	53.77	74.00	20.23	PK	Ver
2483.56	41.00	54.00	13.00	AV	Ver

## Remark:


- (1) Emission level= Original Receiver Reading + Correct Factor
- (2) Correct Factor = Antenna Factor + Cable Loss -Amplifier gain
- (3) Margin = limit – Corrected Reading



**The worst case of Radiated Emission below 1GHz:**

Site: 3 meter chamber	Time: 2024/07/12 - 11:22
Limit: FCC_Part15.209_RE(3m)	Engineer: Cheng Huali
Probe: VULB9168	Polarity: Horizontal
EUT: Wi-Fi and Bluetooth Module, Model no: TCS905-3S	Power: 120VAC, 60Hz
Note: Transmit by at channel 2462MHz for 802.11g (worst case).	

RE\_VULB9168\_pre\_Cont\_30-1000



**Limit and Margin**

Frequency (MHz)	QuasiPeak (dBuV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBuV/m)
168.000000	29.4	1000.0	120.000	158.0	H	189.0	20.4	14.1	43.5
216.000000	32.0	1000.0	120.000	119.0	H	321.0	17.5	14.0	46.0
240.000000	32.8	1000.0	120.000	105.0	H	98.0	19.6	13.2	46.0
320.000000	32.5	1000.0	120.000	168.0	H	206.0	22.2	13.5	46.0
360.000000	36.2	1000.0	120.000	123.0	H	105.0	23.0	9.8	46.0
480.000000	37.7	1000.0	120.000	152.0	H	12.0	26.2	8.4	46.0

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)


Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Note 2: The test trace is same as the ambient noise and the amplitude of the emissions are attenuated more than 20dB below the permissible (the test frequency range: 9kHz ~ 30MHz, 18GHz ~ 25GHz), therefore no data appear in the report.



Site: 3 meter chamber	Time: 2024/07/12 - 11:29
Limit: FCC_Part15.209_RE(3m)	Engineer: Cheng Huali
Probe: VULB9168	Polarity: Vertical
EUT: Wi-Fi and Bluetooth Module, Model no: TCS905-3S	Power: 120VAC, 60Hz
Note: Transmit by at channel 2462MHz for 802.11g (worst case).	

RE\_VULB9168\_pre\_Cont\_30-1000



### Limit and Margin

Frequency (MHz)	QuasiPeak (dBuV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBuV/m)
72.000000	22.6	1000.0	120.000	100.0	V	326.0	18.2	17.4	40.0
120.000000	26.1	1000.0	120.000	123.0	V	98.0	18.1	17.4	43.5
168.000000	29.4	1000.0	120.000	112.0	V	36.0	20.4	14.1	43.5
216.000000	27.6	1000.0	120.000	102.0	V	105.0	17.5	18.4	46.0
360.000000	30.5	1000.0	120.000	119.0	V	118.0	23.0	15.5	46.0
480.000000	33.7	1000.0	120.000	105.0	V	201.0	26.2	12.3	46.0

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)  
 Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Note 2: The test trace is same as the ambient noise and the amplitude of the emissions are attenuated more than 20dB below the permissible (the test frequency range: 9kHz ~ 30MHz, 18GHz ~ 25GHz), therefore no data appear in the report.



## 10 Test Equipment List

List of Test Instruments  
Test Site1

	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL. DATE	CAL. DUE DATE
C	Wideband power sensor	Rohde & Schwarz	NRP-Z81	105903	2024-2-19	2025-2-18
	10dB Attenuator	Aeroflex Weinschel	CG-4689	93459	2024-2-19	2025-2-18
RE	EMI Test Receiver	Rohde & Schwarz	ESR3	101906	2024-8-1	2025-7-31
	Signal Analyzer	Rohde & Schwarz	FSV40	101091	2024-8-1	2025-7-31
	Trilog Super Broadband Test Antenna	Schwarzbeck	VULB 9168	961	2021-9-23	2024-9-22
	Double-ridged waveguide horn antenna	Rohde & Schwarz	HF907	102393	2024-4-14	2027-4-13
	Pre-amplifier	Shenzhen HzEMC	HPA-081843	HYP A23026	2024-4-16	2025-4-15
	Loop antenna	Rohde & Schwarz	HFH2-Z2	100443	2024-6-26	2025-6-25
	Double Ridged Horn Antenna	ETS-Lindgren	3116C	00246076	2023-7-7	2026-7-6
	3m Semi-anechoic chamber	TDK	9X6X6	----	2025-4-15	2027-5-7

Measurement Software Information			
Test Item	Software	Manufacturer	Version
C	MTS 8310	MWRFTtest	3.0.0.0
	Power Viewer	Rohde & Schwarz	V 11.0
RE	EMC 32	Rohde & Schwarz	V10.50.40

### C - Conducted RF tests

- Conducted peak output power.



## 11 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:

Items	Extended Uncertainty
Conducted Disturbance at Mains Terminals	150kHz to 30MHz, LISN, 3.16dB
Radiated Disturbance	9kHz to 30MHz, 3.52dB 30MHz to 1GHz, 5.03dB (Horizontal) 5.12dB (Vertical) 1GHz to 18GHz, 5.49dB 18GHz to 40GHz, 5.63dB
RF Conducted Measurement	Power related: 1.16dB Frequency related: $6.00 \times 10^{-8}$

Measurement Uncertainty Decision Rule:

Determination of conformity with the specification limits is based on the decision rule according to IEC Guide 115: 2023, clause 4.3.3.



## 12 Photographs of Test Set-ups

Refer to the < Test Setup photos >.



## 13 Photographs of EUT

Refer to the < External Photos > & < Internal Photos >.

-----End of Test Report-----