

TEST REPORT

Electromagnetic Compatibility

Report Reference No. : **REP035551**

Date of issue : 2024-04-04

Test Report Verdict : PASS

Testing Laboratory..... : **Nemko S.p.A.**

Address..... : Via Del Carroccio, 4

City : 20853 Biassono (MB)

Country : Italy

Testing location..... : Described at clause 1.4

Customer name..... : **EGICON S.r.l**

Customer information..... : Via Posta Vecchia, n. 36
41037 Mirandola (MO) – Italia

Reference standards..... : **FCC CFR 47 Part 15 Subpart B**

Standard application : Full application

Equipment under test : **Dashboard (DSB) for Ducati motorcycles**

Trademark(s) : EGICON

Manufacturer..... : EGICON S.r.l

Model/Type reference : Described at clause 4.1

Tests performed by : L. Anticono



Report approved by..... : R. Giampaglia

CONTENTS

1. GENERAL INFORMATION.....	3
1.1 Project history	3
1.2 Symbol used in the report	3
1.3 Date of sample(s) reception and tests	3
1.4 Testing location	4
1.5 Environmental conditions	4
1.6 Measurement uncertainty and assessment of conformity	4
1.7 Instruments calibration table	6
2. PRODUCT STANDARDS, TEST METHODS AND TECHNICAL PROCEDURES	7
2.1 Standard(s) applied.....	7
2.2 Test method(s) applied.....	7
2.3 Nemko technical procedures.....	7
3. SUMMARY OF TEST RESULTS AND VERDICTS	8
3.1 Measurement of electromagnetic disturbances emitted by the equipment under test.....	8
4. EQUIPMENT UNDER TEST	9
4.1 EUT Identification	9
4.2 EUT Power Supply.....	10
4.3 EUT Information declared by the Customer ¹	10
4.4 EUT Operation Modes	10
4.5 EUT Configuration Modes.....	10
4.6 EUT Input/Output Ports.....	11
4.7 EUT and Equipment Used During Test	12
4.8 EUT Electric/Block Diagram	13
4.9 Information about radio module(s).....	13
5 TEST RESULTS	14
5.1 Radiated Emission	14
5.2 Conducted emission	18
6 EUT PHOTOS	19

1. GENERAL INFORMATION

1.1 Project history

Report number	Modification to the report / comments	Date
REP035551	First release	2024-04-04

1.2 Symbol used in the report

<input checked="" type="checkbox"/>	The crossed square indicates that the listed condition, standard or equipment is applicable for this report.
<input type="checkbox"/>	The empty square indicates that the listed condition, standard or equipment is not applicable for this report.
NP (Not performed).....	Test case not performed according to customer request
N (Not applicable)	Test case does not apply to the test object
P (Pass)	Test object does meet the requirement
F (Fail)	Test object does not meet the requirement
<input type="checkbox"/> Comma (,) / <input checked="" type="checkbox"/> Dot (.)	Symbol used as decimal separator throughout this report
Asterisk (*)	Symbol used to indicate a standard, a test or a verdict not accredited by ACCREDIA
EUT	Equipment Under Test
The results contained in this report reflect the results for this particular model(s) and serial number(s) and apply to the sample(s) as received. It is the responsibility of the manufacturer to ensure that all production models meet the intent of the requirements detailed within this report.	

1.3 Date of sample(s) reception and tests

Date of receipt of test sample(s)	2024-04-02
Testing start date	2024-04-04
Testing termination date	2024-04-04

1.4 Testing location

The tests have been performed in the place indicated below:

Nemko premises location: Nemko S.p.A.
Via Del Carroccio, 4
20853 Biassono (MB) - Italy
FCC site number: 682159

Other location: --
--
--

1.5 Environmental conditions

The tests were carried out in the ranges of environmental conditions specified below:

Ambient temperature: 18-33 °C ¹

Relative Humidity: 25-70 % ²

Atmospheric pressure: 860-1060 hPa

Notes:
¹ For luminaire, temperature during tests was verified to be within 18 ÷ 30 °C
² During ESD test, humidity was verified to be within 30 ÷ 60 %

The following instruments are used to monitor the environmental conditions:

Equipment	Trademark	Model	Serial No.
Thermo-hygrometer	Testo	175-H2	20012380/305
Thermo-hygrometer	Testo	175-H2	38203337/703
Barometer	Castle	GPB 3300	072015

1.6 Measurement uncertainty and assessment of conformity

The measurement uncertainty was calculated for each test and quantity listed in this test report, according to CISPR 16-4-2 and other specific test standard and is documented in Nemko Spa working manual WML1002. The assessment of conformity for each test performed on the equipment is performed not taking into account the measurement uncertainty. The two following possible verdicts are stated in the report:

P (Pass) - The measured values of the equipment respect the specification limit at the points tested. The specific risk of false accept is up to 50% when the measured result is close to the limit.

F (Fail) - One or more measured values of the equipment do not respect the specification limit at the points tested. The specific risk of false reject is up to 50% when the measured result is close to the limit.

Hereafter Nemko's measurement uncertainties are reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Disturbance	Antenna distance 1 m, 3 m, 10 m 0.009 ÷ 200 MHz	5.0 dB	(1)
	Antenna distance 1 m, 3 m, 10 m 200 ÷ 1000 MHz	5.2 dB	(1)
	Antenna distance 1 m, 3 m, 10 m 1 ÷ 6 GHz	5.2 dB	(1)
	Antenna distance 1 m, 3 m 6 ÷ 18 GHz	5.5 dB	(1)
	Antenna distance 1 m, 3 m 18 ÷ 40 GHz	7.2 dB	(1)
Radiated Disturbance with large loop antenna system (LLAS)	0.009 ÷ 30 MHz	3.3 dB	(1)
Conducted Disturbance	0.02 ÷ 150 kHz with AMN	3.8 dB	(1)
	150 kHz ÷ 30 MHz with AMN	3.4 dB	(1)
	150 kHz ÷ 30 MHz with AAN	4.6 dB	(1)
	9 kHz ÷ 30 MHz with voltage probe	2.9 dB	(1)
	150 kHz ÷ 30 MHz with current probe	2.9 dB	(1)
Frequency	10 Hz ÷ 1 kHz	0.2 %	(1)
	1 kHz ÷ 40 GHz	10 ⁻⁶	(1)
Electromagnetic fields (EMF)	Magnetic, Electric and Electromagnetic fields: 0 Hz ÷ 40 GHz	25 %	(1)
Electrical quantities (voltage, current, resistance)	AC/DC Voltage 10 mV ÷ 1000 V 0÷100 kHz AC/DC Current 0.1 mA ÷ 400 A 0÷1 kHz Resistance 100 mΩ ÷ 10 MΩ	2.5 %	(1)
NOTES: (1) The reported expanded uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k = 2$, which for a normal distribution corresponds to a coverage probability of approximately 95 % (2) The instruments used for this immunity test is according to the tolerances requested by the applicable standard (3) The reported expanded uncertainty of measurement is related to the stimulus quantity			

1.7 Instruments calibration table

Instrument cited in the report and not listed in this paragraph are not subject to calibration. The calibration is valid up to the last day of the due date month.

Description	Manufacturer	Model	Identifier	Cal Date	Due Date
EMI Receiver	Rohde & Schwarz	ESW44	101620	2023-09	2024-09
EMI Receiver	Rohde & Schwarz	ESU8	100202	2023-09	2024-09
Antenna Trilog 25MHz - 8GHz	Schwarzbeck Mess-Elektronik	VULB9162	9162-025	2021-07	2024-07
Antenna Trilog 25-2000 MHz	Schwarzbeck Mess-Elektronik	VULB9168	9168-242	2021-06	2024-06
Antenna 1 - 18 GHz	Schwarzbeck Mess-Elektronik	STLP9148	STLP 9148-152	2021-09	2024-09
Antenna 1 - 18 GHz	Schwarzbeck Mess-Elektronik	STLP9148	STPL 9148-123	2021-06	2024-06
Double Ridge Horn Antenna	RFSpin	DRH40	061106A40	2023-05	2026-05
Broadband Bench Top Amplifier	Sage	STB-1834034030-KFKF-L1	18490-01	2023-05	2024-05
Broadband Amplifier	Schwarzbeck Mess-Elektronik	BBV9718C	00121	2024-02	2025-02
Preamplifier	Schwarzbeck Mess-Elektronik	BBV9718	BBV9718-137	2023-05	2024-05
Semi-anechoic chamber	Nemko Spa	10m semi-anechoic chamber	530	2023-09	2025-09
Common Mode Absorption Device	Schwarzbeck Mess-Elektronik	CMAD1614	00041	2022-05	2025-05
LISN	Rohde & Schwarz	ENV432	101714	2023-09	2024-09
LISN	Rohde & Schwarz	ESH2-Z5	872 460/041	2023-08	2024-08
V-network	Rohde & Schwarz	ESH3-Z5	840 731/004	2023-08	2024-08
Oscilloscopio	Agilent	54846A	MY40000254	2023-08	2024-08
Multimeter	Rohde & Schwarz	HMC8012	101577	2023-05	2024-05
Barometer	Castle	GBP 3300	072015	2023-05	2024-05
Data logger con diagnosi in campo	Testo	175-H2	20012380/305	2022-12	2024-12
Data logger con diagnosi in campo	Testo	175-H2	38203337/703	2022-12	2024-12
Attenuator	Aeroflex / Weinschel	2	CC8577	2024-02	2025-02
3m Semi anechoic chamber	Comtest	SAC-3	1711-150	2022-09	2024-09

2. PRODUCT STANDARDS, TEST METHODS AND TECHNICAL PROCEDURES

2.1 Standard(s) applied

The following standard(s) or specifications, accredited by ACCREDIA, were applied:

FCC CFR 47 Part 15 Subpart B

Code of Federal Regulations – Title 47 – Part 15 Radio Frequency Devices – Subpart B
Unintentional radiators

2.2 Test method(s) applied

The following documents are referred to in the standard(s) in such a way that some or all of their content constitutes requirements for the standard itself.

ANSI C63.4 (2014)

American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz

2.3 Nemko technical procedures

WM L0177: General routines for using instruments at Nemko

WM L1002: Measurement Uncertainty - Policy and Statement

WM L0077: General procedure for conducting EMC tests


3. SUMMARY OF TEST RESULTS AND VERDICTS

3.1 Measurement of electromagnetic disturbances emitted by the equipment under test

Emission Tests		
Requirement / test	Method Standard	Verdict
Part §15.107 – Conducted emission	ANSI C63.4	N ¹
Part §15.109 – Radiated emission	ANSI C63.4	P
Notes: ¹ The EUT is supplied by the vehicle battery		

4. EQUIPMENT UNDER TEST

4.1 EUT Identification

Short description of the EUT	
Dashboard (DSB) for Ducati motorcycles	
Copy of marking plate(s) (if present)	
	
Sample ID	PRJ005400990003 (Nemko internal number)
Model/Type	RTADE002
Ratings	9A, 12V DC from vehicular battery
Equipment installation	Mounted on a motorcycle
Accessories and detachable parts included	None
Test performed.....	All tests were performed on this sample
Hardware /Software	R3/010

4.2 EUT Power Supply

Used ¹	N° ²	Type	Supply Voltage	Phases N°	Supplementary Information
☒	1	DC	14.5 V		
Notes: ¹ The crossed square indicates that the supply voltage is used in at least one test. ² This number will be used all over the report to identify the supply voltage(s) used for each test.					

4.3 EUT Information declared by the Customer ¹

Information	Declaration
EUT highest frequency ²	fc not declared
Environment intended use.....	Other
Equipment classification ³	B
Notes: ¹ Nemko S.p.A. declines all responsibility for the information above declared by the customer that may influence the validity of the results contained in this test report. ² For host products with certified modular transmitter, the frequency range of investigation of the composite system is specified by rule in Sections 15.33(a)(1) through (a)(3), or the range applicable to the digital device, as shown in Section 15.33(b)(1), whichever is the higher frequency range of investigation. ³ Equipment class and category definitions are specified in the standard used.	

4.4 EUT Operation Modes

N°	Description
1	Normal use (14.5V, 0.5A)
Notes: --	

4.5 EUT Configuration Modes

The EUT was configured to measure its highest possible radiation level. The test modes selected are according to EUT instruction manual.

N°	Description
1	The EUT has been tested supplied by an external DC power source and connected to original cables and accessories.
Notes: --	

4.6 EUT Input/Output Ports

Port	Name	Type ¹	Cable Max. >3m	Cable Shielded	Description
0	Enclosure	N/E	—	—	-
1	Power supply	DC	<input type="checkbox"/>	<input type="checkbox"/>	14.5V, 0.5A

Notes:

¹ Port type:

AC = AC Power Port

DC = DC Power Port

N/E = Non-Electrical


ANT = Antenna Port

I/O = Signal/Control Input or Output Port

TP = Wired network or telecommunication Port

4.7 EUT and Equipment Used During Test

Use ¹	Product Type	Manufacturer	Model	Comments
EUT	Dashboard	EGICON S.r.l	RTADE002	-
EUT	Key lock Coil antenna	ZADI	EL216	-
AE	Light indicator	EGICON S.r.l	-	-
SIM	Original cable and accessories	Ducati	--	Provided by the manufacturer



Notes:


¹ Use

EUT - Equipment Under Test

SIM - Simulator (Not Subjected to Test)

AE - Auxiliary/Associated Equipment (Not Subjected to Test)

4.8 EUT Electric/Block Diagram



4.9 Information about radio module(s)

Radio module 1	
Description	Information
Identification:	Model: TMS3705 Transponder Base Station IC Trademark: Texas Instruments
Frequency band (MHz):	The high or low bits are coded in two different high-frequency signals (134.2kHz for low bits and 123kHz for high bits, nominal)
Modulation type:	FSK
Antenna information:	The coil antenna EL216 is integrated into the ZADI key block
Other information:	--
Notes:	

5 TEST RESULTS

5.1 Radiated Emission

5.1.1 Test result

Verdict:	<input checked="" type="checkbox"/> P <input type="checkbox"/> F <input type="checkbox"/> N ¹ <input type="checkbox"/> NP
Frequency range:	30 MHz – 1000 MHz ²
Test site:	Semi anechoic chamber
Measurement distance:	3 m ³
Notes:	
¹ If marked, the test is not applicable for the EUT. ² For host products with certified modular transmitter, the frequency range of investigation of the composite system is specified by rule in Sections 15.33(a)(1) through (a)(3), or the range applicable to the digital device, as shown in Section 15.33(b)(1), whichever is the higher frequency range of investigation. ³ Test was performed at 10 m measurement distance for class A EUT in the frequency range from 30 to 1000 MHz; test was performed at 3 m measurement distance in all other cases.	

5.1.2 Photo documentation of the test set-up



5.1.3 Test method

Method standard is reported at par. 3.1. Measurements were made on a semi anechoic chamber. Preliminary measurements were performed at an antenna to EUT separation distance of 3 or 10 meters with the receive antenna located at a fixed height (from 1 to 4 meter) in both horizontal and vertical polarizations. Final measurements were then performed by rotating the EUT 360° and adjusting the receive antenna height from 1 to 4 meters. All frequencies were investigated in both horizontal and vertical antenna polarization, where applicable.

Receiver reading P_R , reported in tables at clause 5.1.6, was achieved adjusting the input signal P_{IN} by a correction factor CF , to take into account of the insertion loss due to cables and attenuators, the antenna factor, the external preamplifier gain. This correction factor was pre-inserted in the firmware of the receiver and was applied by the instrument during the test. The relationship between P_R and P_{IN} , expressed in dB, is:

$$P_R = P_{IN} + CF$$

5.1.4 Limits for enclosure

Radiated emission ¹				
Frequency (MHz)	Limit for Class A EUT		Limit for Class B EUT	
	µV/m	dBµV/m	µV/m	dBµV/m
30 to 88	90	39.0	100	40.0
88 to 216	150	43.5	150	43.5
216 to 960	210	46.4	200	46.0
960 to 1000	300 ²	49.5 ²	500 ²	54.0 ²
Above 1000 ³	1000 ²	59.5 ²	500 ²	54.0 ²

Notes:

¹ For frequency range between 30 to 1000 MHz Quasi-Peak detector is used. For frequency range above 1000 MHz Average and Peak detector are used.

² Above 1000 MHz, the limit reported refers to measurements performed with Average detector. For measurements performed with Peak detector the limit is 20 dB greater.

³ For Class A radiated emission above 1 GHz, a measurement distance of 3 m can be used, with the limits increased by 10 dB.

 5.1.5 Test equipment used¹

Used ²	Description	Manufacturer	Model	Identifier
<input type="checkbox"/>	SAC	Nemko Spa	10m SAC	530
<input checked="" type="checkbox"/>	SAC	Comtest	3m SAC	1711-150
<input type="checkbox"/>	EMI receiver	Rohde & Schwarz	ESW44	101620
<input checked="" type="checkbox"/>	EMI receiver	R&S	ESU8	100202
<input type="checkbox"/>	Antenna	Schwarzbeck	VULB9162	VULB9162-025
<input checked="" type="checkbox"/>	Antenna	Schwarzbeck	VULB9168	VULB9168-242
<input type="checkbox"/>	Antenna	Schwarzbeck	STLP9148	STLP9148-123
<input type="checkbox"/>	Antenna	RF Spin	DRH40	061106A40
<input type="checkbox"/>	Preamplifier	Schwarzbeck	BBV9718C	00121
<input checked="" type="checkbox"/>	Controller for turntable and antenna mast	Maturo	FCU3.0	10041
<input checked="" type="checkbox"/>	Tilt antenna mast	Maturo	TAM4.0-E	10042
<input checked="" type="checkbox"/>	Turntable 4.5 t	Maturo	TT4.0-5T	2.527

Notes:

¹ See clause 1.7 for calibration information.

² If crossed, the instrument was used during tests.

5.1.7 Test protocol


Antenna Polarization	Supply Voltage ¹	Test Mode		Remarks	Verdict
		Operation ²	Configuration ³		
Horizontal	1	1	1	- Hazard light: 14.5V, 0.5A	P

Notes:

¹ See clause 4.2 EUT Power Supply

² See clause 4.4 EUT Operation Modes

³ See clause 4.5 EUT Configuration Modes




Frequency (MHz)	Level (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Detector
38.0000	16.8	40.0	-23.2	QP
49.8000	18.5	40.0	-21.5	QP
53.9600	12.6	40.0	-27.4	QP
104.5200	30.4	43.5	-13.1	QP
106.7200	30.4	43.5	-13.1	QP
213.7600	22.9	43.5	-20.6	QP
233.1600	38.7	46.0	-7.3	QP
264.0800	27.3	46.0	-18.7	QP
298.4400	21.1	46.0	-24.9	QP
350.0800	24.3	46.0	-21.7	QP
399.5200	17.8	46.0	-28.2	QP
479.8000	24.1	46.0	-21.9	QP
502.7200	22.6	46.0	-23.4	QP
629.6400	21.3	46.0	-24.7	QP
741.3200	22.4	46.0	-23.6	QP
862.9200	24.2	46.0	-21.8	QP
932.2000	27.0	46.0	-19.0	QP

Antenna Polarization	Supply Voltage ¹	Test Mode		Remarks	Verdict
		Operation ²	Configuration ³		
Vertical	1	1	1	- Hazard light: 14.5V, 0.5A	P

Notes:

¹ See clause 4.2 EUT Power Supply

² See clause 4.4 EUT Operation Modes

³ See clause 4.5 EUT Configuration Modes


Frequency (MHz)	Level (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Detector
32.4400	24.4	40.0	-15.6	QP
38.6800	37.7	40.0	-2.3	QP
39.7600	25.8	40.0	-14.2	QP
47.6800	23.2	40.0	-16.8	QP
54.0000	25.8	40.0	-14.2	QP
67.1600	22.0	40.0	-18.0	QP
72.0000	20.7	40.0	-19.3	QP
104.8400	24.8	43.5	-18.7	QP
107.2800	28.2	43.5	-15.3	QP
239.0800	32.0	46.0	-14.0	QP
369.2400	18.2	46.0	-27.8	QP
428.2000	22.8	46.0	-23.2	QP
467.6800	27.5	46.0	-18.5	QP
501.5600	26.0	46.0	-20.0	QP
638.6400	21.5	46.0	-24.5	QP
738.4400	22.5	46.0	-23.5	QP
854.0400	24.2	46.0	-21.8	QP
951.2400	26.1	46.0	-19.9	QP

5.2 Conducted emission

5.2.1 Test result

Verdict for AC mains port ² :	<input type="checkbox"/> P <input type="checkbox"/> F <input checked="" type="checkbox"/> N ¹ <input type="checkbox"/> NP
Frequency range:	0.15 MHz – 30 MHz
Kind of test site:	Shielded room
Notes: ¹ If marked, the test is not applicable for the EUT, according to 15.107 (c)(1) or (d). ² If applicable, KDB 174176D01 criterion was used for devices powered from a computer or any other external power source via a USB connection.	

6 EUT PHOTOS





End of report