

	TEST REPOR	T			
FCC ID:	2AO27-STBOX				
Test Report No::	TCT220601E040	(C)	(C)		
Date of issue::	Jun. 17, 2022				
Testing laboratory:	SHENZHEN TONGCE TESTING	S LAB			
Testing location/ address:	TCT Testing Industrial Park Fuqi Street, Bao'an District Shenzhen Republic of China				
Applicant's name::	Nevron d.o.o.				
Address::	Kidriceva cesta 56, 4220 Skofja	Loka, Slovenia			
Manufacturer's name:	Nevron d.o.o.	(c)			
Address::	Kidriceva cesta 56, 4220 Skofja	Kidriceva cesta 56, 4220 Skofja Loka, Slovenia			
Standard(s):	FCC CFR Title 47 Part 1.1307				
Product Name::	Smart TV BOX	(0)			
Trade Mark:	N/A				
Model/Type reference:	FaSTBox Luxury S905x	(3			
Rating(s)::	DC 5 V From Adapter				
Date of receipt of test item:	Jun. 01, 2022	(3)			
Date (s) of performance of test:	Jun. 01, 2022 ~ Jun. 17, 2022				
Tested by (+signature):	Onnado YE	Onnado Jeron	GCE		
Check by (+signature):	Beryl Zhao	Buy the E	CT		
Approved by (+signature):	Tomsin	Tomsm 45	84		

#### General disclaimer:

This report shall not be reproduced except in full, without the written approval of SHENZHEN TONGCE TESTING LAB. This document may be altered or revised by SHENZHEN TONGCE TESTING LAB personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.





# **Table of Contents**

2.	General Pro 1.1. EUT deso 1.2. Model(s) General Inf 2.1. Test envi 2.2. Descripti Facilities a	cription listormation ironment a ion of Sup	and mode.	(49)	(89)	3 4 4
	3.1. Facilities	······				 5
	3.2. Location Test Result					5 6



## 1. General Product Information

## 1.1. EUT description

Product Name:	Smart TV BOX
Model/Type reference:	FaSTBox Luxury S905x
Sample Number:	TCT220601E032-0101
Operation Frequency:	For BT/ BLE: 2402MHz~2480MHz For WIFI: 2412MHz~2462MHz(802.11b/802.11g/802.11n(HT20)) 2422MHz~2452MHz (802.11n(HT40))
Modulation Type:	For BT: GFSK For BLE: GFSK, π/4-DQPSK, 8DPSK For WIFI: DSSS(802.11b), OFDM (802.11g/802.11n)
Antenna Type:	External Antenna
Antenna Gain:	3dBi
Rating(s):	DC 5 V From Adapter
Remark:	/

Note: The antenna gain listed in this report is provided by applicant, and the test laboratory is not responsible for this parameter.

### 1.2. Model(s) list



### 2. General Information

#### 2.1. Test environment and mode

Item	Normal condition				
Temperature	+25°C				
Voltage	DC 5 V From Adapter				
Humidity	56%				
Atmospheric Pressure:	1008 mbar				
Test Mode:					
Engineering mode:	Keep the EUT in continuous transmitting by select channel				

## 2.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Model No.	Serial No.	FCC ID	Trade Name	
LCD TV	19PFL3120/T3	AU2A1241000762	1	PHILIPS	
Mouse	VX239	VX239H		ASUS	

#### Note:

- 1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
- 2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
- 3. For conducted measurements (Output Power, 20dB Occupied Bandwidth, Carrier Frequencies Separation, Hopping Channel Number, Dwell Time, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.





### 3. Facilities and Accreditations

#### 3.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

• FCC - Registration No.: 645098

SHENZHEN TONGCE TESTING LAB

**Designation Number: CN1205** 

The testing lab has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

IC - Registration No.: 10668A-1

SHENZHEN TONGCE TESTING LAB

CAB identifier: CN0031

The testing lab has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing.

#### 3.2. Location

SHENZHEN TONGCE TESTING LAB

Address: TCT Testing Industrial Park Fuqiao 5th Industrial Zone, Fuhai Street, Bao'an

District Shenzhen, Guangdong, 518103, People's Republic of China

TEL: +86-755-27673339





### 4. Test Results and Measurement Data

According to §1.1307(b), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

Remark: 1)

For BT: The maximum output power for antenna is -0.85dBm (0.82mW) at 2441MHz,

3dBi antenna gain(with 2.00 numeric antenna gain);

**For BLE:** The maximum output power for antenna is-1.58dBm (0.70mW) at 2402MHz,

3dBi antenna gain(with 2.00 numeric antenna gain);

For 2.4G WIFI: The maximum output power for antenna is 9.28dBm (8.47mW) at 2422MHz,

3dBi antenna gain(with 2.00 numeric antenna gain);

2) For mobile or fixed location transmitters, no SAR consideration applied. The minimum separation generally be used is at least 20cm, even if the calculation indicate that the MPE distance would be lesser.

Calculation

Given  $E = \sqrt{\frac{30 \times P \times G}{d}}$  &  $S = \frac{E^2}{3770}$ 

Where E = Field Strength in Volts / meter

P = Power in Watts

G=Numeric antenna gain

d=Distance in meters

S=Power Density in milliwatts / square centimeter

Substituting the MPE safe distance using d=20cm into above equation.

Yields: S=0.000199\*P\*G

	Maximum Emissions Level					
Mode Power(mW)		numeric antenna gain	Power density (mW/cm2)	Limit (mW/cm2)	Result	
ВТ	0.82	2.00	0.000326			
BLE	0.70	2.00	0.000279	1.0	PASS	
2.4G WIFI	8.47	2.00	0.003371			

\*\*\*\*\*END OF REPORT\*\*\*\*