APPENDIX C Probe CALIBRATION CERTIFICATES

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland

S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **Auden**

Certificate No: **EX3-3820_Jun18**

CALIBRATION CERTIFICATE

Object	EX3DV4 - SN:3820
Calibration procedure(s)	QA CAL-01.v9, QA CAL-14.v4, QA CAL-23.v5, QA CAL-25.v6 Calibration procedure for dosimetric E-field probes
Calibration date:	June 26, 2018

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	04-Apr-18 (No. 217-02672/02673)	Apr-19
Power sensor NRP-Z91	SN: 103244	04-Apr-18 (No. 217-02672)	Apr-19
Power sensor NRP-Z91	SN: 103245	04-Apr-18 (No. 217-02673)	Apr-19
Reference 20 dB Attenuator	SN: S5277 (20x)	04-Apr-18 (No. 217-02682)	Apr-19
Reference Probe ES3DV2	SN: 3013	30-Dec-17 (No. ES3-3013_Dec17)	Dec-18
DAE4	SN: 660	21-Dec-17 (No. DAE4-660_Dec17)	Dec-18
Secondary Standards	ID	Check Date (in house)	Scheduled Check
Power meter E4419B	SN: GB41293874	06-Apr-16 (in house check Jun-18)	In house check: Jun-20
Power sensor E4412A	SN: MY41498087	06-Apr-16 (in house check Jun-18)	In house check: Jun-20
Power sensor E4412A	SN: 000110210	06-Apr-16 (in house check Jun-18)	In house check: Jun-20
RF generator HP 8648C	SN: US3642U01700	04-Aug-99 (in house check Jun-18)	In house check: Jun-20
Network Analyzer HP 8753E	SN: US37390585	18-Oct-01 (in house check Oct-17)	In house check: Oct-18

	Name	Function	Signature
Calibrated by:	Leif Klysner	Laboratory Technician	
Approved by:	Katja Pokovic	Technical Manager	

Issued: June 27, 2018

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Glossary:

TSL	tissue simulating liquid
NORMx,y,z	sensitivity in free space
ConvF	sensitivity in TSL / NORMx,y,z
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C, D	modulation dependent linearization parameters
Polarization φ	φ rotation around probe axis
Polarization ϑ	ϑ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., ϑ = 0 is normal to probe axis
Connector Angle	information used in DASY system to align probe sensor X to the robot coordinate system

Calibration is Performed According to the Following Standards:

a) IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
b) IEC 62209-1, ", "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
c) IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
d) KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Methods Applied and Interpretation of Parameters:

- *NORMx,y,z:* Assessed for E-field polarization ϑ = 0 (f ≤ 900 MHz in TEM-cell; f > 1800 MHz: R22 waveguide). NORMx,y,z are only intermediate values, i.e., the uncertainties of NORMx,y,z does not affect the E^2-field uncertainty inside TSL (see below *ConvF*).
- *NORM(f)x,y,z = NORMx,y,z * frequency_response* (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of *ConvF*.
- *DCPx,y,z:* DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- *PAR:* PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- *Ax,y,z; Bx,y,z; Cx,y,z; Dx,y,z; VRx,y,z: A, B, C, D* are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. *VR* is the maximum calibration range expressed in RMS voltage across the diode.
- *ConvF and Boundary Effect Parameters:* Assessed in flat phantom using E-field (or Temperature Transfer Standard for f ≤ 800 MHz) and inside waveguide using analytical field distributions based on power measurements for f > 800 MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to *NORMx,y,z * ConvF* whereby the uncertainty corresponds to that given for *ConvF*. A frequency dependent *ConvF* is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- *Spherical isotropy (3D deviation from isotropy)*: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- *Sensor Offset*: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- *Connector Angle*: The angle is assessed using the information gained by determining the *NORMx* (no uncertainty required).

Probe EX3DV4

SN:3820

Manufactured: September 2, 2011
Calibrated: June 26, 2018

Calibrated for DASY/EASY Systems
(Note: non-compatible with DASY2 system!)

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3820

Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm ($\mu V/(V/m)^2$)[A]	0.40	0.47	0.50	± 10.1 %
DCP (mV)[B]	97.2	102.3	99.7	

Modulation Calibration Parameters

UID	Communication System Name		A dB	B dB√μV	C	D dB	VR mV	Unc[E] (k=2)
0	CW	X	0.0	0.0	1.0	0.00	188.0	±3.5 %
		Y	0.0	0.0	1.0		176.4	
		Z	0.0	0.0	1.0		184.2	

Note: For details on UID parameters see Appendix.

Sensor Model Parameters

	C1 fF	C2 fF	α V^{-1}	T1 $ms.V^{-2}$	T2 $ms.V^{-1}$	T3 ms	T4 V^{-2}	T5 V^{-1}	T6
X	47.66	365.1	37.10	12.32	0.944	5.036	0.000	0.592	1.010
Y	48.98	364.1	35.44	15.30	0.607	5.083	1.076	0.406	1.007
Z	47.72	378.2	40.37	16.84	1.209	5.100	0.000	0.550	1.022

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

[A] The uncertainties of Norm X,Y,Z do not affect the E^2-field uncertainty inside TSL (see Pages 5 and 6).
[B] Numerical linearization parameter: uncertainty not required.
[E] Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3820

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) [C]	Relative Permittivity [F]	Conductivity (S/m) [F]	ConvF X	ConvF Y	ConvF Z	Alpha [G]	Depth [G] (mm)	Unc (k=2)
750	41.9	0.89	9.72	9.72	9.72	0.33	1.06	± 12.0 %
835	41.5	0.90	9.40	9.40	9.40	0.46	0.85	± 12.0 %
900	41.5	0.97	9.22	9.22	9.22	0.39	0.92	± 12.0 %
1450	40.5	1.20	8.31	8.31	8.31	0.39	0.80	± 12.0 %
1640	40.2	1.31	7.78	7.78	7.78	0.29	0.85	± 12.0 %
1750	40.1	1.37	7.80	7.80	7.80	0.36	0.80	± 12.0 %
1810	40.0	1.40	7.58	7.58	7.58	0.40	0.91	± 12.0 %
1900	40.0	1.40	7.57	7.57	7.57	0.45	0.80	± 12.0 %
2000	40.0	1.40	7.55	7.55	7.55	0.46	0.80	± 12.0 %
2450	39.2	1.80	6.79	6.79	6.79	0.43	0.80	± 12.0 %
2600	39.0	1.96	6.61	6.61	6.61	0.45	0.81	± 12.0 %
3500	37.9	2.91	6.66	6.66	6.66	0.30	1.20	± 13.1 %
5200	36.0	4.66	4.82	4.82	4.82	0.40	1.80	± 13.1 %
5300	35.9	4.76	4.60	4.60	4.60	0.40	1.80	± 13.1 %
5500	35.6	4.96	4.61	4.61	4.61	0.40	1.80	± 13.1 %
5600	35.5	5.07	4.50	4.50	4.50	0.40	1.80	± 13.1 %
5800	35.3	5.27	4.53	4.53	4.53	0.40	1.80	± 13.1 %

[C] Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

[F] At frequencies below 3 GHz, the validity of tissue parameters (ε and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ε and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

[G] Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3820

Calibration Parameter Determined in Body Tissue Simulating Media

f (MHz) [C]	Relative Permittivity [F]	Conductivity (S/m) [F]	ConvF X	ConvF Y	ConvF Z	Alpha [G]	Depth [G] (mm)	Unc (k=2)
750	55.5	0.96	9.60	9.60	9.60	0.43	0.80	± 12.0 %
835	55.2	0.97	9.32	9.32	9.32	0.42	0.87	± 12.0 %
900	55.0	1.05	9.28	9.28	9.28	0.47	0.85	± 12.0 %
1450	54.0	1.30	7.92	7.92	7.92	0.34	0.80	± 12.0 %
1640	53.7	1.42	8.03	8.03	8.03	0.45	0.80	± 12.0 %
1750	53.4	1.49	7.55	7.55	7.55	0.43	0.80	± 12.0 %
1810	53.3	1.52	7.42	7.42	7.42	0.43	0.80	± 12.0 %
1900	53.3	1.52	7.36	7.36	7.36	0.40	0.80	± 12.0 %
2000	53.3	1.52	7.31	7.31	7.31	0.42	0.80	± 12.0 %
2450	52.7	1.95	6.84	6.84	6.84	0.34	0.93	± 12.0 %
2600	52.5	2.16	6.75	6.75	6.75	0.27	0.95	± 12.0 %
3500	51.3	3.31	6.62	6.62	6.62	0.25	1.25	± 13.1 %
5200	49.0	5.30	4.40	4.40	4.40	0.50	1.90	± 13.1 %
5300	48.9	5.42	4.23	4.23	4.23	0.50	1.90	± 13.1 %
5500	48.6	5.65	3.99	3.99	3.99	0.50	1.90	± 13.1 %
5600	48.5	5.77	3.84	3.84	3.84	0.50	1.90	± 13.1 %
5800	48.2	6.00	3.94	3.94	3.94	0.50	1.90	± 13.1 %

[C] Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

[F] At frequencies below 3 GHz, the validity of tissue parameters (ε and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ε and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

[G] Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

Frequency Response of E-Field
(TEM-Cell:ifi110 EXX, Waveguide: R22)



Uncertainty of Frequency Response of E-field: ± 6.3% (k=2)

Receiving Pattern (ϕ), ϑ = 0°

f=600 MHz,TEM



f=1800 MHz,R22





Uncertainty of Axial Isotropy Assessment: ± 0.5% (k=2)

Dynamic Range f(SAR_{head})
(TEM cell , f_{eval}= 1900 MHz)





Uncertainty of Linearity Assessment: ± 0.6% (k=2)

Conversion Factor Assessment

f = 900 MHz,WGLS R9 (H_convF)



f = 1810 MHz,WGLS R22 (H_convF)



Deviation from Isotropy in Liquid

Error (ϕ, ϑ), f = 900 MHz





Uncertainty of Spherical Isotropy Assessment: ± 2.6% (k=2)

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3820

Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle (°)	32.4
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	9 mm
Tip Diameter	2.5 mm
Probe Tip to Sensor X Calibration Point	1 mm
Probe Tip to Sensor Y Calibration Point	1 mm
Probe Tip to Sensor Z Calibration Point	1 mm
Recommended Measurement Distance from Surface	1.4 mm

Appendix: Modulation Calibration Parameters

UID	Communication System Name		A dB	B dB√μV	C	D dB	VR mV	Max Unc^E (k=2)
0	CW	X	0.00	0.00	1.00	0.00	188.0	± 3.5 %
		Y	0.00	0.00	1.00		176.4	
		Z	0.00	0.00	1.00		184.2	
10010-CAA	SAR Validation (Square, 100ms, 10ms)	X	2.27	64.87	9.94	10.00	20.0	± 9.6 %
		Y	3.59	70.77	12.79		20.0	
		Z	2.75	66.85	11.07		20.0	
10011-CAB	UMTS-FDD (WCDMA)	X	0.83	64.39	12.93	0.00	150.0	± 9.6 %
		Y	1.14	69.97	16.70		150.0	
		Z	100.00	164.68	47.04		150.0	
10012-CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps)	X	1.06	62.50	13.97	0.41	150.0	± 9.6 %
		Y	1.18	64.85	16.05		150.0	
		Z	1.72	77.78	24.82		150.0	
10013-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps)	X	4.78	66.26	16.74	1.46	150.0	± 9.6 %
		Y	4.89	66.88	17.27		150.0	
		Z	4.97	67.94	18.56		150.0	
10021-DAC	GSM-FDD (TDMA, GMSK)	X	29.58	96.57	22.64	9.39	50.0	± 9.6 %
		Y	100.00	115.92	28.37		50.0	
		Z	100.00	116.12	28.80		50.0	
10023-DAC	GPRS-FDD (TDMA, GMSK, TN 0)	X	17.45	89.91	20.80	9.57	50.0	± 9.6 %
		Y	100.00	115.55	28.25		50.0	
		Z	100.00	115.79	28.70		50.0	
10024-DAC	GPRS-FDD (TDMA, GMSK, TN 0-1)	X	100.00	108.09	23.68	6.56	60.0	± 9.6 %
		Y	100.00	115.38	27.11		60.0	
		Z	100.00	114.83	27.07		60.0	
10025-DAC	EDGE-FDD (TDMA, 8PSK, TN 0)	X	3.83	66.26	23.12	12.57	50.0	± 9.6 %
		Y	6.32	83.32	33.10		50.0	
		Z	5.27	76.55	29.71		50.0	
10026-DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1)	X	8.30	87.99	30.43	9.56	60.0	± 9.6 %
		Y	13.69	102.61	36.80		60.0	
		Z	27.02	120.57	42.89		60.0	
10027-DAC	GPRS-FDD (TDMA, GMSK, TN 0-1-2)	X	100.00	106.08	22.01	4.80	80.0	± 9.6 %
		Y	100.00	116.66	26.90		80.0	
		Z	100.00	116.26	26.81		80.0	
10028-DAC	GPRS-FDD (TDMA, GMSK, TN 0-1-2-3)	X	100.00	104.28	20.57	3.55	100.0	± 9.6 %
		Y	100.00	119.25	27.30		100.0	
		Z	100.00	120.86	27.94		100.0	
10029-DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1-2)	X	5.54	79.45	25.98	7.80	80.0	± 9.6 %
		Y	7.52	87.84	30.19		80.0	
		Z	13.09	102.56	36.16		80.0	
10030-CAA	IEEE 802.15.1 Bluetooth (GFSK, DH1)	X	39.24	96.66	20.08	5.30	70.0	± 9.6 %
		Y	100.00	114.21	26.13		70.0	
		Z	100.00	113.53	25.95		70.0	
10031-CAA	IEEE 802.15.1 Bluetooth (GFSK, DH3)	X	0.70	64.67	7.60	1.88	100.0	± 9.6 %
		Y	100.00	119.57	25.93		100.0	
		Z	100.00	203.35	58.30		100.0	

10032-CAA	IEEE 802.15.1 Bluetooth (GFSK, DH5)	X	0.22	60.00	4.46	1.17	100.0	± 9.6 %
		Y	100.00	128.90	28.50		100.0	
		Z	0.05	60.00	716.63		100.0	
10033-CAA	IEEE 802.15.1 Bluetooth (PI/4-DQPSK, DH1)	X	5.88	82.11	20.60	5.30	70.0	± 9.6 %
		Y	100.00	130.10	35.25		70.0	
		Z	100.00	130.44	35.50		70.0	
10034-CAA	IEEE 802.15.1 Bluetooth (PI/4-DQPSK, DH3)	X	1.91	70.14	14.59	1.88	100.0	± 9.6 %
		Y	15.17	101.17	26.24		100.0	
		Z	100.00	133.78	35.08		100.0	
10035-CAA	IEEE 802.15.1 Bluetooth (PI/4-DQPSK, DH5)	X	1.40	67.44	13.13	1.17	100.0	± 9.6 %
		Y	5.12	86.66	21.65		100.0	
		Z	100.00	135.93	35.45		100.0	
10036-CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH1)	X	7.18	85.26	21.74	5.30	70.0	± 9.6 %
		Y	100.00	130.56	35.46		70.0	
		Z	100.00	130.90	35.71		70.0	
10037-CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH3)	X	1.82	69.68	14.36	1.88	100.0	± 9.6 %
		Y	12.48	98.46	25.46		100.0	
		Z	100.00	133.83	35.05		100.0	
10038-CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH5)	X	1.40	67.68	13.34	1.17	100.0	± 9.6 %
		Y	5.36	87.69	22.12		100.0	
		Z	100.00	137.34	36.07		100.0	
10039-CAB	CDMA2000 (1xRTT, RC1)	X	1.21	66.39	12.34	0.00	150.0	± 9.6 %
		Y	2.64	77.56	17.99		150.0	
		Z	100.00	136.32	35.05		150.0	
10042-CAB	IS-54 / IS-136 FDD (TDMA/FDM, PI/4-DQPSK, Halfrate)	X	8.42	80.60	16.47	7.78	50.0	± 9.6 %
		Y	100.00	111.73	25.67		50.0	
		Z	100.00	110.52	25.33		50.0	
10044-CAA	IS-91/EIA/TIA-553 FDD (FDMA, FM)	X	0.08	120.65	10.32	0.00	150.0	± 9.6 %
		Y	0.02	122.96	9.69		150.0	
		Z	0.00	63.55	28.74		150.0	
10048-CAA	DECT (TDD, TDMA/FDM, GFSK, Full Slot, 24)	X	8.00	77.28	18.17	13.80	25.0	± 9.6 %
		Y	100.00	114.54	29.18		25.0	
		Z	100.00	115.08	29.90		25.0	
10049-CAA	DECT (TDD, TDMA/FDM, GFSK, Double Slot, 12)	X	8.49	80.03	17.94	10.79	40.0	± 9.6 %
		Y	100.00	114.59	28.12		40.0	
		Z	100.00	115.30	28.83		40.0	
10056-CAA	UMTS-TDD (TD-SCDMA, 1.28 Mcps)	X	10.16	85.42	22.06	9.03	50.0	± 9.6 %
		Y	100.00	125.26	34.24		50.0	
		Z	100.00	124.20	33.96		50.0	
10058-DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1-2-3)	X	4.34	75.04	23.40	6.55	100.0	± 9.6 %
		Y	5.46	80.99	26.66		100.0	
		Z	8.64	93.41	32.33		100.0	
10059-CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps)	X	1.09	63.38	14.43	0.61	110.0	± 9.6 %
		Y	1.26	66.48	16.96		110.0	
		Z	2.62	87.60	28.83		110.0	
10060-CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps)	X	2.51	80.68	19.07	1.30	110.0	± 9.6 %
		Y	100.00	141.35	37.14		110.0	
		Z	100.00	167.83	48.09		110.0	

10061-CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps)	X	2.14	74.46	18.99	2.04	110.0	± 9.6 %
		Y	7.65	98.54	28.83		110.0	
		Z	100.00	156.65	45.98		110.0	
10062-CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps)	X	4.57	66.22	16.16	0.49	100.0	± 9.6 %
		Y	4.69	66.85	16.68		100.0	
		Z	4.78	68.02	18.03		100.0	
10063-CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps)	X	4.59	66.31	16.25	0.72	100.0	± 9.6 %
		Y	4.71	66.97	16.79		100.0	
		Z	4.81	68.17	18.16		100.0	
10064-CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps)	X	4.88	66.60	16.50	0.86	100.0	± 9.6 %
		Y	5.00	67.23	17.02		100.0	
		Z	5.10	68.35	18.32		100.0	
10065-CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps)	X	4.74	66.48	16.58	1.21	100.0	± 9.6 %
		Y	4.87	67.15	17.14		100.0	
		Z	4.98	68.34	18.49		100.0	
10066-CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps)	X	4.76	66.51	16.74	1.46	100.0	± 9.6 %
		Y	4.89	67.19	17.32		100.0	
		Z	5.00	68.38	18.68		100.0	
10067-CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps)	X	5.06	66.69	17.19	2.04	100.0	± 9.6 %
		Y	5.18	67.32	17.75		100.0	
		Z	5.28	68.42	19.03		100.0	
10068-CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps)	X	5.11	66.77	17.42	2.55	100.0	± 9.6 %
		Y	5.24	67.43	18.01		100.0	
		Z	5.34	68.50	19.26		100.0	
10069-CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps)	X	5.19	66.78	17.61	2.67	100.0	± 9.6 %
		Y	5.32	67.39	18.18		100.0	
		Z	5.41	68.45	19.42		100.0	
10071-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 9 Mbps)	X	4.87	66.36	17.04	1.99	100.0	± 9.6 %
		Y	4.99	66.98	17.59		100.0	
		Z	5.08	68.03	18.86		100.0	
10072-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 12 Mbps)	X	4.85	66.66	17.23	2.30	100.0	± 9.6 %
		Y	4.98	67.36	17.85		100.0	
		Z	5.10	68.57	19.20		100.0	
10073-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 18 Mbps)	X	4.91	66.82	17.55	2.83	100.0	± 9.6 %
		Y	5.05	67.54	18.19		100.0	
		Z	5.18	68.80	19.56		100.0	
10074-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 24 Mbps)	X	4.90	66.73	17.69	3.30	100.0	± 9.6 %
		Y	5.03	67.44	18.35		100.0	
		Z	5.17	68.69	19.70		100.0	
10075-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 36 Mbps)	X	4.95	66.86	18.00	3.82	90.0	± 9.6 %
		Y	5.08	67.61	18.70		90.0	
		Z	5.23	68.89	20.05		90.0	
10076-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 48 Mbps)	X	4.96	66.66	18.12	4.15	90.0	± 9.6 %
		Y	5.08	67.35	18.79		90.0	
		Z	5.22	68.57	20.11		90.0	
10077-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 54 Mbps)	X	4.99	66.73	18.22	4.30	90.0	± 9.6 %
		Y	5.10	67.42	18.89		90.0	
		Z	5.25	68.64	20.20		90.0	

10081-CAB	CDMA2000 (1xRTT, RC3)	X	0.62	62.47	9.69	0.00	150.0	± 9.6 %
		Y	0.98	68.75	13.96		150.0	
		Z	100.00	144.14	36.74		150.0	
10082-CAB	IS-54 / IS-136 FDD (TDMA/FDM, PI/4-DQPSK, Fullrate)	X	0.76	60.00	4.46	4.77	80.0	± 9.6 %
		Y	0.79	60.00	4.75		80.0	
		Z	0.84	60.00	4.63		80.0	
10090-DAC	GPRS-FDD (TDMA, GMSK, TN 0-4)	X	100.00	108.18	23.74	6.56	60.0	± 9.6 %
		Y	100.00	115.44	27.16		60.0	
		Z	100.00	114.99	27.16		60.0	
10097-CAB	UMTS-FDD (HSDPA)	X	1.61	65.71	14.22	0.00	150.0	± 9.6 %
		Y	1.91	69.00	16.46		150.0	
		Z	9.83	102.12	30.17		150.0	
10098-CAB	UMTS-FDD (HSUPA, Subtest 2)	X	1.57	65.64	14.17	0.00	150.0	± 9.6 %
		Y	1.88	68.97	16.44		150.0	
		Z	10.76	104.21	30.81		150.0	
10099-DAC	EDGE-FDD (TDMA, 8PSK, TN 0-4)	X	8.35	88.07	30.46	9.56	60.0	± 9.6 %
		Y	13.81	102.80	36.86		60.0	
		Z	27.23	120.71	42.92		60.0	
10100-CAD	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, QPSK)	X	2.82	68.51	15.54	0.00	150.0	± 9.6 %
		Y	3.30	71.53	17.30		150.0	
		Z	6.75	86.01	24.16		150.0	
10101-CAD	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM)	X	3.07	66.55	15.23	0.00	150.0	± 9.6 %
		Y	3.28	68.02	16.24		150.0	
		Z	3.86	72.40	19.31		150.0	
10102-CAD	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM)	X	3.18	66.59	15.37	0.00	150.0	± 9.6 %
		Y	3.38	67.95	16.32		150.0	
		Z	3.89	71.91	19.19		150.0	
10103-CAD	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, QPSK)	X	5.78	73.84	19.40	3.98	65.0	± 9.6 %
		Y	7.24	78.41	21.73		65.0	
		Z	10.48	86.31	25.44		65.0	
10104-CAD	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM)	X	5.93	72.40	19.61	3.98	65.0	± 9.6 %
		Y	6.74	75.29	21.26		65.0	
		Z	7.74	78.89	23.50		65.0	
10105-CAD	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM)	X	5.64	71.33	19.45	3.98	65.0	± 9.6 %
		Y	6.26	73.70	20.88		65.0	
		Z	7.20	77.28	23.11		65.0	
10108-CAE	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, QPSK)	X	2.46	67.78	15.34	0.00	150.0	± 9.6 %
		Y	2.87	70.74	17.15		150.0	
		Z	6.31	87.14	24.91		150.0	
10109-CAE	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM)	X	2.72	66.30	15.05	0.00	150.0	± 9.6 %
		Y	2.94	67.95	16.20		150.0	
		Z	3.68	73.83	20.00		150.0	
10110-CAE	LTE-FDD (SC-FDMA, 100% RB, 5 MHz, QPSK)	X	1.97	66.77	14.80	0.00	150.0	± 9.6 %
		Y	2.33	69.93	16.83		150.0	
		Z	7.38	93.63	27.29		150.0	
10111-CAE	LTE-FDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM)	X	2.40	66.79	15.11	0.00	150.0	± 9.6 %
		Y	2.70	69.09	16.66		150.0	
		Z	4.56	81.06	22.94		150.0	

10112-CAE	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM)	X	2.85	66.36	15.15	0.00	150.0	± 9.6 %
		Y	3.07	67.90	16.24		150.0	
		Z	3.72	73.15	19.73		150.0	
10113-CAE	LTE-FDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM)	X	2.55	67.02	15.30	0.00	150.0	± 9.6 %
		Y	2.85	69.17	16.77		150.0	
		Z	4.50	79.81	22.48		150.0	
10114-CAC	IEEE 802.11n (HT Greenfield, 13.5 Mbps, BPSK)	X	5.03	66.81	16.15	0.00	150.0	± 9.6 %
		Y	5.12	67.32	16.54		150.0	
		Z	5.28	68.50	17.87		150.0	
10115-CAC	IEEE 802.11n (HT Greenfield, 81 Mbps, 16-QAM)	X	5.32	66.97	16.25	0.00	150.0	± 9.6 %
		Y	5.41	67.46	16.61		150.0	
		Z	5.53	68.43	17.81		150.0	
10116-CAC	IEEE 802.11n (HT Greenfield, 135 Mbps, 64-QAM)	X	5.12	66.99	16.17	0.00	150.0	± 9.6 %
		Y	5.22	67.53	16.56		150.0	
		Z	5.39	68.71	17.89		150.0	
10117-CAC	IEEE 802.11n (HT Mixed, 13.5 Mbps, BPSK)	X	4.99	66.66	16.09	0.00	150.0	± 9.6 %
		Y	5.09	67.20	16.49		150.0	
		Z	5.20	68.20	17.74		150.0	
10118-CAC	IEEE 802.11n (HT Mixed, 81 Mbps, 16-QAM)	X	5.41	67.19	16.37	0.00	150.0	± 9.6 %
		Y	5.50	67.66	16.72		150.0	
		Z	5.70	68.93	18.07		150.0	
10119-CAC	IEEE 802.11n (HT Mixed, 135 Mbps, 64-QAM)	X	5.10	66.95	16.16	0.00	150.0	± 9.6 %
		Y	5.19	67.47	16.54		150.0	
		Z	5.38	68.73	17.91		150.0	
10140-CAD	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM)	X	3.21	66.59	15.29	0.00	150.0	± 9.6 %
		Y	3.42	67.95	16.23		150.0	
		Z	3.93	71.85	19.05		150.0	
10141-CAD	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM)	X	3.34	66.74	15.49	0.00	150.0	± 9.6 %
		Y	3.54	68.03	16.39		150.0	
		Z	4.02	71.68	19.09		150.0	
10142-CAD	LTE-FDD (SC-FDMA, 100% RB, 3 MHz, QPSK)	X	1.72	66.43	14.23	0.00	150.0	± 9.6 %
		Y	2.13	70.21	16.64		150.0	
		Z	31.12	120.09	34.26		150.0	
10143-CAD	LTE-FDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM)	X	2.19	66.99	14.48	0.00	150.0	± 9.6 %
		Y	2.63	70.26	16.58		150.0	
		Z	11.22	97.58	27.61		150.0	
10144-CAD	LTE-FDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM)	X	2.03	65.12	13.06	0.00	150.0	± 9.6 %
		Y	2.32	67.44	14.72		150.0	
		Z	4.42	80.07	20.90		150.0	
10145-CAE	LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK)	X	0.98	62.52	9.74	0.00	150.0	± 9.6 %
		Y	1.34	66.74	12.73		150.0	
		Z	100.00	124.26	29.87		150.0	
10146-CAE	LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM)	X	1.73	64.88	10.88	0.00	150.0	± 9.6 %
		Y	2.39	68.68	12.88		150.0	
		Z	100.00	126.68	32.43		150.0	
10147-CAE	LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM)	X	1.97	66.42	11.78	0.00	150.0	± 9.6 %
		Y	3.19	72.28	14.57		150.0	
		Z	100.00	128.65	33.41		150.0	

10149-CAD	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM)	X	2.73	66.36	15.09	0.00	150.0	± 9.6 %
		Y	2.96	68.02	16.25		150.0	
		Z	3.71	73.98	20.08		150.0	
10150-CAD	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM)	X	2.86	66.42	15.19	0.00	150.0	± 9.6 %
		Y	3.07	67.96	16.28		150.0	
		Z	3.74	73.28	19.81		150.0	
10151-CAD	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK)	X	5.95	75.83	20.27	3.98	65.0	± 9.6 %
		Y	8.01	81.86	23.19		65.0	
		Z	14.27	94.24	28.37		65.0	
10152-CAD	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM)	X	5.43	72.17	19.19	3.98	65.0	± 9.6 %
		Y	6.33	75.51	21.10		65.0	
		Z	7.69	80.29	23.76		65.0	
10153-CAD	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM)	X	5.80	73.19	20.02	3.98	65.0	± 9.6 %
		Y	6.73	76.49	21.88		65.0	
		Z	8.22	81.53	24.66		65.0	
10154-CAE	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, QPSK)	X	2.01	67.12	15.04	0.00	150.0	± 9.6 %
		Y	2.40	70.46	17.14		150.0	
		Z	8.76	96.93	28.45		150.0	
10155-CAE	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM)	X	2.40	66.80	15.12	0.00	150.0	± 9.6 %
		Y	2.70	69.10	16.68		150.0	
		Z	4.57	81.09	22.97		150.0	
10156-CAE	LTE-FDD (SC-FDMA, 50% RB, 5 MHz, QPSK)	X	1.55	66.19	13.80	0.00	150.0	± 9.6 %
		Y	2.01	70.64	16.60		150.0	
		Z	100.00	140.43	38.57		150.0	
10157-CAE	LTE-FDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM)	X	1.82	65.27	12.83	0.00	150.0	± 9.6 %
		Y	2.20	68.35	14.92		150.0	
		Z	11.45	96.56	26.01		150.0	
10158-CAE	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM)	X	2.56	67.08	15.35	0.00	150.0	± 9.6 %
		Y	2.86	69.24	16.82		150.0	
		Z	4.55	80.05	22.60		150.0	
10159-CAE	LTE-FDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM)	X	1.91	65.64	13.09	0.00	150.0	± 9.6 %
		Y	2.33	68.92	15.26		150.0	
		Z	13.96	99.53	26.98		150.0	
10160-CAD	LTE-FDD (SC-FDMA, 50% RB, 15 MHz, QPSK)	X	2.53	67.25	15.32	0.00	150.0	± 9.6 %
		Y	2.82	69.49	16.80		150.0	
		Z	5.02	82.00	23.21		150.0	
10161-CAD	LTE-FDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM)	X	2.75	66.32	15.09	0.00	150.0	± 9.6 %
		Y	2.97	67.93	16.23		150.0	
		Z	3.70	73.78	20.00		150.0	
10162-CAD	LTE-FDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM)	X	2.86	66.50	15.22	0.00	150.0	± 9.6 %
		Y	3.08	68.06	16.33		150.0	
		Z	3.80	73.66	19.96		150.0	
10166-CAE	LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK)	X	3.50	69.08	18.85	3.01	150.0	± 9.6 %
		Y	3.75	70.62	19.67		150.0	
		Z	4.70	78.19	25.09		150.0	
10167-CAE	LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM)	X	4.23	71.58	19.13	3.01	150.0	± 9.6 %
		Y	4.87	74.34	20.39		150.0	
		Z	7.29	85.90	27.06		150.0	

10168-CAE	LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM)	X	4.74	74.07	20.61	3.01	150.0	± 9.6 %
		Y	5.56	77.15	21.92		150.0	
		Z	9.94	93.24	30.19		150.0	
10169-CAD	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	X	2.90	68.30	18.49	3.01	150.0	± 9.6 %
		Y	3.25	70.96	19.84		150.0	
		Z	4.01	78.75	25.77		150.0	
10170-CAD	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM)	X	3.90	73.75	20.69	3.01	150.0	± 9.6 %
		Y	5.16	79.36	22.99		150.0	
		Z	10.56	100.20	33.39		150.0	
10171-AAD	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM)	X	3.19	69.53	17.81	3.01	150.0	± 9.6 %
		Y	3.94	73.66	19.65		150.0	
		Z	6.17	86.81	27.42		150.0	
10172-CAD	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	X	6.79	85.96	26.31	6.02	65.0	± 9.6 %
		Y	15.63	104.26	33.03		65.0	
		Z	100.00	152.71	48.62		65.0	
10173-CAD	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM)	X	10.73	90.79	26.15	6.02	65.0	± 9.6 %
		Y	76.03	127.18	36.79		65.0	
		Z	100.00	141.65	42.99		65.0	
10174-CAD	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM)	X	7.02	82.76	22.95	6.02	65.0	± 9.6 %
		Y	35.67	111.71	32.19		65.0	
		Z	100.00	139.10	41.61		65.0	
10175-CAE	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, QPSK)	X	2.87	67.97	18.23	3.01	150.0	± 9.6 %
		Y	3.21	70.57	19.56		150.0	
		Z	3.91	78.03	25.33		150.0	
10176-CAE	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM)	X	3.91	73.77	20.70	3.01	150.0	± 9.6 %
		Y	5.17	79.39	23.01		150.0	
		Z	10.60	100.29	33.42		150.0	
10177-CAG	LTE-FDD (SC-FDMA, 1 RB, 5 MHz, QPSK)	X	2.89	68.13	18.33	3.01	150.0	± 9.6 %
		Y	3.24	70.76	19.67		150.0	
		Z	3.97	78.38	25.51		150.0	
10178-CAE	LTE-FDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM)	X	3.87	73.53	20.57	3.01	150.0	± 9.6 %
		Y	5.10	79.07	22.85		150.0	
		Z	10.19	99.34	33.07		150.0	
10179-CAE	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM)	X	3.50	71.45	19.08	3.01	150.0	± 9.6 %
		Y	4.48	76.30	21.16		150.0	
		Z	8.22	93.64	30.41		150.0	
10180-CAE	LTE-FDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM)	X	3.18	69.45	17.76	3.01	150.0	± 9.6 %
		Y	3.93	73.56	19.59		150.0	
		Z	6.11	86.54	27.30		150.0	
10181-CAD	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, QPSK)	X	2.88	68.11	18.32	3.01	150.0	± 9.6 %
		Y	3.23	70.74	19.66		150.0	
		Z	3.96	78.35	25.50		150.0	
10182-CAD	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM)	X	3.86	73.51	20.55	3.01	150.0	± 9.6 %
		Y	5.09	79.04	22.84		150.0	
		Z	10.15	99.27	33.04		150.0	
10183-AAC	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM)	X	3.18	69.43	17.75	3.01	150.0	± 9.6 %
		Y	3.92	73.53	19.58		150.0	
		Z	6.08	86.47	27.28		150.0	

10184-CAD	LTE-FDD (SC-FDMA, 1 RB, 3 MHz, QPSK)	X	2.90	68.16	18.34	3.01	150.0	± 9.6 %
		Y	3.24	70.79	19.69		150.0	
		Z	3.98	78.43	25.53		150.0	
10185-CAD	LTE-FDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM)	X	3.88	73.58	20.59	3.01	150.0	± 9.6 %
		Y	5.12	79.14	22.88		150.0	
		Z	10.26	99.48	33.12		150.0	
10186-AAD	LTE-FDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM)	X	3.19	69.49	17.78	3.01	150.0	± 9.6 %
		Y	3.94	73.61	19.62		150.0	
		Z	6.14	86.65	27.34		150.0	
10187-CAE	LTE-FDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK)	X	2.90	68.21	18.41	3.01	150.0	± 9.6 %
		Y	3.25	70.85	19.75		150.0	
		Z	3.99	78.50	25.61		150.0	
10188-CAE	LTE-FDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM)	X	4.01	74.28	21.00	3.01	150.0	± 9.6 %
		Y	5.35	80.07	23.35		150.0	
		Z	11.41	102.07	34.10		150.0	
10189-AAE	LTE-FDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM)	X	3.26	69.91	18.06	3.01	150.0	± 9.6 %
		Y	4.06	74.17	19.95		150.0	
		Z	6.51	88.00	27.95		150.0	
10193-CAC	IEEE 802.11n (HT Greenfield, 6.5 Mbps, BPSK)	X	4.41	66.16	15.80	0.00	150.0	± 9.6 %
		Y	4.52	66.77	16.27		150.0	
		Z	4.62	67.98	17.65		150.0	
10194-CAC	IEEE 802.11n (HT Greenfield, 39 Mbps, 16-QAM)	X	4.58	66.47	15.93	0.00	150.0	± 9.6 %
		Y	4.69	67.09	16.39		150.0	
		Z	4.81	68.30	17.77		150.0	
10195-CAC	IEEE 802.11n (HT Greenfield, 65 Mbps, 64-QAM)	X	4.62	66.51	15.95	0.00	150.0	± 9.6 %
		Y	4.74	67.11	16.41		150.0	
		Z	4.85	68.31	17.77		150.0	
10196-CAC	IEEE 802.11n (HT Mixed, 6.5 Mbps, BPSK)	X	4.42	66.22	15.81	0.00	150.0	± 9.6 %
		Y	4.53	66.83	16.29		150.0	
		Z	4.63	68.07	17.68		150.0	
10197-CAC	IEEE 802.11n (HT Mixed, 39 Mbps, 16-QAM)	X	4.60	66.49	15.94	0.00	150.0	± 9.6 %
		Y	4.71	67.11	16.40		150.0	
		Z	4.82	68.32	17.78		150.0	
10198-CAC	IEEE 802.11n (HT Mixed, 65 Mbps, 64-QAM)	X	4.62	66.52	15.96	0.00	150.0	± 9.6 %
		Y	4.74	67.13	16.42		150.0	
		Z	4.85	68.34	17.79		150.0	
10219-CAC	IEEE 802.11n (HT Mixed, 7.2 Mbps, BPSK)	X	4.36	66.22	15.77	0.00	150.0	± 9.6 %
		Y	4.48	66.85	16.26		150.0	
		Z	4.59	68.16	17.68		150.0	
10220-CAC	IEEE 802.11n (HT Mixed, 43.3 Mbps, 16-QAM)	X	4.59	66.46	15.93	0.00	150.0	± 9.6 %
		Y	4.70	67.08	16.39		150.0	
		Z	4.81	68.28	17.76		150.0	
10221-CAC	IEEE 802.11n (HT Mixed, 72.2 Mbps, 64-QAM)	X	4.63	66.46	15.95	0.00	150.0	± 9.6 %
		Y	4.75	67.05	16.40		150.0	
		Z	4.85	68.22	17.75		150.0	
10222-CAC	IEEE 802.11n (HT Mixed, 15 Mbps, BPSK)	X	4.97	66.66	16.09	0.00	150.0	± 9.6 %
		Y	5.06	67.21	16.49		150.0	
		Z	5.18	68.23	17.75		150.0	

10223-CAC	IEEE 802.11n (HT Mixed, 90 Mbps, 16-QAM)	X	5.28	66.91	16.24	0.00	150.0	± 9.6 %
		Y	5.36	67.38	16.59		150.0	
		Z	5.53	68.53	17.89		150.0	
10224-CAC	IEEE 802.11n (HT Mixed, 150 Mbps, 64-QAM)	X	5.01	66.77	16.07	0.00	150.0	± 9.6 %
		Y	5.11	67.33	16.47		150.0	
		Z	5.24	68.37	17.74		150.0	
10225-CAB	UMTS-FDD (HSPA+)	X	2.65	65.26	14.61	0.00	150.0	± 9.6 %
		Y	2.82	66.55	15.63		150.0	
		Z	3.24	70.82	18.67		150.0	
10226-CAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM)	X	11.47	92.08	26.66	6.02	65.0	± 9.6 %
		Y	91.36	130.79	37.78		65.0	
		Z	100.00	141.90	43.15		65.0	
10227-CAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM)	X	10.85	89.85	25.35	6.02	65.0	± 9.6 %
		Y	68.33	122.93	35.09		65.0	
		Z	100.00	138.74	41.51		65.0	
10228-CAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK)	X	8.03	89.61	27.69	6.02	65.0	± 9.6 %
		Y	24.81	114.02	35.97		65.0	
		Z	100.00	153.31	48.90		65.0	
10229-CAB	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM)	X	10.81	90.89	26.19	6.02	65.0	± 9.6 %
		Y	76.70	127.32	36.84		65.0	
		Z	100.00	141.61	42.98		65.0	
10230-CAB	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM)	X	10.21	88.74	24.90	6.02	65.0	± 9.6 %
		Y	58.56	120.04	34.29		65.0	
		Z	100.00	138.58	41.40		65.0	
10231-CAB	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, QPSK)	X	7.66	88.62	27.26	6.02	65.0	± 9.6 %
		Y	22.70	112.05	35.32		65.0	
		Z	100.00	153.11	48.77		65.0	
10232-CAD	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM)	X	10.79	90.87	26.18	6.02	65.0	± 9.6 %
		Y	76.69	127.33	36.84		65.0	
		Z	100.00	141.64	42.99		65.0	
10233-CAD	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM)	X	10.19	88.72	24.90	6.02	65.0	± 9.6 %
		Y	58.44	120.02	34.29		65.0	
		Z	100.00	138.61	41.41		65.0	
10234-CAD	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK)	X	7.36	87.72	26.83	6.02	65.0	± 9.6 %
		Y	21.03	110.26	34.68		65.0	
		Z	100.00	152.70	48.52		65.0	
10235-CAD	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM)	X	10.79	90.90	26.19	6.02	65.0	± 9.6 %
		Y	77.22	127.47	36.88		65.0	
		Z	100.00	141.66	43.00		65.0	
10236-CAD	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM)	X	10.28	88.85	24.93	6.02	65.0	± 9.6 %
		Y	59.86	120.39	34.37		65.0	
		Z	100.00	138.52	41.37		65.0	
10237-CAD	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK)	X	7.67	88.67	27.28	6.02	65.0	± 9.6 %
		Y	22.88	112.26	35.38		65.0	
		Z	100.00	153.17	48.79		65.0	
10238-CAD	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM)	X	10.76	90.85	26.17	6.02	65.0	± 9.6 %
		Y	76.68	127.34	36.84		65.0	
		Z	100.00	141.67	43.00		65.0	

10239-CAD	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM)	X	10.16	88.69	24.89	6.02	65.0	± 9.6 %
		Y	58.30	120.01	34.28		65.0	
		Z	100.00	138.65	41.42		65.0	
10240-CAD	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, QPSK)	X	7.65	88.63	27.26	6.02	65.0	± 9.6 %
		Y	22.78	112.18	35.36		65.0	
		Z	100.00	153.20	48.80		65.0	
10241-CAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM)	X	7.64	79.37	24.46	6.98	65.0	± 9.6 %
		Y	9.48	84.64	26.94		65.0	
		Z	13.65	95.22	32.26		65.0	
10242-CAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM)	X	7.05	77.70	23.68	6.98	65.0	± 9.6 %
		Y	8.30	81.77	25.72		65.0	
		Z	12.41	92.80	31.22		65.0	
10243-CAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK)	X	5.84	74.87	23.33	6.98	65.0	± 9.6 %
		Y	6.46	77.70	24.98		65.0	
		Z	8.47	85.73	29.63		65.0	
10244-CAB	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM)	X	5.29	73.69	17.46	3.98	65.0	± 9.6 %
		Y	8.12	80.92	20.73		65.0	
		Z	100.00	126.71	35.61		65.0	
10245-CAB	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM)	X	5.18	73.12	17.16	3.98	65.0	± 9.6 %
		Y	7.73	79.85	20.27		65.0	
		Z	100.00	126.21	35.40		65.0	
10246-CAB	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, QPSK)	X	4.31	73.88	17.47	3.98	65.0	± 9.6 %
		Y	9.24	86.90	23.16		65.0	
		Z	100.00	126.35	34.36		65.0	
10247-CAD	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM)	X	4.45	71.49	17.18	3.98	65.0	± 9.6 %
		Y	6.01	77.14	20.22		65.0	
		Z	10.59	87.86	24.60		65.0	
10248-CAD	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM)	X	4.48	71.09	16.99	3.98	65.0	± 9.6 %
		Y	5.87	76.20	19.81		65.0	
		Z	9.23	84.87	23.50		65.0	
10249-CAD	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, QPSK)	X	5.36	77.27	19.79	3.98	65.0	± 9.6 %
		Y	10.78	90.11	25.21		65.0	
		Z	100.00	130.59	36.94		65.0	
10250-CAD	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM)	X	5.39	74.24	20.05	3.98	65.0	± 9.6 %
		Y	6.75	78.97	22.57		65.0	
		Z	10.28	88.53	26.89		65.0	
10251-CAD	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM)	X	5.19	72.32	18.86	3.98	65.0	± 9.6 %
		Y	6.25	76.21	21.05		65.0	
		Z	8.22	82.50	24.18		65.0	
10252-CAD	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, QPSK)	X	5.87	77.82	21.01	3.98	65.0	± 9.6 %
		Y	9.24	86.82	25.03		65.0	
		Z	37.03	114.88	34.51		65.0	
10253-CAD	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM)	X	5.33	71.70	18.97	3.98	65.0	± 9.6 %
		Y	6.16	74.84	20.81		65.0	
		Z	7.37	79.30	23.34		65.0	
10254-CAD	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM)	X	5.67	72.64	19.71	3.98	65.0	± 9.6 %
		Y	6.53	75.77	21.52		65.0	
		Z	7.87	80.48	24.15		65.0	

10255-CAD	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, QPSK)	X	5.71	75.28	20.26	3.98	65.0	± 9.6 %
		Y	7.47	80.83	23.03		65.0	
		Z	12.56	92.28	27.97		65.0	
10256-CAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM)	X	4.04	69.65	14.62	3.98	65.0	± 9.6 %
		Y	6.07	75.95	17.72		65.0	
		Z	100.00	122.03	32.77		65.0	
10257-CAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM)	X	3.95	69.00	14.23	3.98	65.0	± 9.6 %
		Y	5.69	74.62	17.08		65.0	
		Z	100.00	121.15	32.37		65.0	
10258-CAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK)	X	3.28	69.68	14.78	3.98	65.0	± 9.6 %
		Y	6.37	80.32	19.92		65.0	
		Z	75.35	117.49	30.74		65.0	
10259-CAB	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM)	X	4.82	72.54	18.23	3.98	65.0	± 9.6 %
		Y	6.31	77.82	21.06		65.0	
		Z	10.52	88.16	25.44		65.0	
10260-CAB	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM)	X	4.87	72.35	18.16	3.98	65.0	± 9.6 %
		Y	6.27	77.35	20.88		65.0	
		Z	9.87	86.59	24.88		65.0	
10261-CAB	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, QPSK)	X	5.33	76.81	20.04	3.98	65.0	± 9.6 %
		Y	9.15	87.11	24.61		65.0	
		Z	70.08	125.67	36.47		65.0	
10262-CAD	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM)	X	5.38	74.18	20.01	3.98	65.0	± 9.6 %
		Y	6.73	78.91	22.52		65.0	
		Z	10.24	88.40	26.82		65.0	
10263-CAD	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM)	X	5.18	72.30	18.85	3.98	65.0	± 9.6 %
		Y	6.24	76.18	21.05		65.0	
		Z	8.20	82.47	24.17		65.0	
10264-CAD	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, QPSK)	X	5.82	77.64	20.91	3.98	65.0	± 9.6 %
		Y	9.12	86.55	24.91		65.0	
		Z	35.50	114.00	34.24		65.0	
10265-CAD	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM)	X	5.42	72.17	19.19	3.98	65.0	± 9.6 %
		Y	6.33	75.51	21.10		65.0	
		Z	7.69	80.30	23.77		65.0	
10266-CAD	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM)	X	5.79	73.18	20.01	3.98	65.0	± 9.6 %
		Y	6.73	76.48	21.87		65.0	
		Z	8.21	81.50	24.64		65.0	
10267-CAD	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK)	X	5.94	75.79	20.26	3.98	65.0	± 9.6 %
		Y	7.99	81.80	23.16		65.0	
		Z	14.17	94.10	28.32		65.0	
10268-CAD	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM)	X	6.09	72.33	19.70	3.98	65.0	± 9.6 %
		Y	6.85	74.98	21.24		65.0	
		Z	7.72	78.22	23.32		65.0	
10269-CAD	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM)	X	6.09	71.98	19.61	3.98	65.0	± 9.6 %
		Y	6.78	74.45	21.07		65.0	
		Z	7.54	77.37	23.01		65.0	
10270-CAD	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, QPSK)	X	6.01	73.82	19.62	3.98	65.0	± 9.6 %
		Y	7.24	77.73	21.68		65.0	
		Z	9.32	83.64	24.76		65.0	

10274-CAB	UMTS-FDD (HSUPA, Subtest 5, 3GPP Rel8.10)	X	2.42	65.43	14.40	0.00	150.0	± 9.6 %
		Y	2.62	67.03	15.61		150.0	
		Z	3.33	73.26	19.54		150.0	
10275-CAB	UMTS-FDD (HSUPA, Subtest 5, 3GPP Rel8.4)	X	1.38	65.56	13.83	0.00	150.0	± 9.6 %
		Y	1.72	69.59	16.48		150.0	
		Z	100.00	146.31	41.06		150.0	
10277-CAA	PHS (QPSK)	X	2.29	61.61	7.35	9.03	50.0	± 9.6 %
		Y	2.34	62.34	7.90		50.0	
		Z	2.54	62.33	8.00		50.0	
10278-CAA	PHS (QPSK, BW 884MHz, Rolloff 0.5)	X	4.07	69.55	14.07	9.03	50.0	± 9.6 %
		Y	7.95	80.43	19.13		50.0	
		Z	7.26	77.94	18.06		50.0	
10279-CAA	PHS (QPSK, BW 884MHz, Rolloff 0.38)	X	4.18	69.82	14.25	9.03	50.0	± 9.6 %
		Y	8.16	80.74	19.30		50.0	
		Z	7.49	78.32	18.26		50.0	
10290-AAB	CDMA2000, RC1, SO55, Full Rate	X	1.05	64.64	11.20	0.00	150.0	± 9.6 %
		Y	1.76	71.84	15.41		150.0	
		Z	100.00	132.28	33.17		150.0	
10291-AAB	CDMA2000, RC3, SO55, Full Rate	X	0.61	62.34	9.61	0.00	150.0	± 9.6 %
		Y	0.95	68.38	13.76		150.0	
		Z	100.00	143.78	36.57		150.0	
10292-AAB	CDMA2000, RC3, SO32, Full Rate	X	0.67	64.13	10.90	0.00	150.0	± 9.6 %
		Y	1.74	77.70	18.10		150.0	
		Z	100.00	159.02	42.81		150.0	
10293-AAB	CDMA2000, RC3, SO3, Full Rate	X	0.85	66.91	12.76	0.00	150.0	± 9.6 %
		Y	6.38	96.73	24.88		150.0	
		Z	100.00	168.80	47.18		150.0	
10295-AAB	CDMA2000, RC1, SO3, 1/8th Rate 25 fr.	X	7.66	80.36	21.49	9.03	50.0	± 9.6 %
		Y	12.17	90.88	26.28		50.0	
		Z	50.80	114.51	32.91		50.0	
10297-AAC	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, QPSK)	X	2.47	67.87	15.40	0.00	150.0	± 9.6 %
		Y	2.89	70.87	17.22		150.0	
		Z	6.46	87.63	25.10		150.0	
10298-AAC	LTE-FDD (SC-FDMA, 50% RB, 3 MHz, QPSK)	X	1.26	64.71	11.97	0.00	150.0	± 9.6 %
		Y	1.75	69.75	15.19		150.0	
		Z	100.00	134.02	34.83		150.0	
10299-AAC	LTE-FDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM)	X	2.36	68.20	13.52	0.00	150.0	± 9.6 %
		Y	3.43	73.15	15.84		150.0	
		Z	100.00	132.13	35.60		150.0	
10300-AAC	LTE-FDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM)	X	1.82	64.24	10.85	0.00	150.0	± 9.6 %
		Y	2.18	66.39	12.08		150.0	
		Z	100.00	124.21	31.76		150.0	
10301-AAA	IEEE 802.16e WiMAX (29:18, 5ms, 10MHz, QPSK, PUSC)	X	4.59	64.78	16.94	4.17	50.0	± 9.6 %
		Y	4.96	66.46	18.00		50.0	
		Z	5.39	69.01	19.81		50.0	
10302-AAA	IEEE 802.16e WiMAX (29:18, 5ms, 10MHz, QPSK, PUSC, 3 CTRL symbols)	X	5.13	65.63	17.77	4.96	50.0	± 9.6 %
		Y	5.34	66.57	18.42		50.0	
		Z	5.63	68.33	19.79		50.0	

10303-AAA	IEEE 802.16e WiMAX (31:15, 5ms, 10MHz, 64QAM, PUSC)	X	4.88	65.29	17.60	4.96	50.0	± 9.6 %
		Y	5.09	66.26	18.29		50.0	
		Z	5.39	68.15	19.72		50.0	
10304-AAA	IEEE 802.16e WiMAX (29:18, 5ms, 10MHz, 64QAM, PUSC)	X	4.68	65.10	17.07	4.17	50.0	± 9.6 %
		Y	4.89	66.08	17.75		50.0	
		Z	5.20	68.05	19.27		50.0	
10305-AAA	IEEE 802.16e WiMAX (31:15, 10ms, 10MHz, 64QAM, PUSC, 15 symbols)	X	4.48	67.75	19.41	6.02	35.0	± 9.6 %
		Y	4.71	69.04	20.42		35.0	
		Z	6.14	75.94	23.95		35.0	
10306-AAA	IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, 64QAM, PUSC, 18 symbols)	X	4.73	66.53	18.94	6.02	35.0	± 9.6 %
		Y	4.92	67.52	19.74		35.0	
		Z	5.62	71.52	22.13		35.0	
10307-AAA	IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, QPSK, PUSC, 18 symbols)	X	4.64	66.74	18.93	6.02	35.0	± 9.6 %
		Y	4.84	67.81	19.76		35.0	
		Z	5.66	72.30	22.36		35.0	
10308-AAA	IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, 16QAM, PUSC)	X	4.62	66.96	19.06	6.02	35.0	± 9.6 %
		Y	4.83	68.07	19.93		35.0	
		Z	5.73	72.89	22.67		35.0	
10309-AAA	IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, 16QAM, AMC 2x3, 18 symbols)	X	4.79	66.73	19.08	6.02	35.0	± 9.6 %
		Y	4.98	67.77	19.90		35.0	
		Z	5.71	71.84	22.32		35.0	
10310-AAA	IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, QPSK, AMC 2x3, 18 symbols)	X	4.69	66.61	18.93	6.02	35.0	± 9.6 %
		Y	4.87	67.63	19.73		35.0	
		Z	5.63	71.86	22.23		35.0	
10311-AAC	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, QPSK)	X	2.81	67.24	15.15	0.00	150.0	± 9.6 %
		Y	3.26	70.05	16.82		150.0	
		Z	6.11	82.76	23.09		150.0	
10313-AAA	iDEN 1:3	X	2.72	68.85	13.88	6.99	70.0	± 9.6 %
		Y	6.74	81.65	19.41		70.0	
		Z	100.00	116.93	28.94		70.0	
10314-AAA	iDEN 1:6	X	3.52	73.46	18.52	10.00	30.0	± 9.6 %
		Y	14.65	98.15	27.72		30.0	
		Z	297.27	144.47	38.49		30.0	
10315-AAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 96pc duty cycle)	X	0.97	62.30	13.80	0.17	150.0	± 9.6 %
		Y	1.09	64.70	15.96		150.0	
		Z	1.69	79.83	26.00		150.0	
10316-AAB	IEEE 802.11g WiFi 2.4 GHz (ERP-OFDM, 6 Mbps, 96pc duty cycle)	X	4.47	66.20	15.92	0.17	150.0	± 9.6 %
		Y	4.58	66.85	16.44		150.0	
		Z	4.69	68.08	17.83		150.0	
10317-AAC	IEEE 802.11a WiFi 5 GHz (OFDM, 6 Mbps, 96pc duty cycle)	X	4.47	66.20	15.92	0.17	150.0	± 9.6 %
		Y	4.58	66.85	16.44		150.0	
		Z	4.69	68.08	17.83		150.0	
10400-AAD	IEEE 802.11ac WiFi (20MHz, 64-QAM, 99pc duty cycle)	X	4.57	66.51	15.91	0.00	150.0	± 9.6 %
		Y	4.69	67.14	16.38		150.0	
		Z	4.80	68.40	17.78		150.0	
10401-AAD	IEEE 802.11ac WiFi (40MHz, 64-QAM, 99pc duty cycle)	X	5.31	66.85	16.18	0.00	150.0	± 9.6 %
		Y	5.37	67.26	16.50		150.0	
		Z	5.56	68.46	17.82		150.0	

10402-AAD	IEEE 802.11ac WiFi (80MHz, 64-QAM, 99pc duty cycle)	X	5.54	67.08	16.16	0.00	150.0	± 9.6 %
		Y	5.63	67.59	16.52		150.0	
		Z	5.73	68.34	17.60		150.0	
10403-AAB	CDMA2000 (1xEV-DO, Rev. 0)	X	1.05	64.64	11.20	0.00	115.0	± 9.6 %
		Y	1.76	71.84	15.41		115.0	
		Z	100.00	132.28	33.17		115.0	
10404-AAB	CDMA2000 (1xEV-DO, Rev. A)	X	1.05	64.64	11.20	0.00	115.0	± 9.6 %
		Y	1.76	71.84	15.41		115.0	
		Z	100.00	132.28	33.17		115.0	
10406-AAB	CDMA2000, RC3, SO32, SCH0, Full Rate	X	19.76	100.64	25.59	0.00	100.0	± 9.6 %
		Y	100.00	120.36	29.84		100.0	
		Z	100.00	149.48	43.21		100.0	
10410-AAD	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9, Subframe Conf=4)	X	27.32	104.37	26.03	3.23	80.0	± 9.6 %
		Y	100.00	123.54	31.08		80.0	
		Z	100.00	147.64	42.34		80.0	
10415-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 99pc duty cycle)	X	0.90	61.64	13.32	0.00	150.0	± 9.6 %
		Y	1.00	63.67	15.26		150.0	
		Z	1.35	75.86	24.24		150.0	
10416-AAA	IEEE 802.11g WiFi 2.4 GHz (ERP-OFDM, 6 Mbps, 99pc duty cycle)	X	4.42	66.20	15.87	0.00	150.0	± 9.6 %
		Y	4.52	66.81	16.34		150.0	
		Z	4.63	68.03	17.73		150.0	
10417-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps, 99pc duty cycle)	X	4.42	66.20	15.87	0.00	150.0	± 9.6 %
		Y	4.52	66.81	16.34		150.0	
		Z	4.63	68.03	17.73		150.0	
10418-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 99pc duty cycle, Long preambule)	X	4.40	66.34	15.88	0.00	150.0	± 9.6 %
		Y	4.52	66.98	16.36		150.0	
		Z	4.64	68.31	17.81		150.0	
10419-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 99pc duty cycle, Short preambule)	X	4.43	66.30	15.88	0.00	150.0	± 9.6 %
		Y	4.54	66.92	16.36		150.0	
		Z	4.65	68.20	17.78		150.0	
10422-AAB	IEEE 802.11n (HT Greenfield, 7.2 Mbps, BPSK)	X	4.54	66.32	15.91	0.00	150.0	± 9.6 %
		Y	4.65	66.91	16.37		150.0	
		Z	4.75	68.08	17.72		150.0	
10423-AAB	IEEE 802.11n (HT Greenfield, 43.3 Mbps, 16-QAM)	X	4.70	66.62	16.03	0.00	150.0	± 9.6 %
		Y	4.82	67.23	16.48		150.0	
		Z	4.93	68.42	17.83		150.0	
10424-AAB	IEEE 802.11n (HT Greenfield, 72.2 Mbps, 64-QAM)	X	4.62	66.57	15.99	0.00	150.0	± 9.6 %
		Y	4.74	67.18	16.46		150.0	
		Z	4.85	68.42	17.84		150.0	
10425-AAB	IEEE 802.11n (HT Greenfield, 15 Mbps, BPSK)	X	5.25	66.96	16.24	0.00	150.0	± 9.6 %
		Y	5.33	67.44	16.60		150.0	
		Z	5.49	68.57	17.89		150.0	
10426-AAB	IEEE 802.11n (HT Greenfield, 90 Mbps, 16-QAM)	X	5.26	67.01	16.26	0.00	150.0	± 9.6 %
		Y	5.33	67.46	16.60		150.0	
		Z	5.55	68.77	17.99		150.0	

10427-AAB	IEEE 802.11n (HT Greenfield, 150 Mbps, 64-QAM)	X	5.26	66.96	16.24	0.00	150.0	± 9.6 %
		Y	5.35	67.44	16.59		150.0	
		Z	5.52	68.59	17.89		150.0	
10430-AAB	LTE-FDD (OFDMA, 5 MHz, E-TM 3.1)	X	4.09	70.21	17.69	0.00	150.0	± 9.6 %
		Y	4.37	71.56	18.62		150.0	
		Z	5.82	78.95	22.74		150.0	
10431-AAB	LTE-FDD (OFDMA, 10 MHz, E-TM 3.1)	X	4.07	66.63	15.76	0.00	150.0	± 9.6 %
		Y	4.22	67.44	16.38		150.0	
		Z	4.44	69.46	18.16		150.0	
10432-AAB	LTE-FDD (OFDMA, 15 MHz, E-TM 3.1)	X	4.38	66.58	15.90	0.00	150.0	± 9.6 %
		Y	4.51	67.26	16.42		150.0	
		Z	4.66	68.77	17.95		150.0	
10433-AAB	LTE-FDD (OFDMA, 20 MHz, E-TM 3.1)	X	4.64	66.60	16.01	0.00	150.0	± 9.6 %
		Y	4.76	67.22	16.48		150.0	
		Z	4.87	68.45	17.86		150.0	
10434-AAA	W-CDMA (BS Test Model 1, 64 DPCH)	X	4.15	70.89	17.54	0.00	150.0	± 9.6 %
		Y	4.53	72.64	18.67		150.0	
		Z	7.09	82.89	23.74		150.0	
10435-AAC	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	24.60	102.81	25.59	3.23	80.0	± 9.6 %
		Y	100.00	123.31	30.97		80.0	
		Z	100.00	147.30	42.18		80.0	
10447-AAB	LTE-FDD (OFDMA, 5 MHz, E-TM 3.1, Clipping 44%)	X	3.32	66.37	14.85	0.00	150.0	± 9.6 %
		Y	3.53	67.60	15.79		150.0	
		Z	4.02	71.32	18.30		150.0	
10448-AAB	LTE-FDD (OFDMA, 10 MHz, E-TM 3.1, Clippin 44%)	X	3.91	66.40	15.61	0.00	150.0	± 9.6 %
		Y	4.06	67.22	16.25		150.0	
		Z	4.28	69.30	18.07		150.0	
10449-AAB	LTE-FDD (OFDMA, 15 MHz, E-TM 3.1, Cliping 44%)	X	4.20	66.39	15.78	0.00	150.0	± 9.6 %
		Y	4.32	67.10	16.33		150.0	
		Z	4.48	68.69	17.92		150.0	
10450-AAB	LTE-FDD (OFDMA, 20 MHz, E-TM 3.1, Clipping 44%)	X	4.40	66.35	15.85	0.00	150.0	± 9.6 %
		Y	4.52	67.00	16.34		150.0	
		Z	4.64	68.30	17.78		150.0	
10451-AAA	W-CDMA (BS Test Model 1, 64 DPCH, Clipping 44%)	X	3.18	66.38	14.35	0.00	150.0	± 9.6 %
		Y	3.44	67.83	15.43		150.0	
		Z	4.12	72.39	18.21		150.0	
10456-AAB	IEEE 802.11ac WiFi (160MHz, 64-QAM, 99pc duty cycle)	X	6.12	67.55	16.43	0.00	150.0	± 9.6 %
		Y	6.19	67.95	16.72		150.0	
		Z	6.37	68.83	17.83		150.0	
10457-AAA	UMTS-FDD (DC-HSDPA)	X	3.69	64.85	15.56	0.00	150.0	± 9.6 %
		Y	3.77	65.44	16.05		150.0	
		Z	3.83	66.57	17.51		150.0	
10458-AAA	CDMA2000 (1xEV-DO, Rev. B, 2 carriers)	X	3.74	69.88	16.74	0.00	150.0	± 9.6 %
		Y	4.15	71.87	18.05		150.0	
		Z	6.76	82.62	23.25		150.0	
10459-AAA	CDMA2000 (1xEV-DO, Rev. B, 3 carriers)	X	5.00	68.27	17.97	0.00	150.0	± 9.6 %
		Y	5.14	68.78	18.40		150.0	
		Z	5.73	72.13	20.67		150.0	

10460-AAA	UMTS-FDD (WCDMA, AMR)	X	0.69	64.49	13.27	0.00	150.0	± 9.6 %
		Y	1.03	71.74	18.06		150.0	
		Z	100.00	184.49	54.58		150.0	
10461-AAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	23.89	104.89	26.96	3.29	80.0	± 9.6 %
		Y	100.00	130.07	34.09		80.0	
		Z	100.00	170.21	52.27		80.0	
10462-AAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	1.60	64.82	10.96	3.23	80.0	± 9.6 %
		Y	100.00	106.86	23.34		80.0	
		Z	100.00	143.39	39.69		80.0	
10463-AAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	1.16	61.38	8.85	3.23	80.0	± 9.6 %
		Y	8.49	80.07	15.85		80.0	
		Z	100.00	136.22	36.37		80.0	
10464-AAA	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	15.04	97.12	24.24	3.23	80.0	± 9.6 %
		Y	100.00	127.37	32.66		80.0	
		Z	100.00	170.30	51.97		80.0	
10465-AAA	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	1.45	63.83	10.44	3.23	80.0	± 9.6 %
		Y	100.00	106.10	22.97		80.0	
		Z	100.00	141.97	39.03		80.0	
10466-AAA	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	1.11	60.93	8.58	3.23	80.0	± 9.6 %
		Y	4.16	73.39	13.73		80.0	
		Z	100.00	134.48	35.59		80.0	
10467-AAC	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	18.13	99.69	24.95	3.23	80.0	± 9.6 %
		Y	100.00	127.69	32.81		80.0	
		Z	100.00	170.90	52.23		80.0	
10468-AAC	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	1.48	64.08	10.57	3.23	80.0	± 9.6 %
		Y	100.00	106.32	23.08		80.0	
		Z	100.00	142.55	39.29		80.0	
10469-AAC	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	1.11	60.94	8.58	3.23	80.0	± 9.6 %
		Y	4.24	73.57	13.79		80.0	
		Z	100.00	134.69	35.67		80.0	
10470-AAC	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	18.25	99.80	24.97	3.23	80.0	± 9.6 %
		Y	100.00	127.74	32.82		80.0	
		Z	100.00	171.17	52.34		80.0	
10471-AAC	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	1.48	64.02	10.54	3.23	80.0	± 9.6 %
		Y	100.00	106.24	23.03		80.0	
		Z	100.00	142.54	39.28		80.0	
10472-AAC	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	1.11	60.91	8.55	3.23	80.0	± 9.6 %
		Y	4.14	73.34	13.70		80.0	
		Z	100.00	134.66	35.65		80.0	
10473-AAC	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	18.11	99.68	24.93	3.23	80.0	± 9.6 %
		Y	100.00	127.70	32.80		80.0	
		Z	100.00	171.13	52.32		80.0	
10474-AAC	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	1.47	63.99	10.52	3.23	80.0	± 9.6 %
		Y	100.00	106.24	23.03		80.0	
		Z	100.00	142.62	39.31		80.0	
10475-AAC	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	1.10	60.89	8.55	3.23	80.0	± 9.6 %
		Y	4.09	73.24	13.66		80.0	
		Z	100.00	134.72	35.68		80.0	

10477-AAC	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	1.44	63.78	10.40	3.23	80.0	± 9.6 %
		Y	100.00	106.01	22.93		80.0	
		Z	100.00	142.22	39.12		80.0	
10478-AAC	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	1.10	60.86	8.52	3.23	80.0	± 9.6 %
		Y	3.98	72.96	13.56		80.0	
		Z	100.00	134.57	35.61		80.0	
10479-AAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	6.08	82.51	21.61	3.23	80.0	± 9.6 %
		Y	34.82	110.64	30.41		80.0	
		Z	100.00	145.60	43.20		80.0	
10480-AAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	5.16	75.77	17.47	3.23	80.0	± 9.6 %
		Y	42.85	104.48	26.37		80.0	
		Z	100.00	130.57	36.17		80.0	
10481-AAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	4.16	72.48	15.88	3.23	80.0	± 9.6 %
		Y	24.18	95.59	23.58		80.0	
		Z	100.00	127.95	34.86		80.0	
10482-AAA	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	1.96	65.98	13.58	2.23	80.0	± 9.6 %
		Y	5.64	81.59	20.64		80.0	
		Z	100.00	127.97	34.02		80.0	
10483-AAA	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	3.49	70.21	15.33	2.23	80.0	± 9.6 %
		Y	9.22	83.90	20.77		80.0	
		Z	100.00	128.26	35.29		80.0	
10484-AAA	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	3.32	69.33	14.96	2.23	80.0	± 9.6 %
		Y	7.69	81.20	19.89		80.0	
		Z	100.00	127.48	34.99		80.0	
10485-AAC	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	2.39	68.19	15.57	2.23	80.0	± 9.6 %
		Y	5.26	81.08	21.53		80.0	
		Z	100.00	133.28	37.08		80.0	
10486-AAC	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	2.53	65.87	14.08	2.23	80.0	± 9.6 %
		Y	4.08	73.44	18.08		80.0	
		Z	100.00	124.45	33.58		80.0	
10487-AAC	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	2.56	65.66	13.98	2.23	80.0	± 9.6 %
		Y	3.99	72.72	17.77		80.0	
		Z	100.00	123.84	33.38		80.0	
10488-AAC	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	2.88	68.87	16.67	2.23	80.0	± 9.6 %
		Y	4.62	77.17	20.79		80.0	
		Z	100.00	133.82	38.32		80.0	
10489-AAC	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	3.04	66.77	15.84	2.23	80.0	± 9.6 %
		Y	3.91	71.35	18.47		80.0	
		Z	9.87	89.46	26.24		80.0	
10490-AAC	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	3.14	66.73	15.85	2.23	80.0	± 9.6 %
		Y	3.97	70.99	18.33		80.0	
		Z	8.76	86.64	25.27		80.0	
10491-AAC	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	3.25	68.32	16.64	2.23	80.0	± 9.6 %
		Y	4.46	74.06	19.67		80.0	
		Z	16.65	99.46	29.56		80.0	
10492-AAC	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	3.47	66.60	16.14	2.23	80.0	± 9.6 %
		Y	4.11	69.87	18.11		80.0	
		Z	6.30	79.04	22.87		80.0	

10493-AAC	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	3.54	66.55	16.14	2.23	80.0	± 9.6 %
		Y	4.16	69.65	18.03		80.0	
		Z	6.12	78.04	22.47		80.0	
10494-AAC	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	3.43	69.35	16.92	2.23	80.0	± 9.6 %
		Y	5.08	76.35	20.40		80.0	
		Z	37.13	113.21	33.12		80.0	
10495-AAC	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	3.48	66.89	16.30	2.23	80.0	± 9.6 %
		Y	4.17	70.37	18.35		80.0	
		Z	6.63	80.25	23.38		80.0	
10496-AAC	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	3.58	66.76	16.29	2.23	80.0	± 9.6 %
		Y	4.22	69.93	18.20		80.0	
		Z	6.24	78.46	22.71		80.0	
10497-AAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	1.42	62.38	10.83	2.23	80.0	± 9.6 %
		Y	3.91	75.77	17.45		80.0	
		Z	100.00	120.52	30.09		80.0	
10498-AAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	1.37	60.00	8.61	2.23	80.0	± 9.6 %
		Y	2.01	64.49	11.62		80.0	
		Z	41.09	97.34	21.84		80.0	
10499-AAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	1.39	60.00	8.48	2.23	80.0	± 9.6 %
		Y	1.89	63.54	11.02		80.0	
		Z	5.19	74.74	15.22		80.0	
10500-AAA	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	2.57	68.35	15.99	2.23	80.0	± 9.6 %
		Y	4.74	78.65	20.96		80.0	
		Z	100.00	133.37	37.55		80.0	
10501-AAA	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	2.76	66.36	14.82	2.23	80.0	± 9.6 %
		Y	3.99	72.53	18.20		80.0	
		Z	37.62	110.73	31.16		80.0	
10502-AAA	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	2.82	66.29	14.74	2.23	80.0	± 9.6 %
		Y	4.03	72.24	18.02		80.0	
		Z	29.89	106.28	29.87		80.0	
10503-AAC	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	2.85	68.70	16.58	2.23	80.0	± 9.6 %
		Y	4.54	76.90	20.67		80.0	
		Z	100.00	133.75	38.28		80.0	
10504-AAC	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	3.03	66.68	15.78	2.23	80.0	± 9.6 %
		Y	3.89	71.24	18.41		80.0	
		Z	9.69	89.09	26.09		80.0	
10505-AAC	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	3.13	66.65	15.79	2.23	80.0	± 9.6 %
		Y	3.95	70.89	18.26		80.0	
		Z	8.61	86.33	25.15		80.0	
10506-AAC	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	3.40	69.23	16.86	2.23	80.0	± 9.6 %
		Y	5.02	76.15	20.31		80.0	
		Z	35.05	112.15	32.82		80.0	
10507-AAC	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	3.47	66.84	16.26	2.23	80.0	± 9.6 %
		Y	4.15	70.30	18.31		80.0	
		Z	6.58	80.11	23.32		80.0	

10508-AAC	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	3.57	66.70	16.25	2.23	80.0	± 9.6 %
		Y	4.20	69.85	18.15		80.0	
		Z	6.19	78.29	22.63		80.0	
10509-AAC	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	3.85	68.72	16.71	2.23	80.0	± 9.6 %
		Y	5.07	73.73	19.33		80.0	
		Z	11.66	89.86	26.23		80.0	
10510-AAC	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	3.99	66.90	16.45	2.23	80.0	± 9.6 %
		Y	4.58	69.64	18.10		80.0	
		Z	6.01	75.75	21.63		80.0	
10511-AAC	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	4.06	66.75	16.43	2.23	80.0	± 9.6 %
		Y	4.60	69.28	17.98		80.0	
		Z	5.84	74.71	21.24		80.0	
10512-AAC	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	X	3.89	69.69	16.95	2.23	80.0	± 9.6 %
		Y	5.60	76.17	20.13		80.0	
		Z	22.79	102.04	29.74		80.0	
10513-AAC	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	X	3.86	67.04	16.49	2.23	80.0	± 9.6 %
		Y	4.49	70.06	18.28		80.0	
		Z	6.20	77.14	22.21		80.0	
10514-AAC	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	X	3.91	66.76	16.43	2.23	80.0	± 9.6 %
		Y	4.47	69.48	18.08		80.0	
		Z	5.85	75.55	21.62		80.0	
10515-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps, 99pc duty cycle)	X	0.86	61.72	13.29	0.00	150.0	± 9.6 %
		Y	0.96	63.93	15.37		150.0	
		Z	1.46	79.09	25.79		150.0	
10516-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps, 99pc duty cycle)	X	0.40	64.69	12.76	0.00	150.0	± 9.6 %
		Y	0.91	79.80	21.72		150.0	
		Z	100.00	307.99	99.87		150.0	
10517-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps, 99pc duty cycle)	X	0.69	62.75	13.23	0.00	150.0	± 9.6 %
		Y	0.84	66.74	16.49		150.0	
		Z	100.00	187.53	56.74		150.0	
10518-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps, 99pc duty cycle)	X	4.41	66.27	15.84	0.00	150.0	± 9.6 %
		Y	4.52	66.89	16.32		150.0	
		Z	4.63	68.18	17.74		150.0	
10519-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps, 99pc duty cycle)	X	4.59	66.50	15.96	0.00	150.0	± 9.6 %
		Y	4.70	67.11	16.43		150.0	
		Z	4.81	68.36	17.82		150.0	
10520-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps, 99pc duty cycle)	X	4.44	66.44	15.87	0.00	150.0	± 9.6 %
		Y	4.56	67.09	16.36		150.0	
		Z	4.68	68.44	17.82		150.0	
10521-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps, 99pc duty cycle)	X	4.37	66.42	15.84	0.00	150.0	± 9.6 %
		Y	4.49	67.09	16.35		150.0	
		Z	4.62	68.48	17.84		150.0	
10522-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps, 99pc duty cycle)	X	4.43	66.53	15.94	0.00	150.0	± 9.6 %
		Y	4.55	67.18	16.44		150.0	
		Z	4.69	68.60	17.93		150.0	

10523-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps, 99pc duty cycle)	X	4.31	66.38	15.78	0.00	150.0	± 9.6 %
		Y	4.43	67.06	16.29		150.0	
		Z	4.58	68.52	17.81		150.0	
10524-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps, 99pc duty cycle)	X	4.37	66.44	15.90	0.00	150.0	± 9.6 %
		Y	4.49	67.10	16.40		150.0	
		Z	4.63	68.53	17.91		150.0	
10525-AAB	IEEE 802.11ac WiFi (20MHz, MCS0, 99pc duty cycle)	X	4.36	65.49	15.50	0.00	150.0	± 9.6 %
		Y	4.48	66.16	16.00		150.0	
		Z	4.63	67.54	17.48		150.0	
10526-AAB	IEEE 802.11ac WiFi (20MHz, MCS1, 99pc duty cycle)	X	4.52	65.84	15.64	0.00	150.0	± 9.6 %
		Y	4.65	66.52	16.14		150.0	
		Z	4.82	67.95	17.63		150.0	
10527-AAB	IEEE 802.11ac WiFi (20MHz, MCS2, 99pc duty cycle)	X	4.44	65.78	15.57	0.00	150.0	± 9.6 %
		Y	4.58	66.49	16.09		150.0	
		Z	4.75	67.97	17.61		150.0	
10528-AAB	IEEE 802.11ac WiFi (20MHz, MCS3, 99pc duty cycle)	X	4.46	65.80	15.61	0.00	150.0	± 9.6 %
		Y	4.59	66.51	16.12		150.0	
		Z	4.76	67.98	17.63		150.0	
10529-AAB	IEEE 802.11ac WiFi (20MHz, MCS4, 99pc duty cycle)	X	4.46	65.80	15.61	0.00	150.0	± 9.6 %
		Y	4.59	66.51	16.12		150.0	
		Z	4.76	67.98	17.63		150.0	
10531-AAB	IEEE 802.11ac WiFi (20MHz, MCS6, 99pc duty cycle)	X	4.44	65.88	15.61	0.00	150.0	± 9.6 %
		Y	4.58	66.62	16.14		150.0	
		Z	4.77	68.16	17.68		150.0	
10532-AAB	IEEE 802.11ac WiFi (20MHz, MCS7, 99pc duty cycle)	X	4.31	65.73	15.53	0.00	150.0	± 9.6 %
		Y	4.45	66.48	16.08		150.0	
		Z	4.63	68.06	17.66		150.0	
10533-AAB	IEEE 802.11ac WiFi (20MHz, MCS8, 99pc duty cycle)	X	4.47	65.85	15.60	0.00	150.0	± 9.6 %
		Y	4.60	66.56	16.12		150.0	
		Z	4.78	68.07	17.64		150.0	
10534-AAB	IEEE 802.11ac WiFi (40MHz, MCS0, 99pc duty cycle)	X	5.01	65.98	15.73	0.00	150.0	± 9.6 %
		Y	5.12	66.56	16.15		150.0	
		Z	5.27	67.65	17.43		150.0	
10535-AAB	IEEE 802.11ac WiFi (40MHz, MCS1, 99pc duty cycle)	X	5.08	66.16	15.81	0.00	150.0	± 9.6 %
		Y	5.18	66.73	16.22		150.0	
		Z	5.37	67.96	17.57		150.0	
10536-AAB	IEEE 802.11ac WiFi (40MHz, MCS2, 99pc duty cycle)	X	4.94	66.09	15.75	0.00	150.0	± 9.6 %
		Y	5.05	66.70	16.19		150.0	
		Z	5.24	67.93	17.55		150.0	
10537-AAB	IEEE 802.11ac WiFi (40MHz, MCS3, 99pc duty cycle)	X	5.00	66.06	15.75	0.00	150.0	± 9.6 %
		Y	5.11	66.66	16.17		150.0	
		Z	5.28	67.82	17.49		150.0	
10538-AAB	IEEE 802.11ac WiFi (40MHz, MCS4, 99pc duty cycle)	X	5.09	66.09	15.80	0.00	150.0	± 9.6 %
		Y	5.20	66.67	16.22		150.0	
		Z	5.35	67.77	17.50		150.0	
10540-AAB	IEEE 802.11ac WiFi (40MHz, MCS6, 99pc duty cycle)	X	5.03	66.12	15.83	0.00	150.0	± 9.6 %
		Y	5.13	66.69	16.24		150.0	
		Z	5.31	67.87	17.57		150.0	

10541-AAB	IEEE 802.11ac WiFi (40MHz, MCS7, 99pc duty cycle)	X	5.00	65.97	15.75	0.00	150.0	± 9.6 %
		Y	5.10	66.56	16.17		150.0	
		Z	5.26	67.66	17.46		150.0	
10542-AAB	IEEE 802.11ac WiFi (40MHz, MCS8, 99pc duty cycle)	X	5.15	66.06	15.81	0.00	150.0	± 9.6 %
		Y	5.26	66.62	16.21		150.0	
		Z	5.40	67.65	17.46		150.0	
10543-AAB	IEEE 802.11ac WiFi (40MHz, MCS9, 99pc duty cycle)	X	5.23	66.11	15.86	0.00	150.0	± 9.6 %
		Y	5.33	66.64	16.24		150.0	
		Z	5.48	67.68	17.49		150.0	
10544-AAB	IEEE 802.11ac WiFi (80MHz, MCS0, 99pc duty cycle)	X	5.33	66.11	15.75	0.00	150.0	± 9.6 %
		Y	5.42	66.66	16.13		150.0	
		Z	5.56	67.54	17.28		150.0	
10545-AAB	IEEE 802.11ac WiFi (80MHz, MCS1, 99pc duty cycle)	X	5.52	66.54	15.91	0.00	150.0	± 9.6 %
		Y	5.61	67.05	16.27		150.0	
		Z	5.85	68.25	17.57		150.0	
10546-AAB	IEEE 802.11ac WiFi (80MHz, MCS2, 99pc duty cycle)	X	5.39	66.30	15.81	0.00	150.0	± 9.6 %
		Y	5.49	66.87	16.20		150.0	
		Z	5.65	67.81	17.38		150.0	
10547-AAB	IEEE 802.11ac WiFi (80MHz, MCS3, 99pc duty cycle)	X	5.46	66.35	15.82	0.00	150.0	± 9.6 %
		Y	5.56	66.90	16.20		150.0	
		Z	5.73	67.87	17.39		150.0	
10548-AAB	IEEE 802.11ac WiFi (80MHz, MCS4, 99pc duty cycle)	X	5.70	67.27	16.25	0.00	150.0	± 9.6 %
		Y	5.79	67.77	16.61		150.0	
		Z	6.27	69.70	18.24		150.0	
10550-AAB	IEEE 802.11ac WiFi (80MHz, MCS6, 99pc duty cycle)	X	5.42	66.35	15.84	0.00	150.0	± 9.6 %
		Y	5.51	66.88	16.21		150.0	
		Z	5.72	67.99	17.48		150.0	
10551-AAB	IEEE 802.11ac WiFi (80MHz, MCS7, 99pc duty cycle)	X	5.42	66.37	15.81	0.00	150.0	± 9.6 %
		Y	5.52	66.93	16.20		150.0	
		Z	5.67	67.83	17.36		150.0	
10552-AAB	IEEE 802.11ac WiFi (80MHz, MCS8, 99pc duty cycle)	X	5.34	66.17	15.72	0.00	150.0	± 9.6 %
		Y	5.44	66.74	16.11		150.0	
		Z	5.57	67.60	17.25		150.0	
10553-AAB	IEEE 802.11ac WiFi (80MHz, MCS9, 99pc duty cycle)	X	5.42	66.21	15.77	0.00	150.0	± 9.6 %
		Y	5.52	66.76	16.15		150.0	
		Z	5.64	67.57	17.26		150.0	
10554-AAC	IEEE 802.11ac WiFi (160MHz, MCS0, 99pc duty cycle)	X	5.74	66.49	15.85	0.00	150.0	± 9.6 %
		Y	5.83	67.00	16.20		150.0	
		Z	5.99	67.81	17.29		150.0	
10555-AAC	IEEE 802.11ac WiFi (160MHz, MCS1, 99pc duty cycle)	X	5.86	66.79	15.98	0.00	150.0	± 9.6 %
		Y	5.95	67.29	16.33		150.0	
		Z	6.17	68.28	17.49		150.0	
10556-AAC	IEEE 802.11ac WiFi (160MHz, MCS2, 99pc duty cycle)	X	5.89	66.84	16.00	0.00	150.0	± 9.6 %
		Y	5.97	67.34	16.34		150.0	
		Z	6.18	68.28	17.48		150.0	
10557-AAC	IEEE 802.11ac WiFi (160MHz, MCS3, 99pc duty cycle)	X	5.85	66.73	15.96	0.00	150.0	± 9.6 %
		Y	5.94	67.25	16.32		150.0	
		Z	6.11	68.10	17.42		150.0	

10558-AAC	IEEE 802.11ac WiFi (160MHz, MCS4, 99pc duty cycle)	X	5.89	66.89	16.06	0.00	150.0	± 9.6 %
		Y	5.99	67.41	16.41		150.0	
		Z	6.18	68.32	17.54		150.0	
10560-AAC	IEEE 802.11ac WiFi (160MHz, MCS6, 99pc duty cycle)	X	5.89	66.74	16.02	0.00	150.0	± 9.6 %
		Y	5.99	67.27	16.38		150.0	
		Z	6.14	68.07	17.45		150.0	
10561-AAC	IEEE 802.11ac WiFi (160MHz, MCS7, 99pc duty cycle)	X	5.82	66.72	16.05	0.00	150.0	± 9.6 %
		Y	5.91	67.23	16.40		150.0	
		Z	6.09	68.15	17.54		150.0	
10562-AAC	IEEE 802.11ac WiFi (160MHz, MCS8, 99pc duty cycle)	X	5.93	67.07	16.22	0.00	150.0	± 9.6 %
		Y	6.02	67.60	16.58		150.0	
		Z	6.23	68.56	17.73		150.0	
10563-AAC	IEEE 802.11ac WiFi (160MHz, MCS9, 99pc duty cycle)	X	6.10	67.21	16.25	0.00	150.0	± 9.6 %
		Y	6.23	67.82	16.65		150.0	
		Z	6.42	68.72	17.77		150.0	
10564-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 9 Mbps, 99pc duty cycle)	X	4.74	66.37	16.01	0.46	150.0	± 9.6 %
		Y	4.84	66.94	16.46		150.0	
		Z	4.93	67.97	17.70		150.0	
10565-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 12 Mbps, 99pc duty cycle)	X	4.96	66.82	16.35	0.46	150.0	± 9.6 %
		Y	5.07	67.39	16.78		150.0	
		Z	5.16	68.45	18.03		150.0	
10566-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 18 Mbps, 99pc duty cycle)	X	4.79	66.64	16.14	0.46	150.0	± 9.6 %
		Y	4.90	67.24	16.60		150.0	
		Z	5.00	68.35	17.89		150.0	
10567-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 24 Mbps, 99pc duty cycle)	X	4.82	67.04	16.51	0.46	150.0	± 9.6 %
		Y	4.94	67.66	16.97		150.0	
		Z	5.06	68.91	18.35		150.0	
10568-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 36 Mbps, 99pc duty cycle)	X	4.70	66.40	15.89	0.46	150.0	± 9.6 %
		Y	4.82	67.00	16.36		150.0	
		Z	4.91	68.11	17.64		150.0	
10569-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 48 Mbps, 99pc duty cycle)	X	4.78	67.14	16.57	0.46	150.0	± 9.6 %
		Y	4.90	67.77	17.04		150.0	
		Z	5.04	69.13	18.50		150.0	
10570-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 54 Mbps, 99pc duty cycle)	X	4.81	66.98	16.50	0.46	150.0	± 9.6 %
		Y	4.93	67.59	16.96		150.0	
		Z	5.05	68.87	18.36		150.0	
10571-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 90pc duty cycle)	X	1.04	62.79	14.08	0.46	130.0	± 9.6 %
		Y	1.18	65.50	16.40		130.0	
		Z	2.04	82.50	26.88		130.0	
10572-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps, 90pc duty cycle)	X	1.04	63.21	14.35	0.46	130.0	± 9.6 %
		Y	1.20	66.22	16.84		130.0	
		Z	2.48	87.58	29.01		130.0	
10573-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps, 90pc duty cycle)	X	0.84	70.94	15.96	0.46	130.0	± 9.6 %
		Y	25.46	129.84	35.99		130.0	
		Z	100.00	217.49	66.83		130.0	
10574-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps, 90pc duty cycle)	X	1.03	66.98	16.22	0.46	130.0	± 9.6 %
		Y	1.48	74.48	20.89		130.0	
		Z	100.00	181.51	55.51		130.0	

10575-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 90pc duty cycle)	X	4.52	66.13	16.03	0.46	130.0	± 9.6 %
		Y	4.63	66.75	16.53		130.0	
		Z	4.72	67.89	17.87		130.0	
10576-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 9 Mbps, 90pc duty cycle)	X	4.54	66.29	16.09	0.46	130.0	± 9.6 %
		Y	4.66	66.92	16.60		130.0	
		Z	4.76	68.14	17.98		130.0	
10577-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 12 Mbps, 90pc duty cycle)	X	4.74	66.59	16.28	0.46	130.0	± 9.6 %
		Y	4.86	67.21	16.77		130.0	
		Z	4.96	68.39	18.11		130.0	
10578-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 18 Mbps, 90pc duty cycle)	X	4.64	66.73	16.37	0.46	130.0	± 9.6 %
		Y	4.76	67.39	16.88		130.0	
		Z	4.89	68.74	18.33		130.0	
10579-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 24 Mbps, 90pc duty cycle)	X	4.40	65.97	15.63	0.46	130.0	± 9.6 %
		Y	4.52	66.65	16.18		130.0	
		Z	4.62	67.82	17.52		130.0	
10580-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 36 Mbps, 90pc duty cycle)	X	4.44	66.02	15.66	0.46	130.0	± 9.6 %
		Y	4.57	66.69	16.20		130.0	
		Z	4.67	67.87	17.53		130.0	
10581-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 48 Mbps, 90pc duty cycle)	X	4.53	66.73	16.28	0.46	130.0	± 9.6 %
		Y	4.66	67.45	16.84		130.0	
		Z	4.81	68.92	18.36		130.0	
10582-AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 54 Mbps, 90pc duty cycle)	X	4.34	65.73	15.42	0.46	130.0	± 9.6 %
		Y	4.46	66.39	15.96		130.0	
		Z	4.55	67.53	17.26		130.0	
10583-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps, 90pc duty cycle)	X	4.52	66.13	16.03	0.46	130.0	± 9.6 %
		Y	4.63	66.75	16.53		130.0	
		Z	4.72	67.89	17.87		130.0	
10584-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps, 90pc duty cycle)	X	4.54	66.29	16.09	0.46	130.0	± 9.6 %
		Y	4.66	66.92	16.60		130.0	
		Z	4.76	68.14	17.98		130.0	
10585-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps, 90pc duty cycle)	X	4.74	66.59	16.28	0.46	130.0	± 9.6 %
		Y	4.86	67.21	16.77		130.0	
		Z	4.96	68.39	18.11		130.0	
10586-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps, 90pc duty cycle)	X	4.64	66.73	16.37	0.46	130.0	± 9.6 %
		Y	4.76	67.39	16.88		130.0	
		Z	4.89	68.74	18.33		130.0	
10587-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps, 90pc duty cycle)	X	4.40	65.97	15.63	0.46	130.0	± 9.6 %
		Y	4.52	66.65	16.18		130.0	
		Z	4.62	67.82	17.52		130.0	
10588-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps, 90pc duty cycle)	X	4.44	66.02	15.66	0.46	130.0	± 9.6 %
		Y	4.57	66.69	16.20		130.0	
		Z	4.67	67.87	17.53		130.0	
10589-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps, 90pc duty cycle)	X	4.53	66.73	16.28	0.46	130.0	± 9.6 %
		Y	4.66	67.45	16.84		130.0	
		Z	4.81	68.92	18.36		130.0	
10590-AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps, 90pc duty cycle)	X	4.34	65.73	15.42	0.46	130.0	± 9.6 %
		Y	4.46	66.39	15.96		130.0	
		Z	4.55	67.53	17.26		130.0	

10591-AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS0, 90pc duty cycle)	X	4.67	66.22	16.15	0.46	130.0	± 9.6 %
		Y	4.78	66.80	16.62		130.0	
		Z	4.86	67.85	17.91		130.0	
10592-AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS1, 90pc duty cycle)	X	4.82	66.55	16.28	0.46	130.0	± 9.6 %
		Y	4.93	67.14	16.76		130.0	
		Z	5.02	68.23	18.05		130.0	
10593-AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS2, 90pc duty cycle)	X	4.74	66.43	16.15	0.46	130.0	± 9.6 %
		Y	4.86	67.05	16.64		130.0	
		Z	4.95	68.15	17.94		130.0	
10594-AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS3, 90pc duty cycle)	X	4.79	66.61	16.31	0.46	130.0	± 9.6 %
		Y	4.91	67.22	16.80		130.0	
		Z	5.01	68.36	18.12		130.0	
10595-AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS4, 90pc duty cycle)	X	4.76	66.55	16.20	0.46	130.0	± 9.6 %
		Y	4.88	67.17	16.69		130.0	
		Z	4.98	68.34	18.02		130.0	
10596-AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS5, 90pc duty cycle)	X	4.69	66.53	16.19	0.46	130.0	± 9.6 %
		Y	4.81	67.18	16.70		130.0	
		Z	4.92	68.37	18.06		130.0	
10597-AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS6, 90pc duty cycle)	X	4.64	66.42	16.06	0.46	130.0	± 9.6 %
		Y	4.76	67.08	16.58		130.0	
		Z	4.87	68.26	17.92		130.0	
10598-AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS7, 90pc duty cycle)	X	4.62	66.66	16.33	0.46	130.0	± 9.6 %
		Y	4.75	67.33	16.85		130.0	
		Z	4.87	68.62	18.28		130.0	
10599-AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS0, 90pc duty cycle)	X	5.36	66.82	16.42	0.46	130.0	± 9.6 %
		Y	5.45	67.32	16.81		130.0	
		Z	5.56	68.24	17.99		130.0	
10600-AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS1, 90pc duty cycle)	X	5.49	67.26	16.61	0.46	130.0	± 9.6 %
		Y	5.56	67.67	16.95		130.0	
		Z	5.87	69.29	18.48		130.0	
10601-AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS2, 90pc duty cycle)	X	5.37	66.98	16.49	0.46	130.0	± 9.6 %
		Y	5.46	67.46	16.87		130.0	
		Z	5.65	68.68	18.20		130.0	
10602-AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS3, 90pc duty cycle)	X	5.48	67.04	16.43	0.46	130.0	± 9.6 %
		Y	5.55	67.48	16.79		130.0	
		Z	5.78	68.80	18.16		130.0	
10603-AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS4, 90pc duty cycle)	X	5.55	67.32	16.71	0.46	130.0	± 9.6 %
		Y	5.64	67.79	17.08		130.0	
		Z	5.82	68.99	18.40		130.0	
10604-AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS5, 90pc duty cycle)	X	5.38	66.84	16.46	0.46	130.0	± 9.6 %
		Y	5.45	67.29	16.82		130.0	
		Z	5.58	68.28	18.03		130.0	
10605-AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS6, 90pc duty cycle)	X	5.48	67.13	16.60	0.46	130.0	± 9.6 %
		Y	5.55	67.58	16.96		130.0	
		Z	5.79	68.96	18.37		130.0	
10606-AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS7, 90pc duty cycle)	X	5.21	66.41	16.09	0.46	130.0	± 9.6 %
		Y	5.31	66.95	16.51		130.0	
		Z	5.39	67.75	17.62		130.0	

10607-AAB	IEEE 802.11ac WiFi (20MHz, MCS0, 90pc duty cycle)	X	4.50	65.48	15.75	0.46	130.0	± 9.6 %
		Y	4.63	66.16	16.27		130.0	
		Z	4.76	67.43	17.68		130.0	
10608-AAB	IEEE 802.11ac WiFi (20MHz, MCS1, 90pc duty cycle)	X	4.68	65.87	15.91	0.46	130.0	± 9.6 %
		Y	4.81	66.57	16.44		130.0	
		Z	4.96	67.88	17.86		130.0	
10609-AAB	IEEE 802.11ac WiFi (20MHz, MCS2, 90pc duty cycle)	X	4.57	65.70	15.73	0.46	130.0	± 9.6 %
		Y	4.70	66.42	16.28		130.0	
		Z	4.85	67.75	17.71		130.0	
10610-AAB	IEEE 802.11ac WiFi (20MHz, MCS3, 90pc duty cycle)	X	4.62	65.87	15.90	0.46	130.0	± 9.6 %
		Y	4.75	66.58	16.44		130.0	
		Z	4.91	67.95	17.90		130.0	
10611-AAB	IEEE 802.11ac WiFi (20MHz, MCS4, 90pc duty cycle)	X	4.53	65.67	15.74	0.46	130.0	± 9.6 %
		Y	4.67	66.38	16.29		130.0	
		Z	4.82	67.73	17.74		130.0	
10612-AAB	IEEE 802.11ac WiFi (20MHz, MCS5, 90pc duty cycle)	X	4.53	65.80	15.77	0.46	130.0	± 9.6 %
		Y	4.68	66.54	16.34		130.0	
		Z	4.84	67.98	17.83		130.0	
10613-AAB	IEEE 802.11ac WiFi (20MHz, MCS6, 90pc duty cycle)	X	4.54	65.68	15.65	0.46	130.0	± 9.6 %
		Y	4.68	66.42	16.21		130.0	
		Z	4.83	67.77	17.65		130.0	
10614-AAB	IEEE 802.11ac WiFi (20MHz, MCS7, 90pc duty cycle)	X	4.48	65.87	15.89	0.46	130.0	± 9.6 %
		Y	4.63	66.62	16.46		130.0	
		Z	4.80	68.12	17.99		130.0	
10615-AAB	IEEE 802.11ac WiFi (20MHz, MCS8, 90pc duty cycle)	X	4.53	65.49	15.51	0.46	130.0	± 9.6 %
		Y	4.67	66.20	16.06		130.0	
		Z	4.81	67.48	17.45		130.0	
10616-AAB	IEEE 802.11ac WiFi (40MHz, MCS0, 90pc duty cycle)	X	5.16	66.01	16.00	0.46	130.0	± 9.6 %
		Y	5.27	66.60	16.44		130.0	
		Z	5.41	67.63	17.68		130.0	
10617-AAB	IEEE 802.11ac WiFi (40MHz, MCS1, 90pc duty cycle)	X	5.23	66.20	16.06	0.46	130.0	± 9.6 %
		Y	5.34	66.76	16.49		130.0	
		Z	5.54	68.02	17.85		130.0	
10618-AAB	IEEE 802.11ac WiFi (40MHz, MCS2, 90pc duty cycle)	X	5.11	66.18	16.07	0.46	130.0	± 9.6 %
		Y	5.22	66.79	16.52		130.0	
		Z	5.41	68.02	17.88		130.0	
10619-AAB	IEEE 802.11ac WiFi (40MHz, MCS3, 90pc duty cycle)	X	5.13	65.99	15.91	0.46	130.0	± 9.6 %
		Y	5.24	66.58	16.35		130.0	
		Z	5.42	67.75	17.67		130.0	
10620-AAB	IEEE 802.11ac WiFi (40MHz, MCS4, 90pc duty cycle)	X	5.22	66.04	15.98	0.46	130.0	± 9.6 %
		Y	5.33	66.62	16.42		130.0	
		Z	5.49	67.70	17.69		130.0	
10621-AAB	IEEE 802.11ac WiFi (40MHz, MCS5, 90pc duty cycle)	X	5.22	66.19	16.18	0.46	130.0	± 9.6 %
		Y	5.33	66.76	16.61		130.0	
		Z	5.49	67.85	17.90		130.0	
10622-AAB	IEEE 802.11ac WiFi (40MHz, MCS6, 90pc duty cycle)	X	5.23	66.34	16.25	0.46	130.0	± 9.6 %
		Y	5.34	66.92	16.68		130.0	
		Z	5.55	68.18	18.05		130.0	

10623-AAB	IEEE 802.11ac WiFi (40MHz, MCS7, 90pc duty cycle)	X	5.11	65.86	15.88	0.46	130.0	± 9.6 %
		Y	5.22	66.44	16.31		130.0	
		Z	5.37	67.49	17.57		130.0	
10624-AAB	IEEE 802.11ac WiFi (40MHz, MCS8, 90pc duty cycle)	X	5.30	66.08	16.06	0.46	130.0	± 9.6 %
		Y	5.41	66.63	16.47		130.0	
		Z	5.56	67.66	17.71		130.0	
10625-AAB	IEEE 802.11ac WiFi (40MHz, MCS9, 90pc duty cycle)	X	5.65	67.00	16.57	0.46	130.0	± 9.6 %
		Y	5.76	67.56	16.98		130.0	
		Z	6.03	68.97	18.39		130.0	
10626-AAB	IEEE 802.11ac WiFi (80MHz, MCS0, 90pc duty cycle)	X	5.46	66.10	15.98	0.46	130.0	± 9.6 %
		Y	5.56	66.64	16.38		130.0	
		Z	5.69	67.48	17.50		130.0	
10627-AAB	IEEE 802.11ac WiFi (80MHz, MCS1, 90pc duty cycle)	X	5.71	66.69	16.24	0.46	130.0	± 9.6 %
		Y	5.79	67.17	16.60		130.0	
		Z	6.06	68.44	17.93		130.0	
10628-AAB	IEEE 802.11ac WiFi (80MHz, MCS2, 90pc duty cycle)	X	5.49	66.16	15.90	0.46	130.0	± 9.6 %
		Y	5.59	66.72	16.32		130.0	
		Z	5.75	67.65	17.48		130.0	
10629-AAB	IEEE 802.11ac WiFi (80MHz, MCS3, 90pc duty cycle)	X	5.56	66.22	15.93	0.46	130.0	± 9.6 %
		Y	5.67	66.77	16.33		130.0	
		Z	5.83	67.71	17.50		130.0	
10630-AAB	IEEE 802.11ac WiFi (80MHz, MCS4, 90pc duty cycle)	X	6.00	67.72	16.67	0.46	130.0	± 9.6 %
		Y	6.07	68.17	17.03		130.0	
		Z	6.71	70.51	18.84		130.0	
10631-AAB	IEEE 802.11ac WiFi (80MHz, MCS5, 90pc duty cycle)	X	5.89	67.50	16.77	0.46	130.0	± 9.6 %
		Y	6.00	68.06	17.17		130.0	
		Z	6.28	69.41	18.54		130.0	
10632-AAB	IEEE 802.11ac WiFi (80MHz, MCS6, 90pc duty cycle)	X	5.68	66.76	16.42	0.46	130.0	± 9.6 %
		Y	5.77	67.25	16.78		130.0	
		Z	6.03	68.55	18.14		130.0	
10633-AAB	IEEE 802.11ac WiFi (80MHz, MCS7, 90pc duty cycle)	X	5.55	66.32	16.02	0.46	130.0	± 9.6 %
		Y	5.66	66.90	16.43		130.0	
		Z	5.78	67.69	17.53		130.0	
10634-AAB	IEEE 802.11ac WiFi (80MHz, MCS8, 90pc duty cycle)	X	5.53	66.36	16.09	0.46	130.0	± 9.6 %
		Y	5.65	66.93	16.51		130.0	
		Z	5.77	67.77	17.64		130.0	
10635-AAB	IEEE 802.11ac WiFi (80MHz, MCS9, 90pc duty cycle)	X	5.42	65.68	15.48	0.46	130.0	± 9.6 %
		Y	5.52	66.24	15.90		130.0	
		Z	5.61	66.90	16.91		130.0	
10636-AAC	IEEE 802.11ac WiFi (160MHz, MCS0, 90pc duty cycle)	X	5.88	66.48	16.08	0.46	130.0	± 9.6 %
		Y	5.97	66.99	16.45		130.0	
		Z	6.13	67.79	17.53		130.0	
10637-AAC	IEEE 802.11ac WiFi (160MHz, MCS1, 90pc duty cycle)	X	6.04	66.87	16.26	0.46	130.0	± 9.6 %
		Y	6.12	67.36	16.62		130.0	
		Z	6.37	68.41	17.81		130.0	
10638-AAC	IEEE 802.11ac WiFi (160MHz, MCS2, 90pc duty cycle)	X	6.03	66.83	16.22	0.46	130.0	± 9.6 %
		Y	6.13	67.34	16.59		130.0	
		Z	6.36	68.36	17.76		130.0	

10639-AAC	IEEE 802.11ac WiFi (160MHz, MCS3, 90pc duty cycle)	X	6.01	66.77	16.23	0.46	130.0	± 9.6 %
		Y	6.11	67.30	16.61		130.0	
		Z	6.28	68.13	17.70		130.0	
10640-AAC	IEEE 802.11ac WiFi (160MHz, MCS4, 90pc duty cycle)	X	6.01	66.77	16.17	0.46	130.0	± 9.6 %
		Y	6.11	67.30	16.55		130.0	
		Z	6.29	68.15	17.64		130.0	
10641-AAC	IEEE 802.11ac WiFi (160MHz, MCS5, 90pc duty cycle)	X	6.07	66.72	16.17	0.46	130.0	± 9.6 %
		Y	6.15	67.20	16.52		130.0	
		Z	6.35	68.09	17.63		130.0	
10642-AAC	IEEE 802.11ac WiFi (160MHz, MCS6, 90pc duty cycle)	X	6.10	66.96	16.46	0.46	130.0	± 9.6 %
		Y	6.20	67.47	16.82		130.0	
		Z	6.37	68.31	17.92		130.0	
10643-AAC	IEEE 802.11ac WiFi (160MHz, MCS7, 90pc duty cycle)	X	5.94	66.64	16.19	0.46	130.0	± 9.6 %
		Y	6.03	67.14	16.56		130.0	
		Z	6.23	68.06	17.69		130.0	
10644-AAC	IEEE 802.11ac WiFi (160MHz, MCS8, 90pc duty cycle)	X	6.08	67.08	16.43	0.46	130.0	± 9.6 %
		Y	6.19	67.63	16.82		130.0	
		Z	6.38	68.53	17.94		130.0	
10645-AAC	IEEE 802.11ac WiFi (160MHz, MCS9, 90pc duty cycle)	X	6.34	67.46	16.59	0.46	130.0	± 9.6 %
		Y	6.49	68.13	17.03		130.0	
		Z	6.73	69.17	18.21		130.0	
10646-AAD	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK, UL Subframe=2,7)	X	12.72	99.19	33.35	9.30	60.0	± 9.6 %
		Y	38.29	127.59	42.90		60.0	
		Z	100.00	156.53	52.24		60.0	
10647-AAC	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK, UL Subframe=2,7)	X	11.53	97.66	32.97	9.30	60.0	± 9.6 %
		Y	31.46	123.83	42.04		60.0	
		Z	100.00	158.04	52.90		60.0	
10648-AAA	CDMA2000 (1x Advanced)	X	0.53	61.07	8.36	0.00	150.0	± 9.6 %
		Y	0.71	64.63	11.33		150.0	
		Z	100.00	131.33	31.12		150.0	
10652-AAB	LTE-TDD (OFDMA, 5 MHz, E-TM 3.1, Clipping 44%)	X	3.34	65.47	15.58	2.23	80.0	± 9.6 %
		Y	3.79	67.90	17.18		80.0	
		Z	5.08	74.52	20.94		80.0	
10653-AAB	LTE-TDD (OFDMA, 10 MHz, E-TM 3.1, Clipping 44%)	X	3.92	65.25	16.00	2.23	80.0	± 9.6 %
		Y	4.24	66.88	17.11		80.0	
		Z	4.81	70.18	19.49		80.0	
10654-AAB	LTE-TDD (OFDMA, 15 MHz, E-TM 3.1, Clipping 44%)	X	3.92	64.97	16.04	2.23	80.0	± 9.6 %
		Y	4.20	66.47	17.09		80.0	
		Z	4.67	69.32	19.28		80.0	
10655-AAB	LTE-TDD (OFDMA, 20 MHz, E-TM 3.1, Clipping 44%)	X	3.99	64.97	16.10	2.23	80.0	± 9.6 %
		Y	4.26	66.44	17.11		80.0	
		Z	4.70	69.09	19.22		80.0	
10658-AAA	Pulse Waveform (200Hz, 10%)	X	6.09	75.48	15.93	10.00	50.0	± 9.6 %
		Y	100.00	113.01	27.29		50.0	
		Z	100.00	113.66	27.93		50.0	
10659-AAA	Pulse Waveform (200Hz, 20%)	X	7.36	78.97	15.80	6.99	60.0	± 9.6 %
		Y	100.00	111.38	25.51		60.0	
		Z	100.00	111.00	25.55		60.0	

10660-AAA	Pulse Waveform (200Hz, 40%)	X	8.43	80.82	14.63	3.98	80.0	± 9.6 %
		Y	100.00	111.85	24.40		80.0	
		Z	100.00	110.00	23.61		80.0	
10661-AAA	Pulse Waveform (200Hz, 60%)	X	1.23	67.24	8.82	2.22	100.0	± 9.6 %
		Y	100.00	114.58	24.29		100.0	
		Z	100.00	106.40	20.63		100.0	
10662-AAA	Pulse Waveform (200Hz, 80%)	X	0.20	60.00	3.70	0.97	120.0	± 9.6 %
		Y	100.00	118.12	23.89		120.0	
		Z	0.04	60.00	57467.54		120.0	

[E] Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

APPENDIX D DIPOLE CALIBRATION CERTIFICATES

In Collaboration with
s p e a g
CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com Http://www.chinattl.cn

中国认可
国际互认
校准
CALIBRATION
CNAS L0570

Client BACL Certificate No: Z16-97195

CALIBRATION CERTIFICATE

Object	D835V2 - SN: 445
Calibration Procedure(s)	FD-Z11-003-01 Calibration Procedures for dipole validation kits
Calibration date:	October 26, 2016

This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements(SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature(22±3)℃ and humidity<70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Power Meter NRP2	101919	27-Jun-16 (CTTL, No.J16X04777)	Jun-17
Power sensor NRP-Z91	101547	27-Jun-16 (CTTL, No.J16X04777)	Jun-17
Reference Probe EX3DV4	SN 7433	26-Sep-16(SPEAG,No.EX3-7433_Sep16)	Sep-17
DAE4	SN 777	22-Aug-16(CTTL-SPEAG,No.Z16-97138)	Aug-17
Secondary Standards	**ID #**	**Cal Date(Calibrated by, Certificate No.)**	**Scheduled Calibration**
Signal Generator E4438C	MY49071430	01-Feb-16 (CTTL, No.J16X00893)	Jan-17
Network Analyzer E5071C	MY46110673	26-Jan-16 (CTTL, No.J16X00894)	Jan-17

	Name	Function	Signature
Calibrated by:	Zhao Jing	SAR Test Engineer	
Reviewed by:	Qi Dianyuan	SAR Project Leader	
Approved by:	Liu Wei	Deputy Director of SEM Department	

Issued: October 27, 2016

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

In Collaboration with
CALIBRATION LABORATORY
Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com Http://www.chinattl.cn

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORMx,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

a) IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
b) IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) For hand-held devices used in close proximity to the ear (frequency range of 300MHz to 3GHz)", February 2005
c) IEC 62209-2, "Procedure to measure the Specific Absorption Rate (SAR) For wireless communication devices used in close proximity to the human body (frequency range of 30MHz to 6GHz)", March 2010
d) KDB865664, SAR Measurement Requirements for 100 MHz to 6 GHz

Additional Documentation:

e) DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- *Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- *Antenna Parameters with TSL:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- *Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- *Electrical Delay:* One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- *SAR measured:* SAR measured at the stated antenna input power.
- *SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- *SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of Measurement multiplied by the coverage factor k=2, which for a normal distribution Corresponds to a coverage probability of approximately 95%.

In Collaboration with
s p e a g
CALIBRATION LABORATORY
Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com Http://www.chinattl.cn

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY52	52.8.8.1258
Extrapolation	Advanced Extrapolation	
Phantom	Triple Flat Phantom 5.1C	
Distance Dipole Center - TSL	15 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	835 MHz ± 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	41.5	0.90 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	41.4 ± 6 %	0.92 mho/m ± 6 %
Head TSL temperature change during test	<1.0 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm^3 (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	2.41 mW / g
SAR for nominal Head TSL parameters	normalized to 1W	**9.46 mW /g ± 20.8 % (k=2)**
SAR averaged over 10 cm^3 (10 g) of Head TSL	Condition	
SAR measured	250 mW input power	1.58 mW / g
SAR for nominal Head TSL parameters	normalized to 1W	**6.23 mW /g ± 20.4 % (k=2)**

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	55.2	0.97 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	55.8 ± 6 %	0.95 mho/m ± 6 %
Body TSL temperature change during test	<1.0 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm^3 (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	2.36 mW / g
SAR for nominal Body TSL parameters	normalized to 1W	**9.60 mW /g ± 20.8 % (k=2)**
SAR averaged over 10 cm^3 (10 g) of Body TSL	Condition	
SAR measured	250 mW input power	1.59 mW / g
SAR for nominal Body TSL parameters	normalized to 1W	**6.44 mW /g ± 20.4 % (k=2)**

In Collaboration with
speag
CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com Http://www.chinattl.cn

Appendix

Antenna Parameters with Head TSL

Impedance, transformed to feed point	45.5Ω- 3.43jΩ
Return Loss	- 24.6dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	47.5Ω- 7.29jΩ
Return Loss	- 22.1dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.497 ns

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.
No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG

In Collaboration with
s p e a g
CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com Http://www.chinattl.cn

DASY5 Validation Report for Head TSL Date: 10.26.2016

Test Laboratory: CTTL, Beijing, China

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN: 445

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium parameters used: f = 835 MHz; σ = 0.922 S/m; ε_r = 41.42; ρ = 1000 kg/m^3

Phantom section: Right Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN7433; ConvF(9.82, 9.82, 9.82); Calibrated: 9/26/2016;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn777; Calibrated: 2016-08-22
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1161/1
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7372)

Dipole Calibration/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 58.51V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 3.63 W/kg

SAR(1 g) = 2.41 W/kg; SAR(10 g) = 1.58 W/kg

Maximum value of SAR (measured) = 3.07 W/kg



0 dB = 3.07 W/kg = 4.87 dBW/kg

In Collaboration with
s p e a g
CALIBRATION LABORATORY
Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com Http://www.chinattl.cn

Impedance Measurement Plot for Head TSL



In Collaboration with
s p e a g
CALIBRATION LABORATORY
Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com Http://www.chinattl.cn

DASY5 Validation Report for Body TSL Date: 10.26.2016

Test Laboratory: CTTL, Beijing, China

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN: 445

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium parameters used: f = 835 MHz; σ = 0.952 S/m; ε_r = 55.79; ρ = 1000 kg/m^3

Phantom section: Center Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: EX3DV4 - SN7433; ConvF(9.5,9.5, 9.5); Calibrated: 9/26/2016;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn777; Calibrated: 2016-08-22
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1161/1
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7372)

Dipole Calibration/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 56.01 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 3.44 W/kg

SAR(1 g) = 2.36 W/kg; SAR(10 g) = 1.59 W/kg

Maximum value of SAR (measured) = 2.95 W/kg



0 dB = 2.95 W/kg = 4.70 dBW/kg

In Collaboration with
s p e a g
CALIBRATION LABORATORY
Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com Http://www.chinattl.cn

Impedance Measurement Plot for Body TSL



NCL CALIBRATION LABORATORIES

Calibration File No: DC-1748
Project Number: 5822

Client.: BACL Corp.
Address: 6/F, the 3rd Phase of Wan Li Industrial Bldg., Shihua Rd.,
FuTian Free Trade Zone, Shenzhen, China

CERTIFICATE OF CALIBRATION

It is certified that the equipment identified below has been calibrated in the **NCL CALIBRATION LABORATORIES** by qualified personnel following recognized procedures and using transfer standards traceable to NRC/NIST.

Validation Dipole (Head & Body)

Manufacturer: APREL Laboratories
Part number: ALS-D-1900-S-2
Frequency: 1900 MHz
Serial No: 210-00710

Calibrated: 20th September 2017
Released on: 27th September 2017

This Calibration Certificate is Incomplete Unless Accompanied with the Calibration Results Summary

Released By: _____
Art Brennan, Quality Manager

NCL CALIBRATION LABORATORIES
Suite 102, 303 Terry Fox Dr.
Kanata, ONTARIO
CANADA K2K 3J1
Division of APREL Lab.
TEL: (613) 435-8300
FAX: (613)435-8306

Conditions

Dipole 210-00710 was a re-calibration.

Ambient Temperature of the Laboratory:	21 °C +/- 0.5°C
Temperature of the Tissue:	21 °C +/- 0.5°C

Attestation

The below named signatories have conducted the calibration and review of the data which is presented in this calibration report.

We the undersigned attest that to the best of our knowledge the calibration of this system has been accurately conducted and that all information contained within this report has been reviewed for accuracy.

Art Brennan QM

Maryna Nesterova R&D Engineer

Primary Measurement Standards

Instrument	Serial Number	Cal due date
Tektronix USB Power Meter	11C940	April 13, 2019
Network Analyzer Anritsu 37347C	002106	Jan. 26, 2019
Agilent Signal Generator	MY45094463	Dec. 11, 2017

Calibration Results Summary

The following results relate the Calibrated Dipole and should be used as a quick reference for the user.

Mechanical Dimensions

Length	Height	Diameter
67.5 mm	39.5 mm	3.6 mm

Tissue Validation

Tissue	Frequency	Dielectric constant, εr	Conductivity, σ [S/m]
Head	1900 MHz	39.44	1.41
Body	1900 MHz	52.70	1.57

Electrical Specification

Tissue	Frequency	Return Loss	SWR	Impedance
Head	1900 MHz	-28.662 dB	1.077 U	52.368 Ω
Body	1900 MHz	-22.498 dB	1.162 U	55.211 Ω

System Validation Results

Tissue	Frequency	1 Gram, W/kg	10 Gram, W/kg
Head	1900 MHz	42.14	21.89
Body	1900 MHz	42.11	22.12

Head



Body



Introduction

This Calibration Report has been produced in line with the SSI Dipole Calibration Procedure SSI-TP-018-ALSAS. The results contained within this report are for Validation Dipole 210-00710. The calibration routine consisted of a three-step process. Step 1 was a mechanical verification of the dipole to ensure that it meets the mechanical specifications. Step 2 was an Electrical Calibration for the Validation Dipole, where the SWR, Impedance, and the Return loss were assessed. Step 3 involved a System Validation using the ALSAS-10U, along with APREL E-020 30 MHz to 6 GHz E-Field Probe Serial Number 225.

References

- IEEE Standard 1528:2013
  IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
- EN 62209-1:2006
  Human Exposure to RF Fields from hand-held and body-mounted wireless communication devices - Human models. instrumentation, and procedures - Part 1: Procedure to measure the Specific Absorption Rate (SAR) for hand-held mobile wireless devices
- IEC 62209-2:2010
  Human exposure to RF fields from hand-held and body-mounted wireless devices - Human models, instrumentation, and procedures - Part 2: specific absorption rate (SAR) for wireless communication devices (30 MHz - 6 GHz)
- D22-012-Tissue dielectric tissue calibration procedure
- D28-002-Dipole procedure for validation of SAR system using a dipole
- IEEE 1309 Standard for Calibration of Electromagnetic Field Sensors and Probes, Excluding Antennas, from 9 kHz to 40 GHz

Conditions

Ambient Temperature of the Laboratory: 21 °C +/- 0.5°C
Temperature of the Tissue: 21 °C +/- 0.5°C

Dipole Calibration uncertainty

The calibration uncertainty for the dipole is made up of various parameters presented below.

Mechanical	1%
Positioning Error	1.22%
Electrical	1.7%
Tissue	2.2%
Dipole Validation	2.2%
Combined Standard Uncertainty	**3.88% (7.76% K=2)**

The Following Graphs are the results as displayed on the Vector Network Analyzer.

S11 Parameter Return Loss

Head

Frequency Range 1868.68 MHz to 1934.44 MHz



Body

Frequency Range 1882.37 MHz to 1928.52 MHz



SWR

Head



Body



Smith Chart Dipole Impedance

Head



Body