



## FCC §15.247 (i), §2.1091 – RF Exposure

**FCC ID: 2A08U-ANKEE**

### Applied procedures / limit

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

### Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

Note: *f* is frequency in MHz

\* = Power density limit is applicable at frequencies greater than 100 MHz

### Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: *f* = frequency in MHz

\* = Plane-wave equivalent power density

	Frequency	Maximum Conducted Output Power(PK)	LIMIT
	(MHz)	(dBm)	dBm
802.11b	2412	16.02	30
	2437	14.78	30
	2462	11.81	30
802.11g	2412	14.36	30
	2437	13.54	30
	2462	11.67	30
802.11n20	2412	13.44	30
	2437	12.68	30
	2462	12.15	30



## MPE PREDICTION

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna, R=20cm

## Test Result of RF Exposure Evaluation

	Frequency (MHz)	Target power W/ tolerance (dBm)	Max tune up power tolerance (dBm)	Total Output power to antenna (mW)	Antenna Gain(dBi)	Total Power Density at R=20cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
802.11g	2412	16±1.0	17	50.12	1.0 (1.258)	0.01255	1.0	Pass
	2437	14±1.0	15	31.62	1.0 (1.258)	0.00792	1.0	Pass
	2462	12±1.0	13	19.95	1.0 (1.258)	0.00500	1.0	Pass
802.11g	2412	14±1.0	15	31.62	1.0 (1.258)	0.00792	1.0	Pass
	2437	13±1.0	14	25.12	1.0 (1.258)	0.00629	1.0	Pass
	2462	11±1.0	12	15.85	1.0 (1.258)	0.00397	1.0	Pass
802.11n20	2412	13±1.0	14	25.12	1.0 (1.258)	0.00629	1.0	Pass
	2437	12±1.0	13	19.95	1.0 (1.258)	0.00500	1.0	Pass
	2462	12±1.0	13	19.95	1.0 (1.258)	0.00500	1.0	Pass