



Occupied Bandwidth

Channel



10MHz Bandwidth QPSK

10MHz Bandwidth 16QAM



Lowest



Middle



Highest





Occupied Bandwidth

Channel



15MHz Bandwidth QPSK

15MHz Bandwidth 16QAM



Lowest



Middle



Highest





Occupied Bandwidth

Channel



20MHz Bandwidth QPSK

20MHz Bandwidth 16QAM



Lowest



Middle



Highest





Spurious Emissions at Antenna Terminal



Channel

5MHz Bandwidth QPSK



Lowest



Middle



Highest





Spurious Emissions at Antenna Terminal



Channel

10MHz Bandwidth QPSK



Lowest



Middle



Highest





Spurious Emissions at Antenna Terminal



Channel

15MHz Bandwidth QPSK



Lowest



Middle



Highest





Spurious Emissions at Antenna Terminal



Channel

20MHz Bandwidth QPSK



Lowest




Middle




Highest




Out of band emission, Band Edge




Out of band emission, Band Edge



Out of band emission, Band Edge



Out of band emission, Band Edge



4.12 Spurious Emissions

Serial Number:	CR22050038-RF-S1	Test Date:	2022-06-09~2022-06-21
Test Site:	966-2, 966-1	Test Mode:	Transmit
Tester:	Carl Liang	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	23.9~25.5	Relative Humidity: (%)	66~68	ATM Pressure: (kPa)	100~100.1
----------------------	-----------	---------------------------	-------	------------------------	-----------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
ETS-Lindgren	Horn Antenna	3115	9912-5985	2020-10-13	2023-10-12
R&S	Spectrum Analyzer	FSV40	101591	2021-07-22	2022-07-21
MICRO-COAX	Coaxial Cable	UFA210A-1-1200-70U300	217423-008	2021-08-08	2022-08-07
MICRO-COAX	Coaxial Cable	UFA210A-1-2362-300300	235780-001	2021-08-08	2022-08-07
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2021-11-10	2022-11-09
AH	Double Ridge Guide Horn Antenna	SAS-571	1396	2021-10-18	2024-10-17
MICRO-COAX	Coaxial Cable	UFA210B-0-0720-300300	99G1448	2021-07-25	2022-07-24
PASTERNAK	Horn Antenna	PE9852/2F-20	112002	2021-02-05	2024-02-04
PASTERNAK	Horn Antenna	PE9852/2F-20	112001	2021-02-05	2024-02-04
AH	Preamplifier	PAM-1840VH	190	2021-11-19	2022-11-18
MICRO-COAX	Coaxial Cable	UFB142A-1-2362-200200	235772-001	2021-08-08	2022-08-07
Sunol Sciences	Antenna	JB6	A082520-5	2020-10-19	2023-10-18
R&S	EMI Test Receiver	ESR3	102724	2021-07-22	2022-07-21
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0470-02	2021-07-18	2022-07-17
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0780-01	2021-07-18	2022-07-17
Sonoma	Amplifier	310N	186165	2021-07-18	2022-07-17
EMCO	Adjustable Dipole Antenna	3121C	9109-756	N/A	N/A
MICRO-COAX	Coaxial Cable	UFA210B-0-0720-300300	99G1448	2021-07-25	2022-07-24
Agilent	Signal Generator	E8247C	MY43321352	2022-04-25	2023-04-24

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Please refer to the below table and plots.

Note: The device can be mounted in multiple orientations, test was performed with X,Y, Z Axis according to C63.26 figure 5, the worst orientation was photographed and it's data was recorded.

Cellular Band (PART 22H)**30 MHz-10 GHz:**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
WCDMA Band 5 Frequency:826.4 MHz								
1652.80	H	52.49	-51.84	8.68	0.81	-43.97	-13.00	30.97
1652.80	V	53.01	-51.40	8.68	0.81	-43.53	-13.00	30.53
2479.20	H	55.58	-45.18	9.39	1.01	-36.80	-13.00	23.80
2479.20	V	55.61	-45.12	9.39	1.01	-36.74	-13.00	23.74
3305.60	H	33.28	-63.45	10.32	1.15	-54.28	-13.00	41.28
3305.60	V	34.35	-62.15	10.32	1.15	-52.98	-13.00	39.98
151.61	H	51.60	-60.29	0.00	0.23	-60.52	-13.00	47.52
85.72	V	47.96	-61.05	0.00	0.17	-61.22	-13.00	48.22
WCDMA Band 5 Frequency:836.6MHz								
1673.20	H	51.92	-52.39	8.71	0.85	-44.53	-13.00	31.53
1673.20	V	53.78	-50.63	8.71	0.85	-42.77	-13.00	29.77
2509.80	H	56.34	-44.27	9.42	1.01	-35.86	-13.00	22.86
2509.80	V	46.07	-54.55	9.42	1.01	-46.14	-13.00	33.14
3346.40	H	32.42	-64.75	10.34	1.16	-55.57	-13.00	42.57
3346.40	V	33.62	-63.41	10.34	1.16	-54.23	-13.00	41.23
152.58	H	53.67	-58.19	0.00	0.23	-58.42	-13.00	45.42
56.65	V	47.73	-56.68	-11.84	0.14	-68.66	-13.00	55.66
WCDMA Band 5 Frequency:846.6MHz								
1693.20	H	57.19	-47.11	8.73	0.89	-39.27	-13.00	26.27
1693.20	V	56.85	-47.57	8.73	0.89	-39.73	-13.00	26.73
2539.80	H	50.03	-50.35	9.46	1.01	-41.90	-13.00	28.90
2539.80	V	46.96	-53.38	9.46	1.01	-44.93	-13.00	31.93
3386.40	H	33.42	-64.17	10.35	1.18	-55.00	-13.00	42.00
3386.40	V	33.65	-63.89	10.35	1.18	-54.72	-13.00	41.72
151.61	H	51.89	-60.00	0.00	0.23	-60.23	-13.00	47.23
54.71	V	47.70	-55.78	-12.73	0.13	-68.64	-13.00	55.64

PCS Band (PART 24E)**30 MHz-20 GHz:**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
WCDMA Band II, Frequency:1852.4 MHz								
3704.80	H	50.18	-47.08	10.60	1.25	-37.73	-13.00	24.73
3704.80	V	48.34	-48.89	10.60	1.25	-39.54	-13.00	26.54
5557.20	H	49.50	-43.78	11.43	1.49	-33.84	-13.00	20.84
5557.20	V	47.32	-45.81	11.43	1.49	-35.87	-13.00	22.87
152.58	H	51.64	-60.22	0.00	0.23	-60.45	-13.00	47.45
55.35	V	48.21	-55.58	-12.44	0.13	-68.15	-13.00	55.15
WCDMA Band II, Frequency:1880 MHz								
3760.00	H	51.08	-45.33	10.66	1.24	-35.91	-13.00	22.91
3760.00	V	49.43	-46.86	10.66	1.24	-37.44	-13.00	24.44
5640.00	H	50.25	-43.20	11.33	1.54	-33.41	-13.00	20.41
5640.00	V	48.36	-44.97	11.33	1.54	-35.18	-13.00	22.18
154.52	H	50.87	-60.92	0.00	0.23	-61.15	-13.00	48.15
54.71	V	48.46	-55.02	-12.73	0.13	-67.88	-13.00	54.88
WCDMA Band II, Frequency:1907.6MHz								
3815.20	H	50.54	-45.31	10.72	1.29	-35.88	-13.00	22.88
3815.20	V	51.26	-44.43	10.72	1.29	-35.00	-13.00	22.00
5722.80	H	48.86	-44.63	11.23	1.58	-34.98	-13.00	21.98
5722.80	V	49.13	-44.22	11.23	1.58	-34.57	-13.00	21.57
151.61	H	51.26	-60.63	0.00	0.23	-60.86	-13.00	47.86
56.65	V	47.85	-56.56	-11.84	0.14	-68.54	-13.00	55.54

AWS Band (PART 27)

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
WCDMA Band IV, Frequency:1712.4 MHz								
3424.80	H	52.34	-45.43	10.37	1.17	-36.23	-13.00	23.23
3424.80	V	47.40	-50.34	10.37	1.17	-41.14	-13.00	28.14
5137.20	H	52.50	-41.12	11.28	1.46	-31.30	-13.00	18.30
5137.20	V	49.18	-44.32	11.28	1.46	-34.50	-13.00	21.50
151.61	H	51.24	-60.65	0.00	0.23	-60.88	-13.00	47.88
56.65	V	48.30	-56.11	-11.84	0.14	-68.09	-13.00	55.09
WCDMA Band IV, Frequency:1732.6 MHz								
3465.20	H	49.73	-48.08	10.39	1.15	-38.84	-13.00	25.84
3465.20	V	47.88	-49.89	10.39	1.15	-40.65	-13.00	27.65
5197.80	H	49.54	-44.59	11.32	1.44	-34.71	-13.00	21.71
5197.80	V	49.13	-44.85	11.32	1.44	-34.97	-13.00	21.97
152.58	H	51.89	-59.97	0.00	0.23	-60.20	-13.00	47.20
54.71	V	47.65	-55.83	-12.73	0.13	-68.69	-13.00	55.69
WCDMA Band IV, Frequency:1752.6MHz								
3505.20	H	48.65	-49.18	10.41	1.18	-39.95	-13.00	26.95
3505.20	V	47.23	-50.54	10.41	1.18	-41.31	-13.00	28.31
5257.80	H	53.61	-40.12	11.35	1.47	-30.24	-13.00	17.24
5257.80	V	52.26	-41.25	11.35	1.47	-31.37	-13.00	18.37
151.61	H	52.02	-59.87	0.00	0.23	-60.10	-13.00	47.10
56.65	V	48.62	-55.79	-11.84	0.14	-67.77	-13.00	54.77

LTE Band 2 (30MHz-20GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
QPSK, Frequency: 1850.7 MHz								
3701.40	H	50.24	-47.07	10.60	1.25	-37.72	-13.00	24.72
3701.40	V	48.25	-49.04	10.60	1.25	-39.69	-13.00	26.69
5552.10	H	47.50	-45.77	11.44	1.49	-35.82	-13.00	22.82
5552.10	V	46.32	-46.78	11.44	1.49	-36.83	-13.00	23.83
151.61	H	52.70	-59.19	0.00	0.23	-59.42	-13.00	46.42
84.75	V	47.21	-61.73	0.00	0.17	-61.90	-13.00	48.90
QPSK, Frequency: 1880 MHz								
3760.00	H	50.15	-46.26	10.66	1.24	-36.84	-13.00	23.84
3760.00	V	42.19	-54.10	10.66	1.24	-44.68	-13.00	31.68
5640.00	H	46.06	-47.39	11.33	1.54	-37.60	-13.00	24.60
5640.00	V	45.65	-47.68	11.33	1.54	-37.89	-13.00	24.89
232.04	H	53.33	-58.93	0.00	0.29	-59.22	-13.00	46.22
86.69	V	46.54	-62.54	0.00	0.17	-62.71	-13.00	49.71
QPSK, Frequency: 1909.3 MHz								
3818.60	H	44.83	-51.03	10.72	1.29	-41.60	-13.00	28.60
3818.60	V	43.21	-52.50	10.72	1.29	-43.07	-13.00	30.07
5727.90	H	45.98	-47.50	11.23	1.59	-37.86	-13.00	24.86
5727.90	V	47.36	-46.00	11.23	1.59	-36.36	-13.00	23.36
232.04	H	53.65	-58.61	0.00	0.29	-58.90	-13.00	45.90
86.69	V	46.52	-62.56	0.00	0.17	-62.73	-13.00	49.73

LTE Band 4 (30MHz-20GHz):

EYE Band 4 (50MHz to 8GHz)								
Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
QPSK, Frequency: 1710.7 MHz								
3421.40	H	51.19	-46.57	10.37	1.17	-37.37	-13.00	24.37
3421.40	V	48.69	-49.04	10.37	1.17	-39.84	-13.00	26.84
5132.10	H	50.93	-42.64	11.28	1.47	-32.83	-13.00	19.83
5132.10	V	48.32	-45.14	11.28	1.47	-35.33	-13.00	22.33
6842.80	H	45.81	-45.63	11.23	1.87	-36.27	-13.00	23.27
6842.80	V	44.65	-46.64	11.23	1.87	-37.28	-13.00	24.28
151.61	H	51.23	-60.66	0.00	0.23	-60.89	-13.00	47.89
54.71	V	47.46	-56.02	-12.73	0.13	-68.88	-13.00	55.88
QPSK, Frequency: 1732.5 MHz								
3465.00	H	51.94	-45.87	10.39	1.15	-36.63	-13.00	23.63
3465.00	V	48.56	-49.21	10.39	1.15	-39.97	-13.00	26.97
5197.50	H	51.81	-42.32	11.32	1.44	-32.44	-13.00	19.44
5197.50	V	50.21	-43.77	11.32	1.44	-33.89	-13.00	20.89
6930.00	H	47.28	-43.72	11.21	1.89	-34.40	-13.00	21.40
6930.00	V	45.75	-45.12	11.21	1.89	-35.80	-13.00	22.80
151.61	H	51.86	-60.03	0.00	0.23	-60.26	-13.00	47.26
54.71	V	47.93	-55.55	-12.73	0.13	-68.41	-13.00	55.41
QPSK, Frequency: 1752.6 MHz								
3505.20	H	51.06	-46.77	10.41	1.18	-37.54	-13.00	24.54
3505.20	V	50.12	-47.65	10.41	1.18	-38.42	-13.00	25.42
5257.80	H	50.64	-43.09	11.35	1.47	-33.21	-13.00	20.21
5257.80	V	48.36	-45.15	11.35	1.47	-35.27	-13.00	22.27
7010.40	H	44.50	-46.16	11.19	1.90	-36.87	-13.00	23.87
7010.40	V	42.74	-47.77	11.19	1.90	-38.48	-13.00	25.48
151.61	H	52.38	-59.51	0.00	0.23	-59.74	-13.00	46.74
85.72	V	48.96	-60.05	0.00	0.17	-60.22	-13.00	47.22

LTE Band 5(30MHz-10GHz):

EYE Band (QPSK 16QAM 16QAM)								
Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
QPSK, Frequency: 824.7 MHz								
1649.40	H	58.04	-46.29	8.68	0.80	-38.41	-13.00	25.41
1649.40	V	57.52	-46.89	8.68	0.80	-39.01	-13.00	26.01
2474.10	H	49.61	-51.17	9.38	1.00	-42.79	-13.00	29.79
2474.10	V	42.76	-57.97	9.38	1.00	-49.59	-13.00	36.59
3298.80	H	33.18	-63.50	10.32	1.15	-54.33	-13.00	41.33
3298.80	V	33.70	-62.74	10.32	1.15	-53.57	-13.00	40.57
154.52	H	51.76	-60.03	0.00	0.23	-60.26	-13.00	47.26
56.65	V	47.70	-56.71	-11.84	0.14	-68.69	-13.00	55.69
QPSK, Frequency: 836.5 MHz								
1673.00	H	49.52	-54.79	8.71	0.85	-46.93	-13.00	33.93
1673.00	V	47.53	-56.88	8.71	0.85	-49.02	-13.00	36.02
2509.50	H	51.79	-48.82	9.42	1.01	-40.41	-13.00	27.41
2509.50	V	48.23	-52.39	9.42	1.01	-43.98	-13.00	30.98
3346.00	H	33.81	-63.35	10.34	1.16	-54.17	-13.00	41.17
3346.00	V	30.58	-66.44	10.34	1.16	-57.26	-13.00	44.26
232.04	H	52.44	-59.82	0.00	0.29	-60.11	-13.00	47.11
84.75	V	46.35	-62.59	0.00	0.17	-62.76	-13.00	49.76
QPSK, Frequency: 848.3 MHz								
1696.60	H	60.12	-44.17	8.74	0.89	-36.32	-13.00	23.32
1696.60	V	58.87	-45.55	8.74	0.89	-37.70	-13.00	24.70
2544.90	H	57.12	-43.22	9.47	1.01	-34.76	-13.00	21.76
2544.90	V	54.36	-45.94	9.47	1.01	-37.48	-13.00	24.48
3393.20	H	33.88	-63.79	10.36	1.19	-54.62	-13.00	41.62
3393.20	V	31.56	-66.07	10.36	1.19	-56.90	-13.00	43.90
152.58	H	51.55	-60.31	0.00	0.23	-60.54	-13.00	47.54
54.71	V	47.21	-56.27	-12.73	0.13	-69.13	-13.00	56.13

LTE Band 12(30MHz-10GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
QPSK, Frequency: 699.7 MHz								
1399.40	H	46.33	-57.37	8.22	0.71	-49.86	-13.00	36.86
1399.40	V	45.12	-58.63	8.22	0.71	-51.12	-13.00	38.12
2099.10	H	40.87	-61.01	9.16	0.91	-52.76	-13.00	39.76
2099.10	V	38.74	-63.09	9.16	0.91	-54.84	-13.00	41.84
2798.80	H	37.97	-61.96	9.88	1.04	-53.12	-13.00	40.12
2798.80	V	36.33	-63.47	9.88	1.04	-54.63	-13.00	41.63
151.61	H	51.26	-60.63	0.00	0.23	-60.86	-13.00	47.86
54.71	V	47.55	-55.93	-12.73	0.13	-68.79	-13.00	55.79
QPSK, Frequency: 707.5 MHz								
1415.00	H	46.82	-56.85	8.26	0.72	-49.31	-13.00	36.31
1415.00	V	45.30	-58.42	8.26	0.72	-50.88	-13.00	37.88
2122.50	H	37.88	-64.11	9.17	0.92	-55.86	-13.00	42.86
2122.50	V	35.45	-66.52	9.17	0.92	-58.27	-13.00	45.27
2830.00	H	36.55	-63.25	9.93	1.06	-54.38	-13.00	41.38
2830.00	V	34.25	-65.48	9.93	1.06	-56.61	-13.00	43.61
151.61	H	51.98	-59.91	0.00	0.23	-60.14	-13.00	47.14
54.71	V	46.87	-56.61	-12.73	0.13	-69.47	-13.00	56.47
QPSK, Frequency: 715.3 MHz								
1430.60	H	46.43	-57.20	8.31	0.73	-49.62	-13.00	36.62
1430.60	V	45.27	-58.42	8.31	0.73	-50.84	-13.00	37.84
2145.90	H	37.61	-64.49	9.19	0.93	-56.23	-13.00	43.23
2145.90	V	38.36	-63.75	9.19	0.93	-55.49	-13.00	42.49
2861.20	H	37.82	-61.83	9.98	1.07	-52.92	-13.00	39.92
2861.20	V	36.22	-63.45	9.98	1.07	-54.54	-13.00	41.54
152.58	H	50.85	-61.01	0.00	0.23	-61.24	-13.00	48.24
744.66	V	52.81	-47.34	0.00	0.55	-47.89	-13.00	34.89

LTE Band 13(30MHz-10GHz):

EYE Data is (SUMM. TGM).

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
QPSK, Frequency: 779.5 MHz								
1559.00	H	53.66	-50.33	8.57	0.80	-42.56	-40.00	2.56
1559.00	V	55.14	-48.91	8.57	0.80	-41.14	-40.00	1.14
2338.50	H	35.75	-65.84	9.30	0.97	-57.51	-13.00	44.51
2338.50	V	35.62	-65.74	9.30	0.97	-57.41	-13.00	44.41
3118.00	H	36.37	-61.12	10.25	1.13	-52.00	-13.00	39.00
3118.00	V	35.06	-62.29	10.25	1.13	-53.17	-13.00	40.17
150.64	H	52.48	-59.45	0.00	0.22	-59.67	-13.00	46.67
749.51	V	52.87	-47.15	0.00	0.54	-47.69	-13.00	34.69
QPSK, Frequency: 784.5 MHz								
1569.00	H	52.78	-51.30	8.58	0.81	-43.53	-40.00	3.53
1569.00	V	50.22	-53.91	8.58	0.81	-46.14	-40.00	6.14
2353.50	H	36.48	-64.97	9.31	0.97	-56.63	-13.00	43.63
2353.50	V	35.36	-65.86	9.31	0.97	-57.52	-13.00	44.52
3138.00	H	35.68	-61.72	10.26	1.14	-52.60	-13.00	39.60
3138.00	V	33.67	-63.56	10.26	1.14	-54.44	-13.00	41.44
151.61	H	52.78	-59.11	0.00	0.23	-59.34	-13.00	46.34
751.44	V	53.89	-46.08	0.00	0.53	-46.61	-13.00	33.61

LTE Band 14(30MHz-10GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
QPSK, Frequency: 790.5 MHz								
1581.00	H	52.98	-51.21	8.60	0.81	-43.42	-40.00	3.42
1581.00	V	55.24	-49.00	8.60	0.81	-41.21	-40.00	1.21
2371.50	H	36.57	-64.73	9.32	0.97	-56.38	-40.00	16.38
2371.50	V	36.40	-64.65	9.32	0.97	-56.30	-40.00	16.30
3162.00	H	35.30	-61.99	10.26	1.13	-52.86	-40.00	12.86
3162.00	V	36.02	-61.07	10.26	1.13	-51.94	-40.00	11.94
152.58	H	54.14	-57.72	0.00	0.23	-57.95	-13.00	44.95
758.23	V	52.62	-47.18	0.00	0.52	-47.70	-13.00	34.70
QPSK, Frequency: 795.5 MHz								
1591.00	H	53.45	-50.84	8.61	0.82	-43.05	-40.00	3.05
1591.00	V	54.12	-50.20	8.61	0.82	-42.41	-40.00	2.41
2386.50	H	36.08	-65.09	9.33	0.98	-56.74	-40.00	16.74
2386.50	V	37.11	-63.80	9.33	0.98	-55.45	-40.00	15.45
3182.00	H	35.68	-61.52	10.27	1.12	-52.37	-40.00	12.37
3182.00	V	36.89	-60.08	10.27	1.12	-50.93	-40.00	10.93
151.61	H	54.61	-57.28	0.00	0.23	-57.51	-13.00	44.51
751.44	V	52.34	-47.63	0.00	0.53	-48.16	-13.00	35.16

LTE Band 66(30MHz-20GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
QPSK, Frequency: 1710.7 MHz								
3421.40	H	51.22	-46.54	10.37	1.17	-37.34	-13.00	24.34
3421.40	V	48.36	-49.37	10.37	1.17	-40.17	-13.00	27.17
5132.10	H	50.95	-42.62	11.28	1.47	-32.81	-13.00	19.81
5132.10	V	49.22	-44.24	11.28	1.47	-34.43	-13.00	21.43
6842.80	H	45.72	-45.72	11.23	1.87	-36.36	-13.00	23.36
6842.80	V	43.69	-47.60	11.23	1.87	-38.24	-13.00	25.24
152.58	H	51.68	-60.18	0.00	0.23	-60.41	-13.00	47.41
56.65	V	48.10	-56.31	-11.84	0.14	-68.29	-13.00	55.29
QPSK, Frequency:1745 MHz								
3490.00	H	50.70	-47.14	10.40	1.17	-37.91	-13.00	24.91
3490.00	V	47.85	-49.93	10.40	1.17	-40.70	-13.00	27.70
5235.00	H	50.37	-43.53	11.34	1.46	-33.65	-13.00	20.65
5235.00	V	47.23	-46.48	11.34	1.46	-36.60	-13.00	23.60
6980.00	H	45.92	-44.94	11.20	1.90	-35.64	-13.00	22.64
6980.00	V	41.56	-49.15	11.20	1.90	-39.85	-13.00	26.85
151.61	H	51.22	-60.67	0.00	0.23	-60.90	-13.00	47.90
54.71	V	48.41	-55.07	-12.73	0.13	-67.93	-13.00	54.93
QPSK, Frequency: 1779.3 MHz								
3558.60	H	49.76	-47.91	10.46	1.22	-38.67	-13.00	25.67
3558.60	V	47.68	-49.89	10.46	1.22	-40.65	-13.00	27.65
5337.90	H	41.81	-51.66	11.40	1.47	-41.73	-13.00	28.73
5337.90	V	40.32	-53.01	11.40	1.47	-43.08	-13.00	30.08
7117.20	H	38.10	-51.35	11.13	1.93	-42.15	-13.00	29.15
7117.20	V	36.00	-53.42	11.13	1.93	-44.22	-13.00	31.22
152.58	H	51.25	-60.61	0.00	0.23	-60.84	-13.00	47.84
54.71	V	48.71	-54.77	-12.73	0.13	-67.63	-13.00	54.63

LTE Band 71(30MHz-10GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
QPSK, Frequency: 665.5 MHz								
1331.00	H	42.74	-60.29	8.03	0.76	-53.02	-13.00	40.02
1331.00	V	43.22	-60.14	8.03	0.76	-52.87	-13.00	39.87
1996.50	H	35.80	-66.36	9.10	0.89	-58.15	-13.00	45.15
1996.50	V	34.87	-66.67	9.10	0.89	-58.46	-13.00	45.46
2662.00	H	35.23	-64.73	9.66	1.06	-56.13	-13.00	43.13
2662.00	V	34.56	-65.32	9.66	1.06	-56.72	-13.00	43.72
151.61	H	51.41	-60.48	0.00	0.23	-60.71	-13.00	47.71
54.71	V	47.50	-55.98	-12.73	0.13	-68.84	-13.00	55.84
QPSK, Frequency:680.5 MHz								
1361.00	H	47.69	-55.64	8.11	0.77	-48.30	-13.00	35.30
1361.00	V	45.36	-58.17	8.11	0.77	-50.83	-13.00	37.83
2041.50	H	35.91	-66.12	9.12	0.91	-57.91	-13.00	44.91
2041.50	V	34.66	-66.98	9.12	0.91	-58.77	-13.00	45.77
2722.00	H	34.65	-65.32	9.76	1.05	-56.61	-13.00	43.61
2722.00	V	35.12	-64.79	9.76	1.05	-56.08	-13.00	43.08
152.58	H	51.87	-59.99	0.00	0.23	-60.22	-13.00	47.22
54.71	V	47.95	-55.53	-12.73	0.13	-68.39	-13.00	55.39
QPSK, Frequency: 695.5 MHz								
1391.00	H	45.21	-58.41	8.19	0.72	-50.94	-13.00	37.94
1391.00	V	47.33	-56.37	8.19	0.72	-48.90	-13.00	35.90
2086.50	H	37.00	-64.91	9.15	0.91	-56.67	-13.00	43.67
2086.50	V	36.45	-65.34	9.15	0.91	-57.10	-13.00	44.10
2782.00	H	35.57	-64.37	9.85	1.05	-55.57	-13.00	42.57
2782.00	V	34.36	-65.47	9.85	1.05	-56.67	-13.00	43.67
151.61	H	51.36	-60.53	0.00	0.23	-60.76	-13.00	47.76
54.71	V	47.65	-55.83	-12.73	0.13	-68.69	-13.00	55.69

Note:

- 1) The unit of Antenna Gain is dBd for frequency below 1GHz, and the unit of Antenna Gain is dBi for frequency above 1GHz.
- 2) Absolute Level = Substituted Level - Cable loss + Antenna Gain
- 3) Margin = Limit-Absolute Level

******* END OF REPORT *******