Band Edge Emission Test Results for Restricted Bands

EUT Name	Phone	Model Name	W635C
Temperature	25℃	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	DC 3.87V by battery
Test Mode	Mode 3	Antenna Polarity	Vertical

Test Graph for Peak Measurement



Test Graph for Average Measurement

RESULT: PASS

Note: The factor had been edited in the “Input Correction” of the Spectrum Analyzer.

10. Number of Hopping Frequency Measurement

10.1 Provisions Applicable

This frequency hopping system must employ a minimum of 15 hopping channels.

10.2 Measurement Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

1. Span = The frequency band of operation. Depending on the number of channels the device
2. supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
3. RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
4. VBW ⩾ RBW
5. Sweep time = Auto couple
6. Detector = Peak
7. Trace mode = Max hold
8. Allow the trace to stabilize

10.3 Measurement Setup (Block Diagram of Configuration)



10.4 Measurement Result

Test Data of Number of Hopping Frequency			
Test Mode	Number of Hopping Frequency	Limits	Pass or Fail
8DPSK Hopping	79	>=15	Pass

Test Graphs of Number of Hopping Frequency



Test_Graph_EDR_HOP_ANT1_NA_3Mbps_Number of Hopping

Note: All mode rates are tested and evaluated, 8DPSK modulated 3DH5 mode is the worst case and documented in the report.

11. Time of Occupancy (Dwell Time) Measurement

11.1 Provisions Applicable

The maximum permissible time of occupancy is 400ms within a period of 400ms multiplied by the number of hopping channels employed.

11.2 Measurement Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

1. Span = Zero span, centered on a hopping channel.
2. RBW shall be ⩽ channel spacing and where possible RBW should be set >> 1 / T, where T is the expected dwell time per channel.
3. VBW ⩾ RBW
4. Sweep time = As necessary to capture the entire dwell time per hopping channel
5. Detector = Peak
6. Trace mode = Free Run
7. Use the marker-delta function to determine the transmit time per hop. If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation in transmit time. An oscilloscope may be used instead of a spectrum analyzer. The EUT shall show compliance with the appropriate regulatory limit for the number of hopping channels. A plot of the data shall be included in the test report.

11.3 Measurement Setup (Block Diagram of Configuration)



11.4 Measurement Result

Test Data of Dwell Time					
Channel	Time of Pulse for 3DH5 (ms)	Number of hops in the period specified in the requirements	Dwell Time (ms)	Limit (ms)	Pass or Fail
2402	2.887	25.0*4	288.700	400	Pass
2441	2.887	23.0*4	265.604	400	Pass
2480	2.887	25.0*4	288.700	400	Pass

Test Graphs of Dwell Time



Test_Graph_EDR_HOP_ANT1_NA_3Mbps_2402_Number of Busrt



Test_Graph_EDR_HOP_ANT1_NA_3Mbps_2402_Time per Burst



Test_Graph_EDR_HOP_ANT1_NA_3Mbps_2441_Number of Busrt



Test_Graph_EDR_HOP_ANT1_NA_3Mbps_2441_Time per Burst



Test_Graph_EDR_HOP_ANT1_NA_3Mbps_2480_Number of Busrt



Test_Graph_EDR_HOP_ANT1_NA_3Mbps_2480_Time per Burst

Note: All mode rates are tested and evaluated, 8DPSK modulated 3DH5 mode is the worst case and documented in the report.

12. Frequency Separation Measurement

12.1 Provisions Applicable

When the power is less than 0.125W: The minimum permissible channel separation for this system is 2/3 the value of the 20dB BW.
When the power is less than 1W: The minimum permissible channel separation for this system is 20dB BW.

12.2 Measurement Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

1. Span: Wide enough to capture the peaks of two adjacent channels.
2. RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
3. Video (or average) bandwidth (VBW) ⩾ RBW.
4. Sweep: Auto.
5. Detector function: Peak.
6. Trace: Max hold. g) Allow the trace to stabilize.
7. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

12.3 Measurement Setup (Block Diagram of Configuration)



12.4 Measurement Result

Test Data of Frequency Separation			
Test Mode	Channel Separation (MHz)	Limits (MHz)	Pass or Fail
8DPSK	0.949	0.864	Pass

Test Graphs of Frequency Separation



Test_Graph_EDR_HOP_ANT1_NA_3Mbps_Hopping Separation

Note: All mode rates are tested and evaluated, 8DPSK modulated 3DH5 mode is the worst case and documented in the report.

13. AC Power Line Conducted Emission Test

13.1 Measurement Limit

Frequency	Maximum RF Line Voltage	
	Q.P. (dBμV)	Average (dBμV)
150kHz~500kHz	66-56	56-46
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Note:

1. The lower limit shall apply at the transition frequency.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

13.2 Measurement Setup (Block Diagram of Configuration)



13.3 Preliminary Procedure of Line Conducted Emission Test

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
2. Support equipment, if needed, was placed as per ANSI C63.10.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
4. All support equipment received AC120V/60Hz power from a LISN, if any.
5. The EUT received DC 5V power from adapter which received AC120V/60Hz power from a LISN.
6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side).
7. Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
8. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
9. During the above scans, the emissions were maximized by cable manipulation.
10. The test mode(s) were scanned during the preliminary test.
11. Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

13.4 Final Procedure of Line Conducted Emission Test

1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.
3. If EUT emission level was less –2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
4. The test data of the worst case condition(s) was reported on the Summary Data page.
5. A conducted emission is calculated by the following equation:
   - Measurement Level (dBμV) = Receiver reading (dBμV) + Transd (dB)
   - Transd (dB)= AMN Factor(dB)+Cable Loss(dB)+Attenuation(dB)
   - Margin= Limit-Level

13.5 Measurement Result

AC Power Line Conducted Emission Test			
Test Mode	Mode 1	LISN Line	Hot Side



MEASUREMENT RESULT: "agc_fin"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.170000	48.90	6.1	65	16.1	QP	L1
0.194000	47.10	6.1	64	16.8	QP	L1
0.218000	45.50	6.1	63	17.4	QP	L1
0.242000	44.10	6.1	62	17.9	QP	L1
0.266000	42.60	6.1	61	18.6	QP	L1
0.290000	40.80	6.1	61	19.7	QP	L1

MEASUREMENT RESULT: "agc_fin2"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.174000	28.90	6.1	55	25.9	AV	L1
0.222000	27.10	6.1	53	25.6	AV	L1
0.290000	26.30	6.1	51	24.2	AV	L1
0.342000	23.60	6.1	49	25.6	AV	L1
0.558000	22.50	6.2	46	23.5	AV	L1
0.606000	28.70	6.2	46	17.3	AV	L1

RESULT: PASS

AC Power Line Conducted Emission Test			
Test Mode	Mode 1	LISN Line	Neutral Side



MEASUREMENT RESULT: "agc_fin"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.150000	45.60	6.1	66	20.4	QP	N
0.170000	48.90	6.1	65	16.1	QP	N
0.194000	46.90	6.1	64	17.0	QP	N
0.222000	42.50	6.1	63	20.2	QP	N
0.242000	44.00	6.1	62	18.0	QP	N
0.266000	42.30	6.1	61	18.9	QP	N

MEASUREMENT RESULT: "agc_fin2"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.150000	30.10	6.1	56	25.9	AV	N
0.170000	32.00	6.1	55	23.0	AV	N
0.242000	28.50	6.1	52	23.5	AV	N
0.270000	26.50	6.1	51	24.6	AV	N
0.534000	22.40	6.2	46	23.6	AV	N
0.606000	31.30	6.2	46	14.7	AV	N

RESULT: PASS

AC Power Line Conducted Emission Test			
Test Mode	Mode 2	LISN Line	Hot Side



MEASUREMENT RESULT: "agc_fin"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.150000	46.50	6.1	66	19.5	QP	L1
0.170000	49.50	6.1	65	15.5	QP	L1
0.194000	47.70	6.1	64	16.2	QP	L1
0.218000	46.00	6.1	63	16.9	QP	L1
0.242000	44.60	6.1	62	17.4	QP	L1
0.270000	41.80	6.1	61	19.3	QP	L1

MEASUREMENT RESULT: "agc_fin2"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.174000	29.40	6.1	55	25.4	AV	L1
0.246000	27.10	6.1	52	24.8	AV	L1
0.314000	25.50	6.1	50	24.4	AV	L1
0.342000	24.10	6.1	49	25.1	AV	L1
0.462000	22.70	6.1	47	24.0	AV	L1
0.606000	29.00	6.2	46	17.0	AV	L1

RESULT: PASS

AC Power Line Conducted Emission Test			
Test Mode	Mode 2	LISN Line	Neutral Side



MEASUREMENT RESULT: "agc_fin"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.150000	46.70	6.1	66	19.3	QP	N
0.170000	50.00	6.1	65	15.0	QP	N
0.194000	48.10	6.1	64	15.8	QP	N
0.218000	46.30	6.1	63	16.6	QP	N
0.242000	45.10	6.1	62	16.9	QP	N
0.266000	43.60	6.1	61	17.6	QP	N

MEASUREMENT RESULT: "agc_fin2"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.170000	32.80	6.1	55	22.2	AV	N
0.198000	28.80	6.1	54	24.9	AV	N
0.218000	30.00	6.1	53	22.9	AV	N
0.270000	27.00	6.1	51	24.1	AV	N
0.558000	24.00	6.2	46	22.0	AV	N
0.606000	30.80	6.2	46	15.2	AV	N

RESULT: PASS

AC Power Line Conducted Emission Test			
Test Mode	Mode 3	LISN Line	Hot Side



MEASUREMENT RESULT: "agc_fin"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.182000	33.00	6.1	64	31.4	QP	L1
0.586000	26.10	6.2	56	29.9	QP	L1
1.214000	20.90	6.2	56	35.1	QP	L1
4.178000	20.50	6.3	56	35.5	QP	L1
4.506000	21.70	6.3	56	34.3	QP	L1
4.966000	20.80	6.3	56	35.2	QP	L1

MEASUREMENT RESULT: "agc_fin2"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.222000	22.50	6.1	53	30.2	AV	L1
0.538000	17.40	6.2	46	28.6	AV	L1
1.230000	15.70	6.2	46	30.3	AV	L1
4.526000	12.50	6.3	46	33.5	AV	L1
4.982000	13.40	6.3	46	32.6	AV	L1
5.202000	14.60	6.4	50	35.4	AV	L1

RESULT: PASS

AC Power Line Conducted Emission Test			
Test Mode	Mode 3	LISN Line	Neutral Side



MEASUREMENT RESULT: "agc_fin"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.206000	31.50	6.1	63	31.9	QP	N
0.590000	23.90	6.2	56	32.1	QP	N
0.630000	25.30	6.2	56	30.7	QP	N
4.398000	22.20	6.3	56	33.8	QP	N
4.890000	21.90	6.3	56	34.1	QP	N
4.982000	22.20	6.3	56	33.8	QP	N

MEASUREMENT RESULT: "agc_fin2"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.222000	22.90	6.1	53	29.8	AV	N
0.630000	17.70	6.2	46	28.3	AV	N
1.118000	15.60	6.2	46	30.4	AV	N
4.322000	12.80	6.3	46	33.2	AV	N
4.442000	14.60	6.3	46	31.4	AV	N
4.462000	13.60	6.3	46	32.4	AV	N

RESULT: PASS

AC Power Line Conducted Emission Test			
Test Mode	Mode 4	LISN Line	Hot Side



MEASUREMENT RESULT: "agc_fin"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.606000	31.00	10.3	56	25.0	QP	L1
9.030000	40.50	12.0	60	19.5	QP	L1
9.106000	40.10	12.0	60	19.9	QP	L1
9.158000	43.40	12.0	60	16.6	QP	L1
9.170000	39.60	12.0	60	20.4	QP	L1
9.286000	42.80	12.1	60	17.2	QP	L1

MEASUREMENT RESULT: "agc_fin2"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.606000	24.40	10.3	46	21.6	AV	L1
7.486000	25.70	11.5	50	24.3	AV	L1
9.170000	25.60	12.0	50	24.4	AV	L1
9.210000	25.80	12.0	50	24.2	AV	L1
9.250000	26.10	12.0	50	23.9	AV	L1
9.286000	27.40	12.1	50	22.6	AV	L1

RESULT: PASS

AC Power Line Conducted Emission Test			
Test Mode	Mode 4	LISN Line	Neutral Side



MEASUREMENT RESULT: "agc_fin"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.582000	31.40	10.3	56	24.6	QP	N
0.622000	39.30	10.3	56	16.7	QP	N
9.154000	41.80	12.0	60	18.2	QP	N
9.246000	43.00	12.0	60	17.0	QP	N
9.258000	40.60	12.0	60	19.4	QP	N
9.282000	42.20	12.0	60	17.8	QP	N

MEASUREMENT RESULT: "agc_fin2"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.586000	26.20	10.3	46	19.8	AV	N
3.666000	15.10	10.6	46	30.9	AV	N
9.074000	25.90	12.0	50	24.1	AV	N
9.118000	26.70	12.0	50	23.3	AV	N
9.154000	26.70	12.0	50	23.3	AV	N
9.258000	25.80	12.0	50	24.2	AV	N

RESULT: PASS

Appendix I: Photographs of Test Setup

Refer to the Report No.: AGC14499241202AP01

Appendix II: Photographs of Test EUT

Refer to the Report No.: AGC14499241202AP02

Conditions of Issuance of Test Reports

1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the “Company”) solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the “Clients”).
2. Any report issued by Company as a result of this application for testing services (the “Report”) shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
3.The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
7.Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.
9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.

-----End of Report-----