



11 MAXIMUM PERMISSIBLE EXPOSURE (MPE)

11.1 Standard Applicable

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

This is a Mobile device, the MPE is required.

According to §1.1310 and §2.1091 RF exposure is calculated.

Limits for Maximum Permissive Exposure (MPE)

Frequency Range	Electric Field	Magnetic Field	Power Density	Averaging Time			
(MHz)	Strength (V/m)	Strength (A/m)	(mW/cm ²)	(minute)			
Limits for General Population/Uncontrolled Exposure							
0.3-1.34	614	1.63	*(100)	30			
1.34-30	824/f	2.19/f	*(180/f ²)	30			
30-300	27.5	0.073	0.2	30			
300-1500	1	/	F/1500	30			
1500-15000	1	1	1.0	30			

F = frequency in MHz

Note:

Prediction of MPE limit at a given distance

S=PG/4πR²

Where: S = Power density

P = Power input to antenna

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = Distance to the center of radiation of the antenna

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only

公式 (Annual of the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms_and_conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law

台灣檢驗科技股份有限公司 | t (886-2) 2299-3279

No.134,WuKungRoad,NewTaipeiIndustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134 號 f (886-2) 2298-0488

^{* =} Plane-wave equipment power density





11.2 Maximum Permissible Exposure (MPE) Evaluation

Freq.	E-Field	BWCF	EIRP_1MHz	EIRP_50MHz	EIRP_50MHz	Margin	Pol
					Limit		
(MHz)	[dBuV/m]	[dB]	[dBm]	[dBm]	[dBm]	[dB]	[H/V]
7200	37.89	-33.98	-57.31	-23.33	0	-23.33	V
7200	42.17	-33.98	-53.03	-19.05	0	-19.05	Н

MPE Prediction

Max. EIRP:	-19.05	(dBm)
Max. EIRP:	0.01245	(mW)
Duty cycle:	100	(%)
Maximum Pav :	0.012445	(mW)
Peak Antenna gain (linear):	6.18	(numeric)
Prediction distance:	5	(cm)
Prediction frequency:	7200	(MHz)
MPE limit for uncontrolled exposure at prediction	1	
frequency:		(mW/cm2)
Power density at predication frequency at 5 (cm)	0.000039634	
distance		(mW/cm2)

Measurement Result

The predicted power density level at 5 cm is 0.000039634 mW/cm2. This is below the uncontrolled exposure limit of 1 mW/cm2 at 7200MHz.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law

No.134,WuKungRoad,NewTaipeiIndustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134 號 f (886-2) 2298-0488

台灣檢驗科技股份有限公司 t (886-2) 2299-3279

SGS Taiwan Ltd.