

FCC

RF

TEST REPORT

ISSUED BY
Shenzhen BALUN Technology Co., Ltd.



FOR
Wireless remote controller

ISSUED TO
DONG GUANG ZHAN YU ELECTRONIC CO., LTD

No.38, xinxing east road, dalang town, dongguan city



Prepared by: Hu Chao
Hu Chao
(Engineer)
Date: Sep. 18, 2018
Approved by: Wei Yanquan
Wei Yanquan
(Chief Engineer)
Date: Sep. 18, 2018

Report No.: BL-SZ1880507-601
EUT Name: Wireless remote controller
Model Name: JYRF21A-20 (refer section 2.4)
Brand Name: JYRF21A
Test Standard: 47 CFR Part 15 Subpart C
FCC ID: 2AQ3RDGZY180830K029

Test Conclusion: Pass
Test Date: Aug. 31, 2018 ~ Sep. 03, 2018
Date of Issue: Sep. 18, 2018

NOTE: This test report of test results only related to testing samples, which can be duplicated completely for the legal use with the approval of the applicant; it shall not be reproduced except in full, without the written approval of Shenzhen BALUN Technology Co., Ltd. BALUN Laboratory. Any objections should be raised within thirty days from the date of issue. To validate the report, please contact us.

Revision History

Version	Issue Date	Revisions
<u>Rev. 01</u>	<u>Sep. 17, 2018</u>	<u>Initial Issue</u>
<u>Rev. 02</u>	<u>Sep. 18, 2018</u>	<u>Revised the Ancillary Equipment in section 2.5, Update the Test Equipment List in section 4.2.</u>

TABLE OF CONTENTS

1	ADMINISTRATIVE DATA (GENERAL INFORMATION)	5
1.1	Identification of the Testing Laboratory	5
1.2	Identification of the Responsible Testing Location	5
1.3	Laboratory Condition	5
1.4	Announce	5
2	PRODUCT INFORMATION	6
2.1	Applicant	6
2.2	Manufacturer	6
2.3	Factory Information	6
2.4	General Description for Equipment under Test (EUT)	6
2.5	Ancillary Equipment	6
2.6	Technical Information	7
3	SUMMARY OF TEST RESULTS	8
3.1	Test Standards	8
3.2	Verdict	8
4	GENERAL TEST CONFIGURATIONS	9
4.1	Test Environments	9
4.2	Test Equipment List	9
4.3	Measurement Uncertainty	10
4.4	Description of Test Setup	11
4.4.1	For AC Power Supply Port Test	11
4.4.2	For Radiated Test (Below 30 MHz)	11

4.4.3	For Radiated Test (30 MHz-1 GHz)	12
4.4.4	For Radiated Test (Above 1 GHz).....	12
5	TEST ITEMS.....	13
5.1	Antenna Requirements	13
5.1.1	Relevant Standards.....	13
5.1.2	Antenna Anti-Replacement Construction	13
5.1.3	Antenna Gain	13
5.2	Conducted Emission	14
5.2.1	Limit.....	14
5.2.2	Test Setup	14
5.2.3	Test Procedure.....	14
5.2.4	Test Result	14
5.3	20 dB Bandwidth	15
5.3.1	Limit.....	15
5.3.2	Test Setup	15
5.3.3	Test Procedure.....	15
5.3.4	Test Result	15
5.4	Field Strength of Fundamental Emissions and Radiated Emissions.....	16
5.4.1	Limit.....	16
5.4.2	Test Setup	16
5.4.3	Test Procedure.....	16
5.4.4	Test Result	17
5.5	Transmitting Time	18
5.5.1	Limit.....	18
5.5.2	Test Setup	18
5.5.3	Test Procedure.....	18
5.5.4	Test Result	18
ANNEX A	TEST RESULT	19
A.1	Conducted Emission	19
A.2	Bandwidth	20
A.3	Duty cycle.....	21

A.4	Field Strength of Fundamental Emissions	23
A.5	Radiated Emissions	24
A.6	Transmitter Time	27
ANNEX B	TEST SETUP PHOTOS	28
ANNEX C	EUT EXTERNAL PHOTOS	28
ANNEX D	EUT INTERNAL PHOTOS	28

1 ADMINISTRATIVE DATA (GENERAL INFORMATION)

1.1 Identification of the Testing Laboratory

Company Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

1.2 Identification of the Responsible Testing Location

Test Location	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	<p>The laboratory has been listed by Industry Canada to perform electromagnetic emission measurements. The recognition numbers of test site are 11524A-1.</p> <p>The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196.</p> <p>The laboratory is a testing organization accredited by American Association for Laboratory Accreditation(A2LA) according to ISO/IEC 17025.The accreditation certificate is 4344.01.</p> <p>The laboratory is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L6791.</p>
Description	All measurement facilities used to collect the measurement data are located at Block B, FL 1, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China 518055

1.3 Laboratory Condition

Ambient Temperature	20°C to 25°C
Ambient Relative Humidity	45% to 55%
Ambient Pressure	100 kPa to 102 kPa

1.4 Announce

- (1) The test report reference to the report template version v5.4.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
- (5) This document may not be altered or revised in any way unless done so by BALUN and all revisions are duly noted in the revisions section.
- (6) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.

2 PRODUCT INFORMATION

2.1 Applicant

Applicant	DONG GUANG ZHAN YU ELECTRONIC CO., LTD
Address	No.38, xinxing east road, dalang town, dongguan city

2.2 Manufacturer

Manufacturer	Shenzhen Jinyuan Weiye Electronics Co., Ltd.
Address	No. 3, F District, 2 E building, Yicheng Industrial Park, Xixiang, Baoan District, Shenzhen

2.3 Factory Information

Manufacturer	DONG GUANG ZHAN YU ELECTRONIC CO., LTD
Address	No.38, xinxing east road, dalang town, dongguan city

2.4 General Description for Equipment under Test (EUT)

EUT Name	Wireless remote controller
Under Test Model Name	JYRF21A-20
Series Model Name	JYRF21A-xx (xx=1 to 21)
Description of Model name differentiation	All models are same with electrical parameters and internal circuit structure, but only differ in key number. 1 to 21, which represents the number of keys. On the basis of the main model, one to 21 buttons can be made with different PVC surface stickers.
Hardware Version	N/A
Software Version	N/A
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

2.5 Ancillary Equipment

Ancillary Equipment 1	Battery	
	Brand Name	Liyuan
	Model No.	CR2025
	Serial No.	N/A
	Capacity	150 mAh
	Rated Voltage	3.0 V
	Limit Charge Voltage	N/A

2.6 Technical Information

Modulation Type	FSK
Product Type	<input type="checkbox"/> Mobile <input checked="" type="checkbox"/> Portable <input type="checkbox"/> Fix Location
Operating Frequency	433.92 MHz.
Antenna Type	PCB Antenna
Antenna Gain	0 dBi

All channel was listed on the following table:

Channel number	Freq.(MHz)
1	433.92

Note: The above EUT information in section 2.4 and 2.6 was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15, Subpart C (10-1-16 Edition)	Intentional Radiators
2	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices

3.2 Verdict

No.	Description	FCC Part No.	Test Result	Verdict
1	Antenna Requirement	15.203	--	Pass ^{Note 1}
2	Conducted Emission	15.207	ANNEX A.1	N/A ^{Note 2}
3	20 dB Bandwidth	15.231(c)	ANNEX A.2	Pass
4	Duty Cycle	15.35	ANNEX A.3	Pass
5	Field Strength of Fundamental Emissions	15.231(b)	ANNEX A.4	Pass
6	Radiated Emissions	15.209 15.231(b)	ANNEX A.5	Pass
7	Transmitting Time	15.231(a)	ANNEX A.6	Pass

Note 1: Please refer to section 5.1.

Note 2: The EUT only powered by battery, so the Conducted Emission test is not applicable.

4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	45% to 55%	
Atmospheric Pressure	100 kPa to 102 kPa	
Temperature	NT (Normal Temperature)	+22°C to +25°C
Working Voltage of the EUT	NV (Normal Voltage)	3 V

4.2 Test Equipment List

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	ROHDE&SCHWARZ	FSV-30	103118	2018.06.15	2019.06.14
Switch Unit with OSP-B157	ROHDE&SCHWARZ	OSP120	101270	2018.06.15	2019.06.14
Spectrum Analyzer	AGILENT	E4440A	MY45304434	2017.11.02	2018.11.01
EMI Receiver	ROHDE&SCHWARZ	ESRP	101036	2018.06.13	2019.06.12
LISN	SCHWARZBECK	NSLK 8127	8127-687	2018.06.13	2019.06.12
Bluetooth Tester	ROHDE&SCHWARZ	CBT	101005	2018.06.15	2019.06.14
Power Splitter	KMW	DCPD-LDC	1305003215	--	--
Power Sensor	ROHDE&SCHWARZ	NRP-Z21	103971	2018.06.15	2019.06.14
Attenuator (20 dB)	KMW	ZA-S1-201	110617091	--	--
Attenuator (6 dB)	KMW	ZA-S1-61	1305003189	--	--
DC Power Supply	ROHDE&SCHWARZ	HMP2020	018141664	2018.06.14	2019.06.13
Temperature Chamber	ANGELANTIONI SCIENCE	NTH64-40A	1310	2018.06.26	2019.06.25
Test Antenna-Rod(9 kHz-30 MHz)	SCHWARZBECK	VAMP 9243	9243-556	2018.08.25	2019.08.25
Test Antenna-Bi-Log(30 MHz-3 GHz)	SCHWARZBECK	VULB 9163	9163-624	2017.07.22	2019.07.21
Test Antenna-Horn(1-18 GHz)	SCHWARZBECK	BBHA 9120D	9120D-1148	2018.07.11	2020.07.10
Test Antenna-Horn(15-26.5 GHz)	SCHWARZBECK	BBHA 9170	9170-305	2018.06.21	2019.06.20
Anechoic Chamber	EMC TECHNOLOGY LTD	21.1m*11.6m*7.35 m	N/A	2017.08.08	2019.08.07
Anechoic Chamber	RAINFORD	9m*6m*6m	N/A	2017.02.21	2019.02.20
Shielded Enclosure	ChangNing	CN-130701	130703s	--	--
RF Cable1	ROHDE&SCHWARZ	JUNFLON	APR0914004	2018.07.10	2018.10.09
RF Cable2	Huber&Suhner	RG_400_/U	N/A	2018.07.10	2018.10.09
RF Cable3	Huber&Suhner	RG_400_/U	N/A	2018.07.10	2018.10.09
RF Cable4	Huber&Suhner	SX_04172_B-60	54026748	2018.07.10	2018.10.09

Note: The calibration period of the RF cable is three month.

4.3 Measurement Uncertainty


The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Measurement	Value
Occupied Channel Bandwidth	$\pm 4\%$
RF output power, conducted	± 1.4 dB
Power Spectral Density, conducted	± 2.5 dB
Unwanted Emissions, conducted	± 2.8 dB
All emissions, radiated	± 5.4 dB
Temperature	$\pm 1^{\circ}\text{C}$
Humidity	$\pm 4\%$


4.4 Description of Test Setup

4.4.1 For AC Power Supply Port Test




(Diagram 1)

4.4.2 For Radiated Test (Below 30 MHz)




(Diagram 2)

4.4.3 For Radiated Test (30 MHz-1 GHz)



(Diagram 3)

4.4.4 For Radiated Test (Above 1 GHz)



(Diagram 4)

5 TEST ITEMS

5.1 Antenna Requirements

5.1.1 Relevant Standards

FCC §15.203 & 15.247(b)


An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

Protected Method	Description
The antenna is embedded in the product.	An embedded-in antenna design is used.

Reference Documents	Item
Photo	

5.1.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

5.2 Conducted Emission

5.2.1 Limit

FCC §15.207

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
0.50 - 30	60	50

5.2.2 Test Setup

See section 4.4.1 for test setup description for the AC power supply port. The photo of test setup please refer to ANNEX B.

5.2.3 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

5.2.4 Test Result

Please refer to ANNEX A.1.

5.3 20 dB Bandwidth

5.3.1 Limit

FCC §15.231

The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.

5.3.2 Test Setup

See section 4.4.3 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.3.3 Test Procedure

Use the following spectrum analyzer settings:

Span = approximately 2 to 3 times the 20 dB bandwidth

RBW = 100 kHz

VBW \geq 300 kHz

Sweep = auto

Detector function = peak

Trace = max hold

5.3.4 Test Result

Please refer to ANNEX A.2.

5.4 Field Strength of Fundamental Emissions and Radiated Emissions

5.4.1 Limit

FCC §15.231 & §15.209

According to FCC section 15.231(b), In addition to the provisions of §15.205, the field strength of emissions from intentional radiators operated under this section shall not exceed the following:

Fundamental frequency (MHz)	Field strength of fundamental (microvolts/meter)	Field strength of spurious emissions (microvolts/meter)
40.66-40.70	2250	225
70-130	1250	125
130-174	¹ 1250 to 3750	125 to 375
174-260	3750	375
260-470	¹ 3750 to 12500	375 to 1250
Above 470	12500	1250
¹ Linear interpolations.		

Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (μV/m)
0.009 - 0.490	2400/F(kHz)
0.490 - 1.705	24000/F(kHz)
1.705 - 30.0	30
30 - 88	100
88 - 216	150
216 - 960	200
Above 960	500

Note:

- For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit.
- For above 1000 MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK).

5.4.2 Test Setup

See section 4.4.2 to 4.4.4 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.4.3 Test Procedure

The measurement frequency range is from 30 MHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented. The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

5.4.4 Test Result

Please refer to ANNEX A.4 & A.5.

5.5 Transmitting Time

5.5.1 Limit

(1) A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

(2) A transmitter activated automatically shall cease transmission within 5 seconds after activation.

5.5.2 Test Setup

See section 4.4.3 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.5.3 Test Procedure

The EUT transmitter was activated, the spectrum analyzer single sweep was triggered while a command on the EUT was activated and plots were captured

5.5.4 Test Result

Please refer to ANNEX A.6.

ANNEX A TEST RESULT

A.1 Conducted Emission

Note: Not applicable.


A.2 Bandwidth

Test Data


Frequency (MHz)	99% OBW (KHz)	20 dB Bandwidth (kHz)	Limit (kHz)	Verdict
433.92	21.231	50.31	$433908 \times 0.25\% = 1084.77$	Pass

Test plots

99% OBW





20 dB Bandwidth




A.3 Duty cycle


Test Data and Plot

Data Transmissions		Number of pulses
The number of pulses Group		3
Short pulse duration	0.360ms	14
Long pulse duration	1.090 ms	11
Total transmissions duration	$14 \times 0.36 + 11 \times 1.09 = 17.03$	
On time within 100ms	$17.03 \times 2 = 34.06$	
DC correction factor	$10 \times \log(34.06/100) = -4.68$	





A.4 Field Strength of Fundamental Emissions



The Field Strength of Fundamental Emissions (Operating Frequency) is:

$$3750 \text{ uV/m} = 20 \cdot \log(3750) \text{ dBuV/m} = 71.48 \text{ dBuV/m}$$

$$12500 \text{ uV/m} = 20 \cdot \log(12500) \text{ dBuV/m} = 81.94 \text{ dBuV/m}$$

Test Data

Field Strength of Fundamental Emissions and Field strength of spurious emissions Value					
Operating Frequency (MHz)	Field Strength (dBuV/m)	Detector	Limit @3m (dBuV/m)	Margin (dB)	Antenna
434.005	59.92	PEAK	100.8	40.88	Vertical
	75.65	PEAK	100.8	25.15	Horizontal
	55.24	AVERAGE	80.8	25.56	Vertical
	70.97	AVERAGE	80.8	9.83	Horizontal
867.838	52.37	PEAK	80.8	28.43	Vertical
	63.71	PEAK	80.8	17.09	Horizontal
	47.69	AVERAGE	60.8	13.11	Vertical
	59.03	AVERAGE	60.8	1.77	Horizontal

A.5 Radiated Emissions

Note ¹: The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

Note ²: The verdict please refer to the A.3 field strength of fundamental emissions and field strength of spurious emissions value.

Test Data and Plots (30 MHz ~ 10th Harmonic)

30 MHz to 1 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	45.035	18.11	-26.64	40.0	-21.89	Peak	219.00	100	Vertical	Pass
2	60.555	17.29	-27.42	40.0	-22.71	Peak	360.00	100	Vertical	Pass
3	148.340	20.11	-24.91	43.5	-23.39	Peak	219.00	100	Vertical	Pass
4	299.418	21.27	-24.18	46.0	-24.73	Peak	360.00	200	Vertical	Pass
5	434.005	59.92	-20.27	100.8	-40.88	Peak	280.00	100	Vertical	Pass
5**	434.005	55.24	-20.27	80.8	-25.56	AV	280.00	100	Vertical	Pass
6	867.838	52.37	-11.87	80.8	-28.43	Peak	187.00	100	Vertical	Pass
6**	867.838	47.69	-11.87	60.8	-13.11	AV	187.00	100	Vertical	Pass

30 MHz to 1 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	40.428	17.05	-26.26	40.0	-22.95	Peak	232.00	100	Horizontal	Pass
2	105.418	16.48	-28.71	43.5	-27.02	Peak	42.00	100	Horizontal	Pass
3	155.130	19.60	-24.64	43.5	-23.90	Peak	250.00	100	Horizontal	Pass
4	300.873	20.76	-24.25	46.0	-25.24	Peak	153.00	100	Horizontal	Pass
5	434.005	75.65	-20.27	100.8	-25.15	Peak	306.00	100	Horizontal	Pass
5**	434.005	70.97	-20.27	80.8	-9.83	AV	306.00	100	Horizontal	Pass
6	867.838	63.71	-11.87	80.8	-17.09	Peak	268.00	100	Horizontal	Pass
6**	867.838	59.03	-11.87	60.8	-1.77	AV	268.00	100	Horizontal	Pass

1 GHz to 6 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1**	1302.000	39.12	-17.03	60.8	-21.68	AV	34.00	150	Vertical	Pass
1	1302.000	42.56	-17.03	80.8	-38.24	Peak	34.00	150	Vertical	Pass
2**	2169.500	37.36	-13.46	60.8	-23.44	AV	177.00	150	Vertical	Pass
2	2169.500	46.00	-13.46	80.8	-34.80	Peak	177.00	150	Vertical	Pass
3**	2603.500	34.24	-11.82	54.0	-19.76	AV	145.00	150	Vertical	Pass
3	2603.500	42.75	-11.82	74.0	-31.25	Peak	145.00	150	Vertical	Pass
4**	3037.500	40.17	-7.54	60.8	-20.63	AV	213.00	150	Vertical	Pass
4	3037.500	49.09	-7.54	80.8	-31.71	Peak	213.00	150	Vertical	Pass
5**	3993.750	35.92	-3.83	54.0	-18.08	AV	237.00	150	Vertical	Pass
5	3993.750	46.99	-3.83	74.0	-27.01	Peak	237.00	150	Vertical	Pass
6**	4449.750	38.07	-4.18	54.0	-15.93	AV	14.00	150	Vertical	Pass
6	4449.750	49.26	-4.18	74.0	-24.74	Peak	14.00	150	Vertical	Pass

1 GHz to 6 GHz, ANT H


No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1**	1736.000	33.59	-16.92	54.0	-20.41	AV	279.00	150	Horizontal	Pass
1	1736.000	38.84	-16.92	74.0	-35.16	Peak	279.00	150	Horizontal	Pass
2**	2170.000	53.60	-13.50	60.8	-7.2	AV	353.00	150	Horizontal	Pass
2	2170.000	53.67	-13.50	80.8	-27.13	Peak	353.00	150	Horizontal	Pass
3**	2603.500	44.45	-11.82	60.8	-16.35	AV	353.00	150	Horizontal	Pass
3	2603.500	50.22	-11.82	80.8	-30.58	Peak	353.00	150	Horizontal	Pass
4**	3038.250	53.33	-7.59	60.8	-7.47	AV	306.00	150	Horizontal	Pass
4	3038.250	49.26	-7.59	80.8	-31.54	Peak	306.00	150	Horizontal	Pass
5**	3471.750	43.64	-6.95	60.8	-17.16	AV	316.00	150	Horizontal	Pass
5	3471.750	48.29	-6.95	80.8	-32.51	Peak	316.00	150	Horizontal	Pass
6**	3905.250	37.43	-5.93	60.8	-23.37	AV	330.00	150	Horizontal	Pass
6	3905.250	48.43	-5.93	80.8	-32.37	Peak	330.00	150	Horizontal	Pass

A.6 Transmitter Time

Test Data and Plot

The active time is less than 1 seconds

Active time



ANNEX B TEST SETUP PHOTOS

Please refer the document “BL-SZ1880507-AR.PDF”.

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document “BL-SZ1880507-AW.PDF”.

ANNEX D EUT INTERNAL PHOTOS

Please refer the document “BL-SZ1880507-AI.PDF”.

--END OF REPORT--