

Dates of Tests: June 28 ~ August 31, 2017

Test Report S/N: LR500111805K

Test Site : LTA CO., LTD.

CERTIFICATION OF COMPLIANCE

FCC ID

2AQLLENB501

APPLICANT

Enosis Co.,Ltd

Equipment Class : Part 15 Spread Spectrum Transmitter (DSS)
Manufacturing Description : Headset device
Manufacturer : Enosis Co.,Ltd
Model name : ENB-501
Variant Model name : INPA-500, ENH-505, ENH-606, EBH-700, EBH-800, Bon-500
Test Device Serial No.: : Identical prototype
Rule Part(s) : FCC Part 15.247 Subpart C; ANSI C-63.4-2014 / ANSI C-63.10-2013
Frequency Range : 2402 ~ 2480 MHz
RF power : Max 2.87 dBm – Conducted
Data of issue : August 31, 2017

This test report is issued under the authority of:



Yong-Cheol, Wang, Manager

The test was supervised by:



Hee-Cheon, Kwon / Test Engineer

This test result only responds to the tested sample. It is not allowed to copy this report even partly without the allowance of the test laboratory. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.



NVLAP LAB Code.: 200723-0

TABLE OF CONTENTS

1. GENERAL INFORMATION	3
2. INFORMATION ABOUT TEST ITEM	4
3. TEST REPORT	5
3.1 SUMMARY OF TESTS	5
3.2 FREQUENCY HOPPING SYSTEM REQUIREMENTS	6
3.3 TECHNICAL CHARACTERISTICS TEST	8
3.3.1 CARRIER FREQUENCY SEPARATION	8
3.3.2 NUMBER OF HOPPING FREQUENCIES	10
3.3.3 20 dB BANDWIDTH	12
3.3.4 TIME OF OCCUPANCY (Dwell Time)	16
3.3.5 TRANSMITTER OUTPUT POWER	18
3.3.6 BAND EDGE	21
3.3.7 CONDUCTED SPURIOUS EMISSIONS	25
3.3.8 RADIATED SPURIOUS EMISSIONS	28
APPENDIX	
APPENDIX TEST EQUIPMENT USED FOR TESTS	43

1. General information

1-1 Test Performed

Company name	: LTA Co., Ltd.
Address	: 243, Jubug-ri, Yangji-Myeon, Youngin-Si, Kyunggi-Do, Korea. 449-822
Web site	: http://www.ltalab.com
E-mail	: chahn@ltalab.com
Telephone	: +82-31-323-6008
Facsimile	: +82-31-323-6010

Quality control in the testing laboratory is implemented as per ISO/IEC 17025 which is the “General requirements for the competents of calibration and testing laboratory”.

1-2 Accredited agencies

LTA Co., Ltd. is approved to perform EMC testing by the following agencies:

Agency	Country	Accreditation No.	Validity	Reference
NVLAP	U.S.A	200723-0	2018-09-30	ECT accredited Lab.
RRA	KOREA	KR0049	-	EMC accredited Lab.
FCC	U.S.A	649054	2019-04-13	FCC CAB
VCCI	JAPAN	C-4948,	2020-09-10	VCCI registration
VCCI	JAPAN	T-2416,	2020-09-10	VCCI registration
VCCI	JAPAN	R-4483(10 m),	2020-10-15	VCCI registration
VCCI	JAPAN	G-847	2018-12-13	VCCI registration
IC	CANADA	5799A-1	2019-11-07	IC filing
KOLAS	KOREA	NO.551	2021-08-20	KOLAS accredited Lab.

2. Information about test item

2-1 Client & Manufacturer

Company name : Enosis Co.,Ltd
 Address : 177-9, Oksan-ro, Wonmi-gu, Bucheon-si, Gyeonggi-do, 14532, Korea
 Telephone / Facsimile : +82-70-4369-5968 / +82-70-4369-5969

2-2 Equipment Under Test (EUT)

Model name : ENB-501
 Variant Model name : INPA-500, ENH-505, ENH-606, EBH-700, EBH-800, Bon-500
 Serial number : Identical prototype
 Date of receipt : June 28, 2017
 EUT condition : Pre-production, not damaged
 Antenna type : Chip Antenna with Max Gain: 1.05 dBi
 Frequency Range : 2402~2480 MHz
 RF output power : Max. 2.87 dBm – Conducted
 Number of Channels : 79
 Channel Spacing : 1 MHz
 Channel Access Protocol : Frequency Hopping Spread Spectrum (FHSS)
 Type of Modulation : $\pi/4$ DQPSK, 8DPSK
 Power Source : DC 3.7 V by Battery
 Firmware Version : V 1.0.0

2-3 Tested frequency

Bluetooth	LOW	MID	HIGH
Frequency (MHz)	2402	2441	2480

2-4 Ancillary Equipment

Equipment	Model No.	Serial No.	Manufacturer
Notebook	CR720	MS-1736	MSI

3. Test Report

3.1 Summary of tests

FCC Part Section(s)	Parameter	Limit	Test Condition	Status (note 1)
15.247(a)	Carrier Frequency Separation	$\geq 2/3$ of 20 dB BW	Conducted	C
15.247(a)	Number of Hopping Frequencies	≥ 15 channels		C
15.247(a)	20 dB Bandwidth 99% Bandwidth	–		C
15.247(a)	Dwell Time	≤ 0.4 seconds		C
15.247(b)	Transmitter Output Power	≤ 1 W for 1Mbps ≤ 125 mW for 2,3 Mbps		C
15.247(d)	Conducted Spurious emission	> 20 dBc		C
15.247(d)	Band Edge	> 20 dBc		C
15.249 / 15.209	Field Strength of Harmonics	< 54 dBuV (at 3m)	Radiated	C
15.109	Field Strength	–		C
15.207 / 15.107	AC Conducted Emissions	EN 55022	Line Conducted	N/A
15.203	Antenna requirement	–	–	C

Note 1: C=Complies NC=Not Complies NT=Not Tested NA=Not Applicable

Note 2: The data in this test report are traceable to the national or international standards.

Note 1: Antenna Requirement

→ The **Enosis Co.,Ltd** FCC ID: **2AQLLENB501** unit complies with the requirement of §15.203.

The antenna type is Chip antenna.

The sample was tested according to the following specification:

*FCC Parts 15.247; ANSI C-63.4-2014;ANSI C-63.10-2013

*FCC KDB Publication No. 558074 D01 v03r05

*FCC TCB Workshop 2012, April

3.2 Frequency Hopping System Requirements

3.2.1 Standard Applicable

According to FCC Part 15.247(a)(1), The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

(g) Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.


(h) The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

3.2.2 EUT Pseudorandom Frequency Hopping Sequence


The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage, and the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONES; i.e. the shift register is initialized with nine ones. Number of shift register stages: 9

Length of pseudo-random sequence: $2^9 - 1 = 511$ bits

Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence



Each frequency used equally on the average by each transmitter.

The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

3.2.3 Frequency Hopping System

This transmitter device is frequency hopping device, and complies with FCC part 15.247 rule.

This device uses Bluetooth radio which operates in 2400-2483.5 MHz band. Bluetooth uses a radio technology called frequency-hopping spread spectrum, which chops up the data being sent and transmits chunks of it on up to 79 bands (1 MHz each; centred from 2402 to 2480 MHz) in the range 2,400-2,483.5 MHz. The transmitter switches hop frequencies 1,600 times per second to assure a high degree of data security. All Bluetooth devices participating in a given piconet are synchronized to the frequency-hopping channel for the piconet. The frequency hopping sequence is determined by the master's device address and the phase of the hopping sequence (the frequency to hop at a specific time) is determined by the master's internal clock. Therefore, all slaves in a piconet must know the master's device address and must synchronize their clocks with the master's clock.

Adaptive Frequency Hopping (AFH) was introduced in the Bluetooth specification to provide an effective way for a Bluetooth radio to counteract normal interference. AFH identifies "bad" channels, where either other wireless devices are interfering with the Bluetooth signal or the Bluetooth signal is interfering with another device. The AFH-enabled Bluetooth device will then communicate with other devices within its piconet to share details of any identified bad channels. The devices will then switch to alternative available "good" channels, away from the areas of interference, thus having no impact on the bandwidth used.

*Example for a Bluetooth device using channel numbers would be : Chan 44, 35, 78, 03, 15, 21, 76, 40, 56, 13, 02, 19, 67, 39, 78, 20, 21, 64, 75 etc.

3.3 TECHNICAL CHARACTERISTIC TEST

3.3.1 Carrier Frequency Separation

Procedure:

The test follows DA00-705. The carrier frequency separation was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

After the trace being stable, the reading value between the peaks of the adjacent channels using the marker-delta function was recorded as the measurement results.

The spectrum analyzer is set to:

Span = 3 MHz (wide enough to capture the peaks of two adjacent channels)

RBW = 100 kHz (1% of the span or more) Sweep = auto

VBW = 100 kHz Detector function = peak

Trace = max hold

Measurement Data:

Test Results	
Carrier Frequency Separation (MHz)	Result
1.0029	Complies

- See next pages for actual measured spectrum plots.

Minimum Standard:

The EUT shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or two-thirds of 20 dB bandwidth of the hopping channel, whichever is greater.

Measurement Setup





Figure 1: Measurement setup for the carrier frequency separation

Carrier Frequency Separation
EDR Mode



3.3.2 Number of Hopping Frequencies

Procedure:

The test follows DA00-705. The number of hopping frequencies was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

To get higher resolution, four frequency ranges within the 2400 ~ 2483.5 MHz FH band were examined.

The spectrum analyzer is set to (Bluetooth):

Frequency range Start = 2400.0 MHz, Stop = 2483.5 MHz

RBW = 100 kHz (1% of the span or more) Sweep = auto

VBW = 100 kHz (VBW \geq RBW) Detector function = peak

Trace = max hold Span > 40 MHz

Measurement Data : **Complies**

Total number of Hopping Channels	79
---	----

- See next pages for actual measured spectrum plots.


Minimum Standard:

At least 15 channels

Measurement Setup

Same as the Chapter 3.3.1 (Figure 1)

Number of Hopping Frequencies



3.3.3 20 dB Bandwidth

Procedure:

The bandwidth at 20 dB below the highest inband spectral density was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels..

After the trace being stable, Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission.

The spectrum analyzer is set to (Bluetooth):

Center frequency = the highest, middle and the lowest channels

Span = 3 MHz (approximately 2 or 3 times of the 20 dB bandwidth)

RBW = 30 kHz

Sweep = auto

VBW = 30 kHz (VBW \geq RBW)

Detector function = peak

Trace = max hold

Measurement Data: EDR Mode

Frequency (MHz)	Channel No.	Test Results(MHz)	
		20 dB Bandwidth	99 % Bandwidth
2402	0	1.346	1.172
2441	39	1.263	1.185
2480	78	1.259	1.185

- See next pages for actual measured spectrum plots.


Minimum Standard:

N/A

Measurement Setup

Same as the Chapter 3.3.1 (Figure 1)


EDR mode Low
20 dB Bandwidth




99% Bandwidth



EDR mode High
20 dB Bandwidth



99% Bandwidth



3.3.4 Time of Occupancy (Dwell Time)

Procedure:

The test follows DA00-705. The dwell time was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

The spectrum analyzer is set to :

Center frequency = 2441 MHz

Span = zero

RBW = 1 MHz

VBW = 1 MHz (VBW \geq RBW)

Trace = max hold

Detector function = peak

Measurement Data (Bluetooth):

Mode	Number of transmission in a 31.6s (79Hopping*0.4)	Length of Transmission Time (msec)	Result (msec)	Limit (msec)
EDR	10(Times / 3sec) *10.533 = 105.33	2.9855	314.46	400

- See next pages for actual measured spectrum plots.
- dwell time = {(number of hopping per second / number of slot) x duration time per channel} x 0.4 ms



Minimum Standard:

0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed

Measurement Setup

Same as the Chapter 3.3.1 (Figure 1)

EDR mode



3.3.5 Transmitter Output Power

Procedure:

The test follows DA00-705. The peak output power was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels..

After the trace being stable, Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power.

The spectrum analyzer is set to :

Center frequency = the highest, middle and the lowest channels

Span = 10 MHz (approximately 5 times of the 20 dB bandwidth)

RBW = 3 MHz (greater than the 20 dB bandwidth of the emission being measured)

VBW = 3 MHz (VBW \geq RBW)

Detector function = peak

Trace = max hold

Sweep = auto

Measurement Data : EDR Mode

Frequency (MHz)	Ch.	Test Results		
		dBm	mW	Result
2402	0	1.56	1.43	Complies
2441	39	2.63	1.83	Complies
2480	78	2.87	1.94	Complies


- See next pages for actual measured spectrum plots.

Minimum Standard:	For frequency hopping systems with at least 75 non-overlapping hopping channels: 1 watt. For all other frequency hopping systems: 0.125W.
--------------------------	---


Measurement Setup

Same as the Chapter 3.3.1 (Figure 1)


Low Channel
EDR mode



Middle Channel
EDR mode



High Channel EDR mode



3.3.6 Band Edge

Procedure:

The bandwidth at 20 dB down from the highest inband spectral density is measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels.

After the trace being stable, Use the marker-to-peak function to measure 20 dB down both sides of the intentional emission.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

RBW = 100 kHz

VBW = 100 kHz

Span = 10~30 MHz

Detector function = peak

Trace = max hold

Sweep = auto

Measurement Data: **Complies**

- All conducted emission in any 100 kHz bandwidth outside of the spread spectrum band was at least 20 dB lower than the highest inband spectral density. Therefore the applying equipment meets the requirement.
- See next pages for actual measured spectrum plots.


Minimum Standard:	> 20 dBc
--------------------------	----------

Measurement Setup


Same as the Chapter 3.3.1 (Figure 1)

Band Edge

Lower edge




Upper edge




Band Edge- Hopping

Lower edge



Upper edge



Radiated Band-edges in the restricted band 2310-2390 MHz measurement

Frequency [MHz]	Reading [dBuV/m]		Pol.	Correction Factor		Limits [dBuV/m]		Result [dBuV/m]		Margin [dB]	
	AV / Peak			Antenna	Amp. Gain + Cable Loss	AV / Peak		AV / Peak		AV / Peak	
2389.6	32.8	44.9	V	27.86	22.92	54.0	74.0	37.74	49.84	16.26	24.16

Radiated Band-edges in the restricted band 2483.5-2500 MHz measurement

Frequency [MHz]	Reading [dBuV/m]		Pol.	Correction Factor		Limits [dBuV/m]		Result [dBuV/m]		Margin [dB]	
	AV / Peak			Antenna	Amp. Gain + Cable Loss	AV / Peak		AV / Peak		AV / Peak	
2483.6	45.1	58.7	V	27.86	22.92	54.0	74.0	50.04	63.64	3.96	10.36

Note : This EUT was tested in 3 orthogonal positions and the worst-case data was presented.

3.3.7 Conducted Spurious Emissions

Procedure:

The test follows DA00-705. The conducted spurious emissions were measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels..

After the trace being stable, set the marker on the peak of any spurious emission recorded.

The spectrum analyzer is set to:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions

RBW = 100 kHz

Sweep = auto

VBW = 100 kHz

Detector function = peak

Trace = max hold

Measurement Data: **Complies**


- All conducted emission in any 100 kHz bandwidth outside of the spread spectrum band was at least 20 dB lower than the highest inband spectral density. Therefore the applying equipment meets the requirement.
- See next pages for actual measured spectrum plots.

Minimum Standard:	> 20 dBc
--------------------------	----------


Measurement Setup

Same as the Chapter 3.3.1 (Figure 1)


Unwanted Emission – Low channel
Frequency Range = 30 MHz ~ 26.5 GHz



Unwanted Emission – Middle channel
Frequency Range = 30 MHz ~ 26.5 GHz



Unwanted Emission – High channel
Frequency Range = 30 MHz ~ 26.5 GHz



3.3.8 Radiated Spurious Emissions

Procedure:

Radiated emissions from the EUT were measured according to the dictates of DA00-705. The EUT was placed on a 0.8m high wooden table inside a shielded enclosure. An antenna was placed near the EUT and measurements of frequencies and amplitudes of field strengths were recorded for reference during final measurements. For final radiated testing, measurements were performed in OATS. Measurements were performed with the EUT oriented in 3 orthogonal axis and rotated 360 degrees to determine worst-case orientation for maximum emissions.

- (a) In the frequency range of 9 kHz to 30 MHz, magnetic field is measured with Loop Test Antenna. The Test Antenna is positioned with its plane vertical at 3m distance from the EUT. The center of the Loop Test Antenna is 1m above the ground. During the measurement the Loop Test Antenna rotates about its vertical axis for maximum response at each azimuth about the EUT.
- (b) In the frequency range above 30 MHz, Bi-Log Test Antenna (30 MHz to 1 GHz) and Horn Test Antenna (above 1 GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is carried from 1m to 4m above the ground to determine the maximum value of the field strength. The emission levels at both horizontal and vertical polarizations should be tested.

The spectrum analyzer is set to:

Center frequency = the worst channel

Frequency Range = 9 kHz ~ 10th harmonic.

RBW = 120 kHz (30 MHz ~ 1 GHz)

= 1 MHz (1 GHz ~ 10th harmonic)

Span = 100 MHz


Trace = max hold

VBW \geq RBW


Detector function = peak

Sweep = auto


below 30 MHz



below 1 GHz (30 MHz to 1 GHz)



above 1 GHz



Measurement Data: **Complies**

- See next pages for actual measured data.
- No other emissions were detected at a level greater than 20 dB below limit include from 9 kHz to 30 MHz.

Minimum Standard: FCC Part 15.209(a)

Frequency (MHz)	Limit (uV/m) @ 3 m
0.009 ~ 0.490	2400/F(kHz) (@ 300 m)
0.490 ~ 1.705	24000/F(kHz) (@ 30 m)
1.705 ~ 30	30(@ 30 m)
30 ~ 88	100 **
88 ~ 216	150 **
216 ~ 960	200 **
Above 960	500

** Except as provided in 15.209(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.

Measurement Data :

Frequency	Reading [dBuV/m]		Pol.	Correction Factor	Limits [dBuV/m]		Result [dBuV/m]		Margin [dB]	
10484.23	21.16	33.27	V	26.57	54.0	74.0	47.73	59.84	6.27	14.16
10393.71	21.08	33.02	V	26.44	54.0	74.0	47.52	59.46	6.48	14.54
8969.16	20.94	32.90	H	26.76	54.0	74.0	46.70	58.66	7.30	15.34
-	-	-	-	-	-	-	-	-	-	-
Frequency	Reading [dBuV/m]		Pol.	Correction Factor	Limits [dBuV/m]		Result [dBuV/m]		Margin [dB]	
10606.15	21.52	31.23	H	26.85	54.0	74.0	48.37	58.08	5.63	15.92
10484.23	21.68	32.23	V	26.57	54.0	74.0	48.25	58.80	5.75	15.20
10760.54	20.87	31.19	H	27.22	54.0	74.0	48.09	58.41	5.91	15.59
-	-	-	-	-	-	-	-	-	-	-
Frequency	Reading [dBuV/m]		Pol.	Correction Factor	Limits [dBuV/m]		Result [dBuV/m]		Margin [dB]	
7541.11	20.35	31.25	V	26.04	54.0	74.0	46.39	57.29	7.61	16.71
9021.16	20.22	25.92	H	25.92	54.0	74.0	46.14	56.35	7.86	17.65
9126.06	20.27	30.43	H	25.80	54.0	74.0	46.07	56.23	7.93	17.77
-	-	-	-	-	-	-	-	-	-	-

- No other emissions were detected at a level greater than 20 dB below limit.

Radiated Emissions(below 1 GHz) – EDR mode (LOW)




4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com

EUT/Model No.: ENB-501 Temp/Humi: 22 / 42

Test Mode : BT EDR_L Tested by: KWON H C

Data: 2260 File: C:\Program Files (x86)\e3\1804-1.EM6 (2261)



Freq	Reading	C.F	Result	Limit	Margin	Height	Angle	Polarity
MHz	dBuV	dB	QP dBuV/m	dBuV/m	dB	cm	deg	
37.76	34.49	-14.43	20.06	40.00	19.94	205	79	HORIZONTAL
907.85	23.69	1.15	24.84	46.00	21.16	265	85	HORIZONTAL
945.68	22.25	2.36	24.61	46.00	21.39	201	68	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain




4, Songjuro 236Beon-gil, yanggi-myeon,
 Yongin-si, Gyeonggi-do, Korea
 Tel : +82-31-3236008,9
 Fax : +82-31-3236010
 www.ltalab.com

EUT/Model No.: ENB-501 Temp/Humi: 22 / 42

 Test Mode : BT EDR_L Tested by: KWON H C

Data: 2260 File: C:\Program Files (x86)\e3\1804-1.EM6 (2261)



Freq	Reading	C.F	Result	Limit	Margin	Height	Angle	Polarity
MHz	dBuV	dB	QP dBuV/m	dBuV/m	dB	cm	deg	
37.76	45.19	-14.43	30.76	40.00	9.24	172	215	VERTICAL
41.64	35.75	-14.09	21.66	40.00	18.34	117	205	VERTICAL
500.45	33.92	-6.62	27.30	46.00	18.70	168	203	VERTICAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain


Radiated Emissions(below 1 GHz) – EDR mode (MID)



4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com

EUT/Model No.: ENB-501 Temp/Humi: 22 / 42
Test Mode : BT EDR_M Tested by: KWON H C

Data: 2264 File: C:\Program Files (x86)\e3\1804-1.EM6 (2265)




Freq MHz	Reading dBuV	C.F dB	Result QP dBuV/m	Limit dBuV/m	Margin dB	Height cm	Angle deg	Polarity
37.76	39.38	-14.43	24.95	40.00	15.05	137	240	HORIZONTAL
907.85	24.39	1.15	25.54	46.00	20.46	200	210	HORIZONTAL
945.68	28.30	2.36	30.66	46.00	15.34	215	207	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain



4, Songjuro 236Beon-gil, yanggi-myeon,
 Yongin-si, Gyeonggi-do, Korea
 Tel : +82-31-3236008,9
 Fax : +82-31-3236010
 www.ltalab.com

EUT/Model No.: ENB-501 Temp/Humi: 22 / 42
 Test Mode : BT EDR_M Tested by: KWON H C



Freq MHz	Reading dBuV	C.F dB	Result QP dBuV/m	Limit dBuV/m	Margin dB	Height cm	Angle deg	Polarity
37.76	46.25	-14.43	31.82	40.00	8.18	100	360	VERTICAL
41.64	38.75	-14.09	24.66	40.00	15.34	100	360	VERTICAL
500.45	36.93	-6.62	30.31	46.00	15.69	100	360	VERTICAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

Radiated Emissions(below 1 GHz) – Bluetooth mode (HIGH)




4, Songjuro 236Beon-gil, yanggi-myeon,
 Yongin-si, Gyeonggi-do, Korea
 Tel : +82-31-3236008,9
 Fax : +82-31-3236010
 www.ltalab.com

EUT/Model No.: ENB-501 Temp/Humi: 22 / 42

 Test Mode : BT EDR_H Tested by: KWON H C

Data: 2268 File: C:\Program Files (x86)\e3\1804-1.EM6 (2269)



Freq	Reading	C.F	Result	Limit	Margin	Height	Angle	Polarity
MHz	dBuV	dB	QP dBuV/m	dBuV/m	dB	cm	deg	
876.81	24.27	0.14	24.41	46.00	21.59	380	117	HORIZONTAL
879.72	25.40	0.19	25.59	46.00	20.41	390	270	HORIZONTAL
881.66	26.57	0.21	26.78	46.00	19.22	370	300	HORIZONTAL


Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain



4, Songjuro 236Beon-gil, yanggi-myeon,
 Yongin-si, Gyeonggi-do, Korea
 Tel : +82-31-3236008,9
 Fax : +82-31-3236010
 www.ltalab.com

EUT/Model No.: ENB-501 Temp/Humi: 22 / 42
 Test Mode : BT EDR_H Tested by: KWON H C

Data: 2269 File: C:\Program Files (x86)\e3\1804-1.EM6 (2269) Date: 2018-04-30



Freq MHz	Reading dBuV	C.F dB	Result QP dBuV/m	Limit dBuV/m	Margin dB	Height cm	Angle deg	Polarity
846.74	30.14	-0.27	29.87	46.00	16.13	105	130	VERTICAL
879.72	27.60	0.19	27.79	46.00	18.21	100	200	VERTICAL
888.45	27.34	0.32	27.66	46.00	18.34	100	260	VERTICAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain


Radiated Emission(Above 1 GHz) – EDR mode (LOW)



EMI Chamber of LTA CO.,LTD.
 4, Songjuro236Beon-gil, Yangji-myeon,
 Yongin-si, Gyeonggi-do, Korea Autho.by NVLAP
 Tel :+82-31-3236008,9 www.ltalab.com
 Fax:+82-31-3236010

EUT/Model No. : ENB-501 Test Mode: EDR (low) mode
 Tested by : KWON H C Temp/Humi : 23 / 54

Data: 271 File: D:\LTA_e3\e3_backup\1GHz 이상\2017\CH1_ABOVE 1GHz_1706-1.EMI (271) Date: 2017-07-03 Time: 09:10:24
 Level (dBuV/m)



Freq	Reading	C.F	Result	Limit	Margin	Polarity	
MHz	dBuV	dB	PK dBuV/m	dBuV/m	dB		
1	4804.30	45.60	15.53	61.13	74.00	12.87	HORIZONTAL
2	4804.30	31.20	15.53	46.73	54.00	7.27	HORIZONTAL
3	7497.65	32.80	26.17	58.97	74.00	15.03	HORIZONTAL
4	7497.65	20.70	26.17	46.87	54.00	7.13	HORIZONTAL
5	7584.83	32.82	25.87	58.69	74.00	15.31	VERTICAL
6	7584.83	20.83	25.87	46.70	54.00	7.30	VERTICAL
7	8969.16	32.90	25.76	58.66	74.00	15.34	HORIZONTAL
8	8969.16	20.94	25.76	46.70	54.00	7.30	HORIZONTAL
9	10393.71	33.02	26.44	59.46	74.00	14.54	VERTICAL
10	10393.71	21.08	26.44	47.52	54.00	6.48	VERTICAL
11	10484.23	33.27	26.57	59.84	74.00	14.16	VERTICAL
12	10484.23	21.16	26.57	47.73	54.00	6.27	VERTICAL


Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
 Blue : Vertical Black : Horizontal



EMI Chamber of LTA CO.,LTD.
 4, Songjuro236Beon-gil, Yangji-myeon,
 Yongin-si, Gyeonggi-do, Korea Autho.by NVLAP
 Tel :+82-31-3236008,9 www.ltalab.com
 Fax:+82-31-3236010

EUT/Model No. : ENB-501 Test Mode: EDR (low) mode
 Tested by : KWON H C Temp/Humi : 23 / 54

Data: 279 File: D:\LTA_e3\3_backup\1GHz 이상\2017\CH1_ABOVE 1GHz_1706-1.EMI (279)
 Level (dBuV/m) Date: 2017-07-03 Time: 10:03:36



Freq	Reading	C.F	Result	Limit	Margin	Polarity
MHz	dBuV	dB	PK dBuV/m	dBuV/m	dB	
118245.40	36.77	24.62	61.39	74.00	12.61	HORIZONTAL
218245.40	21.58	24.62	46.20	54.00	7.80	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
 Blue : Vertical Black : Horizontal


Radiated Emission(Above 1 GHz) – EDR mode (MID)



EMI Chamber of LTA CO.,LTD.
 4, Songjuro23Beon-gil, Yangji-myeon,
 Yongin-si, Gyeonggi-do, Korea Autho.by NVLAP
 Tel :+82-31-3236008,9 www.ltalab.com
 Fax:+82-31-3236010

EUT/Model No.: ENB-501 Test Mode: EDR(mid) mode
 Tested by : KWON H C Temp/Humi: 23 / 54

Data: 272 File: D:\LTA_e3\e3_backup\1GHz 이상\2017\CH1_ABOVE 1GHz_1706-1.EMI (272) Date: 2017-07-03 Time: 09:22:38
 Level (dBuV/m)



Freq	Reading	C.F	Result	Limit	Margin	Polarity
MHz	dBuV	dB	PK dBuV/m	dBuV/m	dB	
1 4884.70	43.25	15.86	59.11	74.00	14.89	HORIZONTAL
2 4884.70	31.18	15.86	47.04	54.00	6.96	HORIZONTAL
3 7497.65	31.54	26.17	57.71	74.00	16.29	VERTICAL
4 7497.65	21.58	26.17	47.75	54.00	6.25	VERTICAL
5 7673.03	32.24	25.54	57.78	74.00	16.22	HORIZONTAL
6 7673.03	21.66	25.54	47.20	54.00	6.80	HORIZONTAL
710484.23	32.23	26.57	58.80	74.00	15.20	VERTICAL
810484.23	21.68	26.57	48.25	54.00	5.75	VERTICAL
910606.15	31.23	26.85	58.08	74.00	15.92	HORIZONTAL
1010606.15	21.52	26.85	48.37	54.00	5.63	HORIZONTAL
1110760.54	31.19	27.22	58.41	74.00	15.59	HORIZONTAL
1210760.54	20.87	27.22	48.09	54.00	5.91	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
 Blue : Vertical Black : Horizontal



EMI Chamber of LTA CO.,LTD.
 4, Songjuro236Beon-gil, Yangji-myeon,
 Yongin-si, Gyeonggi-do, Korea Autho by NVLAP
 Tel :+82-31-3236008,9 www.ltalab.com
 Fax:+82-31-3236010

EUT/Model No.: ENB-501 Test Mode: EDR (mid) mode
 Tested by : KWON H C Temp/Humi: 23 / 54

Data: 280 File: D:\LTA_e3\3_backup\1GHz 이상\2017\CH1_ABOVE 1GHz_1706-1.EMI (280) Date: 2017-07-03 Time: 10:05:26
 Level (dBuV/m)



Freq	Reading	C.F	Result	Limit	Margin	Polarity
MHz	dBuV	dB	PK dBuV/m	dBuV/m	dB	
118448.29	35.72	24.96	60.68	74.00	13.32	HORIZONTAL
218448.29	21.65	24.96	46.61	54.00	7.39	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
 Blue : Vertical Black : Horizontal


Radiated Emission(Above 1 GHz) – Bluetooth mode (HIGH)



EMI Chamber of LTA CO.,LTD.
 4, Songjuro236Beon-gil, Yangji-myeon,
 Yongin-si, Gyeonggi-do, Korea Autho.by NVLAP
 Tel :+82-31-3236008,9 www.ltalab.com
 Fax:+82-31-3236010

EUT/Model No. : ENB-501 Test Mode: EDR (high) mode
 Tested by : KWON H C Temp/Humi : 23 / 54

Data: 273 File: D:\LTA_e3\e3_backup\1GHz 이상\2017\CH1_ABOVE 1GHz_1706-1.EMI (273) Date: 2017-07-03 Time: 09:31:10
 Level (dBuV/m)



Freq	Reading	C.F	Result	Limit	Margin	Polarity	
MHz	dBuV	dB	PK dBuV/m	dBuV/m	dB		
1	4960.37	40.28	16.16	56.44	74.00	17.56	HORIZONTAL
2	4960.37	28.70	16.16	44.86	54.00	9.14	HORIZONTAL
3	7284.04	32.38	23.98	56.36	74.00	17.64	VERTICAL
4	7284.04	20.19	23.98	44.17	54.00	9.83	VERTICAL
5	7541.11	31.25	26.04	57.29	74.00	16.71	VERTICAL
6	7541.11	20.35	26.04	46.39	54.00	7.61	VERTICAL
7	7673.03	30.94	25.54	56.48	74.00	17.52	HORIZONTAL
8	7673.03	20.27	25.54	45.81	54.00	8.19	HORIZONTAL
9	9021.16	30.43	25.92	56.35	74.00	17.65	HORIZONTAL
10	9021.16	20.22	25.92	46.14	54.00	7.86	HORIZONTAL
11	9126.06	30.43	25.80	56.23	74.00	17.77	HORIZONTAL
12	9126.06	20.27	25.80	46.07	54.00	7.93	HORIZONTAL


Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
 Blue : Vertical Black : Horizontal



EMI Chamber of LTA CO.,LTD.
 4, Songjuro236Beon-gil, Yangji-myeon,
 Yongin-si, Gyeonggi-do, Korea Autho.by NVLAP
 Tel :+82-31-3236008,9 www.ltalab.com
 Fax:+82-31-3236010

EUT/Model No. : ENB-501 Test Mode: EDR (high) mode
 Tested by : KWON H C Temp/Humi: 23 / 54

Data: 281 File: D:\LTA_e3\e3_backup\1GHz 이상\2017\CH1_ABOVE 1GHz_1706-1.EMI (281)
 Level (dBuV/m) Date: 2017-07-03 Time: 10:08:18



Freq	Reading	C.F	Result	Limit	Margin	Polarity
MHz	dBuV	dB	PK dBuV/m	dBuV/m	dB	
118450.74	36.05	24.96	61.01	74.00	12.99	HORIZONTAL
218450.74	22.03	24.96	46.99	54.00	7.01	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
 Blue : Vertical Black : Horizontal

APPENDIX

TEST EQUIPMENT USED FOR TESTS

	Use	Description	Model No.	Serial No.	Manufacturer	Interval	Last Cal. Date
1	■	Signal Analyzer (9 kHz ~ 30 GHz)	FSV30	100757	R&S	1 year	2016-10-11
2	■	Signal Generator (~3.2 GHz)	8648C	3623A02597	HP	1 year	2017-03-20
3		SYNTHESIZED CW GENERATOR	83711B	US34490456	HP	1 year	2017-03-20
4		Attenuator (3 dB)	8491A	37822	HP	1 year	2016-09-12
5		Attenuator (10 dB)	8491A	63196	HP	1 year	2016-09-12
6	■	EMI Test Receiver (~7 GHz)	ESC17	100722	R&S	1 year	2016-09-12
7	■	RF Amplifier (~1.3 GHz)	8447D OPT 010	2944A07684	HP	1 year	2016-09-12
8	■	RF Amplifier (1~26.5 GHz)	8449B	3008A02126	HP	1 year	2017-03-21
9	■	Horn Antenna (1~18 GHz)	3115	00114105	ETS	2 year	2016-08-04
10		DRG Horn (Small)	3116B	81109	ETS-Lindgren	2 year	2016-05-03
11	■	DRG Horn (Small)	3116B	133350	ETS-Lindgren	2 year	2016-05-03
12	■	TRILOG Antenna	VULB 9160	9160-3237	SCHWARZBECK	2 year	2015-07-13
13		Temp.Humidity Data Logger	SK-L200TH II A	00801	SATO	1 year	2017-03-21
14		Splitter (SMA)	ZFSC-2-2500	SF617800326	Mini-Circuits	-	-
15		Power Divider	11636A	06243	HP	1 year	2016-09-12
16	■	DC Power Supply	6674A	3637A01657	Agilent	-	-
17		Frequency Counter	5342A	2826A12411	HP	1 year	2017-03-21
18	■	Power Meter	EPM-441A	GB32481702	HP	1 year	2017-03-20
19	■	Power Sensor	8481A	3318A94972	HP	1 year	2016-12-30
20		Audio Analyzer	8903B	3729A18901	HP	1 year	2016-09-12
21		Modulation Analyzer	8901B	3749A05878	HP	1 year	2016-09-12
22		TEMP & HUMIDITY Chamber	YJ-500	LTAS06041	JinYoung Tech	1 year	2016-09-12
23		Stop Watch	HS-3	812Q08R	CASIO	2 year	2017-03-21
24		LISN	KNW-407	8-1430-1	Kyoritsu	1 year	2016-09-12
25		Two-Lime V-Network	ESH3-Z5	893045/017	R&S	1 year	2017-03-20
26		UNIVERSAL RADIO COMMUNICATION TESTER	CMU200	106243	R&S	1 year	2017-03-20
27		Highpass Filter	WHKX1.5/15G-10SS	74	Wainwright Instruments	1 year	2017-03-20
28		Highpass Filter	WHKX3.0/18G-10SS	118	Wainwright Instruments	1 year	2017-03-20
29	■	Loop Antenna	HFH2-Z2	1519-031	R&S	1 year	2017-02-27
30		OSP120 BASE UNIT	OSP120	101230	R&S	1 year	2017-03-21
31		Signal Generator(100 kHz ~ 40 GHz)	SMB100A03	177621	R&S	1 year	2017-03-23
32		Signal Analyzer (10 Hz ~ 40 GHz)	FSV40	101367	R&S	1 year	2017-03-21