

RF Exposure Requirements

Product Description:Bluetooth earphone

Model No.: BT-23,BT-10,BT-50,BT-90,EB-10,EB-50

FCC ID:2AQSX-BT-23

According to the KDB 447498 D01 v06 section 4.3.1, for 100 MHz to 6 GHz and test separation distances ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$$\left[\frac{\text{(max. power of channel, including tune-up tolerance, mW)}}{\text{(min. test separation distance, mm)}} \right] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz

- Power and distance are rounded to the nearest mW and mm before calculation¹⁷

- The result is rounded to one decimal place for comparison

Calculation Result:

Tx frequency range:2402MHz

Min. test separation distance: 5mm

Maximum Conducted Output Power:-1.3dBm(0.741mW)

Tune-Up output power: 0dBm(1mW)

RF channel transmit frequency:2402MHz

Result: 0.31

Limit: 3.0

Tx frequency range:2442MHz

Min. test separation distance: 5mm

Maximum Conducted Output Power:-0.61dBm(0.869 mW)

Tune-Up output power: 0dBm(1mW)

RF channel transmit frequency:2442MHz

Result: 0.31

Limit: 3.0

Tx frequency range:2480MHz

Min. test separation distance: 5mm

Maximum Conducted Output Power:-0.18dBm(0.959 mW)

Tune-Up output power: 0dBm(1mW)

RF channel transmit frequency:2480MHz

Result: 0.31

Limit: 3.0

The exclusion thresholds is $0.31 < 3$, so the transmitter complies with the RF exposure requirements and the SAR is not required.