

Test Report No.: 24032403-SE-US-01

RF Exposure Report

FCC ID: 2AR2STAX5509

Applicant: MMD Hong Kong Holding Limited

Address: Units 1208-11, 12th Floor, C-Bons International Center, 108 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong

Manufacturer: MMD Hong Kong Holding Limited

Address: Units 1208-11, 12th Floor, C-Bons International Center, 108 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong

Product: Party Speaker

Brand(s): PHILIPS or 

Test Model(s): TAX5509/37

Series Model(s): See section 1.1

Test Date: May. 20, 2024~ Jul. 13, 2024

Issued Date: Jul. 24, 2024

Issued By: Hwa-Hsing (Dongguan) Testing Co., Ltd.

Address: No.101, Building N1, Yuyuan 2 Road, Yuyuan Industrial Park, HuangJiang Town, Dongguan City, People's Republic of China


Test Firm Registration No.: 915896

Designation No.: CN1255


Standards: FCC Part 2 (Section 2.1091)
KDB 447498 D01
IEEE C95.1

The above equipment has been tested by **Hwa-Hsing (Dongguan) Testing Co., Ltd.**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :


Nature Lee

Reviewed by :


Dragon Long

Approved by :


Scott He

"This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. Our report includes all the tests requested by you and the results thereof based upon the information that you provided to us. The report would be invalid without specific stamp of test institute and the signatures of tester and approver."

Lab: [Hwa-Hsing \(Dongguan\) Testing Co., Ltd.](#)Address: [No.101, Building N1, Yuyuan 2 Road, Yuyuan Industrial Park, HuangJiang Town, Dongguan City, People's Republic of China](#)Tel: [0769-83078199](#)Web.: [www.hwa-hsing.com](#)E-Mail: [customerservice.dg@hwa-hsing.com](#)Release
Ver. 1.5

Table of contents

Release control record 3

1 General Information 4

1.1 General Description of EUT4

2 RF exposure limit..... 5

2.1 MPE calculation formula5

3 Calculation result of maximum conducted power..... 6

Appendix – Information on the Testing Laboratories.....7

Test Report No.: 24032403-SE-US-01

Release control record

Issue No.	Reason for change	Date issued
24032403-SE-US-01	Original Release	Jul. 24, 2024

Test Report No.: 24032403-SE-US-01

1 General Information**1.1 General Description of EUT**

Product	Party Speaker
Sample No.	HS2403240011-02
Test Model(s)	TAX5509/37
Series Model(s)	TAX5509, TAX5509/10, TAX5509/61, TAX5509/yy (yy are variable, yy = 00 to 99 or blank, stands for country code)
Status of EUT	Engineering Prototype
Power Supply Rating	AC 100~240V 50/60Hz
Modulation Type	FHSS, DTS
Transfer Rate	1 Mbps, 2Mbps, 3Mbps
Operating Frequency	2402 ~ 2480MHz
Number of Channel	EDR:79; BLE:40
Maximum Output Power	3.24dBm (Average)
Antenna Type	PIFA Antenna
Antenna Gain	2.29dBi Gain
Antenna Connector	I-PEX
Accessory Device	IR remote control
Data Cable Supplied	AC Cable: 150cm Non-shielded, Detachable

Note:

1. Please refer to the EUT photo document (Reference No.: 24032403-01&02) for detailed product photo.
2. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.
3. Model differences: These models are only different from model name for trade purpose.

Test Report No.: 24032403-SE-US-01

2 RF exposure limit

Limits for maximum permissible exposure (MPE)

Limits for general population / uncontrolled exposure				
Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Average time (minutes)
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30
Note: F = Frequency in MHz				

2.1 MPE calculation formula

$$Pd = (Pout * G) / (4 * \pi * r^2)$$

*Where:*Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Classification:

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user.

Test Report No.: 24032403-SE-US-01

3 Calculation result of maximum conducted power

The antennas provided to the EUT, please refer to the following table:

Function	Frequency (MHz)	Antenna Gain (dBi)	Antenna Type	Transmit and Receive Chain	Maximum AVG Power
BT	2402-2480	2.29	PIFA	1TX,1RX	3.24dBm

Frequency (MHz)	Max power (mW)	Antenna gain (dBi)	Distance (cm)	Power density (mW/cm ²)	Limit (mW/cm ²)
2402-2480	2.1086	2.29	20	0.000711	1.0

Conclusion:

Therefore, the worst-case situation is 0.000711 mW/cm², which is less than "1". This confirmed that the device compliance with FCC 1.1310 MPE limit.

Test Report No.: 24032403-SE-US-01

Appendix – Information on the Testing Laboratories

We, [Hwa-Hsing \(Dongguan\) Testing Co., Ltd.](#), A global provider of TESTING and CERTIFICATION services for consumer products, electronic products and wireless information technology products. Adhering to the core values “HONEST and TRUSTWORTHY, OBJECTIVE and IMPARTIALITY, RIGOROUS and AFFICIENT”, commitment to provide professional, perfect and efficient comprehensive ONE-STOP solution of TESTING and CERTIFICATION services for Manufacturers, Buyers, Traders, Brands, Retailers. Assist client to better manage risk, protect their brands, reduce costs and cut time to over 150 markets in global. Our laboratories are FCC recognized accredited test firms and accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lab Address: [No.101, Building N1, Yuyuan 2 Road, Yuyuan Industrial Park, HuangJiang Town, Dongguan City, People's Republic of China](#)

Contact Tel: [0769-83078199](#)

Email: Customerservice.dg@hwa-hsing.com

Web Site: www.hwa-hsing.com

--- END ---