



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0056077(3) Date : Oct 17, 2019

Application No. : LY024939(5)

Applicant : TWELVE SOUTH LLC
1503 KING ST., SUITE 201, CHARLESTON,
SOUTH CAROLINA, US 29405

Sample Description :

Sample Description	Model No.
Bluetooth Transmitter	AirFly Duo

Date Received : Sep 23, 2019

Test Period : Sep 24, 2019 to Oct 11, 2019

Test Requested : FCC Certification for FCC Part 15, subpart C
ISED Certification for License-exempt Device

Test Method : 47 CFR Part 15 (10-1-18 Edition),
ANSI C63.10 – 2013,
ANSI C63.4 – 2014
RSS-247 Issue 2,
RSS-Gen Issue 5,

Test Engineer : Mr. Leung Shu Kan, Ken

Conclusion : The submitted sample was found to comply with technical requirement of FCC
Part 15 Subpart C, section 15.247, and ISED Canada Radio Standards Specification
RSS-247 Issue 2.

For and on behalf of
CMA Industrial Development Foundation Limited

Authorized Signature : _____ Page 1 of 71

Mr. WONG Lap-pong, Andrew
Manager

FCC ID: 2AREB-AIRFLYDUO
IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0056077(3)

Date : Oct 17, 2019

RESULT SUMMARY

Test Item	FCC Requirement	RSS Requirement	Test Method	Result
Number of hopping frequency	§15.247(a)(1)(iii)	RSS-247 §5.1(d)	ANSI C63.10 §7.8.3	PASS
Band-edge	§15.247(d)	RSS-247 §5.5	ANSI C63.10 §7.8.6 and 6.10	PASS
Carrier frequency separation	§15.247(a)	RSS-247 §5.1(b)	ANSI C63.10 §7.8.2	PASS
Time of occupancy (dwell time)	§15.247(a)	RSS-247 §5.1(b)	ANSI C63.10 §7.8.4	PASS
Output power	§15.247(b)(1)	RSS-247 §5.4	ANSI C63.10 §7.8.5	PASS
Occupied bandwidth	§15.247(a)	RSS-247 §5.1(a)	ANSI C63.10 §7.8.7 and 6.9.2	PASS
Conducted spurious emission (Transmitter)	§15.247(d)	RSS-247 §5.5	ANSI C63.10 §7.8.8, and §11.12.2.1	PASS
Radiated spurious emission (Transmitter)	§15.247(d)	RSS-247 §5.5	ANSI C63.10 §6.4 – 6.6	PASS
Radiated spurious emission (Receiver)	§15.109(a)	RSS-Gen, §7.0	ANSI C63.4 §8.3	PASS
Conducted emission on AC mains	§15.207(a)	RSS-Gen, §8.8	ANSI C63.4 §7.3	PASS
Frequency Hopping System Requirement	§15.247(a)(1), (g), (h)	RSS-247 §5.1	N/A	PASS
Frequency Stability	N/A	RSS-Gen, §8.11	ANSI C63.10 §7.8.7 and 6.9.2	PASS

FCC ID: 2AREB-AIRFLYDUO
IC: 24385-AIRFLYDUO

Page 2 of 71

Document name: FCC/ISED for FHSS - Document Ref No: RT-EL-EMC-048 - Issue Date: 13 Mar 2019 - Edition: 2

This document is issued subject to the latest CMA Testing General Terms and Conditions of Testing and Inspection Services, available on request or accessible at website www.cmateesting.org.
This document shall not be reproduced except in full or with written approval by CMA Testing.

CMA Industrial Development Foundation Limited

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, N.T., Hong Kong.

Tel : (852) 2698 8198 Fax : (852) 2695 4177 E-mail : info@cmateesting.org Web Site : <http://www.cmateesting.org>



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0056077(3)

Date : Oct 17, 2019

Table of Contents

Table of Contents	3
1 Product Information	5
1.1 General Information.....	5
1.2 Technical Information.....	5
1.3 Associated Electric Accessories Information	6
1.4 Associated Cables	6
2.0 Equipment Units Tested (EUT).....	6
3.0 Location of Test Facility.....	6
4.0 List of test equipment, supporting equipment and cables.....	7
4.1 Test equipment.....	7
4.2 Supporting equipment.....	8
4.3 Cables.....	8
4.4 Software	8
5.0 Measurement Uncertainty.....	8
6.0 Measurement	9
6.1 General Test condition.....	9
6.2 Number of hopping frequency	9
6.2.1 Measurement	9
6.2.2 Final Result	9
6.3 Band-edge measurement	10
6.3.1 Measurement	10
6.3.2 Final Result	11
6.4 Carrier Frequency Separation	12
6.4.1 Measurement	12
6.4.2 Final Result	12
6.5 Time of occupancy (dwell time)	13
6.5.1 Measurement	13
6.5.2 Final Result	13
6.6 Output Power	14
6.6.1 Measurement	14
6.6.2 Final Result	14
6.7 Occupied Bandwidth and Frequency Stability.....	15
6.7.1 Measurement	15
6.7.2 Final Result	15
6.8 Conducted Spurious emission (Transmitter).....	16
6.8.1 Measurement	16
6.8.2 Final Result	16
6.9 Radiated Spurious emission (Transmitter).....	17
6.9.1 Measurement	17
FCC ID: 2AREB-AIRFLYDUO	
IC: 24385-AIRFLYDUO	



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0056077(3)

Date : Oct 17, 2019

6.9.2 Final Result	18
6.10 Radiated Spurious emission (Receiver)	19
6.10.1 Measurement	19
6.10.2 Final Result	20
6.11 Conducted Emission.....	21
6.11.1 Measurement	21
6.11.2 Final Result	21
7.0 Frequency Hopping System Requirement	22
8.0 External photo, Internal Photo and Test configuration Photo	24
APPENDIX A Test Result	A1

FCC ID: 2AREB-AIRFLYDUO
IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0056077(3)

Date : Oct 17, 2019

1 Product Information

1.1 General Information

Product Description:	Model:
Bluetooth Transmitter	AirFly Duo

Primary function	: Providing the basic Bluetooth transmitter function to transmit the audio signal from player without Bluetooth function.
Power supply	: DC 3.7V (Li-ion rechargeable) DC 5.0V (USB-Type C charging port)
RF related function	: Bluetooth communication
Electric Accessories sold with	: Nil
Interconnection cable associated sold with	: 26cm USB to USB Type-C cable
Operating condition	: Not specified
Model difference	: Not applicable
Remark	: Nil

1.2 Technical Information

Operating Frequency	: 2402 – 2480 MHz
Digital Modulation	: FHSS
Modulation	: GFSK, $\pi/4$ DQPSK, 8DPSK
Number of Channel	: 79
Channel Bandwidth	: 1.0MHz
Occupied Bandwidth	: 1.25MHz
Signal Type	: Data
Number of Antenna	: One
Antenna Type	: Chip type antenna
Antenna Gain	: 2.5dBi
Rated Input Voltage	: DC 3.7V (Li-ion rechargeable battery) DC 5.0V (USB-Type C charging port)
RF Technology Used	: Bluetooth 5.0+EDR (Non BLE)
Simplex or Duplex	: Half-duplex
Adaptivity	: FHSS adaptivity

FCC ID: 2AREB-AIRFLYDUO
IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0056077(3)

Date : Oct 17, 2019

1.3 Associated Electric Accessories Information

N/A

1.4 Associated Cables

Cable Type	Length	Shielding	Ferrite attached
USB to USB Type C cable	26cm	Yes	No

2.0 Equipment Units Tested (EUT)

Product Description : Bluetooth Transmitter
Model : AirFly Duo
PMN : AirFly Duo
HVIN : AirFly Duo
FVIN : N/A
HMN : N/A
Serial No. : Not labelled
Sample Type : Pre-production type
Sample No. : RY047200-003(5)
Rationale of selection : One single model

3.0 Location of Test Facility

CMA Industrial Development Foundation Ltd.
Room 1302, Yan Hing Centre,
9-13 Wong Chuk Yeung,
Fo Tan, Shatin,
New Territories
Hong Kong.

FCC Accredited Lab (Designation Number: HK0004)
ISED Wireless Test Site (ISED Assigned Code: 4093A)

FCC ID: 2AREB-AIRFLYDUO
IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0056077(3)

Date : Oct 17, 2019

4.0 List of test equipment, supporting equipment and cables

4.1 Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Calibration Due Date	Calibration Period
EMI Test Receiver	Rohde & Schwarz	ESCS30	100001	29 Mar 2020	1Year
Spectrum Analyzer	R&S	FSV40	100964	07 Feb 2020	1Year
Spectrum Analyzer	Rohde & Schwarz	FSP30	100628	26 Mar 2020	1Year
Broadband Antenna	Schaffner	CBL6112B	2692	27 Mar 2021	2Years
Loop Antenna	EMCO	6502	00056620	25 Jan 2020	2Years
Horn Antenna	Schwarzbeck	BBHA 9120D	9120D-531	21 Dec 2020	2Years
Broadband Pre-Amplifier	Schwarzbeck	BBV 9718	9718-119	21 Dec 2020	2Years
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170442	01 Aug 2020	2Years
Broadband Pre-Amplifier	Schwarzbeck	BBV 9719	9719-010	01 Aug 2020	2Years
Coaxial Cable	Schaffner	RG 213/U	N/A	16 May 2020	1Year
Coaxial Cable	Suhner	RG 214/U	N/A	16 May 2020	1Year
Coaxial Cable	Suhner	Sucoflex_104	N/A	21 Dec 2019	1Year
LISN	Rohde & Schwarz	ENV216	101323	22 Jan 2020	1Year
Coaxial Cable	Tyco Electronics	RG 58C/U	N/A	23 Oct 2019	1Year
Rohde & Schwarz TS8997 Testing System					
Spectrum Analyzer	Rohde & Schwarz	FSV 40	101190	05 Dec 2019	1Year
OSP	Rohde & Schwarz	OSP	OSP120 V02	24 Apr 2020	1Year

FCC ID: 2AREB-AIRFLYDUO
IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0056077(3)

Date : Oct 17, 2019

4.2 Supporting equipment

Equipment Name	Manufacturer	Model	Serial	Provided by
CSR USB-SPI Adaptor*	CSR	USB-SPI	Not labelled	Applicant
USB Charger	Apple	A1299	Not labelled	CMA
iPod 8GB	Apple	A1285	YM9312JE2ME	CMA

Remark: *only used for configure engineering mode

4.3 Cables

Nil

4.4 Software

Software Name	Version	Function	Provided by
CSR Bluesuite BlueTest3*	V2.6.8	Control the engineering mode of the device	Applicant

Remark: *only used for configure engineering mode

5.0 Measurement Uncertainty

The reported uncertainty is based on a standard uncertainty multiplied by a coverage factor $k=2$, providing a level of confidence of approximately 95%.

Radiated emissions

Frequency	Uncertainty (U_{lab})
30MHz ~ 200MHz (Horizontal)	4.59dB
30MHz ~ 200MHz (Vertical)	4.49dB
200MHz ~ 1000MHz (Horizontal)	4.94dB
200MHz ~ 1000MHz (Vertical)	4.97dB
1GHz ~ 6GHz	4.52dB
6GHz ~ 18GHz	4.58dB
18GHz ~ 40GHz	4.66dB

Line-conducted emissions

Frequency	Uncertainty (U_{lab})
150kHz~30MHz	2.80dB

FCC ID: 2AREB-AIRFLYDUO
IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0056077(3)

Date : Oct 17, 2019

6.0 Measurement

6.1 General Test condition

Temperature : 27.0 °C
Test Voltage : DC3.7V and AC 120V
Humidity : 49.3%
Atmosphere Pressure : 101.0kPa

6.2 Number of hopping frequency

6.2.1 Measurement

Requirement : FCC Part 15 § 15.247(a)(1)(iii) and RSS-247 §5.1(d)
Measuring procedure : ANSI C63.10:2013, clause 7.8.3
Span : 83.5MHz
RBW : 300kHz
VBW : 300kHz
Frequency range : 2.4000 – 2.4835GHz
Modulation tested : GFSK
Packet Type tested : DH5
Additional measuring procedure : Nil

6.2.2 Final Result

No. of hopping channels measured	Limit	Result	Worst case mode
79	≥ 15	PASS	GFSK and DH5

Remark: Detail test result and equipment setting refer to appendix A, A4

FCC ID: 2AREB-AIRFLYDUO
IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0056077(3)

Date : Oct 17, 2019

6.3 Band-edge measurement

6.3.1 Measurement

- | | |
|-------------------------------------|--|
| Requirement | : FCC Part 15 §15.247(d) and RSS-247 §5.5 |
| Measuring procedure | : ANSI C63.10:2013, section 7.8.6 and 6.10 |
| Hopping mode | : Enabled and Disable |
| RBW | : 100kHz |
| VBW | : 300kHz |
| Frequency range | : 2310 – 2400MHz and 2483.5 – 2500MHz |
| Modulation tested | : GFSK, $\pi/4$ DQPSK, 8DPSK |
| Packet Type tested | : DH5, 2DH5, 3DH5 |
| Channel tested for non-hopping mode | : 2402MHz for lowed band edge and 2480MHz for higher band edge |
| Additional measuring procedure | : For lower band edge (2400MHz) <ol style="list-style-type: none">1. Using the “Measurement 1” setting shown below the scan plot within the frequency span from 2400 – 2483.5MHz to measure the maximum peak value of fundamental2. Using the “Measurement 2” setting shown below the scan plot within the frequency span from 2310 – 2400MHz to measure the bandedge reading3. Compare that reading in procedure with the limit which equal to the measured maximum peak in procedure 1 minus 20dB For Upper bandedge (2483.5MHz) <ol style="list-style-type: none">1. Using the “Measurement 1” setting shown below the scan plot within the frequency span from 2400 – 2483.5MHz to measure the maximum peak value of fundamental2. Using the “Measurement 2” setting shown below the scan plot within the frequency span from 2483.5 – 2500MHz to measure the bandedge reading3. Compare that reading in procedure with the limit which equal to the measured maximum peak in procedure 1 minus 20dB |

FCC ID: 2AREB-AIRFLYDUO
IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0056077(3)

Date : Oct 17, 2019

6.3.2 Final Result

Banded frequency for lower bandedge (Worst Case)	Worst case (dBc) ²	Detector	Limit ¹ (dBc)	Result	Worst case
2399.975000	37.2	Peak	≥ 20.0	PASS	GFSK DH5
Banded frequency for higher bandedge (Worst Case)	Worst case in (dBc) ²	Detector	Limit ¹	Result	Worst case
2483.525000	50.4	Peak	≥ 20.0	PASS	GFSK DH5

Remark: 1) The limit is based on the transmitter demonstrated compliance with peak conducted power limit on section 6.4.2 of this report.

2) The Worst case dBc is the peak values measured in procedure 1 minus the worst case bandedge emission

3) Detail test result and equipment setting refer to appendix A, A32-39

FCC ID: 2AREB-AIRFLYDUO
IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0056077(3)

Date : Oct 17, 2019

6.4 Carrier Frequency Separation

6.4.1 Measurement

Requirement	: FCC Part 15 §15.247(a) and RSS-247 §5.1(b)
Measuring procedure	: ANSI C63.10:2013, section 7.8.2
Hopping mode	: Enabled
RBW	: 300kHz
VBW	: 300kHz
Frequency range	: 2401-2404MHz, 2440-2442MHz, 2478-2481MHz
Modulation tested	: GFSK ²
Packet Type tested	: DH5 ²
Additional measuring procedure	: Nil
Remark	: 1) Since the measured value is more than 1.5 times of limit, only middle channel is measured. 2) Since the modulation and packet type does not affect the channel separation, GFSK and DH5 are selected as represented modulation and data type

6.4.2 Final Result

Carrier Frequency Separation	Limit ¹	Result	Worst case mode
1.009900	0.866667	PASS	GFSK and DH5

Remark: 1) Limit is 2/3 of the 20dB bandwidth in section 6.7 and conducted peak power is less than 0.125W in section 6.6 of this report.

2) Detail test result and equipment setting refer to appendix A, A29-31

FCC ID: 2AREB-AIRFLYDUO
IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0056077(3)

Date : Oct 17, 2019

6.5 Time of occupancy (dwell time)

6.5.1 Measurement

Requirement : FCC Part 15 §15.247(a) and RSS-247 §5.1(a)
Measuring procedure : ANSI C63.10:2013, section 7.8.4
Hopping mode : Disable
RBW : 500kHz
VBW : 1MHz
Modulation tested : GFSK³
Packet Type tested : DH1, DH3, DH5
Channel tested for non-hopping mode : 2441MHz
Additional measuring procedure : 1) Setup engineering sample to channel 2441MHz and DH1 packet size to perform the measurement according to ANSI C63.10, section 7.8.4
2) Find the worst case packet size
3) Repeat procedure1 with the worst case packet size for channel 2402MHz and 2480MHz
Remark : 1) Since the modulation does not affect the dwell time, GFSK is selected as represented modulation.

6.5.2 Final Result

Dwell time (worst case)	Limit	Result	Worst case mode
309.150ms	≤400ms	PASS	GFSK and DH5

Remark: 1) Detail test result and equipment setting refer to appendix A, A5-7

FCC ID: 2AREB-AIRFLYDUO
IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0056077(3)

Date : Oct 17, 2019

6.6 Output Power

6.6.1 Measurement

Requirement : FCC Part 15 §15.247(b) (1) and RSS-247 §5.4
 Measuring procedure : ANSI C63.10:2013, section 7.8.5
 Hopping mode : Disable
 Modulation tested : GFSK, $\pi/4$ DQPSK, 8DPSK
 Packet Type tested : DH5¹
 Channel tested for non-hopping mode : 2402MHz, 2441MHz, 2480MHz
 Additional measuring procedure : Nil
 Remark : 1) Since the packet size does not affect the output power, DH5 is selected as represented packet size.

6.6.2 Final Result

(a) Maximum peak conducted output power

Maximum peak conducted output power	Limit(s) ¹	Result	Modulation
0.7dBm	≤ 21.0 dBm	PASS	GFSK
0.7dBm	≤ 21.0 dBm	PASS	$\pi/4$ DQPSK
0.7dBm	≤ 21.0 dBm	PASS	8DPSK

Remark: 1) 0.125W (21.0dBm) limit is used for 2/3 20dB bandwidth requirement for channel separation.

2) Detail test result and equipment setting refer to appendix A, A15, A24, A31

(b) Maximum peak e.i.r.p.(for RSS-247)

Maximum peak e.i.r.p. ¹	Limit(s) ²	Result	Modulation
3.2dBm	≤ 27.0 dBm	PASS	GFSK
3.2dBm	≤ 27.0 dBm	PASS	$\pi/4$ DQPSK
3.2dBm	≤ 27.0 dBm	PASS	8DPSK

Remark: 1) Maximum peak e.i.r.p. = Maximum peak conducted output power + antenna gain (dBi)

2) Maximum peak e.i.r.p. limit = Maximum peak conducted output power limit + 6dBi

3) Detail test result and equipment setting refer to appendix A, A8-10

FCC ID: 2AREB-AIRFLYDUO
 IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0056077(3)

Date : Oct 17, 2019

6.7 Occupied Bandwidth and Frequency Stability

6.7.1 Measurement

Requirement : FCC Part 15 §15.247(a) and RSS-247 §5.1(a)
Measuring procedure : ANSI C63.10:2013, section 7.8.7 and 6.9.2
Hopping mode : Disable
Modulation tested : GFSK, $\pi/4$ DQPSK, 8DPSK
Packet Type tested : DH5¹
Channel tested for non-hopping mode : 2402MHz, 2441MHz, 2480MHz
Additional measuring procedure : Nil
Remark : 1) Since the packet size does not affect the bandwidth, DH5 is selected as represented packet size.

6.7.2 Final Result

20dB bandwidth	99% OBW	Modulation
0.930MHz	0.865MHz	GFSK
1.300MHz	1.250MHz	$\pi/4$ DQPSK
1.300MHz	1.230MHz	8DPSK

Remark: 1) 99% occupied bandwidths fall in the frequency band 2402 – 2480MHz, so it comply the bandwidth and frequency stability requirement in FCC Part 15 and RSS-Gen.
2) Detail test result and equipment setting refer to appendix A, A11-28

FCC ID: 2AREB-AIRFLYDUO
IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0056077(3)

Date : Oct 17, 2019

6.8 Conducted Spurious emission (Transmitter)

6.8.1 Measurement

Requirement	: FCC Part 15 §15.247(d) and RSS-247 §5.5
Measuring procedure	: ANSI C63.10:2013, section 5.5, 5.6, 7.8.8 and 11.12.2.1
Hopping mode	: Disable
RBW	: Refer to pre-measurement and final measurement setting
Detector	: Refer to pre-measurement and final measurement setting
Modulation tested	: GFSK ¹
Packet Type tested	: DH5 ²
Channel tested for non-hopping mode	: 2402MHz, 2441MHz, 2480MHz
Additional measuring procedure	: 1) Setup engineering sample to channel 2402MHz to perform the measurement according to ANSI C63.10, section 7.8.8 with pre-measurement setting 2) If the pre-measurement is over the limit, the final measurement is performed for the specific frequency according to final measurement setting or restricted band frequency 3) For non-restricted band frequency, peak detector and 100kHz RBW will be used for final measurement. 4) Repeat the procedure 1 to 3 for channel frequency of 2441MHz and 2480MHz
Remark	: 1) Since the GFSK generates a higher SPD with power level, GFSK is selected as represented modulation for testing. 2) Since DH5 generates a higher dwell time, DH5 is selected as representative packet size for testing

6.8.2 Final Result

Worst case spurious emission frequency	Worst case spurious emission power ¹	Limit ²	Margin	Result	Worst case mode
2399.225000	-44.8dBm	-20.7dBm	-24.1dB	PASS	GFSK and DH5

Remark: 1) Spurious emission power = measured conducted power + antenna gain(dBi) + ground reflection factor according to ANSI C63.10 section 11.12.2.2 for restricted band emission.

2) For restricted band emission, limit = restricted band field strength limit (dBuV/m) + 4.7dB – 104.8dB according to ANSI C63.10 section 11.12.2.2 For non-restricted band, limit = SPD/100kHz – 20dB.

3) Detail test result and equipment setting refer to appendix A, A40-45

FCC ID: 2AREB-AIRFLYDUO
IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0056077(3)

Date : Oct 17, 2019

6.9 Radiated Spurious emission (Transmitter)

6.9.1 Measurement

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 0.4m and 0.8m high above the ground for below 1GHz measurement and 1.5m high above the ground for above 1GHz measurement. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

For below 30MHz, a loop antenna with its vertical plane is placed 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1 m above the ground.

For 30MHz to 300MHz, biconical antenna with its vertical and horizontal plane is placed 3m from the EUT and rotated about its vertical and horizontal axis for maximum response at each azimuth about the EUT. And the reference point of antenna shall be 1 m above the ground. Same procedure for frequency 300MHz to 1000MHz but Log-periodic antenna is used for final measurements.

For above 1GHz, horn antenna with its vertical and horizontal plane is placed 3m from the EUT and rotated about its vertical and horizontal axis for maximum response at each azimuth about the EUT. Preamplifier and High Pass filter was used for measurements. The reference point of antenna shall be 1 m above the ground.

The device was rotated through three X, Y, Z orthogonal to determine which attitude and configuration produce the highest emission during measurement for Radiated Emission measurement.

The Frequencies from fundamental up to the tenth harmonics were investigated, and emissions more 20dB below limit were not reported.

Bluetooth hopping + charging mode with GFSK modulation and DH5packet type are selected as worst case mode for spurious radiated emission test from cabinet.

FCC ID: 2AREB-AIRFLYDUO
IC: 24385-AIRFLYDUO

Page 17 of 71

Document name: FCC/ISED for FHSS - Document Ref No: RT-EL-EMC-048 - Issue Date: 13 Mar 2019 - Edition: 2

This document is issued subject to the latest CMA Testing General Terms and Conditions of Testing and Inspection Services, available on request or accessible at website www.cmateesting.org.
This document shall not be reproduced except in full or with written approval by CMA Testing.

CMA Industrial Development Foundation Limited
Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, N.T., Hong Kong.
Tel : (852) 2698 8198 Fax : (852) 2695 4177 E-mail : info@cmateesting.org Web Site : <http://www.cmateesting.org>



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0056077(3)

Date : Oct 17, 2019

6.9.2 Final Result

a) Test mode: Bluetooth + Charging

Polarization	Frequency (MHz)	Reading at 3m (dBμV)	Transducer Factor (dB/m)	Field Strength at 3m ¹ (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)	Detector (PK/QP/AV)
H	2400.000	63.1	-4.7	58.4	74.0	-15.6	PK
H	2400.000	54.4	-4.7	49.7	54.0	-4.3	AV
H	2483.500	59.1	-4.7	54.4	74.0	-19.6	PK
H	2483.500	53.9	-4.7	49.2	54.0	-4.8	AV
V	4803.662	52.8	2.3	55.1	74.0	-18.9	PK
V	4804.046	48.9	2.3	51.2	54.0	-2.8	AV
V	4881.718	47.7	2.3	50.0	54.0	-4.0	PK
H	4960.044	41.9	2.8	44.7	54.0	-9.3	PK
H	7206.493	44.1	9.6	53.7	54.0	-0.3	PK
H	7322.532	44.5	9.6	54.1	74.0	-19.9	PK
H	7322.880	37.1	9.6	46.7	54.0	-7.3	AV
V	7439.702	44.6	9.6	54.2	74.0	-19.8	PK
V	7439.852	37.6	9.6	47.2	54.0	-6.8	AV

- Remark: 1) Field Strength = Reading + transducer factor.
2) Other emission with more than 20dB margin are not reported in this report
3) The peak data emissions above 1GHz are compared with average limit except 2400.000MHz, 2483.500MHz, 4803.662MHz, 7322.532MHz and 7439.702MHz.

FCC ID: 2AREB-AIRFLYDUO
IC: 24385-AIRFLYDUO

Page 18 of 71

Document name: FCC/ISED for FHSS - Document Ref No: RT-EL-EMC-048 - Issue Date: 13 Mar 2019 - Edition: 2

This document is issued subject to the latest CMA Testing General Terms and Conditions of Testing and Inspection Services, available on request or accessible at website www.cmateesting.org.
This document shall not be reproduced except in full or with written approval by CMA Testing.

CMA Industrial Development Foundation Limited
Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, N.T., Hong Kong.
Tel : (852) 2698 8198 Fax : (852) 2695 4177 E-mail : info@cmateesting.org Web Site : <http://www.cmateesting.org>



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0056077(3)

Date : Oct 17, 2019

6.10 Radiated Spurious emission (Receiver)

6.10.1 Measurement

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 0.4m and 0.8m high above the ground for below 1GHz measurement and 1.5m high above the ground for above 1GHz measurement. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

For below 30MHz, a loop antenna with its vertical plane is placed 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1 m above the ground.

For 30MHz to 300MHz, biconical antenna with its vertical and horizontal plane is placed 3m from the EUT and rotated about its vertical and horizontal axis for maximum response at each azimuth about the EUT. And the reference point of antenna shall be 1 m above the ground. Same procedure for frequency 300MHz to 1000MHz but Log-periodic antenna is used for final measurements.

For above 1GHz, horn antenna with its vertical and horizontal plane is placed 3m from the EUT and rotated about its vertical and horizontal axis for maximum response at each azimuth about the EUT. Preamplifier and High Pass filter was used for measurements. The reference point of antenna shall be 1 m above the ground.

The device was rotated through three X, Y, Z orthogonal to determine which attitude and configuration produce the highest emission during measurement for Radiated Emission measurement.

The Frequencies from fundamental up to the tenth harmonics were investigated, and emissions more 20dB below limit were not reported.

Bluetooth receiving mode are selected for spurious radiated emission test from cabinet.

FCC ID: 2AREB-AIRFLYDUO
IC: 24385-AIRFLYDUO

Page 19 of 71

Document name: FCC/ISED for FHSS - Document Ref No: RT-EL-EMC-048 - Issue Date: 13 Mar 2019 - Edition: 2

This document is issued subject to the latest CMA Testing General Terms and Conditions of Testing and Inspection Services, available on request or accessible at website www.cmateesting.org.
This document shall not be reproduced except in full or with written approval by CMA Testing.

CMA Industrial Development Foundation Limited

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, N.T., Hong Kong.

Tel : (852) 2698 8198 Fax : (852) 2695 4177 E-mail : info@cmateesting.org Web Site : <http://www.cmateesting.org>



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0056077(3)

Date : Oct 17, 2019

6.10.2 Final Result

Test mode: Receiving mode

Polarization	Frequency (MHz)	Reading at 3m (dBμV)	Transducer Factor (dB/m)	Field Strength at 3m ¹ (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)	Detector (PK/QP/AV)
H	73.979	12.7	9.8	22.5	40.0	-17.5	QP
V	107.397	15.9	11.2	27.1	43.5	-16.4	QP
H	137.033	15.1	12.6	27.7	43.5	-15.8	QP
V	172.315	12.9	14.2	27.1	43.5	-16.4	QP
H	220.366	12.1	14.5	26.6	46.0	-19.4	QP
V	1060.359	48.5	-9.8	38.7	54.0	-15.3	PK
H	1084.320	54.0	-9.8	44.2	54.0	-9.8	PK
V	1267.242	45.9	-8.2	37.7	54.0	-16.3	PK

- Remark: 1) Field Strength = Reading + transducer factor.
2) Other emission with more than 20dB margin are not reported in this report.
3) The peak data emissions above 1GHz are compared with average limit

FCC ID: 2AREB-AIRFLYDUO
IC: 24385-AIRFLYDUO

Page 20 of 71

Document name: FCC/ISED for FHSS - Document Ref No: RT-EL-EMC-048 - Issue Date: 13 Mar 2019 - Edition: 2

This document is issued subject to the latest CMA Testing General Terms and Conditions of Testing and Inspection Services, available on request or accessible at website www.cmateesting.org.
This document shall not be reproduced except in full or with written approval by CMA Testing.

CMA Industrial Development Foundation Limited

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, N.T., Hong Kong.

Tel : (852) 2698 8198 Fax : (852) 2695 4177 E-mail : info@cmateesting.org Web Site : <http://www.cmateesting.org>



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0056077(3)

Date : Oct 17, 2019

6.11 Conducted Emission

6.11.1 Measurement

Requirement : FCC Part 15 §15.207(a) and RSS-Gen, clause 8.8
Measuring procedure : ANSI C63.4:2014, section 7.3
Test mode : Bluetooth + charging
RBW : 9kHz
VBW : 30kHz
Modulation tested : GFSK
Packet Type tested : DH5
Additional measuring procedure : Nil
Remark : Nil

6.11.2 Final Result

Worst case conducted emission frequency	Worst case conducted emission	Limit	Margin	Detector	Lines	Worst case mode	Result
17.8880MHz	42.62dBμV	60.00dBμV	-17.38dB	QP	L1	Charging	PASS

Remark: 1) Detail test result and equipment setting refer to appendix A, A46-47

FCC ID: 2AREB-AIRFLYDUO
IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0056077(3)

Date : Oct 17, 2019

7.0 Frequency Hopping System Requirement

Test Requirement: Section 15.247(a)(1), (g), (h) and RSS-247, section 5.1 requirement

The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom order list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.


Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmissions bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hop sets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

Compliance for section 15.247(a)(1) and RSS-247 section 5.1(a)

According to Bluetooth Core Specification, the pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONES; i.e. the shift register is initialized with nine ones.

- Number of shift register stage: 9
- Length of pseudorandom sequence: $2^9-1=511$ bits
- Longest sequence of zero: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

FCC ID: 2AREB-AIRFLYDUO
IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories


廠商會檢定中心

TEST REPORT

Report No. : AY0056077(3)

Date : Oct 17, 2019

An example of Pseudorandom Frequency Hopping Sequence as following:



Each frequency used equally on the average by each transmitter.

According to Bluetooth Core Specification, Bluetooth receivers are designed to have input and IF bandwidths that match the hopping channel bandwidths of any Bluetooth transmitters and shift frequencies in synchronization with the transmitted signals.

Compliance for section 15.247(g) and RSS-247 section 5.1 2nd paragraph

According to Bluetooth Core Specification, the Bluetooth system transmits the packet with the pseudorandom hopping frequency with a continuous data and the short burst transmission from the Bluetooth system is also transmitted under the frequency hopping system with the pseudorandom hopping frequency system.

Compliance for section 15.247(h) and RSS-247 section 5.1 3rd paragraph

According to Bluetooth Core specification, the Bluetooth system incorporates with an adaptive system to detect other user within the spectrum band so that it individually and independently to avoid hopping on the occupied channels.

According to the Bluetooth Core specification, the Bluetooth system is designed not have the ability to coordinate with other FHSS System in effort to avoid the simultaneous occupancy of the individual hopping frequencies by multiple transmitter.

FCC ID: 2AREB-AIRFLYDUO
IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0056077(3)

Date : Oct 17, 2019

8.0 External photo, Internal Photo and Test configuration Photo

The External Photo, Internal Photo and Test Configuration Photo associated with this report for the tested product are saved in separated pdf file listed in the following

File content	File name
External Photo	2AREB-AIRFLYDUO_24385-AIRFLYRDUO External Photo.pdf
Internal Photo	2AREB-AIRFLYDUO_24385-AIRFLYRDUO Internal Photo.pdf
Test Configuration Photo	2AREB-AIRFLYDUO_24385-AIRFLYRDUO Test Setup photo.pdf

FCC ID: 2AREB-AIRFLYDUO
IC: 24385-AIRFLYDUO

Page 24 of 71

Document name: FCC/ISED for FHSS - Document Ref No: RT-EL-EMC-048 - Issue Date: 13 Mar 2019 - Edition: 2

This document is issued subject to the latest CMA Testing General Terms and Conditions of Testing and Inspection Services, available on request or accessible at website www.cmateesting.org.
This document shall not be reproduced except in full or with written approval by CMA Testing.

CMA Industrial Development Foundation Limited
Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, N.T., Hong Kong.
Tel : (852) 2698 8198 Fax : (852) 2695 4177 E-mail : info@cmateesting.org Web Site : <http://www.cmateesting.org>



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0056077(3)

Date : Oct 17, 2019

APPENDIX A Test Result

FCC ID: 2AREB-AIRFLYDUO
IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0056077(3)

Date : Oct 17, 2019

DUT Information

Frequencies

BT CH 0 (2402 MHz)	BT CH 1 (2403 MHz)	BT CH 2 (2404 MHz)
BT CH 3 (2405 MHz)	BT CH 4 (2406 MHz)	BT CH 5 (2407 MHz)
BT CH 6 (2408 MHz)	BT CH 7 (2409 MHz)	BT CH 8 (2410 MHz)
BT CH 9 (2411 MHz)	BT CH 10 (2412 MHz)	BT CH 11 (2413 MHz)
BT CH 12 (2414 MHz)	BT CH 13 (2415 MHz)	BT CH 14 (2416 MHz)
BT CH 15 (2417 MHz)	BT CH 16 (2418 MHz)	BT CH 17 (2419 MHz)
BT CH 18 (2420 MHz)	BT CH 19 (2421 MHz)	BT CH 20 (2422 MHz)
BT CH 21 (2423 MHz)	BT CH 22 (2424 MHz)	BT CH 23 (2425 MHz)
BT CH 24 (2426 MHz)	BT CH 25 (2427 MHz)	BT CH 26 (2428 MHz)
BT CH 27 (2429 MHz)	BT CH 28 (2430 MHz)	BT CH 29 (2431 MHz)
BT CH 30 (2432 MHz)	BT CH 31 (2433 MHz)	BT CH 32 (2434 MHz)
BT CH 33 (2435 MHz)	BT CH 34 (2436 MHz)	BT CH 35 (2437 MHz)
BT CH 36 (2438 MHz)	BT CH 37 (2439 MHz)	BT CH 38 (2440 MHz)
BT CH 39 (2441 MHz)	BT CH 40 (2442 MHz)	BT CH 41 (2443 MHz)
BT CH 42 (2444 MHz)	BT CH 43 (2445 MHz)	BT CH 44 (2446 MHz)
BT CH 45 (2447 MHz)	BT CH 46 (2448 MHz)	BT CH 47 (2449 MHz)
BT CH 48 (2450 MHz)	BT CH 49 (2451 MHz)	BT CH 50 (2452 MHz)
BT CH 51 (2453 MHz)	BT CH 52 (2454 MHz)	BT CH 53 (2455 MHz)
BT CH 54 (2456 MHz)	BT CH 55 (2457 MHz)	BT CH 56 (2458 MHz)
BT CH 57 (2459 MHz)	BT CH 58 (2460 MHz)	BT CH 59 (2461 MHz)
BT CH 60 (2462 MHz)	BT CH 61 (2463 MHz)	BT CH 62 (2464 MHz)
BT CH 63 (2465 MHz)	BT CH 64 (2466 MHz)	BT CH 65 (2467 MHz)
BT CH 66 (2468 MHz)	BT CH 67 (2469 MHz)	BT CH 68 (2470 MHz)
BT CH 69 (2471 MHz)	BT CH 70 (2472 MHz)	BT CH 71 (2473 MHz)
BT CH 72 (2474 MHz)	BT CH 73 (2475 MHz)	BT CH 74 (2476 MHz)
BT CH 75 (2477 MHz)	BT CH 76 (2478 MHz)	BT CH 77 (2479 MHz)
BT CH 78 (2480 MHz)		

FCC ID: 2AREB-AIRFLYDUO
IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0056077(3)

Date : Oct 17, 2019

Hardware Setup: WMS Measurements\TS8997

Spectrum Analyzer: SA FSV 40 (SA FSV 40) @ VISA (ADR
TCPIP::192.168.48.148::inst0::instr), SN 1321.3008K39/101190,
FW 2.30 SP4

Vector Generator: VG SMBV100A (VG SMBV100A) @ VISA (ADR
TCPIP::192.168.48.149::inst0::instr), SN 262024, FW 3.1.19.8-
3.20.281.28.7

Generator: SMB100A (SMB100A) @ VISA (ADR
TCPIP::192.168.48.152::inst0::instr), SN 103230, FW 3.20.390.24
/ Drv:Rev 2.21.0, 07/2016, CVI 2015

OSP: OSP-B157W (OSP-B157W) @ VISA (ADR
TCPIP::192.168.48.157::inst0::instr), SN 1527.1144.03 / 101057,
FW 1.23.0.2

FCC ID: 2AREB-AIRFLYDUO
IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AY0056077(3)

Date : Oct 17, 2019

Hopping Frequencies (Hopping; GFSK; DH5)

Channels

Channels	Limit Min	Limit Max	Result
79	15	---	PASS



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40000 GHz	2.40000 GHz
Stop Frequency	2.48350 GHz	2.48350 GHz
Span	83.500 MHz	83.500 MHz
RBW	200.000 kHz	≤ 299.000 kHz
VBW	200.000 kHz	≥ 200.000 kHz
SweepPoints	418	~ 418
SweepTime	1.060 ms	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	AUTO
Preamplifier	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	64 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.46 dB	0.50 dB

FCC ID: 2AREB-AIRFLYDUO

IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AY0056077(3)

Date : Oct 17, 2019

Time of Channel Occupancy (2441 MHz; GFSK; DH1)

Result

DUT Frequency (MHz)	Result	Number of Hops	Average time of occupancy (ms)	Threshold (dBm)
2441.000000	PASS	319	132.080	-20.0



Trace Threshold

Measurement

Setting	Instrument Value	Target Value
Center Frequency	2.44100 GHz	2.44100 GHz
Span	ZeroSpan	ZeroSpan
RBW	500.000 kHz	~ 500.000 kHz
VBW	1.000 MHz	~ 1.500 MHz
SweepPoints	30001	~ 30001
SweepTime	31.600 s	31.600 s
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	0.000 dB	0.000 dB
Detector	MaxPeak	MaxPeak
SweepCount	1	1
Filter	Channel	Channel
Trace Mode	Clear Write	Clear Write
SweepType	Sweep	AUTO
Preamp	off	off
Trigger	External	External
Trigger Offset	0.000 s	0.000 s

OSP

Setting	Instrument Value	Target Value
Measurement Time	31.600 s	31.600 s
Tracepoints	31600000	31600000
Time resolution	1.000 μ s	1.000 μ s
Detector	RMS	RMS

FCC ID: 2AREB-AIRFLYDUO

IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心


TEST REPORT

Report No. : AY0056077(3)

Date : Oct 17, 2019

Time of Channel Occupancy(2) (2441 MHz; GFSK; DH3) Result

DUT Frequency (MHz)	Result	Number of Hops	Average time of occupancy (ms)	Threshold (dBm)
2441.000000	PASS	159	266.990	-20.0



Measurement

Setting	Instrument Value	Target Value
Center Frequency	2.44100 GHz	2.44100 GHz
Span	ZeroSpan	ZeroSpan
RBW	500.000 kHz	~ 500.000 kHz
VBW	1.000 MHz	~ 1.500 MHz
SweepPoints	30001	~ 30001
SweepTime	31.600 s	31.600 s
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	0.000 dB	0.000 dB
Detector	MaxPeak	MaxPeak
SweepCount	1	1
Filter	Channel	Channel
Trace Mode	Clear Write	Clear Write
SweepType	Sweep	AUTO
Preamp	off	off
Trigger	External	External
Trigger Offset	0.000 s	0.000 s

OSP

Setting	Instrument Value	Target Value
Measurement Time	31.600 s	31.600 s
Tracepoints	31600000	31600000
Time resolution	1.000 μ s	1.000 μ s
Detector	RMS	RMS

FCC ID: 2AREB-AIRFLYDUO
IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心


TEST REPORT

Report No. : AY0056077(3)

Date : Oct 17, 2019

Time of Channel Occupancy(3) (2441 MHz; GFSK; DH5) Result

DUT Frequency (MHz)	Result	Number of Hops	Average time of occupancy (ms)	Threshold (dBm)
2441.000000	PASS	105	309.150	-20.0



Measurement

Setting	Instrument Value	Target Value
Center Frequency	2.44100 GHz	2.44100 GHz
Span	ZeroSpan	ZeroSpan
RBW	500.000 kHz	~ 500.000 kHz
VBW	1.000 MHz	~ 1.500 MHz
SweepPoints	30001	~ 30001
SweepTime	31.600 s	31.600 s
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	0.000 dB	0.000 dB
Detector	MaxPeak	MaxPeak
SweepCount	1	1
Filter	Channel	Channel
Trace Mode	Clear Write	Clear Write
SweepType	Sweep	AUTO
Preamp	off	off
Trigger	External	External
Trigger Offset	0.000 s	0.000 s

OSP

Setting	Instrument Value	Target Value
Measurement Time	31.600 s	31.600 s
Tracepoints	31600000	31600000
Time resolution	1.000 μ s	1.000 μ s
Detector	RMS	RMS

FCC ID: 2AREB-AIRFLYDUO
IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AY0056077(3)

Date : Oct 17, 2019

RF output power (2402 MHz; GFSK; DH5)

Result

DUT Frequency (MHz)	Gated RMS (dBm)	Limit Max (dBm)	Gated EIRP (dBm)	DutyCycle (%)	Result
2402.000000	-2.7	21.0	-0.2	77.586	PASS



— Gated Trace — Overall — Limit

FCC ID: 2AREB-AIRFLYDUO
IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AY0056077(3)

Date : Oct 17, 2019

RF output power (2441 MHz; GFSK; DH5)

Result

DUT Frequency (MHz)	Gated RMS (dBm)	Limit Max (dBm)	Gated EIRP (dBm)	DutyCycle (%)	Result
2441.000000	-1.6	21.0	0.9	77.594	PASS



— Gated Trace — Overall — Limit

FCC ID: 2AREB-AIRFLYDUO
IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AY0056077(3)

Date : Oct 17, 2019

RF output power (2480 MHz; GFSK; DH5)

Result

DUT Frequency (MHz)	Gated RMS (dBm)	Limit Max (dBm)	Gated EIRP (dBm)	DutyCycle (%)	Result
2480.000000	0.7	21.0	3.2	77.598	PASS



FCC ID: 2AREB-AIRFLYDUO
IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AY0056077(3)

Date : Oct 17, 2019

Emission Bandwidth 20 dB (2402 MHz; GFSK; DH5)

20 dB Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2402.000000	0.930000	---	---	2401.547500	2402.477500



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40100 GHz	2.40100 GHz
Stop Frequency	2.40300 GHz	2.40300 GHz
Span	2.000 MHz	2.000 MHz
RBW	10.000 kHz	>= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	400	~ 400
SweepTime	189.648 μ s	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	8 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.21 dB	0.50 dB

FCC ID: 2AREB-AIRFLYDUO

IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AY0056077(3)

Date : Oct 17, 2019

Emission Bandwidth 20 dB (2402 MHz; $\pi/4$ DQPSK; 2DH5)

20 dB Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2402.000000	1.250000	---	---	2401.365000	2402.615000



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40070 GHz	2.40070 GHz
Stop Frequency	2.40330 GHz	2.40330 GHz
Span	2.600 MHz	2.600 MHz
RBW	20.000 kHz	≥ 13.000 kHz
VBW	100.000 kHz	≥ 60.000 kHz
SweepPoints	260	~ 260
SweepTime	94.727 μ s	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	8 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.50 dB	0.50 dB

FCC ID: 2AREB-AIRFLYDUO
IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AY0056077(3)

Date : Oct 17, 2019

Emission Bandwidth 20 dB(2) (2402 MHz; 8DPSK; 3DH5)

20 dB Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2402.000000	1.270000	---	---	2401.355000	2402.625000



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40070 GHz	2.40070 GHz
Stop Frequency	2.40330 GHz	2.40330 GHz
Span	2.600 MHz	2.600 MHz
RBW	20.000 kHz	>= 13.000 kHz
VBW	100.000 kHz	>= 60.000 kHz
SweepPoints	260	~ 260
SweepTime	94.727 μ s	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	8 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.17 dB	0.50 dB

FCC ID: 2AREB-AIRFLYDUO
IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AY0056077(3)

Date : Oct 17, 2019

Occupied Channel Bandwidth 99% (2402 MHz; GFSK; DH5)

99 % Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2402.000000	0.860000	---	---	2401.567500	2402.427500



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40100 GHz	2.40100 GHz
Stop Frequency	2.40300 GHz	2.40300 GHz
Span	2.000 MHz	2.000 MHz
RBW	10.000 kHz	>= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	400	~ 400
SweepTime	189.648 μ s	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	500	500
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30 dB	0.30 dB
Run	4 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.13 dB	0.30 dB

FCC ID: 2AREB-AIRFLYDUO

IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AY0056077(3)

Date : Oct 17, 2019

Occupied Channel Bandwidth 99% (2402 MHz; $\pi/4$ DQPSK; 2DH5)

99 % Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2402.000000	1.180000	---	---	2401.405000	2402.585000



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40070 GHz	2.40070 GHz
Stop Frequency	2.40330 GHz	2.40330 GHz
Span	2.600 MHz	2.600 MHz
RBW	20.000 kHz	≥ 13.000 kHz
VBW	100.000 kHz	≥ 60.000 kHz
SweepPoints	260	~ 260
SweepTime	94.727 μ s	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	500	500
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamplifier	off	off
Stablemode	Trace	Trace
Stablevalue	0.30 dB	0.30 dB
Run	6 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.07 dB	0.30 dB

FCC ID: 2AREB-AIRFLYDUO

IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AY0056077(3)

Date : Oct 17, 2019

Occupied Channel Bandwidth 99%(2) (2402 MHz; 8DPSK; 3DH5)

99 % Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2402.000000	1.170000	---	---	2401.405000	2402.575000



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40070 GHz	2.40070 GHz
Stop Frequency	2.40330 GHz	2.40330 GHz
Span	2.600 MHz	2.600 MHz
RBW	20.000 kHz	>= 13.000 kHz
VBW	100.000 kHz	>= 60.000 kHz
SweepPoints	260	~ 260
SweepTime	94.727 μ s	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	500	500
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30 dB	0.30 dB
Run	5 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.13 dB	0.30 dB

FCC ID: 2AREB-AIRFLYDUO

IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AY0056077(3)

Date : Oct 17, 2019

Emission Bandwidth 20 dB (2441 MHz; GFSK; DH5)

20 dB Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2441.000000	0.930000	---	---	2440.542500	2441.472500



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.44000 GHz	2.44000 GHz
Stop Frequency	2.44200 GHz	2.44200 GHz
Span	2.000 MHz	2.000 MHz
RBW	10.000 kHz	>= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	400	~ 400
SweepTime	189.648 μ s	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	7 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.15 dB	0.50 dB

FCC ID: 2AREB-AIRFLYDUO
IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AY0056077(3)

Date : Oct 17, 2019

Emission Bandwidth 20 dB (2441 MHz; $\pi/4$ DQPSK; 2DH5)

20 dB Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2441.000000	1.290000	---	---	2440.335000	2441.625000



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.43970 GHz	2.43970 GHz
Stop Frequency	2.44230 GHz	2.44230 GHz
Span	2.600 MHz	2.600 MHz
RBW	20.000 kHz	>= 13.000 kHz
VBW	100.000 kHz	>= 60.000 kHz
SweepPoints	260	~ 260
SweepTime	94.727 μ s	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	14 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.07 dB	0.50 dB

FCC ID: 2AREB-AIRFLYDUO

IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AY0056077(3)

Date : Oct 17, 2019

Emission Bandwidth 20 dB(2) (2441 MHz; 8DPSK; 3DH5)

20 dB Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2441.000000	1.280000	---	---	2440.345000	2441.625000



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.43970 GHz	2.43970 GHz
Stop Frequency	2.44230 GHz	2.44230 GHz
Span	2.600 MHz	2.600 MHz
RBW	20.000 kHz	>= 13.000 kHz
VBW	100.000 kHz	>= 60.000 kHz
SweepPoints	260	~ 260
SweepTime	94.727 μ s	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	8 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.22 dB	0.50 dB

FCC ID: 2AREB-AIRFLYDUO

IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AY0056077(3)

Date : Oct 17, 2019

Occupied Channel Bandwidth 99% (2441 MHz; GFSK; DH5)

99 % Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2441.000000	0.865000	---	---	2440.562500	2441.427500



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.44000 GHz	2.44000 GHz
Stop Frequency	2.44200 GHz	2.44200 GHz
Span	2.000 MHz	2.000 MHz
RBW	10.000 kHz	>= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	400	~ 400
SweepTime	189.648 μ s	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	500	500
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30 dB	0.30 dB
Run	5 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.08 dB	0.30 dB

FCC ID: 2AREB-AIRFLYDUO
IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AY0056077(3)

Date : Oct 17, 2019

Occupied Channel Bandwidth 99% (2441 MHz; $\pi/4$ DQPSK; 2DH5)

99 % Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2441.000000	1.220000	---	---	2440.385000	2441.605000



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.43970 GHz	2.43970 GHz
Stop Frequency	2.44230 GHz	2.44230 GHz
Span	2.600 MHz	2.600 MHz
RBW	20.000 kHz	≥ 13.000 kHz
VBW	100.000 kHz	≥ 60.000 kHz
SweepPoints	260	~ 260
SweepTime	94.727 μ s	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	500	500
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30 dB	0.30 dB
Run	7 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.04 dB	0.30 dB

FCC ID: 2AREB-AIRFLYDUO
IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AY0056077(3)

Date : Oct 17, 2019

Occupied Channel Bandwidth 99%(2) (2441 MHz; 8DPSK; 3DH5)

99 % Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2441.000000	1.230000	---	---	2440.375000	2441.605000



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.43970 GHz	2.43970 GHz
Stop Frequency	2.44230 GHz	2.44230 GHz
Span	2.600 MHz	2.600 MHz
RBW	20.000 kHz	>= 13.000 kHz
VBW	100.000 kHz	>= 60.000 kHz
SweepPoints	260	~ 260
SweepTime	94.727 μ s	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	500	500
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30 dB	0.30 dB
Run	7 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.06 dB	0.30 dB

FCC ID: 2AREB-AIRFLYDUO

IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AY0056077(3)

Date : Oct 17, 2019

Emission Bandwidth 20 dB (2480 MHz; GFSK; DH5)

20 dB Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2480.000000	0.930000	---	---	2479.542500	2480.472500



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47900 GHz	2.47900 GHz
Stop Frequency	2.48100 GHz	2.48100 GHz
Span	2.000 MHz	2.000 MHz
RBW	10.000 kHz	>= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	400	~ 400
SweepTime	189.648 μ s	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	8 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.07 dB	0.50 dB

FCC ID: 2AREB-AIRFLYDUO

IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AY0056077(3)

Date : Oct 17, 2019

Emission Bandwidth 20 dB (2480 MHz; $\pi/4$ DQPSK; 2DH5)

20 dB Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2480.000000	1.300000	---	---	2479.325000	2480.625000



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47870 GHz	2.47870 GHz
Stop Frequency	2.48130 GHz	2.48130 GHz
Span	2.600 MHz	2.600 MHz
RBW	20.000 kHz	≥ 13.000 kHz
VBW	100.000 kHz	≥ 60.000 kHz
SweepPoints	260	~ 260
SweepTime	94.727 μ s	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	14 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.00 dB	0.50 dB

FCC ID: 2AREB-AIRFLYDUO
IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AY0056077(3)

Date : Oct 17, 2019

Emission Bandwidth 20 dB(2) (2480 MHz; 8DPSK; 3DH5)

20 dB Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2480.000000	1.300000	---	---	2479.325000	2480.625000



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47870 GHz	2.47870 GHz
Stop Frequency	2.48130 GHz	2.48130 GHz
Span	2.600 MHz	2.600 MHz
RBW	20.000 kHz	>= 13.000 kHz
VBW	100.000 kHz	>= 60.000 kHz
SweepPoints	260	~ 260
SweepTime	94.727 μ s	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	9 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.13 dB	0.50 dB

FCC ID: 2AREB-AIRFLYDUO

IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AY0056077(3)

Date : Oct 17, 2019

Occupied Channel Bandwidth 99% (2480 MHz; GFSK; DH5)

99 % Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2480.000000	0.865000	---	---	2479.562500	2480.427500



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47900 GHz	2.47900 GHz
Stop Frequency	2.48100 GHz	2.48100 GHz
Span	2.000 MHz	2.000 MHz
RBW	10.000 kHz	>= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	400	~ 400
SweepTime	189.648 μ s	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	500	500
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30 dB	0.30 dB
Run	4 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.16 dB	0.30 dB

FCC ID: 2AREB-AIRFLYDUO

IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AY0056077(3)

Date : Oct 17, 2019

Occupied Channel Bandwidth 99% (2480 MHz; $\pi/4$ DQPSK; 2DH5)

99 % Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2480.000000	1.250000	---	---	2479.375000	2480.625000



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47870 GHz	2.47870 GHz
Stop Frequency	2.48130 GHz	2.48130 GHz
Span	2.600 MHz	2.600 MHz
RBW	20.000 kHz	≥ 13.000 kHz
VBW	100.000 kHz	≥ 60.000 kHz
SweepPoints	260	~ 260
SweepTime	94.727 μ s	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	500	500
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30 dB	0.30 dB
Run	5 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.21 dB	0.30 dB

FCC ID: 2AREB-AIRFLYDUO
IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AY0056077(3)

Date : Oct 17, 2019

Occupied Channel Bandwidth 99%(2) (2480 MHz; 8DPSK; 3DH5)

99 % Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2480.000000	1.230000	---	---	2479.375000	2480.605000



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47870 GHz	2.47870 GHz
Stop Frequency	2.48130 GHz	2.48130 GHz
Span	2.600 MHz	2.600 MHz
RBW	20.000 kHz	>= 13.000 kHz
VBW	100.000 kHz	>= 60.000 kHz
SweepPoints	260	~ 260
SweepTime	94.727 μ s	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	500	500
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30 dB	0.30 dB
Run	6 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.07 dB	0.30 dB

FCC ID: 2AREB-AIRFLYDUO
IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AY0056077(3)

Date : Oct 17, 2019

Carrier Frequency Separation (2402 MHz; GFSK; DH5)

Result

DUT Frequency (MHz)	Frequency Separation (MHz)	Limit Min (MHz)	Limit Max (MHz)	Center Frequency low Channel (MHz)	Center Frequency high Channel (MHz)
2402.000000	1.009900	0.866667	---	2401.995050	2403.004950



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40100 GHz	2.40100 GHz
Stop Frequency	2.40400 GHz	2.40400 GHz
Span	3.000 MHz	3.000 MHz
RBW	300.000 kHz	≤ 300.000 kHz
VBW	300.000 kHz	≥ 300.000 kHz
SweepPoints	101	~ 10
SweepTime	1.000 ms	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	Sweep
Preamplifier	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	26 / max. 150	max. 150
Stable	10 / 10	10
Max Stable Difference	0.02 dB	0.50 dB

FCC ID: 2AREB-AIRFLYDUO

IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AY0056077(3)

Date : Oct 17, 2019

Carrier Frequency Separation (2441 MHz; GFSK; DH5)

Result

DUT Frequency (MHz)	Frequency Separation (MHz)	Limit Min (MHz)	Limit Max (MHz)	Center Frequency low Channel (MHz)	Center Frequency high Channel (MHz)
2441.000000	1.009900	0.866667	---	2440.995050	2442.004950



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.44000 GHz	2.44000 GHz
Stop Frequency	2.44300 GHz	2.44300 GHz
Span	3.000 MHz	3.000 MHz
RBW	300.000 kHz	≤ 300.000 kHz
VBW	300.000 kHz	≥ 300.000 kHz
SweepPoints	101	~ 10
SweepTime	1.000 ms	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	Sweep
Preamplifier	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	11 / max. 150	max. 150
Stable	10 / 10	10
Max Stable Difference	0.00 dB	0.50 dB

FCC ID: 2AREB-AIRFLYDUO

IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT


Report No. : AY0056077(3)

Date : Oct 17, 2019

Carrier Frequency Separation (2479 MHz; GFSK; DH5)

Result

DUT Frequency (MHz)	Frequency Separation (MHz)	Limit Min (MHz)	Limit Max (MHz)	Center Frequency low Channel (MHz)	Center Frequency high Channel (MHz)
2479.000000	1.009900	0.866667	---	2478.995050	2480.004950



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47800 GHz	2.47800 GHz
Stop Frequency	2.48100 GHz	2.48100 GHz
Span	3.000 MHz	3.000 MHz
RBW	300.000 kHz	≤ 300.000 kHz
VBW	300.000 kHz	≥ 300.000 kHz
SweepPoints	101	~ 10
SweepTime	1.000 ms	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	Sweep
Preamplifier	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	17 / max. 150	max. 150
Stable	10 / 10	10
Max Stable Difference	0.15 dB	0.50 dB

FCC ID: 2AREB-AIRFLYDUO

IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0056077(3)

Date : Oct 17, 2019

Band Edge low (Hopping; GFSK; DH5)

Result


DUT Frequency (MHz)	Result
hopping	PASS

Inband Peak

Frequency (MHz)	Level (dBm)
2479.025000	2.6

Measurements

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)	Result
2399.975000	-41.0	13.6	-27.4	PASS
2399.925000	-44.6	17.2	-27.4	PASS
2399.575000	-45.2	17.8	-27.4	PASS
2399.525000	-45.9	18.4	-27.4	PASS
2399.475000	-45.9	18.5	-27.4	PASS
2399.425000	-46.2	18.8	-27.4	PASS
2399.775000	-46.4	19.0	-27.4	PASS
2399.875000	-47.0	19.6	-27.4	PASS
2399.725000	-47.0	19.6	-27.4	PASS
2399.825000	-47.1	19.7	-27.4	PASS
2399.625000	-47.6	20.2	-27.4	PASS
2399.675000	-47.8	20.4	-27.4	PASS
2399.325000	-48.9	21.5	-27.4	PASS
2399.225000	-49.1	21.7	-27.4	PASS
2399.375000	-49.3	21.9	-27.4	PASS



— Limit — Sum Level × Fail

FCC ID: 2AREB-AIRFLYDUO

IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0056077(3)

Date : Oct 17, 2019

Measurement 1

Setting	Instrument Value	Target Value
Start Frequency	2.31000 GHz	2.31000 GHz
Stop Frequency	2.40000 GHz	2.40000 GHz
Span	90.000 MHz	90.000 MHz
RBW	100.000 kHz	<= 100.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	1800	~ 1800
SweepTime	1.800 ms	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	19 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.00 dB	0.50 dB

Measurement 2

Setting	Instrument Value	Target Value
Start Frequency	2.40000 GHz	2.40000 GHz
Stop Frequency	2.48350 GHz	2.48350 GHz
Span	83.500 MHz	83.500 MHz
RBW	100.000 kHz	<= 100.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	1670	~ 1670
SweepTime	1.670 ms	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	120 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.00 dB	0.50 dB

FCC ID: 2AREB-AIRFLYDUO
IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0056077(3)

Date : Oct 17, 2019

Band Edge high (Hopping; GFSK; DH5)

Result


DUT Frequency (MHz)	Result
hopping	PASS

Inband Peak

Frequency (MHz)	Level (dBm)
2480.175000	2.8

Measurements

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)	Result
2483.525000	-53.0	25.8	-27.2	PASS
2483.575000	-53.3	26.1	-27.2	PASS
2483.625000	-54.6	27.4	-27.2	PASS
2483.675000	-55.9	28.7	-27.2	PASS
2484.225000	-57.4	30.1	-27.2	PASS
2484.275000	-57.5	30.3	-27.2	PASS
2483.725000	-57.7	30.5	-27.2	PASS
2484.175000	-58.3	31.1	-27.2	PASS
2484.325000	-59.2	32.0	-27.2	PASS
2483.775000	-59.4	32.2	-27.2	PASS
2485.075000	-60.5	33.3	-27.2	PASS
2483.975000	-60.6	33.4	-27.2	PASS
2484.025000	-60.6	33.4	-27.2	PASS
2491.025000	-60.7	33.5	-27.2	PASS
2484.125000	-60.7	33.5	-27.2	PASS



— Limit — Sum Level × Fail

FCC ID: 2AREB-AIRFLYDUO

IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0056077(3)

Date : Oct 17, 2019

Measurement 1

Setting	Instrument Value	Target Value
Start Frequency	2.40000 GHz	2.40000 GHz
Stop Frequency	2.48350 GHz	2.48350 GHz
Span	83.500 MHz	83.500 MHz
RBW	100.000 kHz	<= 100.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	1670	~ 1670
SweepTime	1.670 ms	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	120 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.00 dB	0.50 dB

Measurement 2

Setting	Instrument Value	Target Value
Start Frequency	2.48350 GHz	2.48350 GHz
Stop Frequency	2.50000 GHz	2.50000 GHz
Span	16.500 MHz	16.500 MHz
RBW	100.000 kHz	<= 100.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	330	~ 330
SweepTime	37.969 μ s	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	4 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.00 dB	0.50 dB

FCC ID: 2AREB-AIRFLYDUO
IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0056077(3)

Date : Oct 17, 2019

Band Edge low (2402 MHz; GFSK; DH5)

Result


DUT Frequency (MHz)	Result
2402.000000	PASS

Inband Peak

Frequency (MHz)	Level (dBm)
2401.825000	-1.2

Measurements

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)	Result
2399.975000	-38.4	7.2	-31.2	PASS
2399.525000	-39.7	8.5	-31.2	PASS
2399.475000	-40.1	8.9	-31.2	PASS
2399.575000	-40.4	9.2	-31.2	PASS
2399.925000	-42.5	11.3	-31.2	PASS
2399.875000	-44.2	13.0	-31.2	PASS
2399.625000	-44.8	13.6	-31.2	PASS
2399.775000	-44.9	13.7	-31.2	PASS
2399.675000	-45.1	13.9	-31.2	PASS
2399.825000	-45.2	14.0	-31.2	PASS
2399.725000	-45.5	14.3	-31.2	PASS
2399.425000	-46.4	15.2	-31.2	PASS
2399.375000	-46.6	15.4	-31.2	PASS
2399.325000	-46.7	15.5	-31.2	PASS
2399.275000	-47.4	16.2	-31.2	PASS



— Limit — Sum Level × Fail

FCC ID: 2AREB-AIRFLYDUO

IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0056077(3)

Date : Oct 17, 2019

Measurement 1

Setting	Instrument Value	Target Value
Start Frequency	2.31000 GHz	2.31000 GHz
Stop Frequency	2.40000 GHz	2.40000 GHz
Span	90.000 MHz	90.000 MHz
RBW	100.000 kHz	<= 100.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	1800	~ 1800
SweepTime	1.800 ms	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	4 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.00 dB	0.50 dB

Measurement 2

Setting	Instrument Value	Target Value
Start Frequency	2.40000 GHz	2.40000 GHz
Stop Frequency	2.48350 GHz	2.48350 GHz
Span	83.500 MHz	83.500 MHz
RBW	100.000 kHz	<= 100.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	1670	~ 1670
SweepTime	1.670 ms	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	10 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.00 dB	0.50 dB

FCC ID: 2AREB-AIRFLYDUO
IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0056077(3)

Date : Oct 17, 2019

Band Edge high (2480 MHz; GFSK; DH5)

Result


DUT Frequency (MHz)	Result
2480.000000	PASS

Inband Peak

Frequency (MHz)	Level (dBm)
2480.175000	2.8

Measurements

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)	Result
2483.525000	-47.6	20.4	-27.2	PASS
2483.575000	-50.7	23.5	-27.2	PASS
2484.425000	-52.6	25.4	-27.2	PASS
2484.375000	-52.7	25.5	-27.2	PASS
2484.325000	-52.9	25.7	-27.2	PASS
2484.275000	-53.5	26.3	-27.2	PASS
2484.475000	-54.0	26.8	-27.2	PASS
2483.625000	-54.1	26.9	-27.2	PASS
2483.675000	-55.0	27.8	-27.2	PASS
2484.225000	-55.0	27.8	-27.2	PASS
2483.925000	-55.1	27.9	-27.2	PASS
2483.975000	-55.1	27.9	-27.2	PASS
2483.825000	-55.5	28.3	-27.2	PASS
2483.875000	-55.5	28.3	-27.2	PASS
2483.725000	-55.6	28.4	-27.2	PASS



— Limit — Sum Level × Fail

FCC ID: 2AREB-AIRFLYDUO

IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0056077(3)

Date : Oct 17, 2019

Measurement 1

Setting	Instrument Value	Target Value
Start Frequency	2.40000 GHz	2.40000 GHz
Stop Frequency	2.48350 GHz	2.48350 GHz
Span	83.500 MHz	83.500 MHz
RBW	100.000 kHz	<= 100.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	1670	~ 1670
SweepTime	1.670 ms	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	6 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.20 dB	0.50 dB

Measurement 2

Setting	Instrument Value	Target Value
Start Frequency	2.48350 GHz	2.48350 GHz
Stop Frequency	2.50000 GHz	2.50000 GHz
Span	16.500 MHz	16.500 MHz
RBW	100.000 kHz	<= 100.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	330	~ 330
SweepTime	37.969 μ s	AUTO
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	4 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.00 dB	0.50 dB

FCC ID: 2AREB-AIRFLYDUO
IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0056077(3)

Date : Oct 17, 2019

Tx Spurious Emission (2402 MHz; GFSK;DH5) Result Inband Peak

Frequency (MHz)	Level (dBm)
2402.000000	-0.7

Final measurements

Frequency (MHz)	Level Pre Measurement (dBm)	level (dBm)	Limit (dBm)	Margin (dB)	Result
---	---	---	---	---	---

Pre Measurements

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)
2399.225000	-44.8	14.1	-30.7
2399.175000	-45.1	14.4	-30.7
2399.125000	-45.9	15.2	-30.7
2399.275000	-46.7	16.0	-30.7
2399.425000	-47.3	16.6	-30.7
2399.375000	-47.4	16.7	-30.7
2399.325000	-47.5	16.8	-30.7
2399.525000	-47.7	17.0	-30.7
2399.475000	-48.2	17.5	-30.7
2399.975000	-48.6	17.9	-30.7
2399.575000	-48.9	18.2	-30.7
2399.075000	-49.0	18.3	-30.7
2399.625000	-49.6	18.9	-30.7
2399.925000	-50.4	19.8	-30.7
2399.675000	-51.4	20.7	-30.7

Measurement Settings

Start Frequency (MHz)	Stop Frequency (MHz)	Pre Measurement	Final Measurement
30.000000	1500.000000	1	1
1500.000000	2400.000000	1	1
2400.000000	2483.500000	1	1
2483.500000	3983.500000	1	1
3983.500000	5483.500000	1	1
5483.500000	6983.500000	1	1
6983.500000	8483.500000	1	1
8483.500000	9983.500000	1	1
9983.500000	11483.500000	1	1
11483.500000	12983.500000	1	1
12983.500000	14483.500000	1	1
14483.500000	15983.500000	1	1
15983.500000	17483.500000	1	1
17483.500000	18983.500000	1	1
18983.500000	20483.500000	1	1
20483.500000	21983.500000	1	1
21983.500000	23483.500000	1	1
23483.500000	24983.500000	1	1
24983.500000	26000.000000	1	1

FCC ID: 2AREB-AIRFLYDUO
IC: 24385-AIRFLYDUO




CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0056077(3)

Date : Oct 17, 2019



— Limit — Sum Level — Threshold × Critical × Final Critical

Pre Measurement 1

Setting	Instrument Value	Target Value
RBW	100.000 kHz	<= 100.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	29400	~ 29400
SweepTime	29.400 ms	AUTO
Reference Level	-30.000 dBm	-30.000 dBm
Attenuation	0.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	30	30
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	1.00 dB	1.00 dB
Run	2 / max. 40	max. 40
Stable	1 / 1	1
Max Stable Difference	0.00 dB	1.00 dB

FCC ID: 2AREB-AIRFLYDUO
IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0056077(3)

Date : Oct 17, 2019

Tx Spurious Emission (2441 MHz; GFSK;DH5) Result Inband Peak

Frequency (MHz)	Level (dBm)
2441.000000	0.8

Final measurements

Frequency (MHz)	Level Pre Measurement (dBm)	level (dBm)	Limit (dBm)	Margin (dB)	Result
---	---	---	---	---	---

Pre Measurements

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)
2597.025000	-53.2	23.9	-29.2
2597.075000	-53.8	24.6	-29.2
2596.975000	-53.8	24.6	-29.2
2596.875000	-54.2	25.0	-29.2
2596.825000	-54.4	25.2	-29.2
2596.925000	-54.5	25.3	-29.2
2545.175000	-54.5	25.3	-29.2
2597.175000	-54.7	25.5	-29.2
2597.125000	-54.8	25.5	-29.2
2544.975000	-55.3	26.1	-29.2
2544.925000	-55.4	26.2	-29.2
2545.025000	-55.5	26.3	-29.2
2545.225000	-55.6	26.4	-29.2
2545.075000	-55.6	26.4	-29.2
2545.125000	-55.8	26.6	-29.2

Measurement Settings

Start Frequency (MHz)	Stop Frequency (MHz)	Pre Measurement	Final Measurement
30.000000	1500.000000	1	1
1500.000000	2400.000000	1	1
2400.000000	2483.500000	1	1
2483.500000	3983.500000	1	1
3983.500000	5483.500000	1	1
5483.500000	6983.500000	1	1
6983.500000	8483.500000	1	1
8483.500000	9983.500000	1	1
9983.500000	11483.500000	1	1
11483.500000	12983.500000	1	1
12983.500000	14483.500000	1	1
14483.500000	15983.500000	1	1
15983.500000	17483.500000	1	1
17483.500000	18983.500000	1	1
18983.500000	20483.500000	1	1
20483.500000	21983.500000	1	1
21983.500000	23483.500000	1	1
23483.500000	24983.500000	1	1
24983.500000	26000.000000	1	1

FCC ID: 2AREB-AIRFLYDUO
IC: 24385-AIRFLYDUO




CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0056077(3)

Date : Oct 17, 2019



— Limit — Sum Level — Threshold × Critical × Final Critical

Pre Measurement 1

Setting	Instrument Value	Target Value
RBW	100.000 kHz	≤ 100.000 kHz
VBW	300.000 kHz	≥ 300.000 kHz
SweepPoints	29400	~ 29400
SweepTime	29.400 ms	AUTO
Reference Level	-30.000 dBm	-30.000 dBm
Attenuation	0.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	30	30
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	1.00 dB	1.00 dB
Run	2 / max. 40	max. 40
Stable	1 / 1	1
Max Stable Difference	0.00 dB	1.00 dB

FCC ID: 2AREB-AIRFLYDUO
IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0056077(3)

Date : Oct 17, 2019

Tx Spurious Emission (2480 MHz; GFSK;DH5) Result Inband Peak

Frequency (MHz)	Level (dBm)
2480.000000	2.8

Final measurements

Frequency (MHz)	Level Pre Measurement (dBm)	level (dBm)	Limit (dBm)	Margin (dB)	Result
---	---	---	---	---	---

Pre Measurements

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)
2635.975000	-53.9	26.7	-27.2
2636.025000	-54.0	26.9	-27.2
2483.525000	-54.4	27.3	-27.2
2636.075000	-54.5	27.3	-27.2
2636.175000	-54.9	27.8	-27.2
2635.925000	-55.0	27.8	-27.2
2635.875000	-55.0	27.8	-27.2
2636.125000	-55.0	27.9	-27.2
2635.825000	-55.2	28.0	-27.2
2583.875000	-55.8	28.7	-27.2
2584.025000	-55.9	28.8	-27.2
2583.975000	-56.0	28.8	-27.2
2484.025000	-56.1	28.9	-27.2
2583.925000	-56.2	29.0	-27.2
2584.075000	-56.2	29.0	-27.2

Measurement Settings

Start Frequency (MHz)	Stop Frequency (MHz)	Pre Measurement	Final Measurement
30.000000	1500.000000	1	1
1500.000000	2400.000000	1	1
2400.000000	2483.500000	1	1
2483.500000	3983.500000	1	1
3983.500000	5483.500000	1	1
5483.500000	6983.500000	1	1
6983.500000	8483.500000	1	1
8483.500000	9983.500000	1	1
9983.500000	11483.500000	1	1
11483.500000	12983.500000	1	1
12983.500000	14483.500000	1	1
14483.500000	15983.500000	1	1
15983.500000	17483.500000	1	1
17483.500000	18983.500000	1	1
18983.500000	20483.500000	1	1
20483.500000	21983.500000	1	1
21983.500000	23483.500000	1	1
23483.500000	24983.500000	1	1
24983.500000	26000.000000	1	1

FCC ID: 2AREB-AIRFLYDUO
IC: 24385-AIRFLYDUO




CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0056077(3)

Date : Oct 17, 2019



— Limit — Sum Level — Threshold × Critical × Final Critical

Pre Measurement 1

Setting	Instrument Value	Target Value
RBW	100.000 kHz	<= 100.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	29400	~ 29400
Sweptime	29.400 ms	AUTO
Reference Level	-30.000 dBm	-30.000 dBm
Attenuation	0.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	30	30
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	1.00 dB	1.00 dB
Run	2 / max. 40	max. 40
Stable	1 / 1	1
Max Stable Difference	0.00 dB	1.00 dB

FCC ID: 2AREB-AIRFLYDUO
IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0056077(3)

Date : Oct 17, 2019


Conducted Emission (Graph):



RBW 9 kHz

MT 1 s

Att 10 dB AUTO PREAMP OFF



FCC ID: 2AREB-AIRFLYDUO
IC: 24385-AIRFLYDUO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0056077(3)

Date : Oct 17, 2019

Conducted Emission (Data):

EDIT PEAK LIST (Final Measurement Results)				
Trace1:	FCC-QP			
Trace2:	FCC-AV			
Trace3:	---			
TRACE	FREQUENCY	LEVEL dB μ V		DELTA LIMIT dB
1 Quasi Peak	177 kHz	31.44	N gnd	-33.17
2 Average	253.5 kHz	18.95	L1 gnd	-32.68
2 Average	406.5 kHz	22.49	L1 gnd	-25.22
1 Quasi Peak	420 kHz	30.34	L1 gnd	-27.10
1 Quasi Peak	456 kHz	36.92	L1 gnd	-19.84
2 Average	460.5 kHz	26.06	L1 gnd	-20.61
1 Quasi Peak	1.0355 MHz	27.80	L1 gnd	-28.19
2 Average	1.0355 MHz	16.19	L1 gnd	-29.80
1 Quasi Peak	1.9535 MHz	26.90	L1 gnd	-29.09
2 Average	1.9535 MHz	17.53	L1 gnd	-28.46
1 Quasi Peak	3.452 MHz	24.68	L1 gnd	-31.31
2 Average	3.452 MHz	17.44	L1 gnd	-28.55
2 Average	4.262 MHz	17.02	L1 gnd	-28.97
1 Quasi Peak	4.9415 MHz	22.49	L1 gnd	-33.50
1 Quasi Peak	9.995 MHz	26.98	L1 gnd	-33.01
2 Average	10.166 MHz	12.47	N gnd	-37.53
1 Quasi Peak	17.4335 MHz	42.17	L1 gnd	-17.82
2 Average	17.564 MHz	31.37	N gnd	-18.62
2 Average	17.8475 MHz	31.46	N gnd	-18.53
1 Quasi Peak	17.888 MHz	42.61	L1 gnd	-17.38

***** End of Report *****

FCC ID: 2AREB-AIRFLYDUO
IC: 24385-AIRFLYDUO