



TEST REPORT

Applicant: LEQIDUO TOYS FACTORY
Address of Applicant: CHENGHAI DISTRICT, SHANTOU CITY, GUANGDONG PROVINCE, CHINA 515800
Manufacturer/Factory: LEQIDUO TOYS FACTORY
Address of Manufacturer/Factory: CHENGHAI DISTRICT, SHANTOU CITY, GUANGDONG PROVINCE, CHINA 515800
Equipment Under Test (EUT)
Product Name: Remote control car series
Model No.: See section 5.1
FCC ID: 2AS6C-LQD
Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.249
Date of sample receipt: August 20, 2025
Date of Test: August 20-25, 2025
Date of report issued: August 25, 2025
Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

Robinson Luo
Laboratory Manager


This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

2 Version

Version No.	Date	Description
00	August 25, 2025	Original

Prepared By:**Date:**

August 25, 2025

Project Engineer**Check By:****Date:**

August 25, 2025

Reviewer

3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY	4
4.1 MEASUREMENT UNCERTAINTY	4
5 GENERAL INFORMATION	5
5.1 GENERAL DESCRIPTION OF EUT	5
5.2 TEST MODE	7
5.3 DESCRIPTION OF SUPPORT UNITS	7
5.4 DEVIATION FROM STANDARDS	7
5.5 ABNORMALITIES FROM STANDARD CONDITIONS	7
5.6 TEST FACILITY	7
5.7 TEST LOCATION	7
5.8 ADDITIONAL INSTRUCTIONS	7
6 TEST INSTRUMENTS LIST	8
7 TEST RESULTS AND MEASUREMENT DATA	10
7.1 ANTENNA REQUIREMENT	10
7.2 RADIATED EMISSION METHOD	11
7.2.1 Field Strength of The Fundamental Signal	13
7.2.2 Spurious emissions	14
7.2.3 Bandedge emissions	22
7.3 20dB OCCUPY BANDWIDTH	26
8 TEST SETUP PHOTO	28
9 EUT CONSTRUCTIONAL DETAILS	28

4 Test Summary

Test Item	Section in CFR 47	Result
Antenna requirement	15.203	Pass
AC Power Line Conducted Emission	15.207	N/A
Field strength of the fundamental signal	15.249 (a)	Pass
Spurious emissions	15.249 (a) (d)/15.209	Pass
Band edge	15.249 (d)/15.205	Pass
20dB Occupied Bandwidth	15.215 (c)	Pass

Remarks:

1. Test according to ANSI C63.10:2013.
2. Pass: The EUT complies with the essential requirements in the standard.
3. N/A: not applicable

4.1 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	$\pm 7.25 \times 10^{-8}$
2	Duty cycle	$\pm 0.37\%$
3	Occupied Bandwidth	$\pm 3\%$
4	RF conducted power	$\pm 0.75\text{dB}$
5	RF power density	$\pm 3\text{dB}$
6	Conducted Spurious emissions	$\pm 2.58\text{dB}$
7	AC Power Line Conducted Emission	$\pm 3.44\text{dB}$ (0.15MHz ~ 30MHz)
8	Radiated Spurious emission test	$\pm 3.1\text{dB}$ (9kHz-30MHz)
		$\pm 3.8039\text{dB}$ (30MHz-200MHz)
		$\pm 3.9679\text{dB}$ (200MHz-1GHz)
		$\pm 4.29\text{dB}$ (1GHz-18GHz)
		$\pm 3.30\text{dB}$ (18GHz-40GHz)
9	Temperature test	$\pm 1^\circ\text{C}$
10	Humidity test	$\pm 3\%$
11	Time	$\pm 3\%$

5 General Information

5.1 General Description of EUT

Product Name:	Remote control car series
Model No.:	LQD02-1E, LQD02-2E, LQD02-3E, LQD02-4E, LQD02-5E, LQD02-6E, LQD02-7E, LQD02-8E, LQD02-9E, LQD02-10E, LQD02-11E, LQD02-12E, 720746BRS, LQD02-1F, LQD02-2F, LQD02-3F, LQD02-4F, LQD02-5F, LQD02-6F, LQD02-7F, LQD02-8F, LQD02-9F, LQD02-10F, LQD02-11F, 9010-1E, 9010-2E, 9010-3E, 9010-4E, 9010-5E, 9010-6E, 9010-7E, 9010-8E, 9010-9E, 9010-10E, 9010-11E, 9020-1E, 9020-2E, 9020-3E, 9020-4E, 9020-5E, 9020-6E, 9020-7E, 9020-8E, 9020-9E, 9020-10E, 9020-11E, 9020-12E, 9010-1F, 9010-2F, 9010-3F, 9010-4F, 9010-5F, 9010-6F, 9010-7F, 9010-8F, 9010-9F, 9010-10F, 9010-11F, 9020-1F, 9020-2F, 9020-3F, 9020-4F, 9020-5F, 9020-6F, 9020-7F, 9020-8F, 9020-9F, 9020-10F, 9020-11F, 9020-12F, 2.4G9060-25E, 2.4G9060-25F, 2.4G9070-25E, 2.4G9070-25F, 2.4G9060-14E, 2.4G9060-15E, 2.4G9060-16E, 2.4G9070-14E, 2.4G9070-15E, 2.4G9070-16E
Test Model No.:	LQD02-1E
Remark: All above models are identical in the same PCB layout, interior structure and electrical circuits. The differences are appearance color and model name for commercial purpose.	
Test sample(s) ID:	GTS2025080369-1
Sample(s) Status	Engineered sample
Operation Frequency:	2407MHz~2477MHz
Channel Numbers:	71
Modulation Type:	GFSK
Antenna Type:	PCB Antenna
Antenna gain:	-2.5dBi(declare by applicant)
Power supply:	DC 3V(2*1.5V Size "AA" Battery)

Remark:

1. Antenna gain information provided by the customer
2. The relevant information of the sample is provided by the entrusting company, and the laboratory is not responsible for its authenticity.

Operation Frequency each of channel							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2407	20	2426	39	2445	58	2464
2	2408	21	2427	40	2446	59	2465
3	2409	22	2428	41	2447	60	2466
4	2410	23	2429	42	2448	61	2467
5	2411	24	2430	43	2449	62	2468
6	2412	25	2431	44	2450	63	2469
7	2413	26	2432	45	2451	64	2470
8	2414	27	2433	46	2452	65	2471
9	2415	28	2434	47	2453	66	2472
10	2416	29	2435	48	2454	67	2473
11	2417	30	2436	49	2455	68	2474
12	2418	31	2437	50	2456	69	2475
13	2419	32	2438	51	2457	70	2476
14	2420	33	2439	52	2458	71	2477
15	2421	34	2440	53	2459		
16	2422	35	2441	54	2460		
17	2423	36	2442	55	2461		
18	2424	37	2443	56	2462		
19	2425	38	2444	57	2463		

The test frequencies are below:

Channel	Frequency
The lowest channel	2407MHz
The middle channel	2447MHz
The Highest channel	2477MHz

5.2 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode.
Remark: New battery is used during all test.	

Per-test mode.

We have verified the construction and function in typical operation, The EUT was placed on three different polar directions; i.e. X axis, Y axis, Z axis. which was shown in this test report (Only show the worst case:Y axis) and defined as follows:

Axis	X	Y	Z
Field Strength(dBuV/m)	90.23	90.77	90.47

5.3 Description of Support Units

None.

5.4 Deviation from Standards

None.

5.5 Abnormalities from Standard Conditions

None.

5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC—Registration No.: 381383**

Designation Number: CN5029

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files.

- **ISED—Registration No.: 9079A**

CAB identifier: CN0091

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of ISED for radio equipment testing

- **NVLAP (LAB CODE:600179-0)**

Global United Technology Services Co., Ltd., is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP).

5.7 Test Location

All tests were performed at:
Global United Technology Services Co., Ltd.
Address: No. 123- 128, Tower A, Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102
Tel: 0755-27798480
Fax: 0755-27798960

5.8 Additional Instructions

Test Software	Special test command provided by manufacturer
Power level setup	Default

6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	Apr. 11, 2025	Apr. 10, 2026
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	Apr. 12, 2025	Apr. 11, 2026
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9168	GTS640	Apr. 12, 2025	Apr. 11, 2026
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	GTS208	Apr. 11, 2025	Apr. 10, 2026
6	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS575	Jul. 01, 2025	Jun. 30, 2026
7	Loop Antenna	ZHINAN	ZN30900A	GTS534	Nov.16, 2024	Nov.15, 2025
8	Broadband Preamplifier	SCHWARZBECK	BBV9718	GTS535	Apr. 11, 2025	Apr. 10, 2026
9	Amplifier(1GHz-26.5GHz)	HP	8449B	GTS601	Apr. 11, 2025	Apr. 10, 2026
10	Horn Antenna (18GH-40GHz)	Schwarzbeck	BBHA 9170	GTS691	Apr. 11, 2025	Apr. 10, 2026
11	FSV·Signal Analyzer (10Hz-40GHz)	Keysight	FSV-40-N	GTS666	Mar. 11, 2025	Mar. 10, 2026
12	Amplifier	/	LNA-1000-30S	GTS650	Apr. 11, 2025	Apr. 10, 2026
13	CDNE M2+M3-16A	HCT	30MHz-300MHz	GTS692	Nov. 13, 2024	Nov. 12, 2025
14	Wideband Amplifier	/	WDA-01004000-15P35	GTS602	Apr. 11, 2025	Apr. 10, 2026
15	Thermo meter	JINCHUANG	GSP-8A	GTS643	Apr. 15, 2025	Apr. 14, 2026
16	RE cable 1	GTS	N/A	GTS675	Jul. 11, 2025	Jul. 10, 2026
17	RE cable 2	GTS	N/A	GTS676	Jul. 11, 2025	Jul. 10, 2026
18	RE cable 3	GTS	N/A	GTS677	Jul. 11, 2025	Jul. 10, 2026
19	RE cable 4	GTS	N/A	GTS678	Jul. 11, 2025	Jul. 10, 2026
20	RE cable 5	GTS	N/A	GTS679	Jul. 11, 2025	Jul. 10, 2026
21	RE cable 6	GTS	N/A	GTS680	Jul. 11, 2025	Jul. 10, 2026
22	RE cable 7	GTS	N/A	GTS681	Jul. 11, 2025	Jul. 10, 2026
23	RE cable 8	GTS	N/A	GTS682	Jul. 11, 2025	Jul. 10, 2026
24	EMI Test Software	AUDIX	E3-6.100614a	GTS725	N/A	N/A

RF Conducted Test:

Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	MXA Signal Analyzer	Agilent	N9020A	GTS566	Apr. 11, 2025	Apr. 10, 2026
2	EMI Test Receiver	R&S	ESCI 7	GTS552	Apr. 12, 2025	Apr. 11, 2026
3	PSA Series Spectrum Analyzer	Agilent	E4440A	GTS536	Apr. 11, 2025	Apr. 10, 2026
4	MXG vector Signal Generator	Agilent	N5182A	GTS567	Apr. 11, 2025	Apr. 10, 2026
5	ESG Analog Signal Generator	Agilent	E4428C	GTS568	Apr. 11, 2025	Apr. 10, 2026
6	Wideband Power Meter	Keysight	N1924A	GTS673	Apr. 11, 2025	Apr. 10, 2026
7	USB RF Power Sensor	DARE	RPR3006W	GTS569	Apr. 11, 2025	Apr. 10, 2026
8	RF Switch Box	Shongyi	RFSW3003328	GTS571	Apr. 11, 2025	Apr. 10, 2026
9	Programmable Constant Temp & Humi Test Chamber	WEWON	WHTH-150L-40-880	GTS572	Apr. 11, 2025	Apr. 10, 2026
10	Thermo meter	JINCHUANG	GSP-8A	GTS641	Apr. 15, 2025	Apr. 14, 2026
11	EXA Signal Analyzer	Keysight	N9010B	MY60241168	Nov. 02, 2024	Nov. 01, 2025

General used equipment:


Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Barometer	KUMAO	SF132	GTS647	Jul. 16, 2025	Jul. 15, 2026


7 Test results and Measurement Data

7.1 Antenna requirement


Standard requirement:	FCC Part15 C Section 15.203
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.	
EUT Antenna:	
The antenna is PCB antenna, reference to the appendix II for details.	

7.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	9kHz-150kHz	Quasi-peak	200Hz	300Hz	Quasi-peak Value
	150kHz-30MHz	Quasi-peak	9kHz	10kHz	Quasi-peak Value
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		Peak	1MHz	10Hz	Average Value
Limit: (Field strength of the fundamental signal)	Frequency		Limit (dBuV/m @3m)		Remark
	2400MHz-2483.5MHz		94.00		Average Value
			114.00		Peak Value
Limit: (Spurious Emissions)	Frequency		Limit (uV/m)		Remark
	0.009MHz-0.490MHz		2400/F(kHz) @300m		Quasi-peak Value
	0.490MHz-1.705MHz		24000/F(kHz) @30m		Quasi-peak Value
	1.705MHz-30.0MHz		30 @30m		Quasi-peak Value
	30MHz-88MHz		100 @3m		Quasi-peak Value
	88MHz-216MHz		150 @3m		Quasi-peak Value
	216MHz-960MHz		200 @3m		Quasi-peak Value
	960MHz-1GHz		500 @3m		Quasi-peak Value
	Above 1GHz		500 @3m		Average Value
5000 @3m			Peak Value		
Limit: (band edge)	Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.				
Test setup:	For radiated emissions from 9kHz to 30MHz  For radiated emissions from 30MHz to1GHz				



For radiated emissions above 1GHz



Test Procedure:

1. The EUT was placed on the top of a rotating table (0.8m for below 1GHz and 1.5 meters for above 1GHz) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Test Instruments:

Refer to section 6.0 for details

Test mode:

Refer to section 5.2 for details

Test environment:

Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar
--------	-------	---------	-----	---------	----------

Test voltage:

DC 3V

Test results:

Pass

Measurement data:

7.2.1 Field Strength of The Fundamental Signal

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2407.00	84.64	27.14	4.16	39.40	76.54	114.00	-37.46	Vertical
2407.00	98.72	27.14	4.16	39.40	90.62	114.00	-23.38	Horizontal
2447.00	84.77	27.18	4.13	39.46	76.62	114.00	-37.38	Vertical
2447.00	98.92	27.18	4.13	39.46	90.77	114.00	-23.23	Horizontal
2477.00	83.64	27.22	4.11	39.51	75.46	114.00	-38.54	Vertical
2477.00	95.63	27.22	4.11	39.51	87.45	114.00	-26.55	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2407.00	74.30	27.14	4.16	39.40	66.20	94.00	-27.80	Vertical
2407.00	88.38	27.14	4.16	39.40	80.28	94.00	-13.72	Horizontal
2447.00	74.43	27.18	4.13	39.46	66.28	94.00	-27.72	Vertical
2447.00	88.58	27.18	4.13	39.46	80.43	94.00	-13.57	Horizontal
2477.00	73.30	27.22	4.11	39.51	65.12	94.00	-28.88	Vertical
2477.00	85.29	27.22	4.11	39.51	77.11	94.00	-16.89	Horizontal

Note:

- For fundamental frequency, RBW>20dB BW, VBW>=RBW, PK detector for PK value, RMS detector for AV value
- Final Level(dBuV/m)=Reading level(dBuV)+Antenna Factor(dB/m)+Cable Loss(dB)-Preamplifier Factor(dB)


7.2.2 Spurious emissions

■ Below 30MHz

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o), the test result no need to reported.

■ Below 1GHz

Pre-scan all test modes, found worst case at 2407MHz, and so only show the test result of it
Horizontal




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	Final level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
31.399	29.43	12.50	1.23	33.59	9.57	40.00	-30.43	QP
57.392	26.25	12.24	1.58	33.52	6.55	40.00	-33.45	QP
141.826	29.18	13.98	2.38	33.50	12.04	43.50	-31.46	QP
186.441	37.06	11.06	2.71	33.42	17.41	43.50	-26.09	QP
447.982	24.96	15.96	4.36	32.96	12.32	46.00	-33.68	QP
711.674	27.63	20.80	5.59	32.37	21.65	46.00	-24.35	QP

Remarks:

Final level(dBuV/m) = Reading level(dBuV) + Antenna factor(dB/m) + Cable loss(dB) - Preamp Factor(dB)

Vertical



Remarks:


Final level(dBuV/m) = Reading level(dBuV) + Antenna factor(dB/m) + Cable loss(dB) - Preamp Factor(dB)

■ Above 1GHz

Test channel:

Lowest channel

Vertical




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	Final level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4812.000	42.60	36.01	5.57	38.01	46.17	74.00	-27.83	Peak
7221.000	42.23	36.56	7.18	37.98	47.99	74.00	-26.01	Peak
9628.000	42.03	38.20	9.08	39.19	50.12	74.00	-23.88	Peak

Remarks:

$$\text{Final level (dBuV/m)} = \text{Reading level (dBuV)} + \text{Antenna factor (dB/m)} + \text{Cable loss (dB)} - \text{Preamp Factor (dB)}$$

Horizontal



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	Final level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4814.000	44.40	38.16	5.57	38.01	50.12	74.00	-23.88	Peak
7221.000	37.92	43.02	7.18	37.98	50.14	74.00	-23.86	Peak
9628.000	40.75	39.08	9.08	39.19	49.72	74.00	-24.28	Peak


Remarks:

Final level(dBuV/m) = Reading level(dBuV) + Antenna factor(dB/m) + Cable loss(dB) - Preamp Factor(dB)

Test channel:

Middle

Vertical




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	Final level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4894.000	43.55	34.29	5.68	37.96	45.56	74.00	-28.44	Peak
7341.000	43.43	36.50	7.28	38.07	49.14	74.00	-24.86	Peak
9788.000	41.84	38.30	9.19	39.24	50.09	74.00	-23.91	Peak

Remarks:

Final level(dBuV/m) = Reading level(dBuV) + Antenna factor(dB/m) + Cable loss(dB) - Preamp Factor(dB)

Horizontal




Remarks:

Final level(dBuV/m) = Reading level(dBuV) + Antenna factor(dB/m) + Cable loss(dB) - Preamplifier Factor(dB)

Test channel:

Highest


Vertical



Remarks:

$$\text{Final level (dBuV/m)} = \text{Reading level (dBuV)} + \text{Antenna factor (dB/m)} + \text{Cable loss (dB)} - \text{Preamp Factor (dB)}$$

Horizontal



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamplifier factor dB	Final level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4954.000	43.02	37.76	5.77	37.93	48.62	74.00	-25.38	Peak
7431.000	35.75	44.96	7.33	38.14	49.90	74.00	-24.10	Peak
9908.000	41.85	38.40	9.24	39.27	50.22	74.00	-23.78	Peak

Remarks:

Final level (dBuV/m) = Reading level (dBuV) + Antenna factor (dB/m) + Cable loss (dB) - Preamp Factor (dB)

Remarks:

1. The emission levels of other frequencies are very lower than the limit and not show in test report.
2. For above 18GHz, no emission found.
3. If the average limit is met when using a Peak detector, the EUT shall be deemed to meet both peak and average limits. And measurement with the average detector is unnecessary.


7.2.3 Bandedge emissions

All of the restriction bands were tested, and only the data of worst case was exhibited.

Test channel:

Lowest channel

Vertical




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	Final level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	34.28	28.05	4.09	38.86	27.56	54.00	-26.44	Average
2310.000	45.36	28.05	4.09	38.86	38.64	74.00	-35.36	Peak
2390.000	34.86	27.03	4.11	38.88	27.12	54.00	-26.88	Average
2390.000	45.94	27.03	4.11	38.88	38.20	74.00	-35.80	Peak
2400.000	39.05	26.94	4.11	38.88	31.22	54.00	-22.78	Average
2400.000	51.91	26.94	4.11	38.88	44.08	74.00	-29.92	Peak

Remarks:

Final level(dBuV/m) = Reading level(dBuV) + Antenna factor(dB/m) + Cable loss(dB) - Preamp Factor(dB)

Horizontal



Freq MHz	Reading level dBUV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	Final level dBUV/m	Limit level dBUV/m	Over limit dB	Remark
2310.000	32.34	26.66	4.09	38.86	24.23	54.00	-29.77	Average
2310.000	46.26	26.66	4.09	38.86	38.15	74.00	-35.85	Peak
2390.000	43.45	26.62	4.11	38.88	35.30	54.00	-18.70	Average
2390.000	56.67	26.62	4.11	38.88	48.52	74.00	-25.48	Peak
2400.000	50.52	26.43	4.11	38.88	42.18	54.00	-11.82	Average
2400.000	66.68	26.43	4.11	38.88	58.34	74.00	-15.66	Peak


Remarks:

Final level(dBUV/m) = Reading level(dBUV) + Antenna factor(dB/m) + Cable loss(dB) - Preamp Factor(dB)

Test channel:

Highest channel

Vertical




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	Final level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2483.500	36.56	28.22	4.13	38.90	30.01	54.00	-23.99	Average
2483.500	50.44	28.22	4.13	38.90	43.89	74.00	-30.11	Peak
2500.000	31.12	28.63	4.14	38.90	24.99	54.00	-29.01	Average
2500.000	45.01	28.63	4.14	38.90	38.88	74.00	-35.12	Peak

Remarks:

$$\text{Final level (dBuV/m)} = \text{Reading level (dBuV)} + \text{Antenna factor (dB/m)} + \text{Cable loss (dB)} - \text{Preamp Factor (dB)}$$

Horizontal



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	Final level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2483.500	50.49	26.78	4.13	38.90	42.50	54.00	-11.50	Average
2483.500	64.34	26.78	4.13	38.90	56.35	74.00	-17.65	Peak
2500.000	39.68	26.48	4.14	38.90	31.40	54.00	-22.60	Average
2500.000	51.55	26.48	4.14	38.90	43.27	74.00	-30.73	Peak


Remarks:

Final level (dBuV/m) = Reading level (dBuV) + Antenna factor (dB/m) + Cable loss (dB) - Preamplifier Factor (dB)

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss - Preamplifier Factor
2. For above 18GHz, no emission found

7.3 20dB Occupy Bandwidth

Test Requirement:	FCC Part15 C Section 15.249/15.215
Test Method:	ANSI C63.10:2013
Limit:	Operation Frequency range 2400MHz~2483.5MHz
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. The setup is on a Non-Conducted Table, which is placed on a Ground Reference Plane.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data

Test channel	20dB bandwidth(MHz)	Result
Lowest	1.083	Pass
Middle	1.081	Pass
Highest	1.123	Pass

Test plot as follows:



Lowest channel



Middle channel



Highest channel

8 Test Setup Photo

Reference to the **appendix I** for details.

9 EUT Constructional Details

Reference to the **appendix II** for details.

-----End-----