





CSE Plot on Ch 78 between 30MHz ~ 3 GHz



Date: 2.AUG.2019 00:07:41

CSE Plot on Ch 78 between 2 GHz ~ 25 GHz



Date: 2.AUG.2019 00:13:14



### 3.8 Radiated Band Edges and Spurious Emission Measurement

#### 3.8.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

#### 3.8.2 Measuring Instruments

See list of measuring equipment of this test report.


**3.8.3 Test Procedures**

1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
4. Set to the maximum power setting and enable the EUT transmit continuously.
5. Use the following spectrum analyzer settings:
  - (1) Span shall wide enough to fully capture the emission being measured;
  - (2) Set RBW=100 kHz for  $f < 1$  GHz, RBW=1MHz for  $f > 1$ GHz ; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
  - (3) For average measurement: use duty cycle correction factor method per 15.35(c).  
Duty cycle = On time/100 milliseconds  
On time =  $N_1 * L_1 + N_2 * L_2 + \dots + N_{n-1} * L_{n-1} + N_n * L_n$   
Where  $N_1$  is number of type 1 pulses,  $L_1$  is length of type 1 pulses, etc.  
Average Emission Level = Peak Emission Level +  $20 * \log(\text{Duty cycle})$
6. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
7. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
8. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.


Note: The average levels were calculated from the peak level corrected with duty cycle correction factor (-24.79dB) derived from  $20 \log(\text{dwell time}/100\text{ms})$ . This correction is only for signals that hop with the fundamental signal, such as band-edge and harmonic. Other spurious signals that are independent of the hopping signal would not use this correction.

### 3.8.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



### 3.8.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

### 3.8.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C and D.

### 3.8.7 Duty Cycle

Please refer to Appendix E.

### 3.8.8 Test Result of Radiated Spurious Emission (30MHz ~ 10<sup>th</sup> Harmonic)

Please refer to Appendix C and D.



### 3.9 AC Conducted Emission Measurement

#### 3.9.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBµV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


#### 3.9.2 Measuring Instruments

See list of measuring equipment of this test report.

#### 3.9.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

### 3.9.4 Test Setup



### 3.9.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



## **3.10 Antenna Requirements**

### **3.10.1 Standard Applicable**

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

### **3.10.2 Antenna Anti-Replacement Construction**

An embedded-in antenna design is used.

### **3.10.3 Antenna Gain**

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Power Meter	Agilent	E4416A	GB412923 44	N/A	Dec. 27, 2018	Jul. 09, 2019 ~ Aug. 02, 2019	Dec. 26, 2019	Conducted (TH05-HY)
Power Sensor	Agilent	E9327A	US404415 48	50MHz~18GHz	Dec. 27, 2018	Jul. 09, 2019 ~ Aug. 02, 2019	Dec. 26, 2019	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSV40	101397	10Hz~40GHz	Nov. 13, 2018	Jul. 09, 2019 ~ Aug. 02, 2019	Nov. 12, 2019	Conducted (TH05-HY)
Switch Box & RF Cable	Burgeon	ETF-058	EC120838 2	N/A	Mar. 27, 2019	Jul. 09, 2019 ~ Aug. 02, 2019	Mar. 26, 2020	Conducted (TH05-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Jan. 07, 2019	Jul. 13, 2019 ~ Aug. 06, 2019	Jan. 06, 2020	Radiation (03CH15-HY)
Preamplifier	EMEC	EM18G40G	060715	18GHz ~ 40GHz	Dec. 06, 2018	Jul. 13, 2019 ~ Aug. 06, 2019	Dec. 05, 2019	Radiation (03CH15-HY)
Bilog Antenna	TESEQ	CBL6111D&0 0800N1D01N- 06	41912&05	30MHz to 1GHz	Feb. 12, 2019	Jul. 13, 2019 ~ Aug. 06, 2019	Feb. 11, 2020	Radiation (03CH15-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120D	9120D-162 0	1G~18GHz	Oct. 17, 2018	Jul. 13, 2019 ~ Aug. 06, 2019	Oct. 16, 2019	Radiation (03CH15-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	BBHA9170 584	18GHz- 40GHz	Dec. 05, 2018	Jul. 13, 2019 ~ Aug. 06, 2019	Dec. 04, 2019	Radiation (03CH15-HY)
Amplifier	SONOMA	310N	363440	9kHz~1GHz	Dec. 28, 2018	Jul. 13, 2019 ~ Aug. 06, 2019	Dec. 27, 2019	Radiation (03CH15-HY)
Preamplifier	Jet-Power	JPA0118-55-3 03	171000180 0055007	1GHz~18GHz	Apr. 01, 2019	Jul. 13, 2019 ~ Aug. 06, 2019	Mar. 31, 2020	Radiation (03CH15-HY)
Preamplifier	Keysight	83017A	MY532701 95	1GHz~26.5GHz	Aug. 23, 2018	Jul. 13, 2019 ~ Aug. 06, 2019	Aug. 22, 2019	Radiation (03CH15-HY)
EMI Test Receiver	Keysight	N9038A (MXE)	MY541300 85	20Hz ~ 8.4GHz	Nov. 01, 2018	Jul. 13, 2019 ~ Aug. 06, 2019	Oct. 31, 2019	Radiation (03CH15-HY)
Spectrum Analyzer	Agilent	E4446A	MY501801 36	3Hz~44GHz	Apr. 29, 2019	Jul. 13, 2019 ~ Aug. 06, 2019	Apr. 28, 2020	Radiation (03CH15-HY)
EMI Test Receiver	Keysight	N9038A (MXE)	MY572901 11	3Hz ~ 26.5GHz	Nov. 29, 2018	Jul. 13, 2019 ~ Aug. 06, 2019	Nov. 28, 2019	Radiation (03CH15-HY)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	Jul. 13, 2019 ~ Aug. 06, 2019	N/A	Radiation (03CH15-HY)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	Jul. 13, 2019 ~ Aug. 06, 2019	N/A	Radiation (03CH15-HY)
Software	Audix	E3 6.2009-8-24(k 5)	RK-00045 1	N/A	N/A	Jul. 13, 2019 ~ Aug. 06, 2019	N/A	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY36980/ 4	30M-18G	Apr. 15, 2019	Jul. 13, 2019 ~ Aug. 06, 2019	Apr. 14, 2020	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY9838/4	30M-18G	Apr. 15, 2019	Jul. 13, 2019 ~ Aug. 06, 2019	Apr. 14, 2020	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY802430 /4	30M~18GHz	May 13, 2019	Jul. 13, 2019 ~ Aug. 06, 2019	May 12, 2020	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY2859/2	30MHz-40GHz	Mar. 13, 2019	Jul. 13, 2019 ~ Aug. 06, 2019	Mar. 12, 2020	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY4274/2	30MHz-40GHz	Mar. 13, 2019	Jul. 13, 2019 ~ Aug. 06, 2019	Mar. 12, 2020	Radiation (03CH15-HY)
Filter	Wainwright	WLK4-1000-1 530-8000-40S S	SN11	1G Low Pass	Sep. 16, 2018	Jul. 13, 2019 ~ Aug. 06, 2019	Sep. 15, 2019	Radiation (03CH15-HY)
Filter	Wainwright	WHKX12-270 0-3000-18000 -60ST	SN1	3 GHz Highpass	Sep. 16, 2018	Jul. 13, 2019 ~ Aug. 06, 2019	Sep. 15, 2019	Radiation (03CH15-HY)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Jul. 06, 2019	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9kHz~3.6GHz	Nov. 12, 2018	Jul. 06, 2019	Nov. 11, 2019	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 14, 2018	Jul. 06, 2019	Nov. 13, 2019	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Nov. 09, 2018	Jul. 06, 2019	Nov. 08, 2019	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Jul. 06, 2019	N/A	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Dec. 31, 2018	Jul. 06, 2019	Dec. 30, 2019	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Dec. 31, 2018	Jul. 06, 2019	Dec. 30, 2019	Conduction (CO05-HY)



## 5 Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	2.20
---	------

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.20
---	------

### Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.50
---	------

### Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.20
---	------

**Appendix A. Test Result of Conducted Test Items**

Test Engineer:	Kai Liao	Temperature:	21~25	°C
Test Date:	2019/07/09 ~ 2019/08/02	Relative Humidity:	51~54	%

<b>TEST RESULTS DATA</b>									
<b>20dB and 99% Occupied Bandwidth and Hopping Channel Separation</b>									
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	20db BW (MHz)	99% Bandwidth (MHz)	Hopping Channel Separation Measurement (MHz)	Hopping Channel Separation Measurement Limit (MHz)	Pass/Fail
DH	1Mbps	1	0	2402	0.880	0.839	1.003	0.5866	Pass
DH	1Mbps	1	39	2441	0.880	0.839	1.003	0.5866	Pass
DH	1Mbps	1	78	2480	0.880	0.839	1.329	0.5866	Pass
2DH	2Mbps	1	0	2402	1.207	1.135	1.003	0.8046	Pass
2DH	2Mbps	1	39	2441	1.207	1.132	1.003	0.8046	Pass
2DH	2Mbps	1	78	2480	1.207	1.132	1.320	0.8046	Pass
3DH	3Mbps	1	0	2402	1.211	1.138	1.003	0.8075	Pass
3DH	3Mbps	1	39	2441	1.211	1.126	1.320	0.8075	Pass
3DH	3Mbps	1	78	2480	1.211	1.126	0.999	0.8075	Pass

<b>TEST RESULTS DATA</b>						
<b>Dwell Time</b>						
Mod.	Hopping Channel Number Rate	Hops Over Occupancy Time(hops)	Package Transfer Time (msec)	Dwell Time (sec)	Limits (sec)	Pass/Fail
Nomal	79	106.67	2.87	0.31	0.4	Pass
AFH	20	53.33	2.87	0.15	0.4	Pass

<b>TEST RESULTS DATA</b>					
<b>Peak Power Table</b>					
DH	CH.	NTX	Peak Power (dBm)	Power Limit (dBm)	Test Result
DH1	0	1	7.26	20.97	Pass
	39	1	7.53	20.97	Pass
	78	1	<b>7.64</b>	20.97	Pass
2DH1	0	1	7.11	20.97	Pass
	39	1	7.46	20.97	Pass
	78	1	<b>7.51</b>	20.97	Pass
3DH1	0	1	7.19	20.97	Pass
	39	1	7.49	20.97	Pass
	78	1	<b>7.60</b>	20.97	Pass

<b>TEST RESULTS DATA</b>				
<b>Average Power Table</b>				
<b>(Reporting Only)</b>				
DH	CH.	NTX	Average Power (dBm)	Duty Factor (dB)
DH1	0	1	6.90	8.30
	39	1	7.20	8.30
	78	1	<b>7.30</b>	8.30
2DH1	0	1	5.16	8.22
	39	1	5.46	8.22
	78	1	<b>5.56</b>	8.22
3DH1	0	1	5.20	8.22
	39	1	5.45	8.22
	78	1	<b>5.59</b>	8.22

<b>TEST RESULTS DATA</b>			
<b>Number of Hopping Frequency</b>			
Number of Hopping (Channel)	Adaptive Frequency Hopping (Channel)	Limits (Channel)	Pass/Fail
79	20	> 15	Pass




## **Appendix B. AC Conducted Emission Test Results**

<b>Test Engineer :</b> Jimmy Chang	<b>Temperature :</b>	24~26°C
	<b>Relative Humidity :</b>	52~56%

# EUT Information

Report NO : 941514-01  
 Test Mode : Mode 1  
 Test Voltage : 120Vac/60Hz  
 Phase : Line

Full Spectrum




## Final\_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	29.75	55.88	26.13	L1	OFF	19.4
0.152250	40.07	---	65.88	25.81	L1	OFF	19.4
0.233250	---	28.37	52.33	23.96	L1	OFF	19.4
0.233250	31.03	---	62.33	31.30	L1	OFF	19.4
0.498750	---	26.65	46.02	19.37	L1	OFF	19.4
0.498750	29.00	---	56.02	27.02	L1	OFF	19.4
3.291000	---	23.79	46.00	22.21	L1	OFF	19.6
3.291000	24.74	---	56.00	31.26	L1	OFF	19.6
9.629250	---	25.10	50.00	24.90	L1	OFF	19.8
9.629250	26.27	---	60.00	33.73	L1	OFF	19.8
21.882750	---	26.00	50.00	24.00	L1	OFF	20.2
21.882750	27.64	---	60.00	32.36	L1	OFF	20.2

# EUT Information

Report NO : 941514-01  
 Test Mode : Mode 1  
 Test Voltage : 120Vac/60Hz  
 Phase : Neutral

Full Spectrum



## Final\_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.165750	---	29.07	55.17	26.10	N	OFF	19.5
0.165750	38.61	---	65.17	26.56	N	OFF	19.5
0.501000	---	28.34	46.00	17.66	N	OFF	19.5
0.501000	31.08	---	56.00	24.92	N	OFF	19.5
0.802500	---	25.18	46.00	20.82	N	OFF	19.5
0.802500	27.48	---	56.00	28.52	N	OFF	19.5
1.812750	---	22.71	46.00	23.29	N	OFF	19.6
1.812750	23.62	---	56.00	32.38	N	OFF	19.6
4.681500	---	24.59	46.00	21.41	N	OFF	19.7
4.681500	25.41	---	56.00	30.59	N	OFF	19.7
15.065250	---	25.64	50.00	24.36	N	OFF	20.1
15.065250	27.30	---	60.00	32.70	N	OFF	20.1



### Appendix C. Radiated Spurious Emission

Test Engineer :	Andy Yang, Karl Hou, Leo Liu, and BigShow Wang	Temperature :	23.2~26.1°C
		Relative Humidity :	50.3~56.2%

2.4GHz 2400~2483.5MHz

BT (Band Edge @ 3m)

BT	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
BT CH00 2402MHz		2348.43	45.39	-28.61	74	42.52	27.7	6.18	31.01	336	130	P	H
		2348.43	20.6	-33.4	54	-	-	-	-	-	-	A	H
	*	2402	103.35	-	-	100.49	27.6	6.25	30.99	336	130	P	H
	*	2402	78.56	-	-	-	-	-	-	-	-	A	H
		2343.18	44.32	-29.68	74	41.45	27.7	6.18	31.01	390	207	P	V
		2343.18	19.53	-34.47	54	-	-	-	-	-	-	A	V
	*	2402	98.41	-	-	95.55	27.6	6.25	30.99	390	207	P	V
	*	2402	73.62	-	-	-	-	-	-	-	-	A	V
BT CH 39 2441MHz		2366	44.07	-29.93	74	41.19	27.67	6.21	31	100	154	P	H
		2366	19.28	-34.72	54	-	-	-	-	-	-	A	H
	*	2441	102.19	-	-	99.27	27.6	6.29	30.97	100	154	P	H
	*	2441	77.4	-	-	-	-	-	-	-	-	A	H
		2490.06	44.48	-29.52	74	41.68	27.4	6.34	30.94	100	154	P	H
		2490.06	19.69	-34.31	54	-	-	-	-	-	-	A	H
		2369.08	45.24	-28.76	74	42.4	27.63	6.21	31	177	78	P	V
		2369.08	20.45	-33.55	54	-	-	-	-	-	-	A	V
	*	2441	99.61	-	-	96.69	27.6	6.29	30.97	177	78	P	V
	*	2441	74.82	-	-	-	-	-	-	-	-	A	V
		2495.94	43.58	-30.42	74	40.77	27.4	6.35	30.94	177	78	P	V
		2495.94	18.79	-35.21	54	-	-	-	-	-	-	A	V



<b>BT CH 78 2480MHz</b>	*	2480	102.71	-	-	99.86	27.47	6.33	30.95	100	155	P	H	
	*	2480	77.92	-	-	-	-	-	-	-	-	A	H	
		2487.16	47.95	-26.05	74	45.09	27.47	6.34	30.95	100	155	P	H	
		2487.16	23.16	-30.84	54	-	-	-	-	-	-	A	H	
	*	2480	100.66	-	-	97.81	27.47	6.33	30.95	151	84	P	V	
	*	2480	75.87	-	-	-	-	-	-	-	-	-	A	V
		2484.28	46.06	-27.94	74	43.21	27.47	6.33	30.95	151	84	P	V	
		2484.28	21.27	-32.73	54	-	-	-	-	-	-	-	A	V
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.													



2.4GHz 2400~2483.5MHz  
BT (Harmonic @ 3m)

BT	Note	Frequency ( MHz )	Level ( dBµV/m )	Over Limit ( dB )	Limit Line ( dBµV/m )	Read Level ( dBµV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
BT CH 00 2402MHz		3600	44.15	-29.85	74	66.97	29.2	8.72	60.74	100	0	P	H
		3600	19.36	-34.64	54	-	-	-	-	-	-	A	H
		4804	37.38	-36.62	74	55.65	31.3	9.59	59.16	100	0	P	H
		4804	12.59	-41.41	54	-	-	-	-	-	-	A	H
		3600	43.04	-30.96	74	65.86	29.2	8.72	60.74	100	0	P	V
		3600	18.25	-35.75	54	-	-	-	-	-	-	A	V
		4804	37.18	-36.82	74	55.45	31.3	9.59	59.16	100	0	P	V
		4804	12.39	-41.61	54	-	-	-	-	-	-	A	V
BT CH 39 2441MHz		3660	43.04	-30.96	74	65.67	29.3	8.71	60.64	100	0	P	H
		3660	18.25	-35.75	54	-	-	-	-	-	-	A	H
		4882	37.3	-36.7	74	55.61	31.3	9.57	59.18	100	0	P	H
		4882	12.51	-41.49	54	-	-	-	-	-	-	A	H
		7323	42.13	-31.87	74	53.41	36.23	11.66	59.17	100	0	P	H
		7323	17.34	-36.66	54	-	-	-	-	-	-	A	H
		3660	41.7	-32.3	74	64.33	29.3	8.71	60.64	100	0	P	V
		3660	16.91	-37.09	54	-	-	-	-	-	-	A	V
		4882	37.52	-36.48	74	55.83	31.3	9.57	59.18	100	0	P	V
		4882	12.73	-41.27	54	-	-	-	-	-	-	A	V
		7323	42.12	-31.88	74	53.4	36.23	11.66	59.17	100	0	P	V
		7323	17.33	-36.67	54	-	-	-	-	-	-	A	V



<b>BT CH 78 2480MHz</b>		3720	43.45	-30.55	74	65.98	29.33	8.69	60.55	100	0	P	H
		3720	18.66	-35.34	54	-	-	-	-	-	-	A	H
		4960	40.61	-33.39	74	58.77	31.47	9.56	59.19	100	0	P	H
		4960	15.82	-38.18	54	-	-	-	-	-	-	A	H
		7440	43.54	-30.46	74	54.36	36.6	11.7	59.12	100	0	P	H
		7440	18.75	-35.25	54	-	-	-	-	-	-	A	H
		3720	41.39	-32.61	74	63.92	29.33	8.69	60.55	100	0	P	V
		3720	16.6	-37.4	54	-	-	-	-	-	-	A	V
		4960	40.07	-33.93	74	58.23	31.47	9.56	59.19	100	0	P	V
		4960	15.28	-38.72	54	-	-	-	-	-	-	A	V
		7440	44.06	-29.94	74	54.88	36.6	11.7	59.12	100	0	P	V
		7440	19.27	-34.73	54	-	-	-	-	-	-	A	V
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Emission below 1GHz

2.4GHz BT (LF)

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	(dBμV)	( dB/m )	( dB )	( dB )	( cm )	( deg )	(P/A)	(H/V)
2.4GHz BT LF		88.2	22	-21.5	43.5	38.81	14.44	1.28	32.53	-	-	P	H
		147.37	31.86	-11.64	43.5	45.35	17.36	1.65	32.5	-	-	P	H
		204.6	33.06	-10.44	43.5	48.42	15.18	1.95	32.49	-	-	P	H
		232.73	33.63	-12.37	46	47.65	16.47	2.02	32.51	-	-	P	H
		265.71	36.71	-9.29	46	47.15	19.86	2.22	32.52	100	0	P	H
		718.7	34.33	-11.67	46	36.11	27.12	3.46	32.36	-	-	P	H
		40.67	31.4	-8.6	40	43.76	19.4	0.84	32.6	-	-	P	V
		147.37	23.77	-19.73	43.5	37.26	17.36	1.65	32.5	-	-	P	V
		202.66	29.12	-14.38	43.5	44.55	15.11	1.95	32.49	-	-	P	V
		259.89	37.79	-8.21	46	48.14	19.98	2.19	32.52	100	0	P	V
		379.2	26.5	-19.5	46	35.44	21.08	2.53	32.55	-	-	P	V
	677.96	29.73	-16.27	46	32.21	26.6	3.36	32.44	-	-	P	V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



**Note symbol**

*	<b>Fundamental Frequency</b> which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is <b>over limit</b> line.
P/A	<b>Peak</b> or <b>Average</b>
H/V	<b>Horizontal</b> or <b>Vertical</b>



A calculation example for radiated spurious emission is shown as below:

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
		( MHz )	( dBμV/m )	( dB )	Limit Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
					( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
BT		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 00		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H
2402MHz													

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
2. Level(dBμV/m) =  
Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
3. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

**For Peak Limit @ 2390MHz:**

1. Level(dBμV/m)  
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)  
= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)  
= 55.45 (dBμV/m)
2. Over Limit(dB)  
= Level(dBμV/m) – Limit Line(dBμV/m)  
= 55.45(dBμV/m) – 74(dBμV/m)  
= -18.55(dB)

**For Average Limit @ 2390MHz:**

1. Level(dBμV/m)  
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)  
= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)  
= 43.54 (dBμV/m)
2. Over Limit(dB)  
= Level(dBμV/m) – Limit Line(dBμV/m)  
= 43.54(dBμV/m) – 54(dBμV/m)  
= -10.46(dB)

**Both peak and average measured complies with the limit line, so test result is “PASS”.**



## Appendix D. Radiated Spurious Emission Plots



Test Engineer :	Andy Yang, Karl Hou, Leo Liu, and BigShow Wang	Temperature :	23.2~26.1°C
		Relative Humidity :	50.3~56.2%

### 2.4GHz 2400~2483.5MHz




#### BT (Band Edge @ 3m)

BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BT CH00 2402MHz	
	Horizontal	Fundamental
Peak	<p>Site : 03CH15-HY            Condition : PEAK_BE_74 3m 9120d_15_1620 HORIZONTAL            : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto            Detector : Peak            Project : 941514-01            Mode : 1</p>	<p>Site : 03CH15-HY            Condition : PEAK_74 3m 9120d_15_1620 HORIZONTAL            : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto            Detector : Peak            Project : 941514-01            Mode : 1</p>






BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BT CH00 2402MHz		
	Vertical	Fundamental
Peak	 <p>Date: 2019-07-28</p> <p>Site : 03CH15-HY Condition : PEAK_8E_74 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 941514-01 Mode : 1</p>	 <p>Date: 2019-07-28</p> <p>Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 941514-01 Mode : 1</p>





BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BT CH39 2441MHz		
	Horizontal	Fundamental
Peak	 <p>Date: 2019-07-28</p> <p>Site : 03CH15-HY            Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 941514-01            Mode : 2</p>	 <p>Date: 2019-07-28</p> <p>Site : 03CH15-HY            Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 941514-01            Mode : 2</p>
Peak	 <p>Date: 2019-07-28</p> <p>Site : 03CH15-HY            Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 941514-01            Mode : 2</p>	Left blank





BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BT CH39 2441MHz		
	Vertical	Fundamental
Peak	 <p>Date: 2019-07-28</p> <p>Site : 03CH15-HY            Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL            : RBW:1000.000KHz VBW:3000.000KHz SWF:Auto            Detector : Peak            Project : 941514-01            Mode : 2</p>	 <p>Date: 2019-07-28</p> <p>Site : 03CH15-HY            Condition : PEAK_74 3m 91200_15_1620 VERTICAL            : RBW:1000.000KHz VBW:3000.000KHz SWF:Auto            Detector : Peak            Project : 941514-01            Mode : 2</p>
Peak	 <p>Date: 2019-07-28</p> <p>Site : 03CH15-HY            Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL            : RBW:1000.000KHz VBW:3000.000KHz SWF:Auto            Detector : Peak            Project : 941514-01            Mode : 2</p>	Left blank



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BT CH78 2480MHz		
	Horizontal	Fundamental
<b>Peak</b>	 <p>Date: 2019-07-28</p> <p>Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 941514-01 Mode : 3</p>	 <p>Date: 2019-07-28</p> <p>Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 941514-01 Mode : 3</p>



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BT CH78 2480MHz		
	Vertical	Fundamental
Peak	 <p>Date: 2019-07-28</p> <p>Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 941514-01 Mode : 3</p>	 <p>Date: 2019-07-28</p> <p>Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 941514-01 Mode : 3</p>





2.4GHz 2400~2483.5MHz



BT (Harmonic @ 3m)

BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BT CH00 2402MHz	
	Horizontal	Vertical
<b>Peak</b> <b>Avg.</b>	<p>Site : 03CH15-1FY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 941514-01 Mode : 1</p>	<p>Site : 03CH15-1FY Condition : PEAK_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 941514-01 Mode : 1</p>



<b>BT</b>	<b>2.4GHz 2400~2483.5MHz Harmonic @ 3m</b>	
	<b>BT CH39 2441MHz</b>	
	<b>Horizontal</b>	<b>Vertical</b>
<b>Peak</b> <b>Avg.</b>	 <p>Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 941514-01 Mode : 2</p>	 <p>Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 941514-01 Mode : 2</p>





BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
BT CH78 2480MHz		
	Horizontal	Vertical
<p><b>Peak</b> <b>Avg.</b></p>	 <p>Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 941514-01 Mode : 3</p>	 <p>Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 941514-01 Mode : 3</p>




Emission below 1GHz

2.4GHz BT (LF)


BT	2.4GHz 2400~2483.5MHz	
BT LF		
	Horizontal	Vertical
<p>QP / Peak</p>	 <p>Site : 03CH15-FY Condition : QP 3m BTL0G_15_41912 HORIZONTAL Detector : Peak Project : 941514-01 Mode : 30</p>	 <p>Site : 03CH15-FY Condition : QP 3m BTL0G_15_41912 VERTICAL Detector : Peak Project : 941514-01 Mode : 30</p>

## Appendix E. Duty Cycle Plots

DH5 on time (One Pulse) Plot on Channel 39



on time (Count Pulses) Plot on Channel 39



**Note:**

1. Worst case Duty cycle = on time/100 milliseconds =  $2 * 2.88 / 100 = 5.76 \%$
2. Worst case Duty cycle correction factor =  $20 * \log(\text{Duty cycle}) = -24.79 \text{ dB}$
3. DH5 has the highest duty cycle worst case and is reported.



**Duty Cycle Correction Factor Consideration for AFH mode:**

Bluetooth normal hopping rate is 1600Hz and reduced to 800Hz in AFH mode; due to the reduced number of hopping frequencies, with the same packet configuration the dwell time in each channel frequency within 100msec period is longer in AFH mode than normal mode.

In AFH mode, the minimum hopping frequencies are 20, to get the longest dwell time DH5 packet is observed; the period to have DH5 packet completing one hopping sequence is

$$2.88 \text{ ms} \times 20 \text{ channels} = 57.6 \text{ ms}$$

There cannot be 2 complete hopping sequences within 100ms period, considering the random hopping behavior, maximum 2 hops can be possibly observed within the period.  $[100\text{ms} / 57.6\text{ms}] = 2$  hops

Thus, the maximum possible ON time:

$$2.88 \text{ ms} \times 2 = 5.76 \text{ ms}$$

Worst case Duty Cycle Correction factor, which is derived from the maximum possible ON time,

$$20 \times \log(5.76 \text{ ms}/100\text{ms}) = -24.79 \text{ dB}$$

—————THE END—————