



# TEST REPORT

Applicant Name : HDTELECOM  
Address : #708, E&C Venture Dream Tower 6th, 41, Digital-ro 31-gil,  
Guro-gu, Seoul, South Korea 08375  
Report Number : SZNS211118-59299E-RF-00C  
FCC ID: 2ASQU-PHOENIXNOTE

## Test Standard (s)

FCC PART 15.407

## Sample Description

Product Type: Phoenix Note  
Model No.: PPS2022-P156  
Multiple Model(s) No.: 1501A, 1502A, 1503A(Please refer to DOS for Model  
difference)  
Trade Mark: N/A  
Date Received: 2021/11/18  
Date of Test: 2021/12/01~2022/01/27  
Report Date: 2022/01/27

Test Result:	Pass*
--------------	-------

\* In the configuration tested, the EUT complied with the standards above.

## Prepared and Checked By:

*Black Ding*

Black Ding  
EMC Engineer

## Approved By:

*Robert Li*

Robert Li  
EMC Engineer

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "\*" .

Shenzhen Accurate Technology Co., Ltd. is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk "\*\*". Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

## Shenzhen Accurate Technology Co., Ltd.

1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China  
Tel: +86 755-26503290 Fax: +86 755-26503396 Web: www.atc-lab.com

## TABLE OF CONTENTS

<b>GENERAL INFORMATION</b> .....	<b>4</b>
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
OBJECTIVE .....	4
TEST METHODOLOGY .....	4
MEASUREMENT UNCERTAINTY.....	5
TEST FACILITY .....	5
<b>SYSTEM TEST CONFIGURATION</b> .....	<b>6</b>
DESCRIPTION OF TEST CONFIGURATION .....	6
EUT EXERCISE SOFTWARE .....	7
DUTY CYCLE .....	7
EQUIPMENT MODIFICATIONS .....	14
SUPPORT EQUIPMENT LIST AND DETAILS .....	14
EXTERNAL I/O CABLE.....	14
BLOCK DIAGRAM OF TEST SETUP .....	15
<b>SUMMARY OF TEST RESULTS</b> .....	<b>17</b>
<b>TEST EQUIPMENT LIST</b> .....	<b>18</b>
<b>FCC §1.1307(B) &amp; §2.1093 - RF EXPOSURE INFORMATION</b> .....	<b>20</b>
APPLICABLE STANDARD .....	20
TEST RESULT .....	20
<b>FCC §15.203 – ANTENNA REQUIREMENT</b> .....	<b>21</b>
APPLICABLE STANDARD .....	21
ANTENNA CONNECTOR CONSTRUCTION .....	21
<b>FCC §15.407 (B) (6) §15.207 (A) – CONDUCTED EMISSIONS</b> .....	<b>22</b>
APPLICABLE STANDARD .....	22
EUT SETUP.....	22
EMI TEST RECEIVER SETUP.....	22
TEST PROCEDURE .....	22
TRANSD FACTOR & MARGIN CALCULATION.....	23
TEST DATA .....	23
<b>§15.205 &amp; §15.209 &amp; §15.407(B)– UNDESIRABLE EMISSION</b> .....	<b>26</b>
APPLICABLE STANDARD .....	26
EUT SETUP .....	26
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP .....	27
TEST PROCEDURE .....	27
FACTOR & MARGIN CALCULATION .....	28
TEST DATA .....	28
<b>FCC §15.407(A),(E) – 26 DB &amp; 6DB EMISSION BANDWIDTH</b> .....	<b>45</b>
APPLICABLE STANDARD .....	45
TEST PROCEDURE .....	45
TEST DATA .....	46

**FCC §15.407(A) – CONDUCTED TRANSMITTER OUTPUT POWER.....69**  
    APPLICABLE STANDARD .....69  
    TEST PROCEDURE .....69  
    TEST DATA .....70

**FCC §15.407(A) - POWER SPECTRAL DENSITY .....72**  
    TEST PROCEDURE .....72  
    TEST DATA .....73

## GENERAL INFORMATION

### Product Description for Equipment under Test (EUT)

Frequency Range	5G Wi-Fi: 5150-5250MHz; 5725-5850MHz
Mode	802.11a/n20/n40/ac20/ac40/ac80
Maximum Conducted Average Output Power	5150-5250 MHz: 7.10dBm 5725-5850 MHz: 11.73dBm
Modulation Technique	OFDM
Antenna Specification*	Antenna: 2.0 dBi (provided by the applicant)
Voltage Range	DC 7.6V from battery or DC 5.0V/9.0V/12.0V/15.0V from adapter
Sample serial number	SZNS211118-59299E-RF-S1 for Conducted and Radiation Emissions SZNS211118-59299E-RF-S2 for RF Conducted Test (Assigned by ATC)
Sample/EUT Status	Good condition
Adapter information	Model: FJ-SW360ARN Input: AC 100-240V, 50/60Hz, 1.2A Max Output: DC 5.0V, 3.0A, 15.0W Max or DC 9.0V, 3.0A, 27.0W Max or DC 12.0V, 3.0A, 36.0W Max or DC 15.0V, 2.4A, 36.0W Max

### Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and E of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart E, section 15.203, 15.205, 15.207, 15.209 and 15.407 rules.

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices. And KDB789033 D02 General U-NII Test Procedures New Rules v02r01.

All emissions measurement was performed at Shenzhen Accurate Technology Co., Ltd. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Each test item follows test standards and with no deviation.

## Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		5%
RF Frequency		$0.082 \times 10^{-7}$
RF output power, conducted		0.73dB
Unwanted Emission, conducted		1.6dB
AC Power Lines Conducted Emissions		2.72dB
Emissions, Radiated	9kHz - 30MHz	2.66dB
	30MHz - 1GHz	4.28dB
	1GHz - 18GHz	4.98dB
	18GHz - 26.5GHz	5.06dB
	26.5GHz - 40GHz	4.72dB
Temperature		1°C
Humidity		6%
Supply voltages		0.4%

*Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.*

## Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the 1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 708358, the FCC Designation No.: CN1189. Accredited by American Association for Laboratory Accreditation (A2LA) The Certificate Number is 429 7.01.

Listed by Innovation, Science and Economic Development Canada (ISED), the Registration Number is 5077A.

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration

The system was configured for testing in an engineering mode, which was provided by manufacturer.

The device support 5G Wi-Fi 802.11a/n20/n40/ac20/ac40/ac80 modes.

For 5150-5250MHz Band, 7 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	44	5220
38	5190	46	5230
40	5200	48	5240
42	5210	/	/

For 802.11a/n20/ac20 mode: channel 36, 40, 48 were tested;

For 802.11n40/ac40 mode: channel 38, 46 were tested;

For 802.11ac80 mode, channel 42 was tested.

For 5725-5850MHz Band, 8 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	157	5785
151	5755	159	5795
153	5765	161	5805
155	5775	165	5825

For 802.11a/n20/ac20 mode: channel 149, 157, 165 were tested;

For 802.11n40/ac40 mode: channel 151, 159 were tested;

For 802.11ac80 mode, channel 155 was tested.

## EUT Exercise Software

“Command window” was used.

The worst case was performed under:

U-NII	Mode	Data rate	Power Level*		
			Low Channel	Middle Channel	High Channel
5150 – 5250MHz	802.11a	6Mbps	40	40	40
	802.11n-HT20	MCS0	40	40	40
	802.11n-HT40	MCS0	40	/	40
	802.11ac20	MCS0	40	40	40
	802.11ac40	MCS0	40	/	40
	802.11ac80	MCS0	/	40	/
5725 – 5850MHz	802.11a	6Mbps	default	default	default
	802.11n-HT20	MCS0	default	default	default
	802.11n-HT40	MCS0	default	/	default
	802.11ac20	MCS0	default	default	default
	802.11ac40	MCS0	default	/	default
	802.11ac80	MCS0	/	default	/

The worse-case data rates are determined to be as follows for each mode based upon investigations by measuring the output power and PSD across all data rated bandwidths, and modulations.

The power level was provided by the applicant.


## Duty cycle

Band	Band	T(ms)	1/T(kHz)	Duty Cycle (%)	Duty Cycle Factor (dB)
5150 – 5250MHz	802.11a	0.186	0.217	85.71	0.67
	802.11n20	0.173	0.204	84.80	0.72
	802.11n40	0.106	0.139	76.26	1.18
	802.11ac20	0.157	0.188	83.51	0.78
	802.11ac40	0.095	0.127	74.80	1.26
	802.11ac80	0.071	0.104	68.27	1.66
5725 – 5850MHz	802.11a	0.186	0.216	86.11	0.65
	802.11n20	0.173	0.204	84.80	0.72
	802.11n40	0.107	0.139	76.98	1.14
	802.11ac20	0.157	0.189	83.07	0.81
	802.11ac40	0.095	0.128	74.22	1.29
	802.11ac80	0.070	0.104	67.31	1.72

Note: Duty cycle factor= $10 \cdot \log(1/\text{duty cycle})$


5150-5250 MHz:

802.11a mode




Date: 16.DEC.2021 00:08:08

802.11n20 mode




Date: 16.DEC.2021 00:06:56

802.11n40 mode




Date: 16.DEC.2021 00:05:57

802.11ac20 Mode




Date: 16.DEC.2021 00:04:52

### 802.11ac40 mode



Date: 16.DEC.2021 00:03:58


### 802.11ac80 Mode



Date: 16.DEC.2021 00:02:52


5725 – 5850MHz:

802.11a mode




Date: 16.DEC.2021 19:29:32

802.11n20 mode




Date: 16.DEC.2021 19:30:21

### 802.11n40 mode




Date: 16.DEC.2021 19:34:23

### 802.11ac20 Mode




Date: 16.DEC.2021 19:31:12

### 802.11ac40 mode



Date: 16.DEC.2021 19:32:25

### 802.11ac80 Mode



Date: 16.DEC.2021 19:35:35

### Equipment Modifications

No modification was made to the EUT tested.

### Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
Sandisk	USB disk	SDCZ38	BL210426179Z
DELL	PC	Latitude E5430	JG3NLV1
Sandisk	SD card	Unknown	SD card

### External I/O Cable


Cable Description	Length (m)	From Port	To
Un-shielding Detachable DC Cable	1.0	Adapter	EUT
Un-shielding Detachable Type-C to HDMI Cable	1.2	EUT	PC
Un-shielding Un-Detachable Audio Cable	1.0	Earphone	EUT

### Block Diagram of Test Setup


#### For Conducted Emissions



#### For Spurious Emissions(Below 1G)



**For Spurious Emissions(Above 1G)**



## SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1307 (b) (1) & §2.1093	RF Exposure	Compliant
§15.203	Antenna Requirement	Compliant
§15.407(b)(9)& §15.207(a)	Conducted Emissions	Compliant
§15.205& §15.209 &§15.407(b)	Undesirable Emission& Restricted Bands	Compliant
§15.407(a) (e)	26 dB Emission Bandwidth & 6dB Bandwidth	Compliant
§15.407(a)	Conducted Transmitter Output Power	Compliant
§15.407 (a)	Power Spectral Density	Compliant
§15.407 (h)	Transmit Power Control (TPC)	Not Applicable
§15.407 (h)	Dynamic Frequency Selection (DFS)	Not Applicable*

Not Applicable: the EUT has no TPC function which was declared by the applicant.

Not Applicable\*: the EUT not operating within frequency range of 5250-5350MHz&5470-5725MHz.

**TEST EQUIPMENT LIST**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emissions Test					
Rohde& Schwarz	EMI Test Receiver	ESCI	100784	2021/12/13	2022/12/12
Rohde & Schwarz	L.I.S.N.	ENV216	101314	2021/12/13	2022/12/12
Anritsu Corp	50 Coaxial Switch	MP59B	6100237248	2021/12/13	2022/12/12
Unknown	RF Coaxial Cable	No.17	N0350	2021/12/14	2022/12/13
Conducted Emission Test Software: e3 19821b (V9)					
Radiated Emissions Test					
Rohde& Schwarz	Test Receiver	ESR	102725	2021/12/13	2022/12/12
Rohde&Schwarz	Spectrum Analyzer	FSV40	101949	2020/12/13	2021/12/12
SONOMA INSTRUMENT	Amplifier	310 N	186131	2021/11/09	2022/11/08
A.H. Systems, inc.	Preamplifier	PAM-0118P	135	2021/11/09	2022/11/08
Quinstar	Amplifier	QLW-18405536-J0	15964001002	2021/11/11	2022/11/10
Schwarzbeck	Bilog Antenna	VULB9163	9163-323	2021/07/06	2024/07/05
Schwarzbeck	Horn Antenna	BBHA9120D	9120D-1067	2020/01/05	2023/01/04
Schwarzbeck	HORN ANTENNA	BBHA9170	9170-359	2020/01/05	2023/01/04
Radiated Emission Test Software: e3 19821b (V9)					
Unknown	RF Coaxial Cable	No.10	N050	2020/12/14	2021/12/13
Unknown	RF Coaxial Cable	No.11	N1000	2020/12/14	2021/12/13
Unknown	RF Coaxial Cable	No.12	N040	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.13	N300	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.14	N800	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.15	N600	2020/12/14	2021/12/13
Unknown	RF Coaxial Cable	No.16	N650	2020/12/14	2021/12/13
CD	Band Reject Filter	BRM-5.15/5.35g-45	075	2020/12/14	2021/12/13
CD	Band Reject Filter	BRM-5.725/5.875G-45	065	2020/12/14	2021/12/13

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
RF Conducted Test					
SPECTRUM ANALYZER	Rohde & Schwarz	FSU26	200982	2021/07/06	2022/07/05
WEINSCHTEL	10dB Attenuator	5324	AU 3842	2021/12/14	2022/12/13
Rohde & Schwarz	Open Switch and Control Unit	OSP120 + OSP-B157	101244 + 100866	2021/12/13	2022/12/12

\* **Statement of Traceability:** Shenzhen Accurate Technology Co., Ltd. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

---

## **FCC §1.1307(b) & §2.1093 - RF EXPOSURE INFORMATION**

---

### Applicable Standard

FCC§1.1310 and §2.1093.

### Test Result

Compliant, please refer to the SAR report: SZNS211118-59299E-SA.

## **FCC §15.203 – ANTENNA REQUIREMENT**

---

### **Applicable Standard**

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.407 (a), if the transmitting antennas of directional gain greater than 6dBi are used, the transmit power and power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### **Antenna Connector Construction**

The EUT has two internal antennas arrangement for 5G Wi-Fi which were permanently attached, one for 802.11 n20/ac40 mode, another for 802.11 a/ac20/n40/ac80 mode, both the antenna gain is 2dBi. Please refer to the EUT photos.


**Result:** Compliant.

## FCC §15.407 (b) (6) §15.207 (a) – CONDUCTED EMISSIONS

### Applicable Standard

FCC §15.207, §15.407(b) (6)

### EUT Setup



- Note: 1. Support units were connected to second LISN.  
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

### EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

### Test Procedure

During the conducted emission test, the adapter was connected to the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and Average detection mode.

### Transd Factor & Margin Calculation

The Transd factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Transd Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Over Limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a over limit of -7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\begin{aligned} \text{Over Limit} &= \text{level} - \text{Limit} \\ \text{Level} &= \text{reading level} + \text{Transd Factor} \end{aligned}$$

### Test Data


#### Environmental Conditions

<b>Temperature:</b>	22 °C
<b>Relative Humidity:</b>	54 %
<b>ATM Pressure:</b>	101.0 kPa

*The testing was performed by Bin Duan on 2022-01-18.*


*EUT operation mode: Transmitting (worst case is 802.11a, 5785MHz)*

AC 120V/60 Hz, Line:



	Freq	Factor	Read Level	Limit Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.185	9.80	33.01	42.81	54.27	-11.46	Average
2	0.185	9.80	43.86	53.66	64.27	-10.61	QP
3	0.202	9.80	30.62	40.42	53.54	-13.12	Average
4	0.202	9.80	40.81	50.61	63.54	-12.93	QP
5	0.430	9.80	27.27	37.07	47.25	-10.18	Average
6	0.430	9.80	32.91	42.71	57.25	-14.54	QP
7	0.525	9.81	24.62	34.43	46.00	-11.57	Average
8	0.525	9.81	31.77	41.58	56.00	-14.42	QP
9	4.991	9.85	20.27	30.12	46.00	-15.88	Average
10	4.991	9.85	26.07	35.92	56.00	-20.08	QP
11	7.476	9.87	28.25	38.12	50.00	-11.88	Average
12	7.476	9.87	32.31	42.18	60.00	-17.82	QP

**AC 120V/60 Hz, Neutral:**



	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.185	9.80	33.86	43.66	54.26	-10.60	Average
2	0.185	9.80	43.82	53.62	64.26	-10.64	QP
3	0.206	9.80	28.77	38.57	53.35	-14.78	Average
4	0.206	9.80	39.33	49.13	63.35	-14.22	QP
5	0.491	9.80	25.98	35.78	46.15	-10.37	Average
6	0.491	9.80	34.61	44.41	56.15	-11.74	QP
7	0.606	9.81	26.43	36.24	46.00	-9.76	Average
8	0.606	9.81	35.00	44.81	56.00	-11.19	QP
9	2.041	9.82	21.29	31.11	46.00	-14.89	Average
10	2.041	9.82	26.11	35.93	56.00	-20.07	QP
11	7.348	9.97	26.26	36.23	50.00	-13.77	Average
12	7.348	9.97	30.51	40.48	60.00	-19.52	QP

## §15.205 & §15.209 & §15.407(B)– UNDESIRABLE EMISSION

### Applicable Standard

FCC §15.407 (b); §15.209; §15.205;


(b) Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:


- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of  $-27$  dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of  $-27$  dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of  $-27$  dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band:
  - (i) All emissions shall be limited to a level of  $-27$  dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209.

### EUT Setup

**Below 1 GHz:**



**Above 1 GHz:**

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC 15.209 and FCC 15.407 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

**EMI Test Receiver & Spectrum Analyzer Setup**

The system was investigated from 30 MHz to 40 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1 MHz	3 MHz	/	PK
	1MHz	10 Hz <sup>Note 1</sup>	/	Average
	1MHz	> 1/T <sup>Note 2</sup>	/	Average

Note 1: when duty cycle is no less than 98%

Note 2: when duty cycle is less than 98%

**Test Procedure****Radiated Spurious Emission**

During the radiated emission test, the adapter was connected to the AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all the installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1GHz, peak and Average detection modes for frequencies above 1GHz.

According to ANSI C63.10-2013,9.4: For field strength measurements made at other than the distance at which the applicable limit is specified, extrapolate the measured field strength to the field strength at the distance specified by the limit using an inverse distance correction factor (20 dB/decade of distance). In some cases, a different distance correction factor may be required;

$$E_{\text{SpecLimit}} = E_{\text{Meas}} + 20 \log \left( \frac{d_{\text{Meas}}}{d_{\text{SpecLimit}}} \right)$$

where

$E_{\text{SpecLimit}}$	is the field strength of the emission at the distance specified by the limit, in dB $\mu$ V/m
$E_{\text{Meas}}$	is the field strength of the emission at the measurement distance, in dB $\mu$ V/m
$d_{\text{Meas}}$	is the measurement distance, in m
$d_{\text{SpecLimit}}$	is the distance specified by the limit, in m

So the extrapolation factor of 1m is  $20 * \log(1/3) = -9.5$  dB

### Factor & Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit or Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a over limit/margin of -7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\begin{aligned} \text{Margin/Over Limit} &= \text{Corrected Amplitude/Level-Limit} \\ \text{Corrected Amplitude/Level} &= \text{Reading} + \text{Corrected Factor} \end{aligned}$$

### Test Data

#### Environmental Conditions


<b>Temperature:</b>	21~25 °C
<b>Relative Humidity:</b>	62~64 %
<b>ATM Pressure:</b>	101.0 kPa

The testing was performed by Chao Mo on 2021-12-23 for below 1GHz and Bin Deng on 2021-12-01 for above 1GHz.

EUT operation mode: Transmitting(Scan with X-AXIS, Y-AXIS, Z-AXIS, the worst case was recorded)

**30 MHz – 1 GHz:** (worst case is 802.11a, 5785MHz)


Horizontal



Site : chamber  
 Condition: 3m HORIZONTAL  
 Job No. : SZNS211118-59299E-RF  
 Test Mode: 5G WIFI

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	75.18	-16.27	44.68	28.41	40.00	-11.59	Peak
2	126.33	-14.45	44.00	29.55	43.50	-13.95	Peak
3	192.50	-11.27	43.88	32.61	43.50	-10.89	Peak
4	208.76	-11.86	49.27	37.41	43.50	-6.09	QP
5	240.83	-10.85	50.18	39.33	46.00	-6.67	QP
6	325.60	-8.23	46.38	38.15	46.00	-7.85	QP

Vertical



Site : chamber  
 Condition: 3m VERTICAL  
 Job No. : SZNS211118-59299E-RF  
 Test Mode: 5G WIFI

	Freq Factor		Read Level		Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	38.97	-10.59	42.68	32.09	40.00	-7.91	Peak
2	76.21	-16.44	48.65	32.21	40.00	-7.79	Peak
3	208.85	-11.86	42.01	30.15	43.50	-13.35	Peak
4	290.65	-9.30	42.15	32.85	46.00	-13.15	Peak
5	330.34	-7.97	42.33	34.36	46.00	-11.64	Peak
6	490.53	-4.65	34.96	30.31	46.00	-15.69	Peak

**Above 1GHz:****5150-5250 MHz:**

Frequency (MHz)	Receiver		Turn-Table Angle Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dB $\mu$ V/m)	FCC Part 15.407	
	Reading (dB $\mu$ V)	PK/QP/AV		Height (m)	Polar (H / V)			Limit (dB $\mu$ V/m)	Margin (dB)
802.11a									
5180 MHz									
4500	63.75	PK	64	1.5	H	-4.72	59.03	74	-14.97
4500	52.78	AV	64	1.5	H	-4.72	48.06	54	-5.94
4500	67.08	PK	81	1	V	-4.72	62.36	74	-11.64
4500	55.59	AV	81	1	V	-4.72	50.87	54	-3.13
5150	62.18	PK	302	2.4	H	-2.73	59.45	74	-14.55
5150	50.77	AV	302	2.4	H	-2.73	48.04	54	-5.96
5150	65.12	PK	8	1.6	V	-2.73	62.39	74	-11.61
5150	51.91	AV	8	1.6	V	-2.73	49.18	54	-4.82
10360	41.32	PK	16	2.1	H	8.12	49.44	68.2	-18.76
10360	40.93	PK	280	2.1	V	8.12	49.05	68.2	-19.15
5200 MHz									
10400	41.31	PK	44	1.2	H	8.24	49.55	68.2	-18.65
10400	41.06	PK	277	1.2	V	8.24	49.3	68.2	-18.90
5240 MHz									
5350	64.90	PK	359	2.2	H	-2.33	62.57	74	-11.43
5350	52.51	AV	359	2.2	H	-2.33	50.18	54	-3.82
5350	63.25	PK	84	2.4	V	-2.33	60.92	74	-13.08
5350	52.72	AV	84	2.4	V	-2.33	50.39	54	-3.61
5460	64.35	PK	252	2.2	H	-2.26	62.09	74	-11.91
5460	52.35	AV	252	2.2	H	-2.26	50.09	54	-3.91
5460	63.97	PK	313	1.4	V	-2.26	61.71	74	-12.29
5460	52.96	AV	313	1.4	V	-2.26	50.70	54	-3.30
10480	41.05	PK	289	1.7	H	8.56	49.61	68.2	-18.59
10480	40.22	PK	104	1.7	V	8.56	48.78	68.2	-19.42

Frequency (MHz)	Receiver		Turn- Table Angle Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dB $\mu$ V/m)	FCC Part15.407	
	Reading (dB $\mu$ V)	PK/QP/AV		Height (m)	Polar (H / V)			Limit (dB $\mu$ V/m)	Margin (dB)
802.11n20									
5180 MHz									
4500	64.16	PK	143	1.9	H	-4.72	59.44	74	-14.56
4500	51.08	AV	143	1.9	H	-4.72	46.36	54	-7.64
4500	72.42	PK	135	2.2	V	-4.72	67.70	74	-6.30
4500	53.93	AV	135	2.2	V	-4.72	49.21	54	-4.79
5150	61.93	PK	324	1.4	H	-2.73	59.20	74	-14.80
5150	49.19	AV	324	1.4	H	-2.73	46.46	54	-7.54
5150	64.16	PK	116	1.6	V	-2.73	61.43	74	-12.57
5150	51.08	AV	116	1.6	V	-2.73	48.35	54	-5.65
10360	41.35	PK	138	2.5	H	8.12	49.47	68.2	-18.73
10360	40.96	PK	328	2.5	V	8.12	49.08	68.2	-19.12
5200 MHz									
10400	41.72	PK	66	2.3	H	8.24	49.96	68.2	-18.24
10400	41.25	PK	183	2.3	V	8.24	49.49	68.2	-18.71
5240 MHz									
5350	64.43	PK	22	1.7	H	-2.33	62.10	74	-11.90
5350	52.90	AV	22	1.7	H	-2.33	50.57	54	-3.43
5350	64.20	PK	337	1.4	V	-2.33	61.87	74	-12.13
5350	52.79	AV	337	1.4	V	-2.33	50.46	54	-3.54
5460	64.55	PK	260	1.8	H	-2.26	62.29	74	-11.71
5460	52.66	AV	260	1.8	H	-2.26	50.40	54	-3.60
5460	63.38	PK	173	1.7	V	-2.26	61.12	74	-12.88
5460	52.72	AV	173	1.7	V	-2.26	50.46	54	-3.54
10480	40.83	PK	259	1.7	H	8.56	49.39	68.2	-18.81
10480	40.46	PK	45	1.7	V	8.56	49.02	68.2	-19.18

Frequency (MHz)	Receiver		Turn-Table Angle Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dB $\mu$ V/m)	FCC Part15.407	
	Reading (dB $\mu$ V)	PK/QP/Ave.		Height (m)	Polar (H / V)			Limit (dB $\mu$ V/m)	Margin (dB)
802.11n40									
5190 MHz									
4500	64.01	PK	307	1.2	H	-4.72	59.29	74	-14.71
4500	53.15	AV	307	1.2	H	-4.72	48.43	54	-5.57
4500	67.54	PK	322	2.3	V	-4.72	62.82	74	-11.18
4500	55.56	AV	322	2.3	V	-4.72	50.84	54	-3.16
5150	62.50	PK	156	1.3	H	-2.73	59.77	74	-14.23
5150	51.22	AV	156	1.3	H	-2.73	48.49	54	-5.51
5150	65.62	PK	351	1.2	V	-2.73	62.89	74	-11.11
5150	53.14	AV	351	1.2	V	-2.73	50.41	54	-3.59
10380	41.55	PK	36	1.4	H	8.18	49.73	68.2	-18.47
10380	41.16	PK	94	1.4	V	8.18	49.34	68.2	-18.86
5230 MHz									
5350	64.66	PK	326	1.2	H	-2.33	62.33	74	-11.67
5350	52.43	AV	326	1.2	H	-2.33	50.10	54	-3.90
5350	63.91	PK	201	1.9	V	-2.33	61.58	74	-12.42
5350	52.79	AV	201	1.9	V	-2.33	50.46	54	-3.54
5460	64.44	PK	254	1.3	H	-2.26	62.18	74	-11.82
5460	52.35	AV	254	1.3	H	-2.26	50.09	54	-3.91
5460	63.75	PK	82	2.2	V	-2.26	61.49	74	-12.51
5460	52.95	AV	82	2.2	V	-2.26	50.69	54	-3.31
10460	40.87	PK	66	1.7	H	8.47	49.34	68.2	-18.86
10460	40.42	PK	97	1.7	V	8.47	48.89	68.2	-19.31

Frequency (MHz)	Receiver		Turn-Table Angle Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dB $\mu$ V/m)	FCC Part15.407	
	Reading (dB $\mu$ V)	PK/QP/Ave.		Height (m)	Polar (H / V)			Limit (dB $\mu$ V/m)	Margin (dB)
802.11ac20									
5180 MHz									
4500	63.67	PK	260	1.7	H	-4.72	58.95	74	-15.05
4500	53.27	AV	260	1.7	H	-4.72	48.55	54	-5.45
4500	65.51	PK	205	2.1	V	-4.72	60.79	74	-13.21
4500	55.66	AV	205	2.1	V	-4.72	50.94	54	-3.06
5150	62.18	PK	16	2.2	H	-2.73	59.45	74	-14.55
5150	51.86	AV	16	2.2	H	-2.73	49.13	54	-4.87
5150	65.12	PK	174	1.7	V	-2.73	62.39	74	-11.61
5150	53.39	AV	174	1.7	V	-2.73	50.66	54	-3.34
10360	41.34	PK	98	2.1	H	8.12	49.46	68.2	-18.74
10360	40.85	PK	221	2.1	V	8.12	48.97	68.2	-19.23
5200 MHz									
10400	41.76	PK	191	1.4	H	8.24	50	68.2	-18.20
10400	41.14	PK	50	1.4	V	8.24	49.38	68.2	-18.82
5240 MHz									
5350	64.85	PK	70	1.9	H	-2.33	62.52	74	-11.48
5350	52.80	AV	70	1.9	H	-2.33	50.47	54	-3.53
5350	63.91	PK	134	1	V	-2.33	61.58	74	-12.42
5350	53.02	AV	134	1	V	-2.33	50.69	54	-3.31
5460	64.57	PK	171	1.3	H	-2.26	62.31	74	-11.69
5460	52.45	AV	171	1.3	H	-2.26	50.19	54	-3.81
5460	64.05	PK	6	1.9	V	-2.26	61.79	74	-12.21
5460	52.73	AV	6	1.9	V	-2.26	50.47	54	-3.53
10480	41.07	PK	6	1.7	H	8.56	49.63	68.2	-18.57
10480	40.40	PK	145	1.7	V	8.56	48.96	68.2	-19.24

Frequency (MHz)	Receiver		Turn-Table	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dB $\mu$ V/m)	FCC Part15.407	
	Reading (dB $\mu$ V)	Detector (PK/QP/AV)	Angle Degree	Height (m)	Polar (H / V)			Limit (dB $\mu$ V/m)	Margin (dB)
802.11ac40									
5190 MHz									
4500	63.98	PK	288	2	H	-4.72	59.26	74	-14.74
4500	53.64	AV	288	2	H	-4.72	48.92	54	-5.08
4500	66.99	PK	287	1.2	V	-4.72	62.27	74	-11.73
4500	56.28	AV	287	1.2	V	-4.72	51.56	54	-2.44
5150	62.41	PK	300	1.7	H	-2.73	59.68	74	-14.32
5150	51.87	AV	300	1.7	H	-2.73	49.14	54	-4.86
5150	64.79	PK	230	2	V	-2.73	62.06	74	-11.94
5150	53.95	AV	230	2	V	-2.73	51.22	54	-2.78
10380	41.67	PK	305	1.4	H	8.18	49.85	68.2	-18.35
10380	41.19	PK	79	1.4	V	8.18	49.37	68.2	-18.83
5230 MHz									
5350	64.72	PK	118	1	H	-2.33	62.39	74	-11.61
5350	52.68	AV	118	1	H	-2.33	50.35	54	-3.65
5350	63.37	PK	284	2.3	V	-2.33	61.04	74	-12.96
5350	53.10	AV	284	2.3	V	-2.33	50.77	54	-3.23
5460	64.84	PK	145	2.2	H	-2.26	62.58	74	-11.42
5460	52.48	AV	145	2.2	H	-2.26	50.22	54	-3.78
5460	63.30	PK	59	2.1	V	-2.26	61.04	74	-12.96
5460	53.04	AV	59	2.1	V	-2.26	50.78	54	-3.22
10460	40.95	PK	68	1.7	H	8.47	49.42	68.2	-18.78
10460	40.20	PK	138	1.7	V	8.47	48.67	68.2	-19.53

Frequency (MHz)	Receiver		Turn- Table	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dB $\mu$ V/m)	FCC Part15.407	
	Reading (dB $\mu$ V)	Detector (PK/QP/AV)	Angle Degree	Height (m)	Polar (H / V)			Limit (dB $\mu$ V/m)	Margin (dB)
802.11ac80									
5210MHz									
4500	64.40	PK	123	2.4	H	-4.72	59.68	74	-14.32
4500	53.86	AV	123	2.4	H	-4.72	49.14	54	-4.86
4500	66.78	PK	122	1.7	V	-4.72	62.06	74	-11.94
4500	55.94	AV	122	1.7	V	-4.72	51.22	54	-2.78
5150	62.46	PK	242	2.3	H	-2.73	59.73	74	-14.27
5150	51.65	AV	242	2.3	H	-2.73	48.92	54	-5.08
5150	65.12	PK	285	1.5	V	-2.73	62.39	74	-11.61
5150	54.07	AV	285	1.5	V	-2.73	51.34	54	-2.66
5350	64.77	PK	292	1.6	H	-2.33	62.44	74	-11.56
5350	52.80	AV	292	1.6	H	-2.33	50.47	54	-3.53
5350	63.60	PK	270	2.5	V	-2.33	61.27	74	-12.73
5350	52.75	AV	270	2.5	V	-2.33	50.42	54	-3.58
5460	64.54	PK	276	2.3	H	-2.26	62.28	74	-11.72
5460	52.69	AV	276	2.3	H	-2.26	50.43	54	-3.57
5460	64.04	PK	230	1.6	V	-2.26	61.78	74	-12.22
5460	53.05	AV	230	1.6	V	-2.26	50.79	54	-3.21
10420	41.31	PK	103	1.7	H	8.32	49.63	68.2	-18.57
10420	41.23	PK	40	1.7	V	8.32	49.55	68.2	-18.65

**5725-5850 MHz:**

Frequency (MHz)	Receiver		Turn-Table Angle Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dB $\mu$ V/m)	FCC Part15.407	
	Reading (dB $\mu$ V)	Detector (PK/QP/AV)		Height (m)	Polar (H / V)			Limit (dB $\mu$ V/m)	Margin (dB)
802.11a									
5745 MHz									
5650	65.76	PK	179	2.4	H	-1.95	63.81	68.2	-4.39
5650	65.58	PK	327	1.3	V	-1.95	63.63	68.2	-4.57
5700	66.81	PK	7	1.6	H	-2.02	64.79	105.2	-40.41
5700	65.99	PK	231	1.1	V	-2.02	63.97	105.2	-41.23
5720	73.26	PK	175	2.5	H	-1.97	71.29	110.8	-39.51
5720	69.85	PK	69	2.4	V	-1.97	67.88	110.8	-42.92
5725	78.28	PK	209	1.1	H	-1.96	76.32	122.2	-45.88
5725	74.56	PK	246	1.6	V	-1.96	72.60	122.2	-49.60
11490	43.00	PK	169	1.3	H	6.63	49.63	74	-24.37
11490	42.60	PK	221	2.5	V	6.63	49.23	74	-24.77
5785 MHz									
11570	43.22	PK	62	1.5	H	6.59	49.81	74	-24.19
11570	42.68	PK	133	2.4	V	6.59	49.27	74	-24.73
5825 MHz									
5850	70.78	PK	262	1.6	H	-1.81	68.97	122.2	-53.23
5850	68.00	PK	23	1.9	V	-1.81	66.19	122.2	-56.01
5855	70.26	PK	93	2.1	H	-1.81	68.45	110.8	-42.35
5855	67.07	PK	35	1.6	V	-1.81	65.26	110.8	-45.54
5875	66.45	PK	279	1.9	H	-1.84	64.61	105.2	-40.59
5875	65.59	PK	33	1.7	V	-1.84	63.75	105.2	-41.45
5925	65.95	PK	19	1.9	H	-1.82	64.13	68.2	-4.07
5925	65.53	PK	71	1.9	V	-1.82	63.71	68.2	-4.49
11650	41.45	PK	166	1.3	H	6.77	48.22	74	-25.78
11650	41.30	PK	164	1.8	V	6.77	48.07	74	-25.93

Frequency (MHz)	Receiver		Turn-Table	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	FCC Part15.407	
	Reading (dBμV)	Detector (PK/QP/AV)	Angle Degree	Height (m)	Polar (H / V)			Limit (dBμV/m)	Margin (dB)
802.11n20									
5745 MHz									
5650	64.39	PK	185	1	H	-1.95	62.44	68.2	-5.76
5650	65.32	PK	353	1.8	V	-1.95	63.37	68.2	-4.83
5700	67.81	PK	29	1.6	H	-2.02	65.79	105.2	-39.41
5700	66.65	PK	180	1.5	V	-2.02	64.63	105.2	-40.57
5720	74.95	PK	263	2	H	-1.97	72.98	110.8	-37.82
5720	70.94	PK	127	2	V	-1.97	68.97	110.8	-41.83
5725	80.96	PK	259	2	H	-1.96	79.00	122.2	-43.20
5725	76.08	PK	94	1.4	V	-1.96	74.12	122.2	-48.08
11490	43.08	PK	126	2	H	6.63	49.71	74	-24.29
11490	42.83	PK	34	2.3	V	6.63	49.46	74	-24.54
5785 MHz									
11570	43.05	PK	145	1.8	H	6.59	49.64	74	-24.36
11570	42.86	PK	327	1.3	V	6.59	49.45	74	-24.55
5825 MHz									
5850	76.61	PK	268	1.5	H	-1.81	74.80	122.2	-47.40
5850	74.35	PK	286	2.1	V	-1.81	72.54	122.2	-49.66
5855	70.68	PK	54	1.4	H	-1.81	68.87	110.8	-41.93
5855	68.75	PK	3	1.3	V	-1.81	66.94	110.8	-43.86
5875	65.92	PK	290	1.2	H	-1.84	64.08	105.2	-41.12
5875	65.59	PK	58	1	V	-1.84	63.75	105.2	-41.45
5925	65.46	PK	335	1.2	H	-1.82	63.64	68.2	-4.56
5925	65.53	PK	119	1.9	V	-1.82	63.71	68.2	-4.49
11650	41.70	PK	129	1.6	H	6.77	48.47	74	-25.53
11650	40.98	PK	18	1.4	V	6.77	47.75	74	-26.25

Frequency (MHz)	Receiver		Turn- Table	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dB $\mu$ V/m)	FCC Part15.407	
	Reading (dB $\mu$ V)	Detector (PK/QP/AV)	Angle Degree	Height (m)	Polar (H / V)			Limit (dB $\mu$ V/m)	Margin (dB)
802.11n40									
5755 MHz									
5650	65.46	PK	128	1.8	H	-1.95	63.51	68.2	-4.69
5650	65.43	PK	85	1.8	V	-1.95	63.48	68.2	-4.72
5700	69.38	PK	85	2	H	-2.02	67.36	105.2	-37.84
5700	67.09	PK	76	2	V	-2.02	65.07	105.2	-40.13
5720	76.58	PK	5	2	H	-1.97	74.61	110.8	-36.19
5720	74.00	PK	61	1	V	-1.97	72.03	110.8	-38.77
5725	76.09	PK	213	1.5	H	-1.96	74.13	122.2	-48.07
5725	73.69	PK	305	1.9	V	-1.96	71.73	122.2	-50.47
11510	43.38	PK	29	2	H	6.58	49.96	74	-24.04
11510	42.54	PK	306	1.1	V	6.58	49.12	74	-24.88
5795 MHz									
5850	68.73	PK	142	1.8	H	-1.81	66.92	122.2	-55.28
5850	67.49	PK	59	1.4	V	-1.81	65.68	122.2	-56.52
5855	66.77	PK	177	1.4	H	-1.81	64.96	110.8	-45.84
5855	66.26	PK	321	1.7	V	-1.81	64.45	110.8	-46.35
5875	65.94	PK	175	1.1	H	-1.84	64.10	105.2	-41.10
5875	65.85	PK	113	2.2	V	-1.84	64.01	105.2	-41.19
5925	65.44	PK	183	1.4	H	-1.82	63.62	68.2	-4.58
5925	66.01	PK	94	1.6	V	-1.82	64.19	68.2	-4.01
11590	43.44	PK	326	1.9	H	6.57	50.01	74	-23.99
11590	42.69	PK	151	1.4	V	6.57	49.26	74	-24.74

Frequency (MHz)	Receiver		Turn-Table Angle Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dB $\mu$ V/m)	FCC Part15.407	
	Reading (dB $\mu$ V)	Detector (PK/QP/AV)		Height (m)	Polar (H / V)			Limit (dB $\mu$ V/m)	Margin (dB)
802.11ac20									
5745 MHz									
5650	64.43	PK	193	1	H	-1.95	62.48	68.2	-5.72
5650	64.80	PK	328	1.1	V	-1.95	62.85	68.2	-5.35
5700	65.17	PK	179	2.1	H	-2.02	63.15	105.2	-42.05
5700	65.43	PK	212	2.2	V	-2.02	63.41	105.2	-41.79
5720	68.12	PK	193	1.6	H	-1.97	66.15	110.8	-44.65
5720	70.98	PK	206	2.1	V	-1.97	69.01	110.8	-41.79
5725	71.94	PK	294	2.4	H	-1.96	69.98	122.2	-52.22
5725	69.49	PK	44	1.6	V	-1.96	67.53	122.2	-54.67
11490	43.21	PK	97	1.2	H	6.63	49.84	74	-24.16
11490	42.52	PK	203	2	V	6.63	49.15	74	-24.85
5785 MHz									
11570	43.12	PK	233	1.1	H	6.59	49.71	74	-24.29
11570	42.58	PK	28	1.8	V	6.59	49.17	74	-24.83
5825 MHz									
5850	67.71	PK	355	2.1	H	-1.81	65.90	122.2	-56.30
5850	67.39	PK	123	2.2	V	-1.81	65.58	122.2	-56.62
5855	67.26	PK	195	1.5	H	-1.81	65.45	110.8	-45.35
5855	66.90	PK	263	1.5	V	-1.81	65.09	110.8	-45.71
5875	65.72	PK	60	1.7	H	-1.84	63.88	105.2	-41.32
5875	66.05	PK	261	1.4	V	-1.84	64.21	105.2	-40.99
5925	65.97	PK	344	2.4	H	-1.82	64.15	68.2	-4.05
5925	66.03	PK	181	1.8	V	-1.82	64.21	68.2	-3.99
11650	41.80	PK	191	1.6	H	6.77	48.57	74	-25.43
11650	41.16	PK	348	1.5	V	6.77	47.93	74	-26.07

Frequency (MHz)	Receiver		Turn-Table	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dB $\mu$ V/m)	FCC Part15.407	
	Reading (dB $\mu$ V)	Detector (PK/QP/AV)	Angle Degree	Height (m)	Polar (H / V)			Limit (dB $\mu$ V/m)	Margin (dB)
802.11ac40									
5755 MHz									
5650	65.63	PK	314	1.1	H	-1.95	63.68	68.2	-4.52
5650	65.41	PK	124	2.1	V	-1.95	63.46	68.2	-4.74
5700	65.48	PK	131	1.7	H	-2.02	63.46	105.2	-41.74
5700	65.70	PK	298	2	V	-2.02	63.68	105.2	-41.52
5720	70.56	PK	152	2.2	H	-1.97	68.59	110.8	-42.21
5720	69.80	PK	316	2	V	-1.97	67.83	110.8	-42.97
5725	72.18	PK	211	1.9	H	-1.96	70.22	122.2	-51.98
5725	71.49	PK	288	2.3	V	-1.96	69.53	122.2	-52.67
11510	42.93	PK	146	1.1	H	6.58	49.51	74	-24.49
11510	42.58	PK	127	2.3	V	6.58	49.16	74	-24.84
5795 MHz									
5850	68.03	PK	103	2.5	H	-1.81	66.22	122.2	-55.98
5850	68.05	PK	246	1.4	V	-1.81	66.24	122.2	-55.96
5855	67.81	PK	298	1.7	H	-1.81	66.00	110.8	-44.80
5855	67.57	PK	9	1.7	V	-1.81	65.76	110.8	-45.04
5875	66.96	PK	106	1.3	H	-1.84	65.12	105.2	-40.08
5875	66.10	PK	92	2.1	V	-1.84	64.26	105.2	-40.94
5925	66.55	PK	178	1.5	H	-1.82	64.73	68.2	-3.47
5925	65.89	PK	326	1.3	V	-1.82	64.07	68.2	-4.13
11590	43.23	PK	65	1.2	H	6.57	49.80	74	-24.20
11590	42.78	PK	210	2.3	V	6.57	49.35	74	-24.65

Frequency (MHz)	Receiver		Turn-Table Angle Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dB $\mu$ V/m)	FCC Part15.407	
	Reading (dB $\mu$ V)	Detector (PK/QP/AV)		Height (m)	Polar (H / V)			Limit (dB $\mu$ V/m)	Margin (dB)
802.11ac80									
5775 MHz									
5650	64.41	PK	19	1.3	H	-1.95	62.46	68.2	-5.74
5650	65.68	PK	301	1	V	-1.95	63.73	68.2	-4.47
5700	65.86	PK	86	2.2	H	-2.02	63.84	105.2	-41.36
5700	65.58	PK	358	1.5	V	-2.02	63.56	105.2	-41.64
5720	66.63	PK	34	2.1	H	-1.97	64.66	110.8	-46.14
5720	66.55	PK	349	2.3	V	-1.97	64.58	110.8	-46.22
5725	66.47	PK	138	1.3	H	-1.96	64.51	122.2	-57.69
5725	66.50	PK	216	2.2	V	-1.96	64.54	122.2	-57.66
5850	66.43	PK	130	1.5	H	-1.81	64.62	122.2	-57.58
5850	65.74	PK	243	1.3	V	-1.81	63.93	122.2	-58.27
5855	66.91	PK	65	2.1	H	-1.81	65.10	110.8	-45.70
5855	66.28	PK	192	2.1	V	-1.81	64.47	110.8	-46.33
5875	67.49	PK	148	2.1	H	-1.84	65.65	105.2	-39.55
5875	67.33	PK	336	1.3	V	-1.84	65.49	105.2	-39.71
5925	67.11	PK	308	2.4	H	-1.82	65.29	68.2	-2.91
5925	65.70	PK	314	1.7	V	-1.82	63.88	68.2	-4.32
11550	42.94	PK	135	2.4	H	6.61	49.55	74	-24.45
11550	42.80	PK	357	1.4	V	6.61	49.41	74	-24.59

**Note:**

Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude = Corrected Factor + Reading

Margin = Corrected. Amplitude - Limit


The other spurious emission which is 20dB to the limit or in noise floor was not recorded.

The test result of peak was less than the limit of average, so just peak values were recorded.


1 GHz - 18 GHz: (Pre-Scan plots)

802.11 n20, 5200MHz

Horizontal




Vertical




18-40GHz: (Pre-Scan plots)

802.11 n20, 5200MHz

Horizontal



Vertical



## **FCC §15.407(a),(e) – 26 dB & 6dB EMISSION BANDWIDTH**

### **Applicable Standard**

The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used. Measurements in the 5.725-5.85 GHz band are made over a reference bandwidth of 500 kHz or the 26 dB emission bandwidth of the device, whichever is less. Measurements in the 5.15-5.25 GHz, 5.25-5.35 GHz, and the 5.47-5.725 GHz bands are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A narrower resolution bandwidth can be used, provided that the measured power is integrated over the full reference bandwidth.

Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

### **Test Procedure**


#### **1. Emission Bandwidth (EBW)**

- a) Set RBW = approximately 1% of the emission bandwidth.
- b) Set the VBW > RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Measure the maximum width of the emission that is 26 dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

#### **2. Minimum Emission Bandwidth for the band 5.725-5.85 GHz**

Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 KHz for the band 5.725-5.85 GHz. The following procedure shall be used for measuring this bandwidth:

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW)  $\geq 3 \times$  RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



**Test Data****Environmental Conditions**

<b>Temperature:</b>	27.7 °C
<b>Relative Humidity:</b>	54 %
<b>ATM Pressure:</b>	101.0 kPa

The testing was performed by Paul Liu on 2021-12-15 and 2021-12-16.


EUT operation mode: Transmitting

**Test Result:** Pass; please refer to the following tables and plots.

**5150 MHz - 5250 MHz:**


Frequency (MHz)	26 dB Bandwidth (MHz)	99% Bandwidth (MHz)	Remark
802.11a			No transmitted signal in the 99% bandwidth extends into the U-NII-2A band
5180	20.962	16.603	
5200	20.962	16.603	
5240	20.962	16.603	
802.11n20			
5180	21.513	17.885	
5200	21.513	17.885	
5240	21.795	17.885	
802.11n40			
5190	40.256	36.410	
5230	40.256	36.410	
802.11ac20			
5180	21.410	17.885	
5200	21.449	17.885	
5240	21.885	17.885	
802.11ac40			
5190	40.385	36.667	
5230	40.385	36.538	
11ac80			
5210	82.308	76.410	

**802.11a mode, 26 dB Emissions & 99% Occupied Bandwidth, 5180 MHz**




Date: 15.DEC.2021 23:40:52

**802.11a mode, 26 dB Emissions & 99% Occupied Bandwidth, 5200 MHz**




Date: 15.DEC.2021 23:42:14

**802.11a mode, 26 dB Emissions & 99% Occupied Bandwidth, 5240 MHz**




Date: 15.DEC.2021 23:43:28

**802.11n20 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5180 MHz**




Date: 15.DEC.2021 23:47:40

**802.11n20 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5200 MHz**



Date: 15.DEC.2021 23:46:05

**802.11n20 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5240 MHz**




Date: 15.DEC.2021 23:44:39






**802.11ac20 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5240 MHz**




Date: 15.DEC.2021 23:49:25

**802.11ac40 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5190 MHz**




Date: 15.DEC.2021 23:54:32

**802.11ac40 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5230 MHz**



Date: 15.DEC.2021 23:53:26

**802.11ac80 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5230 MHz**




Date: 15.DEC.2021 23:58:52

**5725 MHz – 5850 MHz:**


Frequency (MHz)	6 dB Bandwidth (MHz)	99% Bandwidth (MHz)	Limit (MHz)	Remark
802.11a				No transmitted signal in the 99% bandwidth extends into the U-NII-2C band
5745	16.474	17.308	0.5	
5785	16.474	17.949	0.5	
5825	16.449	17.372	0.5	
802.11n20				
5745	17.744	18.397	0.5	
5785	17.756	18.397	0.5	
5825	17.821	18.397	0.5	
802.11n40				
5755	36.538	36.667	0.5	
5795	36.538	36.923	0.5	
802.11ac20				
5745	17.795	18.205	0.5	
5785	17.808	18.141	0.5	
5825	17.821	18.141	0.5	
802.11ac40				
5755	36.538	36.538	0.5	
5795	36.615	36.667	0.5	
802.11ac80				
5775	76.410	76.410	0.5	

### 802.11a mode, 6dB Emission Bandwidth, 5745 MHz




Date: 16.DEC.2021 00:31:56

### 802.11a mode, 6dB Emission Bandwidth, 5785 MHz




Date: 16.DEC.2021 00:33:08

### 802.11a mode, 6dB Emission Bandwidth, 5825 MHz




Date: 16.DEC.2021 00:35:04

### 802.11n20 mode, 6dB Emission Bandwidth, 5745 MHz




Date: 16.DEC.2021 00:38:12

### 802.11n20 mode, 6dB Emission Bandwidth, 5785 MHz




Date: 16.DEC.2021 00:39:25

### 802.11n20 mode, 6dB Emission Bandwidth, 5825 MHz




Date: 16.DEC.2021 00:40:26

### 802.11n40 mode, 6dB Emission Bandwidth, 5755 MHz




Date: 16.DEC.2021 00:43:08

### 802.11n40 mode, 6dB Emission Bandwidth, 5795 MHz




Date: 16.DEC.2021 00:44:20

### 802.11ac20 mode, 6dB Emission Bandwidth, 5745 MHz




Date: 16.DEC.2021 00:45:40

### 802.11ac20 mode, 6dB Emission Bandwidth, 5785 MHz




Date: 16.DEC.2021 00:46:35

### 802.11ac20 mode, 6dB Emission Bandwidth, 5825 MHz




Date: 16.DEC.2021 00:47:31

### 802.11ac40 mode, 6dB Emission Bandwidth, 5755 MHz




Date: 16.DEC.2021 00:49:13

### 802.11ac40 mode, 6dB Emission Bandwidth, 5795 MHz




Date: 16.DEC.2021 00:50:20

### 802.11ac80 mode, 6dB Emission Bandwidth, 5775 MHz




Date: 16.DEC.2021 18:49:09

### 802.11a mode, 99% Occupied Bandwidth, 5745 MHz




Date: 16.DEC.2021 18:53:25

### 802.11a mode, 99% Occupied Bandwidth, 5785 MHz




Date: 16.DEC.2021 18:54:16

**802.11a mode, 99% Occupied Bandwidth, 5825 MHz**




Date: 16.DEC.2021 18:55:04

**802.11n20 mode, 99% Occupied Bandwidth, 5745 MHz**




Date: 16.DEC.2021 18:59:26

### 802.11n20 mode, 99% Occupied Bandwidth, 5785 MHz




Date: 16.DEC.2021 19:00:16

### 802.11n20 mode, 99% Occupied Bandwidth, 5825 MHz




Date: 16.DEC.2021 19:00:59

### 802.11n40 mode, 99% Occupied Bandwidth, 5755 MHz




Date: 16.DEC.2021 19:05:45

### 802.11n40 mode, 99% Occupied Bandwidth, 5795 MHz




Date: 16.DEC.2021 19:06:38

### 802.11ac20 mode, 99% Occupied Bandwidth, 5745 MHz




Date: 16.DEC.2021 19:02:01

### 802.11ac20 mode, 99% Occupied Bandwidth, 5785 MHz




Date: 16.DEC.2021 19:02:59

### 802.11ac20 mode, 99% Occupied Bandwidth, 5825 MHz




Date: 16.DEC.2021 19:03:55

### 802.11ac40 mode, 99% Occupied Bandwidth, 5755 MHz




Date: 16.DEC.2021 19:07:54

**802.11ac40 mode, 99% Occupied Bandwidth, 5795 MHz**



Date: 16.DEC.2021 19:08:55

**802.11ac80 mode, 99% Occupied Bandwidth, 5775 MHz**



Date: 16.DEC.2021 18:52:03

## FCC §15.407(a) – CONDUCTED TRANSMITTER OUTPUT POWER

### Applicable Standard

For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.


For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or  $11 \text{ dBm} + 10 \log B$ , where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

### Test Procedure

- c. Place the EUT on a bench and set it in transmitting mode.
- d. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
- e. Add a correction factor to the display.



**Test Data****Environmental Conditions**

<b>Temperature:</b>	27.7 °C
<b>Relative Humidity:</b>	54 %
<b>ATM Pressure:</b>	101.0 kPa

The testing was performed by Paul Liu on 2021-12-15 and 2021-12-16.

EUT operation mode: Transmitting

**Test Result:** Pass

Please refer to the following tables.

**5150 MHz – 5250 MHz**

Frequency (MHz)	Conducted Average Output Power (dBm)	Limit (dBm)
802.11a		
5180	6.61	24
5200	6.50	
5240	5.23	
802.11n20		
5180	7.10	24
5200	6.68	
5240	5.59	
802.11n40		
5190	6.59	24
5230	6.08	
802.11ac20		
5180	6.96	24
5200	6.68	
5240	5.44	
802.11ac40		
5190	6.27	24
5230	6.05	
802.11ac80		
5210	6.23	24

Note: the duty cycle factor has added into average output power.

**5725 MHz – 5825 MHz:**

Frequency (MHz)	Conducted Average Output Power (dBm)	Limit (dBm)
802.11a		
5745	11.25	30
5785	11.73	
5825	11.28	
802.11n20		
5745	10.28	30
5785	10.46	
5825	10.42	
802.11n40		
5755	9.45	30
5795	9.38	
802.11ac20		
5745	8.32	30
5785	8.18	
5825	8.45	
802.11ac40		
5755	6.01	30
5795	6.16	
802.11ac80		
5775	4.20	30

Note: the duty cycle factor has added into average output power.

## **FCC §15.407(a) - POWER SPECTRAL DENSITY**

For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or  $11 \text{ dBm} + 10 \log B$ , where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

### **Test Procedure**

For devices operating in the bands 5.15-5.25 GHz, 5.25-5.35 GHz, and 5.47-5.725 GHz, the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in § 15.407(a)(5). For devices operating in the band 5.725-5.85 GHz, the rules specify a measurement bandwidth of 500 kHz. Many spectrum analyzers do not have 500 kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500 kHz, “provided that the measured power is integrated over the full reference bandwidth” to show the total power over the specified measurement bandwidth (i.e., 1 MHz, or 500 kHz). If measurements are performed using a reduced resolution bandwidth (< 1 MHz, or < 500 kHz) and integrated over 1 MHz, or 500 kHz bandwidth, the following adjustments to the procedures apply:

- a) Set  $RBW \geq 1/T$ , where T is defined in section II.B.1.a).
- b) Set  $VBW \geq 3 \text{ RBW}$ .
- c) If measurement bandwidth of Maximum PSD is specified in 500 kHz, add  $10 \log (500 \text{ kHz}/RBW)$  to the measured result, whereas  $RBW (< 500 \text{ kHz})$  is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
- d) If measurement bandwidth of Maximum PSD is specified in 1 MHz, add  $10 \log (1\text{MHz}/RBW)$  to the measured result, whereas  $RBW (< 1 \text{ MHz})$  is the reduced resolution bandwidth of spectrum analyzer set during measurement.
- e) Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

**Test Data****Environmental Conditions**

<b>Temperature:</b>	27.7 °C
<b>Relative Humidity:</b>	54 %
<b>ATM Pressure:</b>	101.0 kPa

*The testing was performed by Paul Liu on 2021-12-16 and 2022-01-27.*

*EUT operation mode: Transmitting*

**Test Result:** Pass


Please refer to the following tables and plots.

**5150 MHz – 5250 MHz**

Frequency (MHz)	Reading (dBm/MHz)	Duty Cycle Factor (dB)	Power Spectral Density (dBm/MHz)	Limit (dBm/MHz)
802.11a				
5180	-4.17	0.67	-3.50	11
5200	-3.89	0.67	-3.22	
5240	-5.04	0.67	-4.37	
802.11n20				
5180	-4.17	0.72	-3.45	11
5200	-3.89	0.72	-3.17	
5240	-5.04	0.72	-4.32	
802.11n40				
5190	-7.74	1.18	-6.56	11
5230	-8.17	1.18	-6.99	
802.11ac20				
5180	-3.90	0.78	-3.12	11
5200	-3.62	0.78	-2.84	
5240	-4.65	0.78	-3.87	
802.11ac40				
5190	-7.88	1.26	-6.62	11
5230	-8.11	1.26	-6.85	
802.11ac80				
5210	-10.68	1.66	-9.02	11


Note: Power spectral density = Reading + Duty cycle factor  
Duty cycle factor please refer to section duty cycle of report

### 802.11a mode, Power Spectral Density, 5180 MHz




Date: 16.DEC.2021 00:15:03

### 802.11a mode, Power Spectral Density, 5200 MHz




Date: 16.DEC.2021 00:14:19

### 802.11a mode, Power Spectral Density, 5240 MHz




Date: 16.DEC.2021 00:15:43

### 802.11n20 mode, Power Spectral Density, 5180 MHz




Date: 16.DEC.2021 00:17:33

### 802.11n20 mode, Power Spectral Density, 5200 MHz




Date: 16.DEC.2021 00:16:31

### 802.11n20 mode, Power Spectral Density, 5240 MHz




Date: 16.DEC.2021 00:18:11

### 802.11n40 mode, Power Spectral Density, 5190 MHz




Date: 16.DEC.2021 00:18:53

### 802.11n40 mode, Power Spectral Density, 5230 MHz




Date: 16.DEC.2021 00:19:41

### 802.11ac20 mode, Power Spectral Density, 5180 MHz




Date: 16.DEC.2021 00:20:24

### 802.11ac20 mode, Power Spectral Density, 5200 MHz




Date: 16.DEC.2021 00:21:17

### 802.11ac20 mode, Power Spectral Density, 5240 MHz




Date: 16.DEC.2021 00:22:03

### 802.11ac40 mode, Power Spectral Density, 5190 MHz




Date: 16.DEC.2021 00:22:41

### 802.11ac40 mode, Power Spectral Density, 5230 MHz



Date: 16.DEC.2021 00:23:18

### 802.11ac80 mode, Power Spectral Density, 5210 MHz




Date: 16.DEC.2021 00:23:52

**5725 MHz – 5825 MHz:**

Frequency (MHz)	Reading (dBm/500kHz)	Duty Cycle Factor (dB)	Power Spectral Density (dBm/500kHz)	Limit (dBm/500kHz)
802.11a				
5180	-1.15	0.65	-0.50	30
5200	-0.07	0.65	0.58	
5240	-0.56	0.65	0.09	
802.11n20				
5180	-2.82	0.72	-2.10	30
5200	-2.06	0.72	-1.34	
5240	-1.89	0.72	-1.17	
802.11n40				
5190	-6.40	1.14	-5.26	30
5230	-5.18	1.14	-4.04	
802.11ac20				
5180	-4.73	0.81	-3.92	30
5200	-4.17	0.81	-3.36	
5240	-3.90	0.81	-3.09	
802.11ac40				
5190	-9.77	1.29	-8.48	30
5230	-9.46	1.29	-8.17	
802.11ac80				
5210	-14.37	1.72	-12.65	30


Note: Power spectral density = Reading + Duty cycle factor  
Duty cycle factor please refer to section duty cycle of report

### 802.11a mode, Power Spectral Density, 5745 MHz




Date: 27.JAN.2022 11:23:21

### 802.11a mode, Power Spectral Density, 5785 MHz




Date: 27.JAN.2022 11:24:41

### 802.11a mode, Power Spectral Density, 5825 MHz




Date: 27.JAN.2022 11:26:20

### 802.11n20 mode, Power Spectral Density, 5745 MHz




Date: 27.JAN.2022 11:27:40

### 802.11n20 mode, Power Spectral Density, 5785 MHz




Date: 27.JAN.2022 11:28:59

### 802.11n20 mode, Power Spectral Density, 5825 MHz




Date: 27.JAN.2022 11:31:42

### 802.11n40 mode, Power Spectral Density, 5755 MHz




Date: 27.JAN.2022 11:37:44

### 802.11n40 mode, Power Spectral Density, 5795 MHz




Date: 27.JAN.2022 11:39:29

### 802.11ac20 mode, Power Spectral Density, 5745 MHz




Date: 27.JAN.2022 11:33:07

### 802.11ac20 mode, Power Spectral Density, 5785 MHz




Date: 27.JAN.2022 11:34:37

### 802.11ac20 mode, Power Spectral Density, 5825 MHz




Date: 27.JAN.2022 11:36:07

### 802.11ac40 mode, Power Spectral Density, 5755 MHz




Date: 27.JAN.2022 11:42:44

### 802.11ac40 mode, Power Spectral Density, 5795 MHz



Date: 27.JAN.2022 11:43:59

### 802.11ac80 mode, Power Spectral Density, 5775 MHz



Date: 27.JAN.2022 11:20:20

\*\*\*\*\* END OF REPORT \*\*\*\*\*