

# Maximum Permissible Exposure

## Evaluation

### FCC ID: 2ASV7-AP2152

#### 1. Client Information

<b>Applicant</b>	:	American Time
<b>Address</b>	:	140 3rd Street South Dassel, MN 55325, USA
<b>Manufacturer</b>	:	Parado Enterprises Co.,Ltd
<b>Address</b>	:	#404, Bld #A, DanLi Industrial Park, 16th KangZheng Rd., NanWan, LongGang, Shenzhen, GuangDong, 518112, China

#### 2. General Description of EUT

<b>EUT Name</b>	:	Dynamic Display
<b>Models No.</b>	:	AP2152, AP2152A, AP2152T
<b>Model Different</b>	:	All these models are the same PCB, layout and electrical circuit, the only difference is appearance color.
<b>Product Description</b>	Operation Frequency:	802.11b/g/n(HT20): 2412MHz~2462MHz
	RF Output Power:	802.11b: 16.62dBm 802.11g: 15.48dBm 802.11n (HT20): 15.45dBm
	Antenna Gain:	1.1dBi FPC Antenna
	Modulation Type:	802.11b: DSSS(CCK, DQPSK, DBPSK) 802.11g/n: OFDM(BPSK,QPSK,16QAM, 64QAM)
<b>Power Supply</b>	:	AC/DC adapter: Model:M120300B911 Input:AC100-240V, 1.2A, 50/60Hz Output: DC 12V 3A
<b>Software Version</b>	:	Android 6.0
<b>Hardware Version</b>	:	V1.1
<b>Connecting I/O Port(S)</b>	:	Please refer to the User's Manual

TB-RF-075-1.0

## MPE Calculations for WIFI

### 1. Antenna Gain:

FPC Antenna: 1.1dBi.

### 2. EUT Operation Condition:

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

### 3. Exposure Evaluation:

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = (P_G) / (4\pi R^2)$$

Where

**S**: power density

**P**: power input to the antenna

**G**: power gain of the antenna in the direction of interest relative to an isotropic radiator.

**R**: distance to the center of radiation of the antenna

### 4. Test Result:

Mode	Conducted Power(max) (dBm)	Turn-up Power (dB)	Max tune up power (dBm) [P]	ANT Gain (dBi) [G]	Distance (cm) [R]	Power Density (mW/ cm <sup>2</sup> ) [S]
802.11b	16.62	16±1	17	1.1	20	0.01285
802.11g	15.48	15±1	16	1.1	20	0.01020
802.11n (HT20)	15.45	15±1	16	1.1	20	0.01020

**5. Conclusion:**

As specified in Table 1B of 47 CFR 1.1310- Limits for Maximum Permissible Exposure (MPE),

**Limits for General Population/ Uncontrolled Exposure**

Frequency Range (MHz)	Power density (mW/ cm <sup>2</sup> )
300-1,500	F/1500
1,500-100,000	1.0

For 802.11b/g/n:2412~2462 MHz

MPE limit S: 1mW/ cm<sup>2</sup>

The MPE is calculated as  $0.01285\text{mW/cm}^2 < \text{limit } 1\text{mW/cm}^2$ . So, RF exposure limit warning or SAR test are not required.

The EUT will only be used with a separation of 20cm or greater between the antenna and nearby persons and can therefore be considered a mobile transmitter per 47 CFR2.1091 (b).

The RF Exposure Information page from the manual is included here for reference.

**Note**

For a more detailed features description, please refer to the RF Test Report.

-----END OF REPORT-----