



# RADIO TEST REPORT

## FCC ID: 2AT26-M029B

**Product Designation** : CD Shelf System With AM/FM Stereo Radio and Bluetooth Wireless Technology

**Trademark** : MAGNAVOX,CRAIG,borne,Bluestream,naxa

**Model Name** : MM435,M029B,MS500B,BS029MS,NS-441,MM434

**Applicant** : Dongguan Yihua Electrical Appliance Technology CO., LTD

**Date of Issue** : July. 23, 2020

**Standard(s)** : FCC Part 15.247

**Report No** : S20072801206001

### Prepared for

Dongguan Yihua Electrical Appliance Technology CO., LTD  
No. 5, Nanyu Industrial Park, Nanchang Road, Wanglian Hamlet,  
Wangniudun Town, Dongguan City,Guangdong Province, China

### Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.  
1/F, Building E, Fenda Science Park, Sanwei Community,Xixiang Street  
Bao'an District, Shenzhen 518126 P.R. China  
Tel.: +86-755-6115 9388 Fax.: +86-755-6115 6599  
Website:<http://www.ntek.org.cn>

REPORT REVISE RECORD

Report No	Revise Time	Issued Date	Valid Version	Notes
S20072801206001	/	July 23, 2020	Invalid	Initial release

## TABLE OF CONTENTS

<b>1. GENERAL INFORMATION.....</b>	<b>5</b>
1.1. PRODUCT DESCRIPTION.....	5
1.2. TABLE OF CARRIER FREQUENCIES.....	5
1.3. RECEIVER INPUT BANDWIDTH.....	6
1.4. EXAMPLE OF A HOPPING SEQUENCY IN DATA MODE.....	6
1.5. EQUALLY AVERAGE USE OF FREQUENCIES AND BEHAVIOUR.....	6
1.6. RELATED SUBMITTAL(S) / GRANT (S).....	6
1.7. TEST METHODOLOGY.....	7
<b>2. MEASUREMENT UNCERTAINTY.....</b>	<b>7</b>
<b>3. DESCRIPTION OF TEST MODES.....</b>	<b>7</b>
<b>4. SYSTEM TEST CONFIGURATION.....</b>	<b>8</b>
4.1. CONFIGURATION OF EUT SYSTEM.....	8
4.2 EQUIPMENT USED IN TESTED SYSTEM.....	8
4.3. SUMMARY OF TEST RESULTS.....	8
<b>5. TEST FACILITY.....</b>	<b>9</b>
<b>6. PEAK OUTPUT POWER.....</b>	<b>10</b>
6.1. MEASUREMENT PROCEDURE.....	10
6.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	10
6.3. LIMITS AND MEASUREMENT RESULT.....	11
<b>7. 20DB BANDWIDTH.....</b>	<b>17</b>
7.1. MEASUREMENT PROCEDURE.....	17
7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	17
7.3. LIMITS AND MEASUREMENT RESULTS.....	17
<b>8. CONDUCTED SPURIOUS EMISSION.....</b>	<b>24</b>
8.1. MEASUREMENT PROCEDURE.....	24
8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	24

8.3. MEASUREMENT EQUIPMENT USED.....	24
8.4. LIMITS AND MEASUREMENT RESULT.....	24
<b>9. RADIATED EMISSION.....</b>	<b>34</b>
9.1. MEASUREMENT PROCEDURE.....	34
9.2. TEST SETUP.....	36
9.3. LIMITS AND MEASUREMENT RESULT.....	37
9.4. TEST RESULT.....	37
<b>10. NUMBER OF HOPPING FREQUENCY.....</b>	<b>47</b>
10.1. MEASUREMENT PROCEDURE.....	47
10.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION).....	47
10.3. MEASUREMENT EQUIPMENT USED.....	47
10.4. LIMITS AND MEASUREMENT RESULT.....	47
<b>11. TIME OF OCCUPANCY (DWELL TIME).....</b>	<b>48</b>
11.1. MEASUREMENT PROCEDURE.....	48
11.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION).....	48
11.3. MEASUREMENT EQUIPMENT USED.....	48
11.4. LIMITS AND MEASUREMENT RESULT.....	48
<b>12. FREQUENCY SEPARATION.....</b>	<b>52</b>
12.1. MEASUREMENT PROCEDURE.....	52
12.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION).....	52
12.3. MEASUREMENT EQUIPMENT USED.....	52
12.4. LIMITS AND MEASUREMENT RESULT.....	52
<b>13. FCC LINE CONDUCTED EMISSION TEST.....</b>	<b>55</b>
13.1. LIMITS OF LINE CONDUCTED EMISSION TEST.....	55
13.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST.....	55
13.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST.....	56
13.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST.....	56
13.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST.....	57
<b>APPENDIX A: PHOTOGRAPHS OF TEST SETUP.....</b>	<b>59</b>

## TEST RESULT CERTIFICATION

**Applicant's name**.....: Dongguan Yihua Electrical Appliance Technology CO., LTD  
**Address**.....: No. 5, Nanyu Industrial Park, Nanchang Road, Wanglian Hamlet, Wangniudun Town, Dongguan City, Guangdong Province, China  
**Manufacturer's Name**.....: Dongguan Yihua Electrical Appliance Technology CO., LTD  
**Address**.....: No. 5, Nanyu Industrial Park, Nanchang Road, Wanglian Hamlet, Wangniudun Town, Dongguan City, Guangdong Province, China

### Product description

**Product name**.....: CD Shelf System With AM/FM Stereo Radio and Bluetooth Wireless Technology  
**Trademark** .....: MAGNAVOX, CRAIG, borne, Bluestream, naxa  
**Model Name** .....: MM435  
**Series Model**.....: M029B, MS500B, BS029MS, NS-441, MM434  
**Difference Description**.....: The circuit principle and internal structure are the same, appearance color and the model name are different.  
**Rating(s)**.....: Input: AC 120V 60Hz 18W

**Standards**.....: FCC PART 15.247

We hereby certify that:

The above equipment was tested by Shenzhen NTEK Testing Technology Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with radiated emission limits of FCC PART 15.247.

### Date of Test

Date (s) of performance of tests..... July. 11, 2020 to July. 23, 2020

Date of Issue..... July. 23, 2020

Test Result..... **Pass**

Testing Engineer : Leo.Zhu  
(Leo.Zhu)

Technical Manager : Eder.Zhan  
(Eder.Zhan)

Authorized Signatory : Wetow Huang  
(Wetow Huang)

## 1. GENERAL INFORMATION

### 1.1. PRODUCT DESCRIPTION

The EUT is designed as “Bluetooth Headset”. It is designed by way of utilizing the GFSK, Pi/4 DQPSK and 8DPSK technology to achieve the system operation.

A major technical description of EUT is described as following

Operation Frequency	2.402 GHz to 2.480GHz
RF Output Power	1.36dBm(Max)
Bluetooth Version	V 5.0
Modulation	BR <input checked="" type="checkbox"/> GFSK, EDR <input checked="" type="checkbox"/> $\pi/4$ -DQPSK, <input checked="" type="checkbox"/> 8DPSK BLE <input type="checkbox"/> GFSK 1Mbps <input type="checkbox"/> GFSK 2Mbps
Number of channels	79
Hardware Version	V1.0
Software Version	V1.0
Antenna Designation	PCB Antenna(Comply with requirements of the FCC part 15.203)
Antenna Gain	1.0dBi
Power Supply	Input: DC 5V 1.0A by Micro USB; 3.7V by Battery

### 1.2. TABLE OF CARRIER FREQUENCIES

Frequency Band	Channel Number	Frequency
2402~2480MHZ	0	2402MHZ
	1	2403MHZ
	:	:
	38	2440 MHZ
	39	2441 MHZ
	40	2442 MHZ
	:	:
	77	2479 MHZ
	78	2480 MHZ

### 1.3. RECEIVER INPUT BANDWIDTH

The input bandwidth of the receiver is 1.3MHz. In every connection one Bluetooth device is the master and the other one is slave. The master determines the hopping sequence. The slave follows this sequence. Both devices shift between RX and TX time slot according to the clock of the master. Additionally the type of connection (e.g. single or multislot packet) is set up at the beginning of the connection. The master adapts its hopping frequency and its TX/RX timing according to the packet type of the connection. Also the slave of the connection will use these settings.

Repeating of a packet has no influence on the hopping sequence. The hopping sequence generated by the master of the connection will be followed in any case. That means, a repeated packet will not be sent on the same frequency, it is sent on the next frequency of the hopping sequence.

### 1.4. EXAMPLE OF A HOPPING SEQUENCE IN DATA MODE

Example of a 79 hopping sequence in data mode:

40,21,44,23,42,53,46,55,48,33,52,35,50,65,54,67  
56,37,60,39,58,69,62,71,64,25,68,27,66,57,70,59  
72,29,76,31,74,61,78,63,01,41,05,43,03,73,07,75  
09,45,13,47,11,77,15,00,64,49,66,53,68,02,70,06  
01, 51, 03, 55, 05, 04

### 1.5. EQUALLY AVERAGE USE OF FREQUENCIES AND BEHAVIOUR

The generation of the hopping sequence in connection mode depends essentially on two input values:

1. LAP/UAP of the master of the connection.
2. Internal master clock

The LAP (lower address part) are the 24 LSB's of the 48 BD\_ADDRESS. The BD\_ADDRESS is an unambiguous number of every Bluetooth unit. The UAP (upper address part) are the 24 MSB's of the 48 BD\_ADDRESS. The internal clock of a Bluetooth unit is derived from a free running clock which is never adjusted and is never turned off. For synchronization with other units only offset are used. It has no relation to the time of the day. Its resolution is at least half the RX/TX slot length of 312.5us. The clock has a cycle of about one day (23h30). In most cases it is implemented as 28 bit counter. For the deriving of the hopping sequence the entire LAP (24 bits), 4 LSB's (4 bits) (Input 1) and the 27 MSB's of the clock (Input 2) are used. With this input values different mathematical procedures (permutations, additions, XOR-operations) are performed to generate the Sequence. This will be done at the beginning of every new transmission. Regarding short transmissions the Bluetooth system has the following behavior:

The first connection between the two devices is established, a hopping sequence was generated. For transmitting the wanted data the complete hopping sequence was not used. The connection ended.

The second connection will be established. A new hopping sequence is generated. Due to the fact the Bluetooth clock has a different value, because the period between the two transmissions is longer (and it cannot be shorter) than the minimum resolution of the clock (312.5us). The hopping sequence will always differ from the first one.

### 1.6. RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for **FCC ID: 2AT26-M029B** filing to comply with the FCC PART 15.247 requirements.

### 1.7. TEST METHODOLOGY

Both conducted and radiated testing was performed according to the procedures in ANSI C63.10 (2013). Radiated testing was performed at an antenna to EUT distance 3 meters.

### 2. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95%.

- Uncertainty of Conducted Emission,  $U_c = \pm 3.2$  dB
- Uncertainty of Radiated Emission below 1GHz,  $U_c = \pm 3.9$  dB
- Uncertainty of Radiated Emission above 1GHz,  $U_c = \pm 4.8$  dB
- Uncertainty of total RF power, conducted,  $U_c = \pm 0.8$  dB
- Uncertainty of spurious emissions, conducted,  $U_c = \pm 2.7$  dB
- Uncertainty of Occupied Channel Bandwidth:  $U_c = \pm 2$  %
- Uncertainty of Dwell Time:  $U_c = \pm 2$  %
- Uncertainty of Frequency:  $U_c = \pm 2$  %

### 3. DESCRIPTION OF TEST MODES

NO.	TEST MODE DESCRIPTION
1	Low channel GFSK
2	Middle channel GFSK
3	High channel GFSK
4	Low channel $\pi/4$ -DQPSK
5	Middle channel $\pi/4$ -DQPSK
6	High channel $\pi/4$ -DQPSK
7	Low channel 8DPSK
8	Middle channel 8DPSK
9	High channel 8DPSK
10	Hopping mode GFSK
11	Hopping mode $\pi/4$ -DQPSK
12	Hopping mode 8DPSK

Note:

1. Only the result of the worst case was recorded in the report, if no other cases.
2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
3. For Conducted Test method, a temporary antenna connector is provided by the manufacture.
4. The test software is the Blue Test3 which can set the EUT into the individual test modes.




#### 4. SYSTEM TEST CONFIGURATION

##### 4.1. CONFIGURATION OF EUT SYSTEM

Radiated Emission Configure :



Conducted Emission Configure :



##### 4.2 EQUIPMENT USED IN TESTED SYSTEM

Item	Equipment	Model No.	ID or Specification	Remark
1	CD Shelf System With AM/FM Stereo Radio and Bluetooth Wireless Technology	MM435,M029B,MS500B,B S029MS,NS-441,MM434	2AT26-M029B	EUT
2	Charger line	/	0.7m	AE

##### 4.3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
15.247 (b)(1)	Peak Output Power	Compliant
15.247 (a)(1)	20 dB Bandwidth	Compliant
15.247 (d)	Conducted Spurious Emission	Compliant
15.209	Radiated Emission	Compliant
15.247 (a)(1)(iii)	Number of Hopping Frequency	Compliant
15.247 (a)(1)(iii)	Time of Occupancy	Compliant
15.247 (a)(1)	Frequency Separation	Compliant
15.207	Conducted Emission	Compliant

## 5. TEST FACILITY

Site Description	
CNAS-Lab.	The Laboratory has been assessed and proved to be in compliance with CNAS-CL01:2006 (identical to ISO/IEC 17025:2005) The Certificate Registration Number is L5516.
IC-Registration	The Certificate Registration Number is 9270A-1.
FCC- Accredited	Test Firm Registration Number: 463705. Designation Number: CN1184
A2LA-Lab.	The Certificate Registration Number is 4298.01 This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General requirements for the competence of testing and calibration laboratories. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated 8 January 2009).
Name of Firm	Shenzhen NTEK Testing Technology Co., Ltd.
Site Location	1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen 518126 P.R. China.

## TEST EQUIPMENT OF CONDUCTED EMISSION TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESPI	101206	Jun. 10, 2020	Jun. 09, 2021
LISN	R&S	ESH2-Z5	101313	Apr. 18, 2020	Apr. 17, 2021

## TEST EQUIPMENT OF RADIATED EMISSION TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESCI	10096	Jun. 10, 2020	Jun. 09, 2021
EXA Signal Analyzer	Aglient	N9020A	MY49100060	May. 11, 2020	May. 10, 2021
2.4GHz Fliter	EM Electronics	2400-2500MHz	N/A	Feb. 27, 2020	Feb. 26, 2021
Attenuator	ZHINAN	E-002	N/A	Aug. 26, 2019	Aug. 25, 2020
Horn antenna	SCHWARZBECK	BBHA 9170	#768	Sep. 21, 2017	Sep. 20, 2020
Active loop antenna (9K-30MHz)	ZHINAN	ZN30900C	18051	Jun. 14, 2020	Jun. 13, 2022
Double-Ridged Waveguide Horn	ETS LINDGREN	3117	00034609	May. 26, 2020	May. 25, 2022
Broadband Preamplifier	ETS LINDGREN	3117PA	00225134	Oct. 25, 2019	Oct. 24, 2020
ANTENNA	SCHWARZBECK	VULB9168	D69250	Sep. 28, 2020	Sep. 27, 2022
Spectrum analyzer	R&S	FSU	HKE-048	Dec. 20, 2019	Dec. 19, 2020

## 6. PEAK OUTPUT POWER

### 6.1. MEASUREMENT PROCEDURE


For peak power test:

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
2. Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
3. RBW > 20 dB bandwidth of the emission being measured.
4. VBW  $\geq$  RBW.
5. Sweep: Auto.
6. Detector function: Peak.
7. Trace: Max hold.

Allow trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power, after any corrections for external attenuators and cables.

### 6.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)


#### PEAK POWER TEST SETUP



6.3. LIMITS AND MEASUREMENT RESULT


PEAK OUTPUT POWER MEASUREMENT RESULT FOR GFSK MOUDULATION			
Frequency (GHz)	Peak Power (dBm)	Applicable Limits (dBm)	Pass or Fail
2.402	-1.81	30	Pass
2.441	-2.82	30	Pass
2.480	-4.08	30	Pass

CH0




Date: 22.JUL.2020 13:33:25

CH39



Date: 22.JUL.2020 13:34:04


CH78



Date: 22.JUL.2020 13:34:29


PEAK OUTPUT POWER MEASUREMENT RESULT FOR $\pi$ /4-DQPSK MODULATION			
Frequency (GHz)	Peak Power (dBm)	Applicable Limits (dBm)	Pass or Fail
2.402	0.94	30	Pass
2.441	-0.50	30	Pass
2.480	-1.43	30	Pass

CH0




Date: 22.JUL.2020 13:35:59

CH39



Date: 22.JUL.2020 13:35:34


CH78



Date: 23.JUL.2020 11:05:01

PEAK OUTPUT POWER MEASUREMENT RESULT FOR 8-DPSK MODULATION			
Frequency (GHz)	Peak Power (dBm)	Applicable Limits (dBm)	Pass or Fail
2.402	1.36	30	Pass
2.441	0.25	30	Pass
2.480	-1.08	30	Pass


CH0



Date: 22.JUL.2020 13:36:14




CH39



Date: 22.JUL.2020 13:36:28

CH78




Date: 22.JUL.2020 13:38:12

7. 20DB BANDWIDTH

7.1. MEASUREMENT PROCEDURE

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hoping channel  
The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW; Sweep = auto; Detector function = peak
- 4. Set SPA Trace 1 Max hold, then View.


7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)



7.3. LIMITS AND MEASUREMENT RESULTS


MEASUREMENT RESULT FOR GFSK MOUDULATION			
Applicable Limits	Measurement Result		
	Test Data (MHz)		Criteria
N/A	Low Channel	814.102	PASS
	Middle Channel	814.1025	PASS
	High Channel	814.102	PASS

TEST PLOT OF BANDWIDTH FOR LOW CHANNEL




Date: 23.JUL.2020 11:12:42

TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



Date: 23.JUL.2020 11:13:25


TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



Date: 23.JUL.2020 11:13:59


MEASUREMENT RESULT FOR $\pi$ /4-DQPSK MODULATION			
Applicable Limits	Measurement Result		
	Test Data (MHz)		Criteria
N/A	Low Channel	1.29807	PASS
	Middle Channel	1.2980	PASS
	High Channel	1.2980	PASS

TEST PLOT OF BANDWIDTH FOR LOW CHANNEL




Date: 23.JUL.2020 11:15:49

TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



Date: 23.JUL.2020 11:15:28


TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



Date: 23.JUL.2020 11:15:02


MEASUREMENT RESULT FOR 8-DPSK MODULATION			
Applicable Limits	Measurement Result		
	Test Data (MHz)		Criteria
N/A	Low Channel	1.2916	PASS
	Middle Channel	1.2948	PASS
	High Channel	1.2980	PASS

TEST PLOT OF BANDWIDTH FOR LOW CHANNEL




Date: 23.JUL.2020 11:16:14

TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



Date: 23.JUL.2020 11:16:38

TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



Date: 23.JUL.2020 11:17:05



## 8. CONDUCTED SPURIOUS EMISSION

### 8.1. MEASUREMENT PROCEDURE

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
2. Set the EUT Work on the top, the Middle and the bottom operation frequency individually.
3. Set the Span = wide enough to capture the peak level of the in-band emission and all spurious emissions from the lowest frequency generated in the EUT up through the 10th harmonic.  
RBW = 100 kHz; VBW= 300 kHz; Sweep = auto; Detector function = peak.
4. Set SPA Trace 1 Max hold, then View.

### 8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

The same as described in section 8.2


### 8.3. MEASUREMENT EQUIPMENT USED

The same as described in section 6


### 8.4. LIMITS AND MEASUREMENT RESULT

LIMITS AND MEASUREMENT RESULT		
Applicable Limits	Measurement Result	
	Test Data	Criteria
In any 100 KHz Bandwidth Outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produce by the intentional radiator shall be at least 20 dB below that in 100KHz bandwidth within the band that contains the highest level of the desired power. In addition, radiation emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in§15.209(a))	At least -20dBc than the limit Specified on the BOTTOM Channel	PASS
	At least -20dBc than the limit Specified on the TOP Channel	PASS

# TEST RESULT FOR ENTIRE FREQUENCY RANGE TEST PLOT OF OUT OF BAND EMISSIONS WITH THE WORST CASE OF 8DPQSK MODULATION IN LOW CHANNEL




Date: 22.JUL.2020 14:02:10




Date: 22.JUL.2020 14:03:30

TEST PLOT OF OUT OF BAND EMISSIONS  
OF 8DPQSK MODULATION IN MIDDLE CHANNEL




Date: 22.JUL.2020 14:04:12




Date: 22.JUL.2020 14:04:50

# TEST PLOT OF OUT OF BAND EMISSIONS OF 8DPQSK MODULATION IN HIGH CHANNEL




Date: 22.JUL.2020 14:05:59



Date: 22.JUL.2020 14:06:41


Note: The peak emissions without marker on the above plots are fundamental wave and need not to compare with the limit. The GFSK modulation is the worst case and only those data recorded in the report.

TEST RESULT FOR BAND EDGE  
GFSK MODULATION IN LOW CHANNEL  
Hopping off




Date: 22.JUL.2020 14:20:54

Hopping on




Date: 22.JUL.2020 14:24:30

GFSK MODULATION IN HIGH CHANNEL  
Hopping off




Date: 22.JUL.2020 14:26:39

Hopping on




Date: 22.JUL.2020 14:28:50

$\pi$  /4-DQPSK MODULATION IN LOW CHANNEL  
Hopping off




Date: 22.JUL.2020 14:40:02

Hopping on




Date: 22.JUL.2020 14:43:21

$\pi$  /4-DQPSK MODULATION IN HIGH CHANNEL  
Hopping off



Date: 22.JUL.2020 14:31:43


Hopping on



Date: 22.JUL.2020 14:36:32




8-DPSK MODULATION IN LOW CHANNEL  
Hopping off




Date: 22.JUL.2020 14:49:28

Hopping on




Date: 22.JUL.2020 14:53:54

8-DPSK MODULATION IN HIGH CHANNEL  
Hopping off



Date: 22.JUL.2020 15:04:37

Hopping on



Date: 22.JUL.2020 15:08:11

## **9. RADIATED EMISSION**

### **9.1. MEASUREMENT PROCEDURE**

1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High - Low scan is not required in this case.


The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP
Start ~Stop Frequency	1GHz~26.5GHz 1MHz/3MHz for Peak, 1MHz/3MHz for Average


Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP

## 9.2. TEST SETUP


Radiated Emission Test-Setup Frequency Below 30MHz



RADIATED EMISSION TEST SETUP 30MHz-1000MHz



RADIATED EMISSION TEST SETUP ABOVE 1000MHz



9.3. LIMITS AND MEASUREMENT RESULT

15.209 Limit in the below table has to be followed

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note: All modes were tested For restricted band radiated emission,  
the test records reported below are the worst result compared to other modes.


9.4. TEST RESULT

RADIATED EMISSION BELOW 30MHZ

Emission from 9kHz to 30MHz are more than 20dB below the limit.

RADIATED EMISSION BELOW 1GHZ


EUT	CD Shelf System With AM/FM Stereo Radio and Bluetooth Wireless Technology	Model Name	MM435
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 4	Antenna	Horizontal



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector	Antenna Height cm	Table Degree degree	Comment
1	*	33.5770	50.61	-22.11	28.50	40.00	-11.50	QP			
2		35.2821	45.03	-23.21	21.82	40.00	-18.18	QP			
3		37.2202	46.14	-24.09	22.05	40.00	-17.95	QP			
4		44.6064	42.43	-26.63	15.80	40.00	-24.20	QP			
5		79.6954	44.23	-30.03	14.20	40.00	-25.80	QP			
6		102.7192	40.84	-25.64	15.20	43.50	-28.30	QP			

RESULT: PASS

EUT	CD Shelf System With AM/FM Stereo Radio and Bluetooth Wireless Technology	Model Name	MM435
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 4	Antenna	Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector	Antenna Height cm	Table Degree degree	Comment
1		32.3492	45.17	-21.80	23.37	40.00	-16.63	QP			
2		34.0813	43.89	-22.89	21.00	40.00	-19.00	QP			
3	*	36.0638	52.63	-23.77	28.86	40.00	-11.14	QP			
4		37.9117	40.56	-24.29	16.27	40.00	-23.73	QP			
5		80.8210	44.79	-28.98	15.81	40.00	-24.19	QP			
6		102.7192	46.75	-26.14	20.61	43.50	-22.89	QP			

## RESULT: PASS

**Note:** 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. All test modes had been pre-tested. The mode 4 is the worst case and recorded in the report.



### RADIATED EMISSION ABOVE 1GHZ

<b>EUT</b>	CD Shelf System With AM/FM Stereo Radio and Bluetooth Wireless Technology	<b>Model Name</b>	MM435
<b>Temperature</b>	25°C	<b>Relative Humidity</b>	55.4%
<b>Pressure</b>	960hPa	<b>Test Voltage</b>	Normal Voltage
<b>Test Mode</b>	Mode 7	<b>Antenna</b>	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4804.000	47.75	0.28	48.03	74	-25.97	peak
4804.000	41.02	0.14	41.17	54	-12.83	AVG
7206.000	42.54	2.45	44.99	74	-29.01	peak
7206.000	37.63	2.50	40.13	54	-13.87	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

<b>EUT</b>	CD Shelf System With AM/FM Stereo Radio and Bluetooth Wireless Technology	<b>Model Name</b>	MM435
<b>Temperature</b>	25°C	<b>Relative Humidity</b>	55.4%
<b>Pressure</b>	960hPa	<b>Test Voltage</b>	Normal Voltage
<b>Test Mode</b>	Mode 7	<b>Antenna</b>	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4804.000	46.24	0.18	46.41	74	-27.59	peak
4804.000	39.74	0.26	40.00	54	-14.00	AVG
7206.000	42.80	2.34	45.14	74	-28.86	peak
7206.000	32.53	2.50	35.03	54	-18.97	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

<b>EUT</b>	CD Shelf System With AM/FM Stereo Radio and Bluetooth Wireless Technology	<b>Model Name</b>	MM435
<b>Temperature</b>	25°C	<b>Relative Humidity</b>	55.4%
<b>Pressure</b>	960hPa	<b>Test Voltage</b>	Normal Voltage
<b>Test Mode</b>	Mode 8	<b>Antenna</b>	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4882.000	46.18	0.26	46.44	74	-27.56	peak
4882.000	42.24	0.42	42.66	54	-11.34	AVG
7323.000	41.21	2.44	43.65	74	-30.35	peak
7323.000	37.52	2.57	40.08	54	-13.92	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

<b>EUT</b>	CD Shelf System With AM/FM Stereo Radio and Bluetooth Wireless Technology	<b>Model Name</b>	MM435
<b>Temperature</b>	25°C	<b>Relative Humidity</b>	55.4%
<b>Pressure</b>	960hPa	<b>Test Voltage</b>	Normal Voltage
<b>Test Mode</b>	Mode 8	<b>Antenna</b>	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4882.000	44.14	0.22	44.36	74	-29.64	peak
4882.000	39.30	0.40	39.70	54	-14.30	AVG
7323.000	42.80	2.60	45.39	74	-28.61	peak
7323.000	36.08	2.66	38.74	54	-15.26	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

<b>EUT</b>	CD Shelf System With AM/FM Stereo Radio and Bluetooth Wireless Technology	<b>Model Name</b>	MM435
<b>Temperature</b>	25°C	<b>Relative Humidity</b>	55.4%
<b>Pressure</b>	960hPa	<b>Test Voltage</b>	Normal Voltage
<b>Test Mode</b>	Mode 9	<b>Antenna</b>	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4960.000	47.74	0.43	48.18	74	-25.82	peak
4960.000	39.06	0.50	39.56	54	-14.44	AVG
7440.000	41.96	2.65	44.60	74	-29.40	peak
7440.000	37.06	2.74	39.81	54	-14.19	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

<b>EUT</b>	CD Shelf System With AM/FM Stereo Radio and Bluetooth Wireless Technology	<b>Model Name</b>	MM435
<b>Temperature</b>	25°C	<b>Relative Humidity</b>	55.4%
<b>Pressure</b>	960hPa	<b>Test Voltage</b>	Normal Voltage
<b>Test Mode</b>	Mode 9	<b>Antenna</b>	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4960.000	46.45	0.22	46.67	74	-27.33	peak
4960.000	39.37	0.40	39.77	54	-14.23	AVG
7440.000	41.16	2.91	44.07	74	-29.93	peak
7440.000	34.81	2.66	37.47	54	-16.53	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

## RESULT: PASS

### Note:

Other emissions from 1G to 25 GHz are considered as ambient noise. No recording in the test report.  
Factor = Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.


The “Factor” value can be calculated automatically by software of measurement system.

All test modes had been tested. The GFSK modulation is the worst case and recorded in the report.

### TEST RESULT FOR RESTRICTED BANDS REQUIREMENTS


EUT	CD Shelf System With AM/FM Stereo Radio and Bluetooth Wireless Technology	Model Name	MM435
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 7	Antenna	Horizontal

#### PK



Date: 22.JUL.2020 16:02:03

#### AV




Date: 22.JUL.2020 16:02:41

**RESULT: PASS**


EUT	CD Shelf System With AM/FM Stereo Radio and Bluetooth Wireless Technology	Model Name	MM435
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 7	Antenna	Vertical

PK



Date: 22.JUL.2020 16:04:26

AV




Date: 22.JUL.2020 16:03:37

RESULT: PASS


EUT	CD Shelf System With AM/FM Stereo Radio and Bluetooth Wireless Technology	Model Name	MM435
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 9	Antenna	Horizontal

PK



Date: 22.JUL.2020 16:07:43

AV




Date: 22.JUL.2020 16:15:09

RESULT: PASS


EUT	CD Shelf System With AM/FM Stereo Radio and Bluetooth Wireless Technology	Model Name	MM435
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 9	Antenna	Vertical

PK



Date: 22.JUL.2020 16:16:33

AV



Date: 22.JUL.2020 16:15:50

RESULT: PASS

**Note:** The factor had been edited in the “Input Correction” of the Spectrum Analyzer. So the Amplitude of test plots is equal to Reading level plus the Factor in dB. Use the A dB(μV) to represent the Amplitude. Use the F dB(μV/m) to represent the Field Strength. So A=F. All test modes had been pre-tested. The GFSK modulation is the worst case and recorded in the report.

## 10. NUMBER OF HOPPING FREQUENCY

### 10.1. MEASUREMENT PROCEDURE

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

1. Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
2. RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
3. VBW  $\geq$  RBW. Sweep: Auto. Detector function: Peak. Trace: Max hold.
4. Allow the trace to stabilize.

### 10.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)

Same as described in section 8.2


### 10.3. MEASUREMENT EQUIPMENT USED

The same as described in section 6

### 10.4. LIMITS AND MEASUREMENT RESULT

TOTAL NO. OF HOPPING CHANNEL	LIMIT (NO. OF CH)	MEASUREMENT (NO. OF CH)	RESULT
	$\geq 15$	79	PASS

TEST PLOT FOR NO. OF TOTAL CHANNELS



Date: 23.JUL.2020 15:20:34

Note: The GFSK modulation is the worst case and recorded in the report.



## 11. TIME OF OCCUPANCY (DWELL TIME)

### 11.1. MEASUREMENT PROCEDURE

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

1. Span: Zero span, centered on a hopping channel.
2. RBW shall be  $\leq$  channel spacing and where possible RBW should be set  $\gg 1/T$ , where T is the expected dwell time per channel.
3. Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.
4. Detector function: Peak. Trace: Max hold.
5. Use the marker-delta function to determine the transmit time per hop.
6. Repeat the measurement using a longer sweep time to determine the number of hops over the period specified in the requirements. The sweep time shall be equal to, or less than, the period specified in the requirements. Determine the number of hops over the sweep time and calculate the total number of hops in the period specified in the requirements, using the following equation:  

$$(\text{Number of hops in the period specified in the requirements}) = (\text{number of hops on spectrum analyzer}) \times (\text{period specified in the requirements} / \text{analyzer sweep time})$$
7. The average time of occupancy is calculated from the transmit time per hop multiplied by the number of hops in the period specified in the requirements.

### 11.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)

Same as described in section 8.2

### 11.3. MEASUREMENT EQUIPMENT USED


The same as described in section 6

### 11.4. LIMITS AND MEASUREMENT RESULT


Channel	Time of Pulse for DH5 (ms)	Number of hops in the period specified in the requirements	Sweep Time (ms)	Limit (ms)
Low	2.341	31*3	250.038	400
Middle	2.890	32*3	308.675	400
High	2.879	30*3	307.500	400

Note: The 8-DPSK modulation is the worst case and recorded in the report.

TEST PLOT OF LOW CHANNEL




Date: 22.JUL.2020 16:38:44




Date: 22.JUL.2020 16:49:01

TEST PLOT OF MIDDLE CHANNEL




Date: 22.JUL.2020 16:41:23




Date: 22.JUL.2020 16:44:06

TEST PLOT OF HIGH CHANNEL



Date: 22.JUL.2020 16:46:26



Date: 22.JUL.2020 16:48:02

## 12. FREQUENCY SEPARATION

### 12.1. MEASUREMENT PROCEDURE

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

1. Span: Wide enough to capture the peaks of two adjacent channels.
  2. RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
  3. Video (or average) bandwidth (VBW)  $\geq$  RBW.
  4. Sweep: Auto. e) Detector function: Peak. f) Trace: Max hold. g) Allow the trace to stabilize.
- Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

### 12.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)

Same as described in section 6.2

### 12.3. MEASUREMENT EQUIPMENT USED


The same as described in section 6.3

### 12.4. LIMITS AND MEASUREMENT RESULT


CHANNEL	CHANNEL SEPARATION	LIMIT	RESULT
	KHz	KHz	
CH00	1000	2/3 20 dB BW	Pass
CH39	1005	2/3 20 dB BW	Pass
CH78	1001	2/3 20 dB BW	Pass

TEST PLOT FOR FREQUENCY SEPARATION


CH00



CH39



# CH78



Note: The 8-DPSK modulation is the worst case and recorded in the report.

13. FCC LINE CONDUCTED EMISSION TEST


13.1. LIMITS OF LINE CONDUCTED EMISSION TEST

Frequency	Maximum RF Line Voltage	
	Q.P.( dBuV)	Average( dBuV)
150kHz~500kHz	66-56	56-46
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Note:

- 1. The lower limit shall apply at the transition frequency.
- 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

13.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST





**13.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST**

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
2. Support equipment, if needed, was placed as per ANSI C63.10.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
4. All support equipments received AC120V/60Hz power from a LISN, if any.
5. The EUT received DC 5V power from adapter which received AC120V/60Hz power from a LISN.
6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.
9. The test mode(s) were scanned during the preliminary test.


Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

**13.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST**

1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less -2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
3. The test data of the worst case condition(s) was reported on the Summary Data page.

### 13.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST


Line Conducted Emission Test Line 1-L



No.	Mk.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		0.1620	19.88	9.94	29.82	65.36	-35.54	QP	
2		0.1660	8.79	9.93	18.72	55.16	-36.44	AVG	
3		0.1860	8.33	9.91	18.24	54.21	-35.97	AVG	
4		0.1945	18.89	9.90	28.79	63.84	-35.05	QP	
5		0.3060	17.48	9.92	27.40	60.08	-32.68	QP	
6		0.3067	4.07	9.92	13.99	50.06	-36.07	AVG	
7		0.3620	4.70	9.92	14.62	48.68	-34.06	AVG	
8	*	0.3660	18.28	9.92	28.20	58.59	-30.39	QP	
9		0.4380	16.28	9.92	26.20	57.10	-30.90	QP	
10		0.4420	4.31	9.92	14.23	47.02	-32.79	AVG	
11		0.6980	14.39	9.95	24.34	56.00	-31.66	QP	
12		0.7019	1.14	9.95	11.09	46.00	-34.91	AVG	

RESULT: PASS

# Line Conducted Emission Test Line 2-N



No.	Mk.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		0.1924	17.35	9.90	27.25	63.93	-36.68	QP	
2		0.1949	8.21	9.90	18.11	53.83	-35.72	AVG	
3		0.2404	17.22	9.90	27.12	62.08	-34.96	QP	
4		0.2429	4.30	9.90	14.20	52.00	-37.80	AVG	
5		0.2878	16.60	9.92	26.52	60.59	-34.07	QP	
6		0.2878	4.28	9.92	14.20	50.59	-36.39	AVG	
7		0.3303	14.49	9.92	24.41	59.44	-35.03	QP	
8		0.3345	4.83	9.92	14.75	49.34	-34.59	AVG	
9		0.3704	16.61	9.93	26.54	58.49	-31.95	QP	
10		0.3704	4.19	9.93	14.12	48.49	-34.37	AVG	
11		0.4965	13.81	9.94	23.75	56.06	-32.31	QP	
12	*	0.4965	4.38	9.94	14.32	46.06	-31.74	AVG	


## RESULT: PASS

Note: All the test modes had been tested, the mode 1 was the worst case. Only the data of the worst case would be record in this test report.

**APPENDIX A: PHOTOGRAPHS OF TEST SETUP**  
CONDUCTED EMISSION TEST SETUP




RADIATED EMISSION TEST SETUP BELOW 1GHZ





**RADIATED EMISSION TEST SETUP ABOVE 1GHZ**



**----END OF REPORT----**