

FCC TEST REPORT

Product Name: NuStar 65 Portable Data Collector

Trade Mark:  3nStar

Model No.: Nustar65

Report Number: 24081713266RFC-4

Test Standards: FCC 47 CFR Part 15 Subpart E

FCC ID: 2ATAN-NUSTAR65

Test Result: PASS

Date of Issue: October 23, 2024

Prepared for:

3nStar, Inc.

10813 NW 30th, Street, STE#110, Doral FL, 33172, USA

Prepared by:

Shenzhen UnionTrust Quality and Technology Co., Ltd.

**16/F, Block A, Building 6th, Baoneng Science and Technology Park,
Longhua Street, Longhua District, Shenzhen, China**

TEL: +86-755-2823 0888

FAX: +86-755-2823 0886

Prepared by:

David Chen

David Chen
Senior Project Engineer

Reviewed by:

Henry Lu

Henry Lu
Team Leader

Approved by:

Robben Chen

Robben Chen
Assistant Manager

Date:

October 23, 2024

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2

Version

Version No.	Date	Description
V1.0	October 23, 2024	Original



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China
Tel: +86-755-28230888 Fax: +86-755-28230886 E-mail: info@uttlab.com <http://www.uttlab.com>
UTTR-RF-FCCPART15.407-V1.2

CONTENTS

1. GENERAL INFORMATION	4
1.1 CLIENT INFORMATION	4
1.2 EUT INFORMATION	4
1.2.1 GENERAL DESCRIPTION OF EUT	4
1.2.2 DESCRIPTION OF ACCESSORIES	5
1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD	6
1.4 OTHER INFORMATION	7
1.5 DESCRIPTION OF SUPPORT UNITS	7
1.6 TEST LOCATION	7
1.7 TEST FACILITY	8
1.8 DEVIATION FROM STANDARDS	8
1.9 ABNORMALITIES FROM STANDARD CONDITIONS	8
1.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER	8
1.11 MEASUREMENT UNCERTAINTY	8
2. TEST SUMMARY	9
3. EQUIPMENT LIST	10
4. TEST CONFIGURATION	11
4.1 ENVIRONMENTAL CONDITIONS FOR TESTING	11
4.1.1 NORMAL OR EXTREME TEST CONDITIONS	11
4.1.2 RECORD OF NORMAL ENVIRONMENT AND TEST SAMPLE	11
4.2 TEST CHANNELS	12
4.3 EUT TEST STATUS	12
4.4 PRE-SCAN	13
4.5 TEST SETUP	13
4.5.1 FOR RADIATED EMISSIONS TEST SETUP	13
4.5.2 FOR CONDUCTED EMISSIONS TEST SETUP	15
4.5.3 FOR CONDUCTED RF TEST SETUP	15
4.6 SYSTEM TEST CONFIGURATION	16
4.7 DUTY CYCLE	17
5. RADIO TECHNICAL REQUIREMENTS SPECIFICATION	21
5.1 REFERENCE DOCUMENTS FOR TESTING	21
5.2 ANTENNA REQUIREMENT	21
5.3 26 dB BANDWIDTH & 99% OCCUPIED BANDWIDTH	22
5.4 6 dB BANDWIDTH & 99% OCCUPIED BANDWIDTH	23
5.5 MAXIMUM CONDUCTED OUTPUT POWER	24
5.6 PEAK POWER SPECTRAL DENSITY	29
5.7 RADIATED EMISSIONS AND BAND EDGE MEASUREMENT	31
5.8 DYNAMIC FREQUENCY SELECTION	64
5.9 AC POWER LINE CONDUCTED EMISSION	72
APPENDIX A RF TEST DATA	75
A.1 26 dB BANDWIDTH	75
A.2 99% OCCUPIED BANDWIDTH	102
A.3 6 dB BANDWIDTH	136
A.4 PEAK POWER SPECTRAL DENSITY	147
APPENDIX 1 PHOTOS OF TEST SETUP	184
APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS	184

1. GENERAL INFORMATION

1.1 CLIENT INFORMATION

Applicant:	3nStar, Inc.
Address of Applicant:	10813 NW 30th, Street, STE#110, Doral FL, 33172, USA
Manufacturer:	3nStar, Inc.
Address of Manufacturer:	10813 NW 30th, Street, STE#110, Doral FL, 33172, USA

1.2 EUT INFORMATION

1.2.1 General Description of EUT

Product Name:	NuStar 65 Portable Data Collector		
Model No.:	Nustar65		
Trade Mark:			
DUT Stage:	Identical Prototype		
EUT Supports Function: (Provided by the customer)	GSM Bands:	GSM850/PCS 1900	
	UTRA Bands:	WCDMA Band II/ Band V	
	E-UTRA Bands:	FDD Band 2/ 4/ 5/ 7/ 26	
		TDD Band 38/ 41	
	2.4 GHz ISM Band:	IEEE 802.11b/g/n	
		Bluetooth 5.1	
	5 GHz U-NII Bands:	5 150 - 5 250 MHz	IEEE 802.11a/n/ac
		5 250 - 5 350 MHz	IEEE 802.11a/n/ac
		5 470 - 5 730 MHz	IEEE 802.11a/n/ac
		5 725 - 5 850 MHz	IEEE 802.11a/n/ac
RNSS Bands:	1559 - 1610 MHz	BDS/ GPS/ GLONASS/ Galileo	
NFC:	13.553 - 13.567 MHz		
Software Version:	S651-G1-SC6101-NU419-V3.01.240830 (Provided by the customer)		
Hardware Version:	S651_MA_B08D_V1.0 (Provided by the customer)		
Sample Received Date:	August 16, 2024		
Sample Tested Date:	August 21, 2024 to September 27, 2024		
Remark:	The above EUT's information was provided by customer. Please refer to the specifications or user's manual for more detailed description.		

1.2.2 Description of Accessories

Adapter	
Model No.:	BI12T-050200-BdVU
Input:	100-240 V~50/60 Hz 0.5A
Output:	5.0 V $\equiv$ 2.0A

Battery	
Model No.:	BAT-655001
Battery Type:	Rechargeable Li-ion Battery
Rated Voltage:	3.87 Vdc
Limited Charge Voltage:	4.45 Vdc
Rated Capacity:	5050 mAh

Cable	
Description:	USB Type-C to USB 3.0 Type A Cable
Connector:	USB Type-C / USB 3.0 Type A
Cable Type:	Shielded without ferrite
Length:	1 Meter

Adapter (Desktop Cradle)	
Model No.:	BI24G-120200-AdU
Input:	100-240 V~50/60 Hz 0.8A
Output:	12 V $\equiv$ 2.0A

Desktop Cradle	
Model No.:	S65-HB
Input:	Input: 12.0 V $\equiv$ 2.0A
Output:	Output: 5.0 V $\equiv$ 3.0A and 4.4 V $\equiv$ 1.7A

1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD

Frequency Bands:	5150 MHz to 5250 MHz (U-NII-1)				
	5250 MHz to 5350 MHz (U-NII-2A)				
	5470 MHz to 5725 MHz (U-NII-2C)				
	5725 MHz to 5850 MHz (U-NII-3)				
Frequency Ranges:	5180 MHz to 5240 MHz				
	5260 MHz to 5320 MHz				
	5500 MHz to 5720 MHz				
	5745 MHz to 5825 MHz				
Support Standards:	IEEE 802.11a/n/ac				
TPC Function:	Not Support				
DFS Operational mode:	Slave without radar Interference detection function				
Type of Modulation:	IEEE 802.11a: OFDM(64QAM, 16QAM, QPSK, BPSK)				
	IEEE 802.11n: OFDM(64QAM, 16QAM, QPSK, BPSK)				
	IEEE 802.11ac: OFDM(256QAM, 64QAM, 16QAM, QPSK, BPSK)				
Channel Spacing:	IEEE 802.11a/n-HT20/ac-VHT20: 20 MHz				
	IEEE 802.11n-HT40/ac-VHT40: 40 MHz				
	IEEE 802.11ac-VHT80: 80 MHz				
Data Rate:	IEEE 802.11a: Up to 54 Mbps				
	IEEE 802.11n-HT20: Up to MCS7				
	IEEE 802.11n-HT40: Up to MCS7				
	IEEE 802.11ac-VHT20: Up to MCS8				
	IEEE 802.11ac-VHT40: Up to MCS9				
	IEEE 802.11ac-VHT80: Up to MCS9				
Number of Channels:	5150 MHz to 5250 MHz: 4 for IEEE 802.11a/n-HT20/ac-VHT20 2 for IEEE 802.11n-HT40/ac-VHT40 1 for IEEE 802.11acVHT80				
	5250 MHz to 5350 MHz: 4 for IEEE 802.11a/n-HT20/ac-VHT20 2 for IEEE 802.11n-HT40/ac-VHT40 1 for IEEE 802.11acVHT80				
	5470 MHz to 5725 MHz: 12 for IEEE 802.11a/n-HT20/ac-VHT20 6 for IEEE 802.11n-HT40/ac-VHT40 3 for IEEE 802.11ac-VHT80				
	5725 MHz to 5850 MHz: 5 for IEEE 802.11a/n-HT20/ac-VHT20 2 for IEEE 802.11n-HT40/ac-VHT40 1 for IEEE 802.11ac-VHT80				
Antenna Type:	LDS Antenna				
Antenna Gain: (Provided by the customer)	5150 - 5250 MHz	1.54 dBi			
	5250 - 5350 MHz	1.54 dBi			
	5470 - 5725 MHz	1.54 dBi			
	5725 - 5850 MHz	1.54 dBi			
Maximum conducted output power (dBm):		U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
	IEEE 802.11a:	13.99	13.95	13.82	13.93
	IEEE 802.11n-HT20:	13.64	13.76	13.69	13.69
	IEEE 802.11n-HT40:	13.74	13.62	8.70	13.57

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2

	IEEE 802.11ac-VHT20:	13.77	13.84	13.57	13.56
	IEEE 802.11ac-VHT40:	13.82	13.81	8.70	13.50
	IEEE 802.11ac-VHT80:	13.52	13.54	10.82	13.39
Normal Test Voltage:		3.85 Vdc			

1.4 OTHER INFORMATION

Operation Frequency Each of Channel				
	U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
IEEE 802.11a, IEEE 802.11n-HT20, IEEE 802.11ac-VHT20	$f = 5000 + 5k, k = 32 + 4n$			$f = 5000 + 5k,$ $k = 145 + 4n$
	$n = 1, \dots, 4$	$n = 5, \dots, 8$	$n = 17, \dots, 28$	$n = 1, \dots, 5$
IEEE 802.11n-HT40, IEEE 802.11ac-VHT40	$f = 5000 + 5k, k = 30 + 8n$			$f = 5000 + 5k,$ $k = 143 + 8n$
	$n = 1, 2$	$n = 1, \dots, 5$	$n = 9, \dots, 14$	$n = 1, 2$
IEEE 802.11ac-VHT80	$f = 5000 + 5k, k = 26 + 16n$			$f = 5000 + 5k,$ $k = 155$
	$n = 1$	$n = 1, 2$	$n = 5, 6, 7$	
Note: f is the operating frequency (MHz); k is the operating channel.				

1.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested with associated equipment below.

1) Support Equipment

Description	Manufacturer	Model No.	Serial Number	FCC ID	Supplied by
Notebook	DELL	Latitude 3400	16238087894	N/A	UnionTrust
Mouse	DELL	MS111	CN-011D3V-738	N/A	UnionTrust
Wireless Home Router	SAGEMCOM	FAST5280	253703944	VW3FAST5280	UnionTrust
Key-Press Attenuator	Huaxin	KT2.5-90/1S-2S	UTTL-EN023	N/A	UnionTrust
4 Way Divider	WOKEN	0120A040560002D	UTTL-EN028	N/A	UnionTrust

2) Support Cable

Cable No.	Description	Connector	Length	Supplied by
1	Antenna Cable	SMA	0.3 Meter	UnionTek

1.6 TEST LOCATION

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Telephone: +86 (0) 755 2823 0888

Fax: +86 (0) 755 2823 0886

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2

1.7 TEST FACILITY

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L9069

The measuring equipment utilized to perform the tests documented in this report has been calibrated once a year or in accordance with the manufacturer's recommendations, and is traceable under the ISO/IEC 17025 to international or national standards. Equipment has been calibrated by accredited calibration laboratories.

A2LA-Lab Certificate No.: 4312.01

Shenzhen UnionTrust Quality and Technology Co., Ltd. has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

ISED Wireless Device Testing Laboratories

CAB identifier: CN0032

FCC Accredited Lab.

Designation Number: CN1194

Test Firm Registration Number: 259480

1.8 DEVIATION FROM STANDARDS

None.

1.9 ABNORMALITIES FROM STANDARD CONDITIONS

None.

1.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER

None.

1.11 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

No.	Item	Measurement Uncertainty
1	Conducted emission 9kHz-150kHz	±3.2 dB
2	Conducted emission 150kHz-30MHz	±2.7 dB
3	Radiated emission 9kHz-30MHz	±4.7 dB
4	Radiated emission 30MHz-1GHz	±4.6 dB
5	Radiated emission 1GHz-18GHz	±4.4 dB
6	Radiated emission 18GHz-26GHz	±4.6 dB
7	Radiated emission 26GHz-40GHz	±4.6 dB
8	Conducted spurious emissions	± 2.7 dB
9	RF Power, Conducted	± 0.68 dB
10	Occupied Bandwidth	± 1.86 %
11	Radio Frequency	5.6 GHz: ± 6.4 x 10 ⁻⁸
12	Transmission Time	± 0.19 %

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2

2. TEST SUMMARY

FCC 47 CFR Part 15 Subpart E Test Cases			
Test Item	Test Requirement	Test Method	Result
Antenna Requirement	FCC 47 CFR Part 15 Subpart C Section 15.203 FCC 47 CFR Part 15 Subpart E Section 15.407(a)(1) (2)	N/A	PASS
26 dB emission bandwidth	FCC 47 CFR Part 15 Subpart E Section 15.407 (a)(2)(5)	KDB 789033 D02 v02r01 Section C.1	PASS
6 dB bandwidth	FCC 47 CFR Part 15 Subpart E Section 15.407 (e)	KDB 789033 D02 v02r01 Section C.2	PASS
99% Occupied Bandwidth	N/A	KDB 789033 D02 v02r01 Section D	N/A Note 1
Maximum conducted output power	FCC 47 CFR Part 15 Subpart E Section 15.407 (a)(1)(2)(3)	KDB 789033 D02 v02r01 Section E.3.a (Method PM)	PASS
Peak Power Spectral Density	FCC 47 CFR Part 15 Subpart E Section 15.407 (a)(1)(2)(3)	KDB 789033 D02 v02r01 Section F	PASS
Radiated Emissions and Band Edge Measurement	FCC 47 CFR Part 15 Subpart E Section 15.407 (b)(1)(2)(3)(4)(6) FCC 47 CFR Part 15 Subpart C Section 15.209/205	KDB 789033 D02 v02r01 Section G.3, G.4, G.5, and G.6	PASS
Dynamic Frequency Selection	FCC 47 CFR Part 15 Subpart E Section 15.407 (h)	KDB 905462 D03 Client Without DFS New Rules v01r02	PASS
AC Power Line Conducted Emission	FCC 47 CFR Part 15 Subpart E Section 15.407 (b)(6) FCC 47 CFR Part 15 Subpart C Section 15.207	ANSI C63.10-2013, Section 6.2.	PASS
Disclaimer and Explanations: The declared of product specification and data (e.g., antenna gain, RF specification, etc) for EUT presented in the report are provided by the customer, and the customer takes all the responsibilities for the accuracy of product specification.			
Note: 1) No test requirement, for reporting purposes only.			

For Dynamic Frequency Selection

Test Case	Result
Channel Availability Check Time	N/A Note 1
U-NII Detection Bandwidth	N/A Note 1
Channel Closing Transmission Time	PASS
Channel Move Time	PASS
DFS Detection Threshold	N/A Note 1
Non- Occupancy Period	N/A Note 1
Note: 1) The EUT is slave, NA in this whole report not applicable.	

3. EQUIPMENT LIST

Radiated Emission Test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date	Cal. Due date
☒	3m SAC	ETS-LINDGREN	3M	Euroshiedpn-CT 001270-1317	11-Nov-2023	10-Nov-2026
☒	EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY51440197	29-Mar-2024	28-Mar-2025
☒	Receiver	R&S	ESIB26	100114	27-Oct-2023	26-Oct-2024
☐	Loop Antenna	ETS-LINDGREN	6502	00202525	30-Oct-2023	29-Oct-2024
☒	Broadband Antenna	ETS-LINDGREN	3142E	00201566	30-Oct-2023	29-Oct-2024
☒	6dB Attenuator	Talent	RA6A5-N-18	18103001	30-Oct-2023	29-Oct-2024
☒	Preamplifier	HP	8447F	2805A02960	31-Oct-2023	30-Oct-2024
☒	Double-Ridged Waveguide Horn Antenna	ETS-LINDGREN	3117-PA	00201541	01-Apr-2024	31-Mar-2025
☒	Pre-amplifier	ETS-LINDGREN	00118385	00201874	31-Oct-2023	30-Oct-2024
☒	Double-Ridged Waveguide Horn Antenna	ETS-LINDGREN	3116C-PA	00202652	30-Oct-2023	29-Oct-2024
☒	Pre-amplifier	ETS-LINDGREN	00118384	00202652	30-Oct-2023	29-Oct-2024
☒	Multi device Controller	ETS-LINDGREN	7006-001	00160105	N/A	N/A
☒	Band Rejection Filter (5150MHz~5880MHz)	Micro-Tronics	BRM50716	G186	27-Oct-2023	26-Oct-2024
☒	Test Software	Audix	e3	Software Version: 9.160323		

Conducted Emission Test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date	Cal. Due date
☒	Receiver	R&S	ESR7	101181	27-Oct-2023	26-Oct-2024
☒	Pulse Limiter	R&S	ESH3-Z2	0357.8810.54	27-Oct-2023	26-Oct-2024
☒	LISN	R&S	ESH2-Z5	860014/024	27-Oct-2023	26-Oct-2024
☐	LISN	ETS-Lindgren	3816/2SH	00201088	27-Oct-2023	26-Oct-2024
☒	Test Software	EZ-EMC	EZ-CON	Software Version: EMC-CON 3A1.1		

RF Conducted Test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date	Cal. Due date
☒	EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY51440197	29-Mar-2024	28-Mar-2025
☐	EXA Spectrum Analyzer	KEYSIGHT	N9020A	MY51286807	27-Oct-2023	26-Oct-2024
☒	USB Wideband Power Sensor	KEYSIGHT	U2021XA	MY55430035	27-Oct-2023	26-Oct-2024
☒	EXG-B RF Analog Signal Generator	KEYSIGHT	N5171B	MY53051777	27-Oct-2023	26-Oct-2024
☒	MXG X-Series RF Vector Signal Generator	KEYSIGHT	N5182B	MY51350267	27-Oct-2023	26-Oct-2024

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2

4. TEST CONFIGURATION

4.1 ENVIRONMENTAL CONDITIONS FOR TESTING

4.1.1 Normal or Extreme Test Conditions

Environment Parameter	Selected Values During Tests		
Test Condition	Ambient		
	Temperature (°C)	Voltage	Relative Humidity (%)
NT/NV	+15 to +35	3.85V Battery	20 to 75
Remark: 1) NV: Normal Voltage; NT: Normal Temperature			

4.1.2 Record of Normal Environment and Test Sample

Test Item	Temp. (°C)	Relative Humidity (%)	Pressure (kPa)	Sample No.	Tested by
AC Power Line Conducted Emission	23.7	57.3	99.9	S202408164150-ZJA03/7	Linson Xie
26 dB emission bandwidth	22.8	51.2	99.8	S202408164150-ZJA06/7	Allen Zhou
Maximum conducted output power					
Peak Power Spectral Density					
6 dB bandwidth					
Dynamic Frequency Selection	24.9	52.9	100.1	S202408164150-ZJA03/7	Bowie Zhang
Radiated Emissions and Band Edge Measurement					

4.2 TEST CHANNELS

Mode	Tx/Rx Frequency	Test RF Channel Lists		
		Lowest(L)	Middle(M)	Highest(H)
IEEE 802.11a IEEE 802.11n-HT20 IEEE 802.11ac-VHT20	5150 MHz to 5250 MHz	Channel 36	Channel 44	Channel 48
		5180 MHz	5220 MHz	5240 MHz
	5250 MHz to 5350 MHz	Channel 52	Channel 60	Channel 64
		5260 MHz	5300 MHz	5320 MHz
	5470 MHz to 5725 MHz	Channel 100	Channel 120	Channel 140/144
		5500 MHz	5600 MHz	5700/5720 MHz
	5725 MHz to 5850 MHz	Channel 149	Channel 157	Channel 165
		5745 MHz	5785 MHz	5825 MHz
IEEE 802.11n-HT40 IEEE 802.11ac-VHT40	5150 MHz to 5250 MHz	Channel 38	--	Channel 46
		5190 MHz	--	5230 MHz
	5250 MHz to 5350 MHz	Channel 54	--	Channel 62
		5270 MHz	--	5310 MHz
	5470 MHz to 5725 MHz	Channel 102	Channel 118	Channel 134/142
		5510 MHz	5590 MHz	5670/5710 MHz
	5725 MHz to 5850 MHz	Channel 151	--	Channel 159
		5755 MHz	--	5795 MHz
IEEE 802.11ac-VHT80	5150 MHz to 5250 MHz	--	Channel 42	--
		--	5210 MHz	--
	5250 MHz to 5350 MHz	--	Channel 58	--
		--	5290 MHz	--
	5470 MHz to 5725 MHz	Channel 106	--	Channel 122/138
		5530 MHz	--	5610/5690 MHz
	5725 MHz to 5850 MHz	--	Channel 155	--
		--	5775 MHz	--

4.3 EUT TEST STATUS

Mode	Tx/Rx Function	Description
IEEE 802.11a/n/ac	1Tx/1Rx	1. Keep the EUT in transmitting mode with all kind of modulation and all kind of data rate.

Power Setting (Provided by the customer)					
Mode	U-NII-1	U-NII-2A	U-NII-2C	U-NII-3	
IEEE 802.11a	16	16	16	16	
IEEE 802.11n-HT20	16	16	16	16	
IEEE 802.11n-HT40	16	16	12	12	16
IEEE 802.11ac-VHT20	16	16	16	16	
IEEE 802.11ac-VHT40	16	16	12	12	16
IEEE 802.11ac-VHT80	16	16	14	14	16
Test Software (Provided by the customer)					
Engineering mode: *##3646633*##					

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2

4.4 PRE-SCAN

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and data rate. Following data rate was (were) selected for the final test as listed below

Mode	Worst-case data rates
IEEE 802.11a	6 Mbps
IEEE 802.11n-HT20	MCS0
IEEE 802.11n-HT40	MCS0
IEEE 802.11ac-VHT20	MCS0
IEEE 802.11ac-VHT40	MCS0
IEEE 802.11ac-VHT80	MCS0

4.5 TEST SETUP

4.5.1 For Radiated Emissions test setup

Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz





Figure 3. Above 1GHz



The diagram illustrates the experimental setup within a Shielding Room. On the left, a PC and a Receiver are connected to a Pulse Limiter. The Receiver is connected to LISN 1, which is connected to the AC Mains. The AC Mains are connected to the Test table. The Test table is supported by a frame with a height of 40 cm. The Test table is covered with a material with an insulation property of ≤ 0.15 m. Two EUT/AE units are placed on the Test table, separated by a distance of 10 cm. A PSU is connected to the EUT/AE units. The distance from the AC Mains to the EUT/AE units is 80 cm. The distance from the EUT/AE units to LISN 2 is 80 cm. LISN 2 is connected to the AC Mains. The entire setup is enclosed in a Shielding Room.

The diagram illustrates a Shielding Chamber setup. A Spectrum analyzer is connected to an EUT (Equipment Under Test) via a cable. Both are placed on a Non-Conducted Table. The entire setup is enclosed within a Shielding Chamber, which is situated in a Normal Environment.

4.6 SYSTEM TEST CONFIGURATION

For emissions testing, the equipment under test (EUT) setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, radiated emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario. It was powered by a 3.87V battery. Only the worst case data were recorded in this test report.

The signal is maximized through rotation and placement in the three orthogonal axes. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance. Therefore, all final radiated testing was performed with the EUT in orientation.

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000 MHz. The resolution is 1 MHz or greater for frequencies above 1000 MHz. The spurious emissions more than 20 dB below the permissible value are not reported.

Radiated emission measurement were performed from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

4.7 DUTY CYCLE

Test Procedure: ANSI C63.10-2013 Clause 12.2.


Test Results

Mode	Data Rates	On Time (msec)	Period (msec)	Duty Cycle (linear)	Duty Cycle (%)	Duty Cycle Factor (dB)	1/T Minimum VBW (kHz)
IEEE 802.11a	6 Mbps	1.390	1.435	0.97	96.86	0.14	0.72
IEEE 802.11n-HT20	MCS 0	1.300	1.345	0.97	96.65	0.15	0.77
IEEE 802.11n-HT40	MCS 0	0.650	0.695	0.94	93.53	0.29	1.54
IEEE 802.11ac-VHT20	MCS 0	1.310	1.355	0.97	96.68	0.15	0.76
IEEE 802.11ac-VHT40	MCS 0	0.650	0.695	0.94	93.53	0.29	1.54
IEEE 802.11ac-VHT80	MCS 0	0.325	0.365	0.89	89.04	0.50	3.08

Remark:

- 1) Duty cycle= On Time/ Period;
- 2) Duty Cycle factor = $10 * \log(1/ \text{Duty cycle})$;

The test plots as follows



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China



Tel: +86-755-28230888



Fax: +86-755-28230886


E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2







5. RADIO TECHNICAL REQUIREMENTS SPECIFICATION

5.1 REFERENCE DOCUMENTS FOR TESTING

No.	Identity	Document Title
1	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations
2	FCC 47 CFR Part 15	Radio Frequency Devices
3	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices
4	KDB 789033 D02 General UNII Test Procedures New Rules v02r01	Guidelines for compliance testing of unlicensed national information infrastructure (U-NII) device part 15, subpart E
5	KDB 905462 D06 802.11 Channel Plans New Rules v02	Operation in U-NII bands -802.11 channel PLAN(§15.407)
6	KDB 905462 D02 UNII DFS Compliance Procedures New Rules v02	Compliance measurement procedures for Unlicensed –National Information Infrastructure devices operates in the frequency bands 5250 MHz to 5350 MHz and 5470 MHz to 5725 MHz bands incorporating dynamic frequency selection
7	KDB 905462 D03 Client Without DFS New Rules v01r02	U-NII client devices without radar detection capability

5.2 ANTENNA REQUIREMENT

Standard Requirement
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.
15.407(a)(1) (2) requirement: The conducted output power limit specified in paragraph (a) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (a) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power and the peak power spectral density shall be reduced by the by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
EUT Antenna: Antenna in the interior of the equipment and no consideration of replacement. The max gain of the antenna is 1.54 dBi.

5.326 DB BANDWIDTH & 99% OCCUPIED BANDWIDTH

Test Requirement: FCC 47 CFR Part 15 Subpart E Section 15.407 (a) (2)(5)

Test Method: KDB 789033 D02 v02r01 Section C.1
KDB 789033 D02 v02r01 Section D

Limit: None; for reporting purposes only.

Test Procedure:

The output from the transmitter was connected to an attenuator and then to the input of the RF Spectrum analyzer.

Spectrum analyzer according to the following Settings:

26dB Bandwidth

- a) Set RBW = approximately 1 % of the emission bandwidth.
- b) Set the VBW > RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1 %.

99% Occupied Bandwidth

- a) Set center frequency to the nominal EUT channel center frequency.
- b) Set span = 1.5 times to 5.0 times the OBW.
- c) Set RBW = 1% to 5% of the OBW
- d) Set VBW $\geq 3 \times$ RBW
- e) Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
- f) Use the 99% power bandwidth function of the instrument (if available).
- g) If the instrument does not have a 99% power bandwidth function, the trace data points are recovered and directly summed in power units. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% occupied bandwidth is the difference between these two frequencies.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.5.3 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Link mode

Test Results: Please refer to Appendix A

5.46 DB BANDWIDTH & 99% OCCUPIED BANDWIDTH

Test Requirement: FCC 47 CFR Part 15 Subpart C Section 15.407 (e)

Test Method: KDB 789033 D02 v02r01 Section C.2
KDB 789033 D02 v02r01 Section D

Limit: Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

Test Procedure:

The output from the transmitter was connected to an attenuator and then to the input of the RF Spectrum Analyzer.

Spectrum analyzer according to the following Settings:

6dB Bandwidth

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 * \text{RBW}$.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

99% Occupied Bandwidth

- h) Set center frequency to the nominal EUT channel center frequency.
 - i) Set span = 1.5 times to 5.0 times the OBW.
 - j) Set RBW = 1% to 5% of the OBW
 - k) Set VBW $\geq 3 \times \text{RBW}$
 - l) Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
 - m) Use the 99% power bandwidth function of the instrument (if available).
- If the instrument does not have a 99% power bandwidth function, the trace data points are recovered and directly summed in power units. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% occupied bandwidth is the difference between these two frequencies.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.5.3 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Link mode

Test Results: Please refer to Appendix A

5.5 MAXIMUM CONDUCTED OUTPUT POWER

Test Requirement: FCC 47 CFR Part 15 Subpart E Section 15.407 (a)(1)(2)(3)

Test Method: KDB 789033 D02 v02r01 Section E.3.a(Method PM)

Limits:

1. For the band 5.15-5.25 GHz.
 - (i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).
 - (ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
 - (iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.
 - (iv) For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
2. For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
3. For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

Test Procedure:

1. Connected the EUT's antenna port to measure device by 10dB attenuator.
2. Method PM is used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of Tx on burst.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.5.3 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Transmitter mode

Test Results: Pass

Antenna gain and the maximum output power limit.

Frequency Band	Antenna Gain (dBi)	Peak Power Limits (dBm)
U-NII-1	1.54	24.0
U-NII-2A	1.54	24.0
U-NII-2C	1.54	24.0
U-NII-3	1.54	30.0

For U-NII-1 Band:

Mode	Channel/ Frequency (MHz)	Maximum conducted output power (dBm)		Limit (dBm)	Result
		Meas Power	Corr'd Power		
IEEE 802.11a	36 (5180)	13.69	13.83	24	Pass
	44 (5220)	13.85	13.99	24	Pass
	48 (5240)	13.64	13.78	24	Pass
IEEE 802.11n-HT20	36 (5180)	13.49	13.64	24	Pass
	44 (5220)	13.47	13.62	24	Pass
	48 (5240)	13.44	13.59	24	Pass
IEEE 802.11n-HT40	38 (5190)	13.45	13.74	24	Pass
	46 (5230)	13.41	13.70	24	Pass
IEEE 802.11ac-VHT20	36 (5180)	13.54	13.69	24	Pass
	44 (5220)	13.62	13.77	24	Pass
	48 (5240)	13.44	13.59	24	Pass
IEEE 802.11ac-VHT40	38 (5190)	13.53	13.82	24	Pass
	46 (5230)	13.35	13.64	24	Pass
IEEE 802.11ac-VHT80	42 (5210)	13.02	13.52	24	Pass

Remark:

1. Corr'd Power = Meas Power + Duty Cycle Factor

For U-NII-2A Band:

Mode	Channel/ Frequency (MHz)	Maximum conducted output power (dBm)		Limit (dBm)	Result
		Meas Power	Corr'd Power		
IEEE 802.11a	52 (5260)	13.81	13.95	23.93	Pass
	60 (5300)	13.66	13.80	23.93	Pass
	64 (5320)	13.79	13.93	23.93	Pass
IEEE 802.11n-HT20	52 (5260)	13.55	13.70	23.99	Pass
	60 (5300)	13.46	13.61	23.99	Pass
	64 (5320)	13.61	13.76	23.99	Pass
IEEE 802.11n-HT40	54 (5270)	13.32	13.61	24	Pass
	62 (5310)	13.33	13.62	24	Pass
IEEE 802.11ac-VHT20	52 (5260)	13.56	13.71	23.99	Pass
	60 (5300)	13.66	13.81	23.99	Pass
	64 (5320)	13.69	13.84	23.99	Pass
IEEE 802.11ac-VHT40	54 (5270)	13.24	13.53	24	Pass
	62 (5310)	13.52	13.81	24	Pass
IEEE 802.11ac-VHT80	58 (5290)	13.04	13.54	24	Pass

Remark:

1. Corr'd Power = Meas Power + Duty Cycle Factor

Note:

For IEEE 802.11 a, the minimum 26 dB emission bandwidth is 19.63 MHz

$11 \text{ dBm} + 10\log_{10}(19.63) = 23.93 \text{ dBm} < 24 \text{ dBm (250mW)}$

So the 23.93 dB limit applicable

For IEEE 802.11n-HT20/ac-VHT20, the minimum 26 dB emission bandwidth is 19.89 MHz

$11 \text{ dBm} + 10\log_{10}(19.89) = 23.99 \text{ dBm} < 24 \text{ dBm (250mW)}$

So the 23.99 dB limit applicable

For IEEE 802.11n-HT40/ac-VHT40/ac-VHT80, the minimum 26 dB emission bandwidth is 39.91 MHz

$11 \text{ dBm} + 10\log_{10}(39.91) = 27.01 \text{ dBm} > 24 \text{ dBm (250mW)}$

So the 24 dB limit applicable

For U-NII-2C Band:

Mode	Channel/ Frequency (MHz)	Maximum conducted output power (dBm)		Limit (dBm)	Result
		Meas Power	Corr'd Power		
IEEE 802.11a	100 (5500)	13.68	13.82	23.88	Pass
	120 (5600)	13.64	13.78	23.88	Pass
	140 (5700)	13.57	13.71	23.88	Pass
	144 (5720)	13.51	13.65	23.88	Pass
IEEE 802.11n-HT20	100 (5500)	13.42	13.57	23.98	Pass
	120 (5600)	13.39	13.54	23.98	Pass
	140 (5700)	13.28	13.43	23.98	Pass
	144 (5720)	13.54	13.69	23.98	Pass
IEEE 802.11n-HT40	102 (5510)	8.41	8.70	24	Pass
	118 (5590)	8.16	8.45	24	Pass
	134 (5670)	8.21	8.50	24	Pass
	142 (5710)	8.11	8.40	24	Pass
IEEE 802.11ac-VHT20	100 (5500)	13.34	13.49	23.98	Pass
	120 (5600)	13.42	13.57	23.98	Pass
	140 (5700)	13.37	13.52	23.98	Pass
	144 (5720)	13.31	13.46	23.98	Pass
IEEE 802.11ac-VHT40	102 (5510)	8.12	8.41	24	Pass
	118 (5590)	8.41	8.70	24	Pass
	134 (5670)	8.22	8.51	24	Pass
	142 (5710)	8.06	8.35	24	Pass
IEEE 802.11ac-VHT80	106 (5530)	10.02	10.52	24	Pass
	122 (5610)	10.15	10.65	24	Pass
	138 (5690)	10.32	10.82	24	Pass

Remark:

1. Corr'd Power = Meas Power + Duty Cycle Factor

Note:

For IEEE 802.11 a, the minimum 26 dB emission bandwidth is 19.42 MHz
 $11 \text{ dBm} + 10\log_{10}(19.42) = 23.88 \text{ dBm} < 24 \text{ dBm} (250\text{mW})$
 So the 23.88 dB limit applicable

For IEEE 802.11n-HT20/ac-VHT20, the minimum 26 dB emission bandwidth is 19.88 MHz
 $11 \text{ dBm} + 10\log_{10}(19.88) = 23.98 \text{ dBm} < 24 \text{ dBm} (250\text{mW})$
 So the 23.98 dB limit applicable

For IEEE 802.11n-HT40/ac-VHT40/ac-VHT80, the minimum 26 dB emission bandwidth is 39.72 MHz
 $11 \text{ dBm} + 10\log_{10}(39.72) = 26.99 \text{ dBm} > 24 \text{ dBm} (250\text{mW})$
 So the 24 dB limit applicable

For U-NII-3 Band:

Mode	Channel/ Frequency (MHz)	Maximum conducted output power (dBm)		Limit (dBm)	Result
		Meas Power	Corr'd Power		
IEEE 802.11a	144 (5720)	13.51	13.65	30	Pass
	149 (5745)	13.79	13.93	30	Pass
	157 (5785)	13.58	13.72	30	Pass
	165 (5825)	13.58	13.72	30	Pass
IEEE 802.11n-HT20	144 (5720)	13.54	13.69	30	Pass
	149 (5745)	13.41	13.56	30	Pass
	157 (5785)	13.33	13.48	30	Pass
	165 (5825)	13.46	13.61	30	Pass
IEEE 802.11n-HT40	142 (5710)	8.11	8.40	30	Pass
	151 (5755)	13.19	13.48	30	Pass
	159 (5795)	13.28	13.57	30	Pass
IEEE 802.11ac-VHT20	144 (5720)	13.31	13.46	30	Pass
	149 (5745)	13.41	13.56	30	Pass
	157 (5785)	13.33	13.48	30	Pass
	165 (5825)	13.31	13.46	30	Pass
IEEE 802.11ac-VHT40	142 (5710)	8.06	8.35	30	Pass
	151 (5755)	13.11	13.40	30	Pass
	159 (5795)	13.21	13.50	30	Pass
IEEE 802.11ac-VHT80	138 (5690)	10.32	10.82	30	Pass
	155 (5775)	12.89	13.39	30	Pass

Remark:

1. Corr'd Power = Meas Power + Duty Cycle Factor

5.6 PEAK POWER SPECTRAL DENSITY

Test Requirement: FCC 47 CFR Part 15 Subpart E Section 15.407 (a)(1)(2)(3)

Test Method: KDB 789033 D02 v02r01 Section F

Limits:

1. For the band 5.15-5.25 GHz.
 - (i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).
 - (ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
 - (iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.
 - (iv) For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
2. For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
3. For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

Test Procedure:

The output from the transmitter was connected to an attenuator and then to the input of the RF Spectrum Analyzer.

Spectrum analyzer according to the following Settings:

1. For U-NII-1, U-NII-2A, U-NII-2C band:

Using method SA-2

- a) Set span to encompass the entire emission bandwidth (EBW) of the signal.
- b) Set RBW = 1 MHz, Set VBW $\geq$ 3 RBW, Detector = RMS
- c) Sweep time = auto, trigger set to "free run".
- d) Trace average at least 100 traces in power averaging mode.
- e) Record the max value and add 10 log (1/duty cycle)

2. For U-NII-3 band:

- a) Set span to encompass the entire emission bandwidth (EBW) of the signal.
- b) Set RBW = 500 kHz, Set VBW $\geq$ 3 RBW, Detector = RMS
- c) Use the peak marker function to determine the maximum power level in any 500 kHz band segment within the fundamental EBW.
- d) Sweep time = auto, trigger set to "free run".
- e) Trace average at least 100 traces in power averaging mode.
- f) Record the max value and add 10 log (1/duty cycle)

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.5.3 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Link mode

Test Results: Please refer to Appendix A

Antenna gain and the maximum output power limit.

Frequency Band	Antenna Gain (dBi)	PSD Limits (dBm/MHz or dBm/500kHz)
U-NII-1	1.54	11.0
U-NII-2C	1.54	11.0
U-NII-2A	1.54	11.0
U-NII-3	1.54	30.0

5.7 RADIATED EMISSIONS AND BAND EDGE MEASUREMENT

Test Requirement: FCC 47 CFR Part 15 Subpart E Section 15.407 (b)(1)(2)(3)(4)(6)
FCC 47 CFR Part 15 Subpart C Section 15.209/205

Test Method: KDB 789033 D02 v02r01 Section G.3, G.4, G.5, and G.6

Receiver Setup:

Frequency	RBW
0.009 MHz-0.150 MHz	200/300 kHz
0.150 MHz -30 MHz	9/10 kHz
30 MHz-1 GHz	100/120 kHz
Above 1 GHz	1 MHz

Limits:

1. Limits of Radiated Emission and Band edge Measurement

Radiated emissions that fall in the restricted bands must comply with the general emissions limits in 15.209(a) as below table. Other emissions shall be at least 20 dB below the highest level of the desired power.

Frequency	Field strength (microvolt/meter)	Limit (dBμV/m)	Remark	Measurement distance (m)
0.009 MHz-0.490 MHz	2400/F(kHz)	--	--	300
0.490 MHz-1.705 MHz	24000/F(kHz)	--	--	30
1.705 MHz-30 MHz	30	--	--	30
30 MHz-88 MHz	100	40.0	Quasi-peak	3
88 MHz-216 MHz	150	43.5	Quasi-peak	3
216 MHz-960 MHz	200	46.0	Quasi-peak	3
960MHz-1GHz	500	54.0	Quasi-peak	3
Above 1 GHz	500	54.0	Average	3

Remark:

- The lower limit shall apply at the transition frequencies.
- Emission level (dBuV/m) = 20 log Emission level (uV/m).
- For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

2. Limits of Unwanted Emission Out of the Restricted Bands

Applicable To	Limit	
789033 D02 General U-NII Test Procedures New Rules v01r04	Field Strength at 3 m	
	PK: 74 (dBμV/m)	AV: 54 (dBμV/m)
Applicable To	EIRP Limit	Equivalent Field Strength at 3 m
FCC Part 15.407 (b)(1)	PK: -27 (dBm/MHz)	PK: 74 (dBμV/m)
FCC Part 15.407 (b)(2)	PK: -27 (dBm/MHz)	PK: 74 (dBμV/m)
FCC Part 15.407 (b)(3)	PK: -27 (dBm/MHz)	PK: 68.2 (dBμV/m)
FCC Part 15.407 (b)(4)	27 dBm/MHz at frequencies from the band edges decreasing linearly to 15.6 dBm/MHz at 5 MHz above or below the band edges;	PK: 68.2 (dBμV/m)
	15.6 dBm/MHz at 5 MHz above or below the band edges decreasing linearly to 10 dBm/MHz at 25 MHz above or below the band edges;	
	10 dBm/MHz at 25 MHz above or below the band edges decreasing linearly to -27 dBm/MHz at 75 MHz above or below the band edges;	
	-27 dBm/MHz at frequencies more than 75 MHz above or below the band edges.	

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2

Test Setup: Refer to section 4.5.1 for details.

Test Procedures:

1. The EUT was placed on the top of a rotating table 0.8 meters (for below 1 GHz) / 1.5 meters (for above 1 GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
3. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
6. The test-receiver system was set to peak and average detected function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Remark:

- a) The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) at frequency below 1 GHz.
- b) The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1 GHz.
- c) The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for RMS Average (Duty cycle < 98 %) for Average detection (AV) at frequency above 1 GHz, then the measurement results was added to a correction factor ($10 \log(1/\text{duty cycle})$).
- d) The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz (Duty cycle $\geq 98 \%$) or $\geq 1/T$ (duty cycle is < 98%) for Average detection (AV) at frequency above 1 GHz.
- e) All modes of operation were investigated and the worst-case emissions are reported.


Equipment Used: Refer to section 3 for details.

Test Result: Pass

The measurement data as follows:

Radiated Emission Test Data (9 kHz ~ 30 MHz):

The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

Radiated Emission Test Data (30 MHz ~ 1 GHz):**IEEE 802.11a_5300MHz****Horizontal**

No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	50.461	35.68	-13.75	21.93	40.00	-18.07	QP
2	62.304	34.23	-17.22	17.01	40.00	-22.99	QP
3	102.612	29.88	-15.70	14.18	43.50	-29.32	QP
4	173.815	26.33	-11.36	14.97	43.50	-28.53	QP
5	424.300	27.24	-4.30	22.94	46.00	-23.06	QP
6	912.695	26.40	4.90	31.30	46.00	-14.70	QP

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2



Radiated Emission Test Data (Above 1GHz): Worst-Case Configuration								
No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
IEEE 802.11a_Channel 36								
1	10360	34.2	4.0	38.2	54	-15.9	Average	Horizontal
2	10360	47.1	4.0	51.1	68.2	-17.1	Peak	Horizontal
3	15540	30.6	7.2	37.8	54	-16.2	Average	Horizontal
4	15540	44.0	7.2	51.2	74	-22.8	Peak	Horizontal
5	10360	33.8	4.0	37.8	54	-16.2	Average	Vertical
6	10360	46.8	4.0	50.8	68.2	-17.4	Peak	Vertical
7	15540	30.5	7.2	37.7	54	-16.3	Average	Vertical
8	15540	43.8	7.2	51.0	74	-23.0	Peak	Vertical
IEEE 802.11a_Channel 44								
1	10440	33.8	3.9	37.7	54	-16.3	Average	Horizontal
2	10440	46.7	3.9	50.5	68.2	-17.7	Peak	Horizontal
3	15660	31.4	7.2	38.6	54	-15.4	Average	Horizontal
4	15660	45.4	7.2	52.6	74	-21.4	Peak	Horizontal
5	10440	33.4	3.9	37.3	54	-16.7	Average	Vertical
6	10440	46.1	3.9	50.0	68.2	-18.3	Peak	Vertical
7	15660	31.5	7.2	38.7	54	-15.3	Average	Vertical
8	15660	44.4	7.2	51.6	74	-22.4	Peak	Vertical
IEEE 802.11a_Channel 48								
1	10480	32.2	3.8	36.0	54	-18.0	Average	Horizontal
2	10480	45.9	3.8	49.7	68.2	-18.5	Peak	Horizontal
3	15720	32.1	7.2	39.3	54	-14.7	Average	Horizontal
4	15720	45.1	7.2	52.3	74	-21.8	Peak	Horizontal
5	10480	31.7	3.8	35.5	54	-18.5	Average	Vertical
6	10480	45.6	3.8	49.4	68.2	-18.8	Peak	Vertical
7	15720	32.0	7.2	39.2	54	-14.8	Average	Vertical
8	15720	45.1	7.2	52.3	74	-21.7	Peak	Vertical
IEEE 802.11a_Channel 52								
1	10520	32.3	3.8	36.1	54	-17.9	Average	Horizontal
2	10520	47.4	3.8	51.1	68.2	-17.1	Peak	Horizontal
3	15780	32.3	7.2	39.5	54	-14.5	Average	Horizontal
4	15780	44.8	7.2	51.9	74	-22.1	Peak	Horizontal
5	10520	31.9	3.8	35.7	54	-18.3	Average	Vertical
6	10520	45.6	3.8	49.4	68.2	-18.8	Peak	Vertical
7	15780	32.0	7.2	39.1	54	-14.9	Average	Vertical
8	15780	44.9	7.2	52.1	74	-21.9	Peak	Vertical

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2

No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
IEEE 802.11a_Channel 60								
1	10600	32.3	3.7	35.9	54	-18.1	Average	Horizontal
2	10600	46.1	3.7	49.7	74	-24.3	Peak	Horizontal
3	15900	31.8	7.2	39.0	54	-15.0	Average	Horizontal
4	15900	44.6	7.2	51.8	74	-22.3	Peak	Horizontal
5	10600	31.8	3.7	35.4	54	-18.6	Average	Vertical
6	10600	45.4	3.7	49.1	74	-24.9	Peak	Vertical
7	15900	31.8	7.2	38.9	54	-15.1	Average	Vertical
8	15900	44.0	7.2	51.1	74	-22.9	Peak	Vertical
IEEE 802.11a_Channel 64								
1	10640	32.2	3.6	35.8	54	-18.2	Average	Horizontal
2	10640	46.7	3.6	50.3	74	-23.7	Peak	Horizontal
3	15960	31.9	7.2	39.1	54	-14.9	Average	Horizontal
4	15960	44.3	7.2	51.4	74	-22.6	Peak	Horizontal
5	10640	32.2	3.6	35.8	54	-18.2	Average	Vertical
6	10640	44.8	3.6	48.5	74	-25.5	Peak	Vertical
7	15960	31.9	7.2	39.1	54	-14.9	Average	Vertical
8	15960	43.7	7.2	50.9	74	-23.1	Peak	Vertical
IEEE 802.11a_Channel 100								
1	11000	32.8	3.2	36.0	54	-18.0	Average	Horizontal
2	11000	46.1	3.2	49.3	74	-24.7	Peak	Horizontal
3	16500	32.8	8.4	41.2	54	-12.8	Average	Horizontal
4	16500	44.9	8.4	53.3	68.2	-14.9	Peak	Horizontal
5	11000	32.6	3.2	35.8	54	-18.2	Average	Vertical
6	11000	46.2	3.2	49.4	74	-24.6	Peak	Vertical
7	16500	32.7	8.4	41.1	54	-12.9	Average	Vertical
8	16500	44.4	8.4	52.8	68.2	-15.4	Peak	Vertical
IEEE 802.11a_Channel 120								
1	11200	30.7	3.0	33.7	54	-20.3	Average	Horizontal
2	11200	45.8	3.0	48.8	74	-25.2	Peak	Horizontal
3	16800	31.7	9.0	40.7	54	-13.3	Average	Horizontal
4	16800	43.9	9.0	52.9	68.2	-15.3	Peak	Horizontal
5	11200	30.8	3.0	33.8	54	-20.2	Average	Vertical
6	11200	46.2	3.0	49.2	74	-24.8	Peak	Vertical
7	16800	31.6	9.0	40.6	54	-13.5	Average	Vertical
8	16800	43.8	9.0	52.8	68.2	-15.4	Peak	Vertical

No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
IEEE 802.11a_Channel 140								
1	11400	31.3	2.9	34.2	54	-19.8	Average	Horizontal
2	11400	45.6	2.9	48.5	74	-25.5	Peak	Horizontal
3	17100	31.6	9.6	41.2	54	-12.8	Average	Horizontal
4	17100	44.7	9.6	54.3	68.2	-13.9	Peak	Horizontal
5	11400	31.2	2.9	34.1	54	-19.9	Average	Vertical
6	11400	45.6	2.9	48.5	74	-25.5	Peak	Vertical
7	17100	31.4	9.6	41.1	54	-12.9	Average	Vertical
8	17100	43.2	9.6	52.9	68.2	-15.4	Peak	Vertical
IEEE 802.11a_Channel 144								
1	11440	30.9	2.9	33.8	54	-20.2	Average	Horizontal
2	11440	45.0	2.9	47.9	74	-26.1	Peak	Horizontal
3	17160	32.1	9.8	41.9	54	-12.1	Average	Horizontal
4	17160	44.2	9.8	54.0	68.2	-14.2	Peak	Horizontal
5	11440	30.8	2.9	33.7	54	-20.3	Average	Vertical
6	11440	44.4	2.9	47.3	74	-26.7	Peak	Vertical
7	17160	31.9	9.8	41.7	54	-12.3	Average	Vertical
8	17160	44.2	9.8	54.0	68.2	-14.2	Peak	Vertical
IEEE 802.11a_Channel 149								
1	11490	30.1	2.9	33.0	54	-21.0	Average	Horizontal
2	11490	44.3	2.9	47.1	74	-26.9	Peak	Horizontal
3	17235	31.6	10.0	41.6	54	-12.4	Average	Horizontal
4	17235	43.6	10.0	53.6	68.2	-14.6	Peak	Horizontal
5	11490	30.0	2.9	32.9	54	-21.2	Average	Vertical
6	11490	44.5	2.9	47.4	74	-26.6	Peak	Vertical
7	17235	31.5	10.0	41.6	54	-12.4	Average	Vertical
8	17235	44.6	10.0	54.6	68.2	-13.6	Peak	Vertical
IEEE 802.11a_Channel 157								
1	11570	30.5	2.8	33.3	54	-20.7	Average	Horizontal
2	11570	45.7	2.8	48.6	74	-25.5	Peak	Horizontal
3	17355	32.0	10.4	42.4	54	-11.6	Average	Horizontal
4	17355	44.1	10.4	54.5	68.2	-13.7	Peak	Horizontal
5	11570	30.2	2.8	33.0	54	-21.0	Average	Vertical
6	11570	44.6	2.8	47.5	74	-26.6	Peak	Vertical
7	17355	31.9	10.4	42.2	54	-11.8	Average	Vertical
8	17355	43.7	10.4	54.0	68.2	-14.2	Peak	Vertical

No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
IEEE 802.11a_Channel 165								
1	11650	31.2	2.8	34.0	54	-20.1	Average	Horizontal
2	11650	45.1	2.8	47.9	74	-26.1	Peak	Horizontal
3	17475	31.8	10.7	42.5	54	-11.5	Average	Horizontal
4	17475	44.0	10.7	54.7	68.2	-13.6	Peak	Horizontal
5	11650	31.0	2.8	33.8	54	-20.3	Average	Vertical
6	11650	45.5	2.8	48.3	74	-25.8	Peak	Vertical
7	17475	31.8	10.7	42.5	54	-11.5	Average	Vertical
8	17475	43.8	10.7	54.5	68.2	-13.7	Peak	Vertical

No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
IEEE 802.11n-HT20_Channel 36								
1	10360	34.0	4.0	38.0	54	-16.0	Average	Horizontal
2	10360	46.8	4.0	50.8	68.2	-17.4	Peak	Horizontal
3	15540	30.5	7.2	37.7	54	-16.3	Average	Horizontal
4	15540	45.1	7.2	52.3	74	-21.7	Peak	Horizontal
5	10360	33.9	4.0	37.9	54	-16.1	Average	Vertical
6	10360	46.7	4.0	50.7	68.2	-17.5	Peak	Vertical
7	15540	30.5	7.2	37.7	54	-16.3	Average	Vertical
8	15540	43.8	7.2	51.0	74	-23.1	Peak	Vertical
IEEE 802.11n-HT20_Channel 44								
1	10440	33.9	3.9	37.8	54	-16.2	Average	Horizontal
2	10440	47.2	3.9	51.1	68.2	-17.1	Peak	Horizontal
3	15660	31.5	7.2	38.7	54	-15.3	Average	Horizontal
4	15660	46.0	7.2	53.1	74	-20.9	Peak	Horizontal
5	10440	33.5	3.9	37.4	54	-16.6	Average	Vertical
6	10440	46.4	3.9	50.3	68.2	-17.9	Peak	Vertical
7	15660	31.4	7.2	38.6	54	-15.4	Average	Vertical
8	15660	44.6	7.2	51.8	74	-22.2	Peak	Vertical
IEEE 802.11n-HT20_Channel 48								
1	10480	32.0	3.8	35.8	54	-18.2	Average	Horizontal
2	10480	46.4	3.8	50.3	68.2	-18.0	Peak	Horizontal
3	15720	32.0	7.2	39.2	54	-14.8	Average	Horizontal
4	15720	45.0	7.2	52.2	74	-21.8	Peak	Horizontal
5	10480	32.1	3.8	35.9	54	-18.1	Average	Vertical
6	10480	45.8	3.8	49.6	68.2	-18.6	Peak	Vertical
7	15720	32.1	7.2	39.3	54	-14.8	Average	Vertical
8	15720	44.5	7.2	51.7	74	-22.3	Peak	Vertical

No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
IEEE 802.11n-HT20_Channel 52								
1	10520	32.3	3.8	36.1	54	-17.9	Average	Horizontal
2	10520	46.4	3.8	50.2	68.2	-18.0	Peak	Horizontal
3	15780	32.1	7.2	39.3	54	-14.8	Average	Horizontal
4	15780	45.4	7.2	52.6	74	-21.4	Peak	Horizontal
5	10520	32.3	3.8	36.0	54	-18.0	Average	Vertical
6	10520	45.3	3.8	49.0	68.2	-19.2	Peak	Vertical
7	15780	32.0	7.2	39.1	54	-14.9	Average	Vertical
8	15780	44.9	7.2	52.1	74	-21.9	Peak	Vertical
IEEE 802.11n-HT20_Channel 60								
1	10600	32.5	3.7	36.2	54	-17.8	Average	Horizontal
2	10600	46.1	3.7	49.8	74	-24.3	Peak	Horizontal
3	15900	31.7	7.2	38.9	54	-15.1	Average	Horizontal
4	15900	44.1	7.2	51.2	74	-22.8	Peak	Horizontal
5	10600	31.7	3.7	35.3	54	-18.7	Average	Vertical
6	10600	44.7	3.7	48.3	74	-25.7	Peak	Vertical
7	15900	31.7	7.2	38.9	54	-15.1	Average	Vertical
8	15900	44.5	7.2	51.7	74	-22.4	Peak	Vertical
IEEE 802.11n-HT20_Channel 64								
1	10640	32.3	3.6	35.9	54	-18.1	Average	Horizontal
2	10640	47.6	3.6	51.2	74	-22.8	Peak	Horizontal
3	15960	31.7	7.2	38.9	54	-15.1	Average	Horizontal
4	15960	44.0	7.2	51.2	74	-22.8	Peak	Horizontal
5	10640	31.7	3.6	35.3	54	-18.7	Average	Vertical
6	10640	44.6	3.6	48.3	74	-25.8	Peak	Vertical
7	15960	31.8	7.2	38.9	54	-15.1	Average	Vertical
8	15960	44.3	7.2	51.4	74	-22.6	Peak	Vertical
IEEE 802.11n-HT20_Channel 100								
1	11000	32.7	3.2	35.9	54	-18.1	Average	Horizontal
2	11000	46.3	3.2	49.5	74	-24.5	Peak	Horizontal
3	16500	32.8	8.4	41.2	54	-12.8	Average	Horizontal
4	16500	44.4	8.4	52.8	68.2	-15.4	Peak	Horizontal
5	11000	32.6	3.2	35.8	54	-18.2	Average	Vertical
6	11000	46.2	3.2	49.4	74	-24.6	Peak	Vertical
7	16500	32.7	8.4	41.1	54	-12.9	Average	Vertical
8	16500	44.9	8.4	53.3	68.2	-14.9	Peak	Vertical

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2

No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
IEEE 802.11n-HT20_Channel 120								
1	11200	30.8	3.0	33.8	54	-20.2	Average	Horizontal
2	11200	45.9	3.0	48.9	74	-25.1	Peak	Horizontal
3	16800	31.7	9.0	40.7	54	-13.3	Average	Horizontal
4	16800	44.2	9.0	53.2	68.2	-15.0	Peak	Horizontal
5	11200	30.7	3.0	33.7	54	-20.3	Average	Vertical
6	11200	46.2	3.0	49.3	74	-24.7	Peak	Vertical
7	16800	31.6	9.0	40.6	54	-13.4	Average	Vertical
8	16800	43.9	9.0	52.9	68.2	-15.3	Peak	Vertical
IEEE 802.11n-HT20_Channel 140								
1	11400	31.4	2.9	34.3	54	-19.7	Average	Horizontal
2	11400	46.7	2.9	49.6	74	-24.4	Peak	Horizontal
3	17100	31.6	9.6	41.3	54	-12.7	Average	Horizontal
4	17100	43.6	9.6	53.2	68.2	-15.0	Peak	Horizontal
5	11400	31.4	2.9	34.3	54	-19.7	Average	Vertical
6	11400	45.7	2.9	48.6	74	-25.4	Peak	Vertical
7	17100	31.4	9.6	41.1	54	-12.9	Average	Vertical
8	17100	44.0	9.6	53.7	68.2	-14.5	Peak	Vertical
IEEE 802.11n-HT20_Channel 144								
1	11440	30.9	2.9	33.8	54	-20.2	Average	Horizontal
2	11440	45.3	2.9	48.2	74	-25.9	Peak	Horizontal
3	17160	32.2	9.8	42.0	54	-12.1	Average	Horizontal
4	17160	44.4	9.8	54.2	68.2	-14.0	Peak	Horizontal
5	11440	30.7	2.9	33.6	54	-20.4	Average	Vertical
6	11440	44.9	2.9	47.8	74	-26.2	Peak	Vertical
7	17160	31.8	9.8	41.6	54	-12.4	Average	Vertical
8	17160	44.1	9.8	53.9	68.2	-14.3	Peak	Vertical
IEEE 802.11n-HT20_Channel 149								
1	11490	29.9	2.9	32.8	54	-21.2	Average	Horizontal
2	11490	44.3	2.9	47.2	74	-26.8	Peak	Horizontal
3	17235	31.6	10.0	41.6	54	-12.4	Average	Horizontal
4	17235	43.3	10.0	53.4	68.2	-14.8	Peak	Horizontal
5	11490	29.9	2.9	32.8	54	-21.2	Average	Vertical
6	11490	45.3	2.9	48.2	74	-25.8	Peak	Vertical
7	17235	31.5	10.0	41.5	54	-12.5	Average	Vertical
8	17235	43.4	10.0	53.5	68.2	-14.7	Peak	Vertical

No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
IEEE 802.11n-HT20_Channel 157								
1	11570	30.5	2.8	33.4	54	-20.7	Average	Horizontal
2	11570	44.9	2.8	47.7	74	-26.3	Peak	Horizontal
3	17355	32.0	10.4	42.3	54	-11.7	Average	Horizontal
4	17355	45.0	10.4	55.4	68.2	-12.9	Peak	Horizontal
5	11570	30.4	2.8	33.2	54	-20.8	Average	Vertical
6	11570	45.0	2.8	47.8	74	-26.2	Peak	Vertical
7	17355	32.0	10.4	42.3	54	-11.7	Average	Vertical
8	17355	43.7	10.4	54.0	68.2	-14.2	Peak	Vertical
IEEE 802.11n-HT20_Channel 165								
1	11650	31.2	2.8	34.0	54	-20.0	Average	Horizontal
2	11650	45.9	2.8	48.7	74	-25.3	Peak	Horizontal
3	17475	31.7	10.7	42.4	54	-11.6	Average	Horizontal
4	17475	44.1	10.7	54.7	68.2	-13.5	Peak	Horizontal
5	11650	31.2	2.8	34.0	54	-20.0	Average	Vertical
6	11650	45.8	2.8	48.6	74	-25.4	Peak	Vertical
7	17475	31.8	10.7	42.5	54	-11.5	Average	Vertical
8	17475	44.5	10.7	55.2	68.2	-13.0	Peak	Vertical

No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
IEEE 802.11n-HT40_Channel 38								
1	10380	34.2	4.0	38.2	54	-15.8	Average	Horizontal
2	10380	47.9	4.0	51.9	68.2	-16.3	Peak	Horizontal
3	15570	30.6	7.2	37.8	54	-16.2	Average	Horizontal
4	15570	43.7	7.2	50.9	74	-23.1	Peak	Horizontal
5	10380	33.9	4.0	37.9	54	-16.1	Average	Vertical
6	10380	46.1	4.0	50.0	68.2	-18.2	Peak	Vertical
7	15570	30.4	7.2	37.6	54	-16.4	Average	Vertical
8	15570	44.6	7.2	51.8	74	-22.2	Peak	Vertical
IEEE 802.11n-HT40_Channel 46								
1	10460	33.8	3.9	37.7	54	-16.4	Average	Horizontal
2	10460	46.5	3.9	50.3	68.2	-17.9	Peak	Horizontal
3	15690	31.4	7.2	38.6	54	-15.5	Average	Horizontal
4	15690	44.7	7.2	51.9	74	-22.1	Peak	Horizontal
5	10460	33.4	3.9	37.2	54	-16.8	Average	Vertical
6	10460	45.9	3.9	49.8	68.2	-18.4	Peak	Vertical
7	15690	31.4	7.2	38.6	54	-15.5	Average	Vertical
8	15690	44.5	7.2	51.7	74	-22.3	Peak	Vertical

No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
IEEE 802.11n-HT40_Channel 54								
1	10540	32.5	3.7	36.2	54	-17.8	Average	Horizontal
2	10540	45.6	3.7	49.4	68.2	-18.8	Peak	Horizontal
3	15810	32.2	7.2	39.4	54	-14.6	Average	Horizontal
4	15810	45.6	7.2	52.7	74	-21.3	Peak	Horizontal
5	10540	31.8	3.7	35.5	54	-18.5	Average	Vertical
6	10540	45.6	3.7	49.3	68.2	-18.9	Peak	Vertical
7	15810	32.3	7.2	39.5	54	-14.6	Average	Vertical
8	15810	44.7	7.2	51.9	74	-22.1	Peak	Vertical
IEEE 802.11n-HT40_Channel 62								
1	10620	32.7	3.6	36.4	54	-17.6	Average	Horizontal
2	10620	46.1	3.6	49.7	74	-24.3	Peak	Horizontal
3	15930	31.8	7.2	39.0	54	-15.0	Average	Horizontal
4	15930	44.4	7.2	51.5	74	-22.5	Peak	Horizontal
5	10620	31.8	3.6	35.5	54	-18.6	Average	Vertical
6	10620	44.2	3.6	47.8	74	-26.2	Peak	Vertical
7	15930	31.8	7.2	39.0	54	-15.0	Average	Vertical
8	15930	43.8	7.2	51.0	74	-23.0	Peak	Vertical
IEEE 802.11n-HT40_Channel 102								
1	11020	32.6	3.2	35.7	54	-18.3	Average	Horizontal
2	11020	46.1	3.2	49.3	74	-24.8	Peak	Horizontal
3	16530	32.6	8.5	41.1	54	-12.9	Average	Horizontal
4	16530	44.5	8.5	52.9	68.2	-15.3	Peak	Horizontal
5	11020	32.7	3.2	35.9	54	-18.1	Average	Vertical
6	11020	45.7	3.2	48.8	74	-25.2	Peak	Vertical
7	16530	32.6	8.5	41.1	54	-12.9	Average	Vertical
8	16530	45.4	8.5	53.9	68.2	-14.3	Peak	Vertical
IEEE 802.11n-HT40_Channel 118								
1	11180	30.7	3.1	33.8	54	-20.3	Average	Horizontal
2	11180	46.6	3.1	49.7	74	-24.3	Peak	Horizontal
3	16770	32.0	8.9	40.9	54	-13.1	Average	Horizontal
4	16770	44.9	8.9	53.8	68.2	-14.4	Peak	Horizontal
5	11180	30.7	3.1	33.8	54	-20.2	Average	Vertical
6	11180	45.5	3.1	48.6	74	-25.5	Peak	Vertical
7	16770	31.6	8.9	40.6	54	-13.5	Average	Vertical
8	16770	43.9	8.9	52.8	68.2	-15.4	Peak	Vertical

No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
IEEE 802.11n-HT40_Channel 134								
1	11340	31.7	3.0	34.7	54	-19.3	Average	Horizontal
2	11340	45.1	3.0	48.0	74	-26.0	Peak	Horizontal
3	17010	32.9	9.4	42.3	54	-11.7	Average	Horizontal
4	17010	46.0	9.4	55.3	68.2	-12.9	Peak	Horizontal
5	11340	31.9	3.0	34.8	54	-19.2	Average	Vertical
6	11340	45.2	3.0	48.2	74	-25.8	Peak	Vertical
7	17010	32.4	9.4	41.8	54	-12.2	Average	Vertical
8	17010	44.5	9.4	53.9	68.2	-14.4	Peak	Vertical
IEEE 802.11n-HT40_Channel 142								
1	11420	31.6	2.9	34.5	54	-19.5	Average	Horizontal
2	11420	44.8	2.9	47.7	74	-26.3	Peak	Horizontal
3	17130	31.5	9.7	41.3	54	-12.7	Average	Horizontal
4	17130	43.7	9.7	53.4	68.2	-14.8	Peak	Horizontal
5	11420	31.3	2.9	34.2	54	-19.8	Average	Vertical
6	11420	46.0	2.9	48.9	74	-25.1	Peak	Vertical
7	17130	31.5	9.7	41.2	54	-12.8	Average	Vertical
8	17130	43.7	9.7	53.5	68.2	-14.8	Peak	Vertical
IEEE 802.11n-HT40_Channel 151								
1	11510	30.1	2.9	32.9	54	-21.1	Average	Horizontal
2	11510	44.7	2.9	47.5	74	-26.5	Peak	Horizontal
3	17265	31.7	10.1	41.8	54	-12.3	Average	Horizontal
4	17265	43.2	10.1	53.3	68.2	-14.9	Peak	Horizontal
5	11510	30.1	2.9	32.9	54	-21.1	Average	Vertical
6	11510	45.2	2.9	48.0	74	-26.0	Peak	Vertical
7	17265	31.5	10.1	41.6	54	-12.4	Average	Vertical
8	17265	44.3	10.1	54.4	68.2	-13.8	Peak	Vertical
IEEE 802.11n-HT40_Channel 159								
1	11590	30.5	2.8	33.3	54	-20.7	Average	Horizontal
2	11590	44.7	2.8	47.6	74	-26.5	Peak	Horizontal
3	17385	32.0	10.4	42.4	54	-11.6	Average	Horizontal
4	17385	44.0	10.4	54.4	68.2	-13.8	Peak	Horizontal
5	11590	30.4	2.8	33.2	54	-20.8	Average	Vertical
6	11590	45.0	2.8	47.8	74	-26.2	Peak	Vertical
7	17385	31.9	10.4	42.3	54	-11.7	Average	Vertical
8	17385	43.8	10.4	54.3	68.2	-13.9	Peak	Vertical

No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
IEEE 802.11ac-VHT80_Channel 42								
1	10420	33.7	3.9	37.6	54	-16.4	Average	Horizontal
2	10420	46.6	3.9	50.5	68.2	-17.7	Peak	Horizontal
3	15630	31.5	7.2	38.7	54	-15.3	Average	Horizontal
4	15630	44.8	7.2	52.0	74	-22.0	Peak	Horizontal
5	10420	33.5	3.9	37.4	54	-16.6	Average	Vertical
6	10420	45.8	3.9	49.7	68.2	-18.5	Peak	Vertical
7	15630	31.5	7.2	38.7	54	-15.3	Average	Vertical
8	15630	44.4	7.2	51.6	74	-22.5	Peak	Vertical
IEEE 802.11ac-VHT80_Channel 58								
1	10580	32.2	3.7	35.9	54	-18.1	Average	Horizontal
2	10580	45.1	3.7	48.7	68.2	-19.5	Peak	Horizontal
3	15870	32.5	7.2	39.6	54	-14.4	Average	Horizontal
4	15870	44.8	7.2	52.0	74	-22.0	Peak	Horizontal
5	10580	31.9	3.7	35.6	54	-18.4	Average	Vertical
6	10580	45.5	3.7	49.2	68.2	-19.0	Peak	Vertical
7	15870	32.4	7.2	39.6	54	-14.4	Average	Vertical
8	15870	45.2	7.2	52.4	74	-21.6	Peak	Vertical
IEEE 802.11ac-VHT80_Channel 106								
1	11060	32.2	3.1	35.3	54	-18.7	Average	Horizontal
2	11060	46.5	3.1	49.6	74	-24.4	Peak	Horizontal
3	16590	32.0	8.6	40.6	54	-13.5	Average	Horizontal
4	16590	44.4	8.6	52.9	68.2	-15.3	Peak	Horizontal
5	11060	32.2	3.1	35.3	54	-18.7	Average	Vertical
6	11060	45.8	3.1	49.0	74	-25.0	Peak	Vertical
7	16590	32.1	8.6	40.6	54	-13.4	Average	Vertical
8	16590	44.9	8.6	53.5	68.2	-14.7	Peak	Vertical
IEEE 802.11ac-VHT80_Channel 122								
1	11220	30.7	3.0	33.7	54	-20.3	Average	Horizontal
2	11220	45.8	3.0	48.8	74	-25.2	Peak	Horizontal
3	16830	31.6	9.0	40.6	54	-13.4	Average	Horizontal
4	16830	43.8	9.0	52.8	68.2	-15.4	Peak	Horizontal
5	11220	30.7	3.0	33.7	54	-20.3	Average	Vertical
6	11220	45.8	3.0	48.8	74	-25.2	Peak	Vertical
7	16830	31.6	9.0	40.6	54	-13.4	Average	Vertical
8	16830	43.2	9.0	52.3	68.2	-15.9	Peak	Vertical



No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
IEEE 802.11ac-VHT80_Channel 138								
1	11380	31.1	2.9	34.0	54	-20.0	Average	Horizontal
2	11380	45.2	2.9	48.1	74	-25.9	Peak	Horizontal
3	17070	31.5	9.6	41.1	54	-12.9	Average	Horizontal
4	17070	43.1	9.6	52.7	68.2	-15.5	Peak	Horizontal
5	11380	31.4	2.9	34.3	54	-19.7	Average	Vertical
6	11380	45.3	2.9	48.3	74	-25.8	Peak	Vertical
7	17070	31.5	9.6	41.0	54	-13.0	Average	Vertical
8	17070	44.1	9.6	53.7	68.2	-14.5	Peak	Vertical
IEEE 802.11ac-VHT80_Channel 155								
1	11550	30.1	2.8	32.9	54	-21.1	Average	Horizontal
2	11550	44.2	2.8	47.1	74	-26.9	Peak	Horizontal
3	17325	31.5	10.3	41.8	54	-12.3	Average	Horizontal
4	17325	43.1	10.3	53.4	68.2	-14.9	Peak	Horizontal
5	11550	30.3	2.8	33.1	54	-20.9	Average	Vertical
6	11550	45.3	2.8	48.2	74	-25.8	Peak	Vertical
7	17325	31.4	10.3	41.7	54	-12.3	Average	Vertical
8	17325	44.9	10.3	55.2	68.2	-13.1	Peak	Vertical

Remark:

1. Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain, the value was added to Original Receiver Reading by the software automatically.
2. Result = Reading + Correct Factor.
3. Margin = Result – Limit
4. For Radiated Emission above 18GHz, there was not any unwanted emission detected, so only the results of second and third harmonics are recorded in the report.

Band Edge Measurements (Radiated): Worst-Case Configuration

IEEE 802.11a



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China



Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China



Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China



Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888



Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2

IEEE 802.11n-HT20



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China



Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2



Shenzhen UnionTrust Quality and Technology Co., Ltd.


Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com
<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China



Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888



Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2

IEEE 802.11n-HT40



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China



Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China



Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2



Shenzhen UnionTrust Quality and Technology Co., Ltd.



Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com
<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888



Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2

IEEE 802.11ac-VHT80



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China



Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China



Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2



Shenzhen UnionTrust Quality and Technology Co., Ltd.


Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com
<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com
<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2

5.8 DYNAMIC FREQUENCY SELECTION

Test Requirement: FCC 47 CFR Part 15 Subpart E Section 15.407 (h)

Test Method: KDB 905462 D03 Client Without DFS New Rules v01r02

EUT Operating Mode:

DFS Operational mode	Operating Frequency Range	
	5250 MHz to 5350 MHz	5470 MHz to 5725 MHz
Slave without radar Interference detection function	✓	✓

Applicability:

The following table from KDB905462 and the lists of the applicable requirements for the DFS testing.

Applicability of DFS Requirements Prior to Use of a Channel:

Requirement	Operational Mode		
	Master	Client Without Radar Detection	Client With Radar Detection
Non-Occupancy Period	✓	Not required	Yes
DFS Detection Threshold	✓	Not required	Yes
Channel Availability Check Time	✓	Not required	Not required
U-NII Detection Bandwidth	✓	Not required	Yes

Applicability of DFS requirements during normal operation:

Requirement	Operational Mode	
	Master Device or Client with Radar Detection	Client Without Radar Detection
DFS Detection Threshold	Yes	Not required
Channel Closing Transmission Time	Yes	Yes
Channel Move Time	Yes	Yes
U-NII Detection Bandwidth	Yes	Not required
Additional requirements for devices with multiple bandwidth modes	Master Device or Client with Radar Detection	Client Without Radar Detection
U-NII Detection Bandwidth and Statistical Performance Check	All BW modes must be tested	Not required
Channel Move Time and Channel Closing Transmission Time	Test using widest BW mode available	Test using the widest BW mode available for the link
All other tests	Any single BW mode	Not required
Note: Frequencies selected for statistical performance check (Section 7.8.4) should include several frequencies within the radar detection bandwidth and frequencies near the edge of the radar detection bandwidth. For 802.11 devices it is suggested to select frequencies in each of the bonded 20 MHz channels and the channel center frequency.		

DFS Detection Thresholds for Master Devices and Client Devices with Radar Detection:

Maximum Transmit Power	Value (See Notes 1, 2, and 3)
EIRP ≥ 200 milliwatt	-64 dBm
EIRP < 200 milliwatt and power spectral density < 10 dBm/MHz	-62 dBm
EIRP < 200 milliwatt that do not meet the power spectral density requirement	-64dBm

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2

Note 1: This is the level at the input of the receiver assuming a 0 dBi receive antenna.

Note 2: Throughout these test procedures an additional 1 dB has been added to the amplitude of the test transmission waveforms to account for variations in measurement equipment. This will ensure that the test signal is at or above the detection threshold level to trigger a DFS response.

Note 3: EIRP is based on the highest antenna gain. For MIMO devices refer to KDB Publication 662911 D01.

DFS Radar Signal Parameter Values:

Parameter	Value
Non-occupancy period	Minimum 30 minutes
Channel Availability Check Time	60 seconds
Channel Move Time	10 seconds (See Note 1.)
Channel Closing Transmission Time	200 milliseconds + an aggregate of 60 milliseconds over remaining 10 second period. (See Notes 1 and 2.)
U-NII Detection Bandwidth	Minimum 100% of the U-NII 99% transmission power bandwidth. (See Note 3.)

Note 1: Channel Move Time and the Channel Closing Transmission Time should be performed with Radar Type 0. The measurement timing begins at the end of the Radar Type 0 burst.

Note 2: The Channel Closing Transmission Time is comprised of 200 milliseconds starting at the beginning of the Channel Move Time plus any additional intermittent control signals required to facilitate a Channel move (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions.

Note 3: During the U-NII Detection Bandwidth detection test, radar type 0 should be used. For each frequency step the minimum percentage of detection is 90 percent. Measurements are performed with no data traffic.

DFS Radar Signal Parameter:

Radar Type 0 was used in the evaluation of the Client device for the purpose of measuring the Channel Move Time and the Channel Closing Transmission Time

Table 1-Short Pulse Radar Test Waveforms

Radar Type	Pulse Width (μsec)	PRI (μsec)	Number of Pulses	Minimum Percentage of Successful Detection	Minimum Trials
0	1	1428	18	See Note 1.	See Note 1.
1	1	Test A Test B	$\text{Roundup} \left\{ \left(\frac{1}{\left(\frac{360}{19 \cdot 10^6}{\text{PRI}_{\mu\text{sec}}} \right)} \right) \right\}$	60%	30
2	1-5	150-230	23-29	60%	30
3	6-10	200-500	16-18	60%	30
4	11-20	200-500	12-16	60%	30
Aggregate (Radar Types 1-4)				80%	120

Note 1: Short Pulse Radar Type 0 should be used for the detection bandwidth test, channel move time, and channel closing time tests.

Test A: 15 unique PRI values randomly selected from the list of 23 PRI values in Table 5a

Test B: 15 unique PRI values randomly selected within the range of 518-3066 μsec, with a minimum increment of 1 μsec, excluding PRI values selected in Test A

A minimum of 30 unique waveforms are required for each of the Short Pulse Radar Types 2 through 4. If more than 30 waveforms are used for Short Pulse Radar Types 2 through 4, then each additional waveform must also be unique and not repeated from the previous waveforms.

If more than 30 waveforms are used for Short Pulse Radar Type 1, then each additional waveform is generated with Test B and must also be unique and not repeated from the previous waveforms in Tests A or B.

The aggregate is the average of the percentage of successful detections of short pulse radar types

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2

1-4

Table 2-Long Pulse Radar Test Waveform

Radar Type	Pulse Width (μsec)	Chirp Width (MHz)	PRI (μsec)	Number of Pulses per Burst	Number of Bursts	Minimum Percentage of Successful Detection	Minimum Trials
5	50-100	5-20	1000-2000	1-3	8-20	80%	30

Table 3-Frequency Hopping Radar Test Waveform

Radar Type	Pulse Width (μsec)	PRI (μsec)	Pulses per Hop	Hopping Rate (kHz)	Hopping Sequence Length (msec)	Minimum Percentage of Successful Detection	Minimum Trials
6	1	333	9	0.333	300	70%	30

In-Service Monitoring: Channel Move Time, Channel Closing Transmission Time and Non-Occupancy Period

Limit of In-Service Monitoring:

Reference to DFS Radar Signal Parameter Values.

Test Procedures:

- One frequency will be chosen from the Operating Channels of the EUT within the 5250-5350 MHz or 5470-5725 MHz bands. For 802.11 devices, the test frequency must contain control signals. This can be verified by disabling channel loading and monitoring the spectrum analyzer. If no control signals are detected, another frequency must be selected within the emission bandwidth where control signals are detected.
- In case the EUT is a Master Device, a U-NII device operating as a Client Device will be used and it is assumed that the Client will associate with the EUT (Master). For radiated tests, the emissions of the Radar Waveform generator will be directed towards the Master Device. If the Master Device has antenna gain, the main beam of the antenna will be directed toward the radar emitter. Vertical polarization is used for testing.
- The TCP protocol unicast data stream was generated by the iperf software command line with at least 17% activity ratio over any 100ms period.
- Timing plots are reported with calculations demonstrating a minimum channel loading of approximately 17% or greater. For example, channel loading can be estimated by setting the spectrum analyzer for zero span and approximate the Time On/ (Time On + Off Time).
- At time T₀ the Radar Waveform generator sends a Burst of pulses for one of the Short Pulse Radar Types 1-4 at DFS Detection Threshold levels on the Operating Channel. An additional 1 dB is added to the radar test signal to ensure it is at or above the DFS Detection Threshold, accounting for equipment variations/errors.
- Observe the transmissions of the EUT at the end of the radar Burst on the Operating Channel for duration greater than 10 seconds. Measure and record the transmissions from the EUT during the observation time (Channel Move Time). Measure and record the Channel Move Time and Channel Closing Transmission Time if radar detection occurs.
- When operating as a Master Device, monitor the EUT for more than 30 minutes following instant T₂ to verify that the EUT does not resume any transmissions on this Channel. Perform this test once and record the measurement result.




Figure 17: Channel Closing Transmission Time, Channel Move Time and Non-Occupancy Period

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2


Conducted test setup**Setup for Client with injection at the Master**

Equipment Used: Refer to section 3 for details.

Test Result: Result of Channel Move Time, Channel Closing Transmission Time and Non-Occupancy Period for Client Beacon Test

DFS Detection Thresholds

Test Mode	Frequency[dbm]	Radar Type	Result	Limit[dbm]	Verdict
11AC20SISO	5300	Type0	-60.49	-60.46	PASS
11AC20SISO	5500	Type0	-60.91	-60.46	PASS
11AC80SISO	5290	Type0	-60.84	-60.46	PASS
11AC80SISO	5530	Type0	-60.83	-60.46	PASS

Test Graphs**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886


E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2



11AC80SISO-5290-Type0-PASS




11AC80SISO-5530-Type0-PASS


Channel Move Time and Channel Closing Transmission Time

Test Mode	Frequency [MHz]	CCTT[ms]	Limit[ms]	CMT[ms]	Limit[ms]	Verdict
11AC20SISO	5300	200+40.3	200+60	1146.6	10000	PASS
11AC20SISO	5500	200+15.6	200+60	951.6	10000	PASS
11AC80SISO	5290	200+41.6	200+60	1203.8	10000	PASS
11AC80SISO	5530	200+19.5	200+60	1006.2	10000	PASS

Test Graphs




11AC20SISO-5300-Type0-PASS




Non-Occupancy Period

Test Mode	Frequency[MHz]	Result	Limit[s]	Verdict
11AC20SISO	5300	see test graph	≥1800	PASS
11AC20SISO	5500	see test graph	≥1800	PASS
11AC80SISO	5290	see test graph	≥1800	PASS
11AC80SISO	5530	see test graph	≥1800	PASS

Test Graphs





5.9 AC POWER LINE CONDUCTED EMISSION

Test Requirement: FCC 47 CFR Part 15 Subpart C Section 15.207

Test Method: ANSI C63.10-2013 Section 6.2

Limits:

Frequency range (MHz)	Limits (dB(μV))	
	Quasi-peak	Average
0,15 to 0,50	66 to 56	56 to 46
0,50 to 5	56	46
5 to 30	60	50

Remark:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 to 0.50 MHz.

Test Setup: Refer to section 4.4.2 for details.

Test Procedures:

Test frequency range :150KHz-30MHz

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Equipment Used: Refer to section 3 for details.


Test Result: Pass

The worst measurement data as follows:

Quasi Peak and Average:


Test Mode: WIFI Link

Live Line



No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1723	34.26	10.14	44.40	64.85	-20.45	QP
2	0.1723	17.68	10.14	27.82	54.85	-27.03	AVG
3	0.2174	32.76	10.06	42.82	62.92	-20.10	QP
4	0.2174	12.64	10.06	22.70	52.92	-30.22	AVG
5	0.3570	28.08	10.15	38.23	58.80	-20.57	QP
6	0.3570	15.09	10.15	25.24	48.80	-23.56	AVG
7	0.6450	36.20	10.25	46.45	56.00	-9.55	QP
8	0.6450	26.47	10.25	36.72	46.00	-9.28	AVG
9	1.0544	27.73	10.17	37.90	56.00	-18.10	QP
10	1.0544	16.33	10.17	26.50	46.00	-19.50	AVG
11	11.4990	24.97	10.47	35.44	60.00	-24.56	QP
12	11.4990	15.02	10.47	25.49	50.00	-24.51	AVG

Neutral Line



No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1723	33.34	10.14	43.48	64.85	-21.37	QP
2	0.1723	21.84	10.14	31.98	54.85	-22.87	AVG
3	0.4290	30.84	10.21	41.05	57.27	-16.22	QP
4	0.4290	20.29	10.21	30.50	47.27	-16.77	AVG
5	0.6360	39.94	10.25	50.19	56.00	-5.81	QP
6	0.6360	31.58	10.25	41.83	46.00	-4.17	AVG
7	1.0859	31.07	10.17	41.24	56.00	-14.76	QP
8	1.0859	18.79	10.17	28.96	46.00	-17.04	AVG
9	1.6572	30.30	10.27	40.57	56.00	-15.43	QP
10	1.6572	17.78	10.27	28.05	46.00	-17.95	AVG
11	13.5600	29.50	10.58	40.08	60.00	-19.92	QP
12	13.5600	16.65	10.58	27.23	50.00	-22.77	AVG

Remark:

1. Correct Factor = LISN Factor + Cable Loss + Pulse Limiter Factor, the value was added to Original Receiver Reading by the software automatically.
2. Result = Reading + Correct Factor.
3. Margin = Result - Limit
4. An initial pre-scan was performed on the Phase and neutral lines with peak detector. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.
5. All possible modes of operation were investigated, and testing at two nominal voltages of 240V/50Hz and 120V/60Hz, only the worst case emissions reported.

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2

APPENDIX A RF TEST DATA

A.1 26 DB BANDWIDTH

For U-NII-1, U-NII-2A, U-NII-2C band

Test Mode	Antenna	Frequency[MHz]	26db EBW [MHz]	Limit[MHz]	Verdict
11A	Ant1	5180	19.98	---	---
11A	Ant1	5220	19.65	---	---
11A	Ant1	5240	19.75	---	---
11A	Ant1	5260	19.63	---	---
11A	Ant1	5300	19.85	---	---
11A	Ant1	5320	19.88	---	---
11A	Ant1	5500	19.82	---	---
11A	Ant1	5600	19.64	---	---
11A	Ant1	5700	19.87	---	---
11A	Ant1	5720	19.76	---	---
11N20SISO	Ant1	5180	20.10	---	---
11N20SISO	Ant1	5220	20.17	---	---
11N20SISO	Ant1	5240	19.93	---	---
11N20SISO	Ant1	5260	20.19	---	---
11N20SISO	Ant1	5300	20.21	---	---
11N20SISO	Ant1	5320	20.03	---	---
11N20SISO	Ant1	5500	20.09	---	---
11N20SISO	Ant1	5600	20.13	---	---
11N20SISO	Ant1	5700	19.88	---	---
11N20SISO	Ant1	5720	20.21	---	---
11N40SISO	Ant1	5190	40.27	---	---
11N40SISO	Ant1	5230	40.45	---	---
11N40SISO	Ant1	5270	40.29	---	---
11N40SISO	Ant1	5310	40.06	---	---
11N40SISO	Ant1	5510	40.16	---	---
11N40SISO	Ant1	5590	39.87	---	---
11N40SISO	Ant1	5670	40.15	---	---
11N40SISO	Ant1	5710	39.89	---	---
11AC20SISO	Ant1	5180	20.11	---	---
11AC20SISO	Ant1	5220	20.20	---	---
11AC20SISO	Ant1	5240	20.25	---	---
11AC20SISO	Ant1	5260	19.89	---	---
11AC20SISO	Ant1	5300	20.05	---	---
11AC20SISO	Ant1	5320	19.94	---	---
11AC20SISO	Ant1	5500	19.92	---	---
11AC20SISO	Ant1	5600	20.18	---	---
11AC20SISO	Ant1	5700	20.13	---	---
11AC20SISO	Ant1	5720	20.38	---	---
11AC40SISO	Ant1	5190	39.84	---	---
11AC40SISO	Ant1	5230	40.05	---	---
11AC40SISO	Ant1	5270	39.91	---	---
11AC40SISO	Ant1	5310	40.23	---	---
11AC40SISO	Ant1	5510	39.96	---	---
11AC40SISO	Ant1	5590	40.19	---	---
11AC40SISO	Ant1	5670	39.75	---	---
11AC40SISO	Ant1	5710	40.10	---	---
11AC80SISO	Ant1	5210	80.74	---	---
11AC80SISO	Ant1	5290	80.59	---	---
11AC80SISO	Ant1	5530	80.50	---	---
11AC80SISO	Ant1	5610	80.13	---	---
11AC80SISO	Ant1	5690	80.52	---	---

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2

Test Graphs



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com


<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2

11A-Ant1-5240



11A-Ant1-5260

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com


<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2

11A-Ant1-5300



11A-Ant1-5320

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com


<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2

11A-Ant1-5500



11A-Ant1-5600

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com


<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2

11A-Ant1-5700



11A-Ant1-5720

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com


<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2

11N20SISO-Ant1-5180



11N20SISO-Ant1-5220



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com


<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2

11N20SISO-Ant1-5240



11N20SISO-Ant1-5260

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com


<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2

11N40SISO-Ant1-5510



11N40SISO-Ant1-5590

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com


<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2

11N40SISO-Ant1-5670



11N40SISO-Ant1-5710



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com


<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2

11AC20SISO-Ant1-5180



11AC20SISO-Ant1-5220

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com


<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2

11AC20SISO-Ant1-5240



11AC20SISO-Ant1-5260

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com


<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2

11AC20SISO-Ant1-5300



11AC20SISO-Ant1-5320



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com


<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2

11AC20SISO-Ant1-5500



11AC20SISO-Ant1-5600

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com


<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2

11AC20SISO-Ant1-5700



11AC20SISO-Ant1-5720



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com


<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2

11AC40SISO-Ant1-5190



11AC40SISO-Ant1-5230



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com


<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2

11AC40SISO-Ant1-5270



11AC40SISO-Ant1-5310

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com


<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2

11AC40SISO-Ant1-5510



11AC40SISO-Ant1-5590



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com


<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2

11AC40SISO-Ant1-5670



11AC40SISO-Ant1-5710

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com


<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2

11AC80SISO-Ant1-5530



11AC80SISO-Ant1-5610

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.407-V1.2