



## Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640  
Fax: +86-755-26648637  
Website: [www.cqa-cert.com](http://www.cqa-cert.com)

Report Template Version: V03  
Report Template Revision Date: Mar.1st, 2017

# RF Exposure Evaluation Report

**Report No. :** CQASZ20190500018EX-02  
**Applicant:** Fusion Fnc Co., Ltd  
**Address of Applicant:** F324 Misatesta Tower, Misagangbyeonso-ro 25, Hanam-si, Gyeonggi-do, South Korea  
**Manufacturer:** Dongguan Lingjie Electronics & Technology Co., Ltd  
**Address of Manufacturer:** 1-5/F B Building, 1-4/F A Building, No.16, Zhenxing Northern Road, Taiyuan Community, Xiegang Town, Dongguan City, Guangdong Province, P.R. China  
**Equipment Under Test (EUT):**  
**Product:** wireless mouse dongle  
**All Model No.:** KAKAO Receiver, FS-111L  
**Test Model No.:** KAKAO Receiver  
**Brand Name:** **KAKAO FRIENDS** / INOTE  
**FCC ID:** 2ATCF-KKREC  
**Standards:** 47 CFR Part 1.1307  
47 CFR Part 2.1093  
KDB447498D01 General RF Exposure Guidance v06  
**Date of Test:** 2019-04-28 to 2019-05-19  
**Date of Issue:** 2019-05-19  
**Test Result :** **PASS\***

**Tested By:**

*Daisy Qin*

(Daisy Qin)

**Reviewed By:**

*Aaron Ma*

(Aaron Ma)

**Approved By:**

*Jack Ai*

( Jack Ai)



\* In the configuration tested, the EUT complied with the standards specified above.

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

## 1 Version

### Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20190500018EX-02	Rev.01	Initial report	2019-05-19

## 2 Contents

	Page
1 VERSION .....	2
2 CONTENTS .....	3
3 GENERAL INFORMATION.....	4
3.1 CLIENT INFORMATION.....	4
3.2 GENERAL DESCRIPTION OF EUT .....	4
4 SAR EVALUATION .....	5
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT .....	5
4.1.1 <i>Standard Requirement</i> .....	5
4.1.2 <i>Limits</i> .....	5
4.1.3 <i>EUT RF Exposure</i> .....	6

### 3 General Information

#### 3.1 Client Information

Applicant:	Fusion Fnc Co., Ltd
Address of Applicant:	F324 Misatesta Tower, Misagangbyeonse-ro 25, Hanam-si, Gyeonggi-do, South Korea
Manufacturer:	Dongguan Lingjie Electronics & Technology Co., Ltd
Address of Manufacturer:	1-5/F B Building, 1-4/F A Building, No.16, Zhenxing Northern Road, Taiyuan Community, Xiegang Town, Dongguan City, Guangdong Province, P.R. China

#### 3.2 General Description of EUT

Product Name:	wireless mouse dongle
All Model No.:	KAKAO Receiver, FS-111L
Test Model No.:	KAKAO Receiver
Trade Mark:	<b>KAKAO FRIENDS</b> / INOTE
Hardware Version:	V1.0
Software Version:	V1.0
Operation Frequency:	2403.85 MHz~2479.85MHz
Modulation Type:	GFSK
Transfer Rate:	1Mbps
Number of Channel:	16
Product Type:	<input type="checkbox"/> Mobile <input checked="" type="checkbox"/> Portable <input type="checkbox"/> Fix Location
Antenna Type:	PCB antenna
Antenna Gain:	-0.71dBi
EUT Power Supply:	DC 5.0V from PC

Note:

There are many products, Only the model Wireless mouse RYAN was tested, since the electrical circuit design, layout, components used and internal wiring were identical for the above models, with difference being color of appearance and model name.

## 4 SAR Evaluation

### 4.1 RF Exposure Compliance Requirement

#### 4.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

##### 4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

#### 4.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$$\left[ \frac{\text{max. power of channel, including tune-up tolerance, mW}}{\text{min. test separation distance, mm}} \right] \cdot \sqrt{f(\text{GHz})} \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion

#### 4.1.3 EUT RF Exposure

GFSK						
Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
Lowest (2403.85MHz)	-7.224	-7.2	-7.0	0.200	1.957	3.0
Middle (2441.85MHz)	-7.655	-7.5	-7.0	0.200	1.972	
Highest (2479.85MHz)	-7.603	-7.5	-7.0	0.200	1.987	
<b>Conclusion: the calculated value <math>\leq 3.0</math>, SAR is exempted.</b>						

Remark: The Max Conducted Peak Output Power data refer to report Report No.: CQASZ20190500018EX-01