

FCC 47 CFR MPE REPORT

AnKobot (ShenZhen) Smart Technologies Co.,LTD

Robot vacuum cleaner

Model Number: A980

Additional Model: amarey T6, T6, T61

FCC ID: 2ATCH-SKC1618W

Prepared for:	AnKobot (ShenZhen) Smart Technologies Co.,LTD
	Room 402 4th Floor,Building H,Zhigu Science&Technology Park,Baoan
	District,Shenzhen,China
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
Tel: 86-769-83081888-808	

Report Number:	ESTE-R1908037
Date of Test:	Jul. 15-Aug. 05, 2019
Date of Report:	Aug. 07, 2019



Maximum Permissible Exposure

1、Applicable Standard

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

(a)、Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E 2 , H 2 or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

(b)、Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E 2 , H 2 or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

2、MPE Calculation Method

$$E \text{ (V/m)} = (30 \cdot P \cdot G) / 0.5/d \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = E^2/377$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = (30 \cdot P \cdot G) / (377 \cdot d^2)$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

3、Conducted Power Result

Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)	Target power (dBm)	Antenna gain	
					(dBi)	(Linear)
IEEE 802.11b	2412	18.81	76.033	18 ± 1	4	2.512
	2437	18.82	76.208	18 ± 1	4	2.512
	2462	18.99	79.250	18 ± 1	4	2.512
IEEE 802.11g	2412	21.83	152.405	21 ± 1	4	2.512
	2437	21.88	154.170	21 ± 1	4	2.512
	2462	22.12	162.930	22 ± 1	4	2.512
IEEE 802.11n HT20	2412	21.50	141.254	21 ± 1	4	2.512
	2437	21.38	137.404	21 ± 1	4	2.512
	2462	21.58	143.880	21 ± 1	4	2.512

4、Calculated Result and Limit

Mode	Target power (dBm)	Antenna gain		Power Density (S) (mW /cm ²)	Limited of Power Density (S) (mW /cm ²)	Test Result
		(dBi)	(Linear)			
IEEE 802.11b	19	4	2.512	0.03969	1	Compiles
IEEE 802.11g	23	4	2.512	0.09971	1	Compiles
IEEE 802.11n HT20	22	4	2.512	0.07920	1	Compiles