



RF EXPOSURE EXEMPT REPORT

APPLICANT : SHENZHEN TVT DIGITAL
TECHNOLOGY CO.,LTD.

PRODUCT NAME : Face Recognition & Access
Control Terminal

MODEL NAME : TD-E2127-IC, TD-E2127-IC/TP,
TD-E2127-TP, TD-E2127

BRAND NAME : TVT

FCC ID : 2ATOW-TD-E2127

STANDARD(S) : FCC 47CFR Part 2(2.1093)

RECEIPT DATE : 2021-09-06

TEST DATE : 2021-09-15 to 2021-10-15

ISSUE DATE : 2021-10-15

Edited by: Peng Mi
Peng Mi (Rapporteur)

Approved by: Shen Junsheng
Shen Junsheng (Supervisor)

NOTE: This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.





DIRECTORY

- 1. Technical Information..... 3
- 1.1 Applicant and Manufacturer Information..... 3
- 1.2 Equipment under Test (EUT) Description..... 3
- 1.3 Applied Reference Documents 4
- 2. Device Category and RF Exposure Limit 5
- 3. RF Exposure Assessment..... 6
- Annex A Testing Laboratory Information 7

Change History		
Version	Date	Reason for Change
1.0	2021-10-15	First edition



1. Technical Information

Note: Provide by applicant.

1.1 Applicant and Manufacturer Information

Applicant:	SHENZHEN TVT DIGITAL TECHNOLOGY CO.,LTD.
Applicant Address:	23rd Floor Building B4 Block 9, Shenzhen Bay science and technology ecological garden, Nanshan District, Shenzhen, P.R. China
Manufacturer:	SHENZHEN TVT DIGITAL TECHNOLOGY CO.,LTD.
Manufacturer Address:	23rd Floor Building B4 Block 9, Shenzhen Bay science and technology ecological garden, Nanshan District, Shenzhen, P.R. China

1.2 Equipment under Test (EUT) Description

Product Name:	KEY TOOL PLUS
Sample No.:	1#
Hardware Version:	1.4-1422322
Software Version:	5.0.1.0(21901)
Frequency Bands:	13.56MHz
Modulation Mode:	ASK



1.3 Applied Reference Documents

Leading reference documents for testing:

Identity	Document Title	Method determination /Remark
FCC 47CFR Part 2(2.1093)	Radio Frequency Radiation Exposure Assessment: portable devices	No deviation
KDB 447498 D01v06	General RF Exposure Guidance	No deviation

Note 1: Additions to, deviation, or exclusions from the method shall be judged in the "method determination" column of add, deviate or exclude from the specific method shall be explained in the "Remark" of the above table.

Note 2: When the test result is a critical value, we will use the measurement uncertainty give the judgment result based on the 95% confidence intervals.



2. Device Category and RF Exposure Limit

Per user manual, this device is a Face Recognition & Access Control Terminal. Based on 47CFR 2.1093, this device belongs to portable device category with General Population/Uncontrolled exposure.

Portable Devices: 47CFR 2.1093(b)

For purposes of this section, a portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user.

General Population/Uncontrolled Exposure: 47CFR 2.1093(d) (2)

The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity. Warning labels placed on low-power consumer devices such as cellular telephones are not considered sufficient to allow the device to be considered under the occupational/controlled category, and the general population/uncontrolled exposure limits apply to these devices.

Table 1—Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for General Population/Uncontrolled Exposure				
0.1–1.34	614	1.63	*(100)	6
1.34-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
(B) Limits for General Population/Uncontrolled Exposure				
0.1–1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30

f = frequency in MHz * = Plane-wave equivalent power density

3. RF Exposure Assessment



E-field Strength Result (Test frequency range from 0.1-1.34 MHz)				
Test Loading	E-field Strength (dB μ V/m)	E-field Strength (V/m)	Limit (V/m)	Result
13.56MHz	79.10	0.009016	824/f (60.77)	PASS

Note:

1. According to KDB 447498, MPE assessment is based on source-based time-averaged maximum conducted output power of the RF channel requiring assessment, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.

2. MPE calculate method

$$\text{Power Density} = \text{E.I.R.P.}/4\pi R^2$$

Where: E.I.R.P. = P+G

P = Output Power (dBm)

G = Antenna Gain (dBi)

R = Separation Distance (20cm)

➤ **Simultaneous Transmission Assessment:**

According to the user manual, the NFC transmitters in the device cannot operate simultaneously, therefore simultaneous transmission analysis is not required.

➤ **Conclusion:**

This device complies with human exposure basic restrictions defined in FCC 47CFR Part 2(2.1093) and FCC 47CFR Part 1.1310.



Annex A Testing Laboratory Information

1. Identification of the Responsible Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Laboratory Address:	FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Address:	FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

3. Facilities and Accreditations

All measurement facilities used to collect the measurement data are located at FL.3, Building A, FeiYang Science Park, Block 67, BaoAn District, Shenzhen, 518101 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.10-2013 and CISPR Publication 22; the FCC designation number is CN1192, the test firm registration number is 226174.

_____ END OF REPORT _____