

# FCC RF Exposure

EUT Description: Sound Bar

Model No.: S18L, S18D, S18H, S19L, S19D, S19H, S56L, S56D, S56H, S58L, S58D, S58H, DSB-4010, A80-110

FCC ID: 2ATQL-S18L

## 1. Limits

According to KDB 447498 D01 General RF Exposure Guidance v06 The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq$ 50 mm are determined by:

$[(\text{max power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR,

Where:

Result=P/D\* $\sqrt{F}$

F= the RF channel transmit frequency in GHz

P=Maximum turn-up power in mw

D=Min. test separation distance in mm

## 2. Test Result of RF Exposure Evaluation

2.4G

	Output power (dBm)	Tune Up Power (dBm)	Max Tune Up power dBm/mW	Min test separation distance mm	Result	Limit (mW/cm <sup>2</sup> )	SAR Test Exclusion
BT	3.35	3±1	4/ 2.51	5	0.780	3.0	Pass

Note:  
PK Output power= conducted power.  
Conducted power see the test report HK1907041539-E, antenna gain=0dBi

Per KDB 447498 D01, when the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion. The test exclusion threshold is 0.780 which is  $\leq 3$ , SAR testing is not required.

Note: Exclusion Thresholds Results= $[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Distance=5mm