



# RF TEST REPORT

|                   |                                      |
|-------------------|--------------------------------------|
| <b>Applicant</b>  | Quectel Wireless Solutions Co., Ltd. |
| <b>FCC ID</b>     | XMR201707BG96                        |
| <b>Product</b>    | Quectel BG96                         |
| <b>Brand</b>      | Quectel                              |
| <b>Model</b>      | BG96                                 |
| <b>Report No.</b> | RXA1706-0199RF05                     |
| <b>Issue Date</b> | August 29, 2017                      |

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC CFR47 Part 2 (2017)/ FCC CFR 47 Part 22H (2017)**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Performed by: Jiangpeng Lan

Approved by: Kai Xu

## TA Technology (Shanghai) Co., Ltd.

No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000



## TABLE OF CONTENT

|                                                      |    |
|------------------------------------------------------|----|
| 1. Test Laboratory .....                             | 4  |
| 1.1. Notes of the Test Report .....                  | 4  |
| 1.2. Test facility .....                             | 4  |
| 1.3. Testing Location .....                          | 5  |
| 2. General Description of Equipment under Test ..... | 6  |
| 3. Applied Standards .....                           | 7  |
| 4. Test Configuration .....                          | 8  |
| 5. Test Case Results .....                           | 9  |
| 5.1. RF Power Output .....                           | 9  |
| 5.2. Effective Radiated Power .....                  | 11 |
| 5.3. Occupied Bandwidth .....                        | 14 |
| 5.4. Band Edge Compliance .....                      | 22 |
| 5.5. Peak-to-Average Power Ratio (PAPR) .....        | 27 |
| 5.6. Frequency Stability .....                       | 29 |
| 5.7. Spurious Emissions at Antenna Terminals .....   | 33 |
| 5.8. Radiates Spurious Emission .....                | 36 |
| 6. Main Test Instruments .....                       | 42 |
| ANNEX A: EUT Appearance and Test Setup .....         | 43 |
| A.1 EUT Appearance .....                             | 43 |
| A.2 Test Setup .....                                 | 45 |

### Summary of measurement results

| No.                                                                                                                                                             | Test Type                               | Clause in FCC rules               | Verdict |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------|-----------------------------------|---------|
| 1                                                                                                                                                               | RF power output                         | 2.1046                            | PASS    |
| 2                                                                                                                                                               | Effective Radiated Power                | 22.913(a)(2)                      | PASS    |
| 3                                                                                                                                                               | Occupied Bandwidth                      | 2.1049                            | PASS    |
| 4                                                                                                                                                               | Band Edge Compliance                    | 2.1051 / 22.917(a)                | PASS    |
| 5                                                                                                                                                               | Peak-to-Average Power Ratio             | 22.913(d)/<br>KDB 971168 D01(5.7) | PASS    |
| 6                                                                                                                                                               | Frequency Stability                     | 2.1055 / 22.355                   | PASS    |
| 7                                                                                                                                                               | Spurious Emissions at Antenna Terminals | 2.1051 / 22.917(a)                | PASS    |
| 8                                                                                                                                                               | Radiates Spurious Emission              | 2.1053 / 22.917 (a)               | PASS    |
| Date of Testing: August 4, 2017 ~ August 18, 2017                                                                                                               |                                         |                                   |         |
| Note: PASS: The EUT complies with the essential requirements in the standard.<br>FAIL: The EUT does not comply with the essential requirements in the standard. |                                         |                                   |         |



## 1. Test Laboratory

### 1.1. Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **TA technology (shanghai) co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above. This report must not be used by the client to claim product certification, approval, or endorsement by any government agencies.

### 1.2. Test facility

#### **CNAS (accreditation number: L2264)**

TA Technology (Shanghai) Co., Ltd. has obtained the accreditation of China National Accreditation Service for Conformity Assessment (CNAS).

#### **FCC (Designation number: CN1179, Test Firm Registration Number: 446626)**

TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

#### **IC (recognition number is 8510A)**

TA Technology (Shanghai) Co., Ltd. has been listed by industry Canada to perform electromagnetic emission measurement.

#### **VCCI (recognition number is C-4595, T-2154, R-4113, G-10766)**

TA Technology (Shanghai) Co., Ltd. has been listed by industry Japan to perform electromagnetic emission measurement.

#### **A2LA (Certificate Number: 3857.01)**

TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.



### 1.3. Testing Location

Company: TA Technology (Shanghai) Co., Ltd.  
Address: No.145, Jintang Rd, Tangzhen Industry Park, Pudong  
City: Shanghai  
Post code: 201201  
Country: P. R. China  
Contact: Xu Kai  
Telephone: +86-021-50791141/2/3  
Fax: +86-021-50791141/2/3-8000  
Website: <http://www.ta-shanghai.com>  
E-mail: [xukai@ta-shanghai.com](mailto:xukai@ta-shanghai.com)

## 2. General Description of Equipment under Test

### Client Information

|                      |                                                                                    |
|----------------------|------------------------------------------------------------------------------------|
| Applicant            | Quectel Wireless Solutions Co., Ltd.                                               |
| Applicant address    | 7th Floor, Hongye Building, No. 1801 Hongmei Road, Xuhui District, Shanghai, China |
| Manufacturer         | Quectel Wireless Solutions Co., Ltd.                                               |
| Manufacturer address | 7th Floor, Hongye Building, No. 1801 Hongmei Road, Xuhui District, Shanghai, China |

### General Information

| EUT Description                                                   |                                                                                                                                 |           |           |
|-------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|-----------|-----------|
| Model                                                             | BG96                                                                                                                            |           |           |
| IMEI                                                              | 864508030012063                                                                                                                 |           |           |
| Hardware Version                                                  | R1.0                                                                                                                            |           |           |
| Software Version                                                  | BG96MAR02A02M1G                                                                                                                 |           |           |
| Power Supply                                                      | External power supply                                                                                                           |           |           |
| Antenna Type                                                      | The EUT don't have standard Antenna, The Antenna used for testing in this report is the after-market accessory (Dipole Antenna) |           |           |
| Test Mode(s)                                                      | NB-IOT Band5; NB-IOT Band26;                                                                                                    |           |           |
| Test Modulation                                                   | BPSK, QPSK                                                                                                                      |           |           |
| NB-IOT Category                                                   | NB1                                                                                                                             |           |           |
| Maximum E.R.P.                                                    | NB-IOT Band 5:                                                                                                                  | 26.60 dBm |           |
|                                                                   | NB-IOT Band 26:                                                                                                                 | 26.96 dBm |           |
| Rated Power Supply Voltage                                        | 3.8V                                                                                                                            |           |           |
| Extreme Voltage                                                   | Minimum: 3.3V     Maximum: 4.3V                                                                                                 |           |           |
| Extreme Temperature                                               | Lowest: -40°C     Highest: +85°C                                                                                                |           |           |
| Operating Frequency Range(s)                                      | Band                                                                                                                            | Tx (MHz)  | Rx (MHz)  |
|                                                                   | NB-IOT Band 5                                                                                                                   | 824 ~ 849 | 869 ~ 894 |
|                                                                   | NB-IOT Band 26                                                                                                                  | 824 ~ 849 | 869 ~ 894 |
| Note: The information of the EUT is declared by the manufacturer. |                                                                                                                                 |           |           |

| Accessory equipment |                         |
|---------------------|-------------------------|
| Evaluation Board    | RF Cable                |
| RS232-to-USB Cable  | Antenna: Dipole Antenna |
| Headset             | USB Cable               |



### **3. Applied Standards**

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC CFR47 Part 2 (2017)**

**FCC CFR 47 Part 22H (2017)**

**ANSI/TIA-603-D (2010)**

**KDB 971168 D01 Power Meas License Digital Systems v02r02**

## 4. Test Configuration

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes. EUT stand-up position (X, Y axis), lie-down position (Z axis). Receiver antenna polarization (horizontal and vertical), the worst emission was found in position (Z axis, vertical polarization) and the worst case was recorded.

All mode and data rates and positions were investigated. Subsequently, only the worst case emissions are reported.

The following testing in NB-IOT is set based on the maximum RF Output Power.

Test modes are chosen as the worst case configuration below for NB-IOT Band 5/26

| Test items                                                                                                                                    | Modes      | Deployment mode | Subcarrier Spacing (kHz) |    | Modulation |      | Test Channel |   |   |
|-----------------------------------------------------------------------------------------------------------------------------------------------|------------|-----------------|--------------------------|----|------------|------|--------------|---|---|
|                                                                                                                                               |            | Stand-alone     | 3                        | 15 | BPSK       | QPSK | L            | M | H |
| RF power output                                                                                                                               | NB-IOT B5  | O               | O                        | O  | O          | O    | O            | O | O |
|                                                                                                                                               | NB-IOT B26 | O               | O                        | O  | O          | O    | O            | O | O |
| Effective Isotropic Radiated power                                                                                                            | NB-IOT B5  | O               | O                        | O  | O          | O    | O            | O | O |
|                                                                                                                                               | NB-IOT B26 | O               | O                        | O  | O          | O    | O            | O | O |
| Occupied Bandwidth                                                                                                                            | NB-IOT B5  | O               | O                        | O  | O          | O    | O            | O | O |
|                                                                                                                                               | NB-IOT B26 | O               | O                        | O  | O          | O    | O            | O | O |
| Band Edge Compliance                                                                                                                          | NB-IOT B5  | O               | O                        | O  | O          | O    | O            | - | O |
|                                                                                                                                               | NB-IOT B26 | O               | O                        | O  | O          | O    | O            | - | O |
| Peak-to-Average Power Ratio                                                                                                                   | NB-IOT B5  | O               | O                        | O  | O          | O    | -            | O | - |
|                                                                                                                                               | NB-IOT B26 | O               | O                        | O  | O          | O    | -            | O | - |
| Frequency Stability                                                                                                                           | NB-IOT B5  | O               | O                        | O  | O          | O    | -            | O | - |
|                                                                                                                                               | NB-IOT B26 | O               | O                        | O  | O          | O    | -            | O | - |
| Spurious Emissions at Antenna Terminals                                                                                                       | NB-IOT B5  | O               | -                        | O  | -          | O    | O            | O | O |
|                                                                                                                                               | NB-IOT B26 | O               | -                        | O  | -          | O    | O            | O | O |
| Radiates Spurious Emission                                                                                                                    | NB-IOT B5  | O               | -                        | O  | -          | O    | O            | O | O |
|                                                                                                                                               | NB-IOT B26 | O               | -                        | O  | -          | O    | O            | O | O |
| Note<br>1. The mark "O" means that this configuration is chosen for testing.<br>2. The mark "-" means that this configuration is not testing. |            |                 |                          |    |            |      |              |   |   |



## 5. Test Case Results

### 5.1. RF Power Output


#### Ambient condition

| Temperature | Relative humidity | Pressure |
|-------------|-------------------|----------|
| 23°C ~25°C  | 45%~50%           | 101.5kPa |

#### Methods of Measurement

During the process of the testing, The EUT is controlled by the Base Station Simulator to ensure max power transmission and proper modulation.

#### Test Setup



The loss between RF output port of the EUT and the input port of the tester has been taken into consideration.

#### Limits

No specific RF power output requirements in part 2.1046.

#### Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 2$ ,  $U = 0.4$  dB.

## Test Results

| NB-IOT Band 5   |                          |            |        | Conducted Power(dBm)   |             |             |
|-----------------|--------------------------|------------|--------|------------------------|-------------|-------------|
| Deployment mode | Subcarrier Spacing (kHz) | Modulation | Ntones | Channel/Frequency(MHz) |             |             |
|                 |                          |            |        | 20401/824.1            | 20525/836.5 | 20649/848.9 |
| Stand-alone     | 3.75                     | BPSK       | 1@0    | 22.05                  | 22.19       | 22.38       |
|                 |                          | BPSK       | 1@47   | 21.94                  | 22.18       | 22.35       |
|                 | 15                       | BPSK       | 1@0    | 22.24                  | 22.31       | 22.41       |
|                 |                          | BPSK       | 1@11   | 22.26                  | 22.37       | 22.73       |
|                 | 3.75                     | QPSK       | 1@0    | 22.02                  | 22.09       | 22.31       |
|                 |                          | QPSK       | 1@47   | 21.91                  | 22.13       | 22.34       |
|                 | 15                       | QPSK       | 1@0    | 22.28                  | 22.36       | 22.43       |
|                 |                          | QPSK       | 1@11   | 22.25                  | 22.40       | 22.72       |
|                 |                          | QPSK       | 12@0   | 22.59                  | 22.65       | 22.67       |
|                 |                          |            |        |                        |             |             |

| NB-IOT Band 26  |                          |            |        | Conducted Power(dBm)   |             |             |
|-----------------|--------------------------|------------|--------|------------------------|-------------|-------------|
| Deployment mode | Subcarrier Spacing (kHz) | Modulation | Ntones | Channel/Frequency(MHz) |             |             |
|                 |                          |            |        | 26791/824.1            | 26915/836.5 | 27039/848.9 |
| Stand-alone     | 3.75                     | BPSK       | 1@0    | 23.09                  | 23.14       | 23.10       |
|                 |                          | BPSK       | 1@47   | 23.08                  | 23.15       | 23.09       |
|                 | 15                       | BPSK       | 1@0    | 21.90                  | 22.06       | 22.47       |
|                 |                          | BPSK       | 1@11   | 21.89                  | 22.11       | 22.49       |
|                 | 3.75                     | QPSK       | 1@0    | 23.06                  | 23.16       | 23.10       |
|                 |                          | QPSK       | 1@47   | 23.08                  | 23.14       | 23.11       |
|                 | 15                       | QPSK       | 1@0    | 21.95                  | 22.03       | 22.47       |
|                 |                          | QPSK       | 1@11   | 21.94                  | 22.31       | 22.50       |
|                 |                          | QPSK       | 12@0   | 22.24                  | 22.53       | 22.75       |
|                 |                          |            |        |                        |             |             |

## 5.2. Effective Radiated Power

### Ambient condition


| Temperature | Relative humidity | Pressure |
|-------------|-------------------|----------|
| 23°C ~25°C  | 45%~50%           | 101.5kPa |

### Methods of Measurement


1. The testing follows FCC KDB 971168 v02r02 Section 5.8 and ANSI / TIA-603-D-2010 Section 2.2.12.
2. EUT was placed on a 0.8 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna between 1.0m and 4.0m. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.
3. A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
4. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=1MHz, VBW=3MHz for above 1GHz and RBW=100kHz, VBW=300kHz for 30MHz to 1GHz,, And the maximum value of the receiver should be recorded as (Pr).
5. The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (PMea) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (Pr). The power of signal source (PMea) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.
6. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (Pcl), the Substitution Antenna Gain (Ga) and the Amplifier Gain (PAg) should be recorded after test.
7. The measurement results are obtained as described below:  
$$\text{Power(EIRP)} = \text{PMea} - \text{PAg} - \text{Pcl} + \text{Ga}$$
  
The measurement results are amend as described below:  
$$\text{Power(EIRP)} = \text{PMea} - \text{Pcl} + \text{Ga}$$
8. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power. ERP can be calculated from EIRP by subtracting the gain of the dipole,  $\text{ERP} = \text{EIRP} - 2.15\text{dBi}$ .

## Test configuration

### Below 1GHz:



### Above 1GHz:



## Limits

Rule Part 22.913(a) specifies that "Mobile/portable stations are limited to 7 watts ERP".

|            |                                |
|------------|--------------------------------|
| Limit(ERP) | $\leq 7 \text{ W}$ (38.45 dBm) |
|------------|--------------------------------|

## Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 2$ ,  $U = 1.19 \text{ dB}$



## Test Results:

| NB-IOT Band 5 Standalone |            |                           |          |          |          |          |           |             |            |
|--------------------------|------------|---------------------------|----------|----------|----------|----------|-----------|-------------|------------|
| Frequency (MHz)          | Modulation | Sub-carrier spacing (KHz) | Rt (dBm) | Rs (dBm) | Ps (dBm) | Gs (dBd) | ERP (dBm) | Limit (dBm) | Conclusion |
| 824.1                    | BPSK       | 3.75                      | -48.19   | -47.13   | 0.00     | 1.06     | 26.05     | 38.45       | Pass       |
|                          | QPSK       | 3.75                      | -48.19   | -47.13   | 0.00     | 1.06     | 26.02     | 38.45       | Pass       |
|                          | BPSK       | 15                        | -48.19   | -47.12   | 0.00     | 1.06     | 26.24     | 38.45       | Pass       |
|                          | QPSK       | 15                        | -48.19   | -47.12   | 0.00     | 1.06     | 25.38     | 38.45       | Pass       |
| 836.5                    | BPSK       | 3.75                      | -48.44   | -47.20   | 0.00     | 1.24     | 26.19     | 38.45       | Pass       |
|                          | QPSK       | 3.75                      | -48.44   | -47.20   | 0.00     | 1.24     | 26.09     | 38.45       | Pass       |
|                          | BPSK       | 15                        | -48.34   | -47.10   | 0.00     | 1.24     | 26.31     | 38.45       | Pass       |
|                          | QPSK       | 15                        | -48.34   | -47.10   | 0.00     | 1.24     | 26.07     | 38.45       | Pass       |
| 848.9                    | BPSK       | 3.75                      | -48.97   | -47.59   | 0.00     | 1.38     | 26.38     | 38.45       | Pass       |
|                          | QPSK       | 3.75                      | -48.97   | -47.59   | 0.00     | 1.38     | 26.00     | 38.45       | Pass       |
|                          | BPSK       | 15                        | -48.79   | -47.41   | 0.00     | 1.38     | 26.41     | 38.45       | Pass       |
|                          | QPSK       | 15                        | -48.79   | -47.41   | 0.00     | 1.38     | 26.60     | 38.45       | Pass       |

| NB-IOT Band 26 Standalone |            |                           |          |          |          |          |           |             |            |
|---------------------------|------------|---------------------------|----------|----------|----------|----------|-----------|-------------|------------|
| Frequency (MHz)           | Modulation | Sub-carrier spacing (KHz) | Rt (dBm) | Rs (dBm) | Ps (dBm) | Gs (dBd) | ERP (dBm) | Limit (dBm) | Conclusion |
| 824.1                     | BPSK       | 3.75                      | -48.19   | -47.13   | 0.00     | 1.06     | 26.89     | 38.45       | Pass       |
|                           | QPSK       | 3.75                      | -48.19   | -47.13   | 0.00     | 1.06     | 26.86     | 38.45       | Pass       |
|                           | BPSK       | 15                        | -48.19   | -47.12   | 0.00     | 1.06     | 25.70     | 38.45       | Pass       |
|                           | QPSK       | 15                        | -48.19   | -47.12   | 0.00     | 1.06     | 25.92     | 38.45       | Pass       |
| 836.5                     | BPSK       | 3.75                      | -48.49   | -47.20   | 0.00     | 1.28     | 26.94     | 38.45       | Pass       |
|                           | QPSK       | 3.75                      | -48.49   | -47.20   | 0.00     | 1.28     | 26.96     | 38.45       | Pass       |
|                           | BPSK       | 15                        | -48.39   | -47.10   | 0.00     | 1.28     | 25.86     | 38.45       | Pass       |
|                           | QPSK       | 15                        | -48.39   | -47.10   | 0.00     | 1.28     | 25.83     | 38.45       | Pass       |
| 848.9                     | BPSK       | 3.75                      | -48.97   | -47.59   | 0.00     | 1.38     | 26.90     | 38.45       | Pass       |
|                           | QPSK       | 3.75                      | -48.97   | -47.59   | 0.00     | 1.38     | 26.90     | 38.45       | Pass       |
|                           | BPSK       | 15                        | -48.81   | -47.42   | 0.00     | 1.38     | 26.27     | 38.45       | Pass       |
|                           | QPSK       | 15                        | -48.81   | -47.42   | 0.00     | 1.38     | 26.85     | 38.45       | Pass       |

### 5.3. Occupied Bandwidth

#### Ambient condition

| Temperature | Relative humidity | Pressure |
|-------------|-------------------|----------|
| 23°C ~25°C  | 45%~50%           | 101.5kPa |


#### Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The occupied bandwidth is measured using spectrum analyzer.

RBW is set to 2kHz, VBW is set to 6.2kHz for NB-IOT Band 5/26,

99% power and -26dBc occupied bandwidths are recorded. Spectrum analyzer plots are included on the following pages.

#### Test Setup



#### Limits

No specific occupied bandwidth requirements in part 2.1049.

#### Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 2$ ,  $U = 624\text{Hz}$ .

## Test Result


| NB-IOT Band 5 Standalone       |            |                                 |        |                             |                          |
|--------------------------------|------------|---------------------------------|--------|-----------------------------|--------------------------|
| Channel/<br>Frequency<br>(MHz) | Modulation | Sub-carrier<br>spacing<br>(kHz) | Ntones | 99% Power<br>Bandwidth(kHz) | -26dBc<br>Bandwidth(kHz) |
| 20401/<br>824.1                | BPSK       | 3.75                            | 1@0    | 52.363                      | 38.440                   |
|                                | QPSK       | 3.75                            | 1@0    | 148.470                     | 116.100                  |
|                                | BPSK       | 15                              | 1@0    | 59.335                      | 39.580                   |
|                                | QPSK       | 15                              | 1@0    | 148.250                     | 154.700                  |
|                                | QPSK       | 15                              | 12@0   | 195.600                     | 263.600                  |
| 20525/<br>836.5                | BPSK       | 3.75                            | 1@0    | 56.131                      | 38.570                   |
|                                | QPSK       | 3.75                            | 1@0    | 156.770                     | 117.300                  |
|                                | BPSK       | 15                              | 1@0    | 66.647                      | 42.360                   |
|                                | QPSK       | 15                              | 1@0    | 141.810                     | 130.800                  |
|                                | QPSK       | 15                              | 12@0   | 195.410                     | 265.600                  |
| 20649/<br>848.9                | BPSK       | 3.75                            | 1@0    | 53.834                      | 38.500                   |
|                                | QPSK       | 3.75                            | 1@0    | 149.760                     | 113.200                  |
|                                | BPSK       | 15                              | 1@0    | 62.498                      | 40.040                   |
|                                | QPSK       | 15                              | 1@0    | 139.860                     | 130.100                  |
|                                | QPSK       | 15                              | 12@0   | 196.640                     | 291.600                  |

| NB-IOT Band 26 Standalone      |            |                                 |        |                             |                          |
|--------------------------------|------------|---------------------------------|--------|-----------------------------|--------------------------|
| Channel/<br>Frequency<br>(MHz) | Modulation | Sub-carrier<br>spacing<br>(kHz) | Ntones | 99% Power<br>Bandwidth(kHz) | -26dBc<br>Bandwidth(kHz) |
| 26791/<br>824.1                | BPSK       | 3.75                            | 1@0    | 49.135                      | 36.100                   |
|                                | QPSK       | 3.75                            | 1@0    | 148.040                     | 113.600                  |
|                                | BPSK       | 15                              | 1@0    | 58.200                      | 35.610                   |
|                                | QPSK       | 15                              | 1@0    | 146.510                     | 144.700                  |
|                                | QPSK       | 15                              | 12@0   | 196.220                     | 299.300                  |
| 26915/<br>836.5                | BPSK       | 3.75                            | 1@0    | 49.953                      | 36.490                   |
|                                | QPSK       | 3.75                            | 1@0    | 146.270                     | 117.600                  |
|                                | BPSK       | 15                              | 1@0    | 61.664                      | 42.130                   |
|                                | QPSK       | 15                              | 1@0    | 141.820                     | 117.300                  |
|                                | QPSK       | 15                              | 12@0   | 192.310                     | 284.600                  |
| 27039/<br>848.9                | BPSK       | 3.75                            | 1@0    | 54.566                      | 38.650                   |
|                                | QPSK       | 3.75                            | 1@0    | 159.220                     | 143.400                  |
|                                | BPSK       | 15                              | 1@0    | 61.568                      | 41.690                   |
|                                | QPSK       | 15                              | 1@0    | 143.730                     | 116.100                  |
|                                | QPSK       | 15                              | 12@0   | 187.340                     | 272.100                  |






NB-IOT Band 5 BPSK 3.75kHz 1@0 CH-Low




NB-IOT Band 5 BPSK 15kHz 1@0 CH-Low




NB-IOT Band 5 BPSK 3.75kHz 1@0 CH-Middle



NB-IOT Band 5 BPSK 15kHz 1@0 CH-Middle




NB-IOT Band 5 BPSK 3.75kHz 1@0 CH-High




NB-IOT Band 5 BPSK 15kHz 1@0 CH-High




NB-IOT Band 5 QPSK 3.75kHz 1@0 CH-Low




NB-IOT Band 5 QPSK 15kHz 1@0 CH-Low




NB-IOT Band 5 QPSK 3.75kHz 1@0 CH-Middle



NB-IOT Band 5 QPSK 15kHz 1@0 CH-Middle



NB-IOT Band 5 QPSK 3.75kHz 1@0 CH-High




NB-IOT Band 5 QPSK 15kHz 1@0 CH-High







## NB-IOT Band 5 QPSK 15kHz 12@0 CH-Low




## NB-IOT Band 26 BPSK 3.75kHz 1@0 CH-Low




## NB-IOT Band 5 QPSK 15kHz 12@0 CH-Middle




## NB-IOT Band 26 BPSK 3.75kHz 1@0 CH-Middle



## NB-IOT Band 5 QPSK 15kHz 12@0 CH-High




## NB-IOT Band 26 BPSK 3.75kHz 1@0 CH-High







## NB-IOT Band 26 BPSK 15kHz 1@0 CH-Low




## NB-IOT Band 26 QPSK 3.75kHz 1@0 CH-Low




## NB-IOT Band 26 BPSK 15kHz 1@0 CH-Middle




## NB-IOT Band 26 QPSK 3.75kHz 1@0 CH-Middle



## NB-IOT Band 26 BPSK 15kHz 1@0 CH-High




## NB-IOT Band 26 QPSK 3.75kHz 1@0 CH-High









NB-IOT Band 26 QPSK 15kHz 1@0 CH-Low




NB-IOT Band 26 QPSK 15kHz 12@0 CH-Low




NB-IOT Band 26 QPSK 15kHz 1@0 CH-Middle




NB-IOT Band 26 QPSK 15kHz 12@0 CH-Middle



NB-IOT Band 26 QPSK 15kHz 1@0 CH-High



NB-IOT Band 26 QPSK 15kHz 12@0 CH-High



## 5.4. Band Edge Compliance

### Ambient condition

| Temperature | Relative humidity | Pressure |
|-------------|-------------------|----------|
| 23°C ~25°C  | 45%~50%           | 101.5kPa |

### Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The band edge of the lowest and highest channels were measured. The average detector is used.


RBW is set to 51Hz, VBW is set to 160Hz for 3.75KHz single carrier,

RBW is set to 200Hz, VBW is set to 620Hz for 15KHz single carrier,

RBW is set to 2kHz, VBW is set to 6.2KHz for 15KHz full carrier,

Spectrum analyzer plots are included on the following pages.

### Test Setup



### Limits

Rule Part 22.917(a) specifies that “The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.”

| Limit | -13 dBm |
|-------|---------|
|-------|---------|


### Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 1.96$ ,  $U=0.684$ dB.




## Test Result:


NB-IOT Band 5 BPSK 3.75kHz 1@0 CH-Low




NB-IOT Band 5 BPSK 3.75kHz 1@47 CH-High




NB-IOT Band 5 BPSK 15kHz 1@0 CH-Low




NB-IOT Band 5 BPSK 15kHz 1@11 CH-High




NB-IOT Band 5 QPSK 3.75kHz 1@0 CH-Low




NB-IOT Band 5 QPSK 3.75kHz 1@47 CH-High




NB-IOT Band 5 QPSK 15kHz 1@0 CH-Low




NB-IOT Band 5 QPSK 15kHz 1@11 CH-High



NB-IOT Band 5 QPSK 15kHz 12@0 CH-Low




NB-IOT Band 5 QPSK 15kHz 12@0 CH-High







NB-IOT Band 26 BPSK 3.75kHz 1@0 CH-Low




NB-IOT Band 26 BPSK 3.75kHz 1@47 CH-High




NB-IOT Band 26 BPSK 15kHz 1@0 CH-Low




NB-IOT Band 26 BPSK 15kHz 1@11 CH-High




NB-IOT Band 26 QPSK 3.75kHz 1@0 CH-Low




NB-IOT Band 26 QPSK 3.75kHz 1@47 CH-High




NB-IOT Band 26 QPSK 15kHz 1@0 CH-Low




NB-IOT Band 26 QPSK 15kHz 1@11 CH-High



NB-IOT Band 26 QPSK 15kHz 12@0 CH-Low



NB-IOT Band 26 QPSK 15kHz 12@0 CH-High



## 5.5. Peak-to-Average Power Ratio (PAPR)

### Ambient condition


| Temperature | Relative humidity | Pressure |
|-------------|-------------------|----------|
| 23°C ~25°C  | 45%~50%           | 101.5kPa |

### Methods of Measurement

Measure the total peak power and record as  $P_{Pk}$ . And measure the total average power and record as  $P_{Avg}$ . Both the peak and average power levels must be expressed in the same logarithmic units (e.g., dBm). Determine the PAPR from:

$$PAPR (dB) = P_{Pk} (dBm) - P_{Avg} (dBm).$$

### Test Setup



### Limits

According to the Sec. 22.913(d), The peak-to-average ratio (PAR) of the transmission must not exceed 13 dB.

### Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 2$ ,  $U = 0.4$  dB.

## Test Results

| NB-IOT Band 5 Standalone |                           |                          |            |           |           |            |            |
|--------------------------|---------------------------|--------------------------|------------|-----------|-----------|------------|------------|
| Modulation               | Sub-carrier spacing (KHz) | Channel/ Frequency (MHz) | Peak (dBm) | Avg (dBm) | PAPR (dB) | Limit (dB) | Conclusion |
| BPSK                     | 3.75                      | 20525/836.5              | 25.50      | 22.19     | 3.31      | ≤13        | PASS       |
| QPSK                     | 3.75                      | 20525/836.5              | 28.37      | 22.31     | 6.06      | ≤13        | PASS       |
| BPSK                     | 15                        | 20525/836.5              | 25.27      | 22.09     | 3.18      | ≤13        | PASS       |
| QPSK                     | 15                        | 20525/836.5              | 28.49      | 22.36     | 6.13      | ≤13        | PASS       |

| NB-IOT Band 26 Standalone |                           |                          |            |           |           |            |            |
|---------------------------|---------------------------|--------------------------|------------|-----------|-----------|------------|------------|
| Modulation                | Sub-carrier spacing (KHz) | Channel/ Frequency (MHz) | Peak (dBm) | Avg (dBm) | PAPR (dB) | Limit (dB) | Conclusion |
| BPSK                      | 3.75                      | 26915/836.5              | 26.96      | 23.14     | 3.82      | ≤13        | PASS       |
| QPSK                      | 3.75                      | 26915/836.5              | 28.09      | 22.06     | 6.03      | ≤13        | PASS       |
| BPSK                      | 15                        | 26915/836.5              | 27.08      | 23.16     | 3.92      | ≤13        | PASS       |
| QPSK                      | 15                        | 26915/836.5              | 28.26      | 22.03     | 6.23      | ≤13        | PASS       |

## 5.6. Frequency Stability

### Ambient condition

| Temperature | Relative humidity | Pressure |
|-------------|-------------------|----------|
| 23°C ~25°C  | 45%~50%           | 101.5kPa |

### Method of Measurement

#### 1. Frequency Stability (Temperature Variation)

The temperature inside the climate chamber is varied from -40°C to +85°C in 10°C step size,

(1) With all power removed, the temperature was decreased to 0°C and permitted to stabilize for three hours.

(2) Measure the carrier frequency with the test equipment in a “call mode”. These measurements should be made within 1 minute of powering up the mobile station, to prevent significant self warming.

(3) Repeat the above measurements at 10°C increments from -40°C to +85°C. Allow at least 1.5 hours at each temperature, un-powered, before making measurements. Frequency Stability (Voltage Variation)


The frequency stability shall be measured with variation of primary supply voltage as follows:

(1) Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

(2) For hand carried, battery powered equipment, reduce primary supply voltage to the battery-operating end point which shall be specified by the manufacturer.

This transceiver is specified to operate with an input voltage of between 3.3 V and 4.3 V, with a nominal voltage of 3.8V.

### Test setup



**Limits**

According to the Sec. 22.355, the frequency stability of the carrier shall be accurate to within 2.5 ppm of the received frequency for mobile stations.

|        |                |
|--------|----------------|
| Limits | $\leq 2.5$ ppm |
|--------|----------------|

**Measurement Uncertainty**

The assessed measurement uncertainty to ensure 99.75% confidence level for the normal distribution is with the coverage factor  $k = 3$ ,  $U = 0.01$  ppm.

# Test Result

| NB-IOT Band 5 Standalone CH20525 |                      |          |          |             |            |
|----------------------------------|----------------------|----------|----------|-------------|------------|
| Test Results (ppm)               |                      |          |          |             |            |
| Sub-carrier spacing (kHz)        | Test status          | BPSK     | QPSK     | Limit (ppm) | Conclusion |
| 3.75                             | -40°C/Normal Voltage | -0.00126 | -0.00338 | 2.5         | PASS       |
|                                  | -30°C/Normal Voltage | -0.00216 | -0.00230 | 2.5         | PASS       |
|                                  | -20°C/Normal Voltage | -0.00084 | -0.00408 | 2.5         | PASS       |
|                                  | -10°C/Normal Voltage | -0.00151 | -0.00322 | 2.5         | PASS       |
|                                  | 0°C/Normal Voltage   | -0.00049 | -0.00158 | 2.5         | PASS       |
|                                  | 10°C/Normal Voltage  | -0.00269 | -0.00249 | 2.5         | PASS       |
|                                  | 20°C/Normal Voltage  | -0.00192 | -0.00252 | 2.5         | PASS       |
|                                  | 30°C/Normal Voltage  | -0.00146 | -0.00306 | 2.5         | PASS       |
|                                  | 40°C/Normal Voltage  | -0.00085 | -0.00169 | 2.5         | PASS       |
|                                  | 50°C/Normal Voltage  | -0.00195 | -0.00146 | 2.5         | PASS       |
|                                  | 60°C/Normal Voltage  | -0.00159 | -0.00154 | 2.5         | PASS       |
|                                  | 70°C/Normal Voltage  | -0.00149 | -0.00281 | 2.5         | PASS       |
|                                  | 80°C/Normal Voltage  | -0.00115 | -0.00124 | 2.5         | PASS       |
|                                  | 85°C/Normal Voltage  | -0.00274 | -0.00102 | 2.5         | PASS       |
|                                  | 20°C/Minimum Voltage | -0.00276 | -0.00244 | 2.5         | PASS       |
|                                  | 20°C/Maximum Voltage | -0.00176 | -0.00221 | 2.5         | PASS       |
| 15                               | -40°C/Normal Voltage | -0.00429 | -0.00201 | 2.5         | PASS       |
|                                  | -30°C/Normal Voltage | -0.00149 | -0.00244 | 2.5         | PASS       |
|                                  | -20°C/Normal Voltage | -0.00240 | -0.00255 | 2.5         | PASS       |
|                                  | -10°C/Normal Voltage | -0.00024 | -0.00175 | 2.5         | PASS       |
|                                  | 0°C/Normal Voltage   | -0.00317 | -0.00263 | 2.5         | PASS       |
|                                  | 10°C/Normal Voltage  | 0.00662  | -0.00257 | 2.5         | PASS       |
|                                  | 20°C/Normal Voltage  | -0.00147 | -0.00109 | 2.5         | PASS       |
|                                  | 30°C/Normal Voltage  | -0.00082 | -0.00104 | 2.5         | PASS       |
|                                  | 40°C/Normal Voltage  | -0.00300 | -0.00032 | 2.5         | PASS       |
|                                  | 50°C/Normal Voltage  | -0.00005 | -0.00186 | 2.5         | PASS       |
|                                  | 60°C/Normal Voltage  | -0.00069 | -0.00160 | 2.5         | PASS       |
|                                  | 70°C/Normal Voltage  | -0.00073 | -0.00067 | 2.5         | PASS       |
|                                  | 80°C/Normal Voltage  | -0.00207 | -0.00261 | 2.5         | PASS       |
|                                  | 85°C/Normal Voltage  | -0.00282 | -0.00255 | 2.5         | PASS       |
|                                  | 20°C/Minimum Voltage | -0.01197 | -0.00100 | 2.5         | PASS       |
|                                  | 20°C/Maximum Voltage | -0.00196 | -0.00141 | 2.5         | PASS       |

| NB-IOT Band 26 Standalone CH26915 |                      |          |          |             |            |
|-----------------------------------|----------------------|----------|----------|-------------|------------|
| Test Results (ppm)                |                      |          |          |             |            |
| Sub-carrier spacing (kHz)         | Test status          | BPSK     | QPSK     | Limit (ppm) | Conclusion |
| 3.75                              | -40°C/Normal Voltage | -0.00127 | -0.00152 | 2.5         | PASS       |
|                                   | -30°C/Normal Voltage | -0.00258 | -0.00147 | 2.5         | PASS       |
|                                   | -20°C/Normal Voltage | 0.00111  | -0.00252 | 2.5         | PASS       |
|                                   | -10°C/Normal Voltage | -0.00149 | -0.00294 | 2.5         | PASS       |
|                                   | 0°C/Normal Voltage   | -0.00045 | -0.00375 | 2.5         | PASS       |
|                                   | 10°C/Normal Voltage  | 0.00130  | 0.00090  | 2.5         | PASS       |
|                                   | 20°C/Normal Voltage  | -0.00079 | -0.00111 | 2.5         | PASS       |
|                                   | 30°C/Normal Voltage  | 0.00276  | 0.00042  | 2.5         | PASS       |
|                                   | 40°C/Normal Voltage  | -0.00253 | -0.00241 | 2.5         | PASS       |
|                                   | 50°C/Normal Voltage  | -0.00189 | 0.00054  | 2.5         | PASS       |
|                                   | 60°C/Normal Voltage  | -0.00354 | -0.00142 | 2.5         | PASS       |
|                                   | 70°C/Normal Voltage  | -0.00139 | 0.00080  | 2.5         | PASS       |
|                                   | 80°C/Normal Voltage  | -0.00032 | -0.00041 | 2.5         | PASS       |
|                                   | 85°C/Normal Voltage  | -0.00073 | -0.00240 | 2.5         | PASS       |
|                                   | 20°C/Minimum Voltage | -0.00106 | -0.00285 | 2.5         | PASS       |
|                                   | 20°C/Maximum Voltage | -0.00307 | -0.00196 | 2.5         | PASS       |
| 15                                | -40°C/Normal Voltage | -0.00245 | -0.00348 | 2.5         | PASS       |
|                                   | -30°C/Normal Voltage | -0.00209 | -0.00020 | 2.5         | PASS       |
|                                   | -20°C/Normal Voltage | 0.00059  | 0.00111  | 2.5         | PASS       |
|                                   | -10°C/Normal Voltage | -0.00118 | 0.00197  | 2.5         | PASS       |
|                                   | 0°C/Normal Voltage   | 0.00154  | 0.00136  | 2.5         | PASS       |
|                                   | 10°C/Normal Voltage  | 0.00134  | 0.00061  | 2.5         | PASS       |
|                                   | 20°C/Normal Voltage  | -0.00100 | -0.00137 | 2.5         | PASS       |
|                                   | 30°C/Normal Voltage  | 0.00318  | 0.00124  | 2.5         | PASS       |
|                                   | 40°C/Normal Voltage  | -0.00200 | 0.00253  | 2.5         | PASS       |
|                                   | 50°C/Normal Voltage  | 0.00134  | -0.00110 | 2.5         | PASS       |
|                                   | 60°C/Normal Voltage  | 0.00071  | -0.00030 | 2.5         | PASS       |
|                                   | 70°C/Normal Voltage  | -0.00109 | -0.00151 | 2.5         | PASS       |
|                                   | 80°C/Normal Voltage  | -0.00196 | -0.00114 | 2.5         | PASS       |
|                                   | 85°C/Normal Voltage  | -0.00164 | -0.00080 | 2.5         | PASS       |
|                                   | 20°C/Minimum Voltage | -0.00171 | -0.00183 | 2.5         | PASS       |
|                                   | 20°C/Maximum Voltage | 0.00127  | -0.00227 | 2.5         | PASS       |



## 5.7. Spurious Emissions at Antenna Terminals


### Ambient condition

| Temperature | Relative humidity | Pressure |
|-------------|-------------------|----------|
| 23°C ~25°C  | 45%~50%           | 101.5kPa |

### Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The measurement is carried out using a spectrum analyzer. The spectrum analyzer scans from 9kHz to the 10th harmonic of the carrier. The peak detector is used. RBW are set to 100 kHz and VBW are set to 300 kHz for below 1G, RBW are set to 1MHz and VBW are set to 3MHz for above 1G, Sweep is set to ATUO.

### Test setup



### Limits

Rule Part 22.917(a) specifies that “The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log (P)$  dB.”

| Limit | -13 dBm |
|-------|---------|
|-------|---------|

### Measurement Uncertainty

The assessed measurement uncertainty to ensure 99.75% confidence level for the normal distribution is with the coverage factor  $k = 1.96$ .

| Frequency     | Uncertainty |
|---------------|-------------|
| 100kHz-2GHz   | 0.684 dB    |
| 2GHz-12.75GHz | 1.407 dB    |

## Test Result


Sweep from 9 kHz to 30MHz, and the emissions more than 20 dB below the permissible value are not reported.

If disturbances were found more than 20dB below limit line, the mark is not required for the EUT.


The signal beyond the limit is carrier.

**Standalone deployment with 15 KHz subcarrier spacing and QPSK mode for CAT NB1:**


NB-IOT Band 5 CH-Low 30MHz-1.5GHz




NB-IOT Band 5 CH-Low 1.5GHz-9GHz




NB-IOT Band 5 CH-Middle 30MHz-1.5GHz




NB-IOT Band 5 CH-Middle 1.5GHz-9GHz



NB-IOT Band 5 CH-High 30MHz-1.5GHz




NB-IOT Band 5 CH-High 1.5GHz-9GHz







NB-IOT Band 26 CH-Low 30MHz-1.5GHz




NB-IOT Band 26 CH-Low 1.5GHz~9GHz




NB-IOT Band 26 CH-Middle 30MHz-1.5GHz




NB-IOT Band 26 CH-Middle 1.5GHz~9GHz



NB-IOT Band 26 CH-High 30MHz-1.5GHz



NB-IOT Band 26 CH-High 1.5GHz~9GHz



## 5.8. Radiates Spurious Emission

### Ambient condition

| Temperature | Relative humidity | Pressure |
|-------------|-------------------|----------|
| 23°C ~25°C  | 45%~50%           | 101.5kPa |


### Method of Measurement

1. The testing follows FCC KDB 971168 v02r02 Section 5.8 and ANSI / TIA-603-D-2010 Section 2.2.12.
2. Above 30MHz: The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H). Above 1GHz: (Note: the FCC's permission to use 1.5m as an aNB-IoT native per TCBC Conf call of Dec. 2, 2014.) The EUT is placed on a turntable 1.5 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).
3. A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
4. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=1MHz, VBW=3MHz for above 1GHz and RBW=100kHz, VBW=300kHz for 30MHz to 1GHz, And the maximum value of the receiver should be recorded as (Pr).
5. The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (PMea) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (Pr). The power of signal source (PMea) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.
6. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (Pcl), the Substitution Antenna Gain (Ga) and the Amplifier Gain (PAg) should be recorded after test.
7. The measurement results are obtained as described below:  
$$\text{Power(EIRP)} = \text{PMea} - \text{PAg} - \text{Pcl} + \text{Ga}$$
  
The measurement results are amend as described below:  
$$\text{Power(EIRP)} = \text{PMea} - \text{Pcl} + \text{Ga}$$


8. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power. ERP can be calculated from EIRP by subtracting the gain of the dipole,  $ERP = EIRP - 2.15\text{dBi}$ .

### Test setup

30MHz~~~ 1GHz



Above 1GHz



Note: Area side:2.4mX3.6m

The radiated emission was measured in the following position: EUT lie-down position (Z axis), stand-up position (X, Y axis). The worst emission was found in lie-down position (Z axis) and the worst case was recorded.

## Limits

Rule Part 22.917(a) specifies that “The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log (P)$  dB.”

|       |         |
|-------|---------|
| Limit | -13 dBm |
|-------|---------|

## Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 1.96$ ,  $U = 3.55$  dB.

## Test Result

The other Spurious RF Radiated emissions level is no more than noise floor.

The worst emission was found in the antenna is vertical position.

**Standalone deployment with 15 KHz subcarrier spacing and QPSK mode for CAT NB1:**

### NB-IOT Band 5 CH-Low

| Harmonic | Frequency (MHz) | SG (dBm) | Cable Loss (dB) | Gain (dBi) | Antenna Polarization | ERP Level (dBm) | Limit (dBm) | Margin (dB) | Azimuth (deg) |
|----------|-----------------|----------|-----------------|------------|----------------------|-----------------|-------------|-------------|---------------|
| 2        | 1648.2          | -51.43   | 2.00            | 10.75      | vertical             | -44.83          | -13.0       | 31.83       | 45            |
| 3        | 2472.3          | -50.19   | 2.51            | 11.05      | vertical             | -43.80          | -13.0       | 30.80       | 180           |
| 4        | 3296.4          | -54.02   | 4.20            | 11.15      | vertical             | -49.22          | -13.0       | 36.22       | 225           |
| 5        | 4120.5          | -52.28   | 5.20            | 11.15      | vertical             | -48.48          | -13.0       | 35.48       | 135           |
| 6        | 4944.6          | -51.49   | 5.50            | 11.95      | vertical             | -47.19          | -13.0       | 34.19       | 225           |
| 7        | 5768.7          | -53.53   | 5.70            | 13.55      | vertical             | -47.83          | -13.0       | 34.83       | 90            |
| 8        | 6592.8          | -49.00   | 6.30            | 13.75      | vertical             | -43.70          | -13.0       | 30.70       | 90            |
| 9        | 7416.9          | -45.85   | 6.80            | 13.85      | vertical             | -40.95          | -13.0       | 27.95       | 45            |
| 10       | 8241.0          | -46.71   | 6.90            | 14.25      | vertical             | -41.51          | -13.0       | 28.51       | 180           |

### NB-IOT Band 5 CH-Middle

| Harmonic | Frequency (MHz) | SG (dBm) | Cable Loss (dB) | Gain (dBi) | Antenna Polarization | ERP Level (dBm) | Limit (dBm) | Margin (dB) | Azimuth (deg) |
|----------|-----------------|----------|-----------------|------------|----------------------|-----------------|-------------|-------------|---------------|
| 2        | 1673.0          | -50.41   | 2.00            | 10.75      | vertical             | -43.81          | -13.0       | 30.81       | 45            |
| 3        | 2509.5          | -54.13   | 2.51            | 11.05      | vertical             | -47.74          | -13.0       | 34.74       | 45            |
| 4        | 3346.0          | -54.15   | 4.20            | 11.15      | vertical             | -49.35          | -13.0       | 36.35       | 180           |
| 5        | 4182.5          | -52.83   | 5.20            | 11.15      | vertical             | -49.03          | -13.0       | 36.03       | 315           |
| 6        | 5019.0          | -52.27   | 5.50            | 11.95      | vertical             | -47.97          | -13.0       | 34.97       | 135           |
| 7        | 5855.5          | -51.23   | 5.70            | 13.55      | vertical             | -45.53          | -13.0       | 32.53       | 225           |
| 8        | 6692.0          | -51.64   | 6.30            | 13.75      | vertical             | -46.34          | -13.0       | 33.34       | 90            |
| 9        | 7528.5          | -46.57   | 6.80            | 13.85      | vertical             | -41.67          | -13.0       | 28.67       | 180           |
| 10       | 8365.0          | -48.16   | 6.90            | 14.25      | vertical             | -42.96          | -13.0       | 29.96       | 45            |

**NB-IOT Band 5 CH-High**

| Harmonic | Frequency (MHz) | SG (dBm) | Cable Loss (dB) | Gain (dBi) | Antenna Polarization | ERP Level (dBm) | Limit (dBm) | Margin (dB) | Azimuth (deg) |
|----------|-----------------|----------|-----------------|------------|----------------------|-----------------|-------------|-------------|---------------|
| 2        | 1697.8          | -46.04   | 2.00            | 10.75      | vertical             | -39.44          | -13.0       | 26.4        | 180           |
| 3        | 2546.7          | -55.09   | 2.51            | 11.05      | vertical             | -48.70          | -13.0       | 35.7        | 45            |
| 4        | 3395.6          | -54.79   | 4.20            | 11.15      | vertical             | -49.99          | -13.0       | 37.0        | 0             |
| 5        | 4244.5          | -53.50   | 5.20            | 11.15      | vertical             | -49.70          | -13.0       | 36.7        | 135           |
| 6        | 5093.4          | -48.96   | 5.50            | 11.95      | vertical             | -44.66          | -13.0       | 31.7        | 225           |
| 7        | 5942.3          | -52.54   | 5.70            | 13.55      | vertical             | -46.84          | -13.0       | 33.8        | 90            |
| 8        | 6791.2          | -50.53   | 6.30            | 13.75      | vertical             | -45.23          | -13.0       | 32.2        | 225           |
| 9        | 7640.1          | -44.95   | 6.80            | 13.85      | vertical             | -40.05          | -13.0       | 27.1        | 180           |
| 10       | 8489.0          | -47.16   | 6.90            | 14.25      | vertical             | -41.96          | -13.0       | 29.0        | 270           |

**NB-IOT Band 26 CH-Low**

| Harmonic | Frequency (MHz) | SG (dBm) | Cable Loss (dB) | Gain (dBi) | Antenna Polarization | ERP Level (dBm) | Limit (dBm) | Margin (dB) | Azimuth (deg) |
|----------|-----------------|----------|-----------------|------------|----------------------|-----------------|-------------|-------------|---------------|
| 2        | 1648.2          | -51.54   | 2.00            | 10.75      | vertical             | -44.94          | -13.0       | 31.94       | 90            |
| 3        | 2472.3          | -50.87   | 2.51            | 11.05      | vertical             | -44.48          | -13.0       | 31.48       | 225           |
| 4        | 3296.4          | -55.98   | 4.20            | 11.15      | vertical             | -51.18          | -13.0       | 38.18       | 45            |
| 5        | 4120.5          | -52.50   | 5.20            | 11.15      | vertical             | -48.70          | -13.0       | 35.70       | 180           |
| 6        | 4944.6          | -51.13   | 5.50            | 11.95      | vertical             | -46.83          | -13.0       | 33.83       | 315           |
| 7        | 5768.7          | -51.92   | 5.70            | 13.55      | vertical             | -46.22          | -13.0       | 33.22       | 135           |
| 8        | 6592.8          | -50.01   | 6.30            | 13.75      | vertical             | -44.71          | -13.0       | 31.71       | 225           |
| 9        | 7416.9          | -45.83   | 6.80            | 13.85      | vertical             | -40.93          | -13.0       | 27.93       | 90            |
| 10       | 8241.0          | -46.51   | 6.90            | 14.25      | vertical             | -41.31          | -13.0       | 28.31       | 180           |





## NB-IOT Band 26 CH-Middle

| Harmonic | Frequency (MHz) | SG (dBm) | Cable Loss (dB) | Gain (dBi) | Antenna Polarization | ERP Level (dBm) | Limit (dBm) | Margin (dB) | Azimuth (deg) |
|----------|-----------------|----------|-----------------|------------|----------------------|-----------------|-------------|-------------|---------------|
| 2        | 1673.0          | -49.58   | 2.00            | 10.75      | vertical             | -42.98          | -13.0       | 29.98       | 45            |
| 3        | 2509.5          | -54.21   | 2.51            | 11.05      | vertical             | -47.82          | -13.0       | 34.82       | 180           |
| 4        | 3346.0          | -55.37   | 4.20            | 11.15      | vertical             | -50.57          | -13.0       | 37.57       | 45            |
| 5        | 4182.5          | -52.76   | 5.20            | 11.15      | vertical             | -48.96          | -13.0       | 35.96       | 0             |
| 6        | 5019.0          | -49.56   | 5.50            | 11.95      | vertical             | -45.26          | -13.0       | 32.26       | 135           |
| 7        | 5855.5          | -51.80   | 5.70            | 13.55      | vertical             | -46.10          | -13.0       | 33.10       | 225           |
| 8        | 6692.0          | -48.91   | 6.30            | 13.75      | vertical             | -43.61          | -13.0       | 30.61       | 90            |
| 9        | 7528.5          | -46.35   | 6.80            | 13.85      | vertical             | -41.45          | -13.0       | 28.45       | 225           |
| 10       | 8365.0          | -46.60   | 6.90            | 14.25      | vertical             | -41.40          | -13.0       | 28.40       | 180           |

## NB-IOT Band 26 CH-High

| Harmonic | Frequency (MHz) | SG (dBm) | Cable Loss (dB) | Gain (dBi) | Antenna Polarization | ERP Level (dBm) | Limit (dBm) | Margin (dB) | Azimuth (deg) |
|----------|-----------------|----------|-----------------|------------|----------------------|-----------------|-------------|-------------|---------------|
| 2        | 1697.8          | -47.38   | 2.00            | 10.75      | vertical             | -40.78          | -13.0       | 27.78       | 270           |
| 3        | 2546.7          | -53.64   | 2.51            | 11.05      | vertical             | -47.25          | -13.0       | 34.25       | 135           |
| 4        | 3395.6          | -56.34   | 4.20            | 11.15      | vertical             | -51.54          | -13.0       | 38.54       | 225           |
| 5        | 4244.5          | -52.12   | 5.20            | 11.15      | vertical             | -48.32          | -13.0       | 35.32       | 135           |
| 6        | 5093.4          | -50.54   | 5.50            | 11.95      | vertical             | -46.24          | -13.0       | 33.24       | 90            |
| 7        | 5942.3          | -51.34   | 5.70            | 13.55      | vertical             | -45.64          | -13.0       | 32.64       | 45            |
| 8        | 6791.2          | -49.42   | 6.30            | 13.75      | vertical             | -44.12          | -13.0       | 31.12       | 180           |
| 9        | 7640.1          | -46.71   | 6.80            | 13.85      | vertical             | -41.81          | -13.0       | 28.81       | 45            |
| 10       | 8489.0          | -47.38   | 6.90            | 14.25      | vertical             | -42.18          | -13.0       | 29.18       | 0             |


## 6. Main Test Instruments

| Name                                 | Manufacturer | Type         | Serial Number | Calibration Date | Expiration Time |
|--------------------------------------|--------------|--------------|---------------|------------------|-----------------|
| Base Station Simulator               | R&S          | CMW500       | 150415        | 2017-05-14       | 2018-05-13      |
| Power Splitter                       | Hua Xiang    | SHX-GF2-2-13 | 10120101      | 2017-05-14       | 2018-05-13      |
| Spectrum Analyzer                    | Agilent      | N9010A       | MY47191109    | 2017-05-20       | 2018-05-19      |
| Universal Radio Communication Tester | Agilent      | E5515C       | MY48367192    | 2017-05-20       | 2018-05-19      |
| Signal Analyzer                      | R&S          | FSV30        | 100815        | 2016-12-16       | 2017-12-15      |
| EMI Test Receiver                    | R&S          | ESCI         | 100948        | 2017-05-20       | 2018-05-19      |
| Signal generator                     | R&S          | SMB 100A     | 102594        | 2017-05-14       | 2018-05-13      |
| Signal generator                     | R&S          | SMR27        | 100365        | 2017-05-14       | 2018-05-13      |
| Trilog Antenna                       | SCHWARZBECK  | VUBL 9163    | 9163-201      | 2014-12-06       | 2017-12-05      |
| Horn Antenna                         | R&S          | HF907        | 100126        | 2014-12-06       | 2017-12-05      |
| Horn Antenna                         | ETS-Lindgren | 3160-09      | 00102644      | 2015-01-30       | 2018-01-29      |
| Climatic Chamber                     | Re Ce        | PT-30B       | 20101891      | 2015-07-18       | 2018-07-17      |
| RF Cable                             | Agilent      | SMA 15cm     | 0001          | 2017-02-06       | 2017-08-05      |
| Preamplifier                         | R&S          | SCU18        | 102327        | 2017-06-18       | 2018-06-17      |


\*\*\*\*\*END OF REPORT \*\*\*\*\*

## ANNEX A: EUT Appearance and Test Setup

### A.1 EUT Appearance




shielding



No shielding

Front Side





Back Side

a: EUT



## A.2 Test Setup



Picture 2: Radiated Spurious Emissions Test setup