

TEST REPORT

FCC Rules Part 15.247

Report Reference No...... : **MTEB23070019-R**

FCC ID. : **2ATYP-HK9600**

Compiled by

(position+printed name+signature): File administrators Alisa Luo



Supervised by

(position+printed name+signature): Test Engineer Sunny Deng



Approved by

(position+printed name+signature): Manager Yvette Zhou



Date of issue..... : Jul.04,2023

Representative Laboratory Name

Shenzhen Most Technology Service Co., Ltd.

Address

No.5, 2nd Langshan Road, North District, Hi-tech Industrial
Park, Nanshan, Shenzhen, Guangdong, China.

Applicant' s name : **Shiji (US) Inc.**

Address

730 Peachtree Street NE, Suite 375, Atlanta, Georgia, 30319,
United States

Test specification/ Standard : **FCC Rules Part 15.247**

TRF Originator..... : Shenzhen Most Technology Service Co., Ltd.

Shenzhen Most Technology Service Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Most Technology Service Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Most Technology Service Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description..... : POS COMPUTER

Trade Mark: Shiji

Model/Type reference.....: HK9600

Listed Models: HK960U, HK968, HK968U

Modulation Type: GFSK, $\pi/4$ DQPSK, 8DPSK

Operation Frequency.....: From 2402MHz to 2480MHz

Hardware Version..... MTGU3BP

Software Version F4e

Rating: DC 24V (by Adapter)

Result: PASS

TEST REPORT

Equipment under Test : POS COMPUTER

Model /Type : HK9600

Listed Models HK960U, HK968, HK968U

Remark All models are identical to each other, except model name.

Applicant : **Shiji (US) Inc.**

Address : 730 Peachtree Street NE, Suite 375, Atlanta, Georgia, 30319, United States

Manufacturer : **Shiji (US) Inc.**

Address : 730 Peachtree Street NE, Suite 375, Atlanta, Georgia, 30319, United States

Test Result:	PASS
--------------	------

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

<u>1</u>	<u>REVISION HISTORY</u>	<u>5</u>
<u>2</u>	<u>TEST STANDARDS</u>	<u>6</u>
<u>3</u>	<u>SUMMARY</u>	<u>7</u>
3.1	General Remarks	7
3.2	Product Description	7
3.3	Equipment Under Test	7
3.4	Short description of the Equipment under Test (EUT)	7
3.5	EUT operation mode	8
3.6	Block Diagram of Test Setup	8
3.7	Test Item (Equipment Under Test) Description*	8
3.8	Auxiliary Equipment (AE) Description	8
3.9	Antenna Information*	8
3.10	Related Submittal(s) / Grant (s)	9
3.11	EUT configuration	9
3.12	Modifications	9
<u>4</u>	<u>TEST ENVIRONMENT</u>	<u>10</u>
4.1	Address of the test laboratory	10
4.2	Environmental conditions	10
4.3	Summary of measurement results	11
4.4	Statement of the measurement uncertainty	11
4.5	Equipments Used during the Test	12
<u>5</u>	<u>TEST CONDITIONS AND RESULTS</u>	<u>13</u>
5.1	AC Power Conducted Emission	13
5.2	Radiated Emission	18
5.3	Maximum Peak Output Power	27
5.4	20dB Bandwidth	28
5.5	Frequency Separation	29
5.6	Number of hopping frequency	30
5.7	Time of Occupancy (Dwell Time)	31
5.8	Spurious RF Conducted Emission	32
5.9	Pseudorandom Frequency Hopping Sequence	33
5.10	Antenna Requirement	34
<u>6</u>	<u>TEST SETUP PHOTOS OF THE EUT</u>	<u>35</u>
<u>7</u>	<u>PHOTOS OF THE EUT</u>	<u>38</u>
	APPENDIX I. Conducted Peak Output Power	39
	APPENDIX II. 99% Bandwidth	40
	APPENDIX III. 20dB Bandwidth	43
	APPENDIX IV. Carrier Frequencies Separation	45
	APPENDIX V. Conducted Out Of Band Emission	47
	APPENDIX VI. Duty Cycle	55

APPENDIX VII.Dwell Time	60
APPENDIX VIII.Number Of Hopping Channel	64

1 Revision History

Revision	Issue Date	Revisions	Revised By
00	2023-07-04	Initial Issue	Alisa Luo

2 TEST STANDARDS

The tests were performed according to following standards:

[FCC Rules Part 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

[ANSI C63.10-2013](#): American National Standard for Testing Unlicensed Wireless Devices

3 SUMMARY

3.1 General Remarks

Date of receipt of test sample	:	2023.06.26
Testing commenced on	:	2023.06.27
Testing concluded on	:	2023.07.04

3.2 Product Description

Product Name:	POS COMPUTER
Model/Type reference:	HK9600
Power Supply :	DC 24V (by Adapter)
Testing sample ID :	MTYP01898-1899
Bluetooth :	
Supported Type:	Bluetooth BR/EDR
Modulation:	GFSK, $\pi/4$ DQPSK, 8DPSK
Operation frequency:	2402MHz~2480MHz
Channel number:	79
Channel separation:	1MHz
Antenna type:	FPC Antenna
Antenna gain:	1.8dBi

3.3 Equipment Under Test

Power supply system utilised

Power supply voltage	:	☐ 230V / 50 Hz	☐ 120V / 60Hz
		☐ 12 V DC	☐ 24 V DC
		☒ Other (specified in blank below)	

DC 24V (by Adapter)

3.4 Short description of the Equipment under Test (EUT)

This is a BT SPEAKER For more details, refer to the user's manual of the EUT.


3.5 EUT operation mode

The Applicant provides communication tools software(Engineer mode) to control the EUT for staying in continuous transmitting (Duty Cycle more than 98%) and receiving mode for testing .There are 79 channels provided to the EUT and Channel 00/39/78 were selected to test.

Operation Frequency:

Channel	Frequency (MHz)
00	2402
01	2403
⋮	⋮
38	2440
39	2441
40	2442
⋮	⋮
77	2479
78	2480

3.6 Block Diagram of Test Setup



3.7 Test Item (Equipment Under Test) Description*

Short designation	EUT Name	EUT Description	Serial number	Hardware status	Software status
EUT A	Adapter	GM60-240250-F			
EUT B	Adapter	FSP060-DAAN3			
EUT C	Adapter	FSP120-AAAN3			

*: declared by the applicant. According to customers information EUTs A and B are the same devices.

3.8 Auxiliary Equipment (AE) Description

AE short designation	EUT Name (if available)	EUT Description	Serial number (if available)	Software (if used)
AE 1				
AE 2				

3.9 Antenna Information*

Short designation	Antenna Name	Antenna Type	Frequency Range	Serial number	Antenna Peak Gain
Antenna 1	---	FPC Antenna	2.4 – 2.5 GHz	---	1.8dBi
Antenna 2					

*: declared by the applicant.

3.10 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for the device filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

3.11 EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

● - supplied by the manufacturer

○ - Supplied by the lab

●	ADAPTER 1	M/N:	GM60-240250-F
		Manufacturer:	Foshan Shunde GUANYUDA Power Supply Co., Ltd.
●	ADAPTER 2	M/N:	FSP060-DAAN3
		Manufacturer:	FSP Group Inc.
●	ADAPTER 3	M/N:	FSP120-AAAN3
		Manufacturer:	FSP Group Inc.

3.12 Modifications

No modifications were implemented to meet testing criteria.

4 TEST ENVIRONMENT

4.1 Address of the test laboratory

Shenzhen Most Technology Service Co., Ltd.

No.5, 2nd Langshan Road, North District, Hi-tech Industrial Park, Nanshan, Shenzhen, Guangdong, China.
The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.4:2014 and CISPR 16-1-4:2010 SVSWR requirement for radiated emission above 1GHz.

Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 0031192610

Shenzhen Most Technology Service Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

A2LA-Lab Cert. No.: 6343.01

Shenzhen Most Technology Service Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

4.2 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Radiated Emission:

Temperature:	23 ° C
Humidity:	48 %
Atmospheric pressure:	950-1050mbar

AC Main Conducted testing:

Temperature:	24 ° C
Humidity:	45 %
Atmospheric pressure:	950-1050mbar

Conducted testing:

Temperature:	24 ° C
Humidity:	45 %
Atmospheric pressure:	950-1050mbar

4.3 Summary of measurement results

Test Specification clause	Test case	Test Mode	Test Channel	Recorded In Report		Test result
§15.247(a)(1)	Carrier Frequency separation	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Middle ☒ Highest	GFSK Π/4DQPSK 8DPSK	☒ Middle	Compliant
§15.247(a)(1)	Number of Hopping channels	GFSK Π/4DQPSK 8DPSK	☒ Full	GFSK 8DPSK	☒ Full	Compliant
§15.247(a)(1)	Time of Occupancy (dwell time)	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Middle ☒ Highest	GFSK Π/4DQPSK 8DPSK	☒ Middle	Compliant
§15.247(a)(1)	Spectrum bandwidth of aFHSS system 20dB bandwidth	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Middle ☒ Highest	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Middle ☒ Highest	Compliant
§15.247(b)(1)	Maximum output power	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Middle ☒ Highest	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Middle ☒ Highest	Compliant
§15.247(d)	Band edge compliance conducted	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Highest	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Highest	Compliant
§15.205	Band edge compliance radiated	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Highest	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Highest	Compliant
§15.247(d)	TX spurious emissions conducted	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Middle ☒ Highest	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Middle ☒ Highest	Compliant
§15.247(d)	TX spurious emissions radiated	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Middle ☒ Highest	GFSK	☒ Lowest ☒ Middle ☒ Highest	Compliant
§15.209(a)	TX spurious Emissions radiated Below 1GHz	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Middle ☒ Highest	GFSK	☒ Middle	Compliant
§15.107(a) §15.207	Conducted Emissions 9KHz-30 MHz	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Middle ☒ Highest	GFSK	☒ Middle	N/A

Remark:

1. The measurement uncertainty is not included in the test result.
2. We tested all test mode and recorded worst case in report

4.4 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen Most Technology Service Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen Most Technology Service Co., Ltd. is reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	4.10 dB	(1)
Radiated Emission	1~18GHz	4.32 dB	(1)
Radiated Emission	18-40GHz	5.54 dB	(1)
Conducted Disturbance	0.15~30MHz	3.12 dB	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

4.5 Equipments Used during the Test


Item	Equipment	Manufacturer	Model No.	Serial No.	Firmware versions	Last Cal.	Cal. Interval
1.	L.I.S.N.	R&S	ENV216	100093	/	2023/03/17	1 Year
2	Three-phase artificial power network	Schwarzback Mess	NNLK8129	8129178	/	2023/03/17	1 Year
3.	Receiver	R&S	ESCI	100492	V3.0-10-2	2023/03/17	1 Year
4	Receiver	R&S	ESPI	101202	V3.0-10-2	2023/03/17	1 Year
5	Spectrum analyzer	Agilent	9020A	MT-E306	A14.16	2023/03/17	1 Year
6	Bilog Antenna	Sunol Sciences	JB3	A121206	/	2023/03/17	1 Year
7	Horn antenna	HF Antenna	HF Antenna	MT-E158	/	2023/03/17	1 Year
8	Loop antenna	Beijing Daze	ZN30900B	/	/	2023/03/17	1 Year
9	Horn antenna	R&S	OBH100400	26999002	/	2023/03/17	1 Year
10	Wireless Communication Test Set	R&S	CMW500	/	CMW-BASE-3.7.21	2023/03/17	1 Year
11	Spectrum analyzer	R&S	FSP	100019	V4.40 SP2	2023/03/17	1 Year
12	High gain antenna	Schwarzbeck	LB-180400KF	MT-E389	/	2023/03/17	1 Year
13	Preamplifier	Schwarzbeck	BBV 9743	MT-E390	/	2023/03/17	1 Year
14	Pre-amplifier	EMCI	EMC051845S E	MT-E391	/	2023/03/17	1 Year
15	Pre-amplifier	Agilent	83051A	MT-E392	/	2023/03/17	1 Year
16	High pass filter unit	Tonscend	JS0806-F	MT-E393	/	2023/03/17	1 Year
17	RF Cable(below1GHz)	Times	9kHz-1GHz	MT-E394	/	2023/03/17	1 Year
18	RF Cable(above 1GHz)	Times	1-40G	MT-E395	/	2023/03/17	1 Year
19	RF Cable (9KHz-40GHz)	Tonscend	170660	N/A	/	2023/03/17	1 Year

Note: The Cal.Interval was one year.

5 TEST CONDITIONS AND RESULTS

5.1 AC Power Conducted Emission

TEST CONFIGURATION



TEST PROCEDURE

- 1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10-2013.
- 2 Support equipment, if needed, was placed as per ANSI C63.10-2013
- 3 All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10-2013
- 4 The EUT received DC 12V power from adapter, the adapter received AC120V/60Hz and AC 240V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5 All support equipments received AC power from a second LISN, if any.
- 6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8 During the above scans, the emissions were maximized by cable manipulation.

AC Power Conducted Emission Limit

For intentional device, according to § 15.207(a) AC Power Conducted Emission Limits is as following :


Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50


* Decreases with the logarithm of the frequency.

TEST RESULTS

Remark:

1. GFSK, $\pi/4$ DQPSK and 8DPSK modes were test at Low, Middle, and High channel; only the worst result of GFSK Middle Channel was reported as below:
2. Remark: Result=Reading value+Factor,and Margin=Limit- Result
3. GM60-240250-F, FSP060-DAAN3, FSP120-AAAN3 three adapters have been tested, and only the worst adapter(GM60-240250-F) test data is shown





Power supply:


DC 24V (by Adapter)

Polarization

L

M/N:


HK9600(second display: VFD)



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.1590	48.36	9.60	57.96	65.52	-7.56	QP	
2		0.1740	29.84	9.61	39.45	54.77	-15.32	AVG	
3		0.2740	29.17	9.60	38.77	51.00	-12.23	AVG	
4		0.2760	39.92	9.59	49.51	60.94	-11.43	QP	
5		0.5460	36.55	9.59	46.14	56.00	-9.86	QP	
6		0.5460	26.21	9.59	35.80	46.00	-10.20	AVG	
7		1.5220	17.61	9.60	27.21	46.00	-18.79	AVG	
8		1.6180	30.26	9.60	39.86	56.00	-16.14	QP	
9		4.0060	29.66	9.62	39.28	56.00	-16.72	QP	
10		4.3100	16.62	9.62	26.24	46.00	-19.76	AVG	
11		9.9220	24.39	9.69	34.08	50.00	-15.92	AVG	
12		9.9740	36.54	9.69	46.23	60.00	-13.77	QP	

*:Maximum data x:Over limit !:over margin

Power supply:	DC 24V (by Adapter)	Polarization	N
M/N:	HK9600(second display: VFD)		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1820	30.36	9.61	39.97	54.39	-14.42	AVG	
2	*	0.1980	45.58	9.60	55.18	63.69	-8.51	QP	
3		0.2803	26.96	9.59	36.55	50.81	-14.26	AVG	
4		0.2980	39.32	9.59	48.91	60.30	-11.39	QP	
5		0.5500	25.20	9.59	34.79	46.00	-11.21	AVG	
6		0.5540	35.04	9.59	44.63	56.00	-11.37	QP	
7		0.7980	20.82	9.60	30.42	46.00	-15.58	AVG	
8		0.8460	31.94	9.60	41.54	56.00	-14.46	QP	
9		1.7140	28.91	9.60	38.51	56.00	-17.49	QP	
10		1.7260	17.05	9.60	26.65	46.00	-19.35	AVG	
11		9.8540	24.92	9.69	34.61	50.00	-15.39	AVG	
12		10.2420	36.67	9.69	46.36	60.00	-13.64	QP	

*:Maximum data x:Over limit !:over margin


5.2 Radiated Emission

TEST CONFIGURATION


Frequency range 9 KHz – 30MHz



Frequency range 30MHz – 1000MHz



Frequency range above 1GHz-25GHz



TEST PROCEDURE

1. The EUT was placed on a turn table which is 0.8m above ground plane when testing frequency range 9 KHz –1GHz;the EUT was placed on a turn table which is 1.5m above ground plane when testing frequency range 1GHz – 25GHz.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.
5. Radiated emission test frequency band from 9KHz to 25GHz.
6. The distance between test antenna and EUT as following table states:

Test Frequency range	Test Antenna Type	Test Distance
9KHz-30MHz	Active Loop Antenna	3
30MHz-1GHz	Ultra-Broadband Antenna	3
1GHz-18GHz	Double Ridged Horn Antenna	3
18GHz-25GHz	Horn Antenna	1

7. Setting test receiver/spectrum as following table states:

Test Frequency range	Test Receiver/Spectrum Setting	Detector
9KHz-150KHz	RBW=200Hz/VBW=3KHz,Sweep time=Auto	QP
150KHz-30MHz	RBW=9KHz/VBW=100KHz,Sweep time=Auto	QP
30MHz-1GHz	RBW=120KHz/VBW=1000KHz,Sweep time=Auto	QP
1GHz-40GHz	Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto	Peak

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

$$\text{Transd}=AF +CL-AG$$

RADIATION LIMIT

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emission from intentional radiators at a distance of 3 meters shall not exceed the following table. According to § 15.247(d), in any 100kHz bandwidth outside the frequency band in which the EUT is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of desired power.

The pre-test have done for the EUT in three axes and found the worst emission at position shown in test setup photos.

Frequency (MHz)	Distance (Meters)	Radiated (dBμV/m)	Radiated (μV/m)
0.009-0.49	3	$20\log(2400/F(\text{KHz}))+40\log(300/3)$	$2400/F(\text{KHz})$
0.49-1.705	3	$20\log(24000/F(\text{KHz}))+40\log(30/3)$	$24000/F(\text{KHz})$
1.705-30	3	$20\log(30)+40\log(30/3)$	30
30-88	3	40.0	100

88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

TEST RESULTS


Remark:

1. This test was performed with EUT in X, Y, Z position and the worse case was found when EUT in X position.
2. We measured Radiated Emission at GFSK, $\pi/4$ DQPSK and 8DPSK mode from 9 KHz to 25GHz and recorded worst case at 8DPSK 3DH5 mode.
3. For below 1GHz testing recorded worst at 8DPSK 3DH5 middle channel.
4. Radiated emission test from 9 KHz to 10th harmonic of fundamental was verified, and no emission found except system noise floor in 9 KHz to 30MHz and not recorded in this report.
5. Remark: Result=Reading value+Factor
6. GM60-240250-F, FSP060-DAAN3, FSP120-AAAN3 three adapters have been tested, and only the worst adapter(GM60-240250-F) test data is shown

For 30MHz-1GHz


Horizontal

HK9600(second display: 10.1 inch)




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		63.5356	12.04	8.85	20.89	40.00	-19.11	QP	200	26
2		128.1130	4.05	16.08	20.13	43.50	-23.37	QP	200	84
3		216.7828	10.69	14.73	25.42	46.00	-20.58	QP	200	135
4		298.2681	16.98	15.44	32.42	46.00	-13.58	QP	200	199
5		497.6765	10.83	22.58	33.41	46.00	-12.59	QP	200	250
6	*	929.0082	8.47	29.29	37.76	46.00	-8.24	QP	200	304

*:Maximum data x:Over limit !:over margin




Horizontal
HK9600(second display: VFD)



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Antenna Height cm	Table Degree	Comment
1		31.7312	5.58	19.72	25.30	40.00	-14.70	QP	200	34	
2		63.0916	8.45	8.82	17.27	40.00	-22.73	QP	200	89	
3		167.8242	7.77	17.04	24.81	43.50	-18.69	QP	200	152	
4		298.2681	19.45	15.44	34.89	46.00	-11.11	QP	200	196	
5		601.4265	13.73	23.82	37.55	46.00	-8.45	QP	200	237	
6	*	893.8566	10.49	28.93	39.42	46.00	-6.58	QP	200	286	

*:Maximum data x:Over limit !:over margin

Vertical
HK9600(second display: VFD)



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	Comment
			dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1		41.5670	18.29	12.77	31.06	40.00	-8.94	QP	100	23
2	*	64.6594	25.13	8.93	34.06	40.00	-5.94	QP	100	78
3		90.2205	20.40	9.98	30.38	43.50	-13.12	QP	100	125
4		161.4742	12.15	17.25	29.40	43.50	-14.10	QP	100	186
5		298.2681	10.77	15.44	26.21	46.00	-19.79	QP	100	237
6		489.0269	13.94	22.12	36.06	46.00	-9.94	QP	100	302

*:Maximum data x:Over limit !:over margin

For 1GHz to 25GHz

Note: GFSK, Pi/4 DQPSK and 8DPSK all have been tested, only worse case 8DPSK is reported.

8DPSK (above 1GHz)

Frequency(MHz):			2402		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4804	57.07	PK	74	16.93	55.17	31.42	6.98	36.5	1.9
4804	45.63	AV	54	8.37	43.73	31.42	6.98	36.5	1.9
7206	52.59	PK	74	21.41	41.99	37.03	8.87	35.3	10.6
7206	42.86	AV	54	11.14	32.26	37.03	8.87	35.3	10.6

Frequency(MHz):			2402		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4804	56.29	PK	74	17.71	54.39	31.42	6.98	36.5	1.9
4804	46.38	AV	54	7.62	44.48	31.42	6.98	36.5	1.9
7206	52.97	PK	74	21.03	42.37	37.03	8.87	35.3	10.6
7206	43.06	AV	54	10.94	32.46	37.03	8.87	35.3	10.6

Frequency(MHz):			2441		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4882	56.97	PK	74	17.03	54.91	30.98	7.58	36.5	2.06
4882	43.97	AV	54	10.03	41.91	30.98	7.58	36.5	2.06
7323	55.89	PK	74	18.11	44.97	37.66	8.56	35.3	10.92
7323	42.35	AV	54	11.65	31.43	37.66	8.56	35.3	10.92

Frequency(MHz):			2441		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4882	57.42	PK	74	16.58	55.36	30.98	7.58	36.5	2.06
4882	45.85	AV	54	8.15	43.79	30.98	7.58	36.5	2.06
7323	53.85	PK	74	20.15	42.93	37.66	8.56	35.3	10.92
7323	43.04	AV	54	10.96	32.12	37.66	8.56	35.3	10.92

Frequency(MHz):			2480		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4960	57.21	PK	74	16.79	54.14	31.47	7.8	36.2	3.07
4960	44.74	AV	54	9.26	41.67	31.47	7.8	36.2	3.07
7440	54.27	PK	74	19.73	42.53	38.32	8.72	35.3	11.74
7440	42.77	PK	54	11.23	31.03	38.32	8.72	35.3	11.74

Frequency(MHz):			2480		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4960	56.84	PK	74	17.16	53.77	31.47	7.8	36.2	3.07
4960	43.42	AV	54	10.58	40.35	31.47	7.8	36.2	3.07
7440	54.75	PK	74	19.25	43.01	38.32	8.72	35.3	11.74
7440	43.29	PK	54	10.71	31.55	38.32	8.72	35.3	11.74

REMARKS:

1. Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)- Pre-amplifier
3. Margin value = Limit value- Emission level.
4. -- Mean the PK detector measured value is below average limit.
5. The other emission levels were very low against the limit.

Results of Band Edges Test (Radiated)

Note: GFSK, Pi/4 DQPSK and 8DPSK all have been tested, only worse case 8DPSK is reported.

8DPSK

Frequency(MHz):			2402		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2390	58.36	PK	74	15.64	63.77	27.49	3.32	36.22	-5.41
2390	42.42	AV	54	11.58	47.83	27.49	3.32	36.22	-5.41
Frequency(MHz):			2402		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2390	56.78	PK	74	17.22	62.19	27.49	3.32	36.22	-5.41
2390	39.27	AV	54	14.73	44.68	27.49	3.32	36.22	-5.41
Frequency(MHz):			2480		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2483.5	56.03	PK	74	17.97	61.54	27.45	3.38	36.34	-5.51
2483.5	39.65	AV	54	14.35	45.16	27.45	3.38	36.34	-5.51
Frequency(MHz):			2480		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2483.5	55.98	PK	74	18.02	61.49	27.45	3.38	36.34	-5.51
2483.5	41.87	AV	54	12.13	47.38	27.45	3.38	36.34	-5.51

REMARKS:

1. Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)- Pre-amplifier
3. Margin value = Limit value- Emission level.
4. -- Mean the PK detector measured value is below average limit.

5.3 Maximum Peak Output Power


Limit

The Maximum Peak Output Power Measurement is 125mW (20.97).

Test Procedure

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the powersensor.

Test Configuration



Test Results

See Appendix I

5.4 20dB Bandwidth

Limit


For frequency hopping systems operating in the 2400MHz-2483.5MHz no limit for 20dB bandwidth.

Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30 KHz RBW and 100 KHz VBW.

The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

Test Configuration



Test Results

See Appendix III

5.5 Frequency Separation


LIMIT

According to 15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by minimum of 25KHz or the $2/3 \times 20\text{dB}$ bandwidth of the hopping channel, whichever is greater.

TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 KHz RBW and 300 KHz VBW.

TEST CONFIGURATION



TEST RESULTS

See Appendix IV

5.6 Number of hopping frequency


Limit

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels.

Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. Set spectrum analyzer start 2400MHz to 2483.5MHz with 100 KHz RBW and 300 KHz VBW.

Test Configuration



Test Results

See Appendix VIII

5.7 Time of Occupancy (Dwell Time)


Limit

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. Set center frequency of spectrum analyzer=operating frequency with 1MHz RBW and 1MHz VBW, Span 0Hz.

Test Configuration




Test Results

See Appendix VII

5.8 Spurious RF Conducted Emission

TEST CONFIGURATION



TEST PROCEDURE

The Spurious RF conducted emissions compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW=100kHz and VBW= 300KHz to measure the peak field strength, and measure frequency range from 9KHz to 25GHz.

LIMIT

1. Below -20dB of the highest emission level in operating band.
2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

Test Results

See Appendix V

5.9 Pseudorandom Frequency Hopping Sequence

TEST APPLICABLE


For 47 CFR Part 15C section 15.247 (a) (1) requirement:

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hop-ping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hop-ping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

EUT Pseudorandom Frequency Hopping Sequence Requirement


The pseudorandom frequency hopping sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first one of 9 consecutive ones, for example: the shift register is initialized with nine ones.

- Number of shift register stages:9
- Length of pseudo-random sequence:29-1=511 bits
- Longest sequence of zeros:8(non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of pseudorandom frequency hopping sequence as follows:



Each frequency used equally one the average by each transmitter.

The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitter and shift frequencies in synchronization with the transmitted signals.

5.10 Antenna Requirement

Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (c), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

Refer to statement below for compliance

The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

Antenna Connected Construction


The directional gains of antenna used for transmitting is 1.8dBi, and the antenna is a FPC Antenna connect to PCB board and no consideration of replacement. Please see EUT photo for details.

Results: Compliance.

6 Test Setup Photos of the EUT


(HK9600(second display: 10.1 inch))





(HK9600(second display: VFD))





7 Photos of the EUT

See photo report

APPENDIX I. Conducted Peak Output Power

Test Result


Modulation	Packet Type	Channel	Peak Output Power (dBm)	Peak Output Power (mW)	Max. Avg. Power (dBm)	Limit (dBm)	Result
GFSK	DH5	0	1.505	1.414	None	30	PASS
		39	2.106	1.624	None		PASS
		78	3.175	2.077	None		PASS
$\pi/4$ DQPSK	2-DH5	0	2.460	1.762	None	20.97	PASS
		39	2.972	1.982	None		PASS
		78	3.972	2.496	None		PASS
8DPSK	3-DH5	0	2.759	1.888	None		PASS
		39	3.285	2.131	None		PASS
		78	4.338	2.715	None		PASS

APPENDIX II.99% Bandwidth

Test Result


Modulation	Channel	99% BW (MHz)
GFSK	0	0.85509
	39	0.84621
	78	0.84832
π /4DQPSK	0	1.1806
	39	1.1818
	78	1.1795
8DPSK	0	1.1888
	39	1.1954
	78	1.2036

Test Graphs






GFSK_DH5_Channel 39

 $\pi/4$ DQPSK_2-DH5_Channel 39


GFSK_DH5_Channel 78

 $\pi/4$ DQPSK_2-DH5_Channel 78

8DPSK_3-DH5_Channel 0



8DPSK_3-DH5_Channel 39



Void

8DPSK_3-DH5_Channel 78


APPENDIX III.20dB Bandwidth

Test Result


Modulation	Channel	Center Frequency (MHz)	20 dB Bandwidth (MHz)
GFSK	0	2402 MHz	0.9504
	39	2441 MHz	0.9480
	78	2480 MHz	0.9488
$\pi/4$ DQPSK	0	2402 MHz	1.299
	39	2441 MHz	1.303
	78	2480 MHz	1.303
8DPSK	0	2402 MHz	1.292
	39	2441 MHz	1.297
	78	2480 MHz	1.295

Test Graphs







$\pi/4$ DQPSK_2-DH5_Channel 39



$\pi/4$ DQPSK_2-DH5_Channel 78



8DPSK_3-DH5_Channel 0



8DPSK_3-DH5_Channel 39



8DPSK_3-DH5_Channel 78


Void

APPENDIX IV. Carrier Frequencies Separation

Test Result

Modulation	Packet	Left Center frequency (MHz)	Right Center frequency (MHz)	Hopping Frequency Separation (MHz)	Limit (MHz)	Result
GFSK	DH5	2439.9406	2441.2649	1.3243	0.634	PASS
GFSK	DH5	2440.252	2441.2643	1.0123	0.632	PASS
GFSK	DH5	2439.9364	2440.9391	1.0027	0.633	PASS
$\pi/4$ DQPSK	2-DH5	2440.09	2441.2493	1.1593	0.866	PASS
$\pi/4$ DQPSK	2-DH5	2439.943	2440.9394	0.9964	0.869	PASS
$\pi/4$ DQPSK	2-DH5	2440.2499	2441.1575	0.9076	0.869	PASS
8DPSK	3-DH5	2439.9301	2440.9508	1.0207	0.861	PASS
8DPSK	3-DH5	2439.9406	2440.9442	1.0036	0.865	PASS
8DPSK	3-DH5	2439.937	2440.94	1.0030	0.863	PASS

Test Graphs





$\pi/4$ DQPSK



$\pi/4$ DQPSK



8DPSK



8DPSK



8DPSK

Void

APPENDIX V. Conducted Out Of Band Emission

Test Result

Non-Hopping


Modulation	Packet	Channel	OOB Emission Frequency (MHz)	OOB Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result
GFSK	DH5	0	2400.00	-49.481	-18.56	-30.921	PASS
			2399.00	-36.044	-18.56	-17.484	PASS
			2498.30	-44.040	-18.56	-25.480	PASS
		39	4882.42	-44.487	-18.14	-26.347	PASS
		78	2483.50	-38.259	-16.9	-21	PASS
			4960.45	-41.112	-16.9	-24.212	PASS
$\pi/4$ DQPSK	2-DH5	0	2400.00	-48.882	-18.66	-30.222	PASS
			2398.94	-36.429	-18.66	-17.769	PASS
			24968.2	-46.142	-18.66	-27.482	PASS
		39	4879.30	-45.301	-17.96	-27.341	PASS
		78	2483.50	-38.766	-16.88	-22	PASS
			9914.62	-44.187	-16.88	-27.307	PASS
8DPSK	3-DH5	0	2400.00	-47.839	-18.53	-29.309	PASS
			2398.94	-37.368	-18.53	-18.838	PASS
			24991.3	-47.036	-18.53	-28.506	PASS
		39	2537.05	-46.659	-18.06	-28.599	PASS
		78	2483.50	-38.579	-17.17	-21	PASS
			4959.83	-43.705	-17.17	-26.535	PASS


Hopping

Modulation	Packet	Channel	OOB Emission Frequency (MHz)	OOB Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result
GFSK	DH5	Hopping	2398.96	-36.446	-18.57	-17.876	PASS
			2400.00	-36.540	-18.57	-17.970	PASS
			2483.50	-38.969	-17.13	-21.839	PASS
			2400.00	-36.887	-18.51	-18.377	PASS
			2483.50	-38.697	-16.87	-21.827	PASS
			2400.00	-36.528	-18.57	-17.958	PASS
			2483.50	-37.517	-17.08	-20.437	PASS
			2398.95	-36.259	-18.55	-17.709	PASS
$\pi/4$ DQPSK	2-DH5	Hopping	2400.00	-39.018	-18.55	-20.468	PASS
			2483.50	-41.370	-16.92	-24.450	PASS


8DPSK	3-DH5	2398.94	-36.524	-18.61	-17.914	PASS
		2400.00	-39.179	-18.61	-20.569	PASS
		2483.50	-38.581	-17.11	-21.471	PASS
		2398.94	-37.495	-18.59	-18.905	PASS
		2400.00	-38.480	-18.59	-19.890	PASS
		2483.50	-38.261	-17.06	-21.201	PASS
		2398.69	-40.377	-18.56	-21.817	PASS
		2400.00	-40.487	-18.56	-21.927	PASS
		2483.50	-40.711	-17.06	-23.651	PASS
		2398.96	-36.630	-18.55	-18.080	PASS
		2400.00	-41.779	-18.55	-23.229	PASS
		2483.50	-40.791	-16.96	-23.831	PASS
8DPSK	3-DH5	2398.94	-37.182	-18.58	-18.602	PASS
		2400.00	-41.107	-18.58	-22.527	PASS
		2483.50	-41.942	-17.28	-24.662	PASS

Test Graphs







Out Of Band Emission
GFSK_DH5_Channel 39




Out Of Band Emission
 $\pi/4$ DQPSK_2-DH5_Channel 39




Spurious Emissions
GFSK_DH5_Channel 39




Spurious Emissions
 $\pi/4$ DQPSK_2-DH5_Channel 39




Out Of Band Emission
GFSK_DH5_Channel 78




Out Of Band Emission
 $\pi/4$ DQPSK_2-DH5_Channel 78




Spurious Emission
GFSK_DH5_Channel 78




Spurious Emission
 $\pi/4$ DQPSK_2-DH5_Channel 78




Out Of Band Emission
8DPSK_3-DH5_Channel 0



Spurious Emission
8DPSK_3-DH5_Channel 0




Out Of Band Emission
8DPSK_3-DH5_Channel 39



Spurious Emissions
8DPSK_3-DH5_Channel 39



Out Of Band Emission
8DPSK_3-DH5_Channel 78



Spurious Emission
8DPSK_3-DH5_Channel 78



Out Of Band Emission(Left)
GFSK_DH5_Channel Hopping




Out Of Band Emission(Left)
 $\pi/4$ DQPSK_2-DH5_Channel Hopping



Out Of Band Emission(Right)
GFSK_DH5_Channel Hopping



Out Of Band Emission(Right)
 $\pi/4$ DQPSK_2-DH5_Channel Hopping



Out Of Band Emission(Left)
GFSK_DH5_Channel Hopping




Out Of Band Emission(Left)
 $\pi/4$ DQPSK_2-DH5_Channel Hopping



Out Of Band Emission(Right)
GFSK_DH5_Channel Hopping



Out Of Band Emission(Right)
 $\pi/4$ DQPSK_2-DH5_Channel Hopping



Out Of Band Emission(Left)
GFSK_DH5_Channel Hopping



Out Of Band Emission(Left)
 $\pi/4$ DQPSK_2-DH5_Channel Hopping



Out Of Band Emission(Right)
GFSK_DH5_Channel Hopping




Out Of Band Emission(Right)
 $\pi/4$ DQPSK_2-DH5_Channel Hopping



Out Of Band Emission(Left)
8DPSK_3-DH5_Channel Hopping



Out Of Band Emission(Right)
8DPSK_3-DH5_Channel Hopping



Out Of Band Emission(Left)
8DPSK_3-DH5_Channel Hopping



Out Of Band Emission(Right)
8DPSK_3-DH5_Channel Hopping



Out Of Band Emission(Left)
8DPSK_3-DH5_Channel Hopping




Out Of Band Emission(Right)
8DPSK_3-DH5_Channel Hopping


APPENDIX VI.Duty Cycle

Test Result


Modulation	Packets	Channel	On Time (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle (linear)	Duty Cycle Factor (dB)
GFSK	DH5	0	2.879	3.745	76.88	0.7688	1.1419
		39	2.879	3.745	76.88	0.7688	1.1419
		78	2.879	3.735	77.09	0.7709	1.13
π /4DQPSK	2-DH5	0	2.879	3.735	77.09	0.7709	1.13
		39	2.889	3.745	77.15	0.7715	1.1266
		78	2.879	3.735	77.09	0.7709	1.13
8DPSK	3-DH5	0	2.889	3.745	77.15	0.7715	1.1266
		39	2.879	3.735	77.09	0.7709	1.13
		78	2.879	3.735	77.09	0.7709	1.13

Test Graphs







GFSK(DH5)_Channel 39




GFSK(DH5)_Channel 78




π/4DQPSK(2-DH5)_Channel 0




π/4DQPSK(2-DH5)_Channel 39




π/4DQPSK(2-DH5)_Channel 78



8DPSK(3-DH5)_Channel 0



8DPSK(3-DH5)_Channel 39




8DPSK(3-DH5)_Channel 78


APPENDIX VII.Dwell Time

Test Result


Modulation	Packet	Channel	Pulse Width (ms)	Number of Pulses in 31.6 seconds	Dwell Time (ms)	Limit (ms)	Result
GFSK	DH5	CH0 (2402MHz)	2.880	96	276.48	< 400	PASS
	DH5	CH39 (2441MHz)	2.880	100	288.0		PASS
	DH5	CH78 (2480MHz)	2.880	108	311.04		PASS
π /4DQPSK	2-DH5	CH0 (2402MHz)	2.880	98	282.24		PASS
	2-DH5	CH39 (2441MHz)	2.880	120	345.6		PASS
	2-DH5	CH78 (2480MHz)	2.896	108	312.77		PASS
8DPSK	3-DH5	CH0 (2402MHz)	2.880	86	247.68		PASS
	3-DH5	CH39 (2441MHz)	2.896	95	275.12		PASS
	3-DH5	CH78 (2480MHz)	2.880	109	313.92		PASS

Test Graphs







Pulse Width
GFSK_DH5




Number of Pulses in 31.6 seconds
GFSK_DH5




Pulse Width
GFSK_DH5




Number of Pulses in 31.6 seconds
GFSK_DH5




Pulse Width
 $\pi/4$ DQPSK_2-DH5




Number of Pulses in 31.6 seconds
 $\pi/4$ DQPSK_2-DH5




Pulse Width
 $\pi/4$ DQPSK_2-DH5




Number of Pulses in 31.6 seconds
 $\pi/4$ DQPSK_2-DH5




Pulse Width
 $\pi/4$ DQPSK_2-DH5




Number of Pulses in 31.6 seconds
 $\pi/4$ DQPSK_2-DH5




Pulse Width
8DPSK_3-DH5




Number of Pulses in 31.6 seconds
8DPSK_3-DH5




Pulse Width
8DPSK_3-DH5



Number of Pulses in 31.6 seconds
8DPSK_3-DH5



Pulse Width
8DPSK_3-DH5




Number of Pulses in 31.6 seconds
8DPSK_3-DH5


APPENDIX VIII. Number Of Hopping Channel

Test Result


Modulation	Packet	Number of Hopping Channel	Limit	Result
GFSK	DH5	79	15	PASS
GFSK	DH5	79	15	PASS
GFSK	DH5	79	15	PASS
$\pi/4$ DQPSK	2-DH5	79	15	PASS
$\pi/4$ DQPSK	2-DH5	79	15	PASS
$\pi/4$ DQPSK	2-DH5	79	15	PASS
8DPSK	3-DH5	79	15	PASS
8DPSK	3-DH5	79	15	PASS
8DPSK	3-DH5	79	15	PASS

Test Graphs







Hopping Plot
 $\pi/4$ DQPSK




Hopping Plot
 $\pi/4$ DQPSK



Hopping Plot
8DPSK



Hopping Plot
8DPSK



Hopping Plot
8DPSK

