



Report No.: FCC 1908024 File Reference No.: 2019-08-22

Applicant: Quanzhou Fengtai Electronics Co., Ltd.

Product: Solar Bluetooth Light & Speaker

Model No.: DY20190708-07A, DY20190708-01A, DY20190708-02A,

DY20190708-03A, DY20190708-04A, DY20190708-05A,

DY20190708-06A, DY20190708-08A

Trademark: N/A

Test Standards: FCC Part 15.247

Test Result:

It is herewith confirmed and found to comply with the

requirements set up by ANSI C63.10, FCC Part 15.247 for

the evaluation of electromagnetic compatibility

Approved By

Jack Chung

Jack Chung

Manager

Dated: August 22, 2019

Results appearing herein relate only to the sample tested

The technical reports is issued errors and omissions exempt

The technical reports is issued errors and omissions exempt and is subject to withdrawal at

SHENZHEN TIMEWAY TESTING LABORATORIES

Zone C, 1st Floor, Block B, Jun Xiang Da Building, Zhongshan Park Road West, Tong Le Village, Nanshan District, Shenzhen, China

Tel (755) 83448688, Fax (755) 83442996, E-Mail:info@timeway-lab.com

Report No.: FCC1908024

Date: 2019-08-22



Special Statement:

The testing quality ability of our laboratory meet with "Quality Law of People's Republic of China" Clause 19.

Page 2 of 105

The testing quality system of our laboratory meet with ISO/IEC-17025 requirements, which is approved by CNAS. This approval result is accepted by MRA of APLAC.

Our test facility is recognized, certified, or accredited by the following organizations:

CNAS-LAB Code: L2292

The EMC Laboratory has been assessed and in compliance with CNAS-CL01 accreditation criteria for testing Laboratories (identical to ISO/IEC 17025:2005 General Requirements) for the Competence of testing Laboratories.

FCC-Registration No.: 744189

The EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 744189.

Industry Canada (IC) — **Registration No.:5205A**

The EMC Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 5205A.

A2LA (Certification Number: 5013.01)

The EMC Laboratory has been accredited by the American Association for Laboratory Accreditation (A2LA). Certification Number:5013.01

Page 3 of 105

Report No.: FCC1908024

Date: 2019-08-22



Test Report Conclusion

Content

1.0	General Details	4
1.1	Test Lab Details	4
1.2	Applicant Details	4
1.3	Description of EUT	4
1.4	Submitted Sample	4
1.5	Test Duration.	5
1.6	Test Uncertainty.	5
1.7	Test By	5
2.0	List of Measurement Equipment	6
3.0	Technical Details	7
3.1	Summary of Test Results	7
3.2	Test Standards	7
4.0	EUT Modification.	7
5.0	Power Line Conducted Emission Test.	8
5.1	Schematics of the Test.	8
5.2	Test Method and Test Procedure	8
5.3	Configuration of the EUT	8
5.4	EUT Operating Condition.	9
5.5	Conducted Emission Limit.	9
5.6	Test Result.	9
6.0	Radiated Emission test	12
6.1	Test Method and Test Procedure	12
6.2	Configuration of the EUT	12
6.3	EUT Operation Condition.	12
6.4	Radiated Emission Limit	13
7.0	20dB Bandwidth	25
8.0	Maximum Output Power	37
9.0	Carrier Frequency Separation.	40
10.0	Number of Hopping Channel	44
11.0	Time of Occupancy (Dwell Time)	48
12.0	Out of Band Measurement.	55
13.0	Antenna Requirement	72
14.0	FCC ID Label	73
15.0	Photo of Test Setup and EUT View.	74

Report No.: FCC1908024

Date: 2019-08-22



Page 4 of 105

1.0 General Details

1.1 Test Lab Details

Name: SHENZHEN TIMEWAY TESTING LABORATORIES.

Address: Zone C, 1st Floor, Block B, Jun Xiang Da Building, Zhongshan Park Road West, Tong Le

Village, Nanshan District, Shenzhen, China

Telephone: (755) 83448688 Fax: (755) 83442996

Site Listed with Federal Communications commission (FCC)

Registration Number: 744189 For 3m Anechoic Chamber

Site Listed with Industry Canada of Ottawa, Canada

Registration Number: IC: 5205A

For 3m Anechoic Chamber

1.2 Applicant Details

Applicant: Quanzhou Fengtai Electronics Co., Ltd.

Address: No.5, Fengshun Road, Beifeng Industrial Area, Fengze District, Quanzhou, Fujian, China

Telephone: 86-595-22892957 Fax: 86-595-22892857

1.3 Description of EUT

Product: Solar Bluetooth Light & Speaker

Manufacturer: Quanzhou Fengtai Electronics Co., Ltd.

Address: No.5, Fengshun Road, Beifeng Industrial Area, Fengze District, Quanzhou, Fujian,

China

Brand Name: N/A

Model Number: DY20190708-07A

Additional Model Number: DY20190708-01A, DY20190708-02A, DY20190708-03A, DY20190708-04A,

DY20190708-05A, DY20190708-06A, DY20190708-08A

Type of Modulation GFSK, 月/4DQPSK, 8DPSK for Bluetooth

Frequency range 2402-2480MHz for Bluetooth

Channel Spacing 1MHz for Bluetooth

Frequency Selection By software

Channel Number 79 channel for Bluetooth

Antenna: PCB antenna used. The gain of the antennas is 0dBi Input: 5V, 1A, 5 W or built-in 3.7V, 2000mAh Li-ion battery

Power Supply: N/A

1.4 Submitted Sample: 1 Samples

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No.: FCC1908024 Page 5 of 105

Date: 2019-08-22



1.5 Test Duration 2019-08-05 to 2019-08-22

1.6 Test Uncertainty

Conducted Emissions Uncertainty = 3.6dB Radiated Emissions below 1GHz Uncertainty =4.7dB Radiated Emissions above 1GHz Uncertainty =6.0dB Conducted Power Uncertainty = 6.0dB Occupied Channel Bandwidth Uncertainty = 5%

1.7 Test Engineer

Terry Tang The sample tested by

Print Name: Terry Tang

Page 6 of 105

Report No.: FCC1908024

Date: 2019-08-22



2.0 Test Equipment					
Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
ESPI Test Receiver	R&S	ESPI 3	100379	2019-06-21	2020-06-20
TWO Line-V-NETW	R&S	EZH3-Z5	100294	2019-06-21	2020-06-20
TWO Line-V-NETW	R&S	EZH3-Z5	100253	2019-06-21	2020-06-20
Impuls-Begrenzer	R&S	ESH3-Z2	100281	2019-06-21	2020-06-20
Loop Antenna	EMCO	6507	00078608	2020-06-20	2020-06-20
Spectrum	R&S	FSIQ26	100292	2019-06-21	2020-06-20
Horn Antenna	A-INFO	LB-180400-KF	J211060660	2019-06-21	2020-06-20
Horn Antenna	R&S	BBHA 9120D	9120D-631	2018-07-09	2021-07-08
Power meter	Anritsu	ML2487A	6K00003613	2018-08-23 2019-08-22	2019-08-22 2020-08-21
Power sensor	Anritsu	MA2491A	32263	2019-08-22 2018-08-23 2019-08-22	2019-08-22 2020-08-21
Bilog Antenna	Schwarebeck	VULB9163	9163/340	2018-07-04	2021-07-03
9*6*6 Anechoic			N/A	2018-02-07	2021-02-06
EMI Test Receiver	RS	ESVB	826156/011	2019-06-21	2020-06-20
EMI Test Receiver	RS	ESH3	860904/006	2019-06-21	2020-06-20
Spectrum	HP/Agilent	ESA-L1500A	US37451154	2019-06-21	2020-06-20
Spectrum	HP/Agilent	E4407B	MY50441392	2019-06-21	2020-06-20
Spectrum	RS	FSP	1164.4391.38	2019-01-20	2020-01-19
RF Cable	Zhengdi	ZT26-NJ-NJ-8 M/FA		2019-06-21	2020-06-20
RF Cable	Zhengdi	7m		2019-06-21	2020-06-20
RF Switch	EM	EMSW18	060391	2019-06-21	2020-06-20
Pre-Amplifier	Schwarebeck	BBV9743	#218	2019-06-21	2020-06-20
Pre-Amplifier	HP/Agilent	8449B	3008A00160	2019-06-21	2020-06-20
LISN	SCHAFFNER	NNB42	00012	2019-01-08	2020-01-07

Report No.: FCC1908024 Page 7 of 105

Date: 2019-08-22



3.0 **Technical Details**

3.1 **Summary of test results**

The EUT has been tested according to the following specifications:

Requirement	CFR 47 Section	Result	Notes
Antenna Requirement	15.203, 15.247(b)(4)	PASS	Complies
Maximum Peak Out Power	15.247 (b)(1), (4)	PASS	Complies
Carrier Frequency Separation	15.247(a)(1)	PASS	Complies
20dB Channel Bandwidth	15.247 (a)(1)	PASS	Complies
Number of Hopping Channels	15.247(a)(iii), 15.247(b)(1)	PASS	Complies
Time of Occupancy (Dwell Time)	15.247(a)(iii)	PASS	Complies
Spurious Emission, Band Edge, and Restricted bands	15.247(d),15.205(a) , 15.209 (a)	PASS	Complies
Conducted Emissions	15.207(a)	PASS	Complies
RF Exposure	15.247(i), 1.1307(b)(1)	PASS	Complies

3.2 **Test Standards**

FCC Part 15 Subpart & Subpart C, Paragraph 15.247

4.0 **EUT Modification**

No modification by SHENZHEN TIMEWAY TESTING LABORATORIES.

Page 8 of 105


Report No.: FCC1908024

Date: 2019-08-22



5. Power Line Conducted Emission Test

5.1 Schematics of the test




EUT: Equipment Under Test

5.2 Test Method and test Procedure

The EUT was tested according to ANSI C63.10-2013. The Frequency spectrum From 0.15MHz to 30MHz was investigated. The LISN used was 50ohm/50uH as specified by section 5.1 of ANSI C63.10-2013.

Test Voltage: 120V~60Hz Block diagram of Test setup



5.3 Configuration of The EUT

The EUT was configured according to ANSI C63.10-2013. All interface ports were connected to the appropriate peripherals. All peripherals and cables are listed below.

Report No.: FCC1908024 Page 9 of 105

Date: 2019-08-22



A. EUT

Device	Manufacturer	Model	FCC ID
		DY20190708-07A,DY20190708-01A,	
Solar Bluetooth Light &	Quanzhou Fengtai	DY20190708-02A,DY20190708-03A,	2AUBZ-190708
Speaker	Electronics Co., Ltd.	DY20190708-04A,DY20190708-05A,	ZAUBZ-190/08
		DY20190708-06A, DY20190708-08A	

B. Internal Device

Device	Manufacturer	Model	Rating

C. Peripherals

Device	Manufacturer	Model	Rating
Power Supply	h.TV	S012BES0500200	Input: 100-240V~, 50/60Hz, 0.5A;
			Output: DC5V, 2A

5.4 EUT Operating Condition

Operating condition is according to ANSI C63.10-2013.

- A Setup the EUT and simulators as shown on follow
- B Enable AF signal and confirm EUT active to normal condition

5.5 Power line conducted Emission Limit according to Paragraph 15.107, 15.207

Frequency	Class A Lim	its (dB µ V)	Class B Limits (dB µ V)		
(MHz)	Quasi-peak Level	Average Level	Quasi-peak Level	Average Level	
$0.15 \sim 0.50$	79.0	66.0	66.0~56.0*	56.0~46.0*	
$0.50 \sim 5.00$	73.0	60.0	56.0	46.0	
5.00 ~ 30.00	73.0	60.0	60.0	50.0	

Notes:

- 1. *Decreasing linearly with logarithm of frequency.
- 2. The tighter limit shall apply at the transition frequencies

5.6 Test Results

The frequency spectrum from 0.15MHz to 30MHz was investigated. All reading are quasi-peak values with a resolution bandwidth of 9kHz.

The report refers only to the sample tested and does not apply to the bulk.

Report No.: FCC1908024

Date: 2019-08-22



Conducted Emission on Live Terminal (150kHz to 30MHz) A:

EUT Operating Environment


Humidity: 65%RH Atmospheric Pressure: 101 KPa Temperature: 26°C

EUT set Condition: Keep Bluetooth Transmitting

Equipment Level: Class B

Results: PASS

Please refer to following diagram for individual



No. Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		
	MHz	dBu∨	dB	dBu∀	dBu∀	dB	Detector	Comment
1	0.3716	32.30	9.76	42.06	58.47	-16.41	QP	
2	0.3716	25.50	9.76	35.26	48.47	-13.21	AVG	
3 *	0.4767	38.70	9.77	48.47	56.40	-7.93	QP	
4	0.4767	23.10	9.77	32.87	46.40	-13.53	AVG	
5	0.9530	30.30	9.79	40.09	56.00	-15.91	QP	
6	0.9530	5.40	9.79	15.19	46.00	-30.81	AVG	
7	1.8522	29.00	9.80	38.80	56.00	-17.20	QP	
8	1.8522	11.00	9.80	20.80	46.00	-25.20	AVG	

Report No.: FCC1908024

Date: 2019-08-22



B: Conducted Emission on Neutral Terminal (150kHz to 30MHz)

EUT Operating Environment


Humidity: 65%RH Atmospheric Pressure: 101 KPa Temperature: 26°C

EUT set Condition: Keep Bluetooth Transmitting

Equipment Level: Class B

Results: Pass

Please refer to following diagram for individual



No. N	No. Mk. Freq.		Reading Level	Correct Factor	Measure- ment	Limit	Over		
		MHz	dBu∀	dB	dBu∀	dBu∀	dB	Detector	Comment
1		0.3720	31.00	9.76	40.76	58.46	-17.70	QP	
2		0.3720	24.40	9.76	34.16	48.46	-14.30	AVG	
3 ,	ŧ	0.4796	37.80	9.77	47.57	56.35	-8.78	QP	
4		0.4796	25.00	9.77	34.77	46.35	-11.58	AVG	
5		0.7772	24.70	9.78	34.48	56.00	-21.52	QP	
6		0.7772	13.00	9.78	22.78	46.00	-23.22	AVG	

Report No.: FCC1908024 Page 12 of 105


Date: 2019-08-22



6 Radiated Emission Test

- 6.1 Test Method and test Procedure:
- (1) The EUT was tested according to ANSI C63.10-2013. The radiated test was performed at Timeway EMC Laboratory. This site is on file with the FCC laboratory division, Registration No. 744189
- (2) The EUT, peripherals were put on the turntable which table size is 1m x 1.5 m, table high 0.8 m. All set up is according to ANSI C63.10-2013.
- (3) The frequency spectrum from 30 MHz to 25GHz was investigated. All readings from 30 MHz to 1 GHz are quasi-peak values with a resolution bandwidth of 120 kHz. For measurement above 1GHz, peak values with RBW=VBW=1MHz and PK detector. AV value with RBW=1MHz, VBW=10Hz and PK detector. Measurements were made at 3 meters.
- (4) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
- (5) Maximizing procedure was performed on the six (6) highest emissions to ensure EUT compliance is with all installation combinations. All data was recorded in the peak detection mode. Quasi-peak readings was performed only when an emission was found to be marginal (within -4 dB of specification limit), and are distinguished with a "QP" in the data table.
- (6) The antenna polarization: Vertical polarization and Horizontal polarization.

Block diagram of Test setup



- 6.2 Configuration of The EUT

 Same as section 5.3 of this report
- 6.3 EUT Operating Condition
 Same as section 5.4 of this report.

The report refers only to the sample tested and does not apply to the bulk.

Report No.: FCC1908024 Page 13 of 105

Date: 2019-08-22



6.4 Radiated Emission Limit

All emission from a digital device, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strength specified below:

Frequencies in restricted band are complied to limit on Paragraph 15.209 and 15.109 and RSS-210

Frequency Range (MHz)	Distance (m)	Field strength (dB μ V/m)
30-88	3	40.0
88-216	3	43.5
216-960	3	46.0
Above 960	3	54.0

Note:

- 1. RF Voltage $(dBuV) = 20 \log RF \text{ Voltage } (uV)$
- 2. In the Above Table, the higher limit applies at the band edges.
- 3. Distance refers to the distance in meters between the measuring instrument antenna and the EUT
- 4. GFSK was the worse case because it has highest output power

Report No.: FCC1908024

Date: 2019-08-22



Page 14 of 105

Test result

General Radiated Emission Data and Harmonics Radiated Emission Data

Radiated Emission In Horizontal/Vertical (30MHz----1000MHz)

EUT set Condition: Keep Bluetooth Transmitting

Results: Pass


Page 15 of 105 Report No.: FCC1908024

Date: 2019-08-22



Test Figure:

H




No.	Frequen	Results	Factor	Limit	Over	Detector	Table (o)	Height	ANT	Verdict
	cy (MHz)	(dBuV/m	(dB)	(dBuV/m	Limit			(cm)		
))	(dB)					
1	107.338	21.59	-13.39	43.5	-21.91	Peak	43.00	100	Н	Pass
2	150.250	26.46	-17.02	43.5	-17.04	Peak	32.00	200	Н	Pass
3	230.982	22.03	-12.65	46.0	-23.97	Peak	253.00	100	Н	Pass

Page 16 of 105 Report No.: FCC1908024

Date: 2019-08-22



Test Figure:



No.	Frequen	Results	Factor	Limit	Over	Detector	Table (o)	Height	ANT	Verdict
	cy (MHz)	(dBuV/m	(dB)	(dBuV/m	Limit			(cm)		
))	(dB)					
1	108.065	25.74	-13.42	43.5	-17.76	Peak	290.00	100	V	Pass
2	151.462	27.11	-16.95	43.5	-16.39	Peak	295.00	100	V	Pass

Report No.: FCC1908024 Page 17 of 105

Date: 2019-08-22



Operation Mode: Transmitting under Low Channel (2402MHz)

	8	, ,	
Frequency (MHz)	Level@3m (dBμV/m)	Antenna Polarity	Limit@3m (dB \(\mu \)V/m)
4804		Н	74(Peak)/ 54(AV)
4804		V	74(Peak)/ 54(AV)
7206		H/V	74(Peak)/ 54(AV)
9608		H/V	74(Peak)/ 54(AV)
12010		H/V	74(Peak)/ 54(AV)
14412		H/V	74(Peak)/ 54(AV)
16814		H/V	74(Peak)/ 54(AV)
19216		H/V	74(Peak)/ 54(AV)
21618		H/V	74(Peak)/ 54(AV)
24020		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

2. Remark "---" means that the emissions level is too low to be measured

Operation Mode: Transmitting g under Middle Channel (2441MHz)

Frequency (MHz)	Level@3m (dB \u03ba V/m)	Antenna Polarity	Limit@3m (dB \u03b4 V/m)
4882	1	Н	74(Peak)/ 54(AV)
4882		V	74(Peak)/ 54(AV)
7323	-	H/V	74(Peak)/ 54(AV)
9764	-	H/V	74(Peak)/ 54(AV)
12205		H/V	74(Peak)/ 54(AV)
14646		H/V	74(Peak)/ 54(AV)
17087		H/V	74(Peak)/ 54(AV)
19528		H/V	74(Peak)/ 54(AV)
21969		H/V	74(Peak)/ 54(AV)
24410		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

2. Remark "---" means that the emissions level is too low to be measured

Report No.: FCC1908024 Page 18 of 105

Date: 2019-08-22



Operation Mode: Transmitting under High Channel (2480MHz)

_			
Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \u03b4 V/m)
4960		Н	74(Peak)/ 54(AV)
4960		V	74(Peak)/ 54(AV)
7440		H/V	74(Peak)/ 54(AV)
9920		H/V	74(Peak)/ 54(AV)
12400		H/V	74(Peak)/ 54(AV)
14880		H/V	74(Peak)/ 54(AV)
17360		H/V	74(Peak)/ 54(AV)
19840		H/V	74(Peak)/ 54(AV)
22320		H/V	74(Peak)/ 54(AV)
24800		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

^{2.} Remark "---" means that the emissions level is too low to be measured


Page 19 of 105 Report No.: FCC1908024

Date: 2019-08-22



Please refer to the following test plots for details:

Low Channel: Vertical




No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table (o)	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)			(cm)		
1	4802.799	46.13	3.12	74.0	-27.87	Peak	355.00	100	V	Pass

Page 20 of 105 Report No.: FCC1908024

Date: 2019-08-22



Low Channel: Horizontal



No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table (o)	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)			(cm)		
1	4802.799	48.40	3.12	74.0	-25.60	Peak	149.00	100	Н	Pass


Report No.: FCC1908024 Page 21 of 105

Date: 2019-08-22



Middle Channel: Horizontal






No.	Frequency	Results	Factor (dB)	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)		(dBuV/m)	(dB)		(o)	(cm)		
1	4879.280	47.58	3.20	74.0	-26.42	Peak	33.00	100	Н	Pass

Page 22 of 105 Report No.: FCC1908024

Date: 2019-08-22



Middle Channel: Vertical




No.	Frequency	Results	Factor	Limit	Over	Detector	Table (o)	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	Limit (dB)			(cm)		
1	4879.280	44.09	3.20	74.0	-29.91	Peak	0.00	100	V	Pass

Page 23 of 105 Report No.: FCC1908024

Date: 2019-08-22



High Channel: Horizontal




No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table (o)	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)			(cm)		
1	4960.010	48.41	3.36	74.0	-25.59	Peak	120.00	100	Н	Pass

Report No.: FCC1908024 Page 24 of 105

Date: 2019-08-22



High Channel: Vertical



No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table (o)	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)			(cm)		
1	4960.010	44.58	3.36	74.0	-29.42	Peak	149.00	100	V	Pass

Note: for the radiated emissions above 18G, it is the floor noise.

Report No.: FCC1908024 Page 25 of 105

Date: 2019-08-22



7.0 20dB Bandwidth Measurement

7.1 Regulation

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

7.2 Limits of 20dB Bandwidth Measurement

N/A

7.3 Test Procedure.

- 1. Check the calibration of the measuring instrument (spectrum analyzer) using either an internal calibrator or a known signal from an external generator.
- 2. Set the spectrum analyzer as follows: Span =3MHz, RBW =30 kHz, VBW=100 kHz, Sweep = auto Detector function = peak, Trace = max hold
- 3. Measure the highest amplitude appearing on spectral display and record the level to calculate results. 6. Repeat above procedures until all frequencies measured were complete.

7.4 Test Result

Type of Modulation: GFSK

Type of Modulations of ST								
EUT	Solar Blue	etooth Light & Speaker	Model	DY20190708-07A				
Mode	Ke	ep Transmitting	Input Voltage	DC3.7V				
Temperat	ure	24 deg. C,	Humidity	56% RH				
Channel	Channel Frequency (MHz)	20 dB Bandwidth (kHz)	Minimum Limit (kHz)	Pass/ Fail				
Low	2402	885		Pass				
Middle	2441	889		Pass				
High	2480	885		Pass				

Page 26 of 105


Report No.: FCC1908024

Date: 2019-08-22



Test Figure:

1. Condition: Low Channel



Date: 15.AUG.2019 01:22:23


Page 27 of 105

Report No.: FCC1908024

Date: 2019-08-22



2. Condition: Middle Channel



Date: 15.AUG.2019 01:21:47


Page 28 of 105

Report No.: FCC1908024

Date: 2019-08-22



3. High Channel



Date: 15.AUG.2019 01:20:37

Page 29 of 105 Report No.: FCC1908024

Date: 2019-08-22



Test Result

Type of Modulation: $\sqrt{1/4}$ DQPSK

EUT	Solar Blu	netooth Light & Speaker	Model	DY20190708-07A
Mode	K	eep Transmitting	Input Voltage	DC3.7V
Temperat	ure	24 deg. C,	Humidity	56% RH
Channel	Channel Frequency (MHz)	20 dB Bandwidth (kHz)	Maximum Limit (kHz)	Pass/ Fail
Low	2402	1231		Pass
Middle	2441	1236		Pass
High	2480	1231		Pass

Page 30 of 105


Report No.: FCC1908024

Date: 2019-08-22



Test Figure:

1. Condition: Low Channel



Date: 15.AUG.2019 01:23:04


Page 31 of 105

Report No.: FCC1908024

Date: 2019-08-22



2. Condition: Middle Channel



Date: 15.AUG.2019 01:26:06


Page 32 of 105

Report No.: FCC1908024

Date: 2019-08-22



3. High Channel



Date: 15.AUG.2019 01:26:48

Page 33 of 105 Report No.: FCC1908024

Date: 2019-08-22



Test Result

Type of Modulation: 8DPSK

EUT	Solar Blu	netooth Light & Speaker	Model	DY20190708-07A
Mode	K	eep Transmitting	Input Voltage	DC3.7V
Temperat	ure	24 deg. C,	Humidity	56% RH
Channel	Channel Frequency (MHz)	20 dB Bandwidth (kHz)	Maximum Limit (kHz)	Pass/ Fail
Low	2402	1231		Pass
Middle	2441	1240		Pass
High	2480	1240	-	Pass

Page 34 of 105


Report No.: FCC1908024

Date: 2019-08-22



Test Figure:

1. Condition: Low Channel



Date: 15.AUG.2019 01:24:00


Page 35 of 105

Report No.: FCC1908024

Date: 2019-08-22



2. Condition: Middle Channel



Date: 15.AUG.2019 01:25:25


Page 36 of 105

Report No.: FCC1908024

Date: 2019-08-22



3. High Channel



Date: 15.AUG.2019 01:27:30

Report No.: FCC1908024 Page 37 of 105

Date: 2019-08-22



8. Maximum Output Power

8.1 Regulation

According to §15.247(b)(1), for frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5MHz band:0.125 watts. According to §15.247(b)(4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

8.2 Limits of Maximum Output Power

The Maximum Output Power Measurement is 30dBm.

8.3 Test Procedure

- 1. Check the calibration of the measuring instrument (spectrum analyzer) using either an internal calibrator or a known signal from an external generator.
- 2. Set the spectrum analyzer as follows: Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel; RBW > the 20 dB bandwidth of the emission being measured; VBW = RBW=3MHz; Sweep = 60s; Detector function = PK; Trace = max hold
- 3. Measure the highest amplitude appearing on spectral display and record the level to calculate results.
- 4. Repeat above procedures until all frequencies measured were complete.

Page 38 of 105

Report No.: FCC1908024

Date: 2019-08-22



8.4Test Results

Type of Modulation: GFSK

EUT	Solar Blu	Solar Bluetooth Light & Speaker Me		Model	DY20190708-07A
Mode	K	Keep Transmitting Input Vo		Voltage	DC3.7V
Temperature	е	24 deg. C,	Humi	idity	56% RH
Channel	Channel Frequency (MHz)	Max. Power Output (dBm)	Peak Power Limit	Pass/ Fail
Low	2402	-0.25		(dBm) 30	Pass
Middle	2441	-0.05		30	Pass
High	2480	-0.08		30	Pass

Note: 1. the result basic equation calculation as follow:

Max. Power Output = Power Reading + Cable loss + Attenuator

- 2. The worse case was recorded
- 3. The Peak power was measured

Type of Modulation: Л/4DQPSK

EUT	Solar Bluetooth Light & Speaker		l	Model	DY20190708-07A	
Mode		Ke	ep Transmitting	Input Voltage		DC3.7V
Temperature	e		24 deg. C,	Hum	idity	56% RH
Channel	Channel Frequency		Max. Power Output (dBm)		Peak Power	Pass/ Fail
		(MHz)	Peak		Limit (dBm)	
Low		2402	-0.71		30	Pass
Middle		2441	-0.50		30	Pass
High		2480	-0.50		30	Pass

Note: 1. the result basic equation calculation as follow:

Max. Power Output = Power Reading + Cable loss + Attenuator

- 2. The worse case was recorded
- 3. The Peak power was measured

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to

adopt any other remedies which may be appropriate.

Page 39 of 105 Report No.: FCC1908024

Date: 2019-08-22



Type of Modulation: 8DPSK

EUT	Solar Blue	Solar Bluetooth Light & Speaker		Model	DY20190708-07A
Mode	Ke	Keep Transmitting		ıt Voltage	DC3.7V
Temperature	e	24 deg. C,	Hı	umidity	56% RH
Channel	Channel Frequency (MHz)	Max. Power Output (dBm) Peak		Peak Power Limit (dBm)	Pass/ Fail
Low	2402	-0.66		30	Pass
Middle	2441	-0.50		30	Pass
High	2480	-0.50		30	Pass

Note: 1. the result basic equation calculation as follow:

Max. Power Output = Power Reading + Cable loss + Attenuator

- 2. The worse case was recorded
- 3. The Peak power was measured

Report No.: FCC1908024 Page 40 of 105

Date: 2019-08-22



9. Carrier Frequency Separation

9.1 Regulation

According to §15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

9.2 Limits of Carrier Frequency Separation

The Maximum Power Spectral Density Measurement is 25kHz or two-thirds of the 20dB bandwidth of the hopping Channel which is great.

9.3 Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Set the spectrum analyzer as follows: Span = wide enough to capture the peaks of two adjacent channels: Resolution (or IF) Bandwidth (RBW) \geq 1% of the span; Video (or Average) Bandwidth (VBW) \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold
- 3. Measure the separation between the peaks of the adjacent channels using the marker-delta function.
- 4. Repeat above procedures until all frequencies measured were complete.

Page 41 of 105

Report No.: FCC1908024

Date: 2019-08-22




9.4Test Result

Type of Modulation: GFSK

EUT	Solar Bluetooth Light	Model	DY2	0190708-07A	
Mode	Hopping O	Input Voltage		DC3.7V	
Temperature	24 deg. C,		Humidity		56% RH
Carrier Frequency Separation			Limit		Pass/ Fail
	1.000MHz	≥ 25 kHz or 2/3	of the 20 dB ban	dwidth	Pass

Test Plots



Date: 13.AUG.2019 17:17:32

Report No.: FCC1908024 Page 42 of 105


Date: 2019-08-22



Type of Modulation: Л/4DQPSK

EUT	Solar Bluetooth Light	Model	DY2	0190708-07A	
Mode	Hopping O	Input Voltage		DC3.7V	
Temperature	24 deg. C,		Humidity		56% RH
Carrier Frequency Separation			Limit		Pass/ Fail
	1.000MHz	≥ 25 kHz or 2	2/3 of 20 dB bandy	vidth	Pass

Test Plots



Date: 13.AUG.2019 18:14:21

Report No.: FCC1908024 Page 43 of 105


Date: 2019-08-22



Type of Modulation: 8DPSK

EUT	Solar Bluetooth Light	Model	DY2	0190708-07A	
Mode	Hopping On Ir		Input Voltage	DC3.7V	
Temperature	24 deg. C,		Humidity	56% RH	
Carrier Frequency Separation			Limit		Pass/ Fail
	1.000MHz	≥ 25 kHz or 2	/3 of 20 dB bandy	vidth	Pass

Test Plots



Date: 14.AUG.2019 21:43:28

Report No.: FCC1908024 Page 44 of 105

Date: 2019-08-22



10. Number of Hopping Channels

10.1 Regulation

According to §15.247(a)(1)(iii), frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used. According to §15.247(b)(1), for frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

10.2 Limits of Number of Hopping Channels

The frequency hopping systems in the 2400-2483.5MHz band shall use at least 15 channels.

10.3 Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Set the spectrum analyzer as follows: Span = the frequency band of operation; RBW=100 kHz, VBW=300 kHz; Sweep = auto; Detector function = peak; Trace = max hold
- 3. Record the number of hopping channels.

Page 45 of 105

Report No.: FCC1908024

Date: 2019-08-22




10.4Test Result

Type of Modulation: GFSK

EUT	Solar Bluetooth Light & Speaker		Model	DY2	0190708-07A
Mode	Hopping On		Input Voltage	DC3.7V	
Temperature	2	24 deg. C,	Humidity	56% RH	
Operating Frequency		Number of hopping channels		Limit	Pass/ Fail
2402-2480MHz		79		≥ 15	Pass

Test Plot



Date: 13.AUG.2019 16:58:17

Page 46 of 105

Report No.: FCC1908024


Date: 2019-08-22



Type of Modulation: Л/4DQPSK

EUT	Solar Bluetooth Light & Speaker		Model	DY20190708-07A	
Mode	Hopping On		Input Voltage	DC3.7V	
Temperature		24 deg. C,	Humidity	56% RH	
Operating Frequency		Number of hopping channels	Limit	Pass/ Fail	
2402-2480MHz		79	≥ 15	Pass	

Test Plot



Date: 14.AUG.2019 23:08:00

Page 47 of 105

Date: 2019-08-22




Type of Modulation: 8DPSK

Report No.: FCC1908024

EUT	Solar Bluetooth Light & Speaker		M	odel	DY	DY20190708-07A	
Mode	Hopping On		Input	Voltage		DC3.7V	
Temperature		24 deg. C,	Humi	dity		56% RH	
Operating Frequency		Number of hopping channels	ng	Liı	mit	Pass/ Fail	
2402-2480MHz		79		>	15	Pass	

Test Plot





Date: 14.AUG.2019 22:37:27

Report No.: FCC1908024

Date: 2019-08-22



Page 48 of 105

11. Time of Occupancy (Dwell Time)

11.1 Regulation

According to §15.247(a)(1)(iii), frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

11.2 Limits of Carrier Frequency Separation

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed

11.3 Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Set the spectrum analyzer as follows: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW \geq RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold
- 3. Measure the dwell time using the marker-delta function.
- 4. Repeat above procedures until all frequencies measured were complete.
- 5. Repeat this test for different modes of operation (e.g., data rate, modulation format, etc.), if applicable.

Report No.: FCC1908024 Page 49 of 105

Date: 2019-08-22



11.4 Test Result

Type of Modulation: GFSK

EUT	Solar Bluetooth	Solar Bluetooth Light & Speaker Model		DY20190708-07A	
Mode	Keep Tr	Keep Transmitting		120V~	
Temperatur	e 24 d	leg. C,	Humidity	56% RH	
Channel	Reading	Hoping	g Rate	Actual	Limit
DH5					
Middle	2.917ms	266.667	266.667 hop/s		0.4s

Actual = Reading × (Hopping rate / Number of channels) × Test period, Test period = 0.4 [seconds / channel] × 79 [channel] = 31.6 [seconds] NOTE: The EUT makes worst case 1600 hops per second or 1 time slot has a length of $625\mu s$ with 79 channels.

A DH5 Packet needs 5 time slot for transmitting and 1 time slot for receiving. Then the EUT makes worst case 266.667 hops per second with 79 channels.

A DH3 Packet needs 3 time slot for transmitting and 1 time slot for receiving. Then the EUT makes worst case 400 hops per second with 79 channels.

A DH1 Packet needs 1 time slot for transmitting and 1 time slot for receiving. Then the EUT makes worst case 800 hops per second with 79 channels.

Note: DH5 was the worst case.

Page 50 of 105


Report No.: FCC1908024

Date: 2019-08-22



Test Plots:

DH5



Date: 15.AUG.2019 01:47:03

Report No.: FCC1908024 Page 51 of 105

Date: 2019-08-22



Test Result

Type of Modulation: Л/4DQPSK

EUT	Solar Bluetooth Light & Speaker Model		DY20	0190708-07A	
Mode	Keep Tr	ansmitting	ing Input Voltage 120V~		120V~
Temperatur	e 24 c	leg. C,	Humidity	5	66% RH
Channel	Reading	Hoping	g Rate	Actual	Limit
			DH5		
Middle	2.965ms	266.667 hop/s		0.316s	0.4s

Actual = Reading × (Hopping rate / Number of channels) × Test period, Test period = 0.4 [seconds / channel] × 79 [channel] = 31.6 [seconds] NOTE: The EUT makes worst case 1600 hops per second or 1 time slot has a length of 625µs with 79 channels.

A DH5 Packet needs 5 time slot for transmitting and 1 time slot for receiving. Then the EUT makes worst case 266.667 hops per second with 79 channels.

A DH3 Packet needs 3 time slot for transmitting and 1 time slot for receiving. Then the EUT makes worst case 400 hops per second with 79 channels.

A DH1 Packet needs 1 time slot for transmitting and 1 time slot for receiving. Then the EUT makes worst case 800 hops per second with 79 channels.

Note: 2DH5 was the worst case.

Page 52 of 105


Report No.: FCC1908024

Date: 2019-08-22



Test Plots:

2DH5



Date: 15.AUG.2019 01:50:50

Report No.: FCC1908024 Page 53 of 105

Date: 2019-08-22



Type of Modulation: 8DPSK

EUT	Solar Bluetooth	uetooth Light & Speaker Model		DY20	190708-07A
Mode	Keep Tr	ansmitting	Input Voltage	ge 120V~	
Temperature	e 24 d	leg. C,	Humidity	lity 56% RH	
Channel	Reading	Hoping	g Rate	Actual Limit	
DH5					
Middle	2.933ms	266.667	7 hop/s	0.313s	0.4s

Actual = Reading \times (Hopping rate / Number of channels) \times Test period, Test period = 0.4 [seconds / channel] \times 79 [channel] = 31.6 [seconds] NOTE: The EUT makes worst case 1600 hops per second or 1 time slot has a length of 625 μ s with 79 channels.

A DH5 Packet needs 5 time slot for transmitting and 1 time slot for receiving. Then the EUT makes worst case 266.667 hops per second with 79 channels.

A DH3 Packet needs 3 time slot for transmitting and 1 time slot for receiving. Then the EUT makes worst case 400 hops per second with 79 channels.

A DH1 Packet needs 1 time slot for transmitting and 1 time slot for receiving. Then the EUT makes worst case 800 hops per second with 79 channels.

Note: 3DH5 was the worst case.

Page 54 of 105


Report No.: FCC1908024

Date: 2019-08-22



Test Plots:

3DH5



Date: 15.AUG.2019 01:51:59

Report No.: FCC1908024


Date: 2019-08-22



Page 55 of 105

12 Out of Band Measurement

12.1 Test Setup



The restricted band requirement based on radiated emission test; please see the clause 6 for the test setup

12.2 Limits of Out of Band Emissions Measurement

- 1. Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).
- 2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

12.3 Test Procedure

For signals in the restricted bands above and below the 2.4-2.483GHz allocated band a measurement was made of radiated emission test. Peak values with RBW=VBW=1MHz and PK detector.

For bandage test, the spectrum set as follows: RBW=100 kHz, VBW=300 kHz. A conducted measurement used

Note: 1. For band-edge measurement, the frequency from 30MHz-25GHz was tested. And It met the FCC rule.

Page 56 of 105

Report No.: FCC1908024

Date: 2019-08-22




Type of Modulation: GFSK

Band Edge Test Result 12.4

Product:	Solar Bluetooth Light & Speaker	Test Mode:	Low Channel
Mode	Keeping Transmitting	Input Voltage	DC3.7V
Temperature	24 deg. C	Humidity	56% RH
Test Result:	Pass	Detector	PK

Test Figure:



Date: 15.AUG.2019 01:10:57

Page 57 of 105

Report No.: FCC1908024

Date: 2019-08-22




Type of Modulation: GFSK

Band Edge Test Result 12.4

Product:	Solar Bluetooth Light & Speaker	Test Mode:	High Channel
Mode	Keeping Transmitting	Input Voltage	DC3.7V
Temperature	24 deg. C,	Humidity	56% RH
Test Result:	Pass	Detector	PK

Test Figure:



Date: 15.AUG.2019 01:17:52

Page 58 of 105

Report No.: FCC1908024

Date: 2019-08-22




Type of Modulation: GFSK

Band Edge Test Result

Product:	Solar Bluetooth Light & Speaker	Test Mode:	Hopping mode
Mode	Hopping On	Input Voltage	DC3.7V
Temperature	24 deg. C,	Humidity	56% RH
Test Result:	Pass	Detector	PK

Test Figure:



Date: 15.AUG.2019 01:04:19

Page 59 of 105

Date: 2019-08-22




Type of Modulation: GFSK

Band Edge Test Result

Report No.: FCC1908024

Product:	Solar Bluetooth Light & Speaker	Test Mode:	Hopping mode
Mode	Hopping On	Input Voltage	DC3.7V
Temperature	24 deg. C,	Humidity	56% RH
Test Result:	Pass	Detector	PK

Test Figure:



Date: 14.AUG.2019 23:25:13

Page 60 of 105

Report No.: FCC1908024

Date: 2019-08-22




Type of Modulation: Л/4DQPSK

12.4 Out of Band Test Result

Product:	Solar Bluetooth Light & Speaker	Test Mode:	Low Channel
Mode	Keeping Transmitting	Input Voltage	DC3.7V
Temperature	24 deg. C	Humidity	56% RH
Test Result:	Pass	Detector	PK

Test Figure:



Date: 15.AUG.2019 01:13:14

Page 61 of 105

Report No.: FCC1908024

Date: 2019-08-22




Type of Modulation: Л/4DQPSK

Band Edge Test Result 12.4

Product:	Solar Bluetooth Light & Speaker	Test Mode:	High Channel
Mode	Keeping Transmitting	Input Voltage	DC3.7V
Temperature	24 deg. C,	Humidity	56% RH
Test Result:	Pass	Detector	PK

Test Figure:



Date: 15.AUG.2019 01:17:52

Report No.: FCC1908024 Page 62 of 105

Date: 2019-08-22




Type of Modulation: Л/4DQPSK

Out of Band Test Result

Product:	Solar Bluetooth Light & Speaker	Test Mode:	Hopping mode
Mode	Hopping On	Input Voltage	DC3.7V
Temperature	24 deg. C,	Humidity	56% RH
Test Result:	Pass	Detector	PK

Test Figure:



Date: 14.AUG.2019 22:58:05

Report No.: FCC1908024 Page 63 of 105

Date: 2019-08-22




Type of Modulation: Л/4DQPSK

Out of Band Test Result

Product:	Solar Bluetooth Light & Speaker	Test Mode:	Hopping mode
Mode	Hopping On	Input Voltage	DC3.7V
Temperature	24 deg. C,	Humidity	56% RH
Test Result:	Pass	Detector	PK

Test Figure:



Date: 14.AUG.2019 23:18:07

Page 64 of 105

Report No.: FCC1908024

Date: 2019-08-22




Type of Modulation: 8DPSK

12.4 Band Edge Test Result

Product:	Solar Bluetooth Light & Speaker	Test Mode:	Low Channel
Mode	Keeping Transmitting	Input Voltage	DC3.7V
Temperature	24 deg. C	Humidity	56% RH
Test Result:	Pass	Detector	PK

Test Figure:



Date: 15.AUG.2019 01:15:14

Page 65 of 105

Report No.: FCC1908024

Date: 2019-08-22




Type of Modulation: 8DPSK

Band Edge Test Result 12.4

Product:	Solar Bluetooth Light & Speaker	Test Mode:	High Channel
Mode	Keeping Transmitting	Input Voltage	DC3.7V
Temperature	24 deg. C,	Humidity	56% RH
Test Result:	Pass	Detector	PK

Test Figure:



Date: 15.AUG.2019 01:16:54

Report No.: FCC1908024 Page 66 of 105

Date: 2019-08-22




Type of Modulation: 8DPSK

Band Edge Test Result

Product:	Solar Bluetooth Light & Speaker	Test Mode:	Hopping mode
Mode	Hopping On	Input Voltage	DC3.7V
Temperature	24 deg. C,	Humidity	56% RH
Test Result:	Pass	Detector	PK

Test Figure:



Date: 14.AUG.2019 22:50:18

Page 67 of 105

Report No.: FCC1908024

Date: 2019-08-22




Type of Modulation: 8DPSK

Band Edge Test Result

Product:	Solar Bluetooth Light & Speaker	Test Mode:	Hopping mode
Mode	Hopping On	Input Voltage	DC3.7V
Temperature	24 deg. C,	Humidity	56% RH
Test Result:	Pass	Detector	PK

Test Figure:



Date: 14.AUG.2019 23:23:02

Page 68 of 105

Report No.: FCC1908024 Date: 2019-08-22



12.4 Restrict Band Measurement

EUT		T Solar Bluetooth Light & Speaker				Model			DY20190708-07A		
	Mode	Keep Transmitting				Input Voltage			DC3.7V		
Te	mperature		24 deg.	С,		Humidit	y		56% R	Н	
Te	est Result:		Pass		N	Iodulation '	Туре		GFSK	ζ	
CC Part 1	.5B Class B 1GHz-18GHz	: - 2									
80-											
70- 60- 50-											
o) la							M1 dan	, july			
<u>0</u> 50− 40−							A STATE OF THE STA				
40-	diningan pandik ^{an k} akin kanzinkan		ha tagés palitiques des principals procured in	and the second second second		p to the production of any or the	Hamayardina haya			Landon Maria	
	attention to the transfer of	olon and a second beautiful to the second beautiful to	ha tanka addikka a ki dishigir ya marka	annulus des Ademais aconte	Frequency (M	nadajikah kata karakan Maria karakan Maria karakan Maria karakan Maria karakan Maria karakan Maria karakan Mari	Hamarian Andrew			2410	
40-	attention to the transfer of	Results	Factor	Limit	Frequency (M	Hz)	Table (o)	Height	ANT		
40 - 30 - 2350)	A company of the complete for a				1	jamar jaman ja	Height (cm)	ANT	T	

Report No.: FCC1908024 Page 69 of 105

Date: 2019-08-22



12.4 Restrict Band Measurement

	EUT	Solar Blu	etooth L	ight & Speake	er	Model		DY2	0190708-0	07A	
	Mode	Keep Transmitting			In	Input Voltage		DC3.7V			
Teı	mperature		24 deg	g. C,]	Humidity			56% RH		
Te	st Result:		Pas	SS	Mod	lulation Ty _l	pe		GFSK		
CC Part 1:	5B Class B 1GHz-18GHz	: - 2					•				
70- 70- 60- 50-							M1				
40-	te adjustici da la	March March March	and the second	A Company of the Comp	ato and the state of the state of the	adad kirilikani sajil dalah	A CONTRACTOR OF THE PROPERTY O	Mariania Maria Mar		Mahada	
30-)				Frequency (MI	Hz)				2410	
No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)		Over Limit	Detector	Table (o)	Height (cm)	ANT	Verdict	
	2390	43.41	-3.53	74.0 -3	30.59	Peak	160.00	100	V	Pass	

Page 70 of 105 Report No.: FCC1908024

Date: 2019-08-22



Doctrict Dand Macaumamant

2.4	Restrict B EUT	Solar Blu	etooth I	ight & Snea	ker	Model		Γ	Y201907	08-07A	
	Mode		Solar Bluetooth Light & Speaker Keep Transmitting			Input Voltage			DC3.7V		
	nperature	TK.	24 deg			Humidit			56% F		
	t Result:		Pas		1	Modulation	-		GFS]		
	Class B 1GHz-18GHz	7 - 2	1 43		1	Todulation	Турс		GI 5	· · · · · · · · · · · · · · · · · · ·	
90- 80- 70- 60- 40-	/***\\							1	. deli-mata		
30					""\ ₁ ,	Marin Landelle		the traffic and the staff	A THE PARTY OF THE	History of the State of	
30 - 2470					2483.5 Frequency (MH	z)				2500	
No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table (o)	Height	ANT	Verdict	
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)			(cm)			
1	2483.5	53.13	-3.57	74.0	-20.87	Peak	118.00	100	Н	Pass	
	2483.5	38.65	-3.57	54.0	-15.35	AV	118.00	100	Н	Pass	

Report No.: FCC1908024 Page 71 of 105

Date: 2019-08-22



Restrict Band Measurement 12.4

	EUT	Solar Bluetooth Light & Speaker				Model			DY20190708-07A			
Mode Keep Transmitting						Input Voltage			DC3.7V			
Ten	nperature		24 deg	g. C,		Humidity			56% RH			
Tes	t Result:		Pas	SS	M	odulation	Туре		GFSK			
CC Part 158	B Class B 1GHz-18GHz	z - 2										
70 - (ww/\ngp) 100 1		And the state of t										
hat the	A CONTRACTOR OF THE PARTY OF TH	Market Park			Mark deployed	heredally alterbalances		A STATE OF THE STA		dupped didu		
30- 2470					2483.5 Frequency (MF	lz)				2500		
No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table (o)	Height	ANT	Verdict		
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)			(cm)				
1	2483.5	46.27	-3.57	74.0	-27.73	Peak	150.00	100	V	Pass		

Note: For Restricted band test, only the worst case GFSK was reported.

Report No.: FCC1908024

Date: 2019-08-22



Page 72 of 105

13.0 Antenna Requirement

13.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitter antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the mount in dB that the directional gain of the antenna exceeds 6 dBi.

13.2 Antenna Connected constructions

PCB antenna used. The gain of the antennas is 0dBi.