



RF Exposure Evaluation

| | |
|------------------------------|----------------------------------|
| FCC ID | 2AUIE -FSBTC1 |
| Model No. | FS-BT-C1 |
| Supports Radios Spec. | WPAN: Bluetooth V4.2(Dual Mode) |
| BT Specification | BR/EDR/BLE |
| BT Frequency Range | 2402~2480MHz |

According to FCC KDB 447498 Section 4.3 - General SAR test exclusion guidance

For 100 MHz to 6 GHz and test separation distances ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR, and } \leq 7.5 \text{ for 10-g extremity SAR,}$$

where

1. $f(\text{GHz})$ is the RF channel transmit frequency in GHz
2. Power and distance are rounded to the nearest mW and mm before calculation³¹
3. The result is rounded to one decimal place for comparison
4. The values 3.0 and 7.5 are referred to as numeric thresholds in step b) below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.



Calculation Result:

| Mode | Frequency Band (MHz) | Average Output Power (dBm) | Output Power (mW) | SAR Test Exclusion Threshold (mW) |
|------|----------------------|----------------------------|-------------------|-----------------------------------|
| BT | 2402 ~ 2480 | 1 | 0.001 | 10 |

So, this device can complies the SAR test exclusion.