

1. MAXIMUM PERMISSIBLE EXPOSURE (MPE)

1.1 General Information

Client Information

Applicant: Macro-video Technologies Co.,Ltd.
Address of applicant: 9th floor,building No.22, TIANAN-TEP,Panyu Road North No.
555, Panyu District,Guangzhou, Guangdong, China

Manufacturer: Macro-video Technologies Co.,Ltd.
Address of manufacturer: 9th floor,building No.22, TIANAN-TEP,Panyu Road North No.
555, Panyu District,Guangzhou, Guangdong, China

General Description of EUT:

Product Name: Smart camera
Trade Name: /
Model No.: XVV-3630S-Q8
Adding Model(s): Q5, Q7, Q8, Q9, Q10, Q11, P1, P2, P3, P4, P11, P12, B3, B4, B11, D8, XVV-3630S-Q11, XVV-3630S-P1
Rated Voltage: DC 5V
MODEL : TEKA-UCA10UN
Power Adapter Model: INPUT :AC100-240V, 50-60Hz, 0.2A MAX
OUTPUT :DC5.0V, 1.0A
FCC ID: 2AV39-XVV-3630S-Q8
Equipment Type: Fixed

Technical Characteristics of EUT:

Wi-Fi

Support Standards: 802.11b, 802.11g, 802.11n
Frequency Range: 2412-2462MHz for 802.11b/g/n(HT20)
2422-2452MHz for 802.11n(HT40)
RF Output Power: 13.96dBm (Conducted)
Type of Modulation: DBPSK,BPSK,DQPSK,QPSK,16QAM,64QAM
Quantity of Channels: 11 for 802.11b/g/n(HT20); 7 for 802.11n(HT40)
Channel Separation: 5MHz
Type of Antenna: Integral Antenna
Antenna Gain: 2dBi

1.2 Standard Applicable

According to § 1.1307(b)(1) and KDB 447498 D01 General RF Exposure Guidance v06, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

(a) Limits for Occupational / Controlled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	F/300	6
1500-100000	/	/	5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-100000	/	/	1	30

Note: f = frequency in MHz; * = Plane-wave equivalents power density

1.3 MPE Calculation Method

$$S = (30*P*G) / (377*R^2)$$

S = power density (in appropriate units, e.g., mw/cm²)

P = power input to the antenna (in appropriate units, e.g., mw)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator,
the power gain factor is normally numeric gain.

R = distance to the center of radiation of the antenna (in appropriate units, e.g., cm)

1.4 MPE Calculation Result

For Wi-Fi

Maximum Tune-Up output power: 14(dBm)

Maximum peak output power at antenna input terminal: 25.12 (mW)

Prediction distance: >20(cm)

Prediction frequency: 2412 (MHz)

Antenna gain: 2 (dBi)

Directional gain (numeric gain): 1.58

The worst case is power density at prediction frequency at 20cm: 0.0079 (mw/cm²)

MPE limit for general population exposure at prediction frequency: 1 (mw/cm²)

Result: Pass