

1. MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FCC ID: 2AV39XVV-6120S-B1

Client Information

Applicant: Macro-video Technologies Co.,Ltd.
Address of applicant: 9th floor,building No.22, TIANAN-TEP,Panyu Road North No. 555, Panyu District,Guangzhou, Guangdong, China

Manufacturer: Macro-video Technologies Co.,Ltd.
Address of manufacturer: 9th floor,building No.22, TIANAN-TEP,Panyu Road North No. 555, Panyu District,Guangzhou, Guangdong, China

General Description of EUT	
Product Name:	Outdoor camera
Trade Name:	XIAOVV
Model No.:	XVV-6120S-B1
Adding Model(s):	/
Rated Voltage:	DC12V
Power adapter	MODEL:KA1201A-1201000CN INPUT: AC100-240V~50/60Hz, 0.4A Max OUTPUT: DC12V,1000mA
Equipment Type:	Fixed

Note: The test data is gathered from a production sample provided by the manufacturer.

Note: The test data is gathered from a production sample provided by the manufacturer.

1.2 Standard Applicable

According to § 1.1307(b)(1) and KDB 447498 D01 General RF Exposure Guidance v06, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

(a) Limits for Occupational / Controlled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	F/300	6
1500-100000	/	/	5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-100000	/	/	1	30

Note: f = frequency in MHz: * = Plane-wave equivalents power density

1.3 MPE Calculation Method

$$S = (30*P*G) / (377*R^2)$$

S = power density (in appropriate units, e.g., mw/cm²)

P = power input to the antenna (in appropriate units, e.g., mw)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator,

the power gain factor is normally numeric gain.

R = distance to the center of radiation of the antenna (in appropriate units, e.g., cm)

1.4 MPE Calculation Result

Fixed device

Wi-Fi:

Maximum Tune-Up output power: 18 (dBm)

Maximum peak output power at antenna input terminal: 63.09(mW)

Prediction distance: >20(cm)

Prediction frequency: 2412(MHz)

Antenna gain: 3.0(dBi)

Directional gain (numeric gain): 2

The worst case is power density at prediction frequency at 20cm: 0.025 (mw/cm²)

MPE limit for general population exposure at prediction frequency: 1 (mw/cm²)

Result: Pass