

FCC RF EXPOSURE REPORT

SHEN ZHEN EVOWERA TECHNOLOGY CO.,LTD

planck mini

Model Number: planck mini

FCC ID: 2AV42-PLANCKMINI

| | |
|--------------|--|
| Applicant: | SHEN ZHEN EVOWERA TECHNOLOGY CO.,LTD |
| Address: | Room 402, Floor 4, Block C, Skyworth Building, 1st South Gao Xin Ave., |
| | Nanshan, Shenzhen, China |
| | |
| Prepared By: | EST Technology Co., Ltd. |
| | Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China |
| | Tel: 86-769-83081888-808 |

| | |
|-----------------|-----------------------|
| Report Number: | ESTE-R2207076 |
| Date of Test: | Jun. 01~Jul. 07, 2022 |
| Date of Report: | Jul. 11, 2022 |



1. Applicable Standards

FCC Part 2(Section 2.1093)

FCC KD B447498 D01 General RF Exposure Guidance v06

2. Exposure Evaluation of Portable or Mobile Devices

Human exposure to RF emissions from portable devices (47 CFR §2.1093), as defined by the FCC, must be evaluated with respect to the FCC-adopted limits for SAR. Evaluation of mobile devices, as defined by the FCC, may also be performed with respect to SAR limits, but in such cases it is usually simpler and more cost-effective to evaluate compliance with respect to field strength or power density limits. For certain devices that are designed to be used in both mobile and portable configurations similar to those described in 47 CFR §2.1091(d)(4), such as certain desktop phones and wireless modem modules, compliance for mobile configurations is also satisfied when the same device is evaluated for SAR compliance in portable configurations.

SAR Test Exclusion Thresholds for 100 MHz - 6 GHz and ≤ 50 mm

| MHz | 5 | 10 | 15 | 20 | 25 | mm |
|------|----|----|-----|-----|-----|--|
| 150 | 39 | 77 | 116 | 155 | 194 | <i>SAR Test Exclusion Threshold (mW)</i> |
| 300 | 27 | 55 | 82 | 110 | 137 | |
| 450 | 22 | 45 | 67 | 89 | 112 | |
| 835 | 16 | 33 | 49 | 66 | 82 | |
| 900 | 16 | 32 | 47 | 63 | 79 | |
| 1500 | 12 | 24 | 37 | 49 | 61 | |
| 1900 | 11 | 22 | 33 | 44 | 54 | |
| 2450 | 10 | 19 | 29 | 38 | 48 | |
| 3600 | 8 | 16 | 24 | 32 | 40 | |
| 5200 | 7 | 13 | 20 | 26 | 33 | |
| 5400 | 6 | 13 | 19 | 26 | 32 | |
| 5800 | 6 | 12 | 19 | 25 | 31 | |

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR}$$

where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

3. Evaluation Results

| Mode | Frequency (MHz) | Peak output Power (dBm) | Peak output Power (mW) | Target power (dBm) | Results |
|-------------------|-----------------|-------------------------|------------------------|--------------------|---------|
| BLE 1M | 2402 | 3.75 | 2.3714 | 3 ± 1 | 0.779 |
| | 2440 | 1.96 | 1.5704 | 1 ± 1 | 0.495 |
| | 2480 | 1.11 | 1.2912 | 1 ± 1 | 0.499 |
| BLE 2M | 2402 | 3.29 | 2.1330 | 3 ± 1 | 0.779 |
| | 2440 | 2.64 | 1.8365 | 2 ± 1 | 0.623 |
| | 2480 | 1.77 | 1.5031 | 1 ± 1 | 0.499 |
| IEEE 802.11b | 2412 | 1.84 | 1.5276 | 1 ± 1 | 0.492 |
| | 2437 | 1.18 | 1.3122 | 1 ± 1 | 0.495 |
| | 2462 | -0.14 | 0.9683 | 0 ± 1 | 0.395 |
| IEEE 802.11g | 2412 | 1.23 | 1.3274 | 1 ± 1 | 0.492 |
| | 2437 | 1.31 | 1.3521 | 1 ± 1 | 0.495 |
| | 2462 | 0.93 | 1.2388 | 0 ± 1 | 0.395 |
| IEEE 802.11nH T20 | 2412 | 1.05 | 1.2735 | 1 ± 1 | 0.492 |
| | 2437 | 1.25 | 1.3335 | 1 ± 1 | 0.495 |
| | 2462 | 0.61 | 1.1508 | 0 ± 1 | 0.395 |
| IEEE 802.11nH T40 | 2422 | 1.85 | 1.5311 | 1 ± 1 | 0.493 |
| | 2437 | 2.82 | 1.9143 | 2 ± 1 | 0.623 |
| | 2452 | 2.37 | 1.7258 | 2 ± 1 | 0.625 |

Note:

1. [(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] * [$\sqrt{f(\text{GHz})}$] < 3.0.
2. SAR Test Exclusion Thresholds is 3.0 for separation distance 5mm. Therefore, SAR test is not required.

End of Test Report