



FCC Part 15C Measurement and Test Report

For

Xiamen Tenia Lighting & Electrical Co., Ltd.

No.575,Second Ring South Road, Tong'an District, Xiamen,

Fujian 361100, CHINA

FCC ID: 2AV7W-DNA052W

FCC Rule(s): FCC Part 15.247

Product Description: Solid-State Dimming Controls

Tested Model: DNA052M2B-W-300

Report No.: WTX20X04021407W

Sample Receipt Date: Apr.28, 2020

Tested Date: Apr.28, 2020 to May.25, 2020

Issued Date: May.25, 2020

Tested By: Jack Huang / Engineer

Reviewed By: Lion Cai / RF Manager

Approved & Authorized By: Silin Chen / Manager

Prepared By:

Jack Huang

Lion Cai

Silin Chen

Waltek Testing Group (Shenzhen) Co., Ltd.

1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,
Block 70 Bao'an District, Shenzhen, Guangdong, China

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Waltek Testing Group (Shenzhen) Co., Ltd.



TABLE OF CONTENTS

1. GENERAL INFORMATION.....4

 1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....4

 1.2 TEST STANDARDS.....5

 1.3 TEST METHODOLOGY.....5

 1.4 TEST FACILITY.....5

 1.5 EUT SETUP AND TEST MODE.....6

 1.6 MEASUREMENT UNCERTAINTY.....7

 1.7 TEST EQUIPMENT LIST AND DETAILS.....8

2. SUMMARY OF TEST RESULTS.....10

3. RF EXPOSURE.....11

 3.1 STANDARD APPLICABLE.....11

 3.2 TEST RESULT.....11

4. ANTENNA REQUIREMENT.....12

 4.1 STANDARD APPLICABLE.....12

 4.2 EVALUATION INFORMATION.....12

5. POWER SPECTRAL DENSITY.....13

 5.1 STANDARD APPLICABLE.....13

 5.2 TEST PROCEDURE.....13

 5.3 SUMMARY OF TEST RESULTS/PLOTS.....13

6. DTS BANDWIDTH.....17

 6.1 STANDARD APPLICABLE.....17

 6.2 TEST PROCEDURE.....17

 6.3 SUMMARY OF TEST RESULTS/PLOTS.....17

7. RF OUTPUT POWER.....21

 7.1 STANDARD APPLICABLE.....21

 7.2 TEST PROCEDURE.....21

 7.3 SUMMARY OF TEST RESULTS/PLOTS.....21

8. FIELD STRENGTH OF SPURIOUS EMISSIONS.....26

 8.1 STANDARD APPLICABLE.....26

 8.2 TEST PROCEDURE.....26

 8.3 CORRECTED AMPLITUDE & MARGIN CALCULATION.....27

 8.4 SUMMARY OF TEST RESULTS/PLOTS.....27

9. OUT OF BAND EMISSIONS.....35

 9.1 STANDARD APPLICABLE.....35

 9.2 TEST PROCEDURE.....35

 9.3 SUMMARY OF TEST RESULTS/PLOTS.....36

10. CONDUCTED EMISSIONS.....52

 10.1 TEST PROCEDURE.....52

 10.2 BASIC TEST SETUP BLOCK DIAGRAM.....52

 10.3 TEST RECEIVER SETUP.....52

 10.4 SUMMARY OF TEST RESULTS/PLOTS.....52



Report version

Version No.	Date of issue	Description
Rev.00	May.25, 2020	Original
/	/	/



1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: Xiamen Tenia Lighting & Electrical Co., Ltd.
 Address of applicant: No.575,Second Ring South Road, Tong'an District, Xiamen, Fujian 361100, CHINA

Manufacturer: Xiamen Tenia Lighting & Electrical Co., Ltd.
 Address of manufacturer: No.575,Second Ring South Road, Tong'an District, Xiamen, Fujian 361100, CHINA

General Description of EUT	
Product Name:	Solid-State Dimming Controls
Trade Name:	TENIA
Model No.:	DNA052M2B-W-300
Adding Model(s):	/
Rated Voltage:	AC 120V /60Hz
<i>Note: The test data is gathered from a production sample provided by the manufacturer.</i>	

Technical Characteristics of EUT	
Support Standards:	802.11b, 802.11g, 802.11n
Frequency Range:	2412-2462MHz for 802.11b/g/n-HT20
RF Output Power:	17.32dBm (Conducted)
Type of Modulation:	DBPSK,BPSK,DQPSK,QPSK,16QAM,64QAM
Data Rate:	1-11Mbps, 6-54Mbps, up to 72.2Mbps
Quantity of Channels:	11 for 802.11b/g/n-HT20
Channel Separation:	5MHz
Type of Antenna:	PCB Antenna
Antenna Gain:	2.0dBi

1.2 Test Standards

The tests were performed according to following standards:

FCC Rules Part 15.247: Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

558074 D01 15.247 Meas Guidance v05r02: Guidance for Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating under section 15.247 of the Fcc rules.

ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, KDB 558074 D01 15.247 Meas Guidance v05r02.

The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions.

1.4 Test Facility

Address of the test laboratory

Laboratory: Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road, Block 70 Bao'an District, Shenzhen, Guangdong, China

FCC – Registration No.: 125990

Waltek Testing Group (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. The Designation Number is CN5010, and Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Waltek Testing Group (Shenzhen) Co., Ltd., has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.



1.5 EUT Setup and Test Mode

Use “espRFTool_2.3.exe” and follow the instructions given by the manufacturer, you can start to test. During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. Test use the customer default power level, with a duty cycle equal to 100%, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	802.11b	Low:2412MHz, Middle:2437MHz,High:2462MHz
TM2	802.11g	Low:2412MHz, Middle:2437MHz,High:2462MHz
TM3	802.11n-HT20	Low:2412MHz, Middle:2437MHz,High:2462MHz

Test Conditions	
Temperature:	22~25 °C
Relative Humidity:	50~56 %.
ATM Pressure:	1019 mbar

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
AC Cable	0.19	Unshielded	Without Ferrite

Accessories Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
Plug	/	/	/
Notebook	Lenovo	E445	EB12648265



1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	$\pm 0.42\text{dB}$
Occupied Bandwidth	Conducted	$\pm 1.5\%$
Power Spectral Density	Conducted	$\pm 1.8\text{dB}$
Conducted Spurious Emission	Conducted	$\pm 2.17\text{dB}$
Conducted Emissions	Conducted	9-150kHz $\pm 3.74\text{dB}$
		0.15-30MHz $\pm 3.34\text{dB}$
Transmitter Spurious Emissions	Radiated	30-200MHz $\pm 4.52\text{dB}$
		0.2-1GHz $\pm 5.56\text{dB}$
		1-6GHz $\pm 3.84\text{dB}$
		6-18GHz $\pm 3.92\text{dB}$

1.7 Test Equipment List and Details

No.	Description	Manufacturer	Model	Serial No.	Cal Date	Due Date
SEMT-1072	Spectrum Analyzer	Agilent	E4407B	MY41440400	2020-04-28	2021-04-27
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2020-04-28	2021-04-27
SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2020-04-28	2021-04-27
SEMT-1008	Amplifier	Agilent	8447F	3113A06717	2020-04-28	2021-04-27
SEMT-1043	Amplifier	C&D	PAP-1G18	2002	2020-04-28	2021-04-27
SEMT-1011	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2019-05-05	2021-05-04
SEMT-1042	Horn Antenna	ETS	3117	00086197	2019-05-05	2021-05-04
SEMT-1121	Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170582	2019-05-05	2021-05-04
SEMT-1069	Loop Antenna	Schwarz beck	FMZB 1516	9773	2019-05-05	2021-05-04
SEMT-1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2020-04-28	2021-04-27
SEMT-1003	L.I.S.N	Schwarz beck	NSLK8126	8126-224	2020-04-28	2021-04-27
SEMT-1002	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2020-04-28	2021-04-27
SEMT-1168	Pre-amplifier	Direction Systems Inc.	PAP-0126	14141-12838	2020-04-28	2021-04-27
SEMT-1169	Pre-amplifier	Direction Systems Inc.	PAP-2640	14145-14153	2020-04-28	2021-04-27
SEMT-1163	Spectrum Analyzer	Rohde & Schwarz	FSP40	100612	2020-04-28	2021-04-27
SEMT-1170	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2019-05-05	2021-05-04
SEMT-1166	Power Limiter	Agilent	N9356B	MY45450376	2020-04-28	2021-04-27
SEMT-1048	RF Limiter	ATTEN	AT-BSF-2400~2500	/	2020-04-28	2021-04-27
SEMT-1076	RF Switcher	Top Precision	RCS03-A2	/	2020-04-28	2021-04-27
SEMT-C001	Cable	Zheng DI	LL142-07-07-10M(A)	/	2020-03-17	2021-03-16
SEMT-C002	Cable	Zheng DI	ZT40-2.92J-2.92J-6M	/	2020-03-17	2021-03-16
SEMT-C003	Cable	Zheng DI	ZT40-2.92J-2.92J-2.5M	/	2020-03-17	2021-03-16
SEMT-C004	Cable	Zheng DI	2M0RFC	/	2020-03-17	2021-03-16
SEMT-C005	Cable	Zheng DI	1M0RFC	/	2020-03-17	2021-03-16
SEMT-C006	Cable	Zheng DI	1M0RFC	/	2020-03-17	2021-03-16



Software List			
Description	Manufacturer	Model	Version
EMI Test Software (Radiated Emission)*	Farad	EZ-EMC	RA-03A1
EMI Test Software (Conducted Emission)*	Farad	EZ-EMC	RA-03A1

*Remark: indicates software version used in the compliance certification testing



2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§2.1091	RF Exposure	Compliant
§15.203;15.247(b)(4)(i)	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§15.207(a)	Conducted Emission	Compliant
§15.247(e)	Power Spectral Density	Compliant
§15.247(a)(2)	DTS Bandwidth	Compliant
§15.247(b)(3)	RF Output Power	Compliant
§15.209(a)	Radiated Emission	Compliant
§15.247(d)	Band Edge (Out of Band Emissions)	Compliant

N/A: Not applicable



3. RF Exposure

3.1 Standard Applicable

According to §1.1307 and §2.1091, the fixed transmitter must comply the RF exposure requirements.

3.2 Test Result

This product complied with the requirement of the RF exposure, please see the RF Exposure Report.



4. Antenna Requirement

4.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

4.2 Evaluation Information

This product has a PCB antenna, fulfill the requirement of this section.



5. Power Spectral Density

5.1 Standard Applicable

According to 15.247(a)(1)(iii), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

5.2 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.4 and ANSI C63.10-2013 Subclause 11.10.3, such specifications require that the same method as used to determine the conducted output power shall also be used to determine the power spectral density. The test method of power spectral density as below:

- a) Set instrument center frequency to DTS channel center frequency.
- b) Set span to at least 1.5 times the OBW.
- c) Set RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set VBW $\geq 3 \times \text{RBW}$.
- e) Detector = power averaging (RMS) or sample detector (when RMS not available).
- f) Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span}/\text{RBW}$.
- g) Sweep time = auto couple.
- h) Employ trace averaging (RMS) mode over a minimum of 100 traces.
- i) Use the peak marker function to determine the maximum amplitude level.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span in order to meet the minimum measurement point requirement as the RBW is reduced).

5.3 Summary of Test Results/Plots




Test Mode	Test Channel MHz	Power Spectral Density dBm/3kHz	Limit dBm/3kHz
802.11b_11Mbps	2412	-17.81	8
	2437	-17.86	8
	2462	-17.77	8
802.11g_54Mbps	2412	-25.14	8
	2437	-24.97	8
	2462	-24.54	8
802.11n-HT20_MCS7	2412	-23.96	8
	2437	-24.45	8
	2462	-23.04	8

Please refer to the following test plots:



<p>802.11b-Low</p>	<p>Ref 0 dBm Att 20 dB RBW 3 kHz Marker 1 [T1] -17.81 dBm VBW 10 kHz SWT 3.4 s 2.412480000 GHz</p> <p>Center 2.412 GHz 3 MHz/ Span 30 MHz</p> <p>Date: 19.MAY.2020 15:54:45</p>
<p>802.11b-Middle</p>	<p>Ref 0 dBm Att 20 dB RBW 3 kHz Marker 1 [T1] -17.86 dBm VBW 10 kHz SWT 3.4 s 2.436100000 GHz</p> <p>Center 2.437 GHz 3 MHz/ Span 30 MHz</p> <p>Date: 19.MAY.2020 15:55:08</p>
<p>802.11b-High</p>	<p>Ref 0 dBm Att 20 dB RBW 3 kHz Marker 1 [T1] -17.77 dBm VBW 10 kHz SWT 3.4 s 2.461340000 GHz</p> <p>Center 2.462 GHz 3 MHz/ Span 30 MHz</p> <p>Date: 19.MAY.2020 15:55:32</p>



<p>802.11g-Low</p>	 <p>Ref 0 dBm Att 20 dB RBW 3 kHz Marker 1 [T1] -25.14 dBm VBW 10 kHz 2.41200000 GHz SWT 3.4 s</p> <p>Center 2.412 GHz 3 MHz/ Span 30 MHz</p> <p>Date: 19.MAY.2020 15:56:00</p>
<p>802.11g-Middle</p>	 <p>Ref 0 dBm Att 20 dB RBW 3 kHz Marker 1 [T1] -24.97 dBm VBW 10 kHz 2.43700000 GHz SWT 3.4 s</p> <p>Center 2.437 GHz 3 MHz/ Span 30 MHz</p> <p>Date: 19.MAY.2020 15:56:15</p>
<p>802.11g-High</p>	 <p>Ref 0 dBm Att 20 dB RBW 3 kHz Marker 1 [T1] -24.54 dBm VBW 10 kHz 2.46200000 GHz SWT 3.4 s</p> <p>Center 2.462 GHz 3 MHz/ Span 30 MHz</p> <p>Date: 19.MAY.2020 15:56:30</p>



<p>802.11n-HT20-Low</p>	<p>Date: 19.MAY.2020 15:56:42</p>
<p>802.11n-HT20-Middle</p>	<p>Date: 19.MAY.2020 15:57:04</p>
<p>802.11n-HT20-High</p>	<p>Date: 19.MAY.2020 15:57:20</p>



6. DTS Bandwidth

6.1 Standard Applicable

According to 15.247(a)(2), systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

6.2 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.2 and ANSI C63.10-2013 Subclause 11.8.1, the test method of DTS Bandwidth as below:

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.


6.3 Summary of Test Results/Plots

Test Mode	Test Channel MHz	6 dB Bandwidth MHz	Limit kHz
802.11b_11Mbps	2412	8.10	≥ 500
	2437	9.00	≥ 500
	2462	8.10	≥ 500
802.11g_54Mbps	2412	16.38	≥ 500
	2437	16.38	≥ 500
	2462	16.38	≥ 500
802.11n-HT20_MCS7	2412	16.92	≥ 500
	2437	16.68	≥ 500
	2462	16.86	≥ 500

Please refer to the following test plots:




802.11b-Low




Date: 19.MAY.2020 16:21:36

802.11b-Middle



Date: 19.MAY.2020 16:22:53


802.11b-High



Date: 19.MAY.2020 16:24:03




802.11g-Low




Date: 19.MAY.2020 16:25:45

802.11g-Middle



Date: 19.MAY.2020 16:35:22


802.11g-High



Date: 19.MAY.2020 16:36:18




802.11n-HT20-Low




Date: 19.MAY.2020 16:37:12

802.11n-HT20-Middle



Date: 19.MAY.2020 16:37:58

802.11n-HT20-High



Date: 19.MAY.2020 16:38:56

7. RF Output Power

7.1 Standard Applicable

According to 15.247(b)(3), for systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt.

7.2 Test Procedure

According to the KDB-558074 D01 v05r02 Subclause 8.3.2.2 and ANSI C63.10-2013 Subclause 11.9.2.2, when this option is exercised, the measured power is to be referenced to the OBW rather than the DTS bandwidth

- a) Set span to at least 1.5 times the OBW.
- b) Set RBW = 1-5% of the OBW, not to exceed 1 MHz.
- c) Set VBW $\geq 3 \times$ RBW.
- d) Number of points in sweep $\geq 2 \times$ span / RBW. (This gives bin-to-bin spacing \leq RBW/2, so that narrowband signals are not lost between frequency bins.)
- e) Sweep time = auto.
- f) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
- g) If transmit duty cycle < 98 %, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle ≥ 98 %, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “free run” .
- h) Trace average at least 100 traces in power averaging (i.e., RMS) mode.
- i) Compute power by integrating the spectrum across the OBW of the signal using the instrument’s band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.

7.3 Summary of Test Results/Plots



Test Mode	Frequency MHz	Reading dBm	Output Power mW	Limit mW
802.11b _ 11Mbps	2412	16.58	45.50	1000
	2437	17.03	50.47	1000
	2462	17.32	53.95	1000
802.11g_54Mbps	2412	13.04	20.14	1000
	2437	13.72	23.55	1000
	2462	14.15	26.00	1000
802.11n HT20_MCS7	2412	13.33	21.53	1000
	2437	13.91	24.60	1000
	2462	13.73	23.60	1000

Please refer to the following test plots:



<p>802.11b-Low 11Mbps</p>	<p>Date: 19.MAY.2020 15:46:30</p>
<p>802.11b-Middle 11Mbps</p>	<p>Date: 19.MAY.2020 15:47:01</p>
<p>802.11b-High 11Mbps</p>	<p>Date: 19.MAY.2020 15:47:27</p>



<p>802.11g-Low 54Mbps</p>	<p>Ref: 20 dBm Att: 30 dB RBW: 300 kHz VBM: 1 MHz SWT: 5 ms</p> <p>Offset: 1 dB</p> <p>Center: 2.412 GHz Span: 30 MHz</p> <p>Tx Channel1 Bandwidth: 20 MHz Power: 13.04 dBm</p> <p>Date: 19.MAY.2020 15:48:06</p>
<p>802.11g-Middle 54Mbps</p>	<p>Ref: 20 dBm Att: 30 dB RBW: 300 kHz VBM: 1 MHz SWT: 5 ms</p> <p>Offset: 1 dB</p> <p>Center: 2.437 GHz Span: 30 MHz</p> <p>Tx Channel1 Bandwidth: 20 MHz Power: 13.72 dBm</p> <p>Date: 19.MAY.2020 15:48:42</p>
<p>802.11g-High 54Mbps</p>	<p>Ref: 20 dBm Att: 30 dB RBW: 300 kHz VBM: 1 MHz SWT: 5 ms</p> <p>Offset: 1 dB</p> <p>Center: 2.462 GHz Span: 30 MHz</p> <p>Tx Channel1 Bandwidth: 20 MHz Power: 14.15 dBm</p> <p>Date: 19.MAY.2020 15:49:23</p>



<p>802.11n-HT20-Low MCS7</p>	<p>Date: 19.MAY.2020 15:50:01</p>
<p>802.11n-HT20-Middle MCS7</p>	<p>Date: 19.MAY.2020 15:50:36</p>
<p>802.11n-HT20-High MCS7</p>	<p>Date: 19.MAY.2020 15:50:56</p>

8. Field Strength of Spurious Emissions

8.1 Standard Applicable


According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).


The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

8.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.





Frequency :9kHz-30MHz
 RBW=10KHz,
 VBW =30KHz
 Sweep time= Auto
 Trace = max hold
 Detector function = peak

Frequency :30MHz-1GHz
 RBW=120KHz,
 VBW=360KHz
 Sweep time= Auto
 Trace = max hold
 Detector function = peak, QP

Frequency :Above 1GHz
 RBW=1MHz,
 VBW=3MHz(Peak), 10Hz(AV)
 Sweep time= Auto
 Trace = max hold
 Detector function = peak, AV

8.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dBμV means the emission is 6dBμV below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$


8.4 Summary of Test Results/Plots

Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported. All test modes (different data rate and different modulation) are performed, but only the worst case is recorded in this report.



➤ Spurious Emissions Below 1GHz


802.11b_11Mbps			
Test Channel	Low	Polarity:	Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	43.8119	34.46	-13.99	20.47	40.00	-19.53	-	-	peak
2	143.8295	38.97	-16.94	22.03	43.50	-21.47	-	-	peak
3	191.0738	42.70	-13.42	29.28	43.50	-14.22	-	-	peak
4	239.9874	42.10	-11.13	30.97	46.00	-15.03	-	-	peak
5	319.9370	44.19	-8.35	35.84	46.00	-10.16	-	-	peak
6	916.0687	30.19	-0.93	29.26	46.00	-16.74	-	-	peak




802.11b_11Mbps			
Test Channel	Low	Polarity:	Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	40.4172	39.35	-14.14	25.21	40.00	-14.79	-	-	peak
2	102.3597	38.36	-14.88	23.48	43.50	-20.02	-	-	peak
3	191.7450	38.16	-13.35	24.81	43.50	-18.69	-	-	peak
4	277.0935	39.44	-9.82	29.62	46.00	-16.38	-	-	peak
5	383.9318	40.56	-7.92	32.64	46.00	-13.36	-	-	peak
6	900.1474	31.31	-1.20	30.11	46.00	-15.89	-	-	peak




802.11b_11Mbps			
Test Channel	Middle	Polarity:	Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	191.7450	42.39	-13.35	29.04	43.50	-14.46	-	-	peak
2	239.9874	45.20	-11.13	34.07	46.00	-11.93	-	-	peak
3	277.0935	45.41	-9.82	35.59	46.00	-10.41	-	-	peak
4	319.9370	45.57	-8.35	37.22	46.00	-8.78	-	-	peak
5	383.9318	45.94	-7.92	38.02	46.00	-7.98	-	-	peak




802.11b_11Mbps			
Test Channel	Middle	Polarity:	Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	36.0007	42.52	-15.70	26.82	40.00	-13.18	-	-	peak
2	111.3468	43.00	-14.89	28.11	43.50	-15.39	-	-	peak
3	191.7450	39.69	-13.35	26.34	43.50	-17.16	-	-	peak
4	277.0935	39.63	-9.82	29.81	46.00	-16.19	-	-	peak
5	383.9318	40.81	-7.92	32.89	46.00	-13.11	-	-	peak
6	480.5276	39.72	-8.05	31.67	46.00	-14.33	-	-	peak




802.11b_11Mbps			
Test Channel	High	Polarity:	Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	191.7450	42.48	-13.35	29.13	43.50	-14.37	-	-	peak
2	239.9874	45.28	-11.13	34.15	46.00	-11.85	-	-	peak
3	277.0935	44.91	-9.82	35.09	46.00	-10.91	-	-	peak
4	319.9370	47.50	-8.35	39.15	46.00	-6.85	-	-	peak
5	383.9318	46.35	-7.92	38.43	46.00	-7.57	-	-	peak
6	896.9965	31.90	-1.34	30.56	46.00	-15.44	-	-	peak



802.11b_11Mbps			
Test Channel	High	Polarity:	Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	43.0505	39.23	-14.02	25.21	40.00	-14.79	-	-	peak
2	191.7450	39.43	-13.35	26.08	43.50	-17.42	-	-	peak
3	277.0935	41.59	-9.82	31.77	46.00	-14.23	-	-	peak
4	383.9318	39.60	-7.92	31.68	46.00	-14.32	-	-	peak
5	480.5276	40.53	-8.05	32.48	46.00	-13.52	-	-	peak

Remark: '-' Means' the test Degree and Height are not recorded by the test software and only show the worst case in the test report.



- Spurious Emissions Above 1GHz
- Test Mode: 802.11b_11Mbps (worst case)

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2412MHz							
4830.157	60.73	-4.50	56.23	74.00	-17.77	H	PK
4830.157	46.70	-4.50	42.20	54.00	-11.80	H	AV
8601.981	55.27	-0.03	55.24	74.00	-18.76	H	PK
8601.981	43.81	-0.03	43.78	54.00	-10.22	H	AV
2410.364	64.24	-9.46	54.78	74.00	-19.22	V	PK
2410.364	58.06	-9.46	48.60	54.00	-5.40	V	AV
4830.157	58.07	-4.50	53.57	74.00	-20.43	V	PK
4830.157	45.08	-4.50	40.58	54.00	-13.42	V	AV
8601.981	55.99	-0.03	55.96	74.00	-18.04	V	PK
8601.981	44.00	-0.03	43.97	54.00	-10.03	V	AV
Middle Channel-2437MHz							
4879.968	59.31	-4.47	54.84	74.00	-19.16	H	PK
4879.968	46.41	-4.47	41.94	54.00	-12.06	H	AV
8601.981	55.76	-0.03	55.73	74.00	-18.27	H	PK
8601.981	44.13	-0.03	44.10	54.00	-9.90	H	AV
2435.221	62.87	-9.41	53.46	74.00	-20.54	V	PK
2435.221	56.88	-9.41	47.47	54.00	-6.53	V	AV
4879.968	60.23	-4.47	55.76	74.00	-18.24	V	PK
4879.968	46.75	-4.47	42.28	54.00	-11.72	V	AV
8601.981	44.07	-0.03	44.04	54.00	-9.96	V	PK
8624.073	56.26	0.01	56.27	74.00	-17.73	V	AV
High Channel-2462MHz							
4930.293	59.67	-4.44	55.23	74.00	-18.77	H	PK
4930.293	46.63	-4.44	42.19	54.00	-11.81	H	AV
8601.981	55.54	-0.03	55.51	74.00	-18.49	H	PK
8601.981	44.22	-0.03	44.19	54.00	-9.81	H	AV
2460.334	62.24	-9.36	52.88	74.00	-21.12	V	PK
2460.334	56.34	-9.36	46.98	54.00	-7.02	V	AV
4930.293	59.93	-4.44	55.49	74.00	-18.51	V	PK
4930.293	46.41	-4.44	41.97	54.00	-12.03	V	AV
8601.981	44.02	-0.03	43.99	54.00	-10.01	V	PK
8624.073	55.54	0.01	55.55	74.00	-18.45	V	AV

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

9. Out of Band Emissions

9.1 Standard Applicable

According to §15.247 (d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

9.2 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.4 and ANSI C63.10-2013 Subclause 11.11, the emissions in nonrestricted frequency bands test method as follows:

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW $\geq [3 \times \text{RBW}]$.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

According to the KDB 558074 D01 v05r02 Subclause 8.5 and ANSI C63.10-2013 Subclause 11.12, the emissions in restricted frequency bands test method as follows:

A. Radiated emission measurements:

Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation (2310MHz to 2420MHz for low bandedge, 2460MHz to 2500MHz for the high bandedge)

RBW = 1MHz, VBW = 1MHz for peak value measured

RBW = 1MHz, VBW = 10Hz for average value measured

Sweep = auto; Detector function = peak/average; Trace = max hold

All the trace to stabilize, set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. Those emission must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement KDB publication number: 913591 may be used for the radiated bandedge measurements.

**B. Antenna-port conducted measurements**

Peak emission levels are measured by setting the instrument as follows:

- a) RBW = as specified in Table 9.
- b) VBW \geq $[3 \times \text{RBW}]$.
- c) Detector = peak.
- d) Sweep time = auto.
- e) Trace mode = max hold.
- f) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be lengthened for low-duty-cycle applications.)

Table 9—RBW as a function of frequency

Frequency	RBW
9 kHz to 150 kHz	200 Hz to 300 Hz
0.15 MHz to 30 MHz	9 kHz to 10 kHz
30 MHz to 1000 MHz	100 kHz to 120 kHz
>1000 MHz	1 MHz

If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.


Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in section 8.1. Report the three highest emissions relative to the limit.

9.3 Summary of Test Results/Plots



➤ Radiated test


802.11b_11Mbps			
Test Channel	Low	Polarity:	Horizontal (worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	43.49	-9.66	33.83	54.00	-20.17	Average Detector
	2310.000	52.76	-9.66	43.10	74.00	-30.90	Peak Detector
2	2390.000	50.26	-9.50	40.76	54.00	-13.24	Average Detector
	2390.000	59.42	-9.50	49.92	74.00	-24.08	Peak Detector
3	2412.720	108.26	-9.46	98.80	/	/	Average Detector
	2413.440	112.76	-9.46	103.30	/	/	Peak Detector




802.11b_11Mbps			
Test Channel	High	Polarity:	Horizontal (worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2461.250	105.56	-9.36	96.20	/	/	Average Detector
	2460.550	109.81	-9.36	100.45	/	/	Peak Detector
2	2483.500	48.59	-9.31	39.28	54.00	-14.72	Average Detector
	2483.500	57.79	-9.31	48.48	74.00	-25.52	Peak Detector
3	2500.000	43.47	-9.28	34.19	54.00	-19.81	Average Detector
	2500.000	54.98	-9.28	45.70	74.00	-28.30	Peak Detector




802.11g_54Mbps			
Test Channel	Low	Polarity:	Horizontal (worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	43.31	-9.66	33.65	54.00	-20.35	Average Detector
	2310.000	53.65	-9.66	43.99	74.00	-30.01	Peak Detector
2	2390.000	57.47	-9.50	47.97	54.00	-6.03	Average Detector
	2390.000	73.81	-9.50	64.31	74.00	-9.69	Peak Detector
3	2413.680	101.70	-9.45	92.25	/	/	Average Detector
	2408.160	111.08	-9.47	101.61	/	/	Peak Detector




802.11g_54Mbps			
Test Channel	High	Polarity:	Horizontal (worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2459.950	98.30	-9.35	88.95	/	/	Average Detector
	2458.150	107.60	-9.36	98.24	/	/	Peak Detector
2	2483.500	50.05	-9.31	40.74	54.00	-13.26	Average Detector
	2483.500	63.41	-9.31	54.10	74.00	-19.90	Peak Detector
3	2500.000	43.60	-9.28	34.32	54.00	-19.68	Average Detector
	2500.000	54.48	-9.28	45.20	74.00	-28.80	Peak Detector




802.11n-HT20_MCS7			
Test Channel	Low	Polarity:	Horizontal (worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	43.28	-9.66	33.62	54.00	-20.38	Average Detector
	2310.000	54.14	-9.66	44.48	74.00	-29.52	Peak Detector
2	2390.000	59.52	-9.50	50.02	54.00	-3.98	Average Detector
	2390.000	78.27	-9.50	68.77	74.00	-5.23	Peak Detector
3	2405.760	101.30	-9.48	91.82	/	/	Average Detector
	2407.440	110.74	-9.47	101.27	/	/	Peak Detector



802.11n-HT20_MCS7			
Test Channel	High	Polarity:	Horizontal (worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2460.350	97.80	-9.36	88.44	/	/	Average Detector
	2457.300	107.60	-9.36	98.24	/	/	Peak Detector
2	2483.500	51.06	-9.31	41.75	54.00	-12.25	Average Detector
	2483.500	66.17	-9.31	56.86	74.00	-17.14	Peak Detector
3	2500.000	43.67	-9.28	34.39	54.00	-19.61	Average Detector
	2500.000	54.38	-9.28	45.10	74.00	-28.90	Peak Detector




➤ Conducted test

802.11b_11Mbps

Low



Date: 19.MAY.2020 16:07:41




Date: 19.MAY.2020 16:08:04




802.11b_11Mbps

Middle



Date: 19.MAY.2020 16:08:46




Date: 19.MAY.2020 16:09:01




802.11b_11Mbps

High



Date: 19.MAY.2020 16:09:47




Date: 19.MAY.2020 16:10:07




802.11g_54Mbps

Low



Date: 19.MAY.2020 16:11:05




Date: 19.MAY.2020 16:11:26




802.11g_54Mbps

Middle



Date: 19.MAY.2020 16:12:14




Date: 19.MAY.2020 16:12:34




802.11g_54Mbps

High



Date: 19.MAY.2020 16:13:30




Date: 19.MAY.2020 16:13:44




802.11n-HT20_MCS7

Low



Date: 19.MAY.2020 16:14:18




Date: 19.MAY.2020 16:14:44




802.11n-HT20_MCS7

Middle



Date: 19.MAY.2020 16:15:33




Date: 19.MAY.2020 16:16:04




802.11n-HT20_MCS7

High



Date: 19.MAY.2020 16:17:01



Date: 19.MAY.2020 16:17:15


10. Conducted Emissions

10.1 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.

10.2 Basic Test Setup Block Diagram



10.3 Test Receiver Setup


During the conducted emission test, the test receiver was set with the following configurations:

- Start Frequency 150 kHz
- Stop Frequency 30 MHz
- Sweep Speed Auto
- IF Bandwidth..... 10 kHz
- Quasi-Peak Adapter Bandwidth 9 kHz
- Quasi-Peak Adapter Mode Normal

10.4 Summary of Test Results/Plots




Test Mode	Communication	AC120V 60Hz	Polarity:	Neutral
-----------	---------------	-------------	-----------	---------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1*	0.1500	40.14	9.95	50.09	65.99	-15.90	QP
2	0.1700	38.21	9.95	48.16	64.96	-16.80	QP
3	0.1700	22.59	9.95	32.54	54.96	-22.42	AVG
4	0.2020	20.34	9.97	30.31	53.52	-23.21	AVG
5	0.2060	34.05	9.97	44.02	63.36	-19.34	QP
6	0.2779	17.28	10.01	27.29	50.88	-23.59	AVG



Test Mode	Communication	AC120V 60Hz	Polarity:	Line
-----------	---------------	-------------	-----------	------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1*	0.1580	33.50	9.95	43.45	65.56	-22.11	QP
2	0.1580	18.55	9.95	28.50	55.56	-27.06	AVG
3	0.1819	17.45	9.96	27.41	54.39	-26.98	AVG
4	0.2060	29.28	9.97	39.25	63.36	-24.11	QP
5	0.2260	16.06	9.99	26.05	52.59	-26.54	AVG
6	0.3740	23.91	10.02	33.93	58.41	-24.48	QP

***** END OF REPORT *****