



Attachment MPE

Type / Model Name : Calf Monitoring System - Collector

Product Description : SRD - Transceiver

Applicant : Futuro Farming GmbH

Address : Franz-Mayer-Strasse 1

93053 Regensburg

GERMANY

Manufacturer : Futuro Farming GmbH

Address : Franz-Mayer-Strasse 1

93053 Regensburg

GERMANY

**Attachment to
Test Report No. :**

T46462-00-04JP

09. December 2020

Date of issue



Deutsche
Akkreditierungsstelle
D-PL-12030-01-01
D-PL-12030-01-02

Contents

1	<u>SAR Test Exclusion Threshold calculation - FCC</u>	<u>3</u>
2	<u>RF Exposure – Exemption Limits - ISED</u>	<u>4</u>

1 SAR Test Exclusion Threshold calculation - FCC

Portable use

The calculation is done according to:
KDB 447498 D01 General RF Exposure Guidance v06

Calculation formula according to KDB 447498 D01 Part 4.3.1a)

$$(\text{max power of transmitter [mW]}) \div (\text{min. test separation distance [mm]}) \times (\sqrt{\text{TX frequency [GHz]}}) \leq 3.0$$

Calculation :

Max power ¹ [mW]	Separation distance ² [mm]	TX frequency ³ [GHz]	Result	Limit	verdict
24	30	0.928	0.8	3.0	Requirement fulfilled

¹maximum peak conducted power of the transmitter according test report T46462-00-04JP, page 19 clause 5.3.5

²minimum separation distance according to manufacturers declaration

³maximum transmission frequency according to T46462-00-04JP, page 4 clause 2.5 channel plan

Mobile use

Calculation Formula

$$S = \frac{EIRP}{4\pi R^2}$$

EIRP = maximum conducted outputpower + antenna gain

Limit for S < 1 mW/cm²

Max power ¹ [mW]	Max antenna gain ² [dB]	Evaluation distance R [cm]	Result for S [mW/cm ²]	Limit [mW/cm ²]	verdict
24	4.0	20	0.02	1.0	Requirement fulfilled

¹maximum peak conducted power of the transmitter according test report T46462-00-04JP, page 19 clause 5.3.5

²antenna gain according to manufactuerers declaration

³maximum transmission frequency according to T46462-00-04JP, page 4 clause 2.5 channel plan

2 RF Exposure – Exemption Limits - ISED

The calculation is done according to:
RSS-102 Issue 5, March 2015

Calculation of EIRP:

Max power conducted ¹ [mW]	Antenna gain ² [dB]	Antenna gain ² (Factor)	Max power EIRP [mW]	Separation distance ³ [mm]
24	4.0	2.51	60.3	30

¹maximum peak conducted power of the transmitter according test report T46462-00-04JP, page 19 clause 5.3.5

²antenna gain according to manufactuerers declaration

³minimum separation distance according to manufacturers declaration

Comparission with Exemtion limits according to Table 1 of RSS-102

TX frequency ¹ [MHz]	Max power EIRP [mW]	Applicable exemption limit ² [mW]	verdict
928	60.3	99	Requirement fullfilled

¹maximum transmission frequency according to T46462-00-04JP, page 4 clause 2.5 channel plan

²aplicable exemption limit according to RSS-102 issue 5 table 1, no interpolation was made for the frequency.
Instead next highest frequency in table 1 was used.