

# Wireless Charger User Guide



Model:TD01

## Thank you for purchasing and using this product!

Please read this Operation Instruction carefully and keep it properly before using this product.

### Product Specification

Fast Wireless Charger  
Input:  
5V, 2A/9V, 2A/12V, 1.67A  
Output:  
5W/10W/15W  
Charging Efficiency:70%

### Applicable Devices

Compatible with all devices with Qi Standard  
For all other mobiles without Qi Standard, those will be working with wireless receivers.



## ⚠ The LED light turns red during wireless charging to indicate a charging failure.

The following situation can cause failures, like charging slowly, stop charging, over-temperature for charging position

1. The adapter is not run up to standard (No PC USB output power supply).
2. The charging cable is not up to standard.
3. The phone case is too thick ( within 2mm thickness phone case recommended ).
4. The built-in wireless charging receiver position is not coincided with wireless charger coil position.
5. There is metal/magnet on the back of cell phone or phone case.
6. Smartphone does not support wireless charging function.

## ⚠ Attention

1. Please keep the charger away from water or other liquid.
2. If you need to clean the charger, please make sure it is not connected to power supply.
3. Using Environment temperature remains -20~45°C.

## Fingering Installation Steps

1. 3 m Double-sided paper torn



2. Stick the fingers in the middle of the phone coil and clean the surface of the phone before bonding to make the two more secure.



## Step to install air vent

1. Follow the arrows to install 3 parts.



2. Adjust the screw cap to the optimal active state .



3. Press and hold the lock switch open to insert the bracket into the air outlet and loosen the lock switch to lock the air outlet. (\* Lock not too strong to avoid damage to support and outlet strips) .



## Step to Use wireless charger

1. Input: The TYPEC connection line is connected to the device, and the finger button cell phone has been installed into the TX slot to charge the state. (\* QC3.0 adapter is recommended to avoid incompatibility with the device)



## Fingering Installation Steps

# 车载无线快充使用说明



型号:TD01

## 感谢您购买和使用此产品!

请仔细阅读本操作说明，并在使用前妥善保管

### 产品规格

快速无线充电器  
输入:  
5V, 2A/9V, 2A/12V, 1.67A  
输出:  
5W/10W/15W  
充电效率: 70%

### 适用装配

本产品兼容Qi标准的所有移动通讯设备。



## ⚠ 无线充工作状态

以下情况可能导致故障，如充电慢，停止充电，充电区域温度过高等。

- 1.适配器不符合标准/适配器与产品不兼容。
- 2.充电电缆不合格。
- 3.手机外壳偏厚 (推荐厚度2MM以内)
- 4.内置无线充电器线圈位置与无线发射充电器位置不一致。
- 5.手机背面有金属/磁铁。
- 6.手机本身不支持无线充电功能。

## ⚠ 注意

- 1.请将充电器原理水或其它液体
- 2.如果您需要清洁充电器，请确保它没有与电源连接。
- 3.使用环境温度为-20~45°C。

## 手指扣安装步骤

- 1.撕去3M离型纸。




- 2.将手指扣粘贴在手机线圈中间。(请在粘合前清洁手机表面，让两者更加牢固)



## 充电器安装步骤

- 1.按照箭头安装3部分。



- 1.将螺帽调整到最佳活动状态。



- 3.按下支架固定开关打开，将托架插入空气出风口，并松开固定开关锁住出风口 (\*锁紧不可用力过丈，避免损坏支架或出风口条)



## 使用无线充电器步骤

- 1.输入: 将TYPEC连接线连接到设备上，并将安装手指扣的手机出入TX卡槽内进行充电。( \*建议使用QC3.0适配器，避免与此产品识别不兼容)



7## † o  
#

u  
# " h 7## k u  
u

= @

- - k  
- - @  
- - #

- - # ut

u \ two conditions:  
(1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.