

No.: AJT250402021E-1

Applicant Name: GUANGDONG HENGDI TECHNOLOGY CORP.,LTD.

BUILDING C, JINHUI INDUSTRIAL BUILDING, SOUTH OF YUTING Applicant Address:

ROAD, EAST OF TAIAN ROAD, CHENGHAI DISTRICT, SHANTOU

CITY, GUANGDONG PROVINCE, CHINA

Manufacturer: GUANGDONG HENGDI TECHNOLOGY CORP.,LTD.

BUILDING C, JINHUI INDUSTRIAL BUILDING, SOUTH OF YUTING Manufacturer Address:

ROAD, EAST OF TAIAN ROAD, CHENGHAI DISTRICT, SHANTOU

CITY, GUANGDONG PROVINCE, CHINA

The following samples were submitted and identified by/on behalf of the client as:

Sample Description: **RC TOY** Model No.: 2411SE

Additional Model: Please refer to page 4 FCC ID: 2AWZK-2411SETX Sample Received Date: 02 April, 2025 **Testing Completed Date:** 18 June, 2025

Tests conducted: For compliance with application, refer to attached page(s) for details.

Assess standard used:	Conclusion
FCC Part 15, Subpart C, Section 15.249 & ANSI C63,10-2013	PASS

Reviewed by: Fly Living Approved by: Position:

Date

This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Disagreement against this test report, if any, should be filed with to our company in writing within 15 days of receiving the report. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission.

AJT TESTING SERVICES LIMITED

Add: 1-2/F., No.1, Wenhua South Road, Chenghua Industrial Zone, Chenghai District, Shantou, Guangdong, China Tel: 86-754-85860999 Fax: 86-754-86984098

Page



No.: AJT250402021E-1

TABLE OF CONTENTS

1 Test Standards	3
2 Summary	3
2.1 Géneral Remarks	3
2.2 Final Assessment	3
3 Equipment Under Test	
3.1 Short description of the Equipment Under Test (EUT)	4
3.2 EUT Configuration	5
3.3 Description of Test Modes	5
3.3 Description of Test Modes	7
4.1 Address of the test Laboratory	7
4.2 Environmental Conditions	7
4.3 Statement of the Measurement Uncertainty	7
4.4 Test Types and Results	8
5 Test Conditions and Results	9
5.1 Radiated Emission (RE)	9
5.2 20dB Bandwidth	22
5.3 Conducted Emission (CE)	25
5.4 Antenna Requirements	26
6 Test Equipment	27
7 Test Photographs	28
8 Photos of the EUT	28
9 Manufacturer/ Approval Holder Declaration	28

This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Disagreement against this test report, if any, should be filed with to our company in writing within 15 days of receiving the report. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission.



No.: AJT250402021E-1

1 Test Standards

The tests were performed according to following standards:

FCC Part 15, Subpart C, Section 15.249: Operation within the bands 902-928 MHz, 2400-2483.5 MHz, 5725-5875 MHZ, and 24.0-24.25 GHz

ANSI C63,10-2013: American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

2 Summary

2.1 General Remarks

Date of receipt of test sample	02 April, 2025
Testing commenced on	02 April, 2025 18 June, 2025
Testing concluded on	18 June, 2025

2.2 Final Assessment

Test Content:	Assessment	
The RF requirements pertaining to the technical standards and tested operation modes are	Fulfilled	
The equipment under test	Fulfilled the RF requirements	



No.: AJT250402021E-1

3 Equipment Under Test

3.1 Short description of the Equipment Under Test (EUT)

EUT Name	RC TOY
Model No.	2411SE
2306SE, 2308SE, 2316SE, 2418SE, 2411, 2411W, 2411S, 2301, 2303, 2305, 2306, 2308, 2310, 2313, 2314, 2316W, 2316DW, 2320, 2323, 2202, 2205, 2205D, 2209H 2106, 2106S, 2003, 2013, 1336, 1340, 1303, 1343A, H20, H24, H26, H36, H65, HQ051, HQ051S, HQ052, HQ0 HQ056, HQ057, HQ058, BD101, BD102, 2008A, 2101, 2201, 2420, 2008B, 2213, 2401, 2409-1, 2409-2, 2409-4, 1906S, 1906, 1902, 1903, 2416, 1915, 1905-1, 1905-2, DB3-1, DB1-2, DB2-3, DB2-4, DB2-5, 1801SE, 2501, 2502, 2504, 2505, 2506, 2507, 2508, 2509, 2510, 40037, 2103, ODY-1026, ODY-01SI, ODY-02SI, ODY-03SI, ODY-1208, ODY-1208WT, ODY-1012BR, ODY-1956	
FCC ID	2AWZK-2411SETX
Power Supply Voltage	Controller Unit: DC 6.0V(AA*4)
Operating Mode	TX Mode
Operation Frequency	2410-2470MHz
Number of Channel	61
Modulation	GFSK
Antenna Type	Wire Antenna
Antenna Gain	0dBi
Max. RF output power:	87.76 dBµV/m@3m
NOTE	

NOTE

- 1. The above EUT information is declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or user's manual. The laboratory is not responsible for the accuracy of the information provided by manufacturer.
- 2. 2.Only the model 2411SE was tested, since according to the declaration from the applicant, the electrical circuit design, PCB layout, components used and internal wiring and functions were identical for the above model, with only difference on color, appearance and packaging.

This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Disagreement against this test report, if any, should be filed with to our company in writing within 15 days of receiving the report. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission.



No.: AJT250402021E-1

3.2 EUT Configuration

(The CDF filled by the applicant can be viewed at the test laboratory.) The following peripheral devices and interface cables were connected during the measurement:

EUT

3.3 Description of Test Modes

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and packet type. The worst case was found when the EUT was

positioned on Y axis for radiated emission. The EUT was tested under the following mode.

ELIT Configure Mode		Applicable	to		Description	
EUT Configure Mode	RE < 1G	RE≥1G	PLC	BW	Controller Unit: DC 6.0V(AA*4)	
Α	V	√	N/A	V	Controller Offit. DC 6.0V(AA 4)	

Where RE<1G: Radiated Emission below 1GHz RE≥1G: Radiated Emission above 1GHz

BW: 20dB bandwidth PLC: Power Line Conducted Emission

Following channel(s) was (were) selected for the test as listed below.

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2410	17	2426	33	2442	49	2458
2	2411	18	2427	34	2443	50	2459
3	2412	19	2428	35	2444	51	2460
4	2413	20	2429	36	2445	52	2461
5	2414	21	2430	37	2446	53	2462
6	2415	22	2431	38	2447	54	2463
7	2416	23	2432	39	2448	55	2464
8	2417	24	2433	40	2449	56	2465
9	2418	25	2434	41	2450	57	2466
10	2419	26	2435	42	2451	58	2467
11	2420	27	2436	43	2452	59	2468
12	2421	28	2437	44	2453	60	2469
13	2422	29	2438	45	2454	61	2470
14	2423	30	2439	46	2455		
15	2424	31	2440	47	2456	<	-3'Y
16	2425	32	2441	48	2457) * .	

This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Disagreement against this test report, if any, should be filed with to our company in writing within 15 days of receiving the report. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission.



No.: AJT250402021E-1

Channel	Frequency (MHz)
The lowest channel	2410
The middle channel	2440
The highest channel	2470

Note: The more detailed channel, please refer to the product specifications



No.: AJT250402021E-1

4 Test Environment

4.1 Address of the test Laboratory

Test Laboratory:	AJT Testing Services Limited
Test Site:	1-2/F., NO.1, WENHUA SOUTH ROAD, CHENGHUA INDUSTRIAL ZONE, CHENGHAI DISTRICT, SHANTOU, GUANGDONG, CHINA
Tel:	86-754-85860999
Fax:	86-754-86984098

4.2 Environmental Conditions

During the measure	ment the environmental conditions were within the listed ranges:
Temperature	15~35℃
Humidity	30~75%

4.3 Statement of the Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there June be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. Furthermore, component and process variability of devices are similar to that tested June result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Measurement Uncertainty (S	Standard: ETSI TR 100 028)
Conducted Emission (CE)	±2.14dB
Radiated Emission below 1GHz	±4.44dB
Radiated Emission above 1GHz	±5.26dB
Occupied bandwidth	55.4kHz

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Disagreement against this test report, if any, should be filed with to our company in writing within 15 days of receiving the report. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission.



No.: AJT250402021E-1

4.4 Test Types and Results

Stand	ard: FCC PART 15, SUBPART C (SECTION 15.249)	
Standard section	Test Type Result	
§15.209 & §15.249(a)	Radiated Emission (RE)	PASS
§15.215(c)	20dB Bandwidth	PASS
§15.207(a)	Conducted Emission (CE)	N/A
§15.203	Antenna Requirement	PASS
§15.205	Restricted Band Around Fundamental Frequency	PASS



No.: AJT250402021E-1

5 Test Conditions and Results

5.1 Radiated Emission (RE)

For test instruments and accessories used see section 6

5.1.1 Test Procedures

- (1) The EUT was placed on the top of a rotating table 1.5 meters (above 1GHz) and 0.8 meters (below 1GHz) above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- (2) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- (3) The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- (4) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- (5) The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- (6) For below 30MHz, a loop antenna with its vertical plane is place 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1m above the ground.
- (7) If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.


Note:

- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz
- 2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
- 3. All modes of operation were investigated and the worst-case emissions are reported
- 4. The testing of the EUT was performed on all 3 orthogonal axes; the worst-case test configuration was reported on the file test setup photo.


5.1.2 Test Setup



No.: AJT250402021E-1



Below 30MHz



30MHz-1000MHz


This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Disagreement against this test report, if any, should be filed with to our company in writing within 15 days of receiving the report. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission.

AJT TESTING SERVICES LIMITED

Add: 1-2/F., No.1, Wenhua South Road, Chenghua Industrial Zone, Chenghai District, Shantou, Guangdong, China Tel: 86-754-8586099 Fax: 86-754-86984098 Website: www.ajtesting.com Email: info@ajtesting.com



No.: AJT250402021E-1



Above 1GHz

This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Disagreement against this test report, if any, should be filed with to our company in writing within 15 days of receiving the report. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission.

AJT TESTING SERVICES LIMITED

Add: 1-2/F., No.1, Wenhua South Road, Chenghua Industrial Zone, Chenghai District, Shantou, Guangdong, China Tel: 86-754-8586099 Fax: 86-754-86984098 Website: www.ajtesting.com Email: info@ajtesting.com



No.: AJT250402021E-1

5.1.3 Test Limits

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

3.203 as following.		
Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

According to §15.249(a), the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental Frequency	Filed Strength of Fundamental (milli-volts/meter)	Field Strength of Harmonics (micro-volts/meter)		
902 ~ 928 MHz	50	500		
2400 ~ 2483.5 MHz	50	500		
5725 ~5875 MHz	50	500		
24.0 ~24.25 GHz	250	2500		

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply.

Note

- 1. The lower limit shall apply at the transition frequencies.
- 2. Emission level (dB μ V/m) = 20 log Emission level (μ V/m).
- 3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.
- 4. Emission from 9kHz to 30MHz is more than 20dB below the limit.



No.: AJT250402021E-1

5.1.4 Test Results

The disturbance below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.

5.1.4.1 Radiated Emissions Test (Below 1GHz)

Operation Mode	TX mode
Channel	The Lowest Channel (2410MHz)
Test Condition	Ambient Temperature: 24°C Humidity: 58%RH

Frequency (MHz)	Emission Level (dBµV/m)	QP Lim. (dBµV/m)	Margin (dB)	Angle (°)	Height (m)	Polarization
41.64	17.21	40.00	-22.79	19.00	1.48	Horizontal
101.683	15.21	43.50	-28.29	46.00	1.48	Horizontal
345.25	21.19	46.00	-24.81	6.00	1.48	Horizontal
504.427	23.31	46.00	-22.69	303.00	1.48	Horizontal
647.987	26.77	46.00	-19.23	86.00	1.48	Horizontal
835.876	28.74	46.00	-17.26	229.00	1.48	Horizontal
53.571	17.44	40.00	-22.56	297.00	1.50	Vertical
102.75	15.73	43.50	-27.77	78.00	1.50	Vertical
346.123	20.57	46.00	-25.43	251.00	1.50	Vertical
474.648	23.05	46.00	-22.95	120.00	1.50	Vertical
647.987	27.15	46.00	-18.85	177.00	1.50	Vertical
808.716	28.08	46.00	-17.92	177.00	1.50	Vertical

^{1.}QP is abbreviation of Quasi-Peak

This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Disagreement against this test report, if any, should be filed with to our company in writing within 15 days of receiving the report. Any copying or replication of this report to or for any other person or entity, or use of our manner or taken are in the control of the control of


^{2.}Margin = Emission Level - Limit Value

^{3.} The emission levels of other frequencies were more than 20dB margin against the limit




No.: AJT250402021E-1

Test Graph:



Horizontal





No.: AJT250402021E-1

5.1.4.2 Radiated Emissions Test (Above 1GHz)

Channel	The Lowest Channel (2410MHz)	Detector Function	Peak (PK) Average (AV)
Frequency Range	Above 1GHz	Result	PASS


	Antenna Polarity & Test Distance: Horizontal At 3m							
Frequency (MHz)	Emission Level (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (m)	Angle (°)	Polarization	Correction (dB)	Detector
2400	4.07	54.00	-49.93	1.52	248.00	Horizontal	-36.33	Average
*2409.96	51.22	94.00	-42.78	1.52	205.00	Horizontal	-36.33	Average
4820.5	14.90	54.00	-39.10	2.00	226.00	Horizontal	-36.33	Average
7229.8	16.97	54.00	-37.03	1.01	67.00	Horizontal	-36.33	Average
2400	40.40	74.00	-33.60	1.52	248.00	Horizontal	-2.83	Peak
*2409.96	87.55	114.00	-26.45	1.52	205.00	Horizontal	-2.74	Peak
4820.5	51.23	74.00	-22.77	2.00	226.00	Horizontal	2.81	Peak
7229.8	53.30	74.00	-20.70	1.01	67.00	Horizontal	9.27	Peak
		Antenna Po	larity & T	est Dista	nce: Verti	cal At 3m		
Frequency (MHz)	Emission Level (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (m)	Angle (°)	Polarization	Correction (dB)	Detector
2400	4.03	54.00	-49.97	1.48	78.00	Vertical	-36.33	Average
*2409.96	51.15	94.00	-42.85	1.48	73.00	Vertical	-36.33	Average
4820.5	15.10	54.00	-38.90	1.99	328.00	Vertical	-36.33	Average
7229.8	17.68	54.00	-36.32	1.99	274.00	Vertical	-36.33	Average
2400	40.36	74.00	-33.64	1.48	78.00	Vertical	-2.83	Peak
*2409.96	87.48	114.00	-26.52	1.48	73.00	Vertical	-2.74	Peak
4820.5	51.43	74.00	-22.57	1.99	328.00	Vertical	2.81	Peak
7229.8	54.01	74.00	-19.99	1.99	274.00	Vertical	9.27	Peak


Remarks

- 1. Emission level (dBµV/m) = Raw Value (dBµV) + Correction Factor (dB/m)
- 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
- 3. The emission levels of other frequencies were more than 20dB margin against the limit.
- 4. Margin = Emission level Limit value
- 5. " * ": Fundamental frequency.
- 6. The average value of fundamental frequency is: Average value = Peak value +AV factor, where the AV factor is calculated from following formula: AV factor=20 log (Duty cycle) = 20 log (1.5%) = -36.33dB, please see 5.1.4.3.



No.: AJT250402021E-1





This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Disagreement against this test report, if any, should be filed with to our company in writing within 15 days of receiving the report. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission.

AJT TESTING SERVICES LIMITED

Add: 1-2/F., No.1, Wenhua South Road, Chenghua Industrial Zone, Chenghai District, Shantou, Guangdong, China Tel: 86-754-8586099 Fax: 86-754-86984098 Website: www.ajtesting.com Email: info@ajtesting.com



No.: AJT250402021E-1

Channel	The Middle Channel (2440MHz)	Detector Function	Peak (PK) Average (AV)
Frequency Range	Above 1GHz	Result	PASS

	A	Antenna Pol	arity & Te	st Distan	ce: Horizo	ontal At 3m		
Frequency (MHz)	Emission Level (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (m)	Angle (°)	Polarization	Correction (dB)	Detector
*2439.9965	49.69	94.00	-44.31	1.52	205.00	Horizontal	-36.33	Average
4880.8	11.72	54.00	-42.28	1.98	219.00	Horizontal	-36.33	Average
7319.8	7.78	54.00	-46.22	1.98	83.00	Horizontal	-36.33	Average
*2439.9965	86.02	114.00	-27.98	1.52	205.00	Horizontal	-2.97	Peak
4880.8	48.05	74.00	-25.95	1.98	219.00	Horizontal	2.09	Peak
7319.8	44.11	74.00	-29.89	1.98	83.00	Horizontal	9.20	Peak
		Antenna Po	larity & T	est Dista	nce: Verti	cal At 3m		
Frequency (MHz)	Emission Level (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (m)	Angle (°)	Polarization	Correction (dB)	Detector
*2439.9965	50.07	94.00	-43.93	1.48	80.00	Vertical	-36.33	Average
4879.9	12.69	54.00	-41.31	1.00	249.00	Vertical	-36.33	Average
7319.8	8.20	54.00	-45.80	1.99	149.00	Vertical	-36.33	Average
*2439.9965	86.40	114.00	-27.60	1.48	80.00	Vertical	-2.97	Peak
4879.9	49.02	74.00	-24.98	1.00	249.00	Vertical	2.10	Peak
7319.8	44.53	74.00	-29.47	1.99	149.00	Vertical	9.20	Peak

Remarks:

- 1. Emission level $(dB\mu V/m) = Raw Value (dB\mu V) + Correction Factor (dB/m)$
- 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
- 3. The emission levels of other frequencies were more than 20dB margin against the limit.
- 4. Margin = Emission level Limit value
- 5. " * ": Fundamental frequency.
- 6. The average value of fundamental frequency is: Average value = Peak value +AV factor, where the AV factor is calculated from following formula: AV factor=20 log (Duty cycle) = 20 log (1.5%) = -36.33dB, please see 5.1.4.3.

This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Disagreement against this test report, if any, should be filed with to our company in writing within 15 days of receiving the report. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission.



No.: AJT250402021E-1

Channel	The Highest Channel (2470MHz)	Detector Function	Peak (PK) Average (AV)
Frequency Range	Above 1GHz	Result	PASS

	P	Antenna Pola	arity & Te	st Distan	ce: Horizo	ontal At 3m		
Frequency (MHz)	Emission Level (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (m)	Angle (°)	Polarization	Correction (dB)	Detector
*2470	46.57	94.00	-47.43	1.50	233.00	Horizontal	-36.33	Average
2483.5	2.95	54.00	-51.05	1.50	231.00	Horizontal	-36.33	Average
4940.2	11.98	54.00	-42.02	1.98	34.00	Horizontal	-36.33	Average
7409.8	17.79	54.00	-36.21	1.01	320.00	Horizontal	-36.33	Average
*2470	82.90	114.00	-31.10	1.50	233.00	Horizontal	-2.92	Peak
2483.5	39.28	74.00	-34.72	1.50	231.00	Horizontal	-3.03	Peak
4940.2	48.31	74.00	-25.69	1.98	34.00	Horizontal	2.36	Peak
7409.8	54.12	74.00	-19.88	1.01	320.00	Horizontal	9.39	Peak
		Antenna Po	larity & T	est Dista	nce: Verti	cal At 3m		
Frequency (MHz)	Emission Level (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (m)	Angle (°)	Polarization	Correction (dB)	Detector
*2470	51.43	94.00	-42.57	1.48	276.00	Vertical	-36.33	Average
2483.5	2.93	54.00	-51.07	1.48	212.00	Vertical	-36.33	Average
4940.2	13.60	54.00	-40.40	1.00	211.00	Vertical	-36.33	Average
7409.8	17.74	54.00	-36.26	1.99	310.00	Vertical	-36.33	Average
*2470	87.76	114.00	-26.24	1.48	276.00	Vertical	-2.92	Peak
2483.5	39.26	74.00	-34.74	1.48	212.00	Vertical	-3.03	Peak
4940.2	49.93	74.00	-24.07	1.00	211.00	Vertical	2.36	Peak
7409.8	54.07	74.00	-19.93	1.99	310.00	Vertical	9.39	Peak

Remarks

- 1. Emission level $(dB\mu V/m) = Raw Value (dB\mu V) + Correction Factor (dB/m)$
- 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
- 3. The emission levels of other frequencies were more than 20dB margin against the limit.
- 4. Margin = Emission level Limit value
- 5. " * ": Fundamental frequency.
- 6. The average value of fundamental frequency is: Average value = Peak value +AV factor, where the AV factor is calculated from following formula: AV factor=20 log (Duty cycle) = 20 log (1.5%) = -36.33dB, please see 5.1.4.3.


This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Disagreement against this test report, if any, should be filed with to our company in writing within 15 days of receiving the report. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission.

AJT TESTING SERVICES LIMITED

Add: 1-2/F., No.1, Wenhua South Road, Chenghua Industrial Zone, Chenghai District, Shantou, Guangdong, China Tel: 86-754-85860999 Fax: 86-754-86984098 Website: www.ajtesting.com Email: info@ajtesting.com



No.: AJT250402021E-1



This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Disagreement against this test report, if any, should be filed with to our company in writing within 15 days of receiving the report. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission.

AJT TESTING SERVICES LIMITED

Add: 1-2/F., No.1, Wenhua South Road, Chenghua Industrial Zone, Chenghai District, Shantou, Guangdong, China Tel: 86-754-85860999 Fax: 86-754-86984098 Website: www.ajtesting.com Email: info@ajtesting.com



No.: AJT250402021E-1

5.1.4.3 Calculation of Average Factor


Effective period of the cycle = 0.203ms

The duration of one cycle = 13.31ms

Duty Cycle = 0.203ms /13.31ms = 1.5%

Averaging factor in dB = 20 log (duty cycle) = 20 log (1.5%) = -36.33dB

100ms Duty Cycle



This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Disagreement against this test report, if any, should be filed with to our company in writing within 15 days of receiving the report. Any copying or replication of this report to or for any other person or entity, or use of our name of takenary, is permitted only with our prior written permission.

AJT TESTING SERVICES LIMITED

Add: 1-2/F., No.1, Wenhua South Road, Chenghua Industrial Zone, Chenghai District, Shantou, Guangdong, China Tel: 86-754-85860999 Fax: 86-754-86984098 Website: www.ajtesting.com Email: info@ajtesting.com




No.: AJT250402021E-1

Ton of one cycle



The duration of one cycle



This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Disagreement against this test report, if any, should be filed with to our company in writing within 15 days of receiving the report. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission.



No.: AJT250402021E-1

5.2 20dB Bandwidth

For test instruments and accessories used see section 6

5.2.1 Test Procedures

- (1) Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- (2) Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- (3) Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
- (4) Repeat above procedures until all frequencies measured were complete.

5.2.2 Test Setup

Spectrum Analyzer	—	Attenuator	1	EUT and Assistant System	-	DC Power

5.2.3 Test Limits

According to FCC 15.215(c), must be designed to ensure that the 20dB bandwidth of the emission, or whatever bandwidth June otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

5.2.4 Test Results


Channel	frequency (MHz)	20dB Bandwidth (MHz)
The lowest channel	2410	1.167
The middle channel	2440	1.183
The highest channel	2470	1.161



No.: AJT250402021E-1



2410MHz



2440MHz

This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Disagreement against this test report, if any, should be filed with to our company in writing within 15 days of receiving the report. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission.

AJT TESTING SERVICES LIMITED

Add: 1-2/F., No.1, Wenhua South Road, Chenghua Industrial Zone, Chenghai District, Shantou, Guangdong, China Tel: 86-754-85860999 Fax: 86-754-86984098 Website: www.ajtesting.com Email: info@ajtesting.com



No.: AJT250402021E-1



2470MHz

This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Disagreement against this test report, if any, should be filed with to our company in writing within 15 days of receiving the report. Any copying or replication of this report to or for any other person or entity, or use of our name or rademark, is permitted only with our prior written permission.

AJT TESTING SERVICES LIMITED

Add: 1-2/F., No.1, Wenhua South Road, Chenghua Industrial Zone, Chenghai District, Shantou, Guangdong, China Tel: 86-754-8586099 Fax: 86-754-86984098 Website: www.ajtesting.com Email: info@ajtesting.com



No.: AJT250402021E-1


5.3 Conducted Emission (CE)

For test instruments and accessories used see section 6

5.3.1 Test Procedures

The PC Power connected to the power mains through a line impedance stabilization network (L.I.S.N.#2). This provides a 50 ohm coupling impedance for the EUT. Please refer the block diagram of the test setup and photographs. The other peripheral devices power cord connected to the power mains through a line impedance stabilization network (L.I.S.N.#1). Power on the PC and let it work normally, we use a keyboard test software, let EUT working in test mode, then test it. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10-2013 on Conducted Emission Test.

5.3.2 Test Setup



This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Disagreement against this test report, if any, should be filed with to our company in writing within 15 days of receiving the report. Any copying or replication of this report to or for any other person or entity, or use of our name of takenary, is permitted only with our prior written permission.

AJT TESTING SERVICES LIMITED

Add: 1-2/F., No.1, Wenhua South Road, Chenghua Industrial Zone, Chenghai District, Shantou, Guangdong, China Tel: 86-754-85860999 Fax: 86-754-86984098 Website: www.ajtesting.com Email: info@ajtesting.com



No.: AJT250402021E-1

5.3.3 Test Limits

Standard: FCC Part 15 §15.207(a)							
(NALL=)	Maximum RF Line Voltage						
Frequency of emission (MHz)	Quasi-Peak Level dB(μV)	Average Level dB(μV)					
0.15-0.5	66 to 56*	56 to 46*					
0.5-5	56	46					
5-30	60	50					

Notes: 1. * Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.

5.3.4 Test Results

Not Applicable

Note: The device is a DC power supply and does not apply to conducted emissions.

5.4 Antenna Requirements

5.4.1 Test Standard:

FCC Part 15, Subpart C 15.203

5.4.2 Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer June design the unit so that a broken antenna can be replaced by the user. but the use of a standard antenna jack or electrical connector is prohibited.

5.4.3 EUT Antenna:

The antenna is Wire antenna and no consideration of replacement. The best case gain of the antenna is 0dBi. Antenna location: Refer to Internal Photos.



No.: AJT250402021E-1

6 Test Equipment

Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
1	Spectrum Analyzer	Keysight	N9010A	MY51120099	2025/02/17	2026/02/16
2	JS0806-2 RF Control Unit	Tonscend	JS0806-2	188060124	2024/08/07	2025/08/07
3	Broadband Preamplifier	SCHWARZBECK	BBV 9743B	00067	2025/02/17	2026/02/16
4	Broadband Preamplifier	SCHWARZBECK	BBV 9718B	00002	2025/02/17	2026/02/16
5	EMI Test Receiver	ROHDE & SCHWARZ	ESR3	102452	2025/02/17	2026/02/16
6	Trilog Broadband Antenna	SCHWARZBECK	VULB 9163	01127	2025/03/11	2026/03/10
7	Horn Antenna	SCHWARZBECK	BBHA 9120D	01829	2025/03/11	2026/03/10
8	DC Power Supply	SIGLENT	SPD1168X	SPD1XEAD3 R 0167	2025/02/20	2026/02/09
9	Vector Signal Generator	Keysight	N5172B	MY53052255	2025/02/17	2026/02/16
10	Analog Signal Generator	Keysight	N5171B	MY53051692	2025/02/17	2026/02/16
11	Temperature Humidity Chamber	Yiheng	BPS-50CB	191005684	2025/02/17	2026/02/16
12	Temperature and Humidity Indicator	JianDaRenKe	Cos-03	612058	2024/07/08	2025/07/08
13	BAT-EMC Testing (Test Software)	NEXIO	Version: 3.19.1.20	N/A	N/A	N/A
14	JS1120-3 Test System (Test Software)	Tonscend	JS1120-3	Version: 2.6.88.0341	N/A	N/A
15	Active Loop Antenna	HRTY	HR8913A	69331322060 23	2024/07/19	2025/07/19



No.: AJT250402021E-1

7 Test Photographs

Referring to – "Test Setup Photos of AJT250402021P-3".

8 Photos of the EUT

Referring to - "External Photos of AJT250402021P-1" and "Internal Photos of AJT250402021P-2".

9 Manufacturer/ Approval Holder Declaration

The following identical model(s):

N/A

Belong to the tested device:

Sample Description: remote control car

Model No.: LS-X6A-TBX

END OF TEST REPORT