

Product Name: Smart Phone	Report No: ITEZA2-202500034RF2
Product Model: Blade20 Turbo, Blade20 Max, Blade20 Play, Blade20 Pro Max, Blade20 Power, Blade20 Plus, Blade20 Energy, Blade20 Pro Energy, Blade20 Ultra Energy, Blade20 Max Energy, Blade20 Play Energy, Blade20 X	Security Classification: Open
Version: V1.0	Total Page: 32

TIRT Testing Report

Prepared By:	Checked By:	Approved By:	
Aaron Long	Stone Tang	Joky Wang	
<i>Aaron Long</i>	<i>Stone Tang</i>	<i>Joky Wang</i>	

RF TEST REPORT

FCC ID: 2AX4YBLADE20TURBO

According to

47 CFR FCC Part 15, Subpart C(Section 15.247)

ANSI C63.10:2013

Applicant:	Shenzhen DOOGEE Hengtong Technology CO.,LTD
Address:	B, 2/F, Building A4, Silicon Valley Power Digital Industrial Park, No. 22, Longhua New District, Shenzhen, China
Manufacturer:	Shenzhen DOOGEE Hengtong Technology CO.,LTD
Address:	B, 2/F, Building A4, Silicon Valley Power Digital Industrial Park, No. 22, Longhua New District, Shenzhen, China
Sample No:	1000055016
Product Name:	Smart Phone
Brand Name:	DOOGEE
Model No.:	Blade20 Turbo, Blade20 Max, Blade20 Play, Blade20 Pro Max, Blade20 Power, Blade20 Plus, Blade20 Energy, Blade20 Pro Energy, Blade20 Ultra Energy, Blade20 Max Energy, Blade20 Play Energy, Blade20 X
Test No.:	Blade20 Turbo

Date of Receipt:	2025/02/18
Date of Test:	2025/02/18~2025/03/19
Issued Date:	2025/03/26
Testing Lab:	TIRT

Note: This report shall not be reproduced except in full, without the written approval of Beijing TIRT Technology Service Co.,Ltd Shenzhen.Laboratory.

This document may be altered or revised by Beijing TIRT Technology Service Co.,Ltd Shenzhen.Laboratory.Personnel only, and shall be noted in the revision section of the document. The test results of this report relate only to the tested sample identified in this report.

TABLE OF CONTENTS

Description	Page
1. Summary of Standards And Results	6
1.1. Description of Standards and Results	6
2. General Information	7
2.1. Description of Device (EUT)	7
2.2. Accessories of Device (EUT)	8
2.3. Tested Supporting System Details	8
2.4. Block Diagram of connection between EUT and simulators	8
2.5. Test Mode Description	8
2.6. Test Conditions	9
2.7. Test Facility	9
2.8. Measurement Uncertainty	9
2.9. Test Equipment List	10
3. Maximum Peak Output power	11
3.1. Limit	11
3.2. Test Procedure	11
3.3. Test Result	11
4. Bandwidth	12
4.1. Limit	12
4.2. Test Procedure	12
4.3. Test Result	12
5. Carrier Frequency Separation	12
5.1. Limit	12
5.2. Test Procedure	12
5.3. Test Result	12
6. Number Of Hopping Channel	13
6.1. Limit	13
6.2. Test Procedure	13
6.3. Test Result	13
7. Dwell Time	14
7.1. Test limit	14
7.2. Test Procedure	14
7.3. Test Result	14
8. Radiated emissions	15
8.1. Limit	15
8.2. Block Diagram of Test setup	16
8.3. Test Procedure	17
8.4. Test Result	17
9. Band Edge Compliance	21
9.1. Block Diagram of Test Setup	21
9.2. Limit	21
9.3. Test Procedure	21
9.4. Test Result	21
10. Power Line Conducted Emissions	28
10.1. Block Diagram of Test Setup	28
10.2. Limit	28
10.3. Test Procedure	28
10.4. Test Result	29

11. Antenna Requirements	31
11.1. Limit	31
11.2. Result	31
12. Test setup photo	32
13. Photos of EUT	32

History of this test report

Original Report Issue Date: 2025.03.26

- No additional attachment
- Additional attachments were issued following record

Attachment No.	Issue Date	Description

1. SUMMARY OF STANDARDS AND RESULTS

1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below:

Test Item	Standards Paragraph	Result
Maximum Peak Output Power	FCC Part 15: 15.247(b)(1) ANSI C63.10 :2013	P
Bandwidth	FCC Part 15: 15.215 ANSI C63.10 :2013	P
Carrier Frequency Separation	FCC Part 15: 15.247(a)(1) ANSI C63.10 :2013	P
Number Of Hopping Channel	FCC Part 15: 15.247(a)(1)(iii) ANSI C63.10 :2013	P
Dwell Time	FCC Part 15: 15.247(a)(1)(iii) ANSI C63.10 :2013	P
Radiated Emission	FCC Part 15: 15.209 FCC Part 15: 15.247(d) ANSI C63.10 :2013	P
Band Edge Compliance	FCC Part 15: 15.247(d) ANSI C63.10 :2013	P
Power Line Conducted Emissions	FCC Part 15: 15.207 ANSI C63.10 :2013	P
Antenna requirement	FCC Part 15: 15.203	P
<p>Note: 1. P is an abbreviation for Pass. 2. F is an abbreviation for Fail. 3. N/A is an abbreviation for Not Applicable. 4. The conclusion of this test report is judged by actual test data without considering measurement uncertainty.</p>		

2. GENERAL INFORMATION

2.1. Description of Device (EUT)

EUT Name : Smart Phone

Model No. : Blade20 Turbo, Blade20 Max, Blade20 Play, Blade20 Pro Max, Blade20 Power, Blade20 Plus, Blade20 Energy, Blade20 Pro Energy, Blade20 Ultra Energy, Blade20 Max Energy, Blade20 Play Energy, Blade20 X

DIFF. : There is no difference except the name of the model. All tests are made with the Blade20 Turbo model.

Power supply : DC 3.87V from battery or DC11V AC Power Adapter

Radio Technology : Bluetooth V5.2 EDR

Operation frequency : 2402-2480MHz

Channel No. : 79 Channels

Channel spacing : 1MHz

Modulation type : GFSK, $\pi/4$ DQPSK, 8DPSK

Antenna Type : PIFA antenna, Maximum Gain is 1.78dBi.
Antenna information is provided by applicant.

Software version : DOOGEE-Blade20 Turbo-EEA-Android15.0-20250221

Hardware version : M1703-MUB-V2

Intend use : Residential, commercial and light industrial environment
environment

2.2. Accessories of Device (EUT)

Accessories : AC Power Adapter
 Manufacturer : Shenzhen DOOGEE Hengtong Technology CO.,LTD
 Model : TP303C-US
 Input: AC100-240V~ 50/60Hz 0.7A Max
 Output: USB-C: 5.0V=3.0A 15.0W; 9.0V=3.0A 27.0W; 12.0V=2.5A 30.0W;
 Ratings : 15.0V=2.0A 30.0W; 20.0V=1.5A 30.0W
 PPS: 5.0-11.0V=3.0A 33.0W
 Power: 33.0W

2.3. Tested Supporting System Details

No.	Description	Manufacturer	Model	Serial Number	Certification or SDoC
1.	--	--	--	--	--

2.4. Block Diagram of connection between EUT and simulators



2.5. Test Mode Description

Tested mode, channel information		
Mode	Channel	Frequency (MHz)
GFSK	Low :CH1	2402
	Middle: CH40	2441
	High: CH79	2480
$\pi/4$ DQPSK	Low :CH1	2402
	Middle: CH40	2441
	High: CH79	2480
8DPSK	Low :CH1	2402
	Middle: CH40	2441
	High: CH79	2480

2.6. Test Conditions

Items	Required	Actual
Temperature range:	15-35℃	24℃
Humidity range:	25-75%	56%
Pressure range:	86-106kPa	980kPa

2.7. Test Facility

Company:	Beijing TIRT Technology Service Co.,Ltd Shenzhen
Address:	104 Building C, Xinmingsheng Industrial Park No.132, Zhangge Old Village East Zone, Zhangge Community, Fucheng Street, Longhua District, Shenzhen, Guangdong, P. R. China
CNAS Registration Number:	CNAS L14158
A2LA Registration Number:	6049.01
FCC Accredited Lab.Designation Number:	CN1366
FCC Test Firm Registration Number:	820690
Telephone:	+86-0755-27087573

2.8. Measurement Uncertainty

(95% confidence levels, k=2)

Uncertainty	
Parameter	Uncertainty
Occupied Channel Bandwidth	±142.12 KHz
RF power conducted	±0.74 dB
RF power radiated	±3.25dB
Spurious emissions, conducted	±1.78dB
Spurious emissions, radiated (9KHz~30MHz)	±2.56dB
Spurious emissions, radiated (30MHz~1GHz)	±4.6dB
Spurious emissions, radiated (Above 1GHz)	±4.9dB
Conduction Emissions(150kHz~30MHz)	±3.1 dB
Humidity	±4.6%
Temperature	±0.7℃
Time	±1.25

2.9. Test Equipment List

Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
EMI Receiver	Rohde&Schwarz	ESIB 40	YH-TIRT-SAC-966-20220911	2025/01/05	2026/01/04
Integral Antenna	Schwarzbeck	VULB 9163	01314	2023/12/11	2025/12/10
Integral Antenna	Rohde&Schwarz	HF907	RSM2991424	2023/12/11	2025/12/10
Preamplifier	Emtrace	RP01A	'02017	2025/01/05	2026/01/04
Preamplifier	Schwarzbeck	BBV9744	00143	2025/01/05	2026/01/04
Loop Antenna	ZHINAN	ZN30900A	12024	2025/01/05	2026/01/04
Horn Antenna	Schwarzbeck	BBHA9170	00956	2025/01/05	2026/01/04
RF Cable	/	LMR400UF-NMN M-7.0M	/	2025/01/05	2026/01/04
RF Cable	/	SFT2050PUR-N MNM-7.0M	/	2025/01/05	2026/01/04
EMI Receiver	Rohde&Schwarz	ESR7	1316.3003K07-102611-mk	2024/11/02	2025/11/01
LISN	Rohde&Schwarz	ENV216	3560.655.12-1 02915-Bp	2024/11/02	2025/11/01
RF Cable	\	SFT2050PUR-N MNM-2.0M	\	2025/01/05	2026/01/04
Spectrum analyzer	ROHDE&SCHW ARZ	FSU26	200732	2025/01/05	2026/01/04
Spectrum analyzer	ROHDE&SCHW ARZ	FSV40-N	101722	2025/01/05	2026/01/04
Filter	HEWLETT PACKARD	JS0806-F	19K8060209	2025/01/05	2026/01/04

3. MAXIMUM PEAK OUTPUT POWER

3.1. Limit

Please refer section 15.247.

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts

3.2. Test Procedure

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
- b. The following table is the setting of the spectrum analyzer:

Spectrum Parameters	Setting
Span Frequency	$\geq 3 \times \text{RBW}$
RBW	3 MHz
VBW	10MHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

3.3. Test Result

Pass

Please refer to the BT attachments

4. BANDWIDTH

4.1. Limit

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

4.2. Test Procedure

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30kHz RBW and 100kHz VBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

4.3. Test Result

Pass
Please refer to the BT attachments

5. CARRIER FREQUENCY SEPARATION

5.1. Limit

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW

5.2. Test Procedure

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The carrier frequency was measured by spectrum analyzer with 30kHz RBW and 100kHz VBW.

5.3. Test Result

Pass
Please refer to the BT attachments

6. NUMBER OF HOPPING CHANNEL

6.1. Limit

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels

6.2. Test Procedure

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The number of hopping channel was measured by spectrum analyzer with 300kHz RBW and 300KHz VBW.

6.3. Test Result

Pass
Please refer to the BT attachments

7. DWELL TIME

7.1. Test limit

Please refer section 15.247

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz.

The average time of occupancy on any frequency shall not greater than 0.4 s within period of 0.4 sec- onds multiplied by the number of hopping channel employed.

7.2. Test Procedure

7.2.1. Place the EUT on the table and set it in transmitting mode.

7.2.2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

7.2.3. Set center frequency of spectrum analyzer = operating frequency.

7.2.4. Set the spectrum analyzer as RBW=1MHz, VBW=3MHz, Span = 0Hz, Sweep = auto.

7.2.5. Repeat above procedures until all frequency measured were complete.

7.3. Test Result

Pass

Please refer to the BT attachments

8. RADIATED EMISSIONS

8.1. Limit

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

15.205 Restricted frequency band


MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

15.209 Limit


FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		μV/m	dB(μV)/m
0.009-0.490	300	2400/F(KHz)	/
0.490-1.705	30	24000/F(KHz)	/
1.705-30	30	30	29.5
30 88	3	100	40.0
88 216	3	150	43.5
216 960	3	200	46.0
960 1000	3	500	54.0
Above 1000	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	

8.2. Block Diagram of Test setup


8.2.1 In 3m Anechoic Chamber Test Setup Diagram for below 30MHz



8.2.1 In 3m Anechoic Chamber Test Setup Diagram for below 1GHz



8.2.2 In 3m Anechoic Chamber Test Setup Diagram for frequency above 1GHz



Note: For harmonic emissions test a appropriate high pass filter was inserted in the input port of AMP.

8.3. Test Procedure

- (1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber.
- (2) Setup EUT and simulator as shown in section 1.4 and 6.1
- (3) Test antenna was located 3m from the EUT on an adjustable mast. Below pre-scan procedure was first performed in order to find prominent radiated emissions.
 - (a) Change work frequency or channel of device if practicable.
 - (b) Change modulation type of device if practicable.
 - (c) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions
- (4) Spectrum frequency from 9KHz to 25GHz (tenth harmonic of fundamental frequency) was investigated
- (5) For final emissions measurements at each frequency of interest, the EUT were rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10:2013on Radiated Emission test.
- (6) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1MHz, VBW is set at 3MHz for Peak measure; RBW is set at 1MHz, VBW is set at 10Hz for Average measure.

8.4. Test Result


We have scanned the 10th harmonic from 9KHz to the EUT's highest frequency.
Detailed information please see the following page.

From 9KHz to 30MHz: Conclusion: PASS

Note: The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.


From 30MHz to 1000MHz: Conclusion: PASS
All modes had been tested, only show the worst mode GFSK

Vertical:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1 !	30.104	59.98	-23.39	36.59	40.00	-3.41	QP	200	354	P	
2 *	50.852	59.04	-22.09	36.95	40.00	-3.05	QP	100	117	P	
3 !	81.948	61.58	-25.86	35.72	40.00	-4.28	QP	200	0	P	
4	132.149	51.87	-21.98	29.89	43.50	-13.61	QP	100	234	P	
5 !	167.814	58.94	-20.93	38.01	43.50	-5.49	QP	100	12	P	
6	294.426	46.42	-22.37	24.05	46.00	-21.95	QP	100	6	P	

Horizontal:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	30.855	44.52	-23.31	21.21	40.00	-18.79	QP	100	314	P	
2	50.461	48.59	-22.06	26.53	40.00	-13.47	QP	100	333	P	
3	78.564	56.20	-25.61	30.59	40.00	-9.41	QP	200	321	P	
4 *	166.638	56.14	-20.91	35.23	43.50	-8.27	QP	200	282	P	
5	201.454	55.32	-24.74	30.58	43.50	-12.92	QP	100	294	P	
6	300.699	48.19	-22.17	26.02	46.00	-19.98	QP	100	96	P	

Remark: All modes have been tested, and only worst data of GFSK mode, Channel 2480MHz was listed in this report.

From 1G-25GHz

All modes had been tested, only show the worst mode GFSK

Test Mode : GFSK TX Low								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	4804	V	88.79	-27.21	61.58	74	-12.42	Peak
2	4804	V	69.77	-27.21	42.56	54	-11.44	Avg
3	7206	--	--	--		--		--
4	9608	--	--	--		--		--
5	4804	H	91.21	-27.21	64.00	74	-10.00	Peak
6	4804	H	69.29	-27.21	42.08	54	-11.92	Avg
7	7206	--	--	--		--		--
8	9608	--	--	--		--		--
Test Mode : GFSK TX Mid								
1	4882	V	90.82	-27.84	62.98	74	-11.02	Peak
2	4882	V	70.23	-27.84	42.39	54	-11.61	Avg
3	7323	--	--	--		--		--
4	9764	--	--	--		--		--
5	4882	H	91.28	-27.84	63.44	74	-10.56	Peak
6	4882	H	71.56	-27.84	43.72	54	-10.28	Avg
7	7323	--	--	--		--		--
8	9764	--	--	--		--		--
Test Mode : GFSK TX High								
1	4960	V	90.64	-28.49	62.15	74	-11.85	Peak
2	4960	V	69.62	-28.49	41.13	54	-12.87	Avg
3	7440	--	--	--		--		--
4	9920	--	--	--		--		--
5	4960	H	91.53	-28.49	63.04	74	-10.96	Peak
6	4960	H	69.38	-28.49	40.89	54	-13.11	Avg
7	7440	--	--	--		--		--
8	9920	--	--	--		--		--


Note:

1, Result = Read level + Antenna factor + cable loss-Amp factor

2, All the other emissions not reported were too low to read and deemed to comply with FCC limit.

9. BAND EDGE COMPLIANCE

9.1. Block Diagram of Test Setup



9.2. Limit

All the lower and upper band-edges emissions appearing within restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

9.3. Test Procedure

All restriction band and non- restriction band have been tested , only worse case is reported.

9.4. Test Result

PASS. (See below detailed test data)

Test Results					PASS			
Frequency Range					2310MHz~2410MHz			
Test Mode					GFSK TX 2402MHz			
N o.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	2390	H	74.73	-21.47	53.26	74.00	-20.74	Peak
2	2390	H	--	-21.47	--	54.00	--	Avg
3	2400	H	79.43	-26.12	53.31	74.00	-20.69	Peak
4	2400	H	--	-26.12	--	54.00	--	Avg
1	2390	V	75.10	-21.47	53.63	74.00	-20.37	Peak
2	2390	V	--	-21.47	--	54.00	--	Avg
3	2400	V	78.74	-26.12	52.62	74.00	-21.38	Peak
4	2400	V	--	-26.12	--	54.00	--	Avg
Test Results					PASS			
Frequency Range					2450MHz~2550MHz			
Test Mode					GFSK TX 2480MHz			
1	2483.5	H	78.81	-25.29	53.52	74.00	-20.48	Peak
2	2483.5	H	--	-25.29	--	54.00	--	Avg
1	2483.5	V	78.82	-25.29	53.53	74.00	-20.47	Peak
2	2483.5	V	--	-25.29	--	54.00	--	Avg
Note: 1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit. 3. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.								

Test Results					PASS			
Frequency Range					2310MHz~2410MHz			
Test Mode					4 DQPSK TX 2402MHz			
N o.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	2390	H	75.04	-21.47	53.57	74.00	-20.43	Peak
2	2390	H	--	-21.47	--	54.00	--	Avg
3	2400	H	78.81	-26.12	52.69	74.00	-21.31	Peak
4	2400	H	--	-26.12	--	54.00	--	Avg
1	2390	V	74.25	-21.47	52.78	74.00	-21.22	Peak
2	2390	V	--	-21.47	--	54.00	--	Avg
3	2400	V	79.13	-26.12	53.01	74.00	-20.99	Peak
4	2400	V	--	-26.12	--	54.00	--	Avg
Test Results					PASS			
Frequency Range					2450MHz~2550MHz			
Test Mode					4 DQPSK TX 2480MHz			
1	2483.5	H	79.23	-25.29	53.94	74.00	-20.06	Peak
2	2483.5	H	--	-25.29	--	54.00	--	Avg
1	2483.5	V	78.92	-25.29	53.63	74.00	-20.37	Peak
2	2483.5	V	--	-25.29	--	54.00	--	Avg
Note: 1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit. 3. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.								

Test Results					PASS			
Frequency Range					2310MHz~2410MHz			
Test Mode					8DPSK TX 2402MHz			
N o.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	2390	H	74.86	-21.47	53.39	74.00	-20.61	Peak
2	2390	H	--	-21.47	--	54.00	--	Avg
3	2400	H	78.87	-26.12	52.75	74.00	-21.25	Peak
4	2400	H	--	-26.12	--	54.00	--	Avg
1	2390	V	74.46	-21.47	52.99	74.00	-21.01	Peak
2	2390	V	--	-21.47	--	54.00	--	Avg
3	2400	V	79.08	-26.12	52.96	74.00	-21.04	Peak
4	2400	V	--	-26.12	--	54.00	--	Avg
Test Results					PASS			
Frequency Range					2450MHz~2550MHz			
Test Mode					8DPSK TX 2480MHz			
1	2483.5	H	78.56	-25.29	53.27	74.00	-20.73	Peak
2	2483.5	H	--	-25.29	--	54.00	--	Avg
1	2483.5	V	79.18	-25.29	53.89	74.00	-20.11	Peak
2	2483.5	V	--	-25.29	--	54.00	--	Avg
Note: 1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit. 3. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.								


Test Results					PASS			
Frequency Range					2310MHz~2410MHz			
Test Mode					GFSK Hopping			
N o.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	2390	H	74.47	-21.47	53.00	74.00	-21.00	Peak
2	2390	H	--	-21.47	--	54.00	--	Avg
3	2400	H	79.10	-26.12	52.98	74.00	-21.02	Peak
4	2400	H	--	-26.12	--	54.00	--	Avg
1	2390	V	74.72	-21.47	53.25	74.00	-20.75	Peak
2	2390	V	--	-21.47	--	54.00	--	Avg
3	2400	V	79.53	-26.12	53.41	74.00	-20.59	Peak
4	2400	V	--	-26.12	--	54.00	--	Avg
Test Results					PASS			
Frequency Range					2450MHz~2550MHz			
Test Mode					GFSK Hopping			
1	2483.5	H	79.04	-25.29	53.75	74.00	-20.25	Peak
2	2483.5	H	--	-25.29	--	54.00	--	Avg
1	2483.5	V	78.65	-25.29	53.36	74.00	-20.64	Peak
2	2483.5	V	--	-25.29	--	54.00	--	Avg
Note: 1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit. 3. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.								

Test Results					PASS			
Frequency Range					2310MHz~2410MHz			
Test Mode					14 DQPSK Hopping			
N o.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	2390	H	74.92	-21.47	53.45	74.00	-20.55	Peak
2	2390	H	--	-21.47	--	54.00	--	Avg
3	2400	H	78.90	-26.12	52.78	74.00	-21.22	Peak
4	2400	H	--	-26.12	--	54.00	--	Avg
1	2390	V	74.94	-21.47	53.47	74.00	-20.53	Peak
2	2390	V	--	-21.47	--	54.00	--	Avg
3	2400	V	79.56	-26.12	53.44	74.00	-20.56	Peak
4	2400	V	--	-26.12	--	54.00	--	Avg
Test Results					PASS			
Frequency Range					2450MHz~2550MHz			
Test Mode					14 DQPSK Hopping			
1	2483.5	H	78.41	-25.29	53.12	74.00	-20.88	Peak
2	2483.5	H	--	-25.29	--	54.00	--	Avg
1	2483.5	V	78.71	-25.29	53.42	74.00	-20.58	Peak
2	2483.5	V	--	-25.29	--	54.00	--	Avg
Note: 1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit. 3. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.								

Test Results					PASS			
Frequency Range					2310MHz~2410MHz			
Test Mode					8DPSK Hopping			
N o.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	2390	H	74.97	-21.47	53.50	74.00	-20.50	Peak
2	2390	H	--	-21.47	--	54.00	--	Avg
3	2400	H	79.08	-26.12	52.96	74.00	-21.04	Peak
4	2400	H	--	-26.12	--	54.00	--	Avg
1	2390	V	74.67	-21.47	53.20	74.00	-20.80	Peak
2	2390	V	--	-21.47	--	54.00	--	Avg
3	2400	V	78.92	-26.12	52.80	74.00	-21.20	Peak
4	2400	V	--	-26.12	--	54.00	--	Avg
Test Results					PASS			
Frequency Range					2450MHz~2550MHz			
Test Mode					8DPSK Hopping			
1	2483.5	H	78.62	-25.29	53.33	74.00	-20.67	Peak
2	2483.5	H	--	-25.29	--	54.00	--	Avg
1	2483.5	V	78.48	-25.29	53.19	74.00	-20.81	Peak
2	2483.5	V	--	-25.29	--	54.00	--	Avg
Note: 1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit. 3. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.								

10. POWER LINE CONDUCTED EMISSIONS

10.1. Block Diagram of Test Setup



10.2. Limit

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(μV)	Average Level dB(μV)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Notes: 1. * Decreasing linearly with logarithm of frequency.
2. The lower limit shall apply at the transition frequencies.

10.3. Test Procedure


- (1) The EUT was placed on a non-metallic table, 80cm above the ground plane.
- (2) Setup the EUT and simulator as shown in 10.1
- (3) The EUT Power connected to the power mains through a power adapter and a line impedance stabilization network (L.I.S.N1). The other peripheral devices power cord connected to the power mains through a line impedance stabilization network (L.I.S.N2), this provided a 50-ohm coupling impedance for the EUT (Please refer to the block diagram of the test setup and photographs). Both sides of power line were checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10:2013 on conducted Emission test.
- (4) The bandwidth of test receiver is set at 10KHz.
- (5) The frequency range from 150 KHz to 30MHz is checked.

10.4.Test Result

Pass


Remark: All modes have been tested, and only worst data of GFSK mode CH79 was listed in this report.

Polarity: L



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.2714	41.80	9.63	51.43	61.07	-9.64	QP	P	
2	0.2714	28.78	9.63	38.41	51.07	-12.66	AVG	P	
3	0.5775	39.54	9.62	49.16	56.00	-6.84	QP	P	
4	0.5775	29.89	9.62	39.51	46.00	-6.49	AVG	P	
5	0.9825	35.34	9.64	44.98	56.00	-11.02	QP	P	
6	0.9825	22.72	9.64	32.36	46.00	-13.64	AVG	P	
7	1.6620	35.88	9.65	45.53	56.00	-10.47	QP	P	
8	1.6620	24.88	9.65	34.53	46.00	-11.47	AVG	P	
9	12.1875	42.58	9.73	52.31	60.00	-7.69	QP	P	
10 *	12.1875	35.01	9.73	44.74	50.00	-5.26	AVG	P	
11	22.6185	40.30	9.77	50.07	60.00	-9.93	QP	P	
12	22.6185	31.18	9.77	40.95	50.00	-9.05	AVG	P	

Polarity: N



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.3791	39.27	9.62	48.89	58.30	-9.41	QP	P	
2	0.3791	24.96	9.62	34.58	48.30	-13.72	AVG	P	
3	0.8655	38.90	9.64	48.54	56.00	-7.46	QP	P	
4	0.8655	26.91	9.64	36.55	46.00	-9.45	AVG	P	
5	3.5340	36.96	9.67	46.63	56.00	-9.37	QP	P	
6	3.5340	24.28	9.67	33.95	46.00	-12.05	AVG	P	
7	4.9965	37.33	9.68	47.01	56.00	-8.99	QP	P	
8	4.9965	26.89	9.68	36.57	46.00	-9.43	AVG	P	
9	9.5775	42.73	9.73	52.46	60.00	-7.54	QP	P	
10 *	9.5775	33.89	9.73	43.62	50.00	-6.38	AVG	P	
11	11.6475	40.55	9.74	50.29	60.00	-9.71	QP	P	
12	11.6475	33.13	9.74	42.87	50.00	-7.13	AVG	P	

11. ANTENNA REQUIREMENTS

11.1. Limit

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

11.2. Result

The EUT antenna is PIFA Antenna. It comply with the standard requirement.

12. TEST SETUP PHOTO

Please reference to the appendix I Test Setup Photo for details.

13. PHOTOS OF EUT

Please reference to the appendix II external photos and appendix III internal photos for details.

-----END OF REPORT-----