



CFR 47 FCC PART 15 SUBPART C

CERTIFICATION TEST REPORT

For

Cuckoo Clock

MODEL NUMBER: P3NEC4

FCC ID: 2AX7P-7463

REPORT NUMBER: 4899734005-5

ISSUE DATE: January 22, 2021

Prepared for

**Metavolcanic Rock LLC
113 South Monroe Street Tallahassee, FL 32301**

Prepared by

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch

Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China

Tel: +86 769 22038881

Fax: +86 769 33244054

Website: www.ul.com



Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
V0	01/22/2021	Initial Issue	



Summary of Test Results			
Clause	Test Items	FCC Rules	Test Results
1	20dB Bandwidth	FCC 15.247 (a) (1)	Pass
2	Conducted Output Power	FCC 15.247 (b) (1)	Pass
3	Carrier Hopping Channel Separation	FCC 15.247 (a) (1)	Pass
4	Number of Hopping Frequency	15.247 (a) (1) III	Pass
5	Time of Occupancy (Dwell Time)	15.247 (a) (1) III	Pass
6	Conducted Bandedge	FCC 15.247 (d)	Pass
7	Radiated Bandedge and Spurious	FCC 15.247 (d) FCC 15.209 FCC 15.205	Pass
8	Conducted Emission Test for AC Power Port	FCC 15.207	Pass
9	Antenna Requirement	FCC 15.203	Pass

Note:
1. This test report is only published to and used by the applicant, and it is not for evidence purpose in China.
2. The measurement result for the sample received is <Pass> according to < CFR 47 FCC PART 15 SUBPART C >< ISED RSS-247 > when <Accuracy Method> decision rule is applied.

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	6
2. TEST METHODOLOGY	7
3. FACILITIES AND ACCREDITATION	7
4. CALIBRATION AND UNCERTAINTY	8
4.1. <i>MEASURING INSTRUMENT CALIBRATION</i>	8
4.2. <i>MEASUREMENT UNCERTAINTY</i>	8
5. EQUIPMENT UNDER TEST	9
5.1. <i>DESCRIPTION OF EUT</i>	9
5.2. <i>MAXIMUM PEAK OUTPUT POWER</i>	9
5.3. <i>PACKET TYPE CONFIGURATION</i>	9
5.4. <i>CHANNEL LIST</i>	10
5.5. <i>TEST CHANNEL CONFIGURATION</i>	10
5.6. <i>WORST-CASE CONFIGURATIONS</i>	10
5.7. <i>THE WORSE CASE POWER SETTING PARAMETER</i>	11
5.8. <i>DESCRIPTION OF AVAILABLE ANTENNAS</i>	11
5.9. <i>DESCRIPTION OF TEST SETUP</i>	12
6. MEASURING INSTRUMENT AND SOFTWARE USED	13
7. ANTENNA PORT TEST RESULTS	15
7.1. <i>ON TIME AND DUTY CYCLE</i>	15
7.2. <i>20 dB BANDWIDTH</i>	17
7.2.1. <i>GFSK MODE</i>	18
7.2.2. <i>8DPSK MODE</i>	20
7.3. <i>CONDUCTED OUTPUT POWER</i>	23
7.4. <i>CARRIER FREQUENCY SEPARATION</i>	25
7.4.1. <i>GFSK MODE</i>	26
7.4.2. <i>8DPSK MODE</i>	27
7.5. <i>NUMBER OF HOPPING FREQUENCIES</i>	28
7.5.1. <i>GFSK MODE</i>	29
7.5.2. <i>8DPSK MODE</i>	30
7.6. <i>TIME OF OCCUPANCY (DWELL TIME)</i>	31
7.6.1. <i>GFSK MODE</i>	32
7.6.2. <i>8DPSK MODE</i>	35
7.7. <i>CONDUCTED BANDEDGE AND SPURIOUS EMISSION</i>	37
7.7.1. <i>GFSK MODE</i>	38
7.7.2. <i>8DPSK MODE</i>	43



8. RADIATED TEST RESULTS	48
8.1. <i>RESTRICTED BANDEDGE</i>	<i>54</i>
8.1.1. GFSK MODE	54
8.1.2. 8DPSK MODE	57
8.2. <i>SPURIOUS EMISSIONS (1 GHz ~ 3 GHz)</i>	<i>60</i>
8.2.1. GFSK MODE	60
8.3. <i>SPURIOUS EMISSIONS (3 GHz ~ 18 GHz)</i>	<i>66</i>
8.3.1. GFSK MODE	66
8.3.2. 8DPSK MODE	72
8.4. <i>SPURIOUS EMISSIONS (18 GHz ~ 26 GHz)</i>	<i>78</i>
8.4.1. GFSK MODE	78
8.5. <i>SPURIOUS EMISSIONS (30 MHz ~ 1 GHz)</i>	<i>80</i>
8.5.1. GFSK MODE	80
8.6. <i>SPURIOUS EMISSIONS BELOW 30 MHz</i>	<i>82</i>
8.6.1. GFSK MODE	82
9. AC POWER LINE CONDUCTED EMISSIONS	85
9.1.1. GFSK MODE	86
10. ANTENNA REQUIREMENTS	88



1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: Metavolcanic Rock LLC
Address: 113 South Monroe Street Tallahassee, FL 32301

Manufacturer Information

Company Name: TCL Technoly Electronics (Huizhou) Co., Ltd.
Address: Section 37, Zhongkai High-tech Development Zone, Huizhou City, Guang Dong Province, P.R. China

EUT Information

EUT Name: Cuckoo Clock
Model: P3NEC4
Sample Received Date: January 18, 2021
Sample Status: Normal
Sample ID: 3492100
Date of Tested: January 18~22, 2021

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 FCC PART 15 SUBPART C	PASS

Prepared By:

Kebo Zhang
Project Engineer

Checked By:

Shawn Wen
Laboratory Leader

Approved By:

Stephen Guo
Laboratory Manager



2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with KDB 558074 D01 15.247 Meas Guidance v05r02, 414788 D01 Radiated Test Site v01r01, CFR 47 FCC Part 2, CFR 47 FCC Part 15 and ANSI C63.10-2013.

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	<p>A2LA (Certificate No.: 4102.01) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA.</p> <p>FCC (FCC Designation No.: CN1187) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules</p> <p>ISED (Company No.: 21320) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320 and the test lab Conformity Assessment Body Identifier (CABID) is CN0046.</p> <p>VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name: Chamber D, the VCCI registration No. is G-20019 and R-20004 Shielding Room B, the VCCI registration No. is C-20012 and T-20011</p>
---------------------------	--

Note 1: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China

Note 2: The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3: For below 30 MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30 MHz had been correlated to measurements performed on an OFS.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognized national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conduction emission	3.62 dB
Radiated Emission (Included Fundamental Emission) (9 kHz ~ 30 MHz)	2.2 dB
Radiated Emission (Included Fundamental Emission) (30 MHz ~ 1 GHz)	4.00 dB
Radiated Emission (Included Fundamental Emission) (1 GHz to 26 GHz)	5.78 dB (1 GHz ~ 18 GHz)
	5.23 dB (18 GHz ~ 26 GHz)
Duty Cycle	±0.028%
20dB Emission Bandwidth and 99% Occupied Bandwidth	±0.0196%
Carrier Frequency Separation	±1.9%
Maximum Conducted Output Power	±0.743 dB
Number of Hopping Channel	±1.9%
Time of Occupancy	±0.028%
Conducted Band-edge Compliance	±1.328 dB
Conducted Unwanted Emissions In Non-restricted Frequency Bands	±0.746 dB (9 kHz ~ 1 GHz)
	±1.328dB (1 GHz ~ 26 GHz)

Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

EUT Name	Cuckoo Clock		
Model	P3NEC4		
Technology	Bluetooth – BR & EDR		
Transmit Frequency Range	2402 MHz ~ 2480 MHz		
Mode	Basic Rate	Enhanced Data Rate	
Modulation	GFSK	π/4-DQPSK	8DPSK
Packet Type (Maximum Payload):	DH5	2DH5	3DH5
Data Rate	1 Mbps	2 Mbps	3 Mbps
Power Supply	DC 6V (via dry battery) DC 5V (via USB Type-C)		

Note: The EUT can two power supply modes, two kinds of DC power supply modes have been considered, so only the worst-case DC 6V power supply test data record in this report.

5.2. MAXIMUM PEAK OUTPUT POWER

Bluetooth Mode	Frequency (MHz)	Channel Number	Maximum Peak Output Power (dBm)	Maximum EIRP (dBm)
GFSK	2402 ~ 2480	0-78[79]	3.80	7.41
8DPSK	2402 ~ 2480	0-78[79]	-5.01	-1.40

5.3. PACKET TYPE CONFIGURATION

Test Mode	Packet Type	Setting (Packet Length)
GFSK	DH1	27
	DH3	183
	DH5	339
π/4-DQPSK	2-DH1	54
	2-DH3	367
	2-DH5	679
8DPSK	3-DH1	83
	3-DH3	552
	3-DH5	1021

5.4. CHANNEL LIST

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	20	2422	40	2442	60	2462
01	2403	21	2423	41	2443	61	2463
02	2404	22	2424	42	2444	62	2464
03	2405	23	2425	43	2445	63	2465
04	2406	24	2426	44	2446	64	2466
05	2407	25	2427	45	2447	65	2467
06	2408	26	2428	46	2448	66	2468
07	2409	27	2429	47	2449	67	2469
08	2410	28	2430	48	2450	68	2470
09	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461	/	/

5.5. TEST CHANNEL CONFIGURATION

Test Mode	Test Channel	Frequency
GFSK	CH 0(Low Channel), CH 39(MID Channel), CH 78(High Channel)	2402 MHz, 2441 MHz, 2480 MHz
8DPSK	CH 0(Low Channel), CH 39(MID Channel), CH 78(High Channel)	2402 MHz, 2441 MHz, 2480 MHz
GFSK	Hopping	2402 MHz ~ 2480 MHz
8DPSK	Hopping	2402 MHz ~ 2480 MHz

5.6. WORST-CASE CONFIGURATIONS

Test Mode	Modulation Technology	Modulation Type	Data Rate	Packet Type
BR	FHSS	GFSK	1Mbit/s	DH5
EDR	FHSS	8DPSK	3Mbit/s	3-DH5

Note: Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates. Only GFSK and 8DPSK test data were report in this report.

5.7. THE WORSE CASE POWER SETTING PARAMETER

The Worse Case Power Setting Parameter under 2400 ~ 2483.5MHz Band				
Test Software		C256x Bluetooth Hardware Evaluation Tool		
Modulation	Transmit Antenna Number	Test Software setting value		
		CH 00	CH 39	CH 78
GFSK	1	14	14	14
8DPSK	1	12	12	12

5.8. DESCRIPTION OF AVAILABLE ANTENNAS

Antenna	Frequency (MHz)	Antenna Type	MAX Antenna Gain (dBi)
1	2402 ~ 2480	PCB	3.61

Test Mode	Transmit and Receive Mode	Description
GFSK	<input checked="" type="checkbox"/> 1TX, 1RX	Antenna 1 can be used as transmitting/receiving antenna.
8DPSK	<input checked="" type="checkbox"/> 1TX, 1RX	Antenna 1 can be used as transmitting/receiving antenna.

Note: 1. The value of the antenna gain was declared by customer.

5.9. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Item	Equipment	Brand Name	Model Name	Remarks
1	Laptop	Lenovo	TP00094A	/
2	UART	/	/	/
3	Adapter	SAMSUNG	ETA0U83CBC	Input: AC120V.60Hz Output: 5Vdc,1A

I/O CABLES

Cable No	Port	Connector Type	Cable Type	Cable Length(m)	Remarks
1	USB	TYPE C	/	1.0	/

ACCESSORY


Item	Accessory	Brand Name	Model Name	Description
/	/	/	/	/

TEST SETUP

The EUT can work in engineering mode with a software through a Laptop.

SETUP DIAGRAM FOR TESTS

SETUP DIAGRAM FOR TESTS



**6. MEASURING INSTRUMENT AND SOFTWARE USED**

Conducted Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
EMI Test Receiver	R&S	ESR3	101961	Nov. 12, 2020	Nov. 11, 2021
Two-Line V-Network	R&S	ENV216	101983	Nov. 12, 2020	Nov. 11, 2021
Artificial Mains Networks	Schwarzbeck	NSLK 8126	8126465	Nov. 12, 2020	Nov. 11, 2021
Software					
Description			Manufacturer	Name	Version
Test Software for Conducted Emissions			Farad	EZ-EMC	Ver. UL-3A1

Radiated Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
MXE EMI Receiver	KESIGHT	N9038A	MY56400036	Nov. 12, 2020	Nov. 11, 2021
Hybrid Log Periodic Antenna	TDK	HLP-3003C	130960	Aug. 11, 2018	Aug. 10, 2021
Preamplifier	HP	8447D	2944A09099	Nov. 12, 2020	Nov. 11, 2021
EMI Measurement Receiver	R&S	ESR26	101377	Nov. 12, 2020	Nov. 11, 2021
Horn Antenna	TDK	HRN-0118	130939	Sept. 17, 2018	Sept. 17, 2021
Preamplifier	TDK	PA-02-0118	TRS-305-00067	Nov. 20, 2020	Nov. 19, 2021
Horn Antenna	Schwarzbeck	BBHA9170	#691	Aug. 11, 2018	Aug. 11, 2021
Preamplifier	TDK	PA-02-2	TRS-307-00003	Nov. 12, 2020	Nov. 11, 2021
Preamplifier	TDK	PA-02-3	TRS-308-00002	Nov. 12, 2020	Nov. 11, 2021
Loop antenna	Schwarzbeck	1519B	00008	Jan.17, 2019	Jan.17,2022
Preamplifier	TDK	PA-02-001-3000	TRS-302-00050	Nov. 12, 2020	Nov. 11, 2021
Preamplifier	Mini-Circuits	ZX60-83LN-S+	SUP01201941	Nov. 20, 2020	Nov. 19, 2021
High Pass Filter	Wi	WHKX10-2700-3000-18000-40SS	23	Nov. 12, 2020	Nov. 11, 2021
Software					
Description			Manufacturer	Name	Version
Test Software for Radiated Emissions			Farad	EZ-EMC	Ver. UL-3A1



Other instruments					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Spectrum Analyzer	Keysight	N9030A	MY55410512	Nov. 20, 2020	Nov. 19, 2021
Dual Channel Power Meter	Keysight	N1912A	MY55416024	Nov. 20, 2020	Nov. 19, 2021
Power Sensor	Keysight	USB Wideband Power Sensor	MY5100022	Nov. 20, 2020	Nov. 19, 2021

7. ANTENNA PORT TEST RESULTS

7.1. ON TIME AND DUTY CYCLE


LIMITS

None; for reporting purposes only.

PROCEDURE

Refer to ANSI C63.10-2013 Zero – Span Spectrum Analyzer method.

TEST SETUP



TEST ENVIRONMENT

Temperature	24.6 °C	Relative Humidity	48.1 %
Atmosphere Pressure	101 kPa	Test Voltage	DC 6 V

RESULTS

Mode	On Time (msec)	Period (msec)	Duty Cycle x (Linear)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	1/T Minimum VBW (kHz)	Final setting For VBW (kHz)
GFSK	2.88	3.74	0.770	77.0%	1.14	0.35	0.5
8DPSK	2.90	3.76	0.771	77.1%	1.29	0.34	0.5



Note:

Duty Cycle Correction Factor=10log (1/x).

Where: x is Duty Cycle (Linear)

Where: T is On Time

If that calculated VBW is not available on the analyzer then the next higher value should be used.



7.2. 20 dB BANDWIDTH

LIMITS

CFR 47FCC Part15 (15.247) Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247 (a) (1)	20 dB Bandwidth	None; for reporting purposes only.	2400-2483.5


TEST PROCEDURE

Connect the EUT to the spectrum analyser and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	1 % to 5 % of the 20dB bandwidth
VBW	approximately 3×RBW
Span	Approximately 2 to 3 times the 20dB bandwidth
Trace	Max hold
Sweep	Auto couple

a) Use the occupied bandwidth function of the instrument, allow the trace to stabilize and report the measured 99 % occupied bandwidth and 20 dB Bandwidth.

TEST SETUP





TEST ENVIRONMENT


Temperature	24.6 °C	Relative Humidity	48.1 %
Atmosphere Pressure	101 kPa	Test Voltage	DC 6 V

RESULTS

7.2.1. GFSK MODE


Channel	Frequency (MHz)	20 dB Occupied bandwidth (MHz)	Result
Low	2402	0.942	PASS
Middle	2441	0.936	PASS
High	2480	0.942	PASS

20 dB BANDWIDTH LOW CH






20 dB BANDWIDTH MID CH



20 dB BANDWIDTH HIGH CH






7.2.2. 8DPSK MODE


Channel	Frequency (MHz)	20 dB Occupied bandwidth (MHz)	Result
Low	2402	1.336	PASS
Middle	2441	1.342	PASS
High	2480	1.342	PASS



20 dB BANDWIDTH LOW CH




20 dB BANDWIDTH MID CH





20 dB BANDWIDTH HIGH CH



7.3. CONDUCTED OUTPUT POWER


LIMITS

CFR 47 FCC Part15 (15.247), Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247 (b) (1)	Peak Conducted Output Power	Hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel: 1 watt or 30 dBm; Hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel: 125 mW or 21 dBm	2400-2483.5

TEST PROCEDURE

Connect the EUT to a low loss RF cable from the antenna port to the power sensor (video bandwidth is greater than the occupied bandwidth).
Measure peak emission level, the indicated level is the peak output power, after any corrections for external attenuators and cables.

TEST SETUP



TEST ENVIRONMENT

Temperature	24.6 °C	Relative Humidity	48.1 %
Atmosphere Pressure	101 kPa	Test Voltage	DC 6 V

RESULTS



Test Mode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
DH5	Ant1	2402	3.80	<=30	PASS
		2441	2.95	<=30	PASS
		2480	2.46	<=30	PASS
3DH5	Ant1	2402	-5.01	<=21	PASS
		2441	-5.87	<=21	PASS
		2480	-6.34	<=21	PASS

7.4. CARRIER FREQUENCY SEPARATION

LIMITS

CFR 47 FCC Part15 (15.247),			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247 (a) (1))	Carrier Frequency Separation	Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel.	2400-2483.5

TEST PROCEDURE


Connect the EUT to the spectrum analyzer and use the following settings:

Center Frequency	The center frequency of the channel under test
Span	wide enough to capture the peaks of two adjacent channels
Detector	Peak
RBW	Start with the RBW set to approximately 30 % of the channel spacing; adjust as necessary to best identify the center of each individual channel.
VBW	≥RBW
Trace	Max hold
Sweep time	Auto couple

Allow the trace to stabilize and use the marker-delta function to determine the separation between the peaks of the adjacent channels.

Compliance of an EUT with the appropriate regulatory limit shall be determined.

TEST SETUP




TEST ENVIRONMENT

Temperature	24.6 °C	Relative Humidity	48.1 %
Atmosphere Pressure	101 kPa	Test Voltage	DC 6 V

RESULTS

7.4.1. GFSK MODE


Channel	Carrier Hopping Channel Separation (MHz)	Limit (MHz)	Result
Middle	1.0	≥ 20 dB Bandwidth of The Hopping Channel	PASS



Note: For 20 dB Bandwidth of The hopping Channel, please refer to clause 7.2.1.

7.4.2. 8DPSK MODE

Channel	Carrier Hopping Channel Separation (MHz)	Limit (MHz)	Result
Middle	1.0	≥ two-thirds of the 20 dB Bandwidth of The Hopping Channel	PASS



Note: For 20 dB Bandwidth of The Hopping Channel, please refer to clause 7.2.2.

7.5. NUMBER OF HOPPING FREQUENCIES

LIMITS

CFR 47 FCC Part15 (15.247), Subpart C		
Section	Test Item	Limit
CFR 47 15.247 (a) (1) III	Number of Hopping Frequency	at least 15 hopping channels


TEST PROCEDURE

Connect the EUT to the spectrum Analyzer and use the following settings:

Detector	Peak
RBW	To identify clearly the individual channels, set the RBW to less than 30 % of the channel spacing or the 20 dB bandwidth, whichever is smaller.
VBW	\geq RBW
Span	The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
Trace	Max hold
Sweep time	Auto couple

Set EUT to transmit maximum output power and switch on frequency hopping function. then set enough count time (larger than 5000 times) to get all the hopping frequency channel displayed on the screen of spectrum analyzer, count the quantity of peaks to get the number of hopping channels.

TEST SETUP




TEST ENVIRONMENT

Temperature	24.6 °C	Relative Humidity	48.1 %
Atmosphere Pressure	101 kPa	Test Voltage	DC 6 V

RESULTS

7.5.1. GFSK MODE


Hopping numbers	Limit	Results
79	>=15	Pass





7.5.2. 8DPSK MODE

Hopping numbers	Limit	Results
79	≥ 15	Pass



7.6. TIME OF OCCUPANCY (DWELL TIME)

LIMITS

CFR 47 FCC Part15 (15.247), Subpart C ISED RSS-247 ISSUE 2		
Section	Test Item	Limit
CFR 47 15.247 (a) (1) III ISED RSS-247 Clause 5.1 (d)	Time of Occupancy (Dwell Time)	The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds, multiplied by the number of hopping channels employed.

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 7.8.4.

Connect the EUT to the spectrum Analyzer and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	1 MHz
VBW	≥RBW
Span	Zero span, centered on a hopping channel
Trace	Max hold
Sweep time	As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel

Use the marker-delta function to determine the transmit time per hop (Burst Width). If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation in transmit time.

For FHSS Mode (79 Channel):

DH1/3DH1 Dwell Time: $\text{Burst Width} * (1600/2) * 31.6 / (\text{channel number})$

DH3/3DH3 Dwell Time: $\text{Burst Width} * (1600/4) * 31.6 / (\text{channel number})$

DH5/3DH5 Dwell Time: $\text{Burst Width} * (1600/6) * 31.6 / (\text{channel number})$


For AFHSS Mode (20 Channel):

DH1/3DH1 Dwell Time: $\text{Burst Width} * (1600/2) * 8 / (\text{channel number})$

DH3/3DH3 Dwell Time: $\text{Burst Width} * (1600/4) * 8 / (\text{channel number})$

DH5/3DH5 Dwell Time: $\text{Burst Width} * (1600/6) * 8 / (\text{channel number})$

TEST SETUP





TEST ENVIRONMENT


Temperature	24.6 °C	Relative Humidity	48.1 %
Atmosphere Pressure	101 kPa	Test Voltage	DC 6 V

RESULTS

7.6.1. GFSK MODE


FHSS Mode				
Packet Type	Channel	Burst Width [ms/hop/ch]	Dwell Time [ms]	Results
DH1	MCH	0.390	0.125	PASS
DH3	MCH	1.635	0.262	PASS
DH5	MCH	2.895	0.309	PASS
AFHSS Mode				
DH1	MCH	0.390	0.062	PASS
DH3	MCH	1.635	0.131	PASS
DH5	MCH	2.895	0.154	PASS







7.6.2. 8DPSK MODE

FHSS Mode				
Packet Type	Channel	Burst Width [ms/hop/ch]	Dwell Time [ms]	Results
3DH1	MCH	0.390	0.125	PASS
3DH3	MCH	1.650	0.264	PASS
3DH5	MCH	2.895	0.309	PASS
AFHSS Mode				
3DH1	MCH	0.390	0.062	PASS
3DH3	MCH	1.650	0.132	PASS
3DH5	MCH	2.895	0.154	PASS





7.7. CONDUCTED BANDEdge AND SPURIOUS EMISSION

LIMITS

CFR 47 FCC Part15 (15.247), Subpart C		
Section	Test Item	Limit
CFR 47 FCC §15.247 (d)	Conducted Spurious Emission	at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

TEST PROCEDURE

Connect the EUT to the spectrum analyser and use the following settings for reference level measurement:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
Span	1.5 x DTS bandwidth
Trace	Max hold
Sweep time	Auto couple.


Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level.

Change the settings for emission level measurement:

Span	Set the center frequency and span to encompass frequency range to be measured
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
measurement points	$\geq \text{span}/\text{RBW}$
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements.

TEST SETUP






TEST ENVIRONMENT



Temperature	24.6 °C	Relative Humidity	48.1 %
Atmosphere Pressure	101 kPa	Test Voltage	DC 6 V



RESULTS


7.7.1. GFSK MODE





















7.7.2. 8DPSK MODE











8. RADIATED TEST RESULTS

LIMITS

Please refer to CFR 47 FCC §15.205 and §15.209.

Radiation Disturbance Test Limit for FCC (Class B) (9 kHz-1 GHz)

Emissions radiated outside of the specified frequency bands above 30 MHz		
Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m
		Quasi-Peak
30 - 88	100	40
88 - 216	150	43.5
216 - 960	200	46
Above 960	500	54
Above 1000	500	Peak
		Average
		74
		54

FCC Emissions radiated outside of the specified frequency bands below 30 MHz		
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30

ISED General field strength limits at frequencies below 30 MHz

Table 6 – General field strength limits at frequencies below 30 MHz		
Frequency	Magnetic field strength (H-Field) (µA/m)	Measurement distance (m)
9 - 490 kHz ^{Note 1}	6.37/F (F in kHz)	300
490 - 1705 kHz	63.7/F (F in kHz)	30
1.705 - 30 MHz	0.08	30

Note 1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.



ISED Restricted bands please refer to ISED RSS-GEN Clause 8.10

Table 7 – Restricted frequency bands^{Note 1}

MHz	MHz	GHz
0.090 - 0.110	149.9 - 150.05	9.0 - 9.2
0.495 - 0.505	156.52475 - 156.52525	9.3 - 9.5
2.1735 - 2.1905	156.7 - 156.9	10.6 - 12.7
3.020 - 3.026	162.0125 - 167.17	13.25 - 13.4
4.125 - 4.128	167.72 - 173.2	14.47 - 14.5
4.17725 - 4.17775	240 - 285	15.35 - 16.2
4.20725 - 4.20775	322 - 335.4	17.7 - 21.4
5.677 - 5.683	399.9 - 410	22.01 - 23.12
6.215 - 6.218	608 - 614	23.6 - 24.0
6.26775 - 6.26825	960 - 1427	31.2 - 31.8
6.31175 - 6.31225	1435 - 1626.5	36.43 - 36.5
8.291 - 8.294	1645.5 - 1646.5	Above 38.6
8.362 - 8.366	1660 - 1710	
8.37625 - 8.38675	1718.8 - 1722.2	
8.41425 - 8.41475	2200 - 2300	
12.29 - 12.293	2310 - 2390	
12.51975 - 12.52025	2483.5 - 2500	
12.57675 - 12.57725	2655 - 2900	
13.36 - 13.41	3260 - 3267	
16.42 - 16.423	3332 - 3339	
16.69475 - 16.69525	3345.8 - 3358	
16.80425 - 16.80475	3500 - 4400	
25.5 - 25.67	4500 - 5150	
37.5 - 38.25	5350 - 5460	
73 - 74.6	7250 - 7750	
74.8 - 75.2	8025 - 8500	
108 - 138		

Note 1: Certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

FCC Restricted bands of operation refer to FCC §15.205 (a):


MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

Note: ¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

²Above 38.6c

TEST SETUP AND PROCEDURE

Below 30 MHz




The setting of the spectrum analyser

RBW	200 Hz (From 9 kHz to 0.15 MHz) / 9 kHz (From 0.15 MHz to 30 MHz)
VBW	200 Hz (From 9 kHz to 0.15 MHz) / 9 kHz (From 0.15 MHz to 30 MHz)
Sweep	Auto
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.4.
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1 m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.
7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30 m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.

Below 1 GHz and above 30 MHz




The setting of the spectrum analyser

RBW	120 kHz
VBW	300 kHz
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.5.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

Above 1 GHz




The setting of the spectrum analyser

RBW	1 MHz
VBW	3 MHz
Sweep	Auto
Detector	Peak / CISPR AV
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.6.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 1.5 m above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1 GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz, peak detector for peak measurements, CISPR AV detector for average measurements and duty correction factor shall be added to the measurement results. For the Duty Cycle please refer to clause 7.1.ON TIME AND DUTY CYCLE.

X axis, Y axis, Z axis positions:



Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

TEST ENVIRONMENT


Temperature	24.2 °C	Relative Humidity	49.2 %
Atmosphere Pressure	101 kPa	Test Voltage	DC 6 V

RESULTS

8.1. RESTRICTED BANDEDGE

8.1.1. GFSK MODE

RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2376.930	37.94	11.50	49.44	74.00	-24.56	peak
2	2390.000	34.45	11.59	46.04	74.00	-27.96	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)


PEAK



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	45.03	11.97	57.00	74.00	-17.00	peak
2	2483.675	43.78	11.97	55.75	74.00	-18.25	peak
3	2483.825	45.18	11.97	57.15	74.00	-16.85	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. Peak: Peak detector.
 3. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

AVG




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	DCCF (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	22.56	11.97	1.14	35.67	54.00	-18.33	AVG
2	2483.675	23.26	11.97	1.14	36.37	54.00	-17.63	AVG
3	2483.825	22.84	11.97	1.14	35.95	54.00	-18.05	AVG

Note: 1. Measurement = Reading Level + Correct Factor + DCCF
 2. AVG: CISPR AV detector.
 3. For the DCCF please refer to clause 7.1.
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

8.1.2. 8DPSK MODE

RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2384.520	41.72	11.55	53.27	74.00	-20.73	peak
2	2390.000	35.02	11.59	46.61	74.00	-27.39	peak


Note: 1. Measurement = Reading Level + Correct Factor.

2. Peak: Peak detector.

3. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)


PEAK



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	43.01	11.97	54.98	74.00	-19.02	peak
2	2483.550	44.63	11.97	56.60	74.00	-17.40	peak
3	2484.000	42.52	11.97	54.49	74.00	-19.51	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. Peak: Peak detector.
 3. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

AVG



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	DCCF (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	21.59	11.97	1.29	34.85	54.00	-19.15	AVG
2	2483.550	21.52	11.97	1.29	34.78	54.00	-19.22	AVG
3	2484.000	22.37	11.97	1.29	35.63	54.00	-18.37	AVG


Note: 1. Measurement = Reading Level + Correct Factor + DCCF
 2. AVG: CISPR AV detector.
 3. For the DCCF please refer to clause 7.1.
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Note: All the polarities had been tested, only the worst data was recorded in the report.

8.2. SPURIOUS EMISSIONS (1 GHz ~ 3 GHz)

8.2.1. GFSK MODE


HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1172.000	37.56	6.17	43.73	74.00	-30.27	peak
2	1498.000	35.33	6.94	42.27	74.00	-31.73	peak
3	2134.000	33.66	10.86	44.52	74.00	-29.48	peak
4	2402.000	74.75	11.66	86.41	/	/	fundamental
5	2562.000	35.17	11.99	47.16	74.00	-26.84	peak
6	2814.000	35.60	13.27	48.87	74.00	-25.13	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1128.000	40.38	5.66	46.04	74.00	-27.96	peak
2	1184.000	38.25	6.32	44.57	74.00	-29.43	peak
3	1592.000	35.69	7.84	43.53	74.00	-30.47	peak
4	2146.000	35.40	10.89	46.29	74.00	-27.71	peak
5	2402.000	80.36	11.66	92.02	/	/	fundamental
6	2490.000	38.25	12.00	50.25	74.00	-23.75	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.




HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1084.000	40.09	5.32	45.41	74.00	-28.59	peak
2	1108.000	39.70	5.43	45.13	74.00	-28.87	peak
3	1180.000	38.47	6.27	44.74	74.00	-29.26	peak
4	1500.000	37.73	6.94	44.67	74.00	-29.33	peak
5	1594.000	37.07	7.86	44.93	74.00	-29.07	peak
6	2441.000	83.53	11.81	95.34	/	/	fundamental
7	2844.000	34.69	13.35	48.04	74.00	-25.96	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.


HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1172.000	37.95	6.17	44.12	74.00	-29.88	peak
2	1618.000	34.46	7.95	42.41	74.00	-31.59	peak
3	1798.000	34.28	9.62	43.90	74.00	-30.10	peak
4	2441.000	77.45	11.81	89.26	/	/	fundamental
5	2496.000	37.54	12.01	49.55	74.00	-24.45	peak
6	2796.000	34.88	13.21	48.09	74.00	-25.91	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.


HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1080.000	40.22	5.30	45.52	74.00	-28.48	peak
2	1180.000	38.77	6.27	45.04	74.00	-28.96	peak
3	1598.000	37.27	7.89	45.16	74.00	-28.84	peak
4	2410.000	35.12	11.69	46.81	74.00	-27.19	peak
5	2480.000	84.72	11.95	96.67	/	/	fundamental
6	2826.000	35.42	13.29	48.71	74.00	-25.29	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1176.000	36.53	6.22	42.75	74.00	-31.25	peak
2	1616.000	34.91	7.94	42.85	74.00	-31.15	peak
3	1866.000	33.88	9.74	43.62	74.00	-30.38	peak
4	1968.000	34.04	9.96	44.00	74.00	-30.00	peak
5	2390.000	35.57	11.59	47.16	74.00	-26.84	peak
6	2480.000	75.87	11.95	87.82	/	/	fundamental
7	2826.000	35.20	13.29	48.49	74.00	-25.51	peak


Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.

Note: All the modes and channels have been tested, only the worst data was recorded in the report.

8.3. SPURIOUS EMISSIONS (3 GHz ~ 18 GHz)

8.3.1. GFSK MODE

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4800.000	51.12	1.40	52.52	74.00	-21.48	peak
2	5910.000	43.76	4.45	48.21	74.00	-25.79	peak
3	7200.000	42.39	7.36	49.75	74.00	-24.25	peak
4	11820.000	35.40	15.29	50.69	74.00	-23.31	peak
5	14730.000	34.01	17.79	51.80	74.00	-22.20	peak
6	17340.000	30.03	22.31	52.34	74.00	-21.66	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4800.000	49.21	1.40	50.61	74.00	-23.39	peak
2	6000.000	45.44	4.00	49.44	74.00	-24.56	peak
3	11835.000	36.05	15.34	51.39	74.00	-22.61	peak
4	12660.000	35.70	15.69	51.39	74.00	-22.61	peak
5	14865.000	34.70	17.61	52.31	74.00	-21.69	peak
6	17430.000	30.11	21.92	52.03	74.00	-21.97	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	51.14	1.32	52.46	74.00	-21.54	peak
2	7320.000	42.98	7.28	50.26	74.00	-23.74	peak
3	11430.000	36.39	14.72	51.11	74.00	-22.89	peak
4	12645.000	36.05	15.71	51.76	74.00	-22.24	peak
5	13530.000	34.70	17.19	51.89	74.00	-22.11	peak
6	17085.000	30.83	21.80	52.63	74.00	-21.37	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	48.51	1.32	49.83	74.00	-24.17	peak
2	6000.000	45.80	4.00	49.80	74.00	-24.20	peak
3	9330.000	37.94	10.57	48.51	74.00	-25.49	peak
4	12720.000	35.99	15.70	51.69	74.00	-22.31	peak
5	14835.000	34.39	17.80	52.19	74.00	-21.81	peak
6	16860.000	31.42	21.22	52.64	74.00	-21.36	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.




HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4950.000	49.67	1.71	51.38	74.00	-22.62	peak
2	6000.000	44.37	4.00	48.37	74.00	-25.63	peak
3	9330.000	38.17	10.57	48.74	74.00	-25.26	peak
4	12405.000	36.08	15.94	52.02	74.00	-21.98	peak
5	14880.000	37.29	17.51	54.80	74.00	-19.20	peak
6	14880.000	31.99	17.51	49.50	54.00	-4.50	AVG
7	17370.000	30.55	22.10	52.65	74.00	-21.35	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Peak Result (dBuV/m)	DCCF (dB)	AVG Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4575.000	49.16	0.09	49.25	/	/	74.00	-24.75	peak
2	4950.000	48.51	1.71	50.22	/	/	74.00	-23.78	peak
3	5910.000	48.50	4.45	52.95	/	/	74.00	-21.05	peak
4	14880.000	39.49	17.51	57.00	/	/	74.00	-17.00	peak
5	14880.000	32.76	17.51	/	1.14	51.41	54.00	-2.59	AVG
6	16485.000	32.13	19.69	51.82	/	/	74.00	-22.18	peak
7	17655.000	28.63	23.14	51.77	/	/	74.00	-22.23	peak

- Note:
1. Peak Result = Reading Level + Correct Factor.
 2. AVG Result = Reading Level + Correct Factor + DCCF
 3. Peak: Peak detector.
 4. AVG: CISPR AV detector.
 5. For the DCCF please refer to clause 7.1.
 6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 7. Proper operation of the transmitter prior to adding the filter to the measurement chain.

8.3.2. 8DPSK MODE

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4575.000	51.12	0.09	51.21	74.00	-22.79	peak
2	4800.000	51.31	1.40	52.71	74.00	-21.29	peak
3	5910.000	43.88	4.45	48.33	74.00	-25.67	peak
4	8220.000	38.67	9.79	48.46	74.00	-25.54	peak
5	11400.000	36.06	14.76	50.82	74.00	-23.18	peak
6	14790.000	34.01	18.01	52.02	74.00	-21.98	peak
7	16815.000	31.96	20.84	52.80	74.00	-21.20	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.




HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Peak Result (dBuV/m)	DCCF (dB)	AVG Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4800.000	54.56	1.40	55.96	/	/	74.00	-18.04	peak
2	4800.000	48.05	1.40	/	1.29	50.74	54.00	-3.26	AVG
3	6000.000	45.45	4.00	49.45	/	/	74.00	-24.55	peak
4	9600.000	38.66	11.03	49.69	/	/	74.00	-24.31	peak
5	12660.000	36.27	15.69	51.96	/	/	74.00	-22.04	peak
6	14415.000	35.73	17.36	53.09	/	/	74.00	-20.91	peak
7	17130.000	30.11	21.92	52.03	/	/	74.00	-21.97	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.
 2. AVG Result = Reading Level + Correct Factor + DCCF
 3. Peak: Peak detector.
 4. AVG: CISPR AV detector.
 5. For the DCCF please refer to clause 7.1.
 6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 7. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	51.33	1.32	52.65	74.00	-21.35	peak
2	7755.000	39.19	8.94	48.13	74.00	-25.87	peak
3	9360.000	38.73	10.75	49.48	74.00	-24.52	peak
4	12300.000	34.83	16.09	50.92	74.00	-23.08	peak
5	13920.000	34.20	17.55	51.75	74.00	-22.25	peak
6	14805.000	34.27	18.00	52.27	74.00	-21.73	peak
7	17640.000	29.11	23.03	52.14	74.00	-21.86	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Peak Result (dBuV/m)	DCCF (dB)	AVG Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	53.65	1.32	54.97	/	/	74.00	-19.03	peak
2	4875.000	47.75	1.32	/	1.29	50.36	54.00	-3.64	AVG
3	6000.000	44.78	4.00	48.78	/	/	74.00	-25.22	peak
4	9210.000	38.20	9.95	48.15	/	/	74.00	-25.85	peak
5	11895.000	36.59	15.50	52.09	/	/	74.00	-21.91	peak
6	14655.000	35.09	17.54	52.63	/	/	74.00	-21.37	peak
7	17280.000	30.18	22.48	52.66	/	/	74.00	-21.34	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.
 2. AVG Result = Reading Level + Correct Factor + DCCF
 3. Peak: Peak detector.
 4. AVG: CISPR AV detector.
 5. For the DCCF please refer to clause 7.1.
 6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 7. Proper operation of the transmitter prior to adding the filter to the measurement chain.




HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4950.000	49.39	1.71	51.10	74.00	-22.90	peak
2	5910.000	44.08	4.45	48.53	74.00	-25.47	peak
3	9420.000	38.12	10.88	49.00	74.00	-25.00	peak
4	11655.000	36.41	15.07	51.48	74.00	-22.52	peak
5	14880.000	35.49	17.51	53.00	74.00	-21.00	peak
6	16950.000	31.31	21.41	52.72	74.00	-21.28	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Peak Result (dBuV/m)	DCCF (dB)	AVG Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4950.000	50.28	1.71	51.99	/	/	74.00	-22.01	peak
2	5910.000	43.02	4.45	47.47	/	/	74.00	-26.53	peak
3	9000.000	37.14	11.27	48.41	/	/	74.00	-25.59	peak
4	12675.000	35.58	15.66	51.24	/	/	74.00	-22.76	peak
5	14880.000	37.49	17.51	55.00	/	/	74.00	-19.00	peak
6	14880.000	32.06	17.51	/	1.29	50.86	54.00	-3.14	AVG
7	16410.000	32.51	19.69	52.20	/	/	74.00	-21.80	peak

- Note:
1. Peak Result = Reading Level + Correct Factor.
 2. AVG Result = Reading Level + Correct Factor + DCCF
 3. Peak: Peak detector.
 4. AVG: CISPR AV detector.
 5. For the DCCF please refer to clause 7.1.
 6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 7. Proper operation of the transmitter prior to adding the filter to the measurement chain.

8.4. SPURIOUS EMISSIONS (18 GHz ~ 26 GHz)

8.4.1. GFSK MODE

SPURIOUS EMISSIONS (LOW CHANNEL, WORST-CASE CONFIGURATION, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	19336.000	50.04	-5.58	44.46	74.00	-29.54	peak
2	19904.000	49.83	-5.37	44.46	74.00	-29.54	peak
3	21232.000	49.40	-4.77	44.63	74.00	-29.37	peak
4	21600.000	49.52	-4.54	44.98	74.00	-29.02	peak
5	23288.000	48.93	-3.33	45.60	74.00	-28.40	peak
6	24664.000	46.90	-2.33	44.57	74.00	-29.43	peak

Note: 1. Peak Result = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

SPURIOUS EMISSIONS (LOW CHANNEL, WORST-CASE CONFIGURATION, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18528.000	49.61	-5.26	44.35	74.00	-29.65	peak
2	19568.000	49.55	-5.46	44.09	74.00	-29.91	peak
3	20224.000	50.02	-5.60	44.42	74.00	-29.58	peak
4	21664.000	48.73	-4.45	44.28	74.00	-29.72	peak
5	23248.000	47.65	-3.37	44.28	74.00	-29.72	peak
6	24848.000	46.46	-2.23	44.23	74.00	-29.77	peak


- Note: 1. Peak Result = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.

Note: All the modes have been tested, only the worst data was recorded in the report.

8.5. SPURIOUS EMISSIONS (30 MHz ~ 1 GHz)

8.5.1. GFSK MODE


SPURIOUS EMISSIONS (LOW CHANNEL, WORST-CASE CONFIGURATION, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	166.7700	51.41	-17.47	33.94	43.50	-9.56	QP
2	229.8200	60.38	-18.65	41.73	46.00	-4.27	QP
3	288.9900	51.23	-15.98	35.25	46.00	-10.75	QP
4	323.9100	42.26	-14.74	27.52	46.00	-18.48	QP
5	415.0900	36.30	-13.06	23.24	46.00	-22.76	QP
6	769.1400	33.87	-7.60	26.27	46.00	-19.73	QP

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.
 2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
 3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

SPURIOUS EMISSIONS (LOW CHANNEL, WORST-CASE CONFIGURATION, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	165.8000	44.75	-17.51	27.24	43.50	-16.26	QP
2	224.9700	54.19	-18.42	35.77	46.00	-10.23	QP
3	288.9900	37.43	-15.98	21.45	46.00	-24.55	QP
4	321.0000	33.95	-14.78	19.17	46.00	-26.83	QP
5	485.9000	36.53	-11.74	24.79	46.00	-21.21	QP
6	597.4500	29.24	-9.61	19.63	46.00	-26.37	QP

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.
 2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
 3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto


Note: All the modes have been tested, only the worst data was recorded in the report.

8.6. SPURIOUS EMISSIONS BELOW 30 MHz

8.6.1. GFSK MODE

(LOW CHANNEL, LOOP ANTENNA FACE ON TO THE EUT, WORST-CASE CONFIGURATION)

9 kHz~ 150 kHz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	Margin (dB)	Remark
1	0.0100	74.22	-101.40	-27.18	47.6	-74.78	peak
2	0.0131	72.45	-101.38	-28.93	45.25	-74.18	peak
3	0.0177	69.07	-101.35	-32.28	42.64	-74.92	peak
4	0.0279	66.17	-101.38	-35.21	38.69	-73.90	peak
5	0.0427	61.64	-101.45	-39.81	34.99	-74.80	peak
6	0.0792	58.55	-101.63	-43.08	29.63	-72.71	peak
7	0.1242	56.01	-101.72	-45.71	25.72	-71.43	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

3. All 3 polarizations(Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.


150 kHz ~ 490 kHz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	Margin (dB)	Remark
1	0.1554	72.77	-101.65	-28.88	23.77	-52.65	peak
2	0.2068	66.95	-101.73	-34.78	21.29	-56.07	peak
3	0.2235	65.95	-101.75	-35.8	20.61	-56.41	peak
4	0.2972	62.16	-101.85	-39.69	18.14	-57.83	peak
5	0.3180	61.18	-101.88	-40.7	17.55	-58.25	peak
6	0.4097	57.02	-101.97	-44.95	15.35	-60.30	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.
 3. All 3 polarizations(Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

490 kHz ~ 30 MHz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	Margin (dB)	Remark
1	0.5917	61.24	-62.08	-0.84	32.16	-33.00	peak
2	1.0886	60.91	-62.22	-1.31	26.87	-28.18	peak
3	1.7580	56.58	-61.93	-5.35	29.54	-34.89	peak
4	4.2968	54.77	-61.38	-6.61	29.54	-36.15	peak
5	7.4839	53.97	-61.15	-7.18	29.54	-36.72	peak
6	16.8090	54.45	-60.95	-6.5	29.54	-36.04	peak

Note: 1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.
 3. All 3 polarizations(Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

Note: All the modes have been tested, only the worst data was recorded in the report.

9. AC POWER LINE CONDUCTED EMISSIONS


LIMITS

Please refer to CFR 47 FCC §15.207 (a).

FREQUENCY (MHz)	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

TEST SETUP AND PROCEDURE

Refer to ANSI C63.10-2013 clause 6.2.



The EUT is put on a table of non-conducting material that is 80 cm high. The vertical conducting wall of shielding is located 40 cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI Measurement Receiver (R&S Test Receiver ESR3) is used to test the emissions from both sides of AC line. According to the requirements in Section 6.2 of ANSI C63.10-2013. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9 kHz.

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.

TEST ENVIRONMENT


Temperature	22.4 °C	Relative Humidity	50.2 %
Atmosphere Pressure	101 kPa	Test Voltage	AC 120 V, 60 Hz



TEST RESULTS

9.1.1. GFSK MODE


LINE L RESULTS (LOW CHANNEL, WORST-CASE CONFIGURATION)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1503	26.62	9.59	36.21	65.98	-29.77	QP
2	0.1503	0.33	9.59	9.92	55.98	-46.06	AVG
3	0.1771	24.59	9.59	34.18	64.62	-30.44	QP
4	0.1771	-0.59	9.59	9.00	54.62	-45.62	AVG
5	0.2192	21.82	9.59	31.41	62.85	-31.44	QP
6	0.2192	-2.63	9.59	6.96	52.85	-45.89	AVG
7	0.6481	9.68	9.60	19.28	56.00	-36.72	QP
8	0.6481	-4.29	9.60	5.31	46.00	-40.69	AVG
9	2.1575	9.35	9.63	18.98	56.00	-37.02	QP
10	2.1575	3.22	9.63	12.85	46.00	-33.15	AVG
11	5.3838	6.64	9.62	16.26	60.00	-43.74	QP
12	5.3838	-0.11	9.62	9.51	50.00	-40.49	AVG

Note: 1. Result = Reading +Correct Factor.
 2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).
 4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

LINE N RESULTS (LOW CHANNEL, WORST-CASE CONFIGURATION)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1572	28.40	9.59	37.99	65.61	-27.62	QP
2	0.1572	1.87	9.59	11.46	55.61	-44.15	AVG
3	0.1943	25.88	9.59	35.47	63.85	-28.38	QP
4	0.1943	-0.13	9.59	9.46	53.85	-44.39	AVG
5	0.3276	17.33	9.59	26.92	59.51	-32.59	QP
6	0.3276	-1.40	9.59	8.19	49.51	-41.32	AVG
7	2.1657	8.51	9.63	18.14	56.00	-37.86	QP
8	2.1657	2.21	9.63	11.84	46.00	-34.16	AVG
9	5.1114	6.90	9.62	16.52	60.00	-43.48	QP
10	5.1114	-0.71	9.62	8.91	50.00	-41.09	AVG
11	13.5319	6.34	9.66	16.00	60.00	-44.00	QP
12	13.5319	-1.65	9.66	8.01	50.00	-41.99	AVG

Note: 1. Result = Reading +Correct Factor.
 2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).
 4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Note: All the modes have been tested, only the worst data was recorded in the report.



10. ANTENNA REQUIREMENTS

APPLICABLE REQUIREMENTS

Please refer to FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC §15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

RESULTS

Complies

END OF REPORT