

RF Exposure Evaluation

According to KDB 447498 D01 General RF Exposure Guidance v06 and part 2.1093, Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition(s), listed below, is (are) satisfied.

For 100 MHz to 6 GHz and test separation distances ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f_{(\text{GHz})}}] \leq 3.0$ for 1-g SAR, and ≤ 7.5 for 10-g extremity SAR, where

$f_{(\text{GHz})}$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

Here,

For 433.92MHz

Mode	Max Emeas (dBuV/m)	Max Power(dBm)	Max Power(mW)	Frequency(MHz)	Min. distance(mm)	Calc. thresholds	limit
ASK	76.76	-18.398	0.01	433.92	5	0.00190	3.0

For 315MHz

Mode	Max Emeas (dBuV/m)	Max Power(dBm)	Max Power(mW)	Frequency(MHz)	Min. distance(mm)	Calc. thresholds	limit
OOK	78.26	-16.898	0.02	315	5	0.00269	3.0

$$EIRP = E_{\text{Meas}} + 20 \log(d_{\text{Meas}}) - 104.7$$

EIRP is the equivalent isotropically radiated power, in dBm

E_{Meas} is the field strength of the emission at the measurement distance, in dB μ V/m

d_{Meas} is the measurement distance, in m

For BT

Mode	Max Power(dBm)	Max Power(mW)	Frequency(MHz)	Min. distance(mm)	Calc. thresholds	limit
GFSK	-0.209	0.95	2402	5	0.29540	3.0
$\pi/4$ DQPSK	-0.054	0.99	2402	5	0.30614	3.0
8DPSK	0.13	1.03	2402	5	0.31939	3.0

For BLE

Mode	Max Power(dBm)	Max Power(mW)	Frequency(MHz)	Min. distance(mm)	Calc. thresholds	limit
GFSK	0.806	1.20	2402	5	0.37318	3.0

For 2.4G WiFi

Mode	Max Power(dBm)	Max Power(mW)	Frequency(MHz)	Min. distance(mm)	Calc. thresholds	limit
802.11b	6.245	4.21	2412	5	1.30833	3.0
802.11g	5.907	3.90	2412	5	1.21037	3.0
802.11n(HT20)	5.808	3.81	2412	5	1.18309	3.0
802.11n(HT40)	4.593	2.88	2437	5	0.89900	3.0

Note: The 433MHz, 315MHz, BT, BLE and 2.4G WiFi are not transmitting at the same time.

So a SAR test is not required