



Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640

Fax: +86-755-26648637

Website: www.cqa-cert.com

Report Template Version: V03

Report Template Revision Date: Mar.1st, 2017

RF Exposure Evaluation Report

Report No.: CQASZ20200800898E-02

Applicant: Shenzhen Leadcoo Technology Co.,Ltd

Address of Applicant: Unit 5C, Block A, 5th Floor (A), Financial Technology Building, No. 11 Keyuan Road, Science Park Community, Yuehai Street, Nanshan District, Shenzhen

Equipment Under Test (EUT):

Product: WIFI Module

Model No.: LA-WE2S

Brand Name: N/A

FCC ID: 2AXJE-LA-WE2S

Standards: 47 CFR Part 1.1307
47 CFR Part 2.1093
KDB447498D01 General RF Exposure Guidance v06

Date of Receipt: 2020-08-20

Date of Test: 2020-08-20 to 2020-09-21

Date of Issue: 2020-09-21

Test Result: PASS*

*In the configuration tested, the EUT complied with the standards specified above

Tested By:

Jun Li

(Jun Li)

Reviewed By:

Sheek, Luo

(Sheek Luo)

Approved By:

Jack Ai

(Jack Ai)



1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20200800898E-02	Rev.01	Initial report	2020-09-21

2 Contents

	Page
1 VERSION.....	2
2 CONTENTS.....	3
3 GENERAL INFORMATION.....	4
3.1 CLIENT INFORMATION.....	4
3.2 GENERAL DESCRIPTION OF EUT.....	4
4 SAR EVALUATION.....	5
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	5
4.1.1 Limits.....	5
4.1.2 Test Procedure.....	5
4.1.3 EUT RF Exposure.....	6

3 General Information

3.1 Client Information

Applicant:	Shenzhen Leadcoo Technology Co.,Ltd
Address of Applicant:	Unit 5C, Block A, 5th Floor (A), Financial Technology Building, No. 11 Keyuan Road, Science Park Community, Yuehai Street, Nanshan District, Shenzhen
Manufacturer:	Shenzhen Leadcoo Technology Co.,Ltd
Address of Manufacturer:	Unit 5C, Block A, 5th Floor (A), Financial Technology Building, No. 11 Keyuan Road, Science Park Community, Yuehai Street, Nanshan District, Shenzhen

3.2 General Description of EUT

Product Name:	WIFI Module
Model No.:	LA-WE2S
Trade Mark:	N/A
Hardware version:	V1.5
Software version:	V1.1.0
Operation Frequency:	IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz IEEE 802.11n(HT40): 2422MHz to 2452MHz
Channel Numbers:	IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels IEEE 802.11n HT40: 7 Channels
Channel Separation:	5MHz
Type of Modulation:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g : OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(HT20 and HT40) : OFDM (64QAM,16QAM,QPSK,BPSK)
Transfer Rate:	IEEE for 802.11b: 1Mbps/2Mbps/5.5Mbps/11Mbps IEEE for 802.11g: 6Mbps/9Mbps/12Mbps/18Mbps/24Mbps/36Mbps/48Mbps/54Mbps IEEE for 802.11n(HT20): 6.5Mbps/13Mbps/19.5Mbps/26Mbps/39Mbps/52Mbps/58.5Mbps/65Mbps IEEE for 802.11n(HT40): 13.5Mbps/27Mbps/40.5Mbps/54Mbps/81Mbps/108Mbps/121.5Mbps/135Mbps
Product Type:	Mobile or Fix Location
Test Software of EUT:	UTP (manufacturer declare)
Antenna Type:	PCB antenna
Antenna Gain:	0dBi
Power Supply:	DC 3.3V

4 SAR Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

4.1.3 EUT RF Exposure

1) For WIFI

Antenna Gain: 0dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.0 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Measurement Data

IEEE for 802.11b mode				
Test channel	Average Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2412MHz)	14.54	14.5±1	15.0	31.623
Middle(2437MHz)	14.27	14.0±1	14.5	28.184
Highest(2462MHz)	14.15	14.0±1	14.5	28.184
IEEE for 802.11g mode				
Test channel	Average Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2412MHz)	11.82	11.0±1	12.0	15.849
Middle(2437MHz)	11.65	11.0±1	12.0	15.849
Highest(2462MHz)	11.29	10.5±1	11.5	14.125
IEEE for 802.11n(HT20) mode				
Test channel	Average Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2412MHz)	10.77	10.0±1	11.0	12.589
Middle(2437MHz)	10.50	10.0±1	11.0	12.589
Highest(2462MHz)	10.39	9.5±1	10.5	11.220
IEEE for 802.11n(HT40) mode				
Test channel	Average Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2422MHz)	9.83	9.0±1	10.0	10.000
Middle(2437MHz)	9.79	9.0±1	10.0	10.000
Highest(2452MHz)	9.56	9.0±1	10.0	10.000

The worst case:

Maximum tune-up Power (mW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
31.623	0	0.0063	1.0	PASS

Note: 1) Refer to report No. CQASZ20200800898E-01 for EUT test Max Conducted average Output Power value.

2) $P_d = (P_{out} * G) / (4 * \pi * R^2) = (31.623 * 1.0) / (4 * 3.1416 * 20^2) = 0.0063$