

FCC - TEST REPORT

Report Number : **68.950.24.0442.01** Date of Issue: 2024-11-26

Model : **EAV-RC50**

Product Type : Remote Controller

Applicant : SUZHOU EAVISION ROBOTIC TECHNOLOGIES CO., LTD

Address : Unit 1-A, No.3 Workshop, 28 Xiasheng Road, SIP Suzhou, Jiangsu
China 215000

Manufacturer : SUZHOU EAVISION ROBOTIC TECHNOLOGIES CO., LTD

Address : Unit 1-A, No.3 Workshop, 28 Xiasheng Road, SIP Suzhou, Jiangsu
China 215000

Factory : SUZHOU EAVISION ROBOTIC TECHNOLOGIES CO., LTD

Address : Unit 1-A, No.3 Workshop, 28 Xiasheng Road, SIP Suzhou, Jiangsu
China 215000

Test Result : ☒ **Positive** ☐ **Negative**

Total pages including Appendices : **141**

Any use for advertising purposes must be granted in writing. This technical report may only be quoted in full. This report is the result of a single examination of the object in question and is not generally applicable evaluation of the quality of other products in regular production. For further details, please see testing and certification regulation chapter A-3.4.

1 Table of Contents

1	Table of Contents	2
2	Details about the Test Laboratory	3
3	Description of the Equipment under Test.....	4
4	Summary of Test Standards	5
5	Summary of Test Results.....	6
6	General Remarks.....	7
7	Test Setups.....	8
7.1	Radiated test setups	8
7.2	Conducted RF test setups	9
7.3	AC Power Line Conducted Emission test setups.....	9
8	Systems test configuration.....	10
9	Technical Requirement.....	11
9.1	Conducted Emission.....	11
9.2	Conducted output power.....	14
9.3	6dB bandwidth.....	15
9.4	Power spectral density.....	34
9.5	Spurious RF conducted emissions	53
9.6	Band edge	92
9.7	Spurious radiated emissions for transmitter.....	106
10	Test Equipment List	140
11	System Measurement Uncertainty	141

2 Details about the Test Laboratory

Details about the Test Laboratory

Test Site 1

Company name: TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch
Building 12 & 13, Zhiheng Wisdomland Business Park,
Guankou Erlu, Nantou, Nanshan District,
Shenzhen, Guangdong, China

Telephone: +86 755 8828 6998

Fax: +86 755 8828 5299

FCC Registration No.: 514049

FCC Designation Number: CN5009

3 Description of the Equipment under Test

Product:	Remote Controller
Model no.:	EAV-RC50
Brand Name:	EAVISION
FCC ID:	2AXLB-EAV-RC50
Ratings:	Input: DC20V $\overline{\text{---}}$ 3.25A Battery Capacity: 7.6V, 13100mAh
RF Transmission Frequency:	2412MHz-2462MHz
No. of Operated Channel:	11 for 802.11b/g/n20/ax20 (Wi-Fi) 7 for 802.11n40/ax40 (Wi-Fi)
Modulation:	802.11b: CCK, DSSS 802.11g/n20/n40: BPSK, QPSK, 16-QAM, 64-QAM 802.11ax: BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM, 1024-QAM
Antenna Type:	FPC antenna
Antenna Gain:	-3.3 dBi
Description of the EUT:	EUT is a Remote Controller which support 2.4G (BR, Slot), Bluetooth (BR+EDR+BLE), Wi-Fi operated at 2.4GHz and 5GHz, GSM, WCDMA and LTE. Only 2.4GWIFI included in this report.

NOTE 1: The above EUT's information is declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

4 Summary of Test Standards

Test Standards	
FCC Part 15 Subpart C 10-1-2023 Edition	PART 15 - RADIO FREQUENCY DEVICES Subpart C - Intentional Radiators

All the test methods were according to KDB 558074 D01 15.247 Meas Guidance v05r02 Measurement Guidance and ANSI C63.10-2020.

5 Summary of Test Results

Technical Requirements			
FCC Part 15 Subpart C 10-1-2023 Edition			
Test Condition		Test Result	Test Site
§15.207	Conducted emission AC power port	Pass	Site 1
§15.247 (b) (3)	Conducted output power	Pass	Site 1
§15.247(e)	Power spectral density	Pass	Site 1
§15.247(a)(2)	6dB bandwidth	Pass	Site 1
§15.247(a)(1)	20dB Occupied bandwidth	N/A	--
§15.247(a)(1)	Carrier frequency separation	N/A	--
§15.247(a)(1)(iii)	Number of hopping frequencies	N/A	--
§15.247(a)(1)(iii)	Dwell Time	N/A	--
§15.247(d)	Spurious RF conducted emissions	Pass	Site 1
§15.247(d)	Band edge	Pass	Site 1
§15.247(d) & §15.209 & §15.205	Spurious radiated emissions for transmitter	Pass	Site 1
§15.203	Antenna requirement	Pass See note 1	--

Remark 1: N/A – Not Applicable.

Note 1: The EUT uses a FPC antenna, which gain is -3.3dBi. In accordance to §15.203, it is considered sufficiently to comply with the provisions of this section.

6 General Remarks

Remarks

This submittal(s) (test report) is intended for FCC ID: 2AXLB-EAV-RC50, complies with Section 15.207, 15.209, 15.205, 15.247 of the FCC Part 15 Subpart C rules.

SUMMARY:

All tests according to the regulations cited on page 6 were

■ - Performed

□ - **Not** Performed

The Equipment under Test

■ - **Fulfills** the general approval requirements.

□ - **Does not** fulfill the general approval requirements.

Sample Received Date: 2024-03-01

Testing Start Date: 2024-03-01

Testing End Date: 2024-11-21

- TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch –

Reviewed by:

Prepared by:


Tested by:



John Zhi
Project Manager



Hayden Hu
Project Engineer




Carry Cai
Test Engineer


7 Test Setups

7.1 Radiated test setups


9kHz - 30MHz




Below 1GHz




Above 1GHz



7.2 Conducted RF test setups



7.3 AC Power Line Conducted Emission test setups



8 Systems test configuration

Auxiliary Equipment Used during Test:

DESCRIPTION	MANUFACTURER	MODEL NO.	S/N
LAPTOP	LENOVO	X240	L34015282

The system was configured to channel 1, 6, and 11 for the test.

Test Software Information:

Test Software Version	AmebaZ2_mptool_1V3	
Mode	Setting TX Power	Packet Type
802.11b	Power Index: 14	11b 1 Mbps
802.11g	Power Index: 14	11g 6 Mbps
802.11n HT20	Power Index: 14	MCS0 6.5 Mbps
802.11n HT40	Power Index: 14	MCS0 13.5 Mbps
802.11AX20	Power Index: 14	MCS0 8 Mbps
802. 11AX40	Power Index: 14	MCS0 16 Mbps

9 Technical Requirement

9.1 Conducted Emission

Test Method

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. Both sides of AC line were checked for maximum conducted interference.
6. The frequency range from 150 kHz to 30 MHz was searched.
7. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

Limit


According to §15.207, conducted emissions limit as below:

Frequency MHz	QP Limit dB μ V	AV Limit dB μ V
0.150-0.500	66-56*	56-46*
0.500-5	56	46
5-30	60	50

*Decreasing linearly with logarithm of the frequency

Conducted Emission

Product Type : Remote Controller
 M/N : EAV-RC50
 Operating Condition : Normal Working
 Test Specification : Line
 Comment : AC 120V/60Hz



Critical Freqs

Frequency (MHz)	MaxPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)
0.174000	44.68	---	64.77	20.09	L1	9.54
0.526000	29.42	---	56.00	26.58	L1	9.59
0.902000	29.28	---	56.00	26.72	L1	9.60
2.010000	25.90	---	56.00	30.10	L1	9.62
6.878000	25.81	---	60.00	34.19	L1	9.83
29.794000	39.02	---	60.00	20.98	L1	10.03

Final Result

Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)
---	---	---	---	---	---	---

Remark:


Max Peak= Read level + Corrector factor

Correct factor=cable loss + LISN factor

EUT has more than one typical operation, only the worst test mode will be recorded in this report.

Conducted Emission

Product Type : Remote Controller
 M/N : EAV-RC50
 Operating Condition : WIFI transmission
 Test Specification : Power Line, Neutral
 Comment : AC 120V/60Hz



Critical Freqs

Frequency (MHz)	MaxPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)
0.170000	45.62	---	64.96	19.34	N	9.57
0.538000	28.97	---	56.00	27.03	N	9.62
0.902000	29.89	---	56.00	26.11	N	9.63
2.566000	25.84	---	56.00	30.16	N	9.67
6.502000	27.71	---	60.00	32.29	N	9.84
29.790000	37.81	---	60.00	22.19	N	9.88

Final Result

Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)
---	---	---	---	---	---	---

Remark:

Level=Reading Level + Correction Factor


Correction Factor=Cable Loss + LISN Factor

(The Reading Level is recorded by software which is not shown in the sheet)

9.2 Conducted output power

Test Method

- 1) The EUT is configured to transmit continuously, or to transmit with a constant duty cycle.
- 2) At all times when the EUT is transmitting, it shall be transmitting at its maximum power control level.
- 3) The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.
- 4) Measure the peak power of the transmitter. This measurement is a peak over both the ON and OFF periods of the transmitter.



Power meter conducted test setup

Limits

According to §15.247 (b) (3), conducted output power limit as below:

Frequency Range MHz	Limit W	Limit dBm
2400-2483.5	≤1	≤30

Test results

Mode	TX Type	Frequency (MHz)	Maximum Peak Conducted Output Power (dBm)				Verdict
			ANT1	ANT2	MIMO	Limit	
802.11b	SISO	2412	18.6	18.2	21.4	≤30	Pass
		2437	18.10	18.0	21.1	≤30	Pass
		2462	18.50	18.5	21.5	≤30	Pass
802.11g	SISO	2412	18.20	17.9	21.1	≤30	Pass
		2437	17.80	17.8	20.8	≤30	Pass
		2462	18.10	18.1	21.1	≤30	Pass
802.11n (HT20)	SISO	2412	18.20	17.7	21.0	≤30	Pass
		2437	17.80	17.7	20.8	≤30	Pass
		2462	18.00	18.0	21.0	≤30	Pass
802.11n (HT40)	SISO	2422	18.5	17.4	21.0	≤30	Pass
		2437	18.1	17.8	21.0	≤30	Pass
		2452	18.4	17.8	21.1	≤30	Pass
802.11ax (HEW20)	SISO	2412	17.00	16.7	19.9	≤30	Pass
		2437	16.60	16.4	19.5	≤30	Pass
		2462	16.80	17.0	19.9	≤30	Pass
802.11ax (HEW40)	SISO	2422	17.3	16.1	19.8	≤30	Pass
		2437	16.9	16.6	19.8	≤30	Pass
		2452	17.1	16.8	20.0	≤30	Pass

9.3 6dB bandwidth

Test Method

1. The RF output of EUT was connected to the spectrum analyzer. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting, the instrument center frequency is set to the nominal EUT channel center frequency enable the EUT transmit continuously.
3. Use the following spectrum analyzer settings:
RBW=1% to 5% of the occupied bandwidth but not less than 100kHz, VBW $\geq$ 3RBW, Sweep = auto, Detector function = peak, Trace = max hold
4. Use the automatic bandwidth measurement capability of an instrument, use the X dB bandwidth mode with X set to 6 dB.
5. Allow the trace to stabilize, record the 6 dB Bandwidth value.

Limit



Limit [kHz]

≥ 500


Test results

Mode	TX Type	Frequency (MHz)	ANT	6dB Bandwidth (MHz)		Verdict
				Result	Limit	
802.11b	SISO	2412	1	8.330	≥ 0.5	Pass
		2412	2	8.340	≥ 0.5	Pass
		2437	1	8.341	≥ 0.5	Pass
		2437	2	8.330	≥ 0.5	Pass
		2462	1	8.697	≥ 0.5	Pass
		2462	2	8.320	≥ 0.5	Pass
802.11g	SISO	2412	1	16.337	≥ 0.5	Pass
		2412	2	16.434	≥ 0.5	Pass
		2437	1	16.498	≥ 0.5	Pass
		2437	2	16.387	≥ 0.5	Pass
		2462	1	16.460	≥ 0.5	Pass
		2462	2	16.450	≥ 0.5	Pass
802.11n (HT20)	MIMO	2412	1	17.380	≥ 0.5	Pass
		2412	2	17.496	≥ 0.5	Pass
		2437	1	17.634	≥ 0.5	Pass
		2437	2	17.446	≥ 0.5	Pass
		2462	1	17.257	≥ 0.5	Pass
		2462	2	17.437	≥ 0.5	Pass
802.11n (HT40)	MIMO	2422	1	35.452	≥ 0.5	Pass
		2422	2	35.887	≥ 0.5	Pass
		2437	1	35.929	≥ 0.5	Pass
		2437	2	36.015	≥ 0.5	Pass
		2452	1	35.772	≥ 0.5	Pass
		2452	2	36.001	≥ 0.5	Pass
802.11ax (HEW20)	MIMO	2412	1	19.003	≥ 0.5	Pass
		2412	2	19.055	≥ 0.5	Pass
		2437	1	19.066	≥ 0.5	Pass
		2437	2	19.081	≥ 0.5	Pass
		2462	1	18.940	≥ 0.5	Pass
		2462	2	18.956	≥ 0.5	Pass
802.11ax (HEW40)	MIMO	2422	1	37.476	≥ 0.5	Pass
		2422	2	37.724	≥ 0.5	Pass
		2437	1	38.126	≥ 0.5	Pass
		2437	2	38.042	≥ 0.5	Pass
		2452	1	37.659	≥ 0.5	Pass
		2452	2	37.981	≥ 0.5	Pass


Test Graphs




802.11b_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11b_MCH_2437MHz_Ant2 (SISO)_NTNV




802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11b_HCH_2462MHz_Ant2 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant2 (SISO)_NTNV



802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_MCH_2437MHz_Ant2 (SISO)_NTNV







802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant2 (SISO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant1 (MIMO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant2 (MIMO)_NTNV




802.11n(HT20)_LCH_2437MHz_Ant1 (MIMO)_NTNV




802.11n(HT20)_LCH_2437MHz_Ant2 (MIMO)_NTNV



802.11n(HT20) LCH_2462MHz_Ant1 (MIMO)_NTNV




802.11n(HT20) LCH_2462MHz_Ant2 (MIMO)_NTNV







802.11n(HT40)_LCH_2422MHz_Ant1 (MIMO)_NTNV




802.11n(HT40)_LCH_2422MHz_Ant2 (MIMO)_NTNV




802.11n(HT40)_LCH_2437MHz_Ant1 (MIMO)_NTNV




802.11n(HT40)_LCH_2437MHz_Ant2 (MIMO)_NTNV



802.11n(HT40)_LCH_2452MHz_Ant1 (MIMO)_NTNV




802.11n(HT40)_LCH_2452MHz_Ant2 (MIMO)_NTNV







802.11ax(HEW20)_LCH_2412MHz_RU242_61_Ant1 (MIMO)_NTNV




802.11ax(HEW20)_LCH_2412MHz_RU242_61_Ant2 (MIMO)_NTNV




802.11ax(HEW20)_LCH_2437MHz_RU242_61_Ant1 (MIMO)_NTNV




802.11ax(HEW20)_LCH_2437MHz_RU242_61_Ant2 (MIMO)_NTNV




802.11ax(HEW20)_HCH_2462MHz_RU242_61_Ant1 (SISO)_NTNV




802.11ax(HEW20)_HCH_2462MHz_RU242_61_Ant2 (SISO)_NTNV




802.11ax(HEW40)_MCH_2422MHz_RU484_65_Ant1 (SISO)_NTNV




802.11ax(HEW40)_MCH_2422MHz_RU484_65_Ant2 (SISO)_NTNV




802.11ax(HEW40)_MCH_2437MHz_RU484_65_Ant1 (SISO)_NTNV




802.11ax(HEW40)_MCH_2437MHz_RU484_65_Ant2 (SISO)_NTNV



802.11ax(HEW40)_MCH_2452MHz_RU484_65_Ant1 (SISO)_NTNV



802.11ax(HEW40)_MCH_2452MHz_RU484_65_Ant2 (SISO)_NTNV



9.4 Power spectral density

Test Method

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance:

1. The RF output of EUT was connected to the spectrum analyzer. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting, the instrument center frequency is set to the nominal EUT channel center frequency enable the EUT transmit continuously.
3. Use the following spectrum analyzer settings:
4. Set analyzer center frequency to DTS channel center frequency. RBW=3kHz, VBW $\geq$ 3RBW, Span=1.5 times DTS bandwidth, Detector=Peak, Sweep=auto, Trace= max hold.
5. Allow trace to fully stabilize, use the peak marker function to determine the maximum amplitude level within the RBW.
6. Repeat above procedures until other frequencies measured were completed.

Limit



Limit [dBm/3kHz]

≤ 8

Test results


Mode	TX Type	Frequency (MHz)	Maximum PSD (dBm/3kHz)				Verdict
			ANT1	ANT2	MIMO	Limit	
802.11b	SISO	2412	-6.98	-7.14	/	≤ 8	Pass
		2437	-8.16	-7.89	/	≤ 8	Pass
		2462	-6.06	-7.16	/	≤ 8	Pass
802.11g	SISO	2412	-10.93	-10.24	/	≤ 8	Pass
		2437	-10.26	-9.91	/	≤ 8	Pass
		2462	-10.24	-10.12	/	≤ 8	Pass
802.11n (HT20)	SISO	2412	-7.78	-7.87	-4.8	≤ 8	Pass
		2437	-9.07	-9.04	-6.0	≤ 8	Pass
		2462	-9.20	-8.87	-6.0	≤ 8	Pass
802.11n (HT40)	SISO	2422	-11.50	-12.85	-9.1	≤ 8	Pass
		2437	-11.94	-11.71	-8.8	≤ 8	Pass
		2452	-11.55	-12.01	-8.8	≤ 8	Pass
802.11ax (HEW20)	SISO	2412	-11.71	-11.21	-8.4	≤ 8	Pass
		2437	-11.23	-11.39	-8.3	≤ 8	Pass
		2462	-11.62	-11.17	-8.4	≤ 8	Pass
802.11ax (HEW40)	SISO	2422	-13.44	-14.48	-10.9	≤ 8	Pass
		2437	-13.40	-13.33	-10.4	≤ 8	Pass
		2452	-13.09	-13.99	-10.5	≤ 8	Pass

Test Graphs







802.11b_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11b_MCH_2437MHz_Ant2 (SISO)_NTNV




802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11b_HCH_2462MHz_Ant2 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant2 (SISO)_NTNV




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_MCH_2437MHz_Ant2 (SISO)_NTNV



802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant2 (SISO)_NTNV






802.11n(HT20)_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant2 (SISO)_NTNV






802.11n(HT20)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_MCH_2437MHz_Ant2 (SISO)_NTNV






802.11n(HT20)_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_HCH_2462MHz_Ant2 (SISO)_NTNV






802.11n(HT40)_LCH_2422MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_LCH_2422MHz_Ant2 (SISO)_NTNV







802.11n(HT40)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_MCH_2437MHz_Ant2 (SISO)_NTNV




802.11n(HT40)_HCH_2452MHz_Ant1 (SISO)_NTNV



802.11n(HT40)_HCH_2452MHz_Ant2 (SISO)_NTNV



802.11ax(HEW20)_LCH_2412MHz_RU242_61_Ant1 (SISO)_NTNV



802.11ax(HEW20)_LCH_2412MHz_RU242_61_Ant2 (SISO)_NTNV

