



Shenzhen HTT Technology Co., Ltd.

TEST REPORT

FCC Rules and Regulations Part PART 15.249

Report Reference No.....: **HTT202409725F01**

FCC ID.....: **2AXWL-XPRO5**

Compiled by
(position+printed name+signature.. File administrators

Heber He

Supervised by
(position+printed name+signature.. Project Engineer

Bruce Zhu

Approved by
(position+printed name+signature.. RF Manager

Kevin Han



Date of issue..... Oct. 12, 2024

Testing Laboratory Name Shenzhen HTT Technology Co.,Ltd.

Address..... 1F, Building B, Huafeng International Robotics Industrial Park,
Hangcheng Road,Nanchang Community, Xixiang Street, Bao'an
District, Shenzhen, Guangdong, China

Applicant's name Guangzhou Zhiying Technology Co., Ltd

Address Room 2401, Room 2402, Room 2403, Room 2404, Room 2409, No.
68, Huadi Avenue Middle, Liwan District, Guangzhou

Standard **FCC Rules and Regulations Part PART 15.249**

Shenzhen HTT Technology Co.,Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen HTT Technology Co.,Ltd. is acknowledged as copyright owner and source of the material. Shenzhen HTT Technology Co.,Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

**Test item description XTalk X5 Digital 2.4GHz 5-Person Full Duplex
Wireless Intercom Headset System**

Trade Mark SYNCO

Manufacturer Guangzhou Shengke Technology Co., Ltd

Model/Type reference..... XPRO5

Listed Models S1, S2, S5, S9, S13, XPRO1, XPRO2, XPRO9, XPRO13, XMAX1,
XMAX2, XMAX5, XMAX9, XMAX13, X LINK

Modulation GFSK

Frequency..... 2402-2480MHz

Ratings DC 3.7V From Battery and DC 5V From External Circuit

Result..... **PASS**

TEST REPORT

Equipment under Test : XTalk X5 Digital 2.4GHz 5-Person Full Duplex
Wireless Intercom Headset System

Model /Type : **XPRO5**

Listed Models : S1, S2, S5, S9, S13, XPRO1, XPRO2, XPRO9, XPRO13,
XMAX1, XMAX2, XMAX5, XMAX9, XMAX13, X LINK

Applicant : **Guangzhou Zhiying Technology Co., Ltd**

Address : Room 2401, Room 2402, Room 2403, Room 2404, Room 2409,
No. 68, Huadi Avenue Middle, Liwan District, Guangzhou

Manufacturer : **Guangzhou Shengke Technology Co., Ltd**

Address : 2nd Floor, No.68 Xieshi Road, Panyu District, Guangzhou, China

Test Result:	PASS
---------------------	-------------

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

- 1. TEST STANDARDS..... 4**

- 2. SUMMARY..... 5**
 - 2.1. General Remarks5
 - 2.2. Product Description5
 - 2.3. Equipment Under Test5
 - 2.4. Short description of the Equipment under Test (EUT)5
 - 2.5. EUT operation mode5
 - 2.6. Block Diagram of Test Setup.....6
 - 2.7. Modifications6

- 3. TEST ENVIRONMENT 7**
 - 3.1. Address of the test laboratory7
 - 3.2. Test Facility7
 - 3.3. Environmental conditions7
 - 3.4. Summary of measurement results8
 - 3.5. Statement of the measurement uncertainty8
 - 3.6. Equipments Used during the Test8

- 4. TEST CONDITIONS AND RESULTS 10**
 - 4.1. AC Power Conducted Emission..... 10
 - 4.2. Radiated Emission and Band Edges 13
 - 4.3. 20dB Bandwidth Measurement20
 - 4.4. Antenna Requirement25

- 5. TEST SETUP PHOTOS OF THE EUT 26**

- 6. TEST PHOTOS OF THE EUT..... 26**

1. TEST STANDARDS

The tests were performed according to following standards:

FCC Rules Part 15.249: Operation within the bands 902 - 928 MHz, 2400 - 2483.5 MHz, 5725 - 5875 MHz, and 24.0 - 24.25 GHz.

ANSI C63.10:2013 : American National Standard for Testing Unlicensed Wireless Devices

ANSI C63.4: 2014: –American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40GHz
Range of 9 kHz to 40GHz

2. SUMMARY

2.1. General Remarks

Date of receipt of test sample	:	Sep. 30, 2024
Testing commenced on	:	Sep. 30, 2024
Testing concluded on	:	Oct. 12, 2024

2.2. Product Description

Name of EUT	XTalk X5 Digital 2.4GHz 5-Person Ful Duplex Wireless Intercom Headset System
Model Number	XPRO5
List Model:	S1, S2, S5, S9, S13, XPRO1, XPRO2, XPRO9, XPRO13, XMAX1, XMAX2, XMAX5, XMAX9, XMAX13, X LINK
Power Rating	DC 3.7V From Battery and DC 5V From External Circuit
Sample ID:	HTT202409725-1#(Engineer sample) HTT202409725-2#(Normal sample)
Operation frequency	2402-2480MHz
Modulation	GFSK
Antenna Type	Copper tube antenna
Antenna Gain	4.44 dBi for ANT1 and ANT2
Firmware Version	V4.1
Hardware Version	2.0

2.3. Equipment Under Test

Power supply system utilised

Power supply voltage	:	<input type="radio"/> 230V / 50 Hz	<input type="radio"/> 120V / 60Hz
		<input type="radio"/> 12 V DC	<input type="radio"/> 24 V DC
		<input checked="" type="radio"/> Other (specified in blank below)	

DC 3.7V From Battery and DC 5V From External Circuit

2.4. Short description of the Equipment under Test (EUT)

This is a XTalk X5 Digital 2.4GHz 5-Person Ful Duplex Wireless Intercom Headset System

For more details, refer to the user's manual of the EUT.

2.5. EUT operation mode

The Applicant use Key to control the EUT for staying in continuous transmitting and receiving mode for testing .There is 40 channels provided to the EUT. Channel Low, Mid and High was selected to test.


Channel	Frequency(MHz)	Channel	Frequency(MHz)
00	2402	20	2442
01	2404	21	2444
02	2406	22	2446
03	2408	23	2448
04	2410	24	2450
05	2412	25	2452
06	2414	26	2454

07	2416	27	2456
08	2418	28	2458
09	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

Test frequency:

Channel	Frequency (MHz)
Low	2402
Mid	2440
High	2480

2.6. Block Diagram of Test Setup



2.7. Modifications

No modifications were implemented to meet testing criteria.

3. TEST ENVIRONMENT

3.1. Address of the test laboratory

Shenzhen HTT Technology Co.,Ltd.

1F, Building B, Huafeng International Robotics Industrial Park, Hangcheng Road,Nanchang Community, Xixiang Street, Bao'an District, Shenzhen, Guangdong, China

3.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 779513 Designation Number: CN1319

Shenzhen HTT Technology Co.,Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

A2LA-Lab Cert. No.: 6435.01

Shenzhen HTT Technology Co.,Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.10 and CISPR 16-1-4:2010.

3.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Radiated Emission:

Temperature:	23 ° C
Humidity:	48 %
Atmospheric pressure:	950-1050mbar

AC Main Conducted testing:

Temperature:	24 ° C
Humidity:	45 %
Atmospheric pressure:	950-1050mbar

Conducted testing:

Temperature:	24 ° C
Humidity:	45 %
Atmospheric pressure:	950-1050mbar

3.4. Summary of measurement results

FCC PART 15.249		
FCC Part 15.249(a)	Field Strength of Fundamental	PASS
FCC Part 15.209	Spurious Emission	PASS
FCC Part 15.209	Band edge	PASS
FCC Part 15.215(c)	20dB bandwidth	PASS
FCC Part 15.207	Conducted Emission	PASS
FCC Part 15.203	Antenna Requirement	PASS

3.5. Statement of the measurement uncertainty

Measurement Uncertainty

Conducted Emission Expanded Uncertainty	=	2.68 dB, k=2
Radiated emission expanded uncertainty(9kHz-30MHz)	=	2.54dB, k=2
Radiated emission expanded uncertainty(30MHz-1000MHz)	=	4.37 dB, k=2
Radiated emission expanded uncertainty(1~18GHz)	=	5.40 dB, k=2
Radiated emission expanded uncertainty(18-40GHz)	=	5.45 dB, k=2

3.6. Equipments Used during the Test

Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	Shenzhen C.R.T technology co., LTD	9*6*6	HTT-E028	Aug. 10 2024	Aug. 09 2027
2	Control Room	Shenzhen C.R.T technology co., LTD	4.8*3.5*3.0	HTT-E030	Aug. 10 2024	Aug. 09 2027
3	EMI Test Receiver	Rohde&Schwarz	ESCI7	HTT-E022	Apr. 26 2024	Apr. 25 2025
4	Spectrum Analyzer	Rohde&Schwarz	FSP	HTT-E037	Apr. 26 2024	Apr. 25 2025
5	Coaxial Cable	ZDecl	ZT26-NJ-NJ-0.6M	HTT-E018	Apr. 26 2024	Apr. 25 2025
6	Coaxial Cable	ZDecl	ZT26-NJ-SMAJ-2M	HTT-E019	Apr. 26 2024	Apr. 25 2025
7	Coaxial Cable	ZDecl	ZT26-NJ-SMAJ-0.6M	HTT-E020	Apr. 26 2024	Apr. 25 2025
8	Coaxial Cable	ZDecl	ZT26-NJ-SMAJ-8.5M	HTT-E021	Apr. 26 2024	Apr. 25 2025
9	Composite logarithmic antenna	Schwarzbeck	VULB 9168	HTT-E017	May. 21 2024	May. 20 2025
10	Horn Antenna	Schwarzbeck	BBHA9120D	HTT-E016	May. 20 2024	May. 19 2025
11	Loop Antenna	Zhinan	ZN30900C	HTT-E039	Apr. 26 2024	Apr. 25 2025
12	Horn Antenna	Beijing Hangwei Dayang	OBH100400	HTT-E040	Apr. 26 2024	Apr. 25 2025
13	low frequency Amplifier	Sonoma Instrument	310	HTT-E015	Apr. 26 2024	Apr. 25 2025
14	high-frequency Amplifier	HP	8449B	HTT-E014	Apr. 26 2024	Apr. 25 2025
15	Variable frequency power supply	Shenzhen Anbiao Instrument Co., Ltd	ANB-10VA	HTT-082	Apr. 26 2024	Apr. 25 2025
16	EMI Test Receiver	Rohde & Schwarz	ESCS30	HTT-E004	Apr. 26 2024	Apr. 25 2025
17	Artificial Mains	Rohde & Schwarz	ESH3-Z5	HTT-E006	May. 23 2024	May. 22 2025
18	Artificial Mains	Rohde & Schwarz	ENV-216	HTT-E038	May. 23 2024	May. 22 2025
19	Cable Line	Robinson	Z302S-NJ-BNCJ-1.5M	HTT-E001	Apr. 26 2024	Apr. 25 2025
20	Attenuator	Robinson	6810.17A	HTT-E007	Apr. 26 2024	Apr. 25 2025
21	Variable frequency power	Shenzhen Yanghong	YF-650 (5KVA)	HTT-E032	Apr. 26 2024	Apr. 25 2025


	supply	Electric Co., Ltd				
22	Control Room	Shenzhen C.R.T technology co., LTD	8*4*3.5	HTT-E029	Aug. 10 2024	Aug. 09 2027
23	DC power supply	Agilent	E3632A	HTT-E023	Apr. 26 2024	Apr. 25 2025
24	EMI Test Receiver	Agilent	N9020A	HTT-E024	Apr. 26 2024	Apr. 25 2025
25	Analog signal generator	Agilent	N5181A	HTT-E025	Apr. 26 2024	Apr. 25 2025
26	Vector signal generator	Agilent	N5182A	HTT-E026	Apr. 26 2024	Apr. 25 2025
27	Power sensor	Keysight	U2021XA	HTT-E027	Apr. 26 2024	Apr. 25 2025
28	Temperature and humidity meter	Shenzhen Anbiao Instrument Co., Ltd	TH10R	HTT-074	Apr. 28 2024	Apr. 27 2025
29	Radiated Emission Test Software	Farad	EZ-EMC	N/A	N/A	N/A
30	Conducted Emission Test Software	Farad	EZ-EMC	N/A	N/A	N/A
31	RF Test Software	panshanrf	TST	N/A	N/A	N/A

Note: The Cal.Interval was one year.

4. TEST CONDITIONS AND RESULTS

4.1. AC Power Conducted Emission

TEST CONFIGURATION



TEST PROCEDURE

- 1, The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10.
- 2, Support equipment, if needed, was placed as per ANSI C63.10.
- 3, All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4, If a EUT received DC power from the USB Port of Notebook PC, the PC's adapter received power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5, All support equipments received AC power from a second LISN, if any.
- 6, The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7, Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.

AC Power Conducted Emission Limit

For intentional device, according to § 15.207(a) AC Power Conducted Emission Limits is as following :

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50


* Decreases with the logarithm of the frequency.

TEST RESULTS

Remark: Both high and low voltages have been tested to show only the worst low voltage test data.


Measurement data:

Line:



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz		dB	dBuV	dBuV	dB	
1	*	0.1544	37.68	10.16	47.84	65.76	-17.92	QP
2		0.1544	21.80	10.16	31.96	55.76	-23.80	AVG
3		0.3050	23.89	10.24	34.13	60.11	-25.98	QP
4		0.3050	10.33	10.24	20.57	50.11	-29.54	AVG
5		0.6313	13.39	10.32	23.71	56.00	-32.29	QP
6		0.6313	3.34	10.32	13.66	46.00	-32.34	AVG
7		2.5129	13.02	10.45	23.47	56.00	-32.53	QP
8		2.5129	1.83	10.45	12.28	46.00	-33.72	AVG
9		4.3964	15.46	10.60	26.06	56.00	-29.94	QP
10		4.3964	3.84	10.60	14.44	46.00	-31.56	AVG
11		8.1320	25.78	10.65	36.43	60.00	-23.57	QP
12		8.1320	14.62	10.65	25.27	50.00	-24.73	AVG

Neutral:



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz		dB	dBuV	dBuV	dB	Detector
1	*	0.1544	37.11	10.16	47.27	65.76	-18.49	QP
2		0.1544	20.65	10.16	30.81	55.76	-24.95	AVG
3		0.2812	24.47	10.23	34.70	60.78	-26.08	QP
4		0.2812	10.73	10.23	20.96	50.78	-29.82	AVG
5		0.6314	17.50	10.35	27.85	56.00	-28.15	QP
6		0.6314	4.60	10.35	14.95	46.00	-31.05	AVG
7		2.5350	21.40	10.43	31.83	56.00	-24.17	QP
8		2.5350	12.04	10.43	22.47	46.00	-23.53	AVG
9		4.4360	20.17	10.53	30.70	56.00	-25.30	QP
10		4.4360	8.85	10.53	19.38	46.00	-26.62	AVG
11		6.5757	27.44	10.66	38.10	60.00	-21.90	QP
12		6.5757	16.97	10.66	27.63	50.00	-22.37	AVG


Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level =Receiver Read level + LISN Factor + Cable Los


4.2. Radiated Emission and Band Edges

TEST CONFIGURATION


Frequency range 9 KHz – 30MHz



Frequency range 30MHz – 1000MHz



Frequency range above 1GHz-25GHz



TEST PROCEDURE

1. The EUT was placed on a turn table which is 0.8m above ground plane when testing frequency range 9 KHz –25GHz.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0°C to 360°C to acquire the highest emissions from EUT.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.
5. The EUT minimum operation frequency was 26MHz and maximum operation frequency was 1910MHz.so radiated emission test frequency band from 9KHz to 25GHz.
6. The distance between test antenna and EUT as following table states:

Test Frequency range	Test Antenna Type	Test Distance
9KHz-30MHz	Active Loop Antenna	3
30MHz-1GHz	Ultra-Broadband Antenna	3
1GHz-18GHz	Double Ridged Horn Antenna	3
18GHz-25GHz	Horn Antenna	1

7. Setting test receiver/spectrum as following table states:

Test Frequency range	Test Receiver/Spectrum Setting	Detector
9KHz-150KHz	RBW=200Hz/VBW=3KHz, Sweep time=Auto	QP
150KHz-30MHz	RBW=9KHz/VBW=100KHz, Sweep time=Auto	QP
30MHz-1GHz	RBW=120KHz/VBW=1000KHz, Sweep time=Auto	QP
1GHz-40GHz	Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto	Peak

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

FS = RA + AF + CL - AG

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

Transd=AF +CL-AG

RADIATION LIMIT

According 15.249, the field strength of emissions from intentional radiators operated within 2400MHz-2483.5 MHz shall not exceed 94dBµV/m (50mV/m):

FCC PART 15.249(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a)

Radiated emission limits


Frequency (MHz)	Distance (Meters)	Radiated (dBµV/m)	Radiated (µV/m)
0.009-0.49	3	20log(2400/F(KHz))+40log(300/3)	2400/F(KHz)
0.49-1.705	3	20log(24000/F(KHz))+ 40log(30/3)	24000/F(KHz)
1.705-30	3	20log(30)+ 40log(30/3)	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500


TEST RESULTS

Remark:

1. This test was performed with EUT in X, Y, Z position and the worse case was found when EUT in X position.
2. Both modes of GFSK were tested at Low, Middle, and High channel and recorded worst mode at GFSK
3. Radiated emission test from 9 KHz to 10th harmonic of fundamental was verified, and no emission found except system noise floor in 9 KHz to 30MHz and not recorded in this report.

For 30MHz-1GHz





For 1GHz to 25GHz

Frequency(MHz):			2402		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2402.00	87.41	PK	114	26.59	87.61	27.5	5	32.7	-0.2
2402.00	76.33	AV	94	17.67	76.53	27.5	5	32.7	-0.2
4804.00	59.87	PK	74	14.13	54.17	31	6.5	31.8	5.7
4804.00	45.12	AV	54	8.88	39.42	31	6.5	31.8	5.7
7206.00	54.99	PK	74	19.01	42.34	36	8.15	31.5	12.65
7206.00	43.83	AV	54	10.17	31.18	36	8.15	31.5	12.65

Frequency(MHz):			2402		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2402.00	87.69	PK	114	26.31	87.89	27.5	5	32.7	-0.2
2402.00	76.86	AV	94	17.14	77.06	27.5	5	32.7	-0.2
4804.00	58.93	PK	74	15.07	53.23	31	6.5	31.8	5.7
4804.00	45.67	AV	54	8.33	39.97	31	6.5	31.8	5.7
7206.00	53.12	PK	74	20.88	40.47	36	8.15	31.5	12.65
7206.00	43.74	AV	54	10.26	31.09	36	8.15	31.5	12.65

Frequency(MHz):			2440		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2440.00	87.38	PK	114	26.62	87.33	27.55	5.1	32.6	0.05
2440.00	75.57	AV	94	18.43	75.52	27.55	5.1	32.6	0.05
4880.00	61.17	PK	74	12.83	55.01	31.2	6.61	31.65	6.16
4880.00	44.48	AV	54	9.52	38.32	31.2	6.61	31.65	6.16
7320.00	54.06	PK	74	19.94	41.11	36.2	8.23	31.48	12.95
7320.00	44.93	AV	54	9.07	31.98	36.2	8.23	31.48	12.95

Frequency(MHz):			2440		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2440.00	89.41	PK	114	24.59	89.36	27.55	5.1	32.6	0.05
2440.00	78.28	AV	94	15.72	78.23	27.55	5.1	32.6	0.05
4880.00	62.29	PK	74	11.71	56.13	31.2	6.61	31.65	6.16
4880.00	43.90	AV	54	10.10	37.74	31.2	6.61	31.65	6.16
7320.00	55.41	PK	74	18.59	42.46	36.2	8.23	31.48	12.95
7320.00	44.43	AV	54	9.57	31.48	36.2	8.23	31.48	12.95

Frequency(MHz):			2480		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2480.00	89.22	PK	114	24.78	88.98	27.6	5.14	32.5	0.24
2480.00	46.66	AV	94	47.34	46.42	27.6	5.14	32.5	0.24
4960.00	62.29	PK	74	11.71	55.63	31.4	6.76	31.5	6.66
4960.00	42.26	AV	54	11.74	35.60	31.4	6.76	31.5	6.66
7440.00	55.27	PK	74	18.73	41.97	36.4	8.35	31.45	13.3
7440.00	45.84	AV	54	8.16	32.54	36.4	8.35	31.45	13.3

Frequency(MHz):			2480		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2480.00	90.66	PK	114	23.34	90.42	27.6	5.14	32.5	0.24
2480.00	76.52	AV	94	17.48	76.28	27.6	5.14	32.5	0.24
4960.00	63.50	PK	74	10.50	56.84	31.4	6.76	31.5	6.66
4960.00	43.31	AV	54	10.69	36.65	31.4	6.76	31.5	6.66
7440.00	55.21	PK	74	18.79	41.91	36.4	8.35	31.45	13.3
7440.00	45.28	AV	54	8.72	31.98	36.4	8.35	31.45	13.3

Remark:
 (1) Data of measurement within this frequency range shown “--- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
 (2) When the test results of Peak Detected below the limits of Average Detected, the Average Detected is not need completed.


Results of Band Edges Test (Radiated)

Operation Mode: GFSK

Frequency(MHz):			2402		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2390.00	60.99	PK	74	13.01	62.38	27.2	4.31	32.9	-1.39
2390.00	45.27	AV	54	8.73	46.66	27.2	4.31	32.9	-1.39
Frequency(MHz):			2402		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2390.00	59.60	PK	74	14.40	60.99	27.2	4.31	32.9	-1.39
2390.00	47.10	AV	54	6.90	48.49	27.2	4.31	32.9	-1.39
Frequency(MHz):			2480		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2483.50	56.64	PK	74	17.36	57.57	27.4	4.47	32.8	-0.93
2483.50	46.23	AV	54	7.77	47.16	27.4	4.47	32.8	-0.93
Frequency(MHz):			2480		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2483.50	55.67	PK	74	18.33	56.60	27.4	4.47	32.8	-0.93
2483.50	43.88	AV	54	10.12	44.81	27.4	4.47	32.8	-0.93

4.3. 20dB Bandwidth Measurement

TEST CONFIGURATION



TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30KHz RBW and 300KHz VBW.

The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

LIMIT

N/A

TEST RESULTS

ANT1

Mode	Channel	20dB bandwidth (MHz)	Result
1M	Low	1.187	PASS
	Mid	1.167	
	High	1.139	
2M	Low	2.366	PASS
	Mid	2.324	
	High	2.433	

ANT2

Mode	Channel	20dB bandwidth (MHz)	Result
1M	Low	1.173	PASS
	Mid	1.201	
	High	1.186	
2M	Low	2.231	PASS
	Mid	2.307	
	High	2.228	

Note: 1.The test results including the cable lose.

ANT1

1M



Low



Mid



High

2M



Low



Mid



High

ANT2

1M



Low



Mid



High

2M



Low



Mid



High

4.4. Antenna Requirement

Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (c), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

Antenna Information

The maximum gain of antenna was 4.44 dBi for ANT1 and ANT2 .

Remark:The antenna gain is provided by the customer , if the data provided by the customer is not accurate, Shenzhen HTT Technology Co.,Ltd. does not assume any responsibility.

5. Test Setup Photos of the EUT

Reference to the **appendix I** for details

6. Test Photos of the EUT

Reference to the **appendix II** for details.

.....**End of Report**.....