



RF TEST REPORT

Report No.: SET2023-00300

Product Name: RICO Thermal Imaging Sights

FCC ID: 2AYGT-RICO

Model No. : RH50

Serial Model No. : RH50 PRO, RL42, RL42R, RH50R, RH50, RA50, RA50R

Applicant: IRay Technology Co., Ltd.

Address: 11GUIYANG STREET, YANTAI ECONOMY AND TECHNOLOGY
DEVELOPMENT DISTRICT, YANTAI SHANDONG P.R.CHINA.

Dates of Testing: 02/15/2023 —02/15/2023

Issued by: CCIC Southern Testing Co., Ltd.

Lab Location: Electronic Testing Building, No. 43 Shahe Road, Xili Street,
Nanshan District, Shenzhen, Guangdong, China.

Tel: 86 755 26627338 **Fax:** 86 755 26627238

This test report consists of 54 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CCIC-SET. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver. Any objections must be raised to CCIC-SET within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit.



Test Report

Product Name.....: RICO Thermal Imaging Sights

Brand Name.....: InfiRay

Trade Name.....: InfiRay

Applicant.....: IRay Technology Co., Ltd.

Applicant Address.....: 11GUIYANG STREET, YANTAI ECONOMY AND
TECHNOLOGY DEVELOPMENT DISTRICT, YANTAI
SHANDONG P.R.CHINA.

Manufacturer.....: IRay Technology Co., Ltd.

Manufacturer Address.....: 11GUIYANG STREET, YANTAI ECONOMY AND
TECHNOLOGY DEVELOPMENT DISTRICT, YANTAI
SHANDONG P.R.CHINA.

Test Standards.....: 47 CFR Part 15 Subpart C
ANSI C63.10-2013
KDB558074 D01 DTS Meas Guidance v05r02

Test Result.....: PASS

Tested by

Kim Li

2023.02.15

Kim Li, Test Engineer

Reviewed by

Chris You

2023.02.15

Chris You, Senior Engineer

Approved by

Hou Tao

2023.02.15

Hou Tao, Manager

TABLE OF CONTENTS

RF TEST REPORT	1
1. GENERAL INFORMATION	4
1.1. EUT Description	4
1.2. Test Standards and Results	5
1.3. Table for Supporting Units	6
1.4. EUT Operation Test Setup	6
1.5. Facilities and Accreditations	6
2. TEST REQUIREMENTS	7
2.1. Antenna requirement	7
2.2. Maximum Conducted Output Power	8
2.3. 6dB Occupied Bandwidth	10
2.4. Conducted Band Edges and Spurious Emissions	12
2.5. Power spectral density (PSD)	14
2.6. Radiated Band Edge and Spurious Emission	16
2.7. Conducted Emission	31
3. LIST OF MEASURING EQUIPMENT	35
4. UNCERTAINTY OF EVALUATION	36
APPENDIX A	37

Change History		
Issue	Date	Reason for change
1.0	2023.02.15	First edition

1. General Information

1.1. EUT Description

EUT Type	RICO Thermal Imaging Sights
EUT supports Radios application	WLAN2.4GHz 802.11b/g/n (HT20)
Frequency Range	802.11b/g/n-20MHz: 2.412GHz - 2.462GHz
Channel Number	802.11b/g/n-20MHz: 11
Bit Rate of Transmitter	802.11b: 11/5.5/2/1 Mbps 802.11g: 54/48/36/24/18/12/9/6 Mbps 802.11n : up to 72.2 Mbps
Modulation Type	DSSS (802.11b), OFDM (802.11g/n)
MIMO	Not support
Antenna Type	Internal
Antenna Gain	2dBi

Note 1: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

Note 2: The EUT was programmed to be in continuously transmitting mode and the transmit duty cycle is not less than 98%.

Note 3: The antenna gain and RF adapter/cable insert loss provided by manufacture.

Note 4: The EUT is a RICO Thermal Imaging Sights, it contains 8 models, they are RH50, RH50 PRO, RL42, RL42R, RH50R, RH50, RA50, RA50R, They have the same size, appearance and internal structure, and the only difference is the model number.

Note 5: This report is based on SET2021-05226 report. The PCB has changed, but the WIFI chip has not changed. Increase the model and change the lens size. According to the change of EUT, the radiated 30MHz to 1000MHz stray emission and conducted emission items are retested.

1.2. Test Standards and Results

The objective of the report is to perform testing according to below standards for the EUT FCC ID Certification:

No.	Identity	Document Title
1	47 CFR Part 15 Subpart C	Radio Frequency Devices
2	ANSI C63.10 2013	American National Standard for Testing Unlicensed Wireless Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section in CFR 47	Description	Result
1	15.203	Antenna Requirement	PASS
2	15.247(b)	Peak Output Power and EIRP	PASS
3	15.247(a)	6dB and 99% Occupied Bandwidth	PASS
4	15.247(d)	Conducted Band Edges and Spurious Emission	PASS
5	15.247(e)	Power spectral density (PSD)	PASS
6	15.207	Conducted Emission	PASS
7	15.209 15.205 15.247(d)	Radiated Band Edges and Spurious Emission	PASS

Note: The tests of Conducted Emission and Radiated Emission were performed according to the method of measurements prescribed in ANSI C63.10-2013. These RF tests were performed according to the method of measurements prescribed in KDB558074 D01 v05r02.

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

For 20MHz bandwidth systems, use Channel 1~ Channel 11

Channel No.	Frequency	Channel No.	Frequency	Channel No.	Frequency
1	2412MHz	5	2432MHz	9	2452MHz
2	2417MHz	6	2437MHz	10	2457MHz
3	2422MHz	7	2442MHz	11	2462MHz
4	2427MHz	8	2447MHz		

Test Items	Mode	Data Rate	Channel
Peak Conducted Output Power Power Spectral Density 6dB Bandwidth Conducted and Spurious Emission Radiated and Spurious Emission	11b/DSSS	1 Mbps	1/6/11
	11g/OFDM	6 Mbps	1/6/11
	11n(20MHz)/OFDM	MCS 0	1/6/11
Band Edge	11b/DSSS	1 Mbps	1/11
	11g/OFDM	6 Mbps	1/11
	11n(20MHz)/OFDM	MCS 0	1/11

1.3. Table for Supporting Units

No.	Equipment	Brand Name	Model Name	Manufacturer	Serial No.	Note
1	Notebook	DELL	PP11L	DELL	H5914A03	FCC DOC

1.4. EUT Operation Test Setup

For RF test items, an engineering test program was provided and enable to make EUT transmitting.

1.5. Facilities and Accreditations

1.5.1. Facilities

CNAS-Lab Code: L1659

CCIC-SET is a third party testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L1659.

FCC-Registration No.: CN1283

CCIC Southern Testing Co., Ltd EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Designation Number: CN1283, valid time is until April 19th,2023

.ISED Registration: 11185A-1

CAB identifier: CN0064

CCIC Southern Testing Co., Ltd. EMC Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 11185A-1 on Aug. 04, 2016, valid time is until April 19th,2023

A2LA Code: 5721.01

CCIC-SET is a third party testing organization accredited by A2LA according to ISO/IEC 17025. The accreditation certificate number is 5721.01.

1.5.2. Test Environment Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15 °C - 35 °C
Relative Humidity (%):	30% -60%
Atmospheric Pressure (kPa):	86KPa-106KPa

2. Test Requirements

2.1. Antenna requirement

2.1.1. Applicable Standard

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

And according to FCC 47 CFR Section 15.247(c), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

2.1.2. Antenna Information

Antenna General Information:

No.	EUT	Operating frequency range	Ant. Type	Ant. Gain
1	RICO Thermal Imaging Sights	2412-2462MHz	Internal	2dBi

2.1.3. Result: comply

The EUT has a permanently and irreplaceable attached antenna. Please refer to the EUT internal photos.

2.2. Maximum Conducted Output Power


2.2.1. Limit of Peak Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

2.2.2. Measuring Instruments

The measuring equipment is listed in the section 3 of this test report.

2.2.3. Test Setup



2.2.4. Test Procedures

1. The testing follows the Measurement Procedure of ANSI C63.10:2013.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

2.2.5. Test Result

Please refer to Appendix A for detail

2.3. 6dB Occupied Bandwidth


2.3.1. Limit of 6dB Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

2.3.2. Measuring Instruments

The measuring equipment is listed in the section 3 of this test report.

2.3.3. Test Setup



2.3.4. Test Procedures

1. The testing follows FCC KDB558074 D01 v05r02.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz.
5. Measure and record the results in the test report.



2.3.5. Test Results of 6dB Bandwidth

Please refer to Appendix A for detail

2.4. Conducted Band Edges and Spurious Emissions


2.4.1. Limit of Conducted Band Edges and Spurious Emissions

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.

2.4.2. Measuring Instruments

The measuring equipment is listed in the section 3 of this test report.

2.4.3. Test Setup



2.4.4. Test Procedure

1. The testing follows FCC KDB558074 D01 v05r02.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

2.4.5. Test Results of Conducted Band Edges

Please refer to Appendix A for detail

2.5. Power spectral density (PSD)


2.5.1. Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.

2.5.2. Measuring Instruments

The measuring equipment is listed in the section 3 of this test report.

2.5.3. Test Setup



2.5.4. Test Procedures

1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB558074 D01 v05r02.

2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.

3. Set to the maximum power setting and enable the EUT transmit continuously.

4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz.

Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)

5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.

6. Measure and record the results in the test report.

7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

2.5.5. Test Results of Power spectral density

Please refer to Appendix A for detail

2.6. Radiated Band Edge and Spurious Emission

2.6.1. Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Note: Wireless charger configuration was evaluated.


Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)
0.009 - 0.490	$2400/F(\text{kHz})$	300
0.490 - 1.705	$24000/F(\text{kHz})$	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

2.6.2. Measuring Instruments


The measuring equipment is listed in the section 3 of this test report.

2.6.3. Test Setup


For radiated emissions from 9 KHz to 30 MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



2.6.4. Test Procedures

1. The EUT was placed on the top of a rotating table 0.8m for below 1GHz/1.5m for above 1GHz above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
3. Height of receiving antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported.

Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
7. For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

NOTE:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or 10Hz (Duty cycle > 98%) for Average detection (AV) at frequency above 1GHz.
4. All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

2.6.5. Test Results of Radiated Band Edge and Spurious Emission

For 9 kHz to 30MHz


The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

For 30MHz to 1000 MHz



30MHz to 1GHz, Antenna Horizontal

Frequency (MHz)	QuasiPeak (dB μ V/m)	Bandwidth (kHz)	Corr. Factor (dB/m)	Antenna height (cm)	Limit (dB μ V/m)	Margin	Antenna	Verdict
30.000000	20.11	120.000	19.3	100.0	40.0	19.89	Horizontal	Pass
61.050000	15.36	120.000	6.1	100.0	40.0	24.64	Horizontal	Pass
107.650000	23.65	120.000	10.9	100.0	43.5	19.85	Horizontal	Pass
164.050000	31.02	120.000	12.5	100.0	43.5	12.48	Horizontal	Pass
249.650000	41.02	120.000	11.9	100.0	46.0	4.98	Horizontal	Pass
272.650000	41.00	120.000	14.6	100.0	46.0	5.00	Horizontal	Pass



30MHz to 1GHz, Antenna Vertical

Frequency (MHz)	QuasiPeak (dB μ V/m)	Bandwidth (kHz)	Corr. Factor (dB μ V/m)	Antenna height (cm)	Limit (dB μ V/m)	Margin	Antenna	Verdict
41.020000	26.68	120.000	14.0	100.0	40.0	13.32	Vertical	Pass
45.650000	25.19	120.000	11.2	100.0	40.0	14.81	Vertical	Pass
106.650000	26.61	120.000	10.9	100.0	43.5	16.89	Vertical	Pass
191.020000	28.65	120.000	10.0	100.0	43.5	14.85	Vertical	Pass
241.050000	37.60	120.000	11.9	100.0	46.0	8.40	Vertical	Pass
274.650000	33.65	120.000	14.6	100.0	46.0	12.35	Vertical	Pass

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. Margin value = Limit value – Emission Level
4. The other emission levels were very low against the limit.

For 1GHz to 25 GHz
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11b_2412MHz)

No.	Fre. (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	2390.00	49.66	PK	74.00	-24.34	1.50	260.00	48.36	5.20	28.60	32.50	1.30
2	2390.00	37.70	AV	54.00	-16.30	1.50	260.00	36.40	5.20	28.60	32.50	1.30
3	4824.00	51.36	PK	74.00	-22.64	1.50	260.00	44.96	7.40	30.40	31.40	6.40
4	4824.00	39.49	AV	54.00	-14.51	1.50	260.00	33.09	7.40	30.40	31.40	6.40
5	7236.00	52.47	PK	74.00	-21.53	1.50	260.00	41.97	11.50	31.20	32.20	10.50
6	7236.00	40.98	AV	54.00	-13.02	1.50	260.00	30.48	11.50	31.20	32.20	10.50

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11b_2412MHz)

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	2390.00	48.95	PK	74.00	-25.05	1.80	120.00	47.65	5.20	28.60	32.50	1.30
2	2390.00	37.08	AV	54.00	-16.92	1.80	120.00	35.78	5.20	28.60	32.50	1.30
3	4824.00	51.66	PK	74.00	-22.34	1.80	120.00	45.26	7.40	30.40	31.40	6.40
4	4824.00	40.37	AV	54.00	-13.63	1.80	120.00	33.97	7.40	30.40	31.40	6.40
5	7236.00	52.87	PK	74.00	-21.13	1.80	120.00	42.37	11.50	31.20	32.20	10.50
6	7236.00	40.22	AV	54.00	-13.78	1.80	120.00	29.72	11.50	31.20	32.20	10.50

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11b_2437MHz)

No.	Fre. (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	4874.00	51.62	PK	74.00	-22.38	1.50	360.00	45.22	6.70	30.40	31.30	6.40
2	4874.00	39.50	AV	54.00	-14.50	1.50	360.00	33.10	6.70	30.40	31.30	6.40
3	7311.00	52.98	PK	74.00	-21.02	1.50	360.00	42.18	11.80	31.20	32.20	10.80
4	7311.00	40.56	AV	54.00	-13.44	1.50	360.00	29.76	11.80	31.20	32.20	10.80

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11b_2437MHz)

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	4874.00	51.66	PK	74.00	-22.34	1.80	120.00	45.26	6.70	30.40	31.30	6.40
2	4874.00	39.10	AV	54.00	-14.90	1.80	120.00	32.70	6.70	30.40	31.30	6.40
3	7311.00	52.09	PK	74.00	-21.91	1.80	120.00	41.29	11.80	31.20	32.20	10.80
4	7311.00	39.22	AV	54.00	-14.78	1.80	120.00	28.42	11.80	31.20	32.20	10.80

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11b_2462MHz)

No.	Frequency (MHz)	Emssion Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	2483.50	51.25	PK	74.00	-22.75	1.50	360.00	49.65	5.30	28.70	32.40	1.60
2	2483.50	38.86	AV	54.00	-15.14	1.50	360.00	37.26	5.30	28.70	32.40	1.60
3	4924.00	52.36	PK	74.00	-21.64	1.50	360.00	46.66	6.70	30.50	31.50	5.70
4	4924.00	39.79	AV	54.00	-14.21	1.50	360.00	34.09	6.70	30.50	31.50	5.70
5	7386.00	53.07	PK	74.00	-20.93	1.50	360.00	42.27	11.80	31.20	32.20	10.80
6	7386.00	40.65	AV	54.00	-13.35	1.50	360.00	29.85	11.80	31.20	32.20	10.80

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11b_2462MHz)

No.	Frequency (MHz)	Emssion Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	2483.50	48.78	PK	74.00	-25.22	1.60	120.00	47.18	5.30	28.70	32.40	1.60
2	2483.50	36.45	AV	54.00	-17.55	1.60	120.00	34.85	5.30	28.70	32.40	1.60
3	4924.00	52.62	PK	74.00	-21.38	1.60	120.00	46.92	6.70	30.50	31.50	5.70
4	4924.00	40.20	AV	54.00	-13.80	1.60	120.00	34.50	6.70	30.50	31.50	5.70
5	7386.00	52.28	PK	74.00	-21.72	1.60	120.00	41.48	11.80	31.20	32.20	10.80
6	7386.00	40.09	AV	54.00	-13.91	1.60	120.00	29.29	11.80	31.20	32.20	10.80

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11g_2412MHz)

No.	Frequency (MHz)	Emssion Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	2390.00	51.73	PK	74.00	-22.27	1.80	300.00	50.43	5.20	28.60	32.50	1.30
2	2390.00	36.62	AV	54.00	-17.38	1.80	300.00	35.32	5.20	28.60	32.50	1.30
3	4824.00	52.62	PK	74.00	-21.38	1.80	300.00	46.22	7.40	30.40	31.40	6.40
4	4824.00	39.88	AV	54.00	-14.12	1.80	300.00	33.48	7.40	30.40	31.40	6.40
5	7236.00	53.26	PK	74.00	-20.74	1.80	300.00	42.76	11.50	31.20	32.20	10.50
6	7236.00	41.13	AV	54.00	-12.87	1.80	300.00	30.63	11.50	31.20	32.20	10.50

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11g_2412MHz)

No.	Frequency (MHz)	Emssion Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	2390.00	49.77	PK	74.00	-24.23	1.50	90.00	48.47	5.20	28.60	32.50	1.30
2	2390.00	35.80	AV	54.00	-18.20	1.50	90.00	34.50	5.20	28.60	32.50	1.30
3	4824.00	51.88	PK	74.00	-22.12	1.50	90.00	45.48	7.40	30.40	31.40	6.40
4	4824.00	40.01	AV	54.00	-13.99	1.50	90.00	33.61	7.40	30.40	31.40	6.40
5	7236.00	52.99	PK	74.00	-21.01	1.50	90.00	42.79	11.50	31.20	32.20	10.20
6	7236.00	40.80	AV	54.00	-13.20	1.50	90.00	30.60	11.50	31.20	32.20	10.20

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11g_2437MHz)

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	4874.00	51.22	PK	74.00	-22.78	1.80	300.00	45.42	6.70	30.40	31.30	5.80
2	4874.00	39.35	AV	54.00	-14.65	1.80	300.00	33.55	6.70	30.40	31.30	5.80
3	7311.00	51.69	PK	74.00	-22.31	1.80	300.00	40.89	11.80	31.20	32.20	10.80
4	7311.00	40.27	AV	54.00	-13.73	1.80	300.00	29.47	11.80	31.20	32.20	10.80

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11g_2437MHz)

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	4874.00	50.66	PK	74.00	-23.34	1.50	90.00	44.86	6.70	30.40	31.30	5.80
2	4874.00	39.59	AV	54.00	-14.41	1.50	90.00	33.79	6.70	30.40	31.30	5.80
3	7311.00	52.33	PK	74.00	-21.67	1.50	90.00	41.53	11.80	31.20	32.20	10.80
4	7311.00	40.21	AV	54.00	-13.79	1.50	90.00	29.41	11.80	31.20	32.20	10.80

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11g_2462MHz)

No.	Frequency (MHz)	Emssion Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	2483.50	60.31	PK	74.00	-13.69	1.50	220.00	58.71	5.30	28.70	32.40	1.60
2	2483.50	46.57	AV	54.00	-7.43	1.50	220.00	44.97	5.30	28.70	32.40	1.60
3	4924.00	52.34	PK	74.00	-21.66	1.50	220.00	46.64	6.70	30.50	31.50	5.70
4	4924.00	41.09	AV	54.00	-12.91	1.50	220.00	35.39	6.70	30.50	31.50	5.70
5	7386.00	53.06	PK	74.00	-20.94	1.50	220.00	42.26	11.80	31.20	32.20	10.80
6	7386.00	41.61	AV	54.00	-12.39	1.50	220.00	30.81	11.80	31.20	32.20	10.80

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11g_2462MHz)

No.	Frequency (MHz)	Emssion Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	2483.50	53.85	PK	74.00	-20.15	1.80	90.00	52.25	5.30	28.70	32.40	1.60
2	2483.50	42.47	AV	54.00	-11.53	1.80	90.00	40.87	5.30	28.70	32.40	1.60
3	4924.00	51.00	PK	74.00	-23.00	1.80	90.00	45.30	6.70	30.50	31.50	5.70
4	4924.00	38.46	AV	54.00	-15.54	1.80	90.00	32.76	6.70	30.50	31.50	5.70
5	7386.00	52.69	PK	74.00	-21.31	1.80	90.00	41.89	11.80	31.20	32.20	10.80
6	7386.00	39.49	AV	54.00	-14.51	1.80	90.00	28.69	11.80	31.20	32.20	10.80

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11n20_2412MHz)

No.	Frequency (MHz)	Emssion Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	2390.00	57.48	PK	74.00	-16.52	1.50	250.00	56.18	5.20	28.60	32.50	1.30
2	2390.00	44.16	AV	54.00	-9.84	1.50	250.00	42.86	5.20	28.60	32.50	1.30
3	4824.00	51.69	PK	74.00	-22.31	1.50	250.00	45.29	7.40	30.40	31.40	6.40
4	4824.00	39.82	AV	54.00	-14.18	1.50	250.00	33.42	7.40	30.40	31.40	6.40
5	7236.00	53.66	PK	74.00	-20.34	1.50	250.00	43.16	11.50	31.20	32.20	10.50
6	7236.00	42.29	AV	54.00	-11.71	1.50	250.00	31.79	11.50	31.20	32.20	10.50

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11n20_2412MHz)

No.	Frequency (MHz)	Emssion Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	2390.00	57.55	PK	74.00	-16.45	1.80	300.00	56.25	5.20	28.60	32.50	1.30
2	2390.00	43.39	AV	54.00	-10.61	1.80	300.00	42.09	5.20	28.60	32.50	1.30
3	4824.00	51.74	PK	74.00	-22.26	1.80	300.00	45.34	7.40	30.40	31.40	6.40
4	4824.00	40.31	AV	54.00	-13.69	1.80	300.00	33.91	7.40	30.40	31.40	6.40
5	7236.00	53.62	PK	74.00	-20.38	1.80	300.00	43.12	11.50	31.20	32.20	10.50
6	7236.00	42.29	AV	54.00	-11.71	1.80	300.00	31.79	11.50	31.20	32.20	10.50

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11n20_2437MHz)

No.	Frequency (MHz)	Emssion Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	4874.00	52.64	PK	74.00	-21.36	1.60	300.00	46.84	6.70	30.40	31.30	5.80
2	4874.00	41.28	AV	54.00	-12.72	1.60	300.00	35.48	6.70	30.40	31.30	5.80
3	7311.00	52.99	PK	74.00	-21.01	1.60	300.00	42.19	11.80	31.20	32.20	10.80
4	7311.00	41.51	AV	54.00	-12.49	1.60	300.00	30.71	11.80	31.20	32.20	10.80

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11n20_2437MHz)

No.	Frequency (MHz)	Emssion Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	4874.00	52.87	PK	74.00	-21.13	1.50	180.00	46.47	6.70	31.20	31.50	6.40
2	4874.00	40.45	AV	54.00	-13.55	1.50	180.00	34.05	6.70	31.20	31.50	6.40
3	7311.00	53.66	PK	74.00	-20.34	1.50	180.00	42.86	11.80	31.20	32.20	10.80
4	7311.00	42.23	AV	54.00	-11.77	1.50	180.00	31.43	11.80	31.20	32.20	10.80

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11n20_2462MHz)

No.	Frequency (MHz)	Emssion Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	2483.50	56.32	PK	74.00	-17.68	1.60	300.00	54.72	5.30	28.70	32.40	1.60
2	2483.50	44.01	AV	54.00	-9.99	1.60	300.00	42.41	5.30	28.70	32.40	1.60
3	4924.00	52.66	PK	74.00	-21.34	1.60	300.00	46.96	6.70	30.50	31.50	5.70
4	4924.00	40.48	AV	54.00	-13.52	1.60	300.00	34.78	6.70	30.50	31.50	5.70
5	7386.00	52.87	PK	74.00	-21.13	1.60	300.00	42.07	11.80	31.20	32.20	10.80
6	7386.00	41.07	AV	54.00	-12.93	1.60	300.00	30.27	11.80	31.20	32.20	10.80

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11n20_2462MHz)

No.	Frequency (MHz)	Emssion Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	2483.50	54.25	PK	74.00	-19.75	1.80	120.00	52.65	5.30	28.70	32.40	1.60
2	2483.50	40.30	AV	54.00	-13.70	1.80	120.00	38.70	5.30	28.70	32.40	1.60
3	4924.00	53.62	PK	74.00	-20.38	1.80	120.00	47.92	6.70	30.50	31.50	5.70
4	4924.00	41.84	AV	54.00	-12.16	1.80	120.00	36.14	6.70	30.50	31.50	5.70
5	7386.00	52.87	PK	74.00	-21.13	1.80	120.00	42.07	11.80	31.20	32.20	10.80
6	7386.00	41.05	AV	54.00	-12.95	1.80	120.00	30.25	11.80	31.20	32.20	10.80

REMARKS:

- Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
 - Pre-Amplifier Factor(dB)
- The other emission levels were very low against the limit.
- Margin value = Emission Level - Limit value

2.7. Conducted Emission

2.7.1. Limit of Conducted Emission


For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

2.7.2. Measuring Instruments

The measuring equipment is listed in the section 3 of this test report.

2.7.3. Test Setup




2.7.4. Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 micrometry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

2.7.5. Test Results of Conducted Emission


1. The EUT configuration of the emission tests is WLAN Link + USB Cable (Charging from Adapter)



(Plot A: L Phase)

Frequency (MHz)	QuasiPeak (dB μ V)	CAverage (dB μ V)	Cabel Loss (dB)	Corr. (dB)	Margin - QPK	Limit - QPK	Margin - AV	Limit - AV (dB μ V)
0.159000	42.99	26.01	0.2	10.2	22.53	65.5	29.51	55.5
0.195000	40.07	24.57	0.2	10.2	23.75	63.8	29.25	53.8
0.384000	39.06	27.89	0.2	10.2	19.13	58.2	20.30	48.2
0.541500	34.85	20.51	0.2	10.2	21.15	56.0	25.49	46.0
0.735000	33.36	20.68	0.2	10.2	22.64	56.0	25.32	46.0
1.140000	31.97	20.71	0.2	10.2	24.03	56.0	25.29	46.0

Note: Correction factor=Cabel loss+ attenuation factor
attenuation factor=10dB



(Plot B: N Phase)

Frequency (MHz)	QuasiPeak (dB μ V)	Average (dB μ V)	Cabel Loss (dB)	Corr. (dB)	Margin - QPK	Limit - QPK	Margin - AV	Limit - AV (dB μ V)
0.163500	48.56	26.82	0.2	10.2	16.72	65.3	28.46	55.3
0.181500	47.18	24.06	0.2	10.2	17.24	64.4	30.36	54.4
0.348000	39.03	25.45	0.2	10.2	19.98	59.0	23.56	49.0
0.379500	39.40	27.16	0.2	10.2	18.89	58.3	21.13	48.3
0.595500	34.49	22.82	0.2	10.2	21.51	56.0	23.18	46.0
1.077000	32.74	21.20	0.2	10.2	23.26	56.0	24.80	46.0

Note: Correction factor=Cabel loss+ attenuation factor
attenuation factor=10dB

Test Result : Pass

3. List of measuring equipment

Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	Power Meter	R&S	NRP-Z31	A141001975	2022.04.21	2023.04.20
2	EMI Test Receiver	ROHDE&SCHWARZ	ESW26	A180502935	2022.07.21	2023.07.20
3	5M Anechoic Chamber	Albatross	SAC-5MAC 12.8x6.8x6.4m	A0304210	2019.03.25	2023.03.24
4	Loop Antenna	Schwarz beck	HFH2-Z2	A0304220	2022.05.02	2025.05.01
5	Broadband antenna (30MHz~1GHz)	R&S	HL562	A0304224	2020.06.19	2023.06.18
6	EMI Horn Ant. (1-18G)	ETC	1209	A150402241	2021.01.02	2024.01.01
7	Horn antenna (18GHz~26.5GHz)	AR	AT4510	A0804450	2020.06.19	2023.06.18
8	Amplifier 30M~1GHz	MILMEGA	80RF1000-10004	A140101634	2020.09.22	2023.09.21
9	Amplifier 1G~18GHz	MILMEGA	AS0104R-800/400	A160302517	2022.12.13	2023.12.12
10	Spectrum Analyzer	KEYSIGHT	N9030A	A160702554	2022.03.25	2023.03.24
11	Test Receiver	R&S	ESIB7	A0501375	2022.04.18	2023.04.17
12	Broadband Ant.	2786	ETC	A150402240	2021.09.16	2024.03.03
13	3M Anechoic Chamber	Albatross	SAC-3MAC 9*6*6m	A0412375	2019.03.26	2023.03.25
14	Wideband Radio Communication tester	R&S	CMW500	A130101034	2022.06.23	2023.06.22
15	Test Receiver	KEYSIGHT	N9038A	A141202036	2022.07.21	2023.07.20
16	LISN	ROHDE&SCHWARZ	ENV216	A140701847	2022.07.21	2023.07.20
17	Cable	MATCHING PAD	W7	/	2022.07.21	2023.07.20

4. Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013. All the measurement uncertainty value were shown with a coverage $K=2$ to indicate 95% level of confidence . The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Emission Measurement (150KHz~30MHz)

Measuring Uncertainty for a level of confidence of 95%($U=2U_c(y)$)	2.8dB
---	-------

Uncertainty of Radiated Emission Measurement (30MHz~1GHz)

Measuring Uncertainty for a level of confidence of 95%($U=2U_c(y)$)	3.91dB
---	--------

Uncertainty of Radiated Emission Measurement (1GHz~18GHz)

Measuring Uncertainty for a level of confidence of 95%($U=2U_c(y)$)	4.5dB
---	-------

Uncertainty of Radiated Emission Measurement (18GHz~40GHz)

Measuring Uncertainty for a level of confidence of 95%($U=2U_c(y)$)	4.9dB
---	-------

Appendix A

RF Output Power


Test Result and Data

Conducted Output Power				
Mode	Test Frequency (MHz)	Max Conducted Output Power (dBm)	Limit (dBm)	Result
802.11b	2412	15.94	30	Pass
802.11b	2437	16.97	30	Pass
802.11b	2462	16.70	30	Pass
802.11g	2412	14.51	30	Pass
802.11g	2437	14.52	30	Pass
802.11g	2462	14.29	30	Pass
802.11n (HT20)	2412	11.56	30	Pass
802.11n (HT20)	2437	11.56	30	Pass
802.11n (HT20)	2462	11.46	30	Pass


**6dB Bandwidth****Test Result and Data**

WLAN Occupied 6dB Bandwidth				
Mode	Test Frequency (MHz)	Occupied Bandwidth (MHz)	Limit (KHz)	Result
802.11b	2412	8.10	500	Pass
802.11b	2437	9.07	500	Pass
802.11b	2462	9.07	500	Pass
802.11g	2412	15.17	500	Pass
802.11g	2437	15.50	500	Pass
802.11g	2462	15.49	500	Pass
802.11n (HT20)	2412	15.17	500	Pass
802.11n (HT20)	2437	16.09	500	Pass
802.11n (HT20)	2462	15.98	500	Pass


6dB Bandwidth-802.11b,2412MHz




6dB Bandwidth-802.11b,2437MHz



6dB Bandwidth-802.11b,2462MHz




6dB Bandwidth-802.11g,2412MHz




6dB Bandwidth-802.11g,2437MHz




6dB Bandwidth-802.11g,2462MHz




6dB Bandwidth-802.11n(HT20),2412MHz



6dB Bandwidth-802.11n(HT20),2437MHz




6dB Bandwidth-802.11n(HT20),2462MHz




**99% BandWidth****Test Result and Data**

WLAN 99% Occupied Bandwidth				
Mode	Test Frequency (MHz)	99% Occupied Bandwidth (MHz)	Limit (KHz)	Result
802.11b	2412	13.291	500	Pass
802.11b	2437	13.950	500	Pass
802.11b	2462	13.963	500	Pass
802.11g	2412	17.126	500	Pass
802.11g	2437	17.147	500	Pass
802.11g	2462	17.132	500	Pass
802.11n (HT20)	2412	17.920	500	Pass
802.11n (HT20)	2437	17.865	500	Pass
802.11n (HT20)	2462	17.871	500	Pass


99% Bandwidth-802.11b,2412MHz




99% Bandwidth-802.11b,2437MHz




99% Bandwidth-802.11b,2462MHz




99% Bandwidth-802.11g,2412MHz



99% Bandwidth-802.11g,2437MHz



99% Bandwidth-802.11g,2462MHz



99% Bandwidth-802.11n(HT20),2412MHz



99% Bandwidth-802.11n(HT20),2437MHz



99% Bandwidth-802.11n(HT20),2462MHz



**Power Spectral Density****Test Result and Data**

Power Spectral Density					
Mode	Test Frequency (MHz)	PSD (dBm/3KHz)	RBW (kHz)	Limit (dBm/3KHz)	Result
802.11b	2412	-16.166	3	8	Pass
802.11b	2437	-15.035	3	8	Pass
802.11b	2462	-15.272	3	8	Pass
802.11g	2412	-19.692	3	8	Pass
802.11g	2437	-19.539	3	8	Pass
802.11g	2462	-19.945	3	8	Pass
802.11n (HT20)	2412	-22.339	3	8	Pass
802.11n (HT20)	2437	-22.520	3	8	Pass
802.11n (HT20)	2462	-22.169	3	8	Pass


Power spectral density-802.11b
,2412MHz




Power spectral density-802.11b
,2437MHz




Power spectral density-802.11b
,2462MHz




Power spectral density-802.11g
,2412MHz




Power spectral density-802.11g
,2437MHz




Power spectral density-802.11g
,2462MHz




Power spectral density-802.11n(HT20)
,2412MHz



Power spectral density-802.11n(HT20)
,2437MHz




Power spectral density-802.11n(HT20)
,2462MHz




Conducted Band Edges and Spurious Emissions

Test Result and Data


,Plot 1,Reference Level-802.11b
,2412MHz




,Plot 1,Reference Level-802.11b
,2437MHz




,Plot 1,Reference Level-802.11b
,2462MHz



,Plot 2,Band Edge-802.11b,2412MHz




,Plot 2,Band Edge-802.11b,2437MHz




,Plot 2,Band Edge-802.11b,2462MHz







,Plot 3,30MHz~2310MHz-802.11b,2412MHz




,Plot 3,30MHz~2310MHz-802.11b,2437MHz




,Plot 3,30MHz~2310MHz-802.11b,2462MHz


,Plot 4,2500MHz~10000MHz-802.11b
,2412MHz

,Plot 4,2500MHz~10000MHz-802.11b
,2437MHz

,Plot 4,2500MHz~10000MHz-802.11b
,2462MHz



,Plot 5,10000MHz~25000MHz-802.11b
,2412MHz




,Plot 5,10000MHz~25000MHz-802.11b
,2437MHz




,Plot 5,10000MHz~25000MHz-802.11b
,2462MHz




,Plot 1,Reference Level-802.11g
,2412MHz




,Plot 1,Reference Level-802.11g
,2437MHz




,Plot 1,Reference Level-802.11g
,2462MHz




,Plot 2,Band Edge-802.11g,2412MHz




,Plot 2,Band Edge-802.11g,2437MHz




,Plot 2,Band Edge-802.11g,2462MHz




,Plot 3,30MHz~2310MHz-802.11g,2412MHz




,Plot 3,30MHz~2310MHz-802.11g,2437MHz




,Plot 3,30MHz~2310MHz-802.11g,2462MHz




,Plot 4,2500MHz~10000MHz-802.11g
,2412MHz




,Plot 4,2500MHz~10000MHz-802.11g
,2437MHz




,Plot 4,2500MHz~10000MHz-802.11g
,2462MHz




,Plot 5,10000MHz~25000MHz-802.11g
,2412MHz




,Plot 5,10000MHz~25000MHz-802.11g
,2437MHz




,Plot 5,10000MHz~25000MHz-802.11g
,2462MHz




,Plot 1,Reference Level-802.11n(HT20)
,2412MHz




,Plot 1,Reference Level-802.11n(HT20)
,2437MHz




,Plot 1,Reference Level-802.11n(HT20)
,2462MHz



,Plot 2,Band Edge-802.11n(HT20)
,2412MHz



,Plot 2,Band Edge-802.11n(HT20)
,2437MHz



,Plot 2,Band Edge-802.11n(HT20)
,2462MHz

