

TEST REPORT

Applicant: DashX Co.,Ltd
Address of Applicant: C701, Chengshishanhaizhongxin, No.11 Zhongxing Road,
Bantian Street, Longgang District, Shenzhen
Manufacturer: DashX Co.,Ltd
Address of Manufacturer: C701, Chengshishanhaizhongxin, No.11 Zhongxing Road,
Bantian Street, Longgang District, Shenzhen
Equipment Under Test (EUT)

Product Name: Dash cam
Model No.: DX-1, DX-2,DX-3,DX-4,DX-5,DX-6,DX-7,DX-8,DX-9,DX-10
Trade Mark: N/A
FCC ID: 2AYK8-DX1
Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.247
Date of sample receipt: Dec. 26, 2020
Date of Test: Dec. 26, 2020 ~ Jan. 06, 2021
Date of report issued: Jan. 07, 2021
Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

A circular blue ink stamp from Global United Technology Services Co., Ltd. is visible. The stamp contains the text "GTS" in the center, "GLOBAL UNITED TECHNOLOGY SERVICES CO., LTD." around the perimeter, and "Jan 7 2021" at the bottom. A handwritten signature in blue ink is written over the stamp.

Robinson Lo
Laboratory Manager

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

2 Version

Version No.	Date	Description
00	Jan. 07, 2021	Original

Prepared By:




Project Engineer

Date:

Jan. 07, 2021

Check By:



Reviewer

Date:

Jan. 07, 2021

3 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY	4
5 GENERAL INFORMATION	5
5.1 GENERAL DESCRIPTION OF EUT	5
5.2 TEST MODE	7
5.3 DESCRIPTION OF SUPPORT UNITS	7
5.4 DEVIATION FROM STANDARDS	7
5.5 ABNORMALITIES FROM STANDARD CONDITIONS	7
5.6 TEST FACILITY	7
5.7 TEST LOCATION	7
5.8 ADDITIONAL INSTRUCTIONS	7
6 TEST INSTRUMENTS LIST	8
7 TEST RESULTS AND MEASUREMENT DATA	10
7.1 ANTENNA REQUIREMENT	10
7.2 CONDUCTED EMISSIONS	11
7.3 CONDUCTED PEAK OUTPUT POWER	12
7.4 CHANNEL BANDWIDTH & 99% OCCUPY BANDWIDTH	13
7.5 POWER SPECTRAL DENSITY	17
7.6 BAND EDGES	20
7.6.1 Conducted Emission Method	20
7.6.2 Radiated Emission Method	22
7.7 SPURIOUS EMISSION	26
7.7.1 Conducted Emission Method	26
7.7.2 Radiated Emission Method	30
8 TEST SETUP PHOTO	44
9 EUT CONSTRUCTIONAL DETAILS	45

4 Test Summary

Test Item	Section	Result
Antenna requirement	FCC part 15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	FCC part 15.207	N/A
Conducted Peak Output Power	FCC part 15.247 (b)(3)	Pass
Channel Bandwidth & 99% OCB	FCC part 15.247 (a)(2)	Pass
Power Spectral Density	FCC part 15.247 (e)	Pass
Band Edge	FCC part 15.247(d)	Pass
Spurious Emission	FCC part 15.205/15.209	Pass

Remark: Test according to ANSI C63.10:2013 and RSS-Gen

Pass: The EUT complies with the essential requirements in the standard.

N/A: The EUT is not applicable.

Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	30MHz-200MHz	3.8039dB	(1)
Radiated Emission	200MHz-1GHz	3.9679dB	(1)
Radiated Emission	1GHz-18GHz	4.29dB	(1)
Radiated Emission	18GHz-40GHz	3.30dB	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	3.44dB	(1)

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

5 General Information

5.1 General Description of EUT

Product Name:	Dash cam
Model No.:	DX-1, DX-2,DX-3,DX-4,DX-5,DX-6,DX-7,DX-8,DX-9,DX-10
Remark: All above models are identical in the same PCB layout, interior structure and electrical circuits. The only difference is model name for commercial purpose.	
Serial No.:	N/A
Hardware Version:	V1.1
Software Version:	V1.0
Test sample(s) ID:	GTSL202101000018-1
Sample(s) Status:	Engineer sample
Sample(s) Status	Engineer sample
Channel numbers:	802.11b/802.11g /802.11n(HT20): 11
Channel separation:	5MHz
Modulation technology:	802.11b: Direct Sequence Spread Spectrum (DSSS) 802.11g/802.11n(H20): Orthogonal Frequency Division Multiplexing (OFDM)
Antenna Type:	IPEX antenna
Antenna gain:	0 dBi
Power supply:	DC 12V by Adapter AC 100-240V~50/60Hz DC 3.7V battery

Operation Frequency each of channel

Channel List for 802.11b/802.11g/802.11n (HT20)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	Frequency (MHz)
	802.11b/802.11g/802.11n(HT20)
Lowest channel	2412MHz
Middle channel	2437MHz
Highest channel	2462MHz

5.2 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode
<i>Remark: During the test, the dutycycle >98%, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.</i>	

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:			
Pre-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.			
Mode	802.11b	802.11g	802.11n(HT20)
Data rate	1Mbps	6Mbps	6.5Mbps

5.3 Description of Support Units

None.

5.4 Deviation from Standards

None.

5.5 Abnormalities from Standard Conditions

None.

5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations: • FCC —Registration No.: 381383 Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 381383. • IC —Registration No.: 9079A The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A • NVLAP (LAB CODE:600179-0) Global United Technology Services Co., Ltd., is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP). LAB CODE:600179-0

5.7 Test Location

All tests were performed at:
Global United Technology Services Co., Ltd. Address: No. 123-128, Tower A, Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102 Tel: 0755-27798480 Fax: 0755-27798960

5.8 Additional Instructions

Test Software	Ampak RFTestTool, VER: 7.0
Power level setup	Default

6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	July. 02 2020	July. 01 2025
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	June. 25 2020	June. 24 2021
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	June. 25 2020	June. 24 2021
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	GTS208	June. 25 2020	June. 24 2021
6	Horn Antenna	ETS-LINDGREN	3160	GTS217	June. 25 2020	June. 24 2021
7	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
8	Coaxial Cable	GTS	N/A	GTS213	June. 25 2020	June. 24 2021
9	Coaxial Cable	GTS	N/A	GTS211	June. 25 2020	June. 24 2021
10	Coaxial cable	GTS	N/A	GTS210	June. 25 2020	June. 24 2021
11	Coaxial Cable	GTS	N/A	GTS212	June. 25 2020	June. 24 2021
12	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	June. 25 2020	June. 24 2021
13	Amplifier(2GHz-20GHz)	HP	84722A	GTS206	June. 25 2020	June. 24 2021
14	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June. 25 2020	June. 24 2021
15	Band filter	Amindeon	82346	GTS219	June. 25 2020	June. 24 2021
16	Power Meter	Anritsu	ML2495A	GTS540	June. 25 2020	June. 24 2021
17	Power Sensor	Anritsu	MA2411B	GTS541	June. 25 2020	June. 24 2021
18	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS575	June. 25 2020	June. 24 2021
19	Splitter	Agilent	11636B	GTS237	June. 25 2020	June. 24 2021
20	Loop Antenna	ZHINAN	ZN30900A	GTS534	June. 25 2020	June. 24 2021
21	Breitband hornantenne	SCHWARZBECK	BBHA 9170	GTS579	Oct. 18 2020	Oct. 17 2021
22	Amplifier	TDK	PA-02-02	GTS574	Oct. 18 2020	Oct. 17 2021
23	Amplifier	TDK	PA-02-03	GTS576	Oct. 18 2020	Oct. 17 2021
24	PSA Series Spectrum Analyzer	Rohde & Schwarz	FSP	GTS578	June. 25 2020	June. 24 2021

Conducted Emission						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongYu Electron	7.3(L)x3.1(W)x2.9(H)	GTS252	May.15 2019	May.14 2022
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June. 25 2020	June. 24 2021
3	Coaxial Switch	ANRITSU CORP	MP59B	GTS225	June. 25 2020	June. 24 2021
4	ENV216 2-L-V-NETZNACHB.DE	ROHDE&SCHWARZ	ENV216	GTS226	June. 25 2020	June. 24 2021
5	Coaxial Cable	GTS	N/A	GTS227	N/A	N/A
6	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
7	Thermo meter	KTJ	TA328	GTS233	June. 25 2020	June. 24 2021
8	Absorbing clamp	Elektronik-Feinmechanik	MDS21	GTS229	June. 25 2020	June. 24 2021
9	ISN	SCHWARZBECK	NTFM 8158	GTD565	June. 25 2020	June. 24 2021

RF Conducted Test:						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	MXA Signal Analyzer	Agilent	N9020A	GTS566	June. 25 2020	June. 24 2021
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June. 25 2020	June. 24 2021
3	Spectrum Analyzer	Agilent	E4440A	GTS533	June. 25 2020	June. 24 2021
4	MXG vector Signal Generator	Agilent	N5182A	GTS567	June. 25 2020	June. 24 2021
5	ESG Analog Signal Generator	Agilent	E4428C	GTS568	June. 25 2020	June. 24 2021
6	USB RF Power Sensor	DARE	RPR3006W	GTS569	June. 25 2020	June. 24 2021
7	RF Switch Box	Shongyi	RFSW3003328	GTS571	June. 25 2020	June. 24 2021
8	Programmable Constant Temp & Humi Test Chamber	WEWON	WHTH-150L-40-880	GTS572	June. 25 2020	June. 24 2021

General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Humidity/ Temperature Indicator	KTJ	TA328	GTS243	June. 25 2020	June. 24 2021
2	Barometer	ChangChun	DYM3	GTS255	June. 25 2020	June. 24 2021

7 Test results and Measurement Data


7.1 Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.	
EUT Antenna:	
<i>The antennas are IPEX antenna, the best case gain of the antennas are 0dBi, reference to the appendix II for details.</i>	

7.2 Conducted Emissions

Test Requirement:	FCC Part15 C Section 15.207					
Test Method:	ANSI C63.10:2013					
Test Frequency Range:	150KHz to 30MHz					
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto					
Limit:	Frequency range (MHz)		Limit (dBuV)			
			Quasi-peak		Average	
	0.15-0.5		66 to 56*		56 to 46*	
	0.5-5		56		46	
	5-30		60		50	
* Decreases with the logarithm of the frequency.						
Test setup:	Diagram description: The diagram shows a test setup on a 'Test table/Insulation plane'. An 'E.U.T.' (Equipment Under Test) is connected to a 'LISN' (Line Impedance Stabilization Network) via a cable. The 'LISN' is connected to 'AC power' through a 'Filter'. An 'EMI Receiver' is connected to the 'LISN'. A 'Reference Plane' is indicated at a height of 40cm from the test table. The distance from the 'E.U.T.' to the 'LISN' is 80cm. 'AUX Equipment' is also connected to the 'E.U.T.'. Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m					
Test procedure:	1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2013 on conducted measurement.					
Test Instruments:	Refer to section 6.0 for details					
Test mode:	Refer to section 5.2 for details					
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar
Test voltage:	N/A					
Test results:	N/A					


7.3 Conducted Peak Output Power

Test Requirement :	FCC Part15 C Section 15.247 (b)(3)
Test Method :	KDB558074 D01 DTS Meas Guidance v05or02
Limit:	30dBm
Test setup:	 The diagram illustrates the test setup. A 'Power Meter' is connected to an 'E.U.T.' (Equipment Under Test) via a red cable. Both the Power Meter and the E.U.T. are placed on a 'Non-Conducted Table'. This table is supported by two vertical legs and sits on a 'Ground Reference Plane'.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data

Test CH	Peak Output Power (dBm)			Limit(dBm)	Result
	802.11b	802.11g	802.11n(HT20)		
Lowest	7.25	6.51	5.13	30.00	Pass
Middle	7.64	6.26	5.45		
Highest	7.84	6.42	5.38		

7.4 Channel Bandwidth & 99% Occupy Bandwidth

Test Requirement :	FCC Part15 C Section 15.247 (a)(2)
Test Method :	KDB558074 D01 DTS Meas Guidance v05or02
Limit:	>500KHz
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by a Ground Reference Plane.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass



Measurement Data

Test CH	Channel Bandwidth (MHz)			Limit(KHz)	Result
	802.11b	802.11g	802.11n(HT20)		
Lowest	8.546	16.31	17.59	>500	Pass
Middle	8.085	10.06	16.06		
Highest	8.533	16.01	16.01		


Test CH	99% Occupy Bandwidth (MHz)			Result
	802.11b	802.11g	802.11n(HT20)	
Lowest	13.978	16.434	17.702	Pass
Middle	13.965	16.441	16.441	
Highest	13.956	16.443	16.443	

Test plot as follows:

802.11b		802.11g	
---------	--	---------	--



Lowest channel



Middle channel




Highest channel

802.11n(HT20)



Lowest channel




Middle channel



Highest channel

7.5 Power Spectral Density


Test Requirement:	FCC Part15 C Section 15.247 (e)
Test Method:	KDB558074 D01 DTS Meas Guidance v05or02
Limit:	8dBm/3kHz
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by a Ground Reference Plane.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data


Test CH	Power Spectral Density (dBm/3kHz)			Limit (dBm/3kHz)	Result
	802.11b	802.11g	802.11n(HT20)		
Lowest	-13.631	-18.077	-18.760	8.00	Pass
Middle	-15.034	-17.767	-18.843		
Highest	-14.659	-19.095	-19.363		

Test plot as follows:


802.11b	802.11g
---------	---------



Lowest channel




Middle channel




Highest channel


802.11n(HT20)



Lowest channel




Middle channel




Highest channel

7.6 Band edges


7.6.1 Conducted Emission Method

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	KDB558074 D01 DTS Meas Guidance v05or02
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both are placed on a Non-Conducted Table, which is supported by two vertical legs. Below the table is a Ground Reference Plane, represented by a thick grey bar.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Test plot as follows:



7.6.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209 and 15.205				
Test Method:	ANSI C63.10: 2013				
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Average	1MHz	3MHz	Average
Limit:	Frequency		Limit (dBuV/m @3m)		Value
	Above 1GHz		54.00		Average
			74.00		Peak
Test setup:					
Test Procedure:	1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. 7. The radiation measurements are performed in X, Y, Z axis positioning. And found the Y axis positioning which it is worse case, only the test worst case mode is recorded in the report.				
Test Instruments:	Refer to section 6.0 for details				
Test mode:	Refer to section 5.2 for details				
Test results:	Pass				

Measurement data:

Test mode:	802.11b	Test channel:	Lowest
------------	---------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4824	59.24	21.52	3.52	33.12	51.16	74	-22.84	Horizontal
4824	54.25	23.65	4.56	33.08	49.38	74	-24.62	Vertical
7236	49.68	25.58	6.15	33.57	47.84	74	-26.16	Horizontal
7236	44.19	27.68	6.98	33.26	45.59	74	-28.41	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4824	48.25	21.52	3.52	33.12	40.17	54	-13.83	Horizontal
4824	43.49	23.65	4.56	33.08	38.62	54	-15.38	Vertical
7236	38.45	25.58	6.15	33.57	36.61	54	-17.39	Horizontal
7236	33.46	27.68	6.98	33.26	34.86	54	-19.14	Vertical

Test mode:	802.11b	Test channel:	Highest
------------	---------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4924	59.16	21.52	3.52	33.12	51.08	74	-22.92	Horizontal
4924	54.34	23.65	4.56	33.08	49.47	74	-24.53	Vertical
7386	49.25	25.58	6.15	33.57	47.41	74	-26.59	Horizontal
7386	44.23	27.68	6.98	33.26	45.63	74	-28.37	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4924	47.85	21.52	3.52	33.12	39.77	54	-14.23	Horizontal
4924	42.35	23.65	4.56	33.08	37.48	54	-16.52	Vertical
7386	37.26	25.58	6.15	33.57	35.42	54	-18.58	Horizontal
7386	32.13	27.68	6.98	33.26	33.53	54	-20.47	Vertical

Test mode:	802.11g	Test channel:	Lowest
------------	---------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4824	59.22	21.78	3.58	33.27	51.31	74	-22.69	Horizontal
4824	54.36	24.15	4.57	33.87	49.21	74	-24.79	Vertical
7236	49.25	26.04	6.24	33.19	48.34	74	-25.66	Horizontal
7236	44.37	27.98	7.18	33.68	45.85	74	-28.15	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4824	48.56	21.78	3.58	33.27	40.65	54	-13.35	Horizontal
4824	43.34	24.15	4.57	33.87	38.19	54	-15.81	Vertical
7236	38.12	26.04	6.24	33.19	37.21	54	-16.79	Horizontal
7236	33.64	27.98	7.18	33.68	35.12	54	-18.88	Vertical

Test mode:	802.11g	Test channel:	Highest
------------	---------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4924	59.77	21.78	3.58	33.27	51.86	74	-22.14	Horizontal
4924	54.21	24.15	4.57	33.87	49.06	74	-24.94	Vertical
7386	49.12	26.04	6.24	33.19	48.21	74	-25.79	Horizontal
7386	44.21	27.98	7.18	33.68	45.69	74	-28.31	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4924	48.24	21.78	3.58	33.27	40.33	54	-13.67	Horizontal
4924	43.48	24.15	4.57	33.87	38.33	54	-15.67	Vertical
7386	38.26	26.04	6.24	33.19	37.35	54	-16.65	Horizontal
7386	33.46	27.98	7.18	33.68	34.94	54	-19.06	Vertical

Test mode:	802.11n(HT20)	Test channel:	Lowest
------------	---------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4824	59.43	22.56	4.17	33.75	52.41	74	-21.59	Horizontal
4824	54.14	24.78	5.36	33.17	51.11	74	-22.89	Vertical
7236	49.23	27.14	6.97	33.62	49.72	74	-24.28	Horizontal
7236	44.32	28.16	7.65	33.58	46.55	74	-27.45	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4824	47.23	22.56	4.17	33.75	40.21	54	-13.79	Horizontal
4824	42.36	24.78	5.36	33.17	39.33	54	-14.67	Vertical
7236	37.85	27.14	6.97	33.62	38.34	54	-15.66	Horizontal
7236	32.14	28.16	7.65	33.58	34.37	54	-19.63	Vertical

Test mode:	802.11n(HT20)	Test channel:	Highest
------------	---------------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4924	59.29	22.56	4.17	33.75	52.27	74	-21.73	Horizontal
4924	54.14	24.78	5.36	33.17	51.11	74	-22.89	Vertical
7386	49.16	27.14	6.97	33.62	49.65	74	-24.35	Horizontal
7386	43.98	28.16	7.65	33.58	46.21	74	-27.79	Vertical

Average value:


Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4924	47.26	22.56	4.17	33.75	40.24	54	-13.76	Horizontal
4924	42.34	24.78	5.36	33.17	39.31	54	-14.69	Vertical
7386	37.26	27.14	6.97	33.62	37.75	54	-16.25	Horizontal
7386	32.13	28.16	7.65	33.58	34.36	54	-19.64	Vertical

Remarks:

- Only the worst case Main Antenna test data.
- The pre-test were performed on lowest, middle and highest frequencies, only the worst case's (lowest and highest frequencies) data was showed.
- Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
- The emission levels of other frequencies are very lower than the limit and not show in test report.

7.7 Spurious Emission

7.7.1 Conducted Emission Method

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	KDB558074 D01 DTS Meas Guidance v05or02
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by a Ground Reference Plane.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Test plot as follows:

802.11b

Lowest channel



30MHz~25GHz

Middle channel



30MHz~25GHz

Highest channel



30MHz~25GHz

802.11g

Lowest channel



30MHz~25GHz

Middle channel



30MHz~25GHz

Highest channel



30MHz~25GHz

802.11n(HT20)

Lowest channel



30MHz~25GHz

Middle channel




30MHz~25GHz



Highest channel



30MHz~25GHz

7.7.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10: 2013				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Limit:	Frequency	Limit (uV/m)		Value	Measurement Distance
	0.009MHz-0.490MHz	2400/F(KHz)		QP	300m
	0.490MHz-1.705MHz	24000/F(KHz)		QP	300m
	1.705MHz-30MHz	30		QP	30m
	30MHz-88MHz	100		QP	3m
	88MHz-216MHz	150		QP	
	216MHz-960MHz	200		QP	
	960MHz-1GHz	500		QP	
	Above 1GHz	500		Average	
		5000		Peak	
Test setup:	For radiated emissions from 9kHz to 30MHz				
					
	For radiated emissions from 30MHz to 1GHz				

	 For radiated emissions above 1GHz 
Test Procedure:	1. The EUT was placed on the top of a rotating table (0.8m for below 1G and 1.5m for above 1G) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test voltage:	AC120V 60Hz

Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar
Test voltage:	AC 120V, 60Hz					
Test results:	Pass					

Remarks:

1. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.


Measurement data:**■ 9kHz~30MHz**

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o) & RSS-Gen 6.13, the test result no need to reported.

■ Below 1GHz

Pre-scan all test modes, found worst case at 802.11b 2462MHz, and so only show the test result of 802.11b 2462MHz


Horizontal:



Suspected List

NO.	Freq. [MHz]	Factor [dB]	Reading [dBμV/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	104.7648	-15.41	35.28	19.87	43.50	23.63	100	171	Horizontal
2	118.3584	-16.83	36.29	19.46	43.50	24.04	100	171	Horizontal
3	165.9359	-17.67	44.36	26.69	43.50	16.81	100	325	Horizontal
4	214.4845	-14.69	38.87	24.18	43.50	19.32	100	248	Horizontal
5	297.0170	-12.77	38.42	25.65	46.00	20.35	100	209	Horizontal
6	380.5205	-10.82	32.87	22.05	46.00	23.95	100	38	Horizontal

Vertical:



Suspected List

NO.	Freq. [MHz]	Factor [dB]	Reading [dBμV/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	118.3584	-16.83	39.03	22.20	43.50	21.30	100	112	Vertical
2	165.9359	-17.67	47.96	30.29	43.50	13.21	100	172	Vertical
3	197.9780	-15.25	39.45	24.20	43.50	19.30	100	166	Vertical
4	297.9880	-12.76	38.16	25.40	46.00	20.60	100	358	Vertical
5	483.4434	-8.48	36.06	27.58	46.00	18.42	100	12	Vertical
6	547.5275	-7.02	34.57	27.55	46.00	18.45	100	70	Vertical

■ Above 1GHz

Test mode:	802.11b/2412MHz	Test channel:	Lowest
------------	-----------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824	57.56	21.52	3.52	33.12	49.48	74	-24.52	Vertical
7236	52.36	23.65	4.56	33.08	47.49	74	-26.51	Vertical
9648	47.73	25.58	6.15	33.57	45.89	74	-28.11	Vertical
12060	42.49	27.68	6.98	33.26	43.89	74	-30.11	Vertical
14472	*	*	*	*	*	74	*	Vertical
4824	56.98	21.52	3.52	33.12	48.9	74	-25.1	Horizontal
7236	52.14	23.65	4.56	33.08	47.27	74	-26.73	Horizontal
9648	47.02	25.58	6.15	33.57	45.18	74	-28.82	Horizontal
12060	42.64	27.68	6.98	33.26	44.04	74	-29.96	Horizontal
14472	*	*	*	*	*	74	*	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824	48.25	21.52	3.52	33.12	40.17	54	-13.83	Vertical
7236	43.68	23.65	4.56	33.08	38.81	54	-15.19	Vertical
9648	38.47	25.58	6.15	33.57	36.63	54	-17.37	Vertical
12060	33.64	27.68	6.98	33.26	35.04	54	-18.96	Vertical
14472	*	*	*	*	*	54	*	Vertical
4824	47.87	21.52	3.52	33.12	39.79	54	-14.21	Horizontal
7236	42.64	23.65	4.56	33.08	37.77	54	-16.23	Horizontal
9648	38.46	25.58	6.15	33.57	36.62	54	-17.38	Horizontal
12060	33.45	27.68	6.98	33.26	34.85	54	-19.15	Horizontal
14472	*	*	*	*	*	54	*	Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.

Test mode:	802.11b/2437MHz	Test channel:	Middle
------------	-----------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874	57.45	21.78	3.58	33.27	49.54	74	-24.46	Vertical
7311	52.39	24.15	4.57	33.87	47.24	74	-26.76	Vertical
9748	47.54	26.04	6.24	33.19	46.63	74	-27.37	Vertical
12185	43.02	27.98	7.18	33.68	44.5	74	-29.5	Vertical
14622	*	*	*	*	*	74	*	Vertical
4874	56.74	21.78	3.58	33.27	48.83	74	-25.17	Horizontal
7311	52.03	24.15	4.57	33.87	46.88	74	-27.12	Horizontal
9748	47.24	26.04	6.24	33.19	46.33	74	-27.67	Horizontal
12185	42.36	27.98	7.18	33.68	43.84	74	-30.16	Horizontal
14622	*	*	*	*	*	74	*	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874	47.54	21.78	3.58	33.27	39.63	54	-14.37	Vertical
7311	42.37	24.15	4.57	33.87	37.22	54	-16.78	Vertical
9748	37.48	26.04	6.24	33.19	36.57	54	-17.43	Vertical
12185	32.14	27.98	7.18	33.68	33.62	54	-20.38	Vertical
14622	*	*	*	*	*	54	*	Vertical
4874	46.25	21.78	3.58	33.27	38.34	54	-15.66	Horizontal
7311	41.49	24.15	4.57	33.87	36.34	54	-17.66	Horizontal
9748	36.14	26.04	6.24	33.19	35.23	54	-18.77	Horizontal
12185	31.26	27.98	7.18	33.68	32.74	54	-21.26	Horizontal
14622	*	*	*	*	*	54	*	Horizontal

Remark:

1. Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.

Test mode:	802.11b/2462MHz	Test channel:	Highest
------------	-----------------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924	57.65	22.56	4.17	33.75	50.63	74	-23.37	Vertical
7386	52.18	24.78	5.36	33.17	49.15	74	-24.85	Vertical
9848	47.86	27.14	6.97	33.62	48.35	74	-25.65	Vertical
12310	42.16	28.16	7.65	33.58	44.39	74	-29.61	Vertical
14772	*	*	*	*	*	74	*	Vertical
4924	56.48	22.56	4.17	33.75	49.46	74	-24.54	Horizontal
7386	51.24	24.78	5.36	33.17	48.21	74	-25.79	Horizontal
9848	46.14	27.14	6.97	33.62	46.63	74	-27.37	Horizontal
12310	41.26	28.16	7.65	33.58	43.49	74	-30.51	Horizontal
14772	*	*	*	*	*	74	*	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924	47.15	22.56	4.17	33.75	40.13	54	-13.87	Vertical
7386	42.21	24.78	5.36	33.17	39.18	54	-14.82	Vertical
9848	37.48	27.14	6.97	33.62	37.97	54	-16.03	Vertical
12310	32.36	28.16	7.65	33.58	34.59	54	-19.41	Vertical
14772	*	*	*	*	*	54	*	Vertical
4924	46.25	22.56	4.17	33.75	39.23	54	-14.77	Horizontal
7386	41.48	24.78	5.36	33.17	38.45	54	-15.55	Horizontal
9848	36.49	27.14	6.97	33.62	36.98	54	-17.02	Horizontal
12310	31.47	28.16	7.65	33.58	33.70	54	-20.30	Horizontal
14772	*	*	*	*	*	54	*	Horizontal

Remark:

1. Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.

Test mode:	802.11g/2412	Test channel:	lowest
------------	--------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824	57.63	21.52	3.52	33.12	49.55	74	-24.45	Vertical
7236	52.45	23.65	4.56	33.08	47.58	74	-26.42	Vertical
9648	47.38	25.58	6.15	33.57	45.54	74	-28.46	Vertical
12060	42.64	27.68	6.98	33.26	44.04	74	-29.96	Vertical
14472	*	*	*	*	*	74	*	Vertical
4824	56.13	21.52	3.52	33.12	48.05	74	-25.95	Horizontal
7236	52.26	23.65	4.56	33.08	47.39	74	-26.61	Horizontal
9648	47.85	25.58	6.15	33.57	46.01	74	-27.99	Horizontal
12060	42.64	27.68	6.98	33.26	44.04	74	-29.96	Horizontal
14472	*	*	*	*	*	74	*	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824	48.12	21.52	3.52	33.12	40.04	54	-13.96	Vertical
7236	43.24	23.65	4.56	33.08	38.37	54	-15.63	Vertical
9648	37.86	25.58	6.15	33.57	36.02	54	-17.98	Vertical
12060	32.67	27.68	6.98	33.26	34.07	54	-19.93	Vertical
14472	*	*	*	*	*	54	*	Vertical
4824	48.06	21.52	3.52	33.12	39.98	54	-14.02	Horizontal
7236	42.56	23.65	4.56	33.08	37.69	54	-16.31	Horizontal
9648	38.27	25.58	6.15	33.57	36.43	54	-17.57	Horizontal
12060	33.46	27.68	6.98	33.26	34.86	54	-19.14	Horizontal
14472	*	*	*	*	*	54	*	Horizontal

Remark:

1. Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.

Test mode:	802.11g/2437	Test channel:	Middle
------------	--------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874	57.21	21.78	3.58	33.27	49.3	74	-24.7	Vertical
7311	52.64	24.15	4.57	33.87	47.49	74	-26.51	Vertical
9748	47.83	26.04	6.24	33.19	46.92	74	-27.08	Vertical
12185	43.67	27.98	7.18	33.68	45.15	74	-28.85	Vertical
14622	*	*	*	*	*	74	*	Vertical
4874	56.67	21.78	3.58	33.27	48.76	74	-25.24	Horizontal
7311	51.26	24.15	4.57	33.87	46.11	74	-27.89	Horizontal
9748	46.46	26.04	6.24	33.19	45.55	74	-28.45	Horizontal
12185	41.68	27.98	7.18	33.68	43.16	74	-30.84	Horizontal
14622	*	*	*	*	*	74	*	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874	48.86	21.78	3.58	33.27	40.95	54	-13.05	Vertical
7311	43.16	24.15	4.57	33.87	38.01	54	-15.99	Vertical
9748	38.27	26.04	6.24	33.19	37.36	54	-16.64	Vertical
12185	33.36	27.98	7.18	33.68	34.84	54	-19.16	Vertical
14622	*	*	*	*	*	54	*	Vertical
4874	47.86	21.78	3.58	33.27	39.95	54	-14.05	Horizontal
7311	42.36	24.15	4.57	33.87	37.21	54	-16.79	Horizontal
9748	37.64	26.04	6.24	33.19	36.73	54	-17.27	Horizontal
12185	32.33	27.98	7.18	33.68	33.81	54	-20.19	Horizontal
14622	*	*	*	*	*	54	*	Horizontal

Remark:

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *“*” , means this data is the too weak instrument of signal is unable to test.*

Test mode:	802.11g/2462	Test channel:	Highest
------------	--------------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924	57.26	22.56	4.17	33.75	50.24	74	-23.76	Vertical
7386	52.34	24.78	5.36	33.17	49.31	74	-24.69	Vertical
9848	47.26	27.14	6.97	33.62	47.75	74	-26.25	Vertical
12310	42.38	28.16	7.65	33.58	44.61	74	-29.39	Vertical
14772	*	*	*	*	*	74	*	Vertical
4924	56.89	22.56	4.17	33.75	49.87	74	-24.13	Horizontal
7386	51.48	24.78	5.36	33.17	48.45	74	-25.55	Horizontal
9848	46.82	27.14	6.97	33.62	47.31	74	-26.69	Horizontal
12310	42.08	28.16	7.65	33.58	44.31	74	-29.69	Horizontal
14772	*	*	*	*	*	74	*	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924	48.16	22.56	4.17	33.75	41.14	54	-12.86	Vertical
7386	43.64	24.78	5.36	33.17	40.61	54	-13.39	Vertical
9848	38.15	27.14	6.97	33.62	38.64	54	-15.36	Vertical
12310	33.64	28.16	7.65	33.58	35.87	54	-18.13	Vertical
14772	*	*	*	*	*	54	*	Vertical
4924	47.56	22.56	4.17	33.75	40.54	54	-13.46	Horizontal
7386	42.46	24.78	5.36	33.17	39.43	54	-14.57	Horizontal
9848	37.16	27.14	6.97	33.62	37.65	54	-16.35	Horizontal
12310	32.44	28.16	7.65	33.58	34.67	54	-19.33	Horizontal
14772	*	*	*	*	*	54	*	Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.

Test mode:	802.11n(HT20)/2412	Test channel:	Lowest
------------	--------------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824	57.84	21.52	3.52	33.12	49.76	74	-24.24	Vertical
7236	52.36	23.65	4.56	33.08	47.49	74	-26.51	Vertical
9648	47.29	25.58	6.15	33.57	45.45	74	-28.55	Vertical
12060	42.36	27.68	6.98	33.26	43.76	74	-30.24	Vertical
14472	*	*	*	*	*	74	*	Vertical
4824	56.74	21.52	3.52	33.12	48.66	74	-25.34	Horizontal
7236	51.43	23.65	4.56	33.08	46.56	74	-27.44	Horizontal
9648	46.26	25.58	6.15	33.57	44.42	74	-29.58	Horizontal
12060	41.19	27.68	6.98	33.26	42.59	74	-31.41	Horizontal
14472	*	*	*	*	*	74	*	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824	47.76	21.52	3.52	33.12	39.68	54	-14.32	Vertical
7236	42.34	23.65	4.56	33.08	37.47	54	-16.53	Vertical
9648	37.46	25.58	6.15	33.57	35.62	54	-18.38	Vertical
12060	32.16	27.68	6.98	33.26	33.56	54	-20.44	Vertical
14472	*	*	*	*	*	54	*	Vertical
4824	46.49	21.52	3.52	33.12	38.41	54	-15.59	Horizontal
7236	41.28	23.65	4.56	33.08	36.41	54	-17.59	Horizontal
9648	36.81	25.58	6.15	33.57	34.97	54	-19.03	Horizontal
12060	31.25	27.68	6.98	33.26	32.65	54	-21.35	Horizontal
14472	*	*	*	*	*	54	*	Horizontal

Remark:

1. Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.

Test mode:	802.11n(HT20)/2437	Test channel:	Middle
------------	--------------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874	57.68	21.78	3.58	33.27	49.77	74	-24.23	Vertical
7311	52.64	24.15	4.57	33.87	47.49	74	-26.51	Vertical
9748	51.76	26.04	6.24	33.19	50.85	74	-23.15	Vertical
12185	50.39	27.98	7.18	33.68	51.87	74	-22.13	Vertical
14622	*	*	*	*	*	74	*	Vertical
4874	54.81	21.78	3.58	33.27	46.9	74	-27.1	Horizontal
7311	51.09	24.15	4.57	33.87	45.94	74	-28.06	Horizontal
9748	53.64	26.04	6.24	33.19	52.73	74	-21.27	Horizontal
12185	45.85	27.98	7.18	33.68	47.33	74	-26.67	Horizontal
14622	*	*	*	*	*	74	*	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874	43.65	21.78	3.58	33.27	35.74	54	-18.26	Vertical
7311	42.84	24.15	4.57	33.87	37.69	54	-16.31	Vertical
9748	39.74	26.04	6.24	33.19	38.83	54	-15.17	Vertical
12185	36.49	27.98	7.18	33.68	37.97	54	-16.03	Vertical
14622	*	*	*	*	*	54	*	Vertical
4874	42.89	21.78	3.58	33.27	34.98	54	-19.02	Horizontal
7311	41.56	24.15	4.57	33.87	36.41	54	-17.59	Horizontal
9748	39.85	26.04	6.24	33.19	38.94	54	-15.06	Horizontal
12185	38.32	27.98	7.18	33.68	39.8	54	-14.2	Horizontal
14622	*	*	*	*	*	54	*	Horizontal

Remark:

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *“*” , means this data is the too weak instrument of signal is unable to test.*

Test mode:	802.11n(HT20)/2462	Test channel:	Highest
------------	--------------------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924	57.46	21.78	3.58	33.27	49.55	74	-24.45	Vertical
7386	52.64	24.15	4.57	33.87	47.49	74	-26.51	Vertical
9848	47.64	26.04	6.24	33.19	46.73	74	-27.27	Vertical
12310	42.25	27.98	7.18	33.68	43.73	74	-30.27	Vertical
14772	*	*	*	*	*	74	*	Vertical
4924	56.68	21.78	3.58	33.27	48.77	74	-25.23	Horizontal
7386	51.52	24.15	4.57	33.87	46.37	74	-27.63	Horizontal
9848	46.87	26.04	6.24	33.19	45.96	74	-28.04	Horizontal
12310	41.45	27.98	7.18	33.68	42.93	74	-31.07	Horizontal
14772	*	*	*	*	*	74	*	Horizontal

Average value:


Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924	47.78	21.78	3.58	33.27	39.87	54	-14.13	Vertical
7386	43.24	24.15	4.57	33.87	38.09	54	-15.91	Vertical
9848	37.59	26.04	6.24	33.19	36.68	54	-17.32	Vertical
12310	33.54	27.98	7.18	33.68	35.02	54	-18.98	Vertical
14772	*	*	*	*	*	54	*	Vertical
4924	46.25	21.78	3.58	33.27	38.34	54	-15.66	Horizontal
7386	41.49	24.15	4.57	33.87	36.34	54	-17.66	Horizontal
9848	36.49	26.04	6.24	33.19	35.58	54	-18.42	Horizontal
12310	31.55	27.98	7.18	33.68	33.03	54	-20.97	Horizontal
14772	*	*	*	*	*	54	*	Horizontal

Remark:

- 1 Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
- 2 “*”, means this data is the too weak instrument of signal is unable to test.


8 Test Setup Photo

RE






9 EUT Constructional Details





















-----End-----