

# **FCC ID:2AZ9W-WR04-08CH**

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where:

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

## **433.92**

Transmit power:

Frequency (MHz)	EIRP power (dBuV/m)	EIRP power (dBm)
433.92	64.39	-30.87

$$\text{EIRP} = E - 104.8 + 20 \log(D)$$

$\text{EIRP} = \text{conducted power} + \text{antenna gain}$

antenna gain: 0.71dBi;

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
FSK	0.43392	-27.87	0.0016	-28 $\pm$ 1	-27	0.002	<5	0.00026	3.00	YES

## **Conclusion:**

For the max result :  $0.00026 \leq 3.0$  for 1g SAR, SAR is not required.



**Signature:**

**Date:** 2024-09-20

**NAME AND TITLE** (Please print or type): Alex li /Manager

**COMPANY** (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.