

## FCC 1.1307 (B) & §2.1091- MPE-BASED EXEMPTION

### Applicable Standard

According to subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

According to KDB 447498 D04 Interim General RF Exposure Guidance

MPE-Based Exemption:

General frequency and separation-distance dependent MPE-based effective radiated power (ERP) thresholds are in Table B.1 [Table 1 of § 1.1307(b)(1)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

Table 1 to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$ .
1.34-30	$3,450 R^2/f^2$ .
30-300	$3.83 R^2$ .
300-1,500	$0.0128 R^2 f$ .
1,500-100,000	$19.2 R^2$ .

R is the minimum separation distance in meters

f = frequency in MHz

For multiple RF sources: Multiple RF sources are exempt if:

in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation:

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

**Result**

Mode	Frequency (MHz)	Tune up conducted power <sup>#</sup>	Antenna Gain <sup>#</sup>		ERP		Evaluation Distance (m)	ERP Limit (mW)
		(dBm)	(dBi)	(dBd)	(dBm)	(mW)		
BT	2402-2480	9.5	2.11	-0.04	9.46	8.83	0.2	768
BLE	2402-2480	8.0	2.11	-0.04	7.96	6.25	0.2	768
2.4G Wi-Fi	2412-2462	28.5	2.34	0.19	28.69	739.61	0.2	768
5.2G Wi-Fi	5180-5240	13.5	3.19	1.04	14.54	28.44	0.2	768
5.3G Wi-Fi	5260-5320	19.0	3.19	1.04	20.04	100.93	0.2	768
5.6G Wi-Fi	5500-5720	17.0	3.19	1.04	18.04	63.68	0.2	768
5.8G Wi-Fi	5745-5825	18.5	3.19	1.04	19.54	89.95	0.2	768

Note: 1. The tune up conducted power and antenna gain was declared by the applicant.  
 2. The BT and Wi-Fi can transmit at same time. The 2.4G and 5G Wi-Fi cannot transmit at same time.  
 3. 0dBd=2.15dBi

Simultaneous transmitting consideration (worst case):

The ratio= $ERP_{BT}/limit + ERP_{2.4G\ Wi-Fi}/limit = 8.83/768 + 739.61/768 = 0.975 < 1.0$ ,  
 so simultaneous exposure is compliant.

To maintain compliance with the FCC’s RF exposure guidelines, place the equipment at least 20cm from nearby persons.

**Result: Compliant.**