



Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640

Fax: +86-755-26648637

Website: www.cqa-cert.com

Report Template Version: V04

Report Template Revision Date: 2018-07-06

Test Report

Report No. : CQASZ20210300017EX-01

Applicant: KMJ Group Inc

Address of Applicant: 2221 W Custer Pl, Denver, CO 80223

Manufacturer: KMJ Group Inc

Address of Manufacturer: 2221 W Custer Pl, Denver, CO 80223

Equipment Under Test (EUT):

Product: KMJ U-series Mini Box PC

All Model No.: MUCBOX-THE8, MUCBOX -G7, MUCBOX -G6, MUCBOX-GS, MUCBOX-LS

Test Model No.: MUCBOX-THE8

Brand Name: KMJ

FCC ID: 2AZFV-KMJ-MN-UBX

Standards: 47 CFR FCC Part 15 Subpart C 15.247

Date of Test: Mar. 12, 2021 – Mar. 27, 2021

Date of Issue: Mar. 27, 2021

Test Result : PASS

Tested By:

Jun Li

(Jun Li)

Reviewed By:

Ares Liu

(Ares Liu)

Approved By:

Sheek, Luo

(Sheek luo)



* In the configuration tested, the EUT complied with the standards specified above.

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20210300017EX-01	Rev.01	Initial report	Mar. 27, 2021

2 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	ANSI C63.10 2013	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 2013	PASS
Conducted Peak & Average Output Power	47 CFR Part 15, Subpart C Section 15.247 (b)(3)	ANSI C63.10 2013	PASS
6dB Occupied Bandwidth	47 CFR Part 15, Subpart C Section 15.247 (a)(2)	ANSI C63.10 2013	PASS
Power Spectral Density	47 CFR Part 15, Subpart C Section 15.247 (e)	ANSI C63.10 2013	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 2013	PASS
RF Conducted Spurious Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 2013	PASS
Radiated Spurious Emissions	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2013	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2013	PASS

3 Contents

	Page
1 VERSION.....	2
2 TEST SUMMARY.....	3
3 CONTENTS.....	4
4 GENERAL INFORMATION.....	5
4.1 CLIENT INFORMATION.....	5
4.2 GENERAL DESCRIPTION OF EUT.....	5
4.3 TEST ENVIRONMENT.....	6
4.4 DESCRIPTION OF SUPPORT UNITS.....	7
4.5 TEST LOCATION.....	7
4.6 TEST FACILITY.....	7
4.7 STATEMENT OF THE MEASUREMENT UNCERTAINTY.....	8
4.8 DEVIATION FROM STANDARDS.....	8
4.9 ABNORMALITIES FROM STANDARD CONDITIONS.....	8
4.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	8
4.11 EQUIPMENT LIST.....	9
5 TEST RESULTS AND MEASUREMENT DATA.....	10
5.1 ANTENNA REQUIREMENT.....	10
5.2 CONDUCTED EMISSIONS.....	11
5.3 CONDUCTED PEAK & AVERAGE OUTPUT POWER.....	14
5.4 6dB OCCUPY BANDWIDTH.....	15
5.5 POWER SPECTRAL DENSITY.....	20
5.6 BAND-EDGE FOR RF CONDUCTED EMISSIONS.....	26
5.7 RF CONDUCTED SPURIOUS EMISSIONS.....	30
5.8 RADIATED SPURIOUS EMISSIONS.....	44
5.8.1 Radiated emission below 1GHz.....	47
5.8.2 Transmitter emission above 1GHz.....	49
5.9 RESTRICTED BANDS AROUND FUNDAMENTAL FREQUENCY.....	54
6 PHOTOGRAPHS - EUT TEST SETUP.....	60
7 PHOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS.....	62

4 General Information

4.1 Client Information

Applicant:	KMJ Group Inc
Address of Applicant:	2221 W Custer Pl, Denver, CO 80223
Manufacturer:	KMJ Group Inc
Address of Manufacturer:	2221 W Custer Pl, Denver, CO 80223

4.2 General Description of EUT

Product Name:	KMJ U-series Mini Box PC
Test Model No.:	MUCBOX-THE8
Trade Mark:	KMJ
Hardware Version:	KUB-868-V3
Software Version:	/
Operation Frequency:	IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz IEEE 802.11n(H40): 2422MHz~2452MHz
Channel Numbers:	IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels IEEE 802.11n HT40: 7
Channel Separation:	5MHz
Type of Modulation:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g : OFDM IEEE for 802.11n(HT20): OFDM IEEE for 802.11n(HT40): OFDM
Product Type:	☐ Mobile ☐ Portable ☒ Fix Location
Antenna Type	integral antenna
Antenna Gain	3dBi Max
Power Supply:	DC 5V from adapter
Adapter Information:	AC/DC ADAPTER MODEL: GA0501500 INPUT:110-240V AC 50/60Hz 0.6A OUTPUT: DC 5V 1500mA

Note: 1. This report is only for 2.4GHz WiFi.

2. For more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

Operation Frequency each of channel(802.11b/g/n HT20)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

For 802.11b/g/n (HT20):

Channel	Frequency
The Lowest channel	2412MHz
The Middle channel	2437MHz
The Highest channel	2462MHz

For 802.11n (HT40):

Channel	Frequency
The Lowest channel	2422MHz
The Middle channel	2437MHz
The Highest channel	2452MHz

Note: Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

4.3 Test Environment

Operating Environment:	
Conduction emission	
Temperature:	23 °C
Humidity:	51 % RH
Atmospheric Pressure:	992mbar
Radiated Emission (Normal Conditions)	
Temperature:	25.1 °C~25.5 °C
Humidity:	51 % RH~55 % RH
Atmospheric Pressure:	992mbar
RF item test (RF test room Normal Conditions)	
Temperature:	26 °C~27.3 °C
Humidity:	58 % RH~59 % RH
Atmospheric Pressure:	992mbar
Transmitting mode:	Use test software to set the lowest frequency, the middle frequency and the highest frequency keep transmitting of the EUT.

Note: In the process of transmitting of EUT, the duty cycle >98%.

4.4 Description of Support Units

The EUT has been tested with associated equipment below.

Description	Manufacturer	Model No.	Remark	certification
AC/DC ADAPTER	/	MODEL: GA0501500 INPUT: AC 110-240V 50/60Hz 0.6A OUTPUT: DC 5V 1500mA	Provide by appliant	SDOC
/	/	/	/	/

4.5 Test Location

All tests were performed at:

Shenzhen Huaxia Testing Technology Co., Ltd.,

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua New District, Shenzhen, Guangdong, China

4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• **ISED Registration No.: 22984-1**

The 3m Semi-anechoic chamber of Shenzhen Huaxia Testing Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing

• **A2LA (Certificate No. 4742.01)**

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 4742.01.

• **FCC Registration No.: 522263**

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.:522263

4.7 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate.

The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities.

The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the **Shenzhen Huaxia Testing Technology Co., Ltd.** quality system acc. to DIN EN ISO/IEC 17025.

Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CQA laboratory is reported:

No.	Item	Uncertainty	Notes
1	Radiated Emission (Below 1GHz)	5.12dB	(1)
2	Radiated Emission (Above 1GHz)	4.60dB	(1)
3	Conducted Disturbance (0.15~30MHz)	3.34dB	(1)
4	Radio Frequency	3×10^{-8}	(1)
5	Duty cycle	0.6 %.	(1)
6	Occupied Bandwidth	1.1%	(1)
7	RF conducted power	0.86dB	(1)
8	RF power density	0.74	(1)
9	Conducted Spurious emissions	0.86dB	(1)
10	Temperature test	0.8℃	(1)
11	Humidity test	2.0%	(1)
12	Supply voltages	0.5 %.	(1)
13	Frequency Error	5.5 Hz	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

4.8 Deviation from Standards

None.

4.9 Abnormalities from Standard Conditions

None.

4.10 Other Information Requested by the Customer

None.

4.11 Equipment List

Test Equipment	Manufacturer	Model No.	Instrument No.	Calibration Date	Calibration Due Date
EMI Test Receiver	R&S	ESR7	CQA-005	2020/9/22	2021/9/21
Spectrum analyzer	R&S	FSU26	CQA-038	2020/10/24	2021/10/23
Spectrum analyzer	keysight	N9020A	CQA-105	2020/10/24	2021/10/23
Preamplifier	MITEQ	AFS4-00010300-18-10P-4	CQA-035	2020/9/22	2021/9/21
Preamplifier	MITEQ	AMF-6D-02001800-29-20P	CQA-036	2018/11/2	2019/11/1
Loop antenna	Schwarzbeck	FMZB1516	CQA-087	2018/10/28	2020/10/27
Bilog Antenna	R&S	HL562	CQA-011	2020/9/22	2021/9/21
Horn Antenna	R&S	HF906	CQA-012	2020/9/22	2021/9/21
Horn Antenna	Schwarzbeck	BBHA 9170	CQA-088	2020/9/22	2021/9/21
Coaxial Cable (Above 1GHz)	CQA	N/A	C019	2020/9/22	2021/9/21
Coaxial Cable (Below 1GHz)	CQA	N/A	C020	2020/9/22	2021/9/21
Antenna Connector	CQA	RFC-01	CQA-080	2020/9/22	2021/9/21
RF cable(9KHz~40GHz)	CQA	RF-01	CQA-079	2020/9/22	2021/9/21
Power Sensor	KEYSIGHT	U2021XA	CQA-30	2020/9/22	2021/9/21
N1918A Power Analysis Manager Power Panel	Agilent	N1918A	CQA-074	2020/9/22	2021/9/21
Power divider	MIDWEST	PWD-2533-02-SMA-79	CQA-067	2020/9/22	2021/9/21
EMI Test Receiver	R&S	ESPI3	CQA-013	2020/9/22	2021/9/21
LISN	R&S	ENV216	CQA-003	2021/11/1	2021/10/30
Coaxial cable	CQA	N/A	CQA-C009	2020/9/22	2021/9/21

Note:


The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

5 Test results and Measurement Data

5.1 Antenna Requirement

Standard requirement:	47 CFR Part 15C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.	
EUT Antenna:	Antenna 
The antenna is integral antenna. The best case gain of the antenna is 3dBi.	


5.2 Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207		
Test Method:	ANSI C63.10: 2013		
Test Frequency Range:	150kHz to 30MHz		
Limit:	Frequency range (MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
* Decreases with the logarithm of the frequency.			
Test Procedure:	1) The mains terminal disturbance voltage test was conducted in a shielded room. 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded. 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2. 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.		
Test Setup:			
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates at lowest, middle and highest channel.		

Final Test Mode:	All wifi modes of 5.2G/5.8G were tested at Low, Middle, and High channel; only the worst result of 802.11b CH1 was reported as below
Test Voltage:	AC110V/60Hz
Test Results:	Pass

Measurement Data

Live Line:




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.1580	44.59	0.18	44.77	65.56	-20.79	QP	
2		0.1580	22.86	0.18	23.04	55.56	-32.52	AVG	
3		0.1819	21.64	0.19	21.83	54.39	-32.56	AVG	
4		0.2180	39.53	0.20	39.73	62.89	-23.16	QP	
5	*	0.5860	38.35	0.33	38.68	56.00	-17.32	QP	
6		0.5860	26.92	0.33	27.25	46.00	-18.75	AVG	
7		1.1340	16.39	0.28	16.67	46.00	-29.33	AVG	
8		1.1460	29.38	0.28	29.66	56.00	-26.34	QP	
9		11.4220	12.08	0.10	12.18	50.00	-37.82	AVG	
10		12.8940	25.65	0.08	25.73	60.00	-34.27	QP	
11		26.4020	32.94	-0.16	32.78	60.00	-27.22	QP	
12		30.0000	27.92	-0.13	27.79	50.00	-22.21	AVG	

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

Neutral Line:




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1660	47.04	0.19	47.23	65.15	-17.92	QP	
2		0.1660	26.80	0.19	26.99	55.15	-28.16	AVG	
3		0.2779	39.38	0.30	39.68	60.88	-21.20	QP	
4		0.3180	21.71	0.31	22.02	49.76	-27.74	AVG	
5	*	0.5660	39.20	0.33	39.53	56.00	-16.47	QP	
6		0.6100	26.50	0.33	26.83	46.00	-19.17	AVG	
7		1.7700	16.82	0.19	17.01	46.00	-28.99	AVG	
8		1.7900	29.20	0.19	29.39	56.00	-26.61	QP	
9		6.0060	15.03	0.03	15.06	50.00	-34.94	AVG	
10		6.4300	29.65	0.01	29.66	60.00	-30.34	QP	
11		29.9980	31.70	-0.13	31.57	60.00	-28.43	QP	
12		30.0000	27.61	-0.13	27.48	50.00	-22.52	AVG	

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.


5.3 Conducted Peak & Average Output Power

Test Requirement:	47 CFR Part 15C Section 15.247 (b)(3)
Test Method:	ANSI C63.10: 2013
Test Setup:	
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40); Only the worst case is recorded in the report.
Limit:	30dBm
Test Results:	Pass

WIFI(2.4G)

Type	Test channel	Peak Output Power (dBm)	AVG Output Power (dBm)	Limit (dBm)	Result
802.11b	Lowest	17.04	13.17	30.00	Pass
	Middle	16.86	12.24		
	Highest	16.94	12.18		
802.11g	Lowest	13.62	10.86	30.00	Pass
	Middle	13.15	10.35		
	Highest	13.58	10.27		
802.11n(HT20)	Lowest	12.26	8.97	30.00	Pass
	Middle	12.20	9.41		
	Highest	12.32	9.03		
802.11n(HT40)	Lowest	11.97	7.95	30.00	Pass
	Middle	11.65	7.46		
	Highest	12.29	7.19		


5.4 6dB Occupy Bandwidth




Test Requirement:	47 CFR Part 15C Section 15.247 (a)(2)
Test Method:	ANSI C63.10: 2013
Test Setup:	 Offset=cable loss+ attenuation factor
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the 11Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40); Only the worst case is recorded in the report.
Limit:	≥ 500 kHz
Test Results:	Pass



Measurement Data




Type	Channel	6dB Bandwidth (MHz)	Limit (KHz)	Result
802.11b	Lowest	9.535	≥500	Pass
	Middle	9.201		
	Highest	9.540		
802.11g	Lowest	16.61	≥500	Pass
	Middle	16.52		
	Highest	16.54		
802.11n(HT20)	Lowes	17.79	≥500	Pass
	Middle	17.76		
	Highest	17.76		
802.11n(HT40)	Lowest	36.56	≥500	Pass
	Middle	36.06		
	Highest	36.12		

Test plot as follows:




11G/LCH	 KeySight Spectrum Analyzer - Occupied BW Center Freq 2.412000000 GHz Center Freq: 2.412000000 GHz Trig: Free Run Avg/Hold: 100/100 Radio Std: None Radio Device: BTS 10 dB/div Ref 20.00 dBm Center 2.412 GHz #Res BW 100 kHz #VBW 300 kHz Span 40 MHz Sweep 3.867 ms Occupied Bandwidth 16.605 MHz Total Power 19.6 dBm Transmit Freq Error -60.671 kHz % of OBW Power 99.00 % x dB Bandwidth 16.61 MHz x dB -6.00 dB Frequency Center Freq 2.412000000 GHz CF Step 4.000000 MHz Man Auto Freq Offset 0 Hz
11G/MCH	 KeySight Spectrum Analyzer - Occupied BW Center Freq 2.437000000 GHz Center Freq: 2.437000000 GHz Trig: Free Run Avg/Hold: 100/100 Radio Std: None Radio Device: BTS 10 dB/div Ref 20.00 dBm Center 2.437 GHz #Res BW 100 kHz #VBW 300 kHz Span 40 MHz Sweep 3.867 ms Occupied Bandwidth 16.521 MHz Total Power 20.1 dBm Transmit Freq Error 66.823 kHz % of OBW Power 99.00 % x dB Bandwidth 16.52 MHz x dB -6.00 dB Frequency Center Freq 2.437000000 GHz CF Step 4.000000 MHz Man Auto Freq Offset 0 Hz
11G/HCH	 KeySight Spectrum Analyzer - Occupied BW Center Freq 2.462000000 GHz Center Freq: 2.462000000 GHz Trig: Free Run Avg/Hold: 100/100 Radio Std: None Radio Device: BTS 10 dB/div Ref 20.00 dBm Center 2.462 GHz #Res BW 100 kHz #VBW 300 kHz Span 40 MHz Sweep 3.867 ms Occupied Bandwidth 16.627 MHz Total Power 19.6 dBm Transmit Freq Error -105.42 kHz % of OBW Power 99.00 % x dB Bandwidth 16.54 MHz x dB -6.00 dB Frequency Center Freq 2.462000000 GHz CF Step 4.000000 MHz Man Auto Freq Offset 0 Hz

11N20/LCH	 KeySight Spectrum Analyzer - Occupied BW Center Freq 2.412000000 GHz Center Freq: 2.412000000 GHz Trig: Free Run Avg/Hold: 100/100 Radio Std: None Radio Device: BTS 10 dB/div Ref 20.00 dBm Center 2.412 GHz #Res BW 100 kHz #VBW 300 kHz Span 40 MHz Sweep 3.867 ms Occupied Bandwidth 17.704 MHz Total Power 18.3 dBm Transmit Freq Error -19.494 kHz % of OBW Power 99.00 % x dB Bandwidth 17.79 MHz x dB -6.00 dB Frequency Center Freq 2.412000000 GHz CF Step 4.000000 MHz Man Freq Offset 0 Hz
11N20/MCH	 KeySight Spectrum Analyzer - Occupied BW Center Freq 2.437000000 GHz Center Freq: 2.437000000 GHz Trig: Free Run Avg/Hold: 100/100 Radio Std: None Radio Device: BTS 10 dB/div Ref 20.00 dBm Center 2.437 GHz #Res BW 100 kHz #VBW 300 kHz Span 40 MHz Sweep 3.867 ms Occupied Bandwidth 17.657 MHz Total Power 19.1 dBm Transmit Freq Error 66.893 kHz % of OBW Power 99.00 % x dB Bandwidth 17.76 MHz x dB -6.00 dB Frequency Center Freq 2.437000000 GHz CF Step 4.000000 MHz Man Freq Offset 0 Hz
11N20/HCH	 KeySight Spectrum Analyzer - Occupied BW Center Freq 2.462000000 GHz Center Freq: 2.462000000 GHz Trig: Free Run Avg/Hold: 100/100 Radio Std: None Radio Device: BTS 10 dB/div Ref 20.00 dBm Center 2.462 GHz #Res BW 100 kHz #VBW 300 kHz Span 40 MHz Sweep 3.867 ms Occupied Bandwidth 17.688 MHz Total Power 18.3 dBm Transmit Freq Error -42.954 kHz % of OBW Power 99.00 % x dB Bandwidth 17.76 MHz x dB -6.00 dB Frequency Center Freq 2.462000000 GHz CF Step 4.000000 MHz Man Freq Offset 0 Hz

11N40/LCH	 Keysight Spectrum Analyzer - Occupied BW Center Freq: 2.422000000 GHz Center Freq: 2.422000000 GHz Trig: Free Run Avg/Hold: 100/100 Radio Std: None Radio Device: BTS Ref 10.00 dBm 10 dB/div Log Center 2.422 GHz #Res BW 100 kHz #VBW 300 kHz Span 80 MHz Sweep 7.667 ms Occupied Bandwidth 36.269 MHz Total Power 18.3 dBm Transmit Freq Error 45.786 kHz % of OBW Power 99.00 % x dB Bandwidth 36.56 MHz x dB -6.00 dB MSG STATUS
11N40/MCH	 Keysight Spectrum Analyzer - Occupied BW Center Freq: 2.437000000 GHz Center Freq: 2.437000000 GHz Trig: Free Run Avg/Hold: 100/100 Radio Std: None Radio Device: BTS Ref 10.00 dBm 10 dB/div Log Center 2.437 GHz #Res BW 100 kHz #VBW 300 kHz Span 80 MHz Sweep 7.667 ms Occupied Bandwidth 35.927 MHz Total Power 18.9 dBm Transmit Freq Error 120.82 kHz % of OBW Power 99.00 % x dB Bandwidth 36.06 MHz x dB -6.00 dB MSG STATUS
11N40/HCH	 Keysight Spectrum Analyzer - Occupied BW Center Freq: 2.452000000 GHz Center Freq: 2.452000000 GHz Trig: Free Run Avg/Hold: 100/100 Radio Std: None Radio Device: BTS Ref 10.00 dBm 10 dB/div Log Center 2.452 GHz #Res BW 100 kHz #VBW 300 kHz Span 80 MHz Sweep 7.667 ms Occupied Bandwidth 35.869 MHz Total Power 18.5 dBm Transmit Freq Error -64.546 kHz % of OBW Power 99.00 % x dB Bandwidth 36.12 MHz x dB -6.00 dB MSG STATUS


5.5 Power Spectral Density

Test Requirement:	47 CFR Part 15C Section 15.247 (e)
Test Method:	ANSI C63.10: 2013
Test Setup:	 Offset=cable loss+ attenuation factor
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40); Only the worst case is recorded in the report.
Limit:	≤8.00dBm/3kHz
Test Results:	Pass

Measurement Data

Type	Channel	Power Spectral Density (dBm/3KHz)	Limit (dBm/3KHz)	Result
802.1b	Lowes	-11.946	8	Pass
	Middle	-10.567		
	Highest	-11.75		
802.11g	Lowest	-13.481	8	Pass
	Middle	-13.677		
	Highest	-13.633		
802.11n(HT20)	Lowest	-15.039	8	Pass
	Middle	-13.856		
	Highest	-15.191		
802.11n(HT40)	Lowest	-14.931	8	Pass
	Middle	-15.735		
	Highest	-17.141		

Test plot as follows:




11G/LCH	 KeySight Spectrum Analyzer - Sweep SA Center Freq 2.41200000 GHz Mkr1 2.40542 GHz -13.481 dBm Center 2.41200 GHz #Res BW 3.0 kHz #VBW 9.1 kHz Span 24.92 MHz Sweep 2.644 s (501 pts)
11G/MCH	 KeySight Spectrum Analyzer - Sweep SA Center Freq 2.43700000 GHz Mkr1 2.44419 GHz -13.677 dBm Center 2.43700 GHz #Res BW 3.0 kHz #VBW 9.1 kHz Span 24.78 MHz Sweep 2.629 s (501 pts)
11G/HCH	 KeySight Spectrum Analyzer - Sweep SA Center Freq 2.46200000 GHz Mkr1 2.45540 GHz -13.633 dBm Center 2.46200 GHz #Res BW 3.0 kHz #VBW 9.1 kHz Span 24.81 MHz Sweep 2.633 s (501 pts)

11N20/LCH	 Keyight Spectrum Analyzer - Sweep SA Center Freq 2.41200000 GHz Mkr1 2.40538 GHz -15.039 dBm 10 dB/div Ref 20.00 dBm Center 2.41200 GHz #Res BW 3.0 kHz #VBW 9.1 kHz Span 26.60 MHz Sweep 2.832 s (501 pts)
11N20/MCH	 Keyight Spectrum Analyzer - Sweep SA Center Freq 2.43700000 GHz Mkr1 2.44361 GHz -13.856 dBm 10 dB/div Ref 20.00 dBm Center 2.43700 GHz #Res BW 3.0 kHz #VBW 9.1 kHz Span 26.64 MHz Sweep 2.826 s (501 pts)
11N20/HCH	 Keyight Spectrum Analyzer - Sweep SA Center Freq 2.46200000 GHz Mkr1 2.45539 GHz -15.191 dBm 10 dB/div Ref 20.00 dBm Center 2.46200 GHz #Res BW 3.0 kHz #VBW 9.1 kHz Span 26.64 MHz Sweep 2.827 s (501 pts)


11N40/LCH	 KeySight Spectrum Analyzer - Sweep SA Center Freq 2.422000000 GHz Mkr1 2.438 56 GHz -14.931 dBm Center 2.42200 GHz #Res BW 3.0 kHz #VBW 9.1 kHz Span 54.84 MHz Sweep 5.819 s (501 pts) Frequency Auto Tune Center Freq 2.422000000 GHz Start Freq 2.394678500 GHz Stop Freq 2.449421500 GHz CF Step 5.484300 MHz Man Freq Offset 0 Hz Scale Type Log Lin
11N40/MCH	 KeySight Spectrum Analyzer - Sweep SA Center Freq 2.437000000 GHz Mkr1 2.444 79 GHz -15.735 dBm Center 2.43700 GHz #Res BW 3.0 kHz #VBW 9.1 kHz Span 54.08 MHz Sweep 5.738 s (501 pts) Frequency Auto Tune Center Freq 2.437000000 GHz Start Freq 2.409958750 GHz Stop Freq 2.464041250 GHz CF Step 5.408250 MHz Man Freq Offset 0 Hz Scale Type Log Lin
11N40/HCH	 KeySight Spectrum Analyzer - Sweep SA Center Freq 2.452000000 GHz Mkr1 2.448 53 GHz -17.141 dBm Center 2.45200 GHz #Res BW 3.0 kHz #VBW 9.1 kHz Span 54.18 MHz Sweep 5.749 s (501 pts) Frequency Auto Tune Center Freq 2.452000000 GHz Start Freq 2.424910000 GHz Stop Freq 2.479090000 GHz CF Step 5.418000 MHz Man Freq Offset 0 Hz Scale Type Log Lin

5.6 Band-edge for RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10: 2013
Test Setup:	 Offset=cable loss+ attenuation factor
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g ; 6.5Mbps of rate is the worst case of 802.11n(HT20) ; 13.5Mbps of rate is the worst case of 802.11n(HT40); Only the worst case is recorded in the report.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Results:	Pass


Test plot as follows:






11N20/HCH	Keylight Spectrum Analyzer - Swept SA Center Freq 2.466000000 GHz PN0: Fast IF Gain: Low Trig: Free Run #Atten: 30 dB #Avg Type: RMS Avg/Hold: 100/100 ALIGN AUTO 10:09:52 PM Mar 26, 2021 TRACE 1 2 3 4 5 6 TYPE M W W W W W W W DET P N N N N N N 10 dB/div Ref 20.00 dBm Start 2.43200 GHz #Res BW 100 kHz #VBW 300 kHz Stop 2.50000 GHz Sweep 6.533 ms (2001 pts) <table><tr><th>MNTR MODE</th><th>TRC</th><th>SCL</th><th>X</th><th>Y</th><th>FUNCTION</th><th>FUNCTION WIDTH</th><th>FUNCTION VALUE</th></tr><tr><td>1</td><td>N</td><td>1</td><td>f</td><td>2.483 500 GHz</td><td>-46.971 dBm</td><td></td><td></td></tr><tr><td>2</td><td>N</td><td>1</td><td>f</td><td>2.500 000 GHz</td><td>-53.885 dBm</td><td></td><td></td></tr><tr><td>3</td><td>N</td><td>1</td><td>f</td><td>2.500 000 GHz</td><td>-53.885 dBm</td><td></td><td></td></tr><tr><td>4</td><td>N</td><td>1</td><td>f</td><td>2.456 616 GHz</td><td>-1.085 dBm</td><td></td><td></td></tr></table> MSG STATUS Frequency Auto Tune Center Freq 2.466000000 GHz Start Freq 2.432000000 GHz Stop Freq 2.500000000 GHz CF Step 6.800000 MHz Man Freq Offset 0 Hz Scale Type Log Lin	MNTR MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	1	f	2.483 500 GHz	-46.971 dBm			2	N	1	f	2.500 000 GHz	-53.885 dBm			3	N	1	f	2.500 000 GHz	-53.885 dBm			4	N	1	f	2.456 616 GHz	-1.085 dBm		
MNTR MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE																																		
1	N	1	f	2.483 500 GHz	-46.971 dBm																																				
2	N	1	f	2.500 000 GHz	-53.885 dBm																																				
3	N	1	f	2.500 000 GHz	-53.885 dBm																																				
4	N	1	f	2.456 616 GHz	-1.085 dBm																																				
11N40/LCH	Keylight Spectrum Analyzer - Swept SA Center Freq 2.396000000 GHz PN0: Fast IF Gain: Low Trig: Free Run #Atten: 30 dB #Avg Type: RMS Avg/Hold: 100/100 ALIGN AUTO 10:12:44 PM Mar 26, 2021 TRACE 1 2 3 4 5 6 TYPE M W W W W W W W DET P N N N N N N 10 dB/div Ref 20.00 dBm Start 2.31000 GHz #Res BW 100 kHz #VBW 300 kHz Stop 2.48200 GHz Sweep 16.53 ms (2001 pts) <table><tr><th>MNTR MODE</th><th>TRC</th><th>SCL</th><th>X</th><th>Y</th><th>FUNCTION</th><th>FUNCTION WIDTH</th><th>FUNCTION VALUE</th></tr><tr><td>1</td><td>N</td><td>1</td><td>f</td><td>2.380 000 GHz</td><td>-52.254 dBm</td><td></td><td></td></tr><tr><td>2</td><td>N</td><td>1</td><td>f</td><td>2.400 000 GHz</td><td>-44.242 dBm</td><td></td><td></td></tr><tr><td>3</td><td>N</td><td>1</td><td>f</td><td>2.400 000 GHz</td><td>-44.242 dBm</td><td></td><td></td></tr><tr><td>4</td><td>N</td><td>1</td><td>f</td><td>2.439 258 GHz</td><td>-3.692 dBm</td><td></td><td></td></tr></table> MSG STATUS Frequency Auto Tune Center Freq 2.396000000 GHz Start Freq 2.310000000 GHz Stop Freq 2.482000000 GHz CF Step 17.200000 MHz Man Freq Offset 0 Hz Scale Type Log Lin	MNTR MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	1	f	2.380 000 GHz	-52.254 dBm			2	N	1	f	2.400 000 GHz	-44.242 dBm			3	N	1	f	2.400 000 GHz	-44.242 dBm			4	N	1	f	2.439 258 GHz	-3.692 dBm		
MNTR MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE																																		
1	N	1	f	2.380 000 GHz	-52.254 dBm																																				
2	N	1	f	2.400 000 GHz	-44.242 dBm																																				
3	N	1	f	2.400 000 GHz	-44.242 dBm																																				
4	N	1	f	2.439 258 GHz	-3.692 dBm																																				
11N40/HCH	Keylight Spectrum Analyzer - Swept SA Center Freq 2.446000000 GHz PN0: Fast IF Gain: Low Trig: Free Run #Atten: 30 dB #Avg Type: RMS Avg/Hold: 100/100 ALIGN AUTO 10:17:25 PM Mar 26, 2021 TRACE 1 2 3 4 5 6 TYPE M W W W W W W W DET P N N N N N N 10 dB/div Ref 20.00 dBm Start 2.39200 GHz #Res BW 100 kHz #VBW 300 kHz Stop 2.50000 GHz Sweep 10.40 ms (2001 pts) <table><tr><th>MNTR MODE</th><th>TRC</th><th>SCL</th><th>X</th><th>Y</th><th>FUNCTION</th><th>FUNCTION WIDTH</th><th>FUNCTION VALUE</th></tr><tr><td>1</td><td>N</td><td>1</td><td>f</td><td>2.483 500 GHz</td><td>-46.015 dBm</td><td></td><td></td></tr><tr><td>2</td><td>N</td><td>1</td><td>f</td><td>2.500 000 GHz</td><td>-54.094 dBm</td><td></td><td></td></tr><tr><td>3</td><td>N</td><td>1</td><td>f</td><td>2.500 000 GHz</td><td>-54.094 dBm</td><td></td><td></td></tr><tr><td>4</td><td>N</td><td>1</td><td>f</td><td>2.449 834 GHz</td><td>-3.817 dBm</td><td></td><td></td></tr></table> MSG STATUS Frequency Auto Tune Center Freq 2.446000000 GHz Start Freq 2.392000000 GHz Stop Freq 2.500000000 GHz CF Step 10.800000 MHz Man Freq Offset 0 Hz Scale Type Log Lin	MNTR MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	1	f	2.483 500 GHz	-46.015 dBm			2	N	1	f	2.500 000 GHz	-54.094 dBm			3	N	1	f	2.500 000 GHz	-54.094 dBm			4	N	1	f	2.449 834 GHz	-3.817 dBm		
MNTR MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE																																		
1	N	1	f	2.483 500 GHz	-46.015 dBm																																				
2	N	1	f	2.500 000 GHz	-54.094 dBm																																				
3	N	1	f	2.500 000 GHz	-54.094 dBm																																				
4	N	1	f	2.449 834 GHz	-3.817 dBm																																				



5.7 RF Conducted Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10: 2013
Test Setup:	 Offset=cable loss+ attenuation factor
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40); Only the worst case is recorded in the report.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Results:	Pass



Test plot as follows:



11B_MCH_Graphs

Reference	 Key: Knight Spectrum Analyzer - Sweep SA Center Freq 2.43700000 GHz Ref 20.00 dBm Mkr1 2.438 515 GHz 7.969 dBm Center 2.43700 GHz #Res BW 100 kHz #VBW 300 kHz Span 40.00 MHz Sweep 4.267 ms (8001 pts)
30MHz-10GHz	 Key: Knight Spectrum Analyzer - Sweep SA Start Freq 30.000000 MHz Ref 10.00 dBm Mkr1 3.178 5 GHz -57.593 dBm Start 0.030 GHz #Res BW 100 kHz #VBW 300 kHz Stop 10.000 GHz #Sweep 200.0 ms (20001 pts)
10GHz-26.5GHz	 Key: Knight Spectrum Analyzer - Sweep SA Start Freq 10.00000000 GHz Ref 10.00 dBm Mkr1 24.934 975 GHz -49.469 dBm Start 10.000 GHz #Res BW 100 kHz #VBW 300 kHz Stop 26.500 GHz #Sweep 200.0 ms (20001 pts)

11B_HCH_Graphs


Reference	
30MHz-10GHz	
10GHz-26.5GHz	

11G_LCH_Graphs


Reference



30MHz-10GHz




10GHz-26.5GHz




11G_MCH_Graphs


Reference



30MHz-10GHz



10GHz-26.5GHz




11G_HCH_Graphs


Reference





30MHz-10GHz



10GHz-26.5GHz




11N20_LCH_Graphs


Reference	 Keylight Spectrum Analyzer - Sweep SA Center Freq 2.41200000 GHz Ref 20.00 dBm Mkr1 2.403 630 GHz -1.735 dBm Center 2.41200 GHz #Res BW 100 kHz #VBW 300 kHz Span 40.00 MHz Sweep 4.267 ms (8001 pts) Frequency Auto Tune Center Freq 2.41200000 GHz Start Freq 2.39200000 GHz Stop Freq 2.43200000 GHz CF Step 4.000000 MHz Freq Offset 0 Hz Scale Type Log
30MHz-10GHz	 Keylight Spectrum Analyzer - Sweep SA Start Freq 30.000000 MHz Ref 10.00 dBm Mkr1 5.897 3 GHz -59.700 dBm Start 0.030 GHz #Res BW 100 kHz #VBW 300 kHz Stop 10.000 GHz #Sweep 200.0 ms (20001 pts) Frequency Auto Tune Center Freq 5.01500000 GHz Start Freq 30.000000 MHz Stop Freq 10.00000000 GHz CF Step 997.000000 MHz Freq Offset 0 Hz Scale Type Log
10GHz-26.5GHz	 Keylight Spectrum Analyzer - Sweep SA Start Freq 10.00000000 GHz Ref 10.00 dBm Mkr1 24.585 175 GHz -49.898 dBm Start 10.000 GHz #Res BW 100 kHz #VBW 300 kHz Stop 26.500 GHz #Sweep 200.0 ms (20001 pts) Frequency Auto Tune Center Freq 18.25000000 GHz Start Freq 10.00000000 GHz Stop Freq 26.50000000 GHz CF Step 1.65000000 GHz Freq Offset 0 Hz Scale Type Log

11N20_MCH_Graphs


Reference






30MHz-10GHz



10GHz-26.5GHz




11N20_HCH_Graphs


Reference	 Keylight Spectrum Analyzer - Sweep SA Center Freq 2.46200000 GHz Ref 20.00 dBm Mkr1 2.462 000 GHz -11.797 dBm Center Freq 2.46200000 GHz Start Freq 2.442000000 GHz Stop Freq 2.482000000 GHz CF Step 4.000000 MHz Freq Offset 0 Hz Scale Type Log Span 40.00 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 4.267 ms (8001 pts)
30MHz-10GHz	 Keylight Spectrum Analyzer - Sweep SA Start Freq 30.0000000 MHz Ref 10.00 dBm Mkr1 3.160 6 GHz -58.747 dBm Start 0.030 GHz Stop 10.000 GHz Center Freq 5.015000000 GHz Start Freq 30.0000000 MHz Stop Freq 10.000000000 GHz CF Step 997.000000 MHz Freq Offset 0 Hz Scale Type Log #Res BW 100 kHz #VBW 300 kHz #Sweep 200.0 ms (20001 pts)
10GHz-26.5GHz	 Keylight Spectrum Analyzer - Sweep SA Start Freq 10.000000000 GHz Ref 10.00 dBm Mkr1 24.534 025 GHz -49.470 dBm Start 10.000 GHz Stop 26.500 GHz Center Freq 18.250000000 GHz Start Freq 10.000000000 GHz Stop Freq 26.500000000 GHz CF Step 1.650000000 GHz Freq Offset 0 Hz Scale Type Log #Res BW 100 kHz #VBW 300 kHz #Sweep 200.0 ms (20001 pts)

11N40_LCH_Graphs


Reference



30MHz-10GHz




10GHz-26.5GHz




11N40_MCH_Graphs


Reference



30MHz-10GHz



10GHz-26.5GHz




11N40_HCH_Graphs


Reference



30MHz-10GHz



10GHz-26.5GHz



Remark:

Pretest 9kHz to 25GHz, find the highest point when testing, so only the worst data were shown in the test report. Per FCC Part 15.33 (a) and 15.31 (o) ,The amplitude of spurious emissions from intentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this part.

5.8 Radiated Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205				
Test Method:	ANSI C63.10 2013				
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100 kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
	Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.				

Test Setup:




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz


Test Procedure:

- a. 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
Note: For the radiated emission test above 1GHz:
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

	d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel, the middle channel, the Highest channel h. Repeat above procedures until all frequencies measured was complete.
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates. Transmitting mode,
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g ; 6.5Mbps of rate is the worst case of 802.11n(HT20) ; 13.5Mbps of rate is the worst case of 802.11n(HT40) For below 1GHz, through Pre-scan, find the 1Mbps of rate of 802.11b at lowest channel is the worst case.
Test Results:	Pass

5.8.1 Radiated emission below 1GHz

30MHz~1GHz		
Test mode:	Transmitting	Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree
1	!	52.7600	50.92	-16.79	34.13	40.00	-5.87	QP		
2		64.4331	49.27	-17.45	31.82	40.00	-8.18	QP		
3		150.5378	42.74	-12.97	29.77	43.50	-13.73	QP		
4		198.5880	41.78	-13.80	27.98	43.50	-15.52	QP		
5	*	649.6597	42.31	-0.43	41.88	46.00	-4.12	QP		
6		768.7481	35.38	4.39	39.77	46.00	-6.23	QP		

Remark:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Factor= Antenna Factor + Cable Factor – Preamplifier Factor,

Level = Read Level + Factor,

Over Limit=Level-Limit Line.

Test mode:	Transmitting	Horizontal
------------	--------------	------------



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		55.8046	37.69	-16.83	20.86	40.00	-19.14	QP		
2		151.0665	31.56	-13.05	18.51	43.50	-24.99	QP		
3		199.2855	39.63	-13.35	26.28	43.50	-17.22	QP		
4		411.8240	33.65	-7.25	26.40	46.00	-19.60	QP		
5	*	649.6597	37.66	-0.43	37.23	46.00	-8.77	QP		
6		972.3374	32.42	6.79	39.21	54.00	-14.79	QP		

Remark:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Factor= Antenna Factor + Cable Factor – Preamplifier Factor,

Level = Read Level + Factor,

Over Limit=Level-Limit Line.

5.8.2 Transmitter emission above 1GHz

Test mode:		802.11b(1Mbps)		Test channel:		Lowest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
4824.000	55.99	-4.26	51.73	74	-22.27	PK	H
4824.000	40.01	-4.26	35.75	54	-18.25	AV	H
7236.000	51.07	1.18	52.25	74	-21.75	PK	H
7236.000	35.93	1.18	37.11	54	-16.89	AV	H
4824.000	57.07	-4.26	52.81	74	-21.19	PK	V
4824.000	38.72	-4.26	34.46	54	-19.54	AV	V
7236.000	51.04	1.18	52.22	74	-21.78	PK	V
7236.000	39.62	1.18	40.80	54	-13.20	AV	V

Test mode:		802.11b(1Mbps)		Test channel:		Middle	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
4874.000	56.02	-4.12	51.90	74	-22.10	PK	H
4874.000	40.86	-4.12	36.74	54	-17.26	AV	H
7311.000	50.50	1.46	51.96	74	-22.04	PK	H
7311.000	36.14	1.46	37.60	54	-16.40	AV	H
4874.000	55.27	-4.12	51.15	74	-22.85	PK	V
4874.000	38.74	-4.12	34.62	54	-19.38	AV	V
7311.000	53.24	1.46	54.70	74	-19.30	PK	V
7311.000	40.67	1.46	42.13	54	-11.87	AV	V

Test mode:		802.11b(1Mbps)		Test channel:		Highest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
4924.000	54.03	-4.03	50.00	74	-24.00	PK	H
4924.000	38.22	-4.03	34.19	54	-19.81	AV	H
7386.000	50.49	1.66	52.15	74	-21.85	PK	H
7386.000	34.58	1.66	36.24	54	-17.76	AV	H
4924.000	54.84	-4.03	50.81	74	-23.19	PK	V
4924.000	38.85	-4.03	34.82	54	-19.18	AV	V
7386.000	52.13	1.66	53.79	74	-20.21	PK	V
7386.000	40.83	1.66	42.49	54	-11.51	AV	V

Test mode:		802.11g(6Mbps)		Test channel:		Lowest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
4824.000	56.18	-4.26	51.92	74	-22.08	PK	H
4824.000	38.72	-4.26	34.46	54	-19.54	AV	H
7236.000	50.31	1.18	51.49	74	-22.51	PK	H
7236.000	34.10	1.18	35.28	54	-18.72	AV	H
4824.000	56.72	-4.26	52.46	74	-21.54	PK	V
4824.000	39.50	-4.26	35.24	54	-18.76	AV	V
7236.000	53.57	1.18	54.75	74	-19.25	PK	V
7236.000	38.76	1.18	39.94	54	-14.06	AV	V

Test mode:		802.11g(6Mbps)		Test channel:		Middle	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
4874.000	55.06	-4.12	50.94	74	-23.06	PK	H
4874.000	38.12	-4.12	34.00	54	-20.00	AV	H
7311.000	51.03	1.46	52.49	74	-21.51	PK	H
7311.000	35.92	1.46	37.38	54	-16.62	AV	H
4874.000	55.90	-4.12	51.78	74	-22.22	PK	V
4874.000	39.26	-4.12	35.14	54	-18.86	AV	V
7311.000	53.83	1.46	55.29	74	-18.71	PK	V
7311.000	40.22	1.46	41.68	54	-12.32	AV	V

Test mode:		802.11g(6Mbps)		Test channel:		Highest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
4924.000	53.59	-4.03	49.56	74	-24.44	PK	H
4924.000	38.28	-4.03	34.25	54	-19.75	AV	H
7386.000	52.05	1.66	53.71	74	-20.29	PK	H
7386.000	34.89	1.66	36.55	54	-17.45	AV	H
4924.000	55.85	-4.03	51.82	74	-22.18	PK	V
4924.000	38.68	-4.03	34.65	54	-19.35	AV	V
7386.000	52.63	1.66	54.29	74	-19.71	PK	V
7386.000	39.18	1.66	40.84	54	-13.16	AV	V

Test mode:		802.11n(6.5Mbps)		Test channel:		Lowest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
4824.000	55.91	-4.26	51.65	74	-22.35	PK	H
4824.000	38.39	-4.26	34.13	54	-19.87	AV	H
7236.000	49.94	1.18	51.12	74	-22.88	PK	H
7236.000	36.58	1.18	37.76	54	-16.24	AV	H
4824.000	56.98	-4.26	52.72	74	-21.28	PK	V
4824.000	39.59	-4.26	35.33	54	-18.67	AV	V
7236.000	53.78	1.18	54.96	74	-19.04	PK	V
7236.000	41.03	1.18	42.21	54	-11.79	AV	V

Test mode:		802.11n(6.5Mbps)		Test channel:		Middle	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
4874.000	56.03	-4.12	51.91	74	-22.09	PK	H
4874.000	38.90	-4.12	34.78	54	-19.22	AV	H
7311.000	50.98	1.46	52.44	74	-21.56	PK	H
7311.000	35.77	1.46	37.23	54	-16.77	AV	H
4874.000	54.87	-4.12	50.75	74	-23.25	PK	V
4874.000	37.19	-4.12	33.07	54	-20.93	AV	V
7311.000	52.39	1.46	53.85	74	-20.15	PK	V
7311.000	38.79	1.46	40.25	54	-13.75	AV	V

Test mode:		802.11n(6.5Mbps)		Test channel:		Highest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
4924.000	54.84	-4.03	50.81	74	-23.19	PK	H
4924.000	38.10	-4.03	34.07	54	-19.93	AV	H
7386.000	52.03	1.66	53.69	74	-20.31	PK	H
7386.000	36.52	1.66	38.18	54	-15.82	AV	H
4924.000	56.77	-4.03	52.74	74	-21.26	PK	V
4924.000	39.58	-4.03	35.55	54	-18.45	AV	V
7386.000	51.25	1.66	52.91	74	-21.09	PK	V
7386.000	40.73	1.66	42.39	54	-11.61	AV	V

Test mode:		802.11n40(13.5Mbps)		Test channel:		Lowest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
4844.000	55.41	-4.2	51.21	74	-22.79	PK	H
4844.000	38.16	-4.2	33.96	54	-20.04	AV	H
7266.000	50.64	1.18	51.82	74	-22.18	PK	H
7266.000	35.93	1.18	37.11	54	-16.89	AV	H
4844.000	55.61	-4.2	51.41	74	-22.59	PK	V
4844.000	37.37	-4.2	33.17	54	-20.83	AV	V
7266.000	53.27	1.18	54.45	74	-19.55	PK	V
7266.000	39.96	1.18	41.14	54	-12.86	AV	V

Test mode:		802.11n40(13.5Mbps)		Test channel:		Middle	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
4874.000	53.87	-4.12	49.75	74	-24.25	PK	H
4874.000	40.69	-4.12	36.57	54	-17.43	AV	H
7311.000	52.12	1.46	53.58	74	-20.42	PK	H
7311.000	36.46	1.46	37.92	54	-16.08	AV	H
4874.000	54.62	-4.12	50.50	74	-23.50	PK	V
4874.000	37.23	-4.12	33.11	54	-20.89	AV	V
7311.000	53.48	1.46	54.94	74	-19.06	PK	V
7311.000	38.23	1.46	39.69	54	-14.31	AV	V

Test mode:		802.11n40(13.5Mbps)		Test channel:		Highest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
4904.000	56.32	-4.03	52.29	74	-21.71	PK	H
4904.000	38.60	-4.03	34.57	54	-19.43	AV	H
7356.000	49.96	1.66	51.62	74	-22.38	PK	H
7356.000	36.12	1.66	37.78	54	-16.22	AV	H
4904.000	54.85	-4.03	50.82	74	-23.18	PK	V
4904.000	38.02	-4.03	33.99	54	-20.01	AV	V
7356.000	52.15	1.66	53.81	74	-20.19	PK	V
7356.000	38.08	1.66	39.74	54	-14.26	AV	V

Remark:

- 1) The 1Mbps of rate of 802.11b is the worst case.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 3) Scan from 9kHz to 25GHz, The disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

5.9 Restricted bands around fundamental frequency

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205		
Test Method:	ANSI C63.10 2013		
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)		
Limit:	Frequency	Limit (dBuV/m @3m)	Remark
	30MHz-88MHz	40.0	Quasi-peak Value
	88MHz-216MHz	43.5	Quasi-peak Value
	216MHz-960MHz	46.0	Quasi-peak Value
	960MHz-1GHz	54.0	Quasi-peak Value
	Above 1GHz	54.0	Average Value
		74.0	Peak Value
Test Setup:			




Figure 1. 30MHz to 1GHz




Figure 2. Above 1 GHz

Test Procedure:

- 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
 - 2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- Note: For the radiated emission test above 1GHz:
- Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
 - The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

	d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel g. Test the EUT in the lowest channel , the Highest channel h. Repeat above procedures until all frequencies measured was complete.
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates. Transmitting mode.
Final Test Mode:	1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g ; 6.5Mbps of rate is the worst case of 802.11n(HT20) ; 13.5Mbps of rate is the worst case of 802.11n(HT40) Only the worst case is recorded in the report.
Test Results:	Pass

Test data:

Worse case mode:		802.11b(1Mbps)		Test channel:		Lowest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
2390.000	65.43	-9.2	56.23	74	-17.77	PK	H
2390.000	42.18	-9.2	32.98	54	-21.02	AV	H
2400.000	64.58	-9.39	55.19	74	-18.81	PK	H
2400.000	42.55	-9.39	33.16	54	-20.84	AV	H
2390.000	64.9	-9.2	55.70	74	-18.30	PK	V
2390.000	42.84	-9.2	33.64	54	-20.36	AV	V
2400.000	64.56	-9.39	55.17	74	-18.83	PK	V
2400.000	40.36	-9.39	30.97	54	-23.03	AV	V

Worse case mode:		802.11b(1Mbps)		Test channel:		Highest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
2483.500	65.43	-9.29	56.14	74	-17.86	PK	H
2483.500	42.18	-9.29	32.89	54	-21.11	AV	H
2483.500	64.58	-9.29	55.29	74	-18.71	PK	V
2483.500	42.55	-9.29	33.26	54	-20.74	AV	V

Worse case mode:		802.11g(6Mbps)		Test channel:		Lowest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
2390.000	65.43	-9.2	56.23	74	-17.77	PK	H
2390.000	42.18	-9.2	32.98	54	-21.02	AV	H
2400.000	64.58	-9.39	55.19	74	-18.81	PK	H
2400.000	42.55	-9.39	33.16	54	-20.84	AV	H
2390.000	64.9	-9.2	55.70	74	-18.30	PK	V
2390.000	42.84	-9.2	33.64	54	-20.36	AV	V
2400.000	64.56	-9.39	55.17	74	-18.83	PK	V
2400.000	40.36	-9.39	30.97	54	-23.03	AV	V

Worse case mode:		802.11g(6Mbps)		Test channel:		Highest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
2483.500	65.43	-9.29	56.14	74	-17.86	PK	H
2483.500	42.18	-9.29	32.89	54	-21.11	AV	H
2483.500	64.58	-9.29	55.29	74	-18.71	PK	V
2483.500	42.55	-9.29	33.26	54	-20.74	AV	V

Worse case mode:		802.11n(HT20)(6.5Mbps)		Test channel:		Lowest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
2390.000	65.43	-9.2	56.23	74	-17.77	PK	H
2390.000	42.18	-9.2	32.98	54	-21.02	AV	H
2400.000	64.58	-9.39	55.19	74	-18.81	PK	H
2400.000	42.55	-9.39	33.16	54	-20.84	AV	H
2390.000	64.9	-9.2	55.70	74	-18.30	PK	V
2390.000	42.84	-9.2	33.64	54	-20.36	AV	V
2400.000	64.56	-9.39	55.17	74	-18.83	PK	V
2400.000	40.36	-9.39	30.97	54	-23.03	AV	V

Worse case mode:		802.11n(HT20)(6.5Mbps)		Test channel:		Highest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
2483.500	65.43	-9.29	56.14	74	-17.86	PK	H
2483.500	42.18	-9.29	32.89	54	-21.11	AV	H
2483.500	64.58	-9.29	55.29	74	-18.71	PK	V
2483.500	42.55	-9.29	33.26	54	-20.74	AV	V

Worse case mode:		802.11n(HT40)(13.5Mbps)		Test channel:		Lowest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
2390.000	65.43	-9.2	56.23	74	-17.77	PK	H
2390.000	42.18	-9.2	32.98	54	-21.02	AV	H
2400.000	64.58	-9.39	55.19	74	-18.81	PK	H
2400.000	42.55	-9.39	33.16	54	-20.84	AV	H
2390.000	64.9	-9.2	55.70	74	-18.30	PK	V
2390.000	42.84	-9.2	33.64	54	-20.36	AV	V
2400.000	64.56	-9.39	55.17	74	-18.83	PK	V
2400.000	40.36	-9.39	30.97	54	-23.03	AV	V

Worse case mode:		802.11n(HT40)(13.5Mbps)		Test channel:		Highest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
2483.500	65.43	-9.29	56.14	74	-17.86	PK	H
2483.500	42.18	-9.29	32.89	54	-21.11	AV	H
2483.500	64.58	-9.29	55.29	74	-18.71	PK	V
2483.500	42.55	-9.29	33.26	54	-20.74	AV	V

Note:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor

6 Photographs - EUT Test Setup

6.1 Radiated Emission

9kHz~30MHz:



30MHz~1GHz:



Above 1GHz:




6.2 Conducted Emissions Test Setup




7 Photographs - EUT Constructional Details

External Photos












Internal Photos





THE END