

FCC ID: 2AZGE-KC-909

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

BR+EDR:

Antenna Type :PCB Antenna

Antenna Gain: 1.2 dBi

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculatio n	1g SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	-2.909	0.512	-2±1	-1	0.794	<5	0.24622	3.00	YES
	2.441	-2.894	0.514	-2±1	-1	0.794	<5	0.24821	3.00	YES
	2.480	-4.308	0.371	-4±1	-3	0.501	<5	0.15785	3.00	YES
π/4-DQPSK	2.402	-0.763	0.839	-1±1	0	1.000	<5	0.30997	3.00	YES
	2.441	-0.819	0.828	-1±1	0	1.000	<5	0.31247	3.00	YES
	2.480	-2.243	0.597	-2±1	-1	0.794	<5	0.25018	3.00	YES
8-DPSK	2.402	-0.186	0.958	-1±1	0	1.000	<5	0.30997	3.00	YES
	2.441	-0.278	0.938	-1±1	0	1.000	<5	0.31247	3.00	YES
	2.480	-1.696	0.677	-2±1	-1	0.794	<5	0.25018	3.00	YES

BLE:

Antenna Type :PCB Antenna

Antenna Gain: 1.2 dBi

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculatio n	1g SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	-3	0.501	-3±1	-2	0.631	<5	0.19558	3.00	YES
	2.44	-2.933	0.509	-3±1	-2	0.631	<5	0.19712	3.00	YES
	2.480	-4.317	0.370	-4±1	-3	0.501	<5	0.15785	3.00	YES

Conclusion:

For the max result : $0.31247 \leq 3.0$ for 1-g SAR, No SAR is required.



Signature:

Date: 2021-04-25

NAME AND TITLE (Please print or type): Alex Li /Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen 518126 P.R. China