

# Appendix B

## Highest Test Plots

# Table of Contents

1. BT Head-worn 0mm SAR ..... 3

# 1. BT Head-worn 0mm SAR

Date: 06.03.2025

Test Laboratory: Guangdong Dongdian Testing Service Co., Ltd.

## Q24112510-1E

Communication System: UID 0, Bluetooth (0); Communication System Band: Bluetooth; Frequency: 2480 MHz; Communication System PAR: 0 dB; PMF: 1.12202e-005

Medium parameters used:  $f = 2480$  MHz;  $\sigma = 1.791$  S/m;  $\epsilon_r = 39.52$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2011)

### DASY Configuration:

- Probe: EX3DV4 - SN3906; ConvF(7.95, 7.95, 7.95) @ 2480 MHz; Calibrated: 29.04.2024
- Sensor-Surface: 1.4mm (Mechanical Surface Detection),  $z = 1.0, 31.0$
- Electronics: DAE4 Sn1366; Calibrated: 29.04.2024
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1197
- DASYS2 52.10.4(1535); SEMCAD X 14.6.14(7501)

**Configuration/R Left 3DH5 2480/Area Scan (8x8x1):** Measurement grid:  $dx=10$ mm,  $dy=10$ mm  
Maximum value of SAR (measured) = 0.0271 W/kg

**Configuration/R Left 3DH5 2480/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5$ mm,  $dy=5$ mm,  $dz=5$ mm  
Reference Value = 2.368 V/m; Power Drift = -0.09 dB  
Peak SAR (extrapolated) = 0.0600 W/kg  
**SAR(1 g) = 0.014 W/kg; SAR(10 g) = 0.00409 W/kg**  
Smallest distance from peaks to all points 3 dB below: Larger than measurement grid (> 15 mm)  
Ratio of SAR at M2 to SAR at M1 = 37.9%  
Maximum value of SAR (measured) = 0.0256 W/kg

